
# Chapter 7
# Wireless and Mobile Networks




*Computer Networking: A Top Down Approach*

7th edition
Jim Kurose, Keith Ross
Pearson/Addison Wesley
April 2016

A note on the use of these Powerpoint slides:

We're making these slides freely available to all (faculty, students, readers). They're in PowerPoint form so you see the animations; and can add, modify, and delete slides (including this one) and slide content to suit your needs. They obviously represent a *lot* of work on our part. In return for use, we only ask the following:

- If you use these slides (e.g., in a class) that you mention their source (after all, we'd like people to use our book!)
- If you post any slides on a www site, that you note that they are adapted from (or perhaps identical to) our slides, and note our copyright of this material.

Thanks and enjoy! JFK/KWR

© All material copyright 1996-2016
J.F Kurose and K.W. Ross, All Rights Reserved

# Ch. 6: Wireless and Mobile Networks

*Background:*

- # wireless (mobile) phone subscribers now exceeds # wired phone subscribers (10-to-1 2019)!
- # wireless Internet-connected devices equals # wireline Internet-connected devices
  - laptops, Internet-enabled phones promise anytime untethered Internet access
- more mobile-broadband-connected devices than fixed-broadband-connected devices (5-1 in 2019)!
  - 4G/5G cellular networks now embracing Internet protocol stack, including SDN
- two important (but different) challenges
  - *wireless:* communication over wireless link
  - *mobility:* handling the mobile user who changes point of attachment to network



# Chapter 7 outline

7.1 Introduction

## Wireless

7.2 Wireless links, characteristics
- CDMA

7.3 IEEE 802.11 wireless LANs ("Wi-Fi")

7.4 Cellular Internet Access
- architecture
- standards (e.g., 3G, LTE, 4G and 5G)

## Mobility


7.5 Principles: addressing and routing to mobile users

7.6 Mobile IP


7.7 Handling mobility in cellular networks

7.8 Mobility and higher-layer protocols

# Elements of a wireless network



# Elements of a wireless network







## wireless hosts


- laptop, smartphone, IoT
- run applications
- may be stationary (non-mobile) or mobile
  - wireless does *not* always mean mobility

# Elements of a wireless network





network infrastructure






**base station**

- typically connected to wired network
- relay - responsible for sending packets between wired network and wireless host(s) in its "area"
  - e.g., cell towers, 802.11 access points


# Elements of a wireless network





**wireless link**

- typically used to connect mobile(s) to base station
- also used as backbone link
- multiple access protocol coordinates link access
- various data rates, transmission distance and frequency bands


# Characteristics of selected wireless links



# Characteristics of selected wireless links




# Elements of a wireless network




infrastructure mode


- base station connects mobiles into wired network
- handoff: mobile changes base station providing connection into wired network

# Elements of a wireless network



ad hoc mode

- no base stations
- nodes can only transmit to other nodes within link coverage
- nodes organize themselves into a network: route among themselves




# Single Hop vs. Multiple Hop

# Wireless network taxonomy

| | single hop | multiple hops |
|---|---|---|
| infrastructure (e.g., APs) | host connects to base station (WiFi, WiMAX, cellular) which connects to larger Internet | host may have to relay through several wireless nodes to connect to larger Internet: *mesh net* |
| no infrastructure | no base station, no connection to larger Internet (Bluetooth, ad hoc nets) | no base station, no connection to larger Internet. May have to relay to reach other a given wireless node MANET, VANET |

# Chapter 7 outline

7.1 Introduction

Wireless

7.2 Wireless links, characteristics
- CDMA

7.3 IEEE 802.11 wireless LANs ("Wi-Fi")

7.4 Cellular Internet Access
- architecture
- standards (e.g., 3G, LTE, 4G and 5G )

Mobility

7.5 Principles: addressing and routing to mobile users

7.6 Mobile IP

7.7 Handling mobility in cellular networks

7.8 Mobility and higher-layer protocols

# Wireless Link Characteristics (1)


*important* differences from wired link ….

- *decreased signal strength:* radio signal attenuates as it propagates through matter (path loss)
- *interference from other sources:* standardized wireless network frequencies (e.g., 2.4 GHz) shared by many (e.g., WiFi, cellular, motors): interference
- *multipath propagation:* radio signal reflects off objects ground, arriving to the destination at slightly different times

…. make communication across (even a point to point) wireless link much more "difficult"


# Wireless Link Characteristics (2)

- SNR: signal-to-noise ratio
  - larger SNR – easier to extract signal from noise (a "good thing")
- *SNR versus BER tradeoffs*
  - *given physical layer:* increase power -> increase SNR->decrease BER
  - *given SNR:* choose physical layer that meets BER requirement, giving highest thruput
    - SNR may change with mobility: dynamically adapt physical layer (modulation technique, rate)




# Wireless network characteristics

Multiple wireless senders and receivers create additional problems (beyond multiple access):




*Hidden terminal problem*

- B, A hear each other
- B, C hear each other
- A, C can not hear each other means A, C unaware of their interference at B





*Signal attenuation:*

- B, A hear each other
- B, C hear each other
- A, C can not hear each other interfering at B


# Code Division Multiple Access (CDMA)

- unique "code" assigned to each user; i.e., code set partitioning
  - all users share same frequency, but each user has own "chipping" sequence (i.e., code) to encode data
  - allows multiple users to "coexist" and transmit simultaneously with minimal interference (if codes are "orthogonal")
- *encoded signal* = (original data) X (chipping sequence)
- *decoding:* inner-product of encoded signal and chipping sequence

# CDMA encode/decode



# CDMA: two-sender interference




*using same code as sender 1, receiver recovers sender 1's original data from summed channel data!*

# Chapter 7 outline

7.1 Introduction

Wireless

7.2 Wireless links, characteristics
- CDMA

7.3 IEEE 802.11 wireless LANs ("Wi-Fi")

7.4 Cellular Internet Access
- architecture
- standards (e.g., 3G, LTE, 4G and 5G)

Mobility

7.5 Principles: addressing and routing to mobile users

7.6 Mobile IP

7.7 Handling mobility in cellular networks

7.8 Mobility and higher-layer protocols


# IEEE 802.11 Wireless LAN



| IEEE 802.11 standard | Year | Max data rate | Range | Frequency |
|---|---|---|---|---|
| 802.11b | 1999 | 11 Mbps | 30 m | 2.4 Ghz |
| 802.11g | 2003 | 54 Mbps | 30m | 2.4 Ghz |
| 802.11n (WiFi 4) | 2009 | 600 | 70m | 2.4, 5 Ghz |
| 802.11ac (WiFi 5) | 2013 | 3.47Gpbs | 70m | 5 Ghz |
| 802.11ax (WiFi 6) | 2020 (exp.) | 14 Gbps | 70m | 2.4, 5 Ghz |
| 802.11af | 2014 | 35 – 560 Mbps | 1 Km | unused TV bands (54-790 MHz) |
| 802.11ah | 2017 | 347Mbps | 1 Km | 900 Mhz |

- all use CSMA/CA for multiple access, and have base-station and ad-hoc network versions

# 802.11 LAN architecture






- wireless host communicates with base station
  - base station = access point (AP)
- Basic Service Set (BSS) (aka "cell") in infrastructure mode contains:
  - wireless hosts
  - access point (AP): base station
  - ad hoc mode: hosts only

# 802.11: Channels, association

- 802.11b: 2.4GHz-2.485GHz spectrum divided into 11 channels at different frequencies
  - AP admin chooses frequency for AP
  - interference possible: channel can be same as that chosen by neighboring AP!
- host: must *associate* with an AP
  - scans channels, listening for *beacon frames* containing AP's name (SSID) and MAC address
  - selects AP to associate with
  - may perform authentication [Chapter 8]
  - will typically run DHCP to get IP address in AP's subnet

# 802.11: passive/active scanning




*passive scanning:*


(1) beacon frames sent from APs
(2) association Request frame sent: H1 to selected AP
(3) association Response frame sent from selected AP to H1


*active scanning:*

(1) Probe Request frame broadcast from H1
(2) Probe Response frames sent from APs
(3) Association Request frame sent: H1 to selected AP
(4) Association Response frame sent from selected AP to H1

# IEEE 802.11: multiple access

- avoid collisions: $2^+$ nodes transmitting at same time
- 802.11: CSMA - sense before transmitting
  - don't collide with ongoing transmission by other node
- 802.11: *no* collision detection!
  - difficult to receive (sense collisions) when transmitting due to weak received signals (fading)
  - can't sense all collisions in any case: hidden terminal, fading
  - goal: *avoid collisions:* CSMA/C(ollision)A(voidance)



# IEEE 802.11 MAC Protocol: CSMA/CA


*802.11 sender*

1 if sense channel idle for **DIFS** then
  transmit entire frame (no CD)

2 if sense channel busy then
  start random backoff time
  timer counts down while channel idle
  transmit when timer expires
  if no ACK, increase random backoff interval, repeat 2

*802.11 receiver*

- if frame received OK
  return ACK after **SIFS** (ACK needed due to hidden terminal problem)



# Avoiding collisions (more)


*idea:* allow sender to "reserve" channel rather than random access of data frames: avoid collisions of long data frames

- sender first transmits *small* request-to-send (RTS) packets to BS using CSMA
  - RTSs may still collide with each other (but they're short)
- BS broadcasts clear-to-send CTS in response to RTS
- CTS heard by all nodes
  - sender transmits data frame
  - other stations defer transmissions


*avoid data frame collisions completely*

*using small reservation packets!*

# Collision Avoidance: RTS-CTS exchange



# 802.11 frame: addressing





Address 1: MAC address of wireless host or AP to receive this frame

Address 2: MAC address of wireless host or AP transmitting this frame


Address 3: MAC address of router interface to which AP is attached

Address 4: used only in ad hoc mode

# 802.11 frame: addressing




# 802.11 frame: more



# 802.11: mobility within same subnet


- H1 remains in same IP subnet: IP address can remain same
- switch: which AP is associated with H1?
  - self-learning (Ch. 5): switch will see frame from H1 and "remember" which switch port can be used to reach H1




# 802.11: advanced capabilities

## *Rate adaptation*

- base station, mobile dynamically change transmission rate (physical layer modulation technique) as mobile moves, SNR varies




1. SNR decreases, BER increase as node moves away from base station

2. When BER becomes too high, switch to lower transmission rate but with lower BER


# 802.11: advanced capabilities

*power management*

- node-to-AP: "I am going to sleep until next beacon frame"
  - AP knows not to transmit frames to this node
  - node wakes up before next beacon frame
- beacon frame: contains list of mobiles with AP-to-mobile frames waiting to be sent
  - node will stay awake if AP-to-mobile frames to be sent; otherwise sleep again until next beacon frame

# 802.15: personal area network (Bluetooth)

- less than 10 m diameter
- replacement for cables (mouse, keyboard, headphones)
- ad hoc: no infrastructure
- master/slaves:
  - slaves request permission to send (to master)
  - master grants requests
- 802.15: evolved from Bluetooth specification
  - 2.4-2.5 GHz radio band
  - up to 3 Mbps



# Chapter 7 outline

7.1 Introduction

Wireless

7.2 Wireless links, characteristics
- CDMA

7.3 IEEE 802.11 wireless LANs ("Wi-Fi")

7.4 Cellular Internet access
- architecture
- standards (e.g., 3G, LTE, 4G and 5G)

Mobility

7.5 Principles: addressing and routing to mobile users

7.6 Mobile IP


7.7 Handling mobility in cellular networks

7.8 Mobility and higher-layer protocols

# Components of cellular network architecture

**MSC**
- connects cells to wired tel. net.
- manages call setup (more later!)
- handles mobility (more later!)

**cell**
- covers geographical region
- *base station* (BS) analogous to 802.11 AP
- *mobile users* attach to network through BS
- *air-interface:* physical and link layer protocol between mobile and BS



# Cellular networks: the first hop


Two techniques for sharing mobile-to-BS radio spectrum

- combined FDMA/TDMA: divide spectrum in frequency channels, divide each channel into time slots
- CDMA: code division multiple access





# 2G (voice) network architecture




Legend


Base transceiver station (BTS)

Base station controller (BSC)

Mobile Switching Center (MSC)

Mobile subscribers

# 3G (voice+data) network architecture




*Key insight:* new cellular data network operates *in parallel* (except at edge) with existing cellular voice network

- voice network *unchanged* in core
- data network operates in parallel




Serving GPRS Support Node (SGSN)




Gateway GPRS Support Node (GGSN)

# 3G (voice+data) network architecture




# 3G versus 4G LTE network architecture



# 4G: differences from 3G

- all IP core: IP packets tunneled (through core IP network) from base station to gateway
- no separation between voice and data – all traffic carried over IP core to gateway




# Elements of 4G LTE architecture

Extra Slide

Mobile device:

- smartphone, tablet, laptop, IoT, ... with 4G LTE radio
- 64-bit International Mobile Subscriber Identity (IMSI), stored on SIM (Subscriber Identity Module) card
- LTE jargon: User Equipment (UE)




# Elements of 4G LTE architecture



Extra Slide

Base station:

- at "edge" of carrier's network
- manages wireless radio resources, mobile devices in its coverage area ("cell")
- coordinates device authentication with other elements
- similar to WiFi AP but:
  - active role in user mobility
  - coordinates with nearly base stations to optimize radio use
- LTE jargon: eNode-B




# Elements of 4G LTE architecture

Extra Slide

## Home Subscriber Service

- stores info about mobile devices for which the HSS's network is their "home network"
- works with MME in device authentication




# Elements of 4G LTE architecture



Extra Slide

Serving Gateway (S-GW), PDN Gateway (P-GW)

- lie on data path from mobile to/from Internet
- P-GW
  - gateway to mobile cellular network
  - Looks like nay other internet gateway router
  - provides NAT services
- other routers:
  - extensive use of tunneling




# Elements of 4G LTE architecture



Extra Slide


## Mobility Management Entity

- device authentication (device-to-network, network-to-device) coordinated with mobile home network HSS
- mobile device management:
  - device handover between cells
  - tracking/paging device location
- path (tunneling) setup from mobile device to P-GW




# LTE: data plane control plane separation

Extra Slide




control plane

- new protocols for mobility management , security, authentication (later)





data plane

- new protocols at link, physical layers
- extensive use of tunneling to facilitate mobility

# LTE data plane protocol stack: first hop



Extra Slide





## LTE link layer protocols:

- Packet Data Convergence: header compression, encryption
- Radio Link Control (RLC) Protocol: fragmentation/reassembly, reliable data transfer
- Medium Access: requesting, use of radio transmission slots

# LTE data plane protocol stack: first hop




Extra Slide




## LTE radio access network:


- downstream channel: FDM, TDM within frequency channel (OFDM - orthogonal frequency division multiplexing)
  - "orthogonal": minimal interference between channels
  - upstream: FDM, TDM similar to OFDM
- each active mobile device allocated two or more 0.5 ms time slots over 12 frequencies
  - scheduling algorithm not standardized – up to operator
  - 100's Mbps per device possible

# Functional split of major LTE components



# LTE data plane protocol stack: packet core

Extra Slide





tunneling:

- mobile datagram encapsulated using GPRS Tunneling Protocol (GTP), sent inside UDP datagram to S-GW
- S-GW re-tunnels datagrams to P-GW
- supporting mobility: only tunneling endpoints change when mobile user moves

# Radio+Tunneling: UE – eNodeB – PGW

IP packet from UE encapsulated in GPRS Tunneling Protocol (GTP) message at ENodeB

GTP message encapsulated in UDP, then encapsulated in IP. large IP packet addressed to SGW




# Quality of Service in LTE

- QoS from eNodeB to SGW: min and max guaranteed bit rate
- QoS in radio access network: one of 12 QCI values

| QCI | RESOURCE TYPE | PRIORITY | PACKET DELAY BUDGET (MS) | PACKET ERROR LOSS RATE | EXAMPLE SERVICES |
|---|---|---|---|---|---|
| 1 | GBR | 2 | 100 | $10^{-2}$ | Conversational voice |
| 2 | GBR | 4 | 150 | $10^{-3}$ | Conversational video (live streaming) |
| 3 | GBR | 5 | 300 | $10^{-6}$ | Non-conversational video (buffered streaming) |
| 4 | GBR | 3 | 50 | $10^{-3}$ | Real-time gaming |
| 5 | Non-GBR | 1 | 100 | $10^{-6}$ | IMS signaling |
| 6 | Non-GBR | 7 | 100 | $10^{-3}$ | Voice, video (live streaming), interactive gaming |
| 7 | Non-GBR | 6 | 300 | $10^{-6}$ | Video (buffered streaming) |
| 8 | Non-GBR | 8 | 300 | $10^{-6}$ | TCP-based (for example, WWW, e-mail), chat, FTP, p2p file sharing, progressive video and others |
| 9 | Non-GBR | 9 | 300 | $10^{-6}$ | |

# Global cellular network: a network of IP networks

Extra Slide




home network HSS:

- identify & services info, while in home network and roaming

all IP:

- carriers interconnect with each other, and public internet at exchange points
- legacy 2G, 3G: not all IP, handled otherwise



Extra Slide

# On to 5G!

- goal: 10x increase in peak bitrate, 10x decrease in latency, 100x increase in traffic capacity over 4G
- 5G NR (new radio):
  - two frequency bands: FR1 (450 MHz–6 GHz) and FR2 (24 GHz–52 GHz): millimeter wave frequencies
  - not backwards-compatible with 4G
  - MIMO: multiple directional antennae
- millimeter wave frequencies: much higher data rates, but over shorter distances
  - pico-cells: cells diameters: 10-100 m
  - massive, dense deployment of new base stations required



Extra Slide

# 4G/5G cellular networks

*similarities* to wired Internet

- edge/core distinction, but both below to same carrier
- global cellular network: a network of networks
- widespread use of protocols we've studied: HTTP, DNS, TCP, UDP, IP, NAT, separation of data/control planes, SDN, Ethernet, tunneling
- interconnected to wired Internet

*differences* from wired Internet

- different wireless link layer
- mobility as a 1st class service
- user "identity" (via SIM card)
- business model: users subscribe to a cellular provider
  - strong notion of "home network" versus roaming on visited nets
  - global access, with authentication infrastructure, and inter-carrier settlements

# Chapter 7 outline

7.1 Introduction

Wireless

7.2 Wireless links, characteristics
- CDMA

7.3 IEEE 802.11 wireless LANs ("Wi-Fi")

7.4 Cellular Internet Access
- architecture
- standards (e.g., 3G, LTE, 4G and 5G)

Mobility

7.5 Principles: addressing and routing to mobile users


7.6 Mobile IP

7.7 Handling mobility in cellular networks

7.8 Mobility and higher-layer protocols

# What is mobility?


- spectrum of mobility, from the network perspective:



# Mobility: vocabulary

*home network:* permanent "home" of mobile (e.g., 128.119.40/24)

*home agent: entity that will perform mobility functions on behalf of mobile, when mobile is remote*





*permanent address:* address in home network, *can always* be used to reach mobile e.g., 128.119.40.186

# Mobility: more vocabulary

*permanent address:* remains constant (e.g., 128.119.40.186)

*visited network:* network in which mobile currently resides (e.g., 79.129.13/24)

*care-of-address:* address in visited network. (e.g., 79,129.13.2)




*foreign agent:* *entity in visited network that performs mobility functions on behalf of mobile.*

*correspondent:* *wants to communicate with mobile*

# Contacting a mobile friend:




Consider friend frequently changing locations, how do you find him/her?

- search all phone books?
- expect her to let you know where he/she is?
- call his/her parents?
- Facebook!

The importance of having a "home":


- a definitive source of information about you
- a place where people can find out where you are

# Mobility approaches

- let network (routers) handle it:
  - routers advertise well-known name, address (e.g., permanent 32-bit IP address), or number (e.g., cell #) of visiting mobile node via usual routing table exchange
  - Internet routing could do this already *with no* changes! Routing tables indicate where each mobile located via longest prefix match!


# Mobility approaches

- let network (routers) handle it:
  - routers advertise well-known name, address (e.g., permanent 32-bit IP address), or number (e.g., permanent network #) of visiting mobile node via usual routing table exchange
  - Internet routing could do this already *with no* changes! Routing tables indicate where each mobile located via longest prefix match!




- let end-systems handle it: functionality at the "edge"
  - *indirect routing:* communication from correspondent to mobile goes through home network, then forwarded to remote mobile
  - *direct routing:* correspondent gets foreign address of mobile, send directly to mobile


# Mobility: registration




end result:


- foreign agent knows about mobile
- home agent knows location of mobile

# Mobility via indirect routing



# Indirect Routing: comments


- mobile uses two addresses:
  - permanent address: used by correspondent (hence mobile location is *transparent* to correspondent)
  - care-of-address: used by home agent to forward datagrams to mobile
- foreign agent functions may be done by mobile itself
- triangle routing: correspondent-home-network-mobile
  - inefficient when correspondent, mobile are in same network



# Indirect routing: moving between networks


- suppose mobile user moves to another network
  - registers with new foreign agent
  - new foreign agent registers with home agent
  - home agent update care-of-address for mobile
  - packets continue to be forwarded to mobile (but with new care-of-address)
- mobility, changing foreign networks transparent: *on going connections can be maintained!*

# Mobility via direct routing




# Mobility via direct routing: comments

- overcome triangle routing problem
- *non-transparent to correspondent:* correspondent must get care-of-address from home agent
  - what if mobile changes visited network?



# Accommodating mobility with direct routing

- anchor foreign agent: FA in first visited network
- data always routed first to anchor FA
- when mobile moves: new FA arranges to have data forwarded from old FA (chaining)



# Chapter 7 outline

7.1 Introduction

Wireless

7.2 Wireless links, characteristics
- CDMA

7.3 IEEE 802.11 wireless LANs ("Wi-Fi")

7.4 Cellular Internet Access
- architecture
- standards (e.g., 3G, LTE)

Mobility

7.5 Principles: addressing and routing to mobile users

7.6 Mobile IP


7.7 Handling mobility in cellular networks

7.8 Mobility and higher-layer protocols

# Mobile IP

- RFC 3344
- has many features we've seen:
  - home agents, foreign agents, foreign-agent registration, care-of-addresses, encapsulation (packet-within-a-packet)
- three components to standard:
  - indirect routing of datagrams
  - agent discovery
  - registration with home agent

# Mobile IP: indirect routing




# Mobile IP: agent discovery


- *agent advertisement:* foreign/home agents advertise service by broadcasting ICMP messages (typefield = 9)

H,F bits: home and/or foreign agent

R bit: registration required




# Mobile IP: registration example



# Components of cellular network architecture

recall:





different cellular networks,
operated by different providers


# Handling mobility in cellular networks

- *home network:* network of cellular provider you subscribe to (e.g., Sprint PCS, Verizon)
  - *home location register (HLR):* database in home network containing permanent cell phone #, profile information (services, preferences, billing), information about current location (could be in another network)
- *visited network:* network in which mobile currently resides
  - *visitor location register (VLR):* database with entry for each user currently in network
  - could be home network

# GSM: indirect routing to mobile




# GSM: handoff with common MSC




- *handoff goal:* route call via new base station (without interruption)
- reasons for handoff:
  - stronger signal to/from new BSS (continuing connectivity, less battery drain)
  - load balance: free up channel in current BSS
  - GSM doesn't mandate why to perform handoff (policy), only how (mechanism)
- handoff initiated by old BSS


# GSM: handoff with common MSC




1. old BSS informs MSC of impending handoff, provides list of 1+ new BSSs
2. MSC sets up path (allocates resources) to new BSS
3. new BSS allocates radio channel for use by mobile
4. new BSS signals MSC, old BSS: ready
5. old BSS tells mobile: perform handoff to new BSS
6. mobile, new BSS signal to activate new channel
7. mobile signals via new BSS to MSC: handoff complete. MSC reroutes call

8 MSC-old-BSS resources released


# GSM: handoff between MSCs




(a) before handoff

- *anchor MSC:* first MSC visited during call
  - call remains routed through anchor MSC
- new MSCs add on to end of MSC chain as mobile moves to new MSC
- optional path minimization step to shorten multi-MSC chain

# GSM: handoff between MSCs





(b) after handoff

- *anchor MSC:* first MSC visited during call
  - call remains routed through anchor MSC
- new MSCs add on to end of MSC chain as mobile moves to new MSC
- optional path minimization step to shorten multi-MSC chain

# Mobility in 4G networks: major mobility tasks

Extra Slide




① base station association:
- covered earlier
- mobile provides IMSI – identifying itself, home network


② control-plane configuration:
- MME, home HSS establish control-plane state - mobile is in visited network

③ data-plane configuration:
- MME configures forwarding tunnels for mobile
- visited, home network establish tunnels from home P-GW to mobile

④ mobile handover:
- mobile device changes its point of attachment to visited network

# Handling Mobility in LTE

- Paging: idle UE may move from cell to cell: network does not know where the idle UE is resident
  - paging message from MME broadcast by all eNodeB to locate UE
- handoff: similar to 3G:
  - preparation phase
  - execution phase
  - completion phase



# Mobility: cellular versus Mobile IP

| cellular element | Comment on cellular element | Mobile IP element |
|---|---|---|
| **Home system** | Network to which mobile user's permanent phone number belongs | **Home network** |
| **Gateway Mobile Switching Center, or "home MSC". Home Location Register (HLR)** | Home MSC: point of contact to obtain routable address of mobile user. HLR: database in home system containing permanent phone number, profile information, current location of mobile user, subscription information | **Home agent** |
| **Visited System** | Network other than home system where mobile user is currently residing | **Visited network** |
| **Visited Mobile services Switching Center. Visitor Location Record (VLR)** | Visited MSC: responsible for setting up calls to/from mobile nodes in cells associated with MSC. VLR: temporary database entry in visited system, containing subscription information for each visiting mobile user | **Foreign agent** |
| **Mobile Station Roaming Number (MSRN), or "roaming number"** | Routable address for telephone call segment between home MSC and visited MSC, visible to neither the mobile nor the correspondent. | **Care-of-address** |

# Wireless, mobility: impact on higher layer protocols

- logically, impact *should* be minimal …
  - best effort service model remains unchanged
  - TCP and UDP can (and do) run over wireless, mobile
- … but performance-wise:
  - packet loss/delay due to bit-errors (discarded packets, delays for link-layer retransmissions), and handoff
  - TCP interprets loss as congestion, will decrease congestion window un-necessarily
  - delay impairments for real-time traffic
  - limited bandwidth of wireless links

# Chapter 7 summary

## *Wireless*

- wireless links:
  - capacity, distance
  - channel impairments
  - CDMA
- IEEE 802.11 ("Wi-Fi")
  - CSMA/CA reflects wireless channel characteristics
- cellular access
  - architecture
  - standards (e.g., 3G, LTE, 4G and 5G)

## *Mobility*

- principles: addressing, routing to mobile users
  - home, visited networks
  - direct, indirect routing
  - care-of-addresses
- case studies
  - mobile IP
  - mobility in GSM, LTE
- impact on higher-layer protocols