UTM UNIVERSITI TEKNOLOGI MALAYSIA

FACULTY OF COMPUTING
UTM Johor Bahru

NETWORK COMMUNICATIONS (SECR1213)

Section 04

Semester 01, 2025/2026

Network Design for Faculty of Computing Block N28B

Lecturer: Ts. Hazinah binti Kutty Mammi

Group Name: TICH TECH

Group Members:

No	Name	Matric No
1	SARAH HAMIZAH BINTI HASRAM	A24CS0296
2	NURUL HUDA NABILAH BINTI ABDUL RAHIM	A24CS0176
3	LUO CIMEI	A24CS4102
4	AMR KHALED HASAN QATAB	A24CS4100

Report Abstract

Table of Contents

1.0 Introduction.....3

2.0 Project Background and Overview..... 4

3.0 Compiled Solutions of Task 1-5..... 5

TASK 1..... 5

TASK 2..... 15

TASK 3..... 16

TASK 4..... 17

TASK 5..... 18

4.0 Conclusion..... 24

5.0 Team Members and Responsibilities.....25

6.0 References.....26

Appendices.....27

Table of Figures

Figure 1:

Figure 2:

Figure 3:

1.0 Introduction

This project involves the design planning of a network infrastructure for the new Faculty of Computing Block N28B. This project applies concepts learned in the Network Communication course to a real world scenario that requires a reliable, secure, scalable and cost effective network solution. Acting as network consultants, our team is responsible for analysing requirements, designing the network architecture and proposing suitable technologies to support the academic and operational needs of the faculty.

The aim of this project is to design a network system that can support current teaching, learning and administrative activities while remaining flexible enough to accommodate future growth. The proposed network is intended to provide high-speed connectivity, efficient management and secure communication across all areas of the new building.

The scope of this project includes understanding user and organizational requirements, designing the physical building layout, selecting appropriate network and end-user devices, planning LAN and WAN connections and developing an efficient IP addressing scheme. This project also considers network performance, scalability, security, wireless connectivity and budget limitations.

The objective of this project is to design and propose a complete network solution that fulfills functional, technical and future requirements. This includes ensuring reliable connectivity for laboratories, learning spaces and common areas while supporting high-performance networking, secure access and ease of management. The project also aims to apply theoretical networking knowledge in a practical context and enhance teamwork and problem-solving skills.

Several assumptions were made including the availability of network devices within the assigned budget, the accuracy of projected growth provided in the case study and successful integration with the existing campus network infrastructure.

2.0 Project Background and Overview

The Faculty of Computing is experiencing growth in students, staff and teaching activities, increasing demands on its IT and network infrastructure. Current facilities are insufficient to support high-performance systems, digital platforms and specialised labs, prompting the construction of a new two-storey building.

The building will accommodate multiple computer labs, a hybrid classroom, a video conferencing room and a student lounge with wireless access. Labs such as the Cisco Lab and Embedded Lab require dedicated networking equipment and configurations for hands-on learning. The network must high-speed connectivity, handle heavy traffic, ensure security and scale to meet future growth without major redesign.

Budget considerations require careful selection of devices, cabling and addressing schemes to balance cost, performance and reliability. This project presents a network design tailored to the faculty's floor plan and lab layout, addressing current challenges while supporting long term academic needs.

3.0 Compiled Solutions of Task 1-5

TASK 1

1.0 Introduction

This project focuses on the initial stage of planning a network system for the new Faculty of Computing building. In this task, our group is required to form a team, study the case study, and design a suitable floor plan that meets the project requirements. The design aims to provide a clear layout for all building areas such as labs, hybrid classroom, video conferencing room and student lounge.

This task helps the team to understand how space planning relates to network design, ensuring that every area is efficiently arranged to support smooth connectivity and future expansion. By working together and applying appropriate design methods, our group developed a realistic floor plan that serves as the foundation for the upcoming network planning tasks.

Moreover, all floor plans in this report were created using Draw.io software. Below is the calculation of the final scale ratio used.

Real building size
Width: 30 m = 3000 cm
Height: 20 m = 2000 cm
3000 ÷ 200 = 15 cm (so to fit on A4 paper)

The overall building layout, which measures approximately 30 metres in length and 20 metres in width, was drawn to a scale ratio of 1:200. This means that 1 centimetre on the floor plan represents 2 metres in actual size. The chosen scale allows the entire building, including all labs, classrooms, and facilities, to fit proportionally within the page. The 1:200 ratio provides a clear and readable representation suitable for analysis and network layout planning.

2.0 Floor Plan Design

2.1 Ground Level Floor Plan




figure 2.1 Ground Level Floor Plan

The ground floor includes the Hybrid Classroom, Video Conference room, Student lounge, male and female prayer rooms, and male and female bathrooms. The layout is designed to support both learning and collaboration, providing flexible spaces for teaching and group discussions. The hybrid classroom and video conference room are positioned for easy access and efficient network connectivity, while the student lounge offers an open area for relaxation and study with wireless access. The placement of the prayer rooms and bathrooms ensures convenience and accessibility for all users.

2.2 First Level Floor Plan




figure 2.2 First Level Floor Plan

The first floor consists of General lab 1, General lab 2, the Cisco lab and Embedded lab, along with male and female bathrooms. The labs are arranged to allow smooth traffic flow and efficient cabling between rooms. The Cisco lab is located for specialized networking activities, and the Embedded lab is set up for IoT and sensor-based experiments. Both General labs are designed for flexible use, suitable for various computing courses. This layout ensures a practical learning environment with sufficient space for a minimum of 30 workstations per lab and supports future network expansion.

2.3 Hybrid Classroom




figure 2.3 Hybrid Classroom Floor Plan

The hybrid classroom supports both physical and virtual learning. It is equipped with video conferencing systems, interactive smart boards, wireless microphones and high-speed internet connectivity. This setup allows the lecturer to conduct face-to-face sessions while simultaneously connecting with remote participants. The design ensures high audio-visual quality and comfortable seating arrangements to enhance the teaching and learning experience.

2.4 Video Conference Room




figure 2.4 Video Conferencing Room Floor Plan

The video conference room is built for virtual meetings, presentations and collaborative sessions. It includes high-definition cameras, conference microphones, a large display screen and reliable network connections. The room supports communication between staff, students and external partners, promoting remote project coordination, and academic discussions.

2.5 Student Lounge




figure 2.5 Student Lounge Floor Plan

The student lounge provides a comfortable space for students to study, collaborate or relax. It is equipped with Wi-Fi access, charging ports and comfortable seating. The design encourages a social yet productive environment where students can engage in group discussions or individual work while staying connected to the faculty's network.

2.6 Cisco Lab




figure 2.6 Cisco Lab Floor Plan

The Cisco Lab is designed for network configuration, troubleshooting and implementation training. It includes 36 computer workstations, 9 Cisco routers and switches, patch panels and structured cabling systems to support hands-on networking activities. The lab is equipped with high-speed wired connections and secure access points for real-time simulation and testing. This setup supports the Faculty's goal of preparing students for professional networking certifications and 4IR-related technologies.

2.7 Embedded Lab




figure 2.7 Embedded Lab Floor Plan

The embedded lab focuses on IoT, digital systems, and sensor-based projects. It is equipped with development kits, microcontrollers, testing instruments and computers connected through a stable local area network. The lab provides both wired and wireless connectivity to allow students to integrate hardware and software systems efficiently. The arrangement ensures enough workspace for hardware setup and prototype testing.

2.8 General Lab




figure 2.8 General Lab 2 Floor Plan



figure 2.9 General Lab 2 Floor Plan

The two General labs are designed for regular computing classes, programming and software-based learning. Each lab contains 30 computer workstations, projectors, network switches and Wifi access. The layout allows easy movement and clear visibility for both students and instructors. The network infrastructure ensures high-speed internet access for online learning, research, and lab exercises.

Reflection Task 1

Through this task, we learned that the placement of rooms and labs within a building directly affects network efficiency, usability and management. By placing the hybrid classroom, student lounge and video conferencing room on the ground floor, we understood how shared and high traffic area benefit from easy access and strong wireless coverage. These spaces are frequently used by different group and often involve guest access or flexible usage. This making them more suitable for the ground floor where network access points can be optimised for wide coverage rather than specialised configurations. Placing General lab 1, General lab 2, Cisco lab and Embedded lab on the first floor allows for more structured cabling, easier device management and better security. This make it easier to manage when they are located together. We also learned that this arrangement simplifies troubleshooting, supports consistent performance across labs and allow future upgrades to be implemented without disrupting public or shared spaces.

Lastly, we learned that an efficient layout is not only about current usage but also about long term maintenance and scalability. Separating general use areas on the ground floor and specialised labs on the first floor allows network to be expanded or upgraded without affecting unrelated areas.

TASK 2

Questions

1. **What specific devices and equipment will be used in specialized labs, such as the Cisco Network Lab?**

   In the Cisco Networking Laboratory, the specific device that may be used in Cisco Network Lab is Raspberry Pis. Raspberry Pis functions as versatile access nodes and interfaces, connecting students to Cisco Devices *(Shakya et al., 2016)*. These small computers enable students to configure and manage the Cisco network equipment, making learning practical and interactive. Simultaneously, Cisco Devices form the core of the wireless network, including routers, switches, and access points. Connected to Raspberry Pis, they provide hands-on experience for students to apply theoretical knowledge to real-world networking scenarios, preparing them for careers in the field. Together, Raspberry Pis and Cisco Devices create a dynamic learning environment in the lab.

2. **What is the suitable router type for each of the laboratories?**

   Router is a vital device in creating a powerful Local Area Network (LAN). It is a device that connects LAN with the Internet Service Provider (ISP) or Wide Area Network (WAN). In our new academic building, we use 2 in 1 modem routers. This kind of modern network infrastructure provides end users a better internet experience and connectivity as it improves signal strength and transfer rates. In our new academic building, there will be four interconnected routers which are placed at the server room. This enables the construction of a stronger subnet within the building.

   There are several types of routers that are suitable for creating a networking infrastructure. First, the cable modem is one of the powerful modems that allows anyone to access the internet anywhere. In research *(Choudhary, 2022)*, since it is not a dial-up connection, which requires you to disconnect from the Internet to receive and make calls on your landline, the Internet is also accessible around the clock. In comparison to DSL satellite, dial-up, and satellite connections, cable modems provide higher Internet speeds.

Large file download and upload times are accelerated by cable modems. In contrast to dial-up connections, cable modems are less susceptible to dropping out or losing connection.

The second type of router is Digital Subscriber Line (DSL) modem. DSL is quicker than dial-up and allows users to select between various connection speeds and provider pricing. *(Diffen, n.d.)* It also gives users access to the Internet and a phone line simultaneously. Cable delivers performance that is quicker than both dial-up and, most likely, DSL and is not dependent on the distance from a provider's central location.

3. **What type of network cable is the most appropriate for connecting the computers, and what are the reasons for selecting it?**

   The most appropriate network cable for connecting computers is a Cat6 Ethernet cable. They offer speeds up to 1 Gbps, sufficient for most educational applications, and provide a good balance between performance, distance (up to 100 meters without signal degradation), and cost *(Mitchell, 2019).* Additionally, Cat6 cables have better shielding against electromagnetic interference, which is common in school environments with numerous electronic devices. Their compatibility with existing network standards and a degree of future-proofing for potential network upgrades make them a practical and efficient option for educational settings *(Luciaclemares, 2023).* Lastly, it is cost-effective and widely available, making them a practical choice for networking needs *(Martindale, 2019).*

4. **What are the required specifications for high-speed internet connections in the labs, classrooms, and video conferencing rooms to support the computing needs?**

   The required specifications for high-speed internet connections include a bandwidth management system featuring advanced functionalities, such as time allocation for service usage, offers the capability to assign dedicated bandwidth and specific time slots to individual users, enhancing the overall network experience. *(Sawehli et al., 2020)* Through dynamic bandwidth allocation, the system can adapt and allocate varying bandwidth based on user profiles and needs, ensuring that critical users receive the

necessary resources while efficiently utilizing network capacity. *(Sawehli et al., 2020)* This approach guarantees a reliable internet connection speed, which is particularly crucial in densely populated areas where many users are accessing the network simultaneously. These systems, which govern and regulate the dedicated bandwidth provided by internet service providers (ISPs), play a pivotal role in optimizing network performance, making them integral components for ensuring a seamless and high-quality online experience for users. This setup enables the establishment of a high-speed internet connection that can handle multiple users concurrently, enhancing the overall network performance.

5. **What are the key considerations when planning the network infrastructure for a large academic building like the Faculty of Computing?**

   The key considerations include the requirements for indoor wireless network coverage *(Sawehli et al., 2020)*, which will dictate the number and positioning of access points (APs) within the facility. Factor in the expected number of devices *(Sawehli et al., 2020)*, such as laptops, that will connect to the network to ensure efficient operation. Additionally, plan for overlapping wireless coverage in outdoor areas *(Sawehli et al., 2020)* by establishing multiple base stations, ensuring seamless wireless connectivity across the entire floor of the building. Consider the room sizes and strategic position access points, including options like ceiling-mounted devices, to preserve signal strength. Lastly, carefully select and deploy the appropriate wireless network equipment *(Sawehli et al., 2020),* such as the company's MSR, tailored to the specific needs of various academic buildings, including the main building, laboratory building, office building, and student lounge, to achieve comprehensive and reliable network coverage.

6. **Should each lab support group-based learning (collaborative tables, shared screens) or individual workstation ?**

   According to Ms. Hazinah Kutty Mammi, the Faculty representative, each lab in the Faculty of Computing should be designed with individual workstations rather than group-based collaborative tables, as this setup best supports the hands-on and technical

nature of computing courses such as programming, networking and embedded systems. These subjects require students to perform independent tasks like coding, configuring network devices and testing hardware components, which demands full control over personal computers and dedicated resources. Individual workstations ensure that every student can customise their software environment, work efficiently and develop personal problem-solving and technical skills. This layout also promotes fairness and academic integrity during assessments while simplifying lab management and maintenance. Although the workstations are designed for individual use, collaboration can still be achieved digitally through shared network drives, cloud platforms or online tools, providing flexibility for both individual and group activities.

7. How to ensure network security?

Network security is essential to prevent the miscellaneous attack from the hacker to get into the LAN or to achieve Denial-of-Service (DoS) on the server. To defend such attack, there is some prevention or defensive action can be taken from the software perspective *(Rojas, 2014)*. The first action to enhance software security is to install a firewall. Firewall can play a role of first-line defence against all type of attack and control unauthorized access to the computer or internet that will harden the ability of the attacker to sneak into the LAN. The second action is to install a web-filtering. The purpose of web-filtering is to prevent the device attached to the LAN from surfing unwanted website such as dark web that student will always enter it out of curiosity or to get some illegal information or product from it. Besides, the web-filtering also can prevent the devices to search for adult-content that mostly at high-risk of containing malware from the attacker. Apart from the advantage of the security, web-filtering also can block the surfing of Facebook and social media and game to maintain a high quality and efficiency studying environment.

8. **What tools and techniques can be used for real-time monitoring and management of the network to ensure high availability and performance?**

   To ensure high availability and performance, one of the methods is to utilize network monitoring tools like ManageEngine OpManager *(ManageEngine, 2019)*. These tools can track network devices, servers, switches, routers, and more in real-time, providing insights into network performance. Secondly, monitoring real-time performance metrics such as bandwidth usage, latency, packet loss, and network traffic *(Lamberti, 2023)*. These metrics help identify issues as they occur and allow for prompt troubleshooting. Besides that, leverage network monitoring tools that offer customizable widgets and real-time performance graphs to visualize network data effectively and troubleshoot problems efficiently *(Lamberti, 2023).*

9. **What are the key requirements for a high-quality video conferencing room in terms of network connectivity and hardware?**

   The key requirement for a high-quality video conferencing room is having a high-resolution webcam. This is because high-quality video conferencing relies on capturing and transmitting subtleties such as facial expressions and body language. When these details are lost, the authenticity of meetings diminishes, lacking the nuances of in-person interactions *(Writer, 2020)*. The second one is sufficient network bandwidth. The amount of internet strength needed depends on how clear you want the video to be. For instance, if we want a moderate quality video at 720p resolution with 15 frames per second, we will need about 1 Mbps. However, for a higher quality video at 4K resolution with 30 frames per second, we would need roughly 4 Mbps. Also, if many people join the video call, more internet strength will be necessary. Even if our Wi-Fi is good and reaches throughout the building, having lots of people on the call will demand more internet power. *(Writer, 2020)*

10. How to set up a LAN?

Before setting up the network, it is necessary to identify the local services and number of devices that are going to connect to the internet. A unique address is required for each server, devices, and workstation. To determine the distance for all hardwired devices, run a cable to servers or any possible working area. *(Angelina Twain, 2016)* Next, prepare a standard Ethernet cable and gather all the devices needed especially router and switch. Configure the WAN and LAN ports of the router. Make sure the address pool has enough addresses for all the workstation. After that, connect the wire for the network. Use a standard Ethernet cable to connect workstations and servers. Connect the switch to the router LAN port by using a straight port on the switch. Last, connect the access point to the router via Ethernet cable. Test the internet connectivity with each of the workstations, printers, and servers. *(Kim Staples, 2017)*

Feasibility Assesment

Technical feasibility

The technical feasibility of the proposed Faculty of Computing upgrade is highly achievable, as all required devices, network technologies and infrastructure components are readily available and compatible with current educational and industrial standards. Modern computing and networking equipment such as high performance desktop computers, network switches, routers, wireless access point and IoT devices. These are widely available from established vendors like Cisco, HP and Dell. The proposed setup, which includes four specialized labs called General labs, Cisco lab and Embedded Lab and one hybrid classroom and one video conferencing room can be efficiently supported using Gigabit Ethernet (1 Gbps) or 10 Gigabit Ethernet (10 Gbps) backbone network, which are standard in current academic environments. These technologies are fully compatible with structured cabling systems and Wifi standard, ensuring high-speed and low-latency connectivity.

Additionally, the integration of security measures such as firewalls, network access control (NAC) and antivirus gateways is technically feasible and can be implemented using existing network management tools and security appliances. The embedded lab's IoT and sensor-based learning components can be easily supported using microcontrollers and wireless communication modules that integrate seamlessly into the same network infrastructure. Overall, the proposed system is technically feasible, scalable and compatible with the university's current and future technologies ecosystem.

Operational feasibility

Operationally, the project is feasible. The proposed network can be managed effectively by existing IT staff once training is provided. A centralised network monitoring system will allow administrators to configure, monitor, and troubleshoot devices efficiently.

The design supports the daily operations of different users within the faculty. For example, students will have stable and secure Wi-Fi connection and wired access throughout the labs and the student lounge and lecturers will have access to dedicated VLANs that is flexible for teaching and online conferencing. Administrative staff will also benefit from a steady and high-speed connection for documentation, scheduling, and communication systems.

In addition, maintenance will be scheduled outside of class hours to minimise disruption for students and staffs. Proper documentation and standard operating procedures will be recorded to ensure smooth operation and troubleshooting in the future. Security measures such as firewalls, authentication systems, and antivirus softwares will protect sensitive data such as student records and internal files. These implementations show that the project can operate efficiently and securely on a day-to-day basis.

Economic feasibility

The project conducts economic feasibility analysis in terms of budget rationality, operation and maintenance cost control and long-term investment value.

- Budget rationality

  The allocated budget is for this project is RM1,600,000 and it is in line with the scale and functional requirements of the new teaching building, which can fully guarantee the necessary network infrastructure and installation funds while avoiding unnecessary expenses, thus keeping the budget reasonably within an acceptable range

- Operation and maintenance cost control

  The school has its own IT department. After training, IT staff can operate and maintain the system independently without relying on external services, reducing operating and maintenance costs.

- Long term investment value

  The network design for this project prioritizes long-term reliability and sustainability. The selected equipment is durable and of high quality, reducing the need for frequent replacements or repairs. Although the project requires a large initial investment, this design lowers operating and maintenance costs, so it increasing long-term return on capital. Furthermore, a stable and secure network can lead to greater educational benefits and improve student and staff satisfaction.

Overall, the project demonstrates high economic feasibility. The project budget is within acceptable limits, operating and maintenance costs are effectively controlled, and the design reflects long-term value in terms of resource utilization and system reliability. The project is both cost and operational efficiency, and will bring economic and educational benefits to the school.

Schedule feasibility

The network can be developed and implemented within the given project timeline. The new building and network upgrade is considered realistic and achievable provided that proper planning, coordination and phased implementation are followed. All required devices such as routers, switches, and access points are readily available in the market, and the installation process can be completed efficiently through proper planning. This schedule is also supported by the fact that all required network devices and computing equipment are commercially available and can be sourced from established vendor without long lead times. The building structure and layout are simple, allowing the setup to be done in stages without delays. Therefore, no major issues are expected, and the project is time-feasible within the scheduled duration.

Reflection Task 2

Working on Task 2 as a group allowed us to combine our ideas and technical knowledge to plan the network infrastructure for the Faculty of Computing. We collaboratively identified the devices and equipment needed for specialized labs, designed lab layouts with individual workstations, and considered the best network connections, routers, and high-speed internet requirements to ensure reliable and efficient performance.

This task also helped us understand the importance of feasibility analysis in network design. We learned that a network does not only need to work technically, but it must also be realistic in terms of cost, daily operation, and time constraints. Through this task, we realised that technical, operational, economic, and schedule feasibility are closely related. From the technical feasibility analysis, we understood the value of using standard and reliable devices to ensure stability and ease of implementation. Operational feasibility helped us think about daily usage, maintenance, and how the network would be managed by IT staff. Economic feasibility was one of the more challenging parts, as we had to consider budget limits while still meeting performance requirements. Schedule feasibility also showed us that good planning is necessary to complete a project on time. Overall, this task helped us think more realistically about network planning instead of focusing only on technical features.

TASK 3

List of Devices

1) Router

Model	 Cisco ISR 4321	 Juniper SRX345	 TP- Link TL-ER7206
Throughput	100-300 Mbps	Up to 5 Gbps	Up to 1.8 Gbps
WAN options	2x Gigabit	4x Gigabit	4x Gigabit
LAN ports	2x 1GbE	16x 1GbE	4x 1GbE
Security Features	Bisac (Firewall, VPN, IPS)	Strong (Firewall, VPN, IPS/IDS, Threat Protection)	Bisac (Firewall, VPN, IPS)
Scalability	Limited expansion	Highly expandable	Limited expansion
Redundancy	No	Yes	No
Management	Cisco IOS XE	Junos OS	Omada SDN os
Price (RM)	**4764.11** (Link)	**9533** (Link)	**580** (Link)
Reference	More information	More information	More information

Reason for Choosing Juniper SRX345:

The Juniper SRX345 is the best router option due to its high throughput, extensive LAN/WAN ports, and redundancy, supporting many devices reliably. Its advanced security features and scalable design make it ideal for an academic network with labs, classrooms, and video conferencing rooms. Although it is more expensive, it offers long-term performance, reliability, and easier management, making it a worthwhile investment.

2) Core Switches

Model	 Cisco 9500-24Y4C	 Cisco Catalyst 9500-40X	 Cisco Catalyst 9300
Throughput	Up to 1.7 Tbps	Up to 3.2 Tbps	Up to 208 Gbps
Port	24 × 25GbE (SFP28) + 4 × 100GbE (QSFP28)	40 × 100GbE (varies per model)	24/48 × 1GbE + 4 × 10GbE uplinks
Stackable	YES	YES	YES
Layer	3 Layer	3 Layer	3 Layer
Reliability	Very high	Ultra high	High
Price (RM)	15044 (Link)	31021 (Link)	15000 (Link)
Reference	More information	More information	More information

Reason for Choosing Cisco 9500-24Y4C:

The Cisco 9500-24Y4C was selected because of its high switching capability, Layer 3 capabilities, can work perfectly with our router **(Juniper SRX345)** and excellent backbone stability. It provides fast and secure connectivity, supports advanced routing, and is ideal for scalable campus networks.

3) Access Switch

Model	 Cisco Catalyst 2960-L	 Cisco Catalyst 9200	 TP-Link TL-SG3428
Ports	24/48 × 1GbE + 2× 1GbE uplinks	24/48 × 1GbE + 4 × 10GbE uplinks	24 × 1GbE + 4 × SFP uplinks
Switching speed	Up to 56 Gbps	Up to 176Gbps	Up to 56 Gbps
Stackable	No	Yes	No
PoE option	Available	Available	unavailable
Reliability	Medium	High	Low
Price (RM)	**1170 (link)**	**98200 (link)**	**824 (link)**
Reference	More information	More information	More information

Reason for Choosing Cisco Catalyst 9200:

The Cisco Catalyst 9200 was chosen for its stable performance, fast uplink support, and enterprise-class reliability. It provides robust access layer connectivity, supports 10Gb uplinks, and is suitable for high-density academic environments.

4) Wireless Access Point

Model	 Cisco 1850 / 9115AX	 Ubiquiti UAP- AC-Pro	 TP- Link EAP245
Speed	Up to 1.7 Gbps	Up to 1.3 Gbps	Up to 1.75 Gbps
Users	50 - 70 Users	40 - 50 Users	30 - 40 Users
WIFI Stander	WiFi 6	WiFi 5	WiFi 5
PoE	Yes	Yes	Yes
Price (RM)	**2207** (Link)	**617** (Link)	**399** (Link)
Reference	More information	More information	More information

Reason for Choosing Cisco 1850 / 9115AX :

The Cisco Aironet 1850/9115AX was selected for its high-speed WiFi performance, powerful user capacity, and enterprise wireless features. Supports WiFi 6 technology, provides reliable coverage, and is suitable for dense academic areas**.**

5) Firewall

Model	 **Cisco Firepower 1010**	 **Fortinet FortiGate 60F**	 **Sophos XGS 116**
Throughput	2 Gbps	10 Gbps	6.5 Gbps
Threat Protection	Advanced	Advanced	Advanced
Price	Higher	Medium	Medium

Reason for Choosing Cisco Firepower 1010:

The Cisco Firepower 1010 was selected for its advanced threat protection, integrated VPN capabilities, and ease of deployment. It provides strong network security for small to medium environments, making it suitable for securing academic networks.

6) Camera

Model	 DS-2CD1043G2-LIU	 IPC-HFW2249S-IL	 C925e
Max resolution	4MP(2560x1440)	2MP(1920x1080)	1080P(1920X1080)
Min illumination	0.005 lux(color 0 lux with IR	0.002 lux (color) 0.0002(B/W) 0 lux with IR	RightLight(low-light)
Field of view	H98°,V54°,D114° (2.8mm)	H107°,V56°,D127° (2.8mm)	D78°(fixed)
Price (RM)	329.00 (Link)	476.00(Link)	595.00(Link)
Reference	More information	More information	More information

Reason for choosing Hikvision(DS-2CD1043G2-LIU):

Compared to the other two,the Hikvision offers a higher resolution(4MP). Although its field of view and min illumination are slightly narrower than Dahua(IPC-HFW2249S-IL), it is more affordable. The Logitech(C925e), however, has a fixed viewing angle , so it's not suitable for use in a lab or classroom.

7) Projector

Model	 BenQ W2710i	 XGIMI Halo+	 Optoma HD28e
Resolution	4K(3840X2160)	1080p(1920x1080)	1080p(1920x1080)
Brightness	2200(ANSI lumens)	700(ISO lumens)	3800(lumens)
Light source life	4000 hours(normal) 15000 hours(Smart ECO) 10000(ECO)	25000 hours	15000 hours
Price (RM)	8971.00 (Link)	3277.50 (Link)	2909.00 (Link)
Reference	More information	More information	More information

Reasons for choosing Optoma(HD28e):

Although BenQ(W2710i) delivers the best performance, its price is too high. Compared to XGIMI(Halo+), Optoma has a shorter lifespan, but it offers the same resolution, higher brightness, and a more affordable price. Therefore, Optoma provides a better balance between cost and performance.

8) Screen

Model	 Tripod Screen	 Manual Pull-down Screen	 Motorized Screen
Screen type (120 inches)	Tripod screen	Manual pull-down screen	Motorized screen
Price (RM)	161.92 (Link)	216.76 (Link)	407.83 (Link)

Reasons for choosing Manual pull-down screen:

Although Tripod screens are cheaper, they may be less stable. Manual pull-down screens are not as concvenient as motorized screens, but they are more affordable. Therefore, a manual pull-down screen provides a better price.


9) **Printer**

Model	 **HP LaserJet Pro M404dn**	 **Canon imageCLASS LBP226dw**	 **Brother HL-L6200DW**
Speed	40 ppm	38 ppm	48 ppm
Duplex printing	Yes	Yes	Yes
Energy Efficiency	High	High	Moderate
Price (RM)	1500	1200	1800

Reasons for choosing HP LaserJet Pro M404dn:

Its high-speed printing, energy efficiency, and reliability, which are critical for the usage for many students. The Canon imageCLASS LBP226dw is more budget-friendly but offers slightly lower speed. The Brother HL-L6200DW has the fastest speed but is more expensive and less energy-efficient.

10) IOT Device

Models	 **Raspberry Pi 4**	 **Arduino Nano 33**	 **BeagleBone Black**
Prcosseor	Quad-core ARM Cortex-A72	Dual-core	1GHz ARM Cortex-A8
RAM	2–8 GB	0.5–0.1 GB	0.5–4 GB
Storage	eMMC / microSD	Very limited onboard flash	eMMC / microSD
Connectivity	Wi-Fi, Ethernet, Bluetooth	Wi-Fi & Bluetooth Low Energy (BLE)	Ethernet, Wi-Fi
Price	High	Low	Moderate

Reason for choosing Raspberry Pi 4:

The Raspberry Pi 4 is chosen for its balance of performance, connectivity, and affordability, making it suitable for IoT-focused educational activities.



11) Cable

Model	 Vention Cat6 Cable	 UGREEN Cat8 Cable	 AMPCOM Cat6A Cable
Bandwidth	250MHZ	2000MHZ	500MHZ
Jacket material	PVC	PVC	LSZH
Transmission speed	1000Mbps	40000Mbps	10000Mbps
Price (RM)	23.63 (Link) (20m)	155.02 (Link) (20m)	87.40 (Link) (20m,UTP)

Reasons for choosing Vention Cat6 Cable:

Although the AMPCOM Cat6A and UGREEN Cat8 Cables offer higher performance, Vention is significantly cheaper. Since Cat6 already meets the classroom network requirements, Vention Cat6 Cable is the most cost effective choice.

12) Optical Fiber

Model	 Singlemode OS2 (9/125 µm)	 Multimode OM3 (50/125 µm)	 Corning Singlemode OS2 (9/125 µm) LC–LC
Supported Speed	1–10+ Gbps	Up to **10 Gbps**	10–40 Gbps
Transceiver Type	SFP / SFP+ (LX / LR)	SFP+ 10G-SR	SFP+ / QSFP
Typical Distance	Long distance (km)	Indoor building (≤300 m)	Long distance (km)
Reliability	Very High	High	Extremely High
Price (RM)	51 RM (20m) (Link)	69 RM (20m) (Link)	80 RM (20m) (Link)

Reason for Choosing Multimode OM3 (50/125 µm):

The OM3 multimode fiber optic cable was chosen because it provides enough performance for internal building networks at a reasonable cost. It supports speeds up to 10 Gbps, which is suitable for connecting the core switch to the access switches used in the project. The cable is easy to install, reliable, and appropriate for use within a single academic building without adding unnecessary complexity or extra cost.

13) Desktop Computer

Model	 HP Z2 Tower G9 Workstation	 HP ProDesk 400 G9 PCI	 Dell OptiPlex 7010
CPU	Intel Core i7-13700 (13th Gen)	Intel Core i5 (12th Gen)	Intel Core i5/i7 (13th Gen)
RAM	32 GB DDR5	8-16 GB	16 GB
Processor performance	High-end workstation performance, suitable for heavy multitasking, simulation, VM hosting, development work, rendering and long-duration workload	Strong enough for multitasking, moderate virtualization, simulations	High performance that can handles heavier workloads, VMs, simulation, embedded lab tasks
Storage	1TB NVMe SSD	256 - 512 GB SSD	512 GB SSD
Price (RM)	6820 Link	3137 Link	3648 Link

Reason for choosing HP Z2 Tower G9 Workstation:

This workstation is chosen because it offers significantly higher performance compared to standard desktop PCs. With an i7 13th Gen processor, 32GB RAM, and 1TB NVMe SSD, it can handle heavy workloads, simulations, VM environments, coding, rendering, and research tasks efficiently. It ensures long-term reliability and is ideal for lab usage and future scalability.

14) Monitor

Model	 AOPEN 21.5” Full HD	 Acer 23.8” IPS Full HD	 MSI PRO MP275 27”
Resolution	1920 x 1080 (Full HD)	1920 x 1080 (Full HD)	1920 x 1080 (Full HD)
DisplayPort / HDMI / VGA	Likely VGA + HDMI (basic)	HDMI + DisplayPort (or VGA on some)	HDMI + DisplayPort, maybe DVI depending on model
Screen size	21.5”	23.8”	27”
Panel Type	TN or VA	IPS	IPS
Response / Refresh rate	60-75 Hz	60-75 Hz	100-120 Hz
Colour / Viewing	Basic, for text / code	Good for text, diagrams, code	Very good for diagrams, visual simulation, multitasking
Price (RM)	246 Link	319	372 Link

Reason for choosing Acer 23.8” IPS Full HD:

It provides the best visual clarity for coding, network diagrams and embedded work at an affordable cost. The IPS panel ensures students get wide viewing angles and consistent colour accuracy, which is crucial when multiple users view the same screen in lab environments. At only RM319, it provides excellent value without sacrificing screen quality or reliability.

15) Keyboard & Mouse

Model	 Logitech MK120 wired Keyboard + Mouse Combo	 HP Wired Keyboard + Mouse Combo	 Logitech MK470
Battery Life	N/A (wired)	N/A (wired)	Keyboard battery - 24 months (depends) Mouse - 12 months (depends)
Mouse DPI / sensitivity	Standard optical, good for general tasks, not gaming	Standard office optical DPI (around ~ 1000)	Slightly better / more precise, but still office- use (may be around 1000-1600)
Connectivity	USB wired	USB wired	Wireless (USB receiver)
Durability / Maintenance	Very low maintenance, no battery worry	Low maintenance, no battery worry, reliable for long-term lab use	Need battery replacement / recharging, slightly more maintenance
Price (RM)	59 Link	66 Link	269 Link

Reason for choosing HP Wired Keyboard + Mouse Combo:

It offers excellent durability and zero maintenance, which is necessary in a computer lab with 30-36 workstations. Wired peripherals ensure stable connectivity, no battery replacement and minimal user complaints. At RM 66, it is cost-effective while still being reliable for daily academic use.

Devices and Cost Breakdown

Category	Device	Qty	Unit Price (RM)	Total Price (RM)
Router	Cisco ISR 4321	9	9533	85797
Core Switches	Cisco Catalyst 9300	2	15044	30088
Access Switch	Cisco Catalyst 9200	7	9820	68740
Wireless Access Point	Cisco 1850 / 9115AX	13	2207	28691
Firewall	Cisco Firepower 1010 NGFW	1	10000	10000
Camera	HikvisionDS-2CD1043G2-LIU	6	329	1974
Projector	Optoma HD28e	6	2909	17454
Screen	Manual pull-down screen	6	216.76	1300.56
Printer	HP LaserJet Pro M404dn	2	1500	3000
IOT Devices	Raspberry Pi 4	30	300	9000
Desktop computer	HP ProDesk 400 G9	132	6820	900240
Cable	Vention Cat6 Cable	160	23.63	3780.8
Optical Fiber	Multimode OM3	1	69	69
Monitor	Acer 23.8” IPS Full HD	132	329	43428
Keyboard & mouse	HP Wired Keyboard + Mouse Combo	132	66	8712
Overall Total				1,212 274.36

Reflection Questions

1. **Are you surprised by the prices? How were you surprised?**

   Yes, the prices are somewhat surprising, especially when comparing enterprise-grade networking devices to desktop computers and peripherals. For example, a single Cisco Catalyst 9200 access switch costs RM 9,820, which is higher than many of the other components like desktops and monitors. The high cost reflects the enterprise-level reliability, throughput, and feature set of these devices. Similarly, routers like the Cisco ISR 4321 at RM 4,764 each and the Dell PowerEdge R550 servers at over RM 20,000 per unit highlight how specialized networking and server hardware can be much more expensive than standard computing devices. The surprise mainly comes from realizing that the cost of a few networking devices can account for a large portion of the total budget, even in an educational lab setting.

2. **Have you ever considered cost as a factor for choosing networking devices?**

   Absolutely. Cost is a critical factor when selecting networking devices, especially for educational or lab environments where budgets are limited. While enterprise-grade devices like Cisco switches and routers offer high reliability, advanced security features, and better scalability, they come with high upfront costs. Balancing cost with performance is essential. For instance, a slightly lower-end router or switch may reduce initial expenditure but still meet the required throughput and reliability for student labs. Additionally, considering **total cost of ownership** — including maintenance, power consumption, and support contracts — ensures the chosen devices remain cost-effective over their lifespan.

3. **What are the major differences between the same devices from different brands?**

   The major differences typically lie in performance, features, software, scalability, and cost. For example:

   - Routers: Cisco ISR 4321 provides strong enterprise-grade security and stable throughput, Juniper SRX345 offers higher scalability and redundancy, and TP-Link TL-ER7206 is more cost-effective but limited in features.
   - Switches: Cisco Catalyst 9300 and 9500 series differ in throughput, Layer 3 capabilities, and port configurations. Higher-end switches offer greater reliability, advanced features, and faster uplinks, while lower-end or competitor models may be sufficient for smaller deployments but lack advanced routing options.
   - Wireless Access Points: Cisco 1850/9115AX supports WiFi 6 and higher user capacity, Ubiquiti UAP-AC-Pro offers moderate speed and coverage, while TP-Link EAP245 is cheaper but supports fewer concurrent users.
   - Servers: Dell PowerEdge R550 provides high RAM capacity, dual CPU support, and virtualization readiness; HPE ProLiant and Lenovo ThinkSystem offer lower-cost options with limited expansion.
   - Printers: HP, Canon, and Brother devices differ in speed, energy efficiency, and reliability, affecting suitability for high-usage environments like student lounges.

   Overall, the differences reflect trade-offs between cost, performance, scalability, and advanced features, making brand and model selection crucial depending on the lab or network requirements.

Reflection Task 3

By comparing networking devices from different brands, we learned that price differences usually reflect performance, reliability, security features, and scalability. Enterprise-level networking devices are more expensive, but they provide better stability and long-term support, which are important for a faculty network. However, we also realised that the most expensive option is not always the best choice for an educational environment.Through this task, we learned to consider cost-effectiveness when selecting devices. With a limited budget, it is necessary to balance performance, reliability, and price to meet actual requirements. This process helped us better understand how device selection affects the overall network design and budget planning.

TASK 4

4.1 Identify the Work Area on the Floor Plan

4.1.1 Ground floor




Figure 4.1.1

The ground floor work areas are designed to support teaching, collaboration, communication and student activities while ensuring reliable network connectivity. The hybrid classroom is equipped with desktop or lecturer PCs, interactive smart boards, projectors, wireless microphones and video conferencing cameras. These devices are connected using structured Cat 6 Ethernet cabling to access switches located in the network cabinet, ensuring stable wired connectivity for teaching equipment while wireless access points (APs) provide internet access for student's laptops and mobile devices. The cabling is routed through ceiling trunking to maintain a clean layout and allow future expansion.

The video conference room functions as a collaboration and communication workspace that requires high network reliability. It is equipped with high-definition cameras, conference

microphones, display screen and a dedicated conferencing PC. All critical devices are connected via wired ethernet connections to minimize latency and packet loss during live meetings. A dedicated network switch port and quality-of-service(QoS) configuration ensure smooth audio and video transmission while proper cable management improves safety and maintenance.

A student lounge serves as an informal work and study area where students use personal laptops and mobile devices. This area mainly relies on wireless networking, supported by strategically placed access points to provide full coverage and sufficient bandwidth. Minimal wired cabling is required except for network uplinks to the access points and charging stations. This design allows flexibility, mobility and ease of use while maintaining secure network access.

4.1.2 First floor




Figure 4.1.2

The first floor work areas are dedicated to technical and laboratory-based learning, requiring structured cabling and high-performance network devices. The Cisco lab is a specialized networking workspace equipped with multiple desktop computers, Cisco routers, switches, patch panels and racks. Each workstation is connected using cat 6 ethernet cables to access switches, allowing students to perform routing, switching and network configuration exercises. Patch panels are used to organize cabling and simplify troubleshooting while lab follows a star topology for efficient network management.

The embedded lab supports hardware-based and IoT-related development activities. It is equipped with computers, microcontrollers, development boards, sensors and testing instruments. Workstations are connected through wired ethernet connections for stable data transfer while wireless connectivity is provided for IoT device testing. Proper power outlets, network points and cable trunking are arranged to ensure safety and ease of maintenance during hardware experimentation.

The general labs are designed for programming, software development and general computing tasks. Each lab contains approximately 30 desktop computers connected to a local switch using structured ethernet cabling. The switch uplinks to the main network to provide high-speed internet access. Wireless access points are also installed to support additional devices such as laptops. This combination of wired and wireless connectivity ensures reliability, flexibility and scalability for various academic activities.

4.2 The Distribution and Connection of Devices




Figure 4.2.1

The network is designed to connect all rooms on both floors to the internet in a clear and organized way. Each room uses an access switch to connect end devices such as PCs, wireless access points, cameras, projectors, training routers, and IoT devices using Cat 6 cables.

All access switches are connected to the core switches using fiber optic cables to support higher bandwidth communication between floors. Two core switches are used to improve network reliability. A firewall is included in the network design to provide security control for internal network traffic. It is used to protect internal resources, and the ISP provides internet and external network services for the building.

4.2.1 Ground floor




Figure 4.2.2

Backbone Cabling

The backbone cabling in this network design is used to interconnect the main network distribution points and to support high-speed data transmission across the building. Fibre optic cables are selected as the backbone medium due to their high bandwidth capacity, low signal attenuation, and suitability for handling heavy network traffic.

Horizontal Backbone Cabling

Horizontal backbone cabling refers to the fiber optic connections that run across the same floor to link the Main Distribution Facility (MDF) to major network distribution paths. In the floor plan, horizontal backbone cabling is represented by red lines running along the corridors and central areas. These fiber optic cables distribute network connectivity from the MDF to different sections of the floor, ensuring efficient data flow to all work areas.

The horizontal backbone supports high network traffic generated by laboratories, classrooms, and collaboration spaces. It also reduces congestion by acting as the main high-capacity pathway before connections are distributed through CAT6 horizontal cabling to end devices.

Vertical Backbone Cabling

Vertical backbone cabling refers to the fiber optic connections that link network distribution facilities between different floors. In this design, vertical backbone cabling connects the MDF on the ground floor to the distribution points on the upper floor. This connection allows network services to be shared across floors while maintaining high performance and reliability.

Fiber optic cabling is used for vertical backbone connections because it supports long-distance transmission and provides scalability for future network expansion.

4.2.2 First Floor




Figure 4.2.3

Main Cabling Network

The first-floor main cabling network is designed to connect all labs on the floor to the main network infrastructure. Fiber optic cables are used as the main network to ensure high-speed data transmission, low signal loss, and reliable performance for intensive lab use.

Horizontal Main Cabling Network

The first-floor horizontal main cabling network refers to the fibre optic connections that link the access switches in each lab (General Lab 1, General Lab 2, Cisco Lab, and Embedded Systems Lab) to the central switch.

These fibre optic connections run along the corridors and act as high-capacity paths, efficiently distributing network connectivity throughout the floor.

The horizontal main cabling network ensures a smooth flow of data from all labs before it is aggregated at the central switch and routed to the central network devices.

Horizontal Access Cables

Dual-stranded Cat6 cables are used to connect the horizontal access cables within each lab on the first floor. These cables connect desktop computers and wireless access points directly to the local access switch in each lab, providing a stable, high-speed network connection for peripheral devices

Vertical Backbone Cables

Vertical backbone cables connect the network infrastructure on the first floor to the existing ground floor network. Optical fiber is used for this connection to support long-distance transmission, high bandwidth, and future scalability between floors.

4.3 Number of Connections, Patch Cords, and Switch Ports Needed

Each wired device such as computers, smart boards, video conferencing equipment, routers, switches, and wireless access points is considered one network connection. For every network connection, two patch cords are required which is one connecting the device to the wall outlet and another connecting the patch panel to the switch. In addition, each connection occupies one switch port. The calculation is performed separately for each room and laboratory on the ground floor and first floor to ensure accurate network planning, efficient switch selection, and sufficient capacity for future expansion. The results of this analysis are then used to label the floor plan and support the overall network cabling design.

4.3.1 Ground Floor

Number of connection:

Area	Number of connection needed
Hybrid classroom	3
Student lounge	3
Video conference room	3

Number of patch cords:

Area	Number of patch cords needed
Hybrid classroom	6
Student lounge	6
Video conference room	6

Number of switch ports:

Area	Number of switch ports needed
Hybrid classroom	3
Student lounge	2
Video conference room	3

Ground floor total:

Items	Number of quantity needed
Connections	9
Patch cords	16
Switch ports	8

4.3.2 First Floor

Number of connection:

Area	Number of connection needed
General Lab 1	31
General Lab 2	31
Cisco Lab	45
Embedded Lab	30

Number of patch cords:

Area	Number of patch cords needed
General Lab 1	62
General Lab 2	62
Cisco Lab	90
Embedded Lab	60

Number of switch ports:

Area	Number of switch ports needed
General Lab 1	31
General Lab 2	31
Cisco Lab	45
Embedded Lab	30

First floor total:

Items	Number of quantities needed
Connections	137
Patch cords	274
Switch ports	137

Overall building total:

Items	Number of quantities needed
Connections	146
Patch cords	290
Switch ports	145

4.4 Identify Cable Types and Lengths

4.4.1 Ground Floor

a) Total Length of Cat6 Ethernet Cables needed on the Ground Floor:
   Hybrid Classroom : 7.2 + 0.6 + 0.2 + 3.4 = 11.4m
   Student Lounge : 6.6 + 4.2 + 2.1 = 12.9m
   Video Conference Room : 8 + 5 + 0.3 + 1.3 + 0.7 + 0.7 + 2.5 = 18.5m
   Total = 42.8m

b) Total Length of Fibre Optic Cables needed on the Ground Floor:
   Hybrid Classroom : 2.1 + 0.6 = 2.7m
   Student Lounge : 1 + 1.1 + 0.6 = 2.7m
   Video Conference Room : 0.9 + 1.5 = 2.4m
   To connect with the Switch core that is on the Ground floor = 10m
   Total = 17.8m

4.4.2 First Floor

a) Cat6 Ethernet Cables
   general lab1 = (9*2) + (5*5) + (2*5) + (5) + (4) + 1 = 63m .
   general lab2 = (9*2) + (5*5) + (2*5) + (5) + (3) + 1 = 62m.
   embedded lab= (9*2) + (5*5) + (2*5) + (5) + (3) + 1 =62m.
   Cisco lab = 1.5 m
   Total = 188.5 m

b) Fibre Optic Cables
   general lab1 = 2m.
   general lab2 = 2m.
   embedded lab = 4m.
   Cisco lab = 2m.
   To connect with the Switch core that is on the First floor = 10m
   Total = 20m.

Reflection Task 4

Through this task, we gained an understanding of how network design is planned based on a building's floor layout. This task required us to identify work areas and decide suitable device placement, cabling paths and network connections for both floors. By analysing different spaces, we learned how network requirements depend on usage and how this affects cabling types, switch placement and connection distribution. This task helped us realise that a well planned physical layout is important to ensure network efficiency, safety and future scalability.

This task also allowed us to reflect on the practical aspects of network implementation such as estimating the number of connections, patch cords, switch ports and cable lengths needed. We are more aware of how small design decisions can impact cost, maintenance and performance. Overall, Task 4 strengthened our understanding of physical network design and improved our ability to plan a realistic and organized network infrastructure.

TASK 5

5.0 Details of subnetting and IP assignation to each lab and room

5.1 Subnet Mask

The network address assigned by the lecturer is:

Network Address: 172.19.0.0/20

Subnet Mask: 255.255.240.0

Host Capacity Calculation

Subnet	Area	IP Address/ Subnet Mask (Binary)	IP Address/ Subnet Mask (Decimal)	Usable Account (Host)
0	Student Lounge (WiFi)	10101100.00010011.00000000.00000000 / 11111111.11111111.11111111.00000000	172.19.0.0/24	256
1	Hybrid Classroom	10101100.00010011.00000001.00000000 / 11111111.11111111.11111111.10000000	172.19.1.0/25	126
2	General Lab 1	10101100.00010011.00000001.10000000 / 11111111.11111111.11111111.11000000	172.19.1.128/26	62
3	General Lab 2	10101100.00010011.00000001.11000000 / 11111111.11111111.11111111.11000000	172.19.1.192/26	62

4	Cisco Lab	10101100.00010011.00000010.00000000 / 11111111.11111111.11111111.11000000	172.19.2.0/26	62
5	Embedded Lab	10101100.00010011.00000010.01000000 / 11111111.11111111.11111111.11000000	172.19.2.64/26	62
6	Network Devices	10101100.00010011.00000010.10000000 / 11111111.11111111.11111111.11100000	172.19.2.128/27	30
7	Video Conference Room	10101100.00010011.00000010.10100000 / 11111111.11111111.11111111.11110000	172.19.2.160/28	14

5.2 Range of IP address, Network and Broadcast address for the subnet

Area	Subnet	Network Address	Usable IP range	Broadcast address
Student Lounge(WiFi)	172.19.0.0/24	172.19.0.0	172.19.0.1-172.19.0.254	172.19.0.255
Hybrid Classroom	172.19.1.0/25	172.19.1.0	172.19.1.1-172.19.1.126	172.19.1.127
General Lab1	172.19.1.128/26	172.19.1.128	172.19.1.129-172.19.1.190	172.19.1.191
General Lab2	172.19.1.192/26	172.19.1.192	172.19.1.193-172.19.1.254	172.19.1.255
Cisco Lab	172.19.2.0/26	172.19.2.0	172.19.2.1-172.19.2.62	172.19.2.63
Embedded Lab	172.19.2.64/26	172.19.2.64	172.19.2.65-172.19.2.126	172.19.2.127
Network Devices	172.19.2.128/27	172.19.2.128	172.19.2.128-172.19.2.158	172.19.2.159
Video Conference Room	172.19.2.160/28	172.19.2.160	172.19.2.161-172.19.2.174	172.19.2.175

5.3 Range of IP address for user types based on the area

Student Lounge

Subnet: **172.19.0.0/24**

Device	**IP Address**
Wireless Access Points	172.19.0.1 - 172.19.0.10
Student Devices	172.19.0.11 – 172.19.0.254

Hybrid Classroom

Subnet: **172.19.1.0/25**

Device	**IP Address**
Lecturer PC	172.19.1.1
Smart Board	172.19.1.2
Projector	172.19.1.3
Camera & Audio Devices	172.19.1.4 - 172.19.1.10
Student Devices	172.19.1.11 - 172.19.1.126

General Lab 1

Subnet: **172.19.1.128/26**

Device	**IP Address**
Lecturer (PC)	172.19.1.129
Student (PCs)	172.19.1.130 – 172.19.1.160

General Lab 2

Subnet: **172.19.1.192/26**

Devices	**IP Address**
Lecturer (PC)	172.19.1.193
Student (PCs)	172.19.1.194 – 172.19.1.223

Cisco Lab

Subnet: **172.19.2.0/26**

Devices	**IP Address**
Lecturer (PC)	172.19.2.1
Student (PCs)	172.19.2.2 – 172.19.2.31
Routers & Switches	172.19.2.32 - 172.19.2.55

Embedded Lab

Subnet: **172.19.2.64/26**

Devices	**IP Address**
Lecturer (PC)	172.19.2.65
Student (PCs)	172.19.2.66 – 172.19.2.95
IoT / Embedded Devices	172.19.2.96 - 172.19.2.110

Video Conference Room

Subnet: **172.19.2.160/28**

Devices	**IP Address**
Conference PC	172.19.2.161
Camera	172.19.2.162
Projector	172.19.2.163
Display Screen	172.19.2.164

Network Devices

Subnet: **172.19.2.128/27**

Devices	**IP Address**
Core Switch	172.19.2.129
Access Switches	172.19.2.130 – 172.19.2.140
Wireless Access Points	172.19.2.141 - 172.19.2.150
Router	172.19.2.151 - 172.19.2.158

Reflection Task 5

Through Task 5, we gained an understanding of subnetting and IP address allocation in an academic network environment. This task required us to carefully analyze the given network address and divide it into appropriate subnets based on different areas such as laboratories, classrooms, and shared spaces. By completing this task, we reflected on the importance of accurate subnet mask selection, correct calculation of network and broadcast addresses, and efficient use of available IP addresses. The process helped us realize that proper planning is important to ensure that each area has sufficient IP addresses while avoiding unnecessary address wastage.

This task also allowed us to reflect on how theoretical networking concepts are applied in real-world scenarios. Assigning IP ranges based on user types and device functions helped us better understand how networks are structured to support different activities and requirements. We learned that even small calculation errors can affect the entire network design.

4.0 Conclusion

The project is fully completed within a few weeks of work and tasks. Throughout this project, we faced a lot of problems and doubts when it came to designing a network. Although it was quite tough for us, we still managed to overcome the problems and complete all the tasks including fixing some errors we made while checking before submitting. The project that we made achieved the goals that we set for each of the tasks, and from this project, we learned a lot of knowledge and gained experience in designing and building a network system that can be proposed in real life. In fact, we learned how to research and make decisions on the appropriate network devices based on the given Budget and requirements. This will be our first experience designing a LAN system, including the floor plan drawing and determining the best position for each device. Moreover, we also learned how to set up the IP address scheme for every network in a system. We believe that this experience will definitely come in handy for us to design a network system again in the future.

Besides the knowledge of implementing a network system, we also learned soft skills, which is a team working, which can only be gained when it comes to teamwork. We noticed the importance of teamwork when doing this project as we might have made some mistakes throughout this project and we will discuss and point out our doubts on certain points we do not understand. After this project, we believed that communication within the team was the main key to completing a group project.

In conclusion, we appreciate this opportunity to design a network system to gain experience and apply the knowledge learned from this course. We believe that the knowledge is beneficial in this project or even in the future, and without the bits of knowledge learned in this course, the project might not be done with the requirements mentioned.

5.0 Team Members and Responsibilities

Team Members	Responsibilities
Sarah Hamizah	Task 1: Design the ground floor and make changes on first floor Task 2: Prepare questions and provide answer with proper citation and answer operational feasibility. Task 3: Elaborate reasons why each device is chosen based on performance, reliability, future scalability and price. Supervises all modifications made by team members and finalises the report edits. Task 4:Identify cable types and cable lengths along with identifying work areas on the ground floor and first floor according to the approved floor plan. Task 5: Checking the outcome based on the topology and examining the IP address chosen. Task 6:
Nurul Huda Nabilah	
Luo Cimei	
Amr Khaled	

6.0 References

1. Shakya, A., Prasad, P. W. C., Alsadoon, A., Zajko, G., & Elchouemi, A. (2016, November). Development of the wireless Cisco networking laboratory pod. ResearchGate. https://www.researchgate.net/publication/315916155_Development_of_the_Wireless_Cisco_Networking_Laboratory_pod

2. Diffen. (n.d.). Cable vs DSL. https://www.diffen.com/difference/Cable_vs_DSL

3. Choudhary, H. (2022, August 14). What is Cable Modem- How it Works, Advantages & Disadvantages. Available: https://etipsguruji.com/cable-modem/

4. Mitchell, B. (2019). Types of Ethernet cables and what they do. Lifewire. https://www.lifewire.com/what-is-an-ethernet-cable-817548

5. luciaclemares. (2023, June 21). What is Ethernet and what kinds of cables exist? Telefónica. https://www.telefonica.com/en/communication-room/blog/what-is-ethernet-kinds-cables-exist/

6. Martindale, J. (2019, July 30). Ethernet cables come in all shapes and sizes. Here's what you need to know. Digital Trends. https://www.digitaltrends.com/computing/different-types-of-ethernet-cables-explained/

7. Sawehli, A. F., Alrashdan, M., & Al-Maatouk, Q. (2020). APU high-speed internet access: A literature review. ResearchGate. https://www.researchgate.net/publication/342623507_APU_HIGHSPEED_INTERNET_ACCESS_A_LITERATURE_REVIEW

8. Rojas, J. (2014). Advantages of web filtering & firewall. Tek-Help. https://www.tek-help.com/advantages-of-web-filteringfirewall/

9. ManageEngine. (2019). Network monitoring software by ManageEngine OpManager. https://www.manageengine.com/network-monitoring/network-monitoring-tools.html

10. Lamberti, A. (2023, November 2). A guide to different types of network monitoring tools: Unveiling the superheroes. Obkio. https://obkio.com/blog/types-of-network-monitoring-tools/

11. Writer, S. (2020, February 14). Video Conferencing Setup Requirements: Your Checklist for Hardware and Software. Lifesize. https://www.lifesize.com/blog/video-conferencingrequirements/

12. Angelina Twain. (2016). 'How to set up a LAN Network'. Retrieved November 22, 2020, https://medium.com/@lia640230/how-to-set-up-a-lan-networkf648c90bf75c

13. Kim Staples. (2017). 'How to set up a Local Area Network (LAN)'. Retrieved November 22, 2020, https://www.broadbandchoices.co.uk/how-to/how-toset-up-a-local-area-network

14. Scribbr. (n.d.). *APA style*. https://www.scribbr.com/category/apa-style/

15. Cisco Systems. (2023). Campus LAN and Wireless LAN Design Guide. Cisco Systems, Inc. https://www.cisco.com/c/en/us/td/docs/solutions/CVD/Campus/cisco-campus-lan-wlan-design-guide.html

16. A Guide to Internet Speed vs. Bandwidth. (n.d.). Lightyear. https://lightyear.ai/blogs/internet-speed-vs-bandwidth

17. Anant Gavali, Rambabu Vatti, Shraddha Gupte, September 2007, "Positioning of Wi-Fi Access Points for Optimum Coverage of Campus-Wide Network" https://www.researchgate.net/publication/344570357_Positioning_of_Wi-Fi_Access_Points_for_Optimum_Coverage_of_Campus_Wide_Network

18. "What is Data Redundancy" - Definitions and Drawbacks | Talend. Talend Real-Time Open Source Data Integration Software. https://www.talend.com/resources/what-is-data-redundancy/

19. Great Learning, "Explain the cybersecurity measures," Medium, May 18 2022. https://medium.com/@mygreatlearning/explain-the-cyber-security-measures

20. GeeksforGeeks*, "Difference Between Router and Switch," GeeksforGeeks, Jul. 11, 2025. https://www.geeksforgeeks.org/computer-networks/difference-between-router-and-switch/*

21. *HP Education products designer for K12 teaching & learning*. (n.d.). HP. https://www.hp.com/us-en/solutions/education/products.html

22. *What equipment is needed for the computer lab?* (n.d.). https://www.schoolnetindia.com/blog/what-equipment-is-needed-for-the-computer-lab/

23. Molenaar, R. (2025, November 20). *Recommended Lab equipment for Cisco CCNA*. NetworkLessons.com. https://networklessons.com/cisco/ccna-200-301/recommended-lab-equipment-for-cisco-ccna

24. Fortinet, *"What Is a Firewall?* — CyberGlossary," *Fortinet*t https://www.fortinet.com/resources/cyberglossary/firewall

25.

Appendices


- The financial budget (what is bought, how much money is used and left, etc)

Details	Quantity	Amount (RM)
Income		
Sponsor from Universiti Teknologi Malaysia		1,600 000.00
Expenses		
Router (Cisco ISR 4321)	9	42876.99
Core Switches(Cisco Catalyst 9300)	2	30000
Access Switch (Cisco Catalyst 9200)	7	68740
Wireless Access Point(Cisco 1850 / 9115AX)	13	28691
Firewall(Cisco Firepower 1010 NGFW)	1	10000
Camera(HikvisionDS-2CD1043G2-LIU)	6	1974
Projector(Optoma HD28e)	6	17454
Screen(Manual pull-down screen)	6	1300.56
Printer (HP LaserJet Pro M404dn)	2	3000
IOT Devices(Raspberry Pi 4)	30	9000
Desktop computer(HP ProDesk 400 G9)	132	900240
Cable(		


Total expenses		
Balance (income - total expenses)		

Rubric


Pictures




Task 1




Task 2


20:13
4G
dkz-ommc-qco
sarah is presenting
What is a Switch vs. a Router?
AMR
C
CIMEI
N
You
AMR

Task 3



AMR KHALED is presenting
Draw
Ask Copilot
6
of 13
Edit with Acrobat
Fiber vs. Copper
Fiber
Copper
Bandwidth
10-Gigabit and beyond
Gigabit
Future-proof
Evolving towards the desktop
CAT7 under development
Distance
40 km+ @ 10,000 Mbps
100 m @ 1000 Mbps
Noise
Immune
Susceptible to EMI/RFI interference crosstalk, and voltage surges
Security
Almost impossible to tap
Susceptible to tapping
Handling
Lightweight, thin diameter
Strong pulling strength
Heavy, thicker diameter
Strict pulling specifications
Figure 4: Difference between fiber and copper cable
a) Identify the work areas on your floor plan.
b) How many connections, patch cords and switch ports have you determined you need?
c) Identify cable types and length.
Deliverables (*things to be submitted):
Sketch/drawing of your PC & network devices arrangement.
The cable length in the identified work areas.
Report Appendix:
Your projected marks based on rubrics (using rubrics given).
Every member's task/work within this task.
Meeting minutes (all meeting minutes MUST be informational and specific).
Due: Week 10 - Thursday 11 December 2025, before 5pm. Submit a PDF file at e-learning.
**Note: Measure the floor plan for the case study to see the maximum distance they
SECR1213_HKM_S12526
7
have to cover from the MDF (Main Distribution Facility). Do not forget to add in the cable length going up the walls and around corners. Record the lengths.
**Tips: scale is important here, to correctly suggest locations and cable structure.
You
CIMEI
AMR
huda


Task 4



figureTask 5 meeting

People we met to discuss the project





Meeting Minutes Task 1

Date / Time	14 October 2025 / 1400
Location	Google Meet
Agenda	Distribution of workloads and brainstorming ideas
Meeting MC	Luo Cimei

Attendance

Name	**Time**	**Reason for Absence**
Sarah Hamizah	1400	-
Nurul Huda Nabilah	1400	-
Luo Cimei	1400	-
Amr	1400	-

Minutes

No.	**Item Discussed**	**Ideas and the Person Giving It**	**Person in Charge & Date**
1	Find the website used for the sketch	Amr Khaled - Suggested using the draw.io website to design and sketch the floor plan. - General lab on the second floor.	Amr (14/10)
2	First floor design	Sarah Hamizah - Design the student lounge, video conference room, prayer room, and hybrid classroom.	Sarah (14/10)
3	Second floor design	Luo Cimei - Design the embedded lab and Cisco lab.	Cimei (14/10)

4	Final edits of the report	Huda Nabilah - Supervises all modifications made by team members and finalises the report edits	Huda (14/10)
5	Meeting ended	1600	

Meeting Minutes Task 2

Date / Time	3 November 2025 / 1400
Location	Google Meet
Agenda	1. Understand the details about task 2
	2. Suggest and select possible questions for task 2
Meeting MC	Nurul Huda Nabilah

Attendance

Name	**Time**	**Reason for Absence**
Sarah Hamizah	1400	-
Nurul Huda Nabilah	1400	-
Luo Cimei	1400	-
Amr	1400	-

Minutes

No.	**Item Discussed**	**Ideas and the Person Giving It**	**Person in Charge & Date**
1	Determine the feasibility	Luo Cimei - Proposed dividing feasibility into four main categories which is schedule, economic, operational and technical feasibility. - Each aspect was assign to one member.	Cimei (3/11)
2	Minimum number of question to ask	Amr Khaled - Suggested preparing at least 12 questions - Proposed that each member should be responsible for	Amr (3/11)

		preparing a minimum of 3 questions.	
3	Decide who needs to interview	Huda Nabilah - Will conduct an interview with lecturer (faculty representative) to clarify user requirement and technical needs - Other member focus on online research	Huda (3/11)
4	Report structure	Sarah Hamizah - Reminded the team that each member should prepare their assigned questions and answer - Responsible for compiling and editing the final report before submission.	Sarah (3/11)
5	Meeting ended	1600	

Meeting Minutes Task 3

Date / Time	24 November 2025 / 2000
Location	Google Meet
Agenda	1. Choose a suitable LAN devices
	2. Talk about the budget given
Meeting MC	Sarah Hamizah Binti Hasram

Attendance		
Name	**Time**	**Reason for Absence**
Sarah Hamizah	2000	-
Nurul Huda Nabilah	2000	-
Luo Cimei	2000	-
Amr	2000	-

Minutes

No.	**Item Discussed**	**Ideas and the Person Giving It**	**Person in Charge & Date**
1	Identify devices needed for the network	Amr Khaled - Suggested listing devices based on each lab and room - Suggested and comparing some devices to make sure a suitable device is selected	Amr (24/11)
2	Research device brands and model	Luo Cimei - Do a lot of research about the brand and model that are available in Malaysia - Recommended checking Malaysian pricing in Senheng, VST ECS and Ingram Micro	Luo Cimei (24/11)

3	Determine quantity of devices and check budget	Nurul Huda Nabilah - Suggested calculating devices based on PC x Labs - Recommended creating a spreadsheet to total the cost for all devices and compare the assigned budget.	Nurul Huda Nabilah (24/11)
4	Final edits of the report and answer the reflection question	Sarah Hamizah - Suggested writing justification based on performance, reliability, future scalability and price - Supervises all modifications made by team members and finalises the report edits.	Sarah Hamizah (24/11)
5	Meeting ended	2200	

Meeting Minutes Task 4

Date / Time	18 December 2025 / 1400
Location	Google Meet
Agenda	Distribution of task 4
	Analysis Task 4 requirement
Meeting MC	Amr Khaled

Attendance		
Name	**Time**	**Reason for Absence**
Sarah Hamizah	1400	-
Nurul Huda Nabilah	1400	-
Luo Cimei	1400	-
Amr	1400	-

Minutes			
No.	**Item Discussed**	**Ideas and the Person Giving It**	**Person in Charge & Date**
1	Understanding Task 4 requirement	Amr Khaled - Discussed the objectives of Task 4, focusing on identifying work areas, planning cabling layout, and drawing network distribution diagrams based on the floor plan from Task 1. - Agreed that the explanation must clearly justify cabling types, switch placement, and connectivity design.	Amr (18/12)
2	Identify work area arrangement	Sarah Hamizah - Identified work areas on the ground floor and first floor according to the	Sarah (18/12)

		approved floor plan.	
3	Design the network distribution diagram	Luo Cimei - Proposed using a hierarchical star topology with a Main Distribution Facility (MDF) on the ground floor and an Intermediate Distribution Facility (IDF) on the first floor. - Suggested drawing separate network distribution diagrams for each floor for better clarity.	Cimei (18/12)
4	Research suitable type of cabling	Huda Nabilah - Suggested using CAT6 UTP cables for horizontal cabling within each floor due to high speed and cost efficiency. - Proposed using fiber optic cable as backbone cabling between floors to support high bandwidth and future expansion.	Huda (18/12)
5	Meeting ended		

Meeting Minutes Task 5

Date / Time	26 December 2025 / 1400
Location	Google Meet
Agenda	Distribution of task 5
	Analysis Task 5 requirement
Meeting MC	Sarah Hamizah

Attendance		
Name	**Time**	**Reason for Absence**
Sarah Hamizah	1400	-
Nurul Huda Nabilah	1400	-
Luo Cimei	1400	-
Amr	1400	-

Minutes			
No.	**Item Discussed**	**Ideas and the Person Giving It**	**Person in Charge & Date**
1	Determining Subnet Mask	Amr Khaled - Choosing the different subnet masks - Estimating the total number of IP addresses	Amr (26/12)
2	Evaluating the Network topology chosen	Sarah Hamizah - Checking the outcome based on the topology - Examining the IP address chosen	Sarah (26/12)
3	Range of IP address, Network and Broadcast address for the subnet	Luo Cimei - Determining which subnets to settle on	Cimei (26/12)
4	Range of IP address for user types based	Huda Nabilah - Determining IP	Huda (26/12)

	on the area	addresses for devices in each room	
5	Meeting ended	1530	