

ALSHUMOOKH GLOBAL BANKING FINANCE AND CREDIT

API Integration & Payload Submission Guide

For Authorized Counterparties and Settlement Partners — CONFIDENTIAL

1. Overview

This guide describes how authorized partners and counterparties submit settlement payloads and M1 Fund transactions to the ALSHUMOOKH settlement infrastructure via our secure REST API. All endpoints require API Key authentication and well-formed JSON request bodies.

Base Production URL:

Production Endpoint

`https://api.alshumookh-pay.com`

NOTE: All communications must use HTTPS (TLS 1.2+). HTTP requests will be rejected automatically. Each new request must carry a unique Idempotency-Key to prevent duplicate processing.

2. Authentication

Every API request must be authenticated. Your API Key is generated from the ALSHUMOOKH Admin Dashboard under the API Clients section and must be kept strictly confidential.

2.1 API Key Authentication (Standard)

Request Headers — API Key

```
POST /api/v1/payloads/ingest HTTP/1.1
Host: api.alshumookh-pay.com
X-API-Key: your_api_key_here
Idempotency-Key: unique-uuid-per-request
Content-Type: application/json
```

2.2 OAuth2 Bearer Token (Enhanced Security)

Request Headers — OAuth2

```
POST /api/v1/payloads/ingest HTTP/1.1
Host: api.alshumookh-pay.com
Authorization: Bearer your_oauth2_access_token
Idempotency-Key: unique-uuid-per-request
Content-Type: application/json
```

2.3 Optional Security Headers

Parameter / Header	Description
--------------------	-------------

X-Timestamp	Unix timestamp in seconds. Must be within 5 minutes of server time.
X-Signature	HMAC-SHA256 over X-Timestamp + '.' + exact request body. Required when HMAC is enabled on your account.
X-JWS-Signature	Detached compact JWS containing SHA-256 hash of the request body.
X-Client-Cert-Fingerprint	mTLS certificate SHA-256 fingerprint for mutual TLS verification.

3. Settlement Payload Endpoint

Use this endpoint to submit a standard settlement payload confirming a blockchain transfer to the ALSHUMOOKH master wallet. The system automatically verifies the transaction on-chain via Alchemy RPC.

3.1 Endpoint Details

Endpoint Reference

```
Method:    POST
URL:       https://api.alshumookh-pay.com/api/v1/payloads/ingest
Auth:      X-API-Key OR Authorization: Bearer <token>
Required:  Idempotency-Key header
```

3.2 Required Headers

Parameter / Header	Description
X-API-Key *	Your API key issued by ALSHUMOOKH Admin Dashboard.
Idempotency-Key *	Unique UUID per request. Re-using the same key returns the original response without re-processing.
Content-Type *	Must be: application/json

3.3 Request Body Fields

Parameter / Header	Description
transaction_reference *	Your unique reference for this transaction (e.g. W2W-2026-00123).
tx_hash *	On-chain transaction hash (0x...). Required for automatic blockchain verification.
sender_wallet *	Sending wallet address (0x...) that initiated the transfer.
receiver_wallet *	ALSHUMOOKH master wallet address that received the funds.
amount *	Token amount as string or number (e.g. '88.92').
asset *	Token symbol: USDT, USDC, ETH, SIG, M1, or other supported assets.
network *	Blockchain network: ethereum, base, or tron-placeholder.
token_contract *	ERC-20 contract address of the transferred token.
timestamp	ISO 8601 timestamp of the transaction (e.g. 2026-06-29T14:00:00Z).
settlement_type	Optional label. Use 'wallet_to_wallet' for standard transfers.
callback_url	Optional URL to receive webhook status updates from ALSHUMOOKH.
authorization_code	Optional authorization code from your system for audit trail.

* = Required for automatic blockchain verification

3.4 Full Example Request

Settlement Payload — Full Example

```
POST /api/v1/payloads/ingest HTTP/1.1
Host: api.alshumookh-pay.com
X-API-Key: alsh_live_XXXXXXXXXXXXXXXXXXXXX
Idempotency-Key: a1b2c3d4-e5f6-7890-abcd-ef1234567890
Content-Type: application/json

{
  "transaction_reference": "W2W-2026-00123",
  "tx_hash": "0xd4e5f885f36e148e15c9f728304fd803a96b784c7bdd965490f5c0b09fe60058",
  "sender_wallet": "0xAf7DFBcc4C28f0d23cb4ddefD8C40CC0b07bE68D",
  "receiver_wallet": "0xBD682cfD8382a90adFDd6745780D3D7959c4d939",
  "amount": "88.92",
  "asset": "USDT",
  "network": "ethereum",
  "token_contract": "0xdAC17F958D2ee523a2206206994597C13D831ec7",
  "timestamp": "2026-06-29T19:38:00Z",
  "settlement_type": "wallet_to_wallet"
}
```

3.5 Success Response

Success Response — 200 OK

```
HTTP/1.1 200 OK
Content-Type: application/json

{
  "status": "payload_received",
  "payload_id": "uuid-generated-by-server",
  "transaction_reference": "W2W-2026-00123",
  "parsed": true,
  "request_id": "uuid",
  "verification_status": "ALCHEMY_PENDING"
}
```

3.6 Verification Status Values

Parameter / Header	Description
ALCHEMY_PENDING	Payload received. Blockchain verification in progress.
ALCHEMY_VERIFIED	Transaction found on-chain and matches submitted details.
ON_CHAIN_CONFIRMED	Transaction has 6+ confirmations. Fully confirmed.
AWAITING_TX_HASH	No tx_hash provided. Pending manual or deferred verification.
MANUAL_REVIEW	Flagged for manual review by ALSHUMOOKH compliance team.
FAILED	Verification failed. Transaction could not be confirmed on-chain.
RECONCILED	Payment fully reconciled and approved by ALSHUMOOKH operations.

4. M1 Fund Submission Endpoint

The M1 Fund endpoint accepts structured M1-grouped financial data (Model 3 JSON format) from authorized partners. This endpoint handles large-scale fund transfer records with full tokenization metadata and payout structure.

4.1 Endpoint Details

M1 Fund Endpoint Reference

Method: POST

```

URL:      https://api.alshumookh-pay.com/api/v1/payloads/m1-fund
Auth:     X-API-Key (required)
Optional: Idempotency-Key, X-Sender-ID

```

4.2 Required Headers

Parameter / Header	Description
X-API-Key *	Your API key issued by ALSHUMOOKH. Required for all requests.
Idempotency-Key	Unique key per submission. Prevents duplicate processing on retry.
X-Sender-ID	Your organization identifier. Overrides API client name in audit logs.
Content-Type *	Must be: application/json

4.3 Request Body Structure

Parameter / Header	Description
grouped_m1_detail *	Object containing M1 group financial data including total_group_value_eur.
token *	Object with token details: symbol, type (ERC-20), contract_address, network.
payout_structure *	Object specifying receiver_wallet, receiver_entity, iban, bic.
verification	Object with hash_sha256 (SHA-256 of payload) and authorization_code.

4.4 Full Example Request

M1 Fund — Full Example

```

POST /api/v1/payloads/m1-fund HTTP/1.1
Host: api.alshumookh-pay.com
X-API-Key: alsh_live_XXXXXXXXXXXXXXXXXXXXX
Idempotency-Key: m1-2026-0629-001
X-Sender-ID: PARTNER-ORGANIZATION-ID
Content-Type: application/json

{
  "grouped_m1_detail": {
    "group_name": "M1 Settlement Group — June 2026",
    "total_group_value_eur": "1000000000.00",
    "currency": "EUR",
    "settlement_date": "2026-06-29"
  },
  "token": {
    "symbol": "USDT",
    "type": "ERC-20",
    "contract_address": "0xdAC17F958D2ee523a2206206994597C13D831ec7",
    "network": "Ethereum Mainnet"
  },
  "payout_structure": {
    "receiver_wallet": "0xBD682cfD8382a90adfDd6745780D3D7959c4d939",
    "receiver_entity": "Alshumookh Global Banking Finance and Credit",
    "receiver_iban": "AE960260001015754367301",
    "receiver_bic": "EBILAEADXXX"
  },
  "verification": {
    "hash_sha256": "abc123def456...",
    "authorization_code": "SND-ACK-20260629-1400"
  }
}

```

4.5 M1 Fund Success Response

M1 Fund — Success Response

```
HTTP/1.1 200 OK

{
  "status": "RECEIVED",
  "m1_reference": "ALSH-M1-20260629-140000-A1B2C3",
  "fund_id": "uuid-generated-by-server",
  "received_at": "2026-06-29T14:00:00Z",
  "payload_hash": "sha256-of-your-payload",
  "receiver": {
    "entity": "Alshumookh Global Banking Finance and Credit",
    "iban": "AE960260001015754367301",
    "bic": "EBILAEADXXX",
    "wallet": "0xBD682cfD8382a90adfDd6745780D3D7959c4d939",
    "network": "Ethereum Mainnet — ERC-20 USDT"
  },
  "next_steps": "Your M1 Fund file has been received and queued for compliance review."
}
```

5. Error Codes & Troubleshooting

HTTP	Status	Meaning
200	OK	Request accepted and processed successfully.
400	Bad Request	Invalid JSON, missing required fields, or malformed request.
401	Unauthorized	Missing or invalid API key / Bearer token. Verify credentials.
401	Missing Idempotency	Idempotency-Key header is absent. Add a unique UUID.
401	Timestamp Expired	X-Timestamp older than 5 minutes. Use current Unix time.
403	IP Not Allowed	Your IP is not whitelisted for this API client account.
404	Not Found	Endpoint URL or method is incorrect. Verify path and use POST.
429	Rate Limited	Too many requests. Implement exponential backoff and retry.

5.1 Common Error Response Examples

Error & Idempotency Response Examples

```
// Missing API Key — 401
{ "error": "missing_credentials",
  "message": "X-API-Key or OAuth2 Bearer token is required" }

// Invalid API Key — 401
{ "error": "invalid_api_key",
  "message": "API key is invalid or inactive" }

// Missing Idempotency-Key — 400
{ "error": "missing_idempotency_key",
  "message": "Idempotency-Key header is required" }

// Duplicate request (idempotent) — 200
{ "status": "payload_received", "idempotent": true,
  "message": "Duplicate Idempotency-Key — returning original response" }
```

6. Step-by-Step Submission Process

Step 1 — Obtain Your API Key

Contact the ALSHUMOOKH operations team at ceo@alshumookhgroup.ae to request an API client account. Upon approval, your API key will be provisioned and delivered via secure channel.

Step 2 — Prepare Your JSON Payload

Ensure your payload includes all required fields:

- A unique transaction_reference (your internal reference number)
- The blockchain tx_hash of the completed on-chain transfer
- Exact sender_wallet and receiver_wallet addresses (0x...)
- The precise amount, asset symbol (USDT/USDC), and token_contract address
- The correct network: ethereum, base, or tron-placeholder

Step 3 — Generate a Unique Idempotency Key

Generate a UUID for each new request. Store it with your submission record for auditing and safe retries.

Generating Idempotency Key

```
# Python example
import uuid
idempotency_key = str(uuid.uuid4())
# Result: '3fa85f64-5717-4562-b3fc-2c963f66afa6'
```

Step 4 — Submit the Request

cURL Submission Example

```
curl -X POST https://api.alshumookh-pay.com/api/v1/payloads/ingest \
-H 'X-API-Key: your_api_key' \
-H 'Idempotency-Key: 3fa85f64-5717-4562-b3fc-2c963f66afa6' \
-H 'Content-Type: application/json' \
-d '{"transaction_reference": "W2W-001", "tx_hash": "0x...", ...}'
```

Step 5 — Store the Response

Save the payload_id and verification_status from the response. Use the payload_id when following up with ALSHUMOOKH operations.

Step 6 — Await Verification

ALSHUMOOKH will automatically verify your transaction on-chain. If automatic verification cannot be completed, our compliance team will contact you at your registered address.

7. Supported Networks & Master Wallet

Parameter / Header	Description
ethereum	Ethereum Mainnet — ERC-20 tokens (USDT, USDC, M1, SIG)
base	Base Network (Coinbase L2) — ERC-20 tokens

tron-placeholder	TRON Network — TRC-20 USDT. Requires manual compliance review.
-------------------------	--

ALSHUMOOKH Master Receiving Wallet (Ethereum Mainnet):
0xBD682cfD8382a90adfDd6745780D3D7959c4d939

USDT Contract: 0xdAC17F958D2ee523a2206206994597C13D831ec7
USDC Contract: 0xA0b86991c6218b36c1d19D4a2e9Eb0cE3606eB48
IBAN: AE960260001015754367301
BIC/SWIFT: EBILAEADXXX (Emirates NBD)

8. Support & Contact

Parameter / Header	Description
Email	ceo@alshumookhgroup.ae
Platform	https://api.alshumookh-pay.com
Version	1.0 — July 2026 — CONFIDENTIAL

For API key provisioning, technical integration assistance, or compliance inquiries, contact the ALSHUMOOKH operations team at the email above. Please include your organization name and a brief description of your inquiry.