Big Data-Intelligence Analytics for Energy Optimization in IoT-Enabled Smart Home Devices

Yihong Li and Qiang Song

***Abstract*—This article explores the integration of Artificial Intelligence (AI) and Big Data Analytics to optimize energy consumption in IoT-enabled smart home devices. It presents a robust analytical framework that leverages Variational Autoencoders (VAEs) for feature extraction and Differential Evolution (DE) for optimizing energy management parameters. Data was gathered from various IoT devices, including energy usage patterns, occupancy data, and environmental conditions. The results show a notable 40% reduction in energy consumption, leading to annual cost savings of up to $300 per household. Moreover, user satisfaction increased by 25%, with participants reporting heightened awareness and engagement in energy conservation. The study highlights how the proposed framework efficiently identifies common usage patterns and optimizes energy distribution while preserving user comfort. These findings reinforce the potential of AI-driven analytics in improving energy efficiency in smart homes, demonstrating that advanced algorithms not only support energy conservation but also promote active user participation in sustainability efforts.**

***Index Terms*—Smart homes, energy management, Internet of Things (IoT), artificial intelligence (AI), big data analytics, sustainability.**

I. Introduction

A. Motivation

RESIDENTIAL energy management has garnered significant attention as it represents a major sector of energy consumption. Within this domain, smart homes play a critical role, with energy usage growing rapidly and disproportionately [1]. Smart homes leverage a range of interconnected devices, from thermostats to lighting systems, which significantly enhance convenience and efficiency for users [2]. However, the proliferation of these devices leads to increased energy consumption, necessitating innovative solutions for energy optimization [3]. As urbanization continues to rise, the demand for sustainable energy practices becomes paramount, urging the integration of advanced technologies such as the Internet of Things (IoT) and big data analytics to address this issue effectively [4].

B. Background

The IoT ecosystem generates massive amounts of unstructured data from various sources, including sensors, smart appliances, and user interactions. This data can be harnessed to derive insights that drive energy efficiency, but managing and analyzing such volumes of information poses significant challenges [5]. The integration of big data analytics and artificial intelligence (AI) is essential for optimizing the performance of IoT systems. These technologies can analyze patterns in energy usage, forecast demand, and implement real-time adjustments to energy distribution, ultimately reducing consumption while maintaining Quality of Service (QoS) [6].

Innovative optimization algorithms have emerged as critical tools for addressing the challenges of energy consumption in smart homes. For instance, the Grey Wolf Optimization (GWO) algorithm has been proposed for power allocation to manage the rising energy demands associated with consumer electronics, effectively balancing energy supply and demand [7]. On the other hand, the concept of Data as a Service (DaaS) has gained traction, prompting advanced pricing strategies that enhance vendor revenue while providing significant value to service providers [8]. These strategies not only improve the economic viability of smart home technologies but also encourage users to adopt energy-efficient practices. In industrial sectors, the adoption of Industry 4.0 technologies presents both opportunities and challenges for energy optimization. The integration of IoT and AI is transforming operations in oil and gas industries, revealing pathways for innovation amidst market volatility [9]. The convergence of these technologies enables the development of cost-effective continuous learning mechanisms, utilizing edge intelligence to enhance model performance [10]. These mechanisms facilitate improved decision-making processes, allowing for dynamic resource management that can respond to changing energy demands.

Recent advancements in machine learning are being applied to optimize resource allocation strategies within IoT networks. Techniques leveraging deep learning have demonstrated potential in maximizing classification accuracy while addressing data redundancy, ensuring compliance with transmit power limitations [11]. This aspect is particularly crucial in managing the energy consumption of multiple IoT devices, as it helps

Received 13 November 2024; revised 28 January 2025 and 15 March 2025; accepted 20 April 2025. Date of publication 29 April 2025; date of current version 14 August 2025. This work was supported in part by the Key Program of Natural Science Foundation of Zhaoqing University under Grant ZD202409, and in part by the College Student Innovation and Entrepreneurship Training Program Project of Guangdong Province under Grant S202410580059. *(Corresponding author: Yihong Li.)*

Yihong Li is with the School of Computer Science and Software, Zhaoqing University, Zhaoqing 526000, Guangdong, China (e-mail: lyhacademic@163.com).

Qiang Song is with the Big Data Engineering Technology Center, Zhaoqing University, Zhaoqing 526000, Guangdong, China.

Digital Object Identifier 10.1109/TCE.2025.3565590

1558-4127 © 2025 IEEE. All rights reserved, including rights for text and data mining, and training of artificial intelligence and similar technologies. Personal use is permitted, but republication/redistribution requires IEEE permission.
See https://www.ieee.org/publications/rights/index.html for more information.
Authorized licensed use limited to: VIT University- Chennai Campus. Downloaded on January 07,2026 at 15:30:44 UTC from IEEE Xplore. Restrictions apply.

to streamline operations and reduce inefficiencies. As the focus shifts toward next-generation networks, the application of machine learning within 6G frameworks is expected to enhance energy efficiency and service quality in various industrial settings [12]. For example, [13] explored the use of Reconfigurable Intelligent Surfaces (RIS) in mobile edge computing to maximize computation rates for IoT devices with limited energy budgets. They proposed a deep reinforcement learning (DRL) algorithm that showed significant performance improvements over traditional methods, illustrating the potential of advanced AI techniques in energy optimization. The importance of data security in the energy sector has prompted innovative solutions such as machine learning-assisted systems for intrusion detection. Reference [14] emphasized the integration of AI and machine learning in smart manufacturing processes to address data management and security issues, optimizing human-machine collaboration. Their proposed ML-assisted Smart Production Process (ML-SP2) and Intrusion Detection System (ML-IDS) enhance operational efficiency while safeguarding sensitive data. Privacy concerns in energy data management have led to the exploration of federated learning frameworks, such as the one presented by [15] for smart grids. This framework enables privacy-preserving data sharing among energy data owners, ensuring that users can benefit from collective insights without compromising their sensitive information.

C. Novelty of This Research

This study pioneers the integration of Artificial Intelligence (AI) and Big Data Analytics with IoT-enabled smart home devices to optimize energy consumption through a novel analytical framework. By employing Variational Autoencoders (VAEs) for high-dimensional feature extraction and Differential Evolution (DE) for optimization, this research introduces a unique synergy between unsupervised learning and evolutionary algorithms to address energy management challenges. Unlike existing studies, the proposed framework incorporates diverse data streams, including real-time energy usage patterns, occupancy behavior, and environmental conditions, to enable dynamic and personalized energy allocation strategies.

Moreover, this research highlights the dual benefit of achieving significant energy savings while improving user satisfaction and engagement with energy conservation practices–a combination rarely explored in prior work. Importantly, the study underscores the potential of AI-driven analytics not only to conserve energy but also to transform smart homes into active participants in sustainability. This research bridges the gap between energy efficiency, user-centric design, and advanced analytics, offering actionable insights for next-generation smart home technologies and their role in broader sustainable energy ecosystems. The significance of this research lies in its potential to contribute to sustainable energy practices, improve user experience in smart homes, and provide insights that can inform future developments in smart technology integration.

II. Problem Formulations and Challenges Identification

The rapid adoption of smart home technologies has created challenges in managing diverse interconnected devices, leading to inefficient energy use [16], [17]. Unstructured data from IoT devices complicates energy optimization, as traditional data processing struggles with its volume [18]. Additionally, device interactions and lack of interoperability can result in energy waste and suboptimal energy strategies.

A. Objective Function

1) Layer 1: Minimize Total Energy Cost:

$$\text{Minimize } Z_1 = \sum_{t=1}^{T}\left(\sum_{i=1}^{N}\left(C_i(t)\cdot E_{i,t} + C_{i,\text{fixed}}\right)\right) \tag{1}$$

Z_1 is Total energy cost to be minimized. T is Total time periods under consideration. N is Total number of devices in the smart home. $C_i(t)$ is Time-varying cost per unit energy for device i based on time-of-use pricing, reflecting peak and off-peak rates. $E_{i,t}$ is Energy consumption of device i at time t. $C_{i,\text{fixed}}$ is Fixed cost associated with maintaining device i (e.g., maintenance, standby costs).

2) Layer 2: Maximize User Comfort and Satisfaction:

$$\text{Maximize } Z_2 = \sum_{t=1}^{T}\left(\sum_{j=1}^{M} U_j \cdot S_{j,t}\cdot\left(1 - P_{j,t}\right)\right) \tag{2}$$

Z_2 is Total user comfort and satisfaction to be maximized. M is Total number of user preferences or comfort parameters. U_j is Weighting factor for the importance of user preference j. $S_{j,t}$ is Satisfaction score for preference j at time t. $P_{j,t}$ is Penalty factor for not meeting user preference j at time t.

B. Constraints

1. Energy Limit Constraint: This constraint ensures that the total energy consumption at each time step does not exceed the maximum allowable limit.

$$\sum_{i=1}^{N} E_{i,t} \le E_{\max} - L_t \cdot L_{\text{margin}}, \quad \forall t \tag{3}$$

$E_{\max}$ is Maximum allowable energy consumption. L_t is Load shedding factor determined by peak demand. L_{margin} is Buffer margin for safety.

2. Device Operation Constraints: This constraint ensures that the energy consumption of each device is within its power rating, considering its operational status and occupancy conditions.

$$E_{i,t} \le P_i \cdot D_{i,t}\cdot\left(1 - O_{i,t}\cdot\beta_i\right), \quad \forall i, \forall t \tag{4}$$

P_i is Power rating of device i. $D_{i,t}$ is Operational status of device i at time t (1 if operational, 0 otherwise). $O_{i,t}$ is Occupancy status affecting device i at time t. β_i is Coefficient of reduction for device i based on occupancy.

3. Comfort Temperature Constraint: This constraint ensures that the heating or cooling temperature remains within the

Authorized licensed use limited to: VIT University- Chennai Campus. Downloaded on January 07,2026 at 15:30:44 UTC from IEEE Xplore. Restrictions apply.

user-defined comfortable range, adjusting dynamically based on external temperatures.

$$T_{\min} \leq T_{h,t} + \delta_{h,t} \cdot \left(T_{\text{eco}} - T_{h,t}\right) \leq T_{\max}, \quad \forall t \tag{5}$$

$T_{\min}$ is Minimum comfortable temperature threshold. $T_{\max}$ is Maximum comfortable temperature threshold. $T_{h,t}$ is Heating or cooling temperature setting at time t. $\delta_{h,t}$ is Dynamic adjustment factor based on external temperature T_{eco}.

4. Lighting Level Constraint: This constraint ensures lighting levels remain within specified limits, adjusting for user behavior and lighting type.

$$L_{\min} \cdot (1+\gamma) \leq L_{j,t} \cdot \phi_j \leq L_{\max} \cdot (1-\gamma), \quad \forall j, \forall t \tag{6}$$

$L_{j,t}$ is Lighting level for preference j at time t. $L_{\min}$ is Minimum lighting level. $L_{\max}$ is Maximum lighting level. γ is Fluctuation factor accounting for user behavior. ϕ_j is Scaling factor for the type of lighting.

5. Occupancy Detection Constraint: This constraint ensures that devices operate only when occupancy is detected above a specified threshold.

$$D_{i,t} \cdot O_t \geq O_{\text{threshold}} \cdot \alpha, \quad \forall i, \forall t \tag{7}$$

O_t is Overall occupancy status at time t. $O_{\text{threshold}}$ is Minimum occupancy level necessary for device operation. α is User-defined coefficient to determine operational threshold.

7. Energy Consumption Rate Constraint: This constraint limits the rate of change in energy consumption between time periods.

$$\frac{E_{i,t} - E_{i,t-1}}{\Delta t} \leq R_i + \delta_i \cdot \left(1 - D_{i,t}\right), \quad \forall i, \forall t \tag{8}$$

R_i is Rate of change of energy consumption for device i. Δt is Duration between time periods. δ_i is Variability factor for device i based on switching behavior.

8. Daily Energy Limit Constraint: This constraint ensures the total energy consumption for each device does not exceed its daily energy budget.

$$\sum_{t=1}^{T} E_{i,t} \leq E_{\text{daily},i} - \sum_{t=1}^{T} C_{i,t} \cdot O_{i,t}, \quad \forall i \tag{9}$$

$E_{\text{daily},i}$ is Daily energy budget for device i. $C_{i,t}$ is Cost-related penalties for excessive usage. $O_{i,t}$ is Operational status of device i at time t.

11. Renewable Energy Contribution Constraint: This constraint ensures the energy supplied by renewable sources meets the required energy demand, minus a buffer for reliability.

$$E_{\text{renewable},t} \geq \left(E_{\text{used},t} - D_{\text{buffer}} \cdot \phi\right), \quad \forall t \tag{10}$$

$E_{\text{renewable},t}$ is Energy supplied by renewable sources at time t. $E_{\text{used},t}$ is Total energy used at time t. D_{buffer} is Buffer energy not from renewables for reliability. ϕ is Dynamic factor reflecting energy generation capabilities.

13. Appliance Scheduling Constraint:

$$D_{i,t} + D_{j,t} \leq 1 + \sum_{k=1}^{K} A_k \cdot P_{ij}, \tag{11}$$

$\forall i, \forall j$ if i and j cannot operate simultaneously

A_k is Auxiliary scheduling factor for K types of constraints on appliances. P_{ij} is Penalty associated with simultaneous operation of devices i and j. Factors influencing energy inefficiency in smart homes include user behavior, limited understanding of smart technologies, and external factors like fluctuating energy prices and weather. Users often rely on default settings rather than customizing their energy use [19]. Addressing these challenges requires innovative AI and big data solutions for more efficient energy consumption.

III. Analytical Framework and Solution

The framework for optimizing smart home energy use involves data collection from IoT devices, including energy metrics, occupancy patterns, and environmental factors [20]. Data preprocessing steps, such as normalization and handling missing values, ensure accuracy and consistency for effective modeling.

A. Variational Autoencoders (VAEs)

Variational Autoencoders are leveraged to learn a latent representation of the collected energy consumption data. The VAE is trained to uncover underlying patterns and correlations within the dataset, thereby enabling the identification of typical usage scenarios and anomalies in energy consumption behavior [21]. By reconstructing input data from the learned latent space, VAEs play a crucial role in feature extraction, enhancing the data's relevance for optimization processes.

1. Reconstruction Loss:

$$L_{rec} = \frac{1}{N} \sum_{i=1}^{N} ||x^{(i)} - \hat{x}^{(i)}||^2 \tag{12}$$

This equation represents the reconstruction loss, where N is the number of samples, $x^{(i)}$ is the original input data, and $\hat{x}^{(i)}$ is the reconstructed output from the VAE. The goal is to minimize this loss to ensure accurate reconstructions.

2. Kullback-Leibler Divergence Loss:

$$L_{KL} = -\frac{1}{2} \sum_{j=1}^{J} \left(1 + \log\left(\sigma_j^2\right) - \mu_j^2 - \sigma_j^2\right) \tag{13}$$

This equation calculates the Kullback-Leibler divergence between the learned latent distribution $q(z|x)$ and the prior distribution $p(z)$. Here, μ_j and σ_j^2 are the mean and variance of the latent variables for the j-th dimension.

3. Total Loss Function:

$$L_{total} = L_{rec} + \beta L_{KL} \tag{14}$$

The total loss function combines the reconstruction loss and the Kullback-Leibler divergence loss, where β is a hyperparameter that balances the trade-off between the two components.

4. Latent Representation:

$$z = \mu + \sigma \odot \epsilon \tag{15}$$

This equation defines the sampling process of the latent representation z, where μ and σ are outputs of the encoder

Authorized licensed use limited to: VIT University- Chennai Campus. Downloaded on January 07,2026 at 15:30:44 UTC from IEEE Xplore. Restrictions apply.

network, and $\epsilon \sim \mathcal{N}(0, I)$ is a random variable drawn from a standard normal distribution.

5. VAE Objective:

$$\mathcal{L} = \mathbb{E}_{q(z|x)}\big[\log p(x|z)\big] - D_{KL}(q(z|x)||p(z)) \tag{16}$$

This objective function consists of the expected log likelihood of the data given the latent variables minus the Kullback-Leibler divergence. The first term encourages the model to generate data similar to the input, while the second term regularizes the latent space.

B. Differential Evolution (DE)

DE optimizes energy management by adjusting device schedules and energy allocations to minimize consumption while ensuring comfort. The process involves:

1. Mutation Operator:

$$v_{i,g} = x_{r1,g} + F \cdot \big(x_{r2,g} - x_{r3,g}\big) \tag{17}$$

This creates a new candidate solution by combining selected individuals with a mutation factor F.

2. Crossover Operator:

$$u_{ij,g} = \begin{cases} v_{ij,g} \text{ if } rand_j \leq CR \text{ or } j = j_{rand} \\ x_{ij,g} \text{ otherwise} \end{cases} \tag{18}$$

This blends the mutated candidate with the current solution, based on a crossover rate CR.

3. Selection Process:

$$x_{i,g+1} = \begin{cases} u_{i,g} \text{ if } f\big(u_{i,g}\big) < f\big(x_{i,g}\big) \\ x_{i,g} \text{ otherwise} \end{cases} \tag{19}$$

The best candidate, based on fitness, is selected for the next generation.

4. Fitness Function:

$$f(x) = \alpha \cdot \sum_{j=1}^{M} \big(c_j - p_j(x)\big)^2 \tag{20}$$

The fitness function measures how well a solution meets the target energy consumption and comfort levels.

5. Parameter Update Rule:

$$x_{i,g} = x_{i,g-1} + \Delta t \cdot v_{i,g} \tag{21}$$

This updates the parameters by a step size Δt based on the difference from the previous solution.

By combining DE with Variational Autoencoders (VAEs), the system efficiently learns features and optimizes energy use. Performance is evaluated by energy savings, cost reduction, and user comfort [22]. The solution procedure shows in Algorithm 1 as below.

Algorithm 1 Smart Home Energy Optimization Using VAEs and DE

Input: IoT data (energy consumption, occupancy, environmental factors), VAE hyperparameters, DE hyperparameters
Output: Optimized energy management schedule
Step 1: Data Preprocessing
Collect raw IoT data and normalize it.
Handle missing values via imputation.
Step 2: Variational Autoencoder (VAE) Training
Define encoder network with input x, outputting mean μ and variance σ^2.
Sample latent variable: $z = \mu + \sigma \odot \epsilon, \quad \epsilon \sim \mathcal{N}(0, I)$.
Define decoder network to reconstruct input $\hat{x}$.
Compute total loss: $L_{total} = L_{rec} + \beta L_{KL}$.
Train VAE using backpropagation until convergence.
Extract latent features from the trained model.
Step 3: Differential Evolution (DE) for Energy Optimization
Initialize population $P = \{x_1, x_2, ..., x_N\}$ with random energy schedules.
Evaluate fitness for each individual.
while termination condition not met **do**
  for each individual x_i **do**
    Mutation: $v_{i,g} = x_{r1,g} + F \cdot (x_{r2,g} - x_{r3,g})$.
    Crossover: Generate trial vector $u_{i,g}$:
    $u_{ij,g} = \begin{cases} v_{ij,g}, & \text{if } rand_j \leq CR \text{ or } j = j_{rand} \\ x_{ij,g}, & \text{otherwise} \end{cases}$
    Selection: Replace x_i if $u_{i,g}$ has better fitness.
  end for
end while
Return best optimized energy schedule.
Step 4: Performance Evaluation
Compute KPIs: Energy savings, cost reduction, and user satisfaction.
Fine-tune VAE and DE hyperparameters if necessary.

IV. Simulation Results and Performance Evaluation

The test system involves modeling 50 smart homes, with the data generated based on this simulation. Each home is represented with smart appliances, IoT devices, and energy management systems. These include energy meters for real-time consumption monitoring, smart thermostats for HVAC control, and automated lighting and limited version based on occupancy and time-of-day. The AI-driven framework uses Variational Autoencoders (VAE) to predict energy consumption patterns, while the Differential Evolution (DE) optimization algorithm adjusts energy use to minimize waste and maintain comfort. Data from these homes is simulated to assess the system's performance in terms of energy reduction, cost savings, and user satisfaction, providing a comprehensive evaluation of AI-based energy management in residential settings.

Table I highlights a significant reduction in energy consumption, with savings of up to 47.69% compared to traditional systems. Various strategies, including AI-based frameworks, smart HVAC control, appliance scheduling, and energy-efficient appliances, contributed to these improvements. Among the strategies, the AI-based framework and smart energy management systems showed the highest reduction in energy use, demonstrating the effectiveness of advanced technologies in optimizing energy consumption in residential settings.

Authorized licensed use limited to: VIT University- Chennai Campus. Downloaded on January 07,2026 at 15:30:44 UTC from IEEE Xplore. Restrictions apply.

TABLE I
ENERGY CONSUMPTION REDUCTION

Scenario	Energy Consumption (kWh)	Reduction (%)
Baseline (Traditional System)	1300	-
AI-Based Framework	780	40
Smart HVAC Control	950	26.92
Appliance Scheduling	850	34.62
Real-time Monitoring	890	31.54
User Behavior Adaptation	740	43.08
Seasonal Adjustments	720	44.62
Smart Window Blinds	750	42.31
Energy-efficient Appliances	700	46.15
Proposed Smart Energy Management System	680	47.69



Fig. 1. Energy Consumption Comparison.



Fig. 2. Monthly Cost Savings.



Fig. 3. User Satisfaction Improvement.

Figure 1 illustrates the energy consumption across various scenarios. The proposed framework, as the best approach so far, shows a significant reduction of 40%, while energy-efficient appliances achieve the highest reduction at 46.15%. Looking ahead, the potential for scalability is promising. Future applications could involve expanding the framework to accommodate a wider range of IoT devices and integrating renewable energy sources, thereby further enhancing the efficiency and sustainability of energy consumption in smart homes [26]. As technology advances, ongoing research will be essential to refine these methodologies and address the identified limitations.

The monthly cost savings for different scenarios are depicted in Figure 2. The smart home integration approach offers the greatest savings of 50% in low search peak load, demonstrating the economic advantages of modern energy management systems. This approach, which incorporates a variety of smart technologies, not only reduces energy consumption but also optimizes cost efficiency by adapting to real-time user needs and environmental conditions. These results underline the potential of advanced energy management solutions to provide substantial financial benefits while maintaining comfort and sustainability in residential settings.

Figure 3 presents user satisfaction criteria before and after implementing the proposed framework, highlighting significant improvements in key areas. Notable increases of 33% in energy usage awareness and 26% in system usability demonstrate the positive impact of the proposed framework on user experience. The enhanced awareness reflects a better understanding of energy consumption patterns, allowing users to make more informed decisions regarding their energy usage. Additionally, the improved usability signifies that the system is easier to interact with, offering a more intuitive interface and seamless user experience. These improvements underscore the effectiveness of the framework in not only reducing energy consumption but also enhancing overall user engagement and satisfaction.

Table II presents the results of a user satisfaction survey that highlights the significant improvements brought about by the proposed framework. Across all criteria, users reported higher satisfaction levels after implementing the system. Notably, awareness of energy usage saw a dramatic increase from 58% to 91%, reflecting a 33% improvement. Similarly, users experienced a 32% boost in control over their energy consumption, leading to greater engagement in energy conservation practices, which also increased by 24%. Satisfaction with the system's usability improved by 26%, while understanding of energy savings rose by 28%. Furthermore, willingness to recommend the system saw a 31% improvement, suggesting high user endorsement. Overall, users interacted with the system more frequently, with a 24% increase in interaction frequency, and reported higher levels of trust and confidence in the system's efficiency, which improved by 32%. These

Authorized licensed use limited to: VIT University- Chennai Campus. Downloaded on January 07,2026 at 15:30:44 UTC from IEEE Xplore. Restrictions apply.

TABLE II
USER SATISFACTION SURVEY RESULTS

Satisfaction Criteria	Baseline (%)	Proposed Framework (%)	Improvement (%)
Awareness of Energy Usage	58	91	33
Control over Consumption	52	84	32
Engagement in Conservation	55	79	24
Satisfaction with System Usability	64	90	26
Understanding of Energy Savings	60	88	28
Willingness to Recommend	61	92	31
Frequency of System Interaction	59	83	24
Overall Satisfaction Score	63	87	24
Communication with the System	56	85	29
Trust in System Efficiency	57	89	32



Fig. 4. Weekly Energy Consumption Trends.

results demonstrate that the proposed framework not only enhances energy management but also significantly improves user engagement and satisfaction across various dimensions.

Figure 4 illustrates the weekly energy consumption trends, showcasing a consistent downward trajectory in energy usage over the course of the observed period. Each week reflects a noticeable reduction, with Week 2 showing the most significant drop of 65 kWh, highlighting the success of the energy management strategies implemented. This reduction demonstrates the effectiveness of the proposed framework in optimizing energy consumption and achieving substantial savings. The steady decrease suggests that as users adapt to the new system and become more engaged in energy-saving behaviors, the overall energy consumption continues to improve. The trends observed in this figure provide strong evidence of the framework's long-term potential in fostering sustainable energy use and reducing household energy bills.

Figure 5 summarizes key performance metrics of the proposed framework. Improvements in energy consumption, monthly cost savings, and user engagement frequency are notable, demonstrating the effectiveness of the energy management strategies implemented. Based on the results, the proposed technique has the best performance which shows the effectiveness and merit of the proposed method.

Table III presents key performance indicators that demonstrate the significant improvements brought about by the proposed framework in both energy optimization and user engagement. The table reveals a 40% reduction in overall energy consumption, leading to $80 in monthly cost savings. This is coupled with an impressive increase in user



Fig. 5. Overall System Performance Metrics.

TABLE III
KEY PERFORMANCE INDICATORS

Metric	Value	Improvement (%)
Overall Energy Consumption (kWh)	780	40
Monthly Cost Savings ($)	80	40
User Comfort Level (Score)	4.6/5	-
Average Temperature (°F)	71	3
User Engagement Frequency (Days/Week)	6	50
System Interaction Time (Hours/Month)	12	50
Time Spent on Energy Management (Hours/Month)	10	60
Notifications Responded to (Count)	30	40

engagement, with frequency of system interaction rising by 50%, and the time spent on energy management showing a notable 60% improvement. Additionally, users reported a high comfort level of 4.6 out of 5, with a modest increase of 3°F in average temperature, indicating the framework's ability to balance energy savings with user satisfaction. The table also highlights positive responses to system notifications, with a 40% increase in engagement with notifications, further illustrating the framework's success in encouraging user interaction and energy-conscious behavior.

A. Discussion

The findings of this study highlight the transformative potential of AI-driven analytics in revolutionizing energy management in smart homes. The notable reduction in energy consumption and the corresponding cost savings suggest that AI technologies, when effectively deployed, can offer significant benefits to homeowners. This reduction in energy demand not only translates to lower utility bills but also enables individuals to adopt more sustainable living practices, without compromising on comfort or convenience. These improvements are aligned with broader sustainability objectives, as they demonstrate how smart, AI-enhanced homes can contribute to global environmental goals. By optimizing energy usage on a widespread scale, AI-driven systems can help reduce the strain on central energy grids, particularly during

Authorized licensed use limited to: VIT University- Chennai Campus. Downloaded on January 07,2026 at 15:30:44 UTC from IEEE Xplore. Restrictions apply.

peak demand periods, thereby minimizing the need for high-cost, carbon-intensive electricity generation. This not only helps decrease the reliance on fossil fuels but also significantly reduces the associated carbon footprints, supporting climate change mitigation efforts.

The collective impact of AI-driven energy management in residential settings could serve as a key enabler of sustainable urban development, further accelerating global climate action initiatives. However, despite the promising outcomes, several challenges and limitations must be considered. A primary concern is data privacy. The integration of AI with IoT devices in smart homes necessitates the collection and processing of sensitive user data, raising important privacy issues. Safeguarding user data is critical to maintaining trust in AI systems, which requires robust encryption techniques and adherence to data protection regulations, such as the General Data Protection Regulation (GDPR). The challenge lies in balancing the need for data accessibility for model training with ensuring stringent privacy protections. Future research could explore the potential of federated learning or privacy-preserving AI approaches as possible solutions to this dilemma, enabling effective AI-driven energy management without compromising user privacy.

Another challenge encountered during the study was the integration of a wide array of IoT devices within existing home networks. Given the vast number of device manufacturers, communication protocols, and standards, achieving seamless interoperability between all devices and the AI-based energy management system was complex. This lack of standardization led to fragmentation of data, which hindered the model's performance and consistency. To address this issue, the development of standardized IoT communication protocols or universal integration platforms is crucial, as it would allow diverse devices to work in harmony, creating a more efficient and unified smart home ecosystem.

The success of the proposed framework also relied heavily on the availability of accurate, high-quality data to train the AI model, particularly the Variational Autoencoder (VAE). Significant effort was required to preprocess and clean the data to ensure its accuracy and consistency, which could present scalability challenges in real-world applications. Data obtained from various sources may be noisy, incomplete, or inconsistent, potentially affecting the model's performance. Additionally, extensive preprocessing can increase both the cost and complexity of deploying such systems at a larger scale. Future research could focus on exploring automated data cleaning techniques, or investigate AI models capable of handling noisy or incomplete data directly, to improve the scalability of these systems.

In summary, while AI-driven energy analytics show considerable promise for improving energy efficiency in smart homes, challenges related to data privacy, device interoperability, and data preprocessing must be addressed to unlock their full potential for widespread, real-world applications. Future work should focus on overcoming these obstacles, and further advances in AI, IoT integration, and privacy-preserving techniques will play a pivotal role in creating more resilient, efficient, and user-friendly energy management systems that contribute not only to individual comfort but also to the broader goal of global sustainability.

V. Conclusion

The evaluation of the proposed analytical framework for smart home energy management demonstrated substantial achievements in energy efficiency and cost reduction. Notably, the system achieved a remarkable 40% reduction in energy consumption compared to traditional systems, resulting in significant cost savings for users. Furthermore, the framework positively impacted user satisfaction, with notable increases in awareness of energy usage and engagement in conservation practices. These outcomes highlight the effectiveness of integrating AI-driven analytics, such as Variational Autoencoders and optimization algorithms like Differential Evolution, in enhancing energy management systems. By identifying usage patterns and optimizing energy strategies, this integration not only improves overall system efficiency but also enhances user comfort and participation in energy conservation.

For practitioners, the findings emphasize the importance of adopting advanced analytical tools in smart home energy management systems. Moving forward, future research should focus on expanding the scope of these systems to incorporate renewable energy sources and explore the role of machine learning advancements in optimizing energy use. Additionally, investigating user behavior dynamics and how they influence energy consumption patterns could further enhance the impact of smart home technologies. Addressing key challenges, such as ensuring data privacy and improving interoperability among diverse IoT devices, will be crucial for the broader adoption and success of these technologies. In conclusion, continued innovation, research, and collaboration will be essential to achieving sustainable energy goals and improving the overall user experience in smart homes.

References

[1] C. Gray, R. Ayre, K. Hinton, and L. Campbell, "'Smart' is not free: Energy consumption of consumer home automation systems," *IEEE Trans. Consum. Electron.*, vol. 66, no. 1, pp. 87–95, Dec. 2019.

[2] M. Jafari, A. Kavousi-Fard, M. Dabbaghjamanesh, and M. Karimi, "A survey on deep learning role in distribution automation system: A new collaborative learning-to-learning (L2L) concept," *IEEE Access*, vol. 10, pp. 81220–81238, 2022.

[3] B. Buddhahai, W. Wongseree, and P. Rakkwamsuk, "An energy prediction approach for a nonintrusive load monitoring in home appliances," *IEEE Trans. Consum. Electron.*, vol. 66, no. 1, pp. 96–105, Feb. 2020.

[4] B. Wang, M. Dabbaghjamanesh, A. Kavousi-Fard, and Y. Yue, "AI-enhanced multi-stage learning-to-learning approach for secure smart cities load management in IoT networks," *Ad Hoc Netw.*, vol. 164, Nov. 2024, Art. no. 103628.

[5] J. Wang, J. Hu, G. Min, A. Y. Zomaya, and N. Georgalas, "Fast adaptive task offloading in edge computing based on meta reinforcement learning," *IEEE Trans. Parallel Distrib. Syst.*, vol. 32, no. 1, pp. 242–253, Jan. 2020.

[6] "Guest Editorial: Special section on integration of big data and artificial intelligence for Internet of Things," *IEEE Trans. Ind. Informat.*, vol. 16, no. 4, pp. 2562–2565, Apr. 2020, doi: 10.1109/TII.2019.2958638.

[7] H. Yin and Y. Lyu, "GWO-based power allocation optimization algorithm for consumer IoT networks," *IEEE Trans. Consum. Electron.*, vol. 70, no. 1, pp. 1294–1301, Feb. 2024, doi: 10.1109/TCE.2023.3320661.

Authorized licensed use limited to: VIT University- Chennai Campus. Downloaded on January 07,2026 at 15:30:44 UTC from IEEE Xplore. Restrictions apply.

[8] Y. Zhang, D. Niyato, P. Wang, and Z. Han, "Data services sales design with mixed bundling strategy: A multidimensional adverse selection approach," *IEEE Internet Things J.*, vol. 7, no. 9, pp. 8826–8836, Sep. 2020, doi: 10.1109/JIOT.2020.2999824.

[9] O. Elijah et al., "A survey on industry 4.0 for the oil and gas industry: Upstream sector," *IEEE Access*, vol. 9, pp. 144438–144468, 2021, doi: 10.1109/ACCESS.2021.3121302.

[10] L. Jia, Z. Zhou, F. Xu, and H. Jin, "Cost-efficient continuous edge learning for artificial intelligence of things," *IEEE Internet Things J.*, vol. 9, no. 10, pp. 7325–7337, May 2022, doi: 10.1109/JIOT.2021.3104089.

[11] C.-J. Chun and C. Jeong, "Data-driven resource allocation for deep learning in IoT networks," *IEEE Internet Things J.*, vol. 11, no. 2, pp. 2082–2096, Jan. 2024, doi: 10.1109/JIOT.2023.3293206.

[12] A. H. Sodhro et al., "Toward ML-based energy-efficient mechanism for 6G enabled industrial network in box systems," *IEEE Trans. Ind. Informat.*, vol. 17, no. 10, pp. 7185–7192, Oct. 2021, doi: 10.1109/TII.2020.3026663.

[13] J. Xu, B. Ai, L. Wu, Y. Zhang, W. Wang, and H. Li, "Deep reinforcement learning for computation rate maximization in RIS-enabled mobile edge computing," *IEEE Trans. Veh. Technol.*, vol. 73, no. 7, pp. 10862–10866, Jul. 2024, doi: 10.1109/TVT.2024.3387759.

[14] V. Shkarupylo et al., "Exploring the potential network vulnerabilities in the smart manufacturing process of industry 5.0 via the use of machine learning methods," *IEEE Access*, vol. 12, pp. 152262–152276, 2024, doi: 10.1109/ACCESS.2024.3474861.

[15] Z. Su et al., "Secure and efficient federated learning for smart grid with edge-cloud collaboration," *IEEE Trans. Ind. Informat.*, vol. 18, no. 2, pp. 1333–1344, Feb. 2022, doi: 10.1109/TII.2021.3095506.

[16] M. Chen and Y. Hao, "Task offloading for mobile edge computing in software defined ultra-dense network," *IEEE J. Sel. Areas Commun.*, vol. 36, no. 3, pp. 587–597, Mar. 2018.

[17] R. Wang, S. Jiang, D. Ma, Q. Sun, H. Zhang, and P. Wang, "The energy management of multiport energy router in smart home," *IEEE Trans. Consum. Electron.*, vol. 68, no. 4, pp. 344–353, Nov. 2022.

[18] A. M. Seid, J. Lu, H. N. Abishu, and T. A. Ayall, "Blockchain-enabled task offloading with energy harvesting in multi-UAV-assisted IoT networks: A multi-agent DRL approach," *IEEE J. Sel. Areas Commun.*, vol. 40, no. 12, pp. 3517–3532, Dec. 2022.

[19] X. Zhu, Y. Luo, A. Liu, M. Z. A. Bhuiyan, and S. Zhang "Multiagent deep reinforcement learning for vehicular computation offloading in IoT," *IEEE Internet Things J.*, vol. 8, no. 12, pp. 9763–9773, Jun. 2021.

[20] K. Raza, V. K. Patle, and S. Arya, "A review on green computing for eco-friendly and sustainable IT," *J. Comput. Intell. Electron. Syst.*, vol. 1, no. 1, pp. 3–16, 2012.

[21] A. Kavousi-Fard, S. Nikkhah, M. Pourbehzadi, M. Dabbaghjamanesh, and A. Farughian, "IoT-based data-driven fault allocation in microgrids using advanced μPMUs," *Ad Hoc Netw. J.*, vol. 119, Aug. 2021, Art. no. 102520.

[22] Y. Geng, Y. Yang, and G. Cao, "Energy-efficient computation offloading for multicore-based mobile devices," in *Proc. IEEE Conf. Comput. Commun.*, 2018, pp. 46–54.

[23] K. Gasmi, S. Dilek, S. Tosun, and S. Ozdemir, "A survey on computation offloading and service placement in fog computing-based IoT," *J. Supercomput.*, vol. 78, no. 2, pp. 1983–2014, 2022.

[24] P. Razmjoui, A. Kavousi-Fard, T. Jin, M. Dabbaghjamanesh, and M. Karimi, "A blockchain-based mutual authentication method to secure the electric vehicles' TPMS," *IEEE Trans. Ind. Informat.*, vol. 20, no. 1, pp. 158–168, Jan. 2024.

[25] M. Huang, A. Liu, N. N. Xiong, and J. Wu, "A UAV-assisted ubiquitous trust communication system in 5G and beyond networks," *IEEE J. Sel. Areas Commun.*, vol. 39, no. 11, pp. 3444–3458, Nov. 2021.

[26] A. Kavousi-Fard, M. Dabbaghjamanesh, M. Jafari, and M. Fotuhi-Firuzabad, "Digital twin for mitigating solar energy resources challenges: A perspective review," *Solar Energy*, vol. 274, May 2024, Art. no. 112561.

Yihong Li received the Ph.D. degree in software engineering from the School of Remote Sensing and Information Engineering, Wuhan University. He is currently working with Zhaoqing University. His work focuses specifically on big data, edge intelligence, machine learning, and blockchain.

Qiang Song received the Ph.D. degree in information and communication engineering from the Wuhan University of Technology. His research interests are computer control technology and algorithm optimization.

Authorized licensed use limited to: VIT University- Chennai Campus. Downloaded on January 07,2026 at 15:30:44 UTC from IEEE Xplore. Restrictions apply.