Text Generation

Copy page

Generating text with Groq's Chat Completions API enables you to have natural, conversational interactions with Groq's large language models. It processes a series of messages and generates human-like responses that can be used for various applications including conversational agents, content generation, task automation, and generating structured data outputs like JSON for your applications.

Chat Completions

Chat completions allow your applications to have dynamic interactions with Groq's models. You can send messages that include user inputs and system instructions, and receive responses that match the conversational context.

Chat models can handle both multi-turn discussions (conversations with multiple back-and-forth exchanges) and single-turn tasks where you need just one response.

For details about all available parameters, visit the API reference page.

Getting Started with Groq SDK

To start using Groq's Chat Completions API, you'll need to install the Groq SDK and set up your API key.

Python JavaScript

shell

```
pip install groq
```

Performing a Basic Chat Completion

The simplest way to use the Chat Completions API is to send a list of messages and receive a single response. Messages are provided in chronological order, with each message containing a role ("system", "user", or "assistant") and content.

Docs

GETTING STARTED

Overview

Quickstart

Models

OpenAI Compatibility

Responses API

Rate Limits

Templates

API Reference

CORE FEATURES

Text Generation

Speech to Text

Text to Speech

Orpheus

OCR and Image Recognition

Reasoning

Content Moderation

Structured Outputs

Prompt Caching

TOOLS & INTEGRATIONS

Tool Use

Overview

Groq Built-In Tools

Web Search

Visit Website

```
22        ],
```

Docs
Browser Automation
Code Execution
GETTING STARTED
Wolfram Alpha
Overview
Browser Search (GPT OSS Models)
Quickstart
Remote Tools and MCP
Models
Connectors
OpenAI Compatibility
Local Tool Calling
Responses API
Integrations Catalog
Rate Limits
Coding with Groq
Templates
Factory Droid
API Reference
OpenCode
CORE FEATURES
Kilo Code
Text Generation
Roo Code
Speech to Text
Cline
Text to Speech
COMPOUND (AGENTIC AI)
Orpheus
Overview
OCR and Image Recognition
Built-In Tools
Reasoning
Systems
Content Moderation
Use Cases
Structured Outputs
GUIDES
Prompt Caching
Prompting Guide
TOOLS & INTEGRATIONS
Basics
Tool Use
Patterns
Overview
Model Migration
Groq Built-In Tools
Assistant Message Prefilling
Web Search
SERVICE TIERS
Visit Website

```
    {
        "role": "user",
        "content": "Explain the importance of fast language models",
```

Docs
GETTING STARTED
Overview
Quickstart
ADVANCED
Models
OpenAI Compatibility
PRODUCTION READINESS
Production Checklist
Integrations Catalog
Rate Limits
Optimizing Latency
Coding with Groq
Templates
Security Onboarding
API Reference
Prometheus Metrics
CORE FEATURES
ACCOUNT AND CONSOLE
Text Generation
Spend Limits
Speech to Text
Projects
Text to Speech
Model Permissions
COMPOUND (AGENTIC AI)
Billing FAQs
Overview
OCR and Image Recognition
Your Data
Reasoning
DEVELOPER RESOURCES
Systems
Content Moderation
SDK Libraries
Use Cases
Structured Outputs
Groq Badge
GUIDES
Prompt Caching
Developer Community
Prompting Guide
TOOLS & INTEGRATIONS
OpenBench
Tool Use
Error Codes
Changelog
Groq Built-In Tools
LEGAL
Policies & Notices
SERVICE TIERS
Service Tiers
Performance Tier
Flex Processing
Batch Processing
Quickstart
LoRA Inference
OpenAI Compatibility
Local Tool Calling
Responses API
Integrations Catalog
Optimizing Latency
Coding with Groq
Security Onboarding
Factory Droid
Prometheus Metrics
OpenCode
Kilo Code
Text Generation
Spend Limits
Roo Code
Speech to Text
Projects
Cline
Text to Speech
Model Permissions
Orpheus
Billing FAQs
Overview
OCR and Image Recognition
Your Data
Built-In Tools
Reasoning
Systems
Content Moderation
SDK Libraries
Use Cases
Structured Outputs
Groq Badge
Prompt Caching
Developer Community
Prompting Guide
OpenBench
Basics
Tool Use
Error Codes
Patterns
Overview
Changelog
Model Migration
Groq Built-In Tools
Assistant Message Prefilling
Web Search
Visit Website

```
# markers like "[end]".
    stop=None,
```

Docs
GETTING STARTED
Overview
Quickstart
ADVANCED
Models
OpenAI Compatibility
PRODUCTION READINESS
Production Checklist
Integrations Catalog
Rate Limits
Optimizing Latency
Coding with Groq
Templates
Security Onboarding
API Reference
Prometheus Metrics
CORE FEATURES
ACCOUNT AND CONSOLE
Text Generation
Spend Limits
Speech to Text
Projects
Text to Speech
Model Permissions
COMPOUND (AGENTIC AI)
Billing FAQs
Overview
OCR and Image Recognition
Your Data
Reasoning
DEVELOPER RESOURCES
Systems
Content Moderation
SDK Libraries
Use Cases
Structured Outputs
Groq Badge
GUIDES
Prompt Caching
Developer Community
Prompting Guide
TOOLS & INTEGRATIONS
OpenBench
Tool Use
Error Codes
Changelog
LEGAL
Policies & Notices
SERVICE TIERS
Service Tiers
Performance Tier
Flex Processing
Batch Processing
Quickstart
LoRA Inference
OpenAI Compatibility
Local Tool Calling
Responses API
Integrations Catalog
Optimizing Latency
Coding with Groq
Security Onboarding
Factory Droid
Prometheus Metrics
OpenCode
Kilo Code
Text Generation
Spend Limits
Roo Code
Speech to Text
Projects
Cline
Text to Speech
Model Permissions
Orpheus
Billing FAQs
Overview
OCR and Image Recognition
Your Data
Built-In Tools
Reasoning
Systems
Content Moderation
SDK Libraries
Use Cases
Structured Outputs
Groq Badge
Prompt Caching
Developer Community
Prompting Guide
OpenBench
Tool Use
Error Codes
Changelog
Model Migration
Assistant Message Prefilling
Policies & Notices
Visit Website
Browser Automation
Code Execution
Wolfram Alpha
Browser Search (GPT OSS Models)
Remote Tools and MCP
Connectors
Responses API
Factory Droid
OpenCode
Kilo Code
Roo Code
Cline
Orpheus
Built-In Tools
Systems
Use Cases
Groq Badge
Basics
Patterns
Overview
Model Migration
Groq Built-In Tools
Web Search