Solana

Sign a message

Open in Claude

Environment

React

When using Privy's server-side SDKs to sign messages, you can use the authorization context to automatically sign requests. Learn more about **signing on the server**.

Use the `signMessage` method exported from the `useSignMessage` hook to sign a message with a Solana wallet.

```
signMessage: ({
  message,
  options
}: {
  message: Uint8Array;
  wallet: ConnectedStandardSolanaWallet;
  options?: {
    uiOptions?: SignMessageModalUIOptions;
  };
}) =>
  Promise<{
    signature: Uint8Array;
  }>;
```

Usage

```
import {useWallets, useSignMessage} from '@privy-io/react-auth/solana';
import bs58 from 'bs58';

const {wallets} = useWallets();
const {signMessage} = useSignMessage();

const selectedWallet = wallets[0];

const message = 'Hello world';
const signatureUint8Array = (
  await signMessage({
    message: new TextEncoder().encode(message),
    wallet: selectedWallet,
    options: {
      uiOptions: {
        title: 'Sign this message'
      }
    }
  })
).signature;
const signature = bs58.encode(signatureUint8Array);
```

Parameters

message `Uint8Array` `required`

Message to be signed as a Uint8Array.

---

wallet `string`

The Solana wallet to use for signing the message.

---

options `{uiOptions?: SignMessageModalUIOptions}`

Additional options for signing the message.

› Show uiOptions

Response

signature `Uint8Array`

The signature produced by the wallet.

signedMessage `Uint8Array`

The original message that was signed.

Was this page helpful? Yes No