Solana

# Sign a transaction

Open in Claude

Environment

React

When using Privy's server-side SDKs to sign transactions, you can use the authorization context to automatically sign requests. Learn more about **signing on the server**.

Use the `signTransaction` method exported from the `useSignTransaction` hook to sign a transaction with a Solana wallet.

```
signTransaction: (input: {
  transaction: SupportedSolanaTransaction;
  wallet: ConnectedStandardSolanaWallet;
  options?: SolanaSignTransactionOptions & {uiOptions?: SendTransactionModalUIOpt
}) =>
  Promise<{
    signedTransaction: Uint8Array;
  }>;
```

## Usage

```
import {useSignTransaction, useWallets} from '@privy-io/react-auth/
import {pipe, createSolanaRpc, getTransactionEncoder, createTransactionMessage} fr

// Inside your component
const {signTransaction} = useSignTransaction();
const {wallets} = useWallets();

const selectedWallet = wallets[0];

// Configure your connection to point to the correct Solana network
const {getLatestBlockhash} = createSolanaRpc('https://api.mainnet-beta.solana.com

// Get the latest blockhash
const {value} = await getLatestBlockhash().send();

// Create your transaction (either legacy Transaction or VersionedTransaction)
const transaction = pipe(
  createTransactionMessage({version: 0}),
  // Set the message fee payer...
  // Set recent blockhash...
  // Add your instructions to the transaction...
  // Finally encode the transaction
  (tx) => new Uint8Array(getTransactionEncoder().encode(tx))
);

// Sign the transaction
const signedTransaction = await signTransaction({
  transaction: transaction,
  wallet: selectedWallet
});

console.log('Transaction signed successfully');
```

## Parameters

**transaction** `Uint8Array` `required`

The encoded transaction to be signed.



**wallet** `ConnectedStandardSolanaWallet` `required`

The Solana wallet to use for signing the transaction.

**chain** `SolanaChain`

Type of all Solana chains supported by Privy.

**options** `SolanaSignTransactionOptions & {uiOptions?: SendTransactionModalUIOptions}`

Additional options for signing the transaction.

Show uiOptions

## Response

**signedTransaction** `Uint8Array`

The signed transaction that can be sent to the network.

Was this page helpful? Yes No



Powered by mintlify