

Visualization of large multivariate datasets with the `tabplot` package

Martijn Tennekes and Edwin de Jonge

July 4, 2012

(A later version may be available on [CRAN](#))

Abstract

The tableplot is a powerful visualization method to explore and analyse large multivariate datasets. In this vignette, the implementation of tableplots in R is described.

1 Introduction

The tableplot is a visualization method that is used to explore and analyse large datasets. Tableplots are used to explore the relationships between the variables, to discover strange data patterns, and to check the occurrence and selectivity of missing values.

A tableplot applied to the diamonds dataset of the `ggplot2` package (where some missing values were added) is illustrated in Figure 1. Each column represents a variable. The whole data set is sorted according to one column (in this case, `carat`), and then grouped into row bins. Algorithm 1 in Appendix A describes the creation of a tableplot into detail.

Tableplots are aimed to visualize multivariate datasets with several variables (up to a dozen) and a large number of records, say at least one thousand. Tableplots can also be generated for datasets with less records, but they may be less useful. The maximum number of rows that can be visualized with the `tabplot` package depends on the R's memory, or, when using the `ff` package, on the limitations of that package.

A graphical user interface for generating tableplots is implemented in the package `tabplotGTK`.

2 Getting started with the `tableplot` function

The diamonds dataset is very suitable to demonstrate the `tabplot` package. To illustrate the visualization of missing values, we add several NA's.

```
require(ggplot2)
data(diamonds)
## add some NA's
is.na(diamonds$price) <- diamonds$cut == "Ideal"
is.na(diamonds$cut) <- (runif(nrow(diamonds))) > 0.8)
```

A tableplot is simply created by the function `tableplot`:

```
tableplot(diamonds)
```




Figure 1: Tableplot of the diamonds dataset

The result is depicted in Figure 1. By default, all variables of the dataset are depicted. With the argument `select`, we can specify which variables are plotted. The dataset is by default sorted according to the values of the first column. With the argument `sortCol`, we can specify on which column(s) the data is sorted.

The resulting tableplot in Figure 2 consists of five columns, where the data is sorted on price. Notice that the missing values that we have added are placed at the bottom and (by default) shown in a bright red color.

Setting an appropriate number of row bins (by the argument `nBins`) is important, like in a histogram. A good number of row bins is a trade of between good polished but meaningless data, and detailed, but noisy data.

```
tableplot(diamonds, select = c(carat, price, cut, color,
                               clarity),
          sortCol = price)
```




Figure 2: Tableplot of the diamonds dataset: sorted by price

In practice, we found that the default number of 100 usually is a good starting point.

The percentages near the vertical axis indicate which subset of the data in terms of units (rows) is depicted. The range from 0% to 100% in Figure 2 means that all units of the data are plotted.

3 Zooming and filtering

3.1 Zooming

We can focus our attention to the 5% most expensive diamonds by setting the `from` argument to 0 and the `to` argument to 5. The resulting tableplot are depicted in Figure 3. Observe that the number of row bins is still 100, so that the number of units per row bin is now 27 instead of 540. Therefore, much more detail can be observed in this tableplot.

```
tableplot(diamonds, select=c(carat, price, cut, color,
                             clarity), sortCol=price, from=0,
to=5)
```




Figure 3: Tableplot of the diamonds dataset: zooming in

The vertical axis contains two sets of tick marks. The small tick marks correspond with the row bins and the large tick marks correspond with the percentages between `from` and `to`. The latter are determined by R's base function `pretty`.

3.2 Filtering

The argument `subset` serves as a data filter. The tableplot in Figure 4 shows that data of premium cut diamonds that cost less than 5000\$.

```
tableplot(diamonds, subset = price < 5000 & cut == "Premium")
```




Figure 4: Tableplot of the diamonds dataset: filtered

It is also possible to create a tableplot of each category of a categorical variable in one call. For instance, by setting `subset=color`, we create a tableplot for each color class.

4 Customizing the tableplot

4.1 Continuous variables

For each bin of a continuous variable, the mean value is calculated (see Algorithm 1). When the distribution of these mean values is exponential, it is useful to apply a logarithmic transformation. The argument `scales` can be set to linear mode `"lin"`, logarithmic mode `"log"`, or the default value `"auto"`, which automatically determines which of the former two modes is used.

Observe that the x-axes of the variables `depth` and `table` in Figure 1 are broken. The x-axis of a variable i is broken if either

$$\begin{aligned} 0 < \max(m_{i1}, m_{i2}, \dots, m_{in}) \quad \text{AND} \\ \text{bias_brokenX} \cdot \max(m_{i1}, m_{i2}, \dots, m_{in}) < \min(m_{i1}, m_{i2}, \dots, m_{in}) \end{aligned}$$

OR

$$\begin{aligned} 0 > \min(m_{i1}, m_{i2}, \dots, m_{in}) \quad \text{AND} \\ \text{bias_brokenX} \cdot \min(m_{i1}, m_{i2}, \dots, m_{in}) > \max(m_{i1}, m_{i2}, \dots, m_{in}), \end{aligned}$$

where `bias_brokenX` is a bias parameter that should be a number between 0 and 1. If `bias_brokenX=1` then the above conditions are always false, which implies that the x-axes are never broken. On the other hand, if `bias_brokenX=0` then the x-axes are always broken. By default, `bias_brokenX=0.8`, which mean that an x-axis is broken if (in case of a variable with positive values) the minimum value is at least 0.8 times the maximum value. In the diamonds dataset, this applies to the variables `depth` and `table`.

4.2 Categorical variables

The color palettes of categorical variables can be customized with the argument `pals`. Several qualitative palettes are implemented. They can be shown by

The default palette is a combination of Set1 and Set2. It has the advantage that each category has a unique color for variables with up to 16 categories.

Suppose we want a to use the default palette for the variable `cut`, but starting with the seventh color, pink. Further we want the fifth palette for the variable `color`, but without the first color (black), and a custom palette, say a rainbow palette, for the variable `clarity`:

4.3 The tabplot object

The function `tableplot` returns a `tabplot`-object, that can be used to make minor changes to the tableplot, for instance the order of columns or the color

```
tablePalettes()
```




Figure 5: Color palettes

palettes. Of course, these changes can also be made by generating a new tableplot, such as in the examples above. However, if it takes considerable time to generate a tableplot, then it is practical to make minor changes immediately.

The output of the `tableplot` function can be assigned to a variable. The graphical output can be omitted by setting the argument `plot` to `FALSE`.

```
tab <- tableplot(diamonds, plot = FALSE)
```

The `tabplot`-object is a list that contains all information to depict a tableplot. The generic functions `summary` and `plot` can be applied to the `tabplot` object.

```
summary(tab)

##      general      variable1      variable2
## dataset :diamonds  name      :carat      name      :cut
## variables:10      type      :numeric     type      :categorical
## objects  :53940    sort      :decreasing  sort      :NA
## bins     :100      scale_init :auto       categories:6
## from     :0%       scale_final:lin
## to       :100%
```

```
tableplot(diamonds, pals = list("Set1(7)", "Set5",
rainbow(8)))
```






Figure 6: Tableplot of the diamonds dataset: other colour palettes

```
##      variable3      variable4      variable5
## name      :color      name      :clarity      name      :depth
## type      :categorical type      :categorical type      :numeric
## sort      :NA         sort      :NA         sort      :NA
## categories:7         categories:8         scale_init :auto
##                                     scale_final:lin
##
##      variable6      variable7      variable8
## name      :table      name      :price      name      :x
## type      :numeric   type      :numeric   type      :numeric
## sort      :NA         sort      :NA         sort      :NA
## scale_init :auto      scale_init :auto      scale_init :auto
## scale_final:lin       scale_final:lin       scale_final:lin
##
##      variable9      variable10
## name      :y         name      :z
## type      :numeric   type      :numeric
## sort      :NA         sort      :NA
## scale_init :auto      scale_init :auto
## scale_final:lin       scale_final:lin
##
plot(tab)
```

The function `tableChange` is used to make minor changes to a `tabplot`-object. Suppose we want the columns in the order of `2`, and we want to change all color palettes to default starting with the second color.

```
tab2 <- tableChange(tab, colNames = c("carat", "price", "cut",
  "color",
  "clarity"), pals = list("Set1(2)"))
plot(tab2)
```



With the function `tableSave`, tableplots can be saved to a desired graphical output format: pdf, eps, svg, wmf, png, jpg, bmp, or tiff.

```
tableSave(tab, filename = "diamonds.png", width = 5, height = 3,
          fontsize = 6, legend.lines = 6)
```

5 Resources

- Summary of the package: `help(package=tabplot)`
- The main help page: `?tabplot`
- Project site: <http://code.google.com/p/tableplot/>
- References:

- Tennekes, M., Jonge, E. de, Daas, P.J.H. (2011) Visual profiling of large statistical datasets. Paper presented at the 2011 New Techniques and Technologies for Statistics conference, Brussels, Belgium. ([paper](#), [presentation](#))

A Tableplot creation algorithm

A tabplot is basically created by Algorithm 1.

Algorithm 1 Create tableplot

Input: Tabular dataset t , column i_s of which the distribution is of interest^a, number of row bins n .

- 1: $t' \leftarrow$ sort t according to the values of column i_s .
- 2: Divide t' into n equally sized row bins according to the order of t' .
- 3: **for** each column i **do**
- 4: **if** i is numeric **then**
- 5: $m_{ib} \leftarrow$ mean value per bin b
- 6: $c_{ib} \leftarrow$ fraction of missing values per bin b
- 7: **end if**
- 8: **if** i is categorical **then**
- 9: $f_{ijb} \leftarrow$ frequency of each category j (including missing values) per bin b
- 10: **end if**
- 11: **end for**
- 12: **for** each column i **do**
- 13: **if** i is numeric **then**
- 14: Plot a bar chart of the mean values $\{m_{i1}, m_{i2}, \dots, m_{in}\}$, optionally with a logarithmic scale. The fraction of missing values $\{c_{i1}, c_{i2}, \dots, c_{in}\}$ determines the lightness of the bar colour. The lighter the colour, the more missing values occur in bin b . If all values are missing, a light red bar of full length is drawn.
- 15: **end if**
- 16: **if** i is categorical **then**
- 17: Plot a stacked bar chart according to the frequencies $\{f_{i1b}, f_{i2b}, \dots\}$ for each bin b . Each category is shown as a distinct colour. If there are missing values, they are depicted by a red colour.
- 18: **end if**
- 19: **end for**

Output: Tableplot

^aThe dataset t can also be sorted according to multiple columns.
