Timings of BIG data visualization with the tabplot package

Martijn Tennekes and Edwin de Jonge

 $\begin{array}{c} {\rm July}\ 7,\ 2013 \\ {\rm (A\ later\ version\ may\ be\ available\ on\ CRAN)} \end{array}$

Abstract

We test the speed of tabplot package with datasets over 1,00,000,000 records. For this purpose we multiply the diamonds dataset from the ggplot2 package 2,000 times.

Contents

1	Introduction	3
2	Create testdata	3
3	Prepare data	3
4	Create tableplots	3

1 Introduction

This dataset contains 53940 records and 10 variables.

2 Create testdata

```
require(ggplot2)
data(diamonds)
## add some NA's
is.na(diamonds$price) <- diamonds$cut == "Ideal"
is.na(diamonds$cut) <- (runif(nrow(diamonds)) > 0.8)
```

```
n <- nrow(diamonds)
N <- 200L * n

## convert to ff format (not enough memory otherwise)
require(ffbase)
diamondsff <- as.ffdf(diamonds)
nrow(diamondsff) <- N

# fill with identical data
for (i in chunk(from = 1, to = N, by = n)) {
    diamondsff[i, ] <- diamonds
}</pre>
```

3 Prepare data

The preparation step is the most time consuming. Per column, the rank order is determined.

```
system.time(p <- tablePrepare(diamondsff))

## user system elapsed
## 21.28 2.61 24.01</pre>
```

4 Create tableplots

To focus on the processing time of the tableplot function, the plot argument is set to FALSE.

```
system.time(tab <- tableplot(p, maxN = 100, plot = FALSE))</pre>
##
     user system elapsed
     3.73 0.56 4.29
##
system.time(tab <- tableplot(p, maxN = 1000, plot = FALSE))</pre>
##
     user system elapsed
##
     3.37 0.67 4.05
system.time(tab <- tableplot(p, maxN = 10000, plot = FALSE))</pre>
##
     user system elapsed
## 3.40 0.72 4.13
system.time(tab <- tableplot(p, maxN = 1e+05, plot = FALSE))</pre>
##
     user system elapsed
     3.40 0.66 4.07
system.time(tab <- tableplot(p, maxN = 1e+06, plot = FALSE))</pre>
##
     user system elapsed
## 3.46 0.69 4.15
system.time(tab <- tableplot(p, maxN = 0, plot = FALSE))</pre>
     user system elapsed
## 3.42 0.62 4.05
```