

Oracle Berkeley DB

*Berkeley DB
API Reference
for the STL C++ API*

Release 4.8



Legal Notice

This documentation is distributed under an open source license. You may review the terms of this license at:
<http://www.oracle.com/technology/software/products/berkeley-db/htdocs/oslicense.html>

Oracle, Berkeley DB, and Sleepycat are trademarks or registered trademarks of Oracle. All rights to these marks are reserved. No third-party use is permitted without the express prior written consent of Oracle.

To obtain a copy of this document's original source code, please submit a request to the Oracle Technology Network forum at:
<http://forums.oracle.com/forums/forum.jspa?forumID=271>

Published 6/1/2009

Table of Contents

| | |
|--|----|
| 1. dbstl global public functions | 1 |
| close_db | 3 |
| close_all_dbs | 4 |
| close_db_env | 5 |
| close_all_db_envs | 6 |
| begin_txn | 7 |
| commit_txn | 8 |
| abort_txn | 10 |
| current_txn | 12 |
| set_current_txn_handle | 13 |
| register_db | 14 |
| register_db_env | 15 |
| open_db | 16 |
| open_env | 18 |
| alloc_mutex | 20 |
| lock_mutex | 21 |
| unlock_mutex | 22 |
| free_mutex | 23 |
| dbstl_startup | 24 |
| dbstl_exit | 25 |
| operator== | 26 |
| set_global_dbfile_suffix_number | 27 |
| close_db_cursors | 28 |
| 2. dbstl container classes | 29 |
| 3. db_container | 30 |
| get_db_open_flags | 32 |
| get_db_set_flags | 33 |
| get_db_handle | 34 |
| get_db_env_handle | 35 |
| set_db_handle | 36 |
| set_all_flags | 37 |
| set_txn_begin_flags | 38 |
| get_txn_begin_flags | 39 |
| set_commit_flags | 40 |
| get_commit_flags | 41 |
| get_cursor_open_flags | 42 |
| set_cursor_open_flags | 43 |
| db_container | 44 |
| ~db_container | 46 |
| 4. db_vector | 47 |
| begin | 49 |
| end | 51 |
| rbegin | 52 |
| rend | 54 |
| max_size | 55 |
| capacity | 56 |

| | |
|--------------|-----|
| operator[] | 57 |
| at | 59 |
| front | 61 |
| back | 62 |
| operator== | 63 |
| operator!= | 64 |
| operator< | 65 |
| assign | 66 |
| push_front | 68 |
| pop_front | 69 |
| insert | 70 |
| erase | 72 |
| remove | 73 |
| remove_if | 74 |
| merge | 75 |
| unique | 76 |
| sort | 77 |
| reverse | 78 |
| splice | 79 |
| size | 81 |
| empty | 82 |
| db_vector | 83 |
| ~db_vector | 86 |
| operator= | 87 |
| resize | 88 |
| reserve | 89 |
| push_back | 90 |
| pop_back | 91 |
| swap | 92 |
| clear | 93 |
| 5. db_map | 94 |
| db_map | 96 |
| ~db_map | 98 |
| insert | 99 |
| begin | 101 |
| end | 103 |
| rbegin | 104 |
| rend | 106 |
| is_hash | 107 |
| bucket_count | 108 |
| size | 109 |
| max_size | 110 |
| empty | 111 |
| erase | 112 |
| find | 114 |
| lower_bound | 116 |
| equal_range | 118 |
| count | 120 |
| upper_bound | 121 |

| | |
|---------------------------------|-----|
| key_eq | 123 |
| hash_funct | 124 |
| value_comp | 125 |
| key_comp | 126 |
| operator= | 127 |
| operator[] | 128 |
| swap | 129 |
| clear | 130 |
| operator== | 131 |
| operator!= | 132 |
| 6. db_multimap | 133 |
| insert | 135 |
| erase | 137 |
| equal_range | 139 |
| equal_range_N | 141 |
| count | 143 |
| upper_bound | 144 |
| db_multimap | 146 |
| ~db_multimap | 148 |
| operator= | 149 |
| swap | 150 |
| operator== | 151 |
| operator!= | 152 |
| 7. db_set | 153 |
| db_set | 154 |
| ~db_set | 156 |
| insert | 157 |
| operator= | 160 |
| value_comp | 161 |
| swap | 162 |
| operator== | 163 |
| operator!= | 164 |
| 8. db_multiset | 165 |
| db_multiset | 166 |
| ~db_multiset | 168 |
| insert | 169 |
| erase | 172 |
| operator= | 174 |
| swap | 175 |
| operator== | 176 |
| operator!= | 177 |
| 9. dbstl iterator classes | 178 |
| 10. db_base_iterator | 179 |
| refresh | 180 |
| close_cursor | 181 |
| set_bulk_buffer | 182 |
| get_bulk_bufsize | 183 |
| db_base_iterator | 184 |
| operator= | 185 |

| | |
|---|-----|
| ~db_base_iterator | 186 |
| get_bulk_retrieval | 187 |
| is_rmw | 188 |
| is_directdb_get | 189 |
| 11. iterator classes for db_vector | 190 |
| 12. db_vector_base_iterator | 191 |
| db_vector_base_iterator | 192 |
| ~db_vector_base_iterator | 193 |
| operator== | 194 |
| operator!= | 195 |
| operator< | 196 |
| operator<= | 197 |
| operator>= | 198 |
| operator> | 199 |
| operator++ | 200 |
| operator-- | 201 |
| operator= | 202 |
| operator+ | 203 |
| operator+= | 204 |
| operator- | 205 |
| operator-= | 207 |
| operator * | 208 |
| operator-> | 209 |
| operator[] | 210 |
| get_current_index | 211 |
| move_to | 212 |
| refresh | 213 |
| close_cursor | 214 |
| set_bulk_buffer | 215 |
| get_bulk_bufsize | 216 |
| 13. db_vector_iterator | 217 |
| db_vector_iterator | 218 |
| ~db_vector_iterator | 219 |
| operator++ | 220 |
| operator-- | 221 |
| operator= | 222 |
| operator+ | 223 |
| operator+= | 224 |
| operator- | 225 |
| operator-= | 227 |
| operator * | 228 |
| operator-> | 229 |
| operator[] | 230 |
| refresh | 231 |
| 14. iterator classes for db_map and db_multimap | 232 |
| assign_second0 | 233 |
| assign_second | 234 |
| hash_default | 235 |
| 15. db_map_base_iterator | 236 |

| | |
|---|-----|
| db_map_base_iterator | 237 |
| ~db_map_base_iterator | 239 |
| operator++ | 240 |
| operator-- | 241 |
| operator== | 242 |
| operator!= | 243 |
| operator * | 244 |
| operator-> | 245 |
| refresh | 246 |
| close_cursor | 247 |
| move_to | 248 |
| set_bulk_buffer | 249 |
| get_bulk_bufsize | 250 |
| operator= | 251 |
| 16. db_map_iterator | 252 |
| db_map_iterator | 253 |
| ~db_map_iterator | 255 |
| operator++ | 256 |
| operator-- | 257 |
| operator * | 258 |
| operator-> | 259 |
| refresh | 260 |
| operator= | 261 |
| 17. iterator classes for db_set and db_multiset | 262 |
| 18. db_set_base_iterator | 263 |
| ~db_set_base_iterator | 264 |
| db_set_base_iterator | 265 |
| operator++ | 267 |
| operator-- | 268 |
| operator * | 269 |
| operator-> | 270 |
| refresh | 271 |
| 19. db_set_iterator | 272 |
| ~db_set_iterator | 273 |
| db_set_iterator | 274 |
| operator++ | 276 |
| operator-- | 277 |
| operator * | 278 |
| operator-> | 279 |
| refresh | 280 |
| 20. db_reverse_iterator | 281 |
| operator++ | 282 |
| operator-- | 283 |
| operator+ | 284 |
| operator- | 285 |
| operator+= | 286 |
| operator-= | 287 |
| operator< | 288 |
| operator> | 289 |

| | |
|--|-----|
| operator<= | 290 |
| operator>= | 291 |
| db_reverse_iterator | 292 |
| operator= | 293 |
| operator[] | 294 |
| 21. dbstl helper classes | 295 |
| 22. ElementRef and ElementHolder wappers | 296 |
| 23. ElementHolder | 298 |
| _DB_STL_CopyData | 300 |
| _DB_STL_CopyData_int | 301 |
| _DB_STL_GetIterator | 302 |
| _DB_STL_GetData | 303 |
| _DB_STL_SetIterator | 304 |
| _DB_STL_SetData | 305 |
| _DB_STL_SetDelltr | 306 |
| ElementHolder | 307 |
| ~ElementHolder | 309 |
| operator+= | 310 |
| operator-= | 311 |
| operator *= | 312 |
| operator/= | 313 |
| operator%= | 314 |
| operator &= | 315 |
| operator = | 316 |
| operator^= | 317 |
| operator>>= | 318 |
| operator<<= | 319 |
| operator++ | 320 |
| operator-- | 321 |
| operator= | 322 |
| _DB_STL_value | 323 |
| _DB_STL_StoreElement | 324 |
| operator ptype | 325 |
| 24. ElementRef | 326 |
| ~ElementRef | 327 |
| ElementRef | 328 |
| operator= | 330 |
| _DB_STL_StoreElement | 331 |
| _DB_STL_value | 332 |
| _DB_STL_SetDelltr | 333 |
| _DB_STL_CopyData | 334 |
| _DB_STL_GetIterator | 335 |
| _DB_STL_GetData | 336 |
| _DB_STL_SetIterator | 337 |
| _DB_STL_SetData | 338 |
| 25. DbstlDbt | 339 |
| DbstlDbt | 341 |
| ~DbstlDbt | 342 |
| operator= | 343 |

| | |
|---------------------------------------|-----|
| free_mem | 344 |
| 26. DbstlElemTraits | 345 |
| assign | 348 |
| eq | 349 |
| lt | 350 |
| compare | 351 |
| length | 352 |
| copy | 353 |
| find | 354 |
| move | 355 |
| to_char_type | 356 |
| to_int_type | 357 |
| eq_int_type | 358 |
| eof | 359 |
| not_eof | 360 |
| set_restore_function | 361 |
| get_restore_function | 362 |
| set_assign_function | 363 |
| get_assign_function | 364 |
| get_size_function | 365 |
| set_size_function | 366 |
| get_copy_function | 367 |
| set_copy_function | 368 |
| set_sequence_len_function | 369 |
| get_sequence_len_function | 370 |
| get_sequence_copy_function | 371 |
| set_sequence_copy_function | 372 |
| set_compare_function | 373 |
| get_compare_function | 374 |
| set_sequence_compare_function | 375 |
| get_sequence_compare_function | 376 |
| set_sequence_n_compare_function | 377 |
| get_sequence_n_compare_function | 378 |
| instance | 379 |
| ~DbstlElemTraits | 380 |
| DbstlElemTraits | 381 |
| 27. BulkRetrievalOption | 382 |
| BulkRetrievalOption | 383 |
| operator== | 384 |
| operator= | 385 |
| bulk_buf_size | 386 |
| bulk_retrieval | 387 |
| no_bulk_retrieval | 388 |
| 28. ReadModifyWriteOption | 389 |
| operator= | 390 |
| operator== | 391 |
| read_modify_write | 392 |
| no_read_modify_write | 393 |
| 29. dbstl exception classes | 394 |

| | |
|---|-----|
| 30. DbstlException | 395 |
| DbstlException | 396 |
| operator= | 397 |
| ~DbstlException | 398 |
| 31. InvalidDbtException | 399 |
| InvalidDbtException | 400 |
| 32. FailedAssertionException | 401 |
| what | 402 |
| FailedAssertionException | 403 |
| ~FailedAssertionException | 404 |
| 33. InvalidCursorException | 405 |
| InvalidCursorException | 406 |
| 34. NoSuchKeyException | 407 |
| NoSuchKeyException | 408 |
| 35. NotEnoughMemoryException | 409 |
| NotEnoughMemoryException | 410 |
| 36. NotSupportedException | 411 |
| NotSupportedException | 412 |
| 37. InvalidIteratorException | 413 |
| InvalidIteratorException | 414 |
| 38. InvalidFunctionCall | 415 |
| InvalidFunctionCall | 416 |
| 39. InvalidArgumentException | 417 |
| InvalidArgumentException | 418 |
| 40. Assign functions used internally only | 419 |
| 41. operators that enable the n + itr expression | 420 |
| operator+ | 421 |
| 42. C++ iostream support for ElementHolder and ElementRef | 422 |
| operator<< | 423 |
| operator>> | 424 |
| 43. dbstl global functions for internal use only | 425 |
| dbstl_strcmp | 426 |
| dbstl_strcpy | 427 |
| dbstl_strlen | 428 |
| dbstl_strncmp | 429 |
| dbstl_wscmp | 430 |
| dbstl_wscpy | 431 |
| dbstl_wcslen | 432 |
| dbstl_wcsncmp | 433 |
| DbstlMalloc | 434 |
| DbstlReAlloc | 435 |
| hash_default | 436 |

Chapter 1. dbstl global public functions

dbstl global public functions

dbstl global public functions

Public Members

| Member | Description |
|--|---|
| close_db | Close pdb regardless of reference count. |
| close_all_dbs | Close all open database handles regardless of reference count. |
| close_db_env | Close specified database environment handle regardless of reference count. |
| close_all_db_envs | Close all open database environment handles regardless of reference count. |
| begin_txn | Begin a new transaction from the specified environment "env". |
| commit_txn | Commit current transaction opened in the environment "env". |
| abort_txn | Abort current transaction of environment "env". |
| current_txn | Get current transaction of environment "env". |
| set_current_txn_handle | Set environment env's current transaction handle to be newtxn. |
| register_db | Register a Db handle "pdb1". |
| register_db_env | Register a DbEnv handle env1, this handle and handles opened in it will be closed by ResourceManager . |
| open_db | Helper function to open a database and register it into dbstl for the calling thread. |
| open_env | Helper function to open an environment and register it into dbstl for the calling thread. |
| alloc_mutex | Allocate a Berkeley DB mutex. |
| lock_mutex | Lock a mutex, wait if it is held by another thread. |
| unlock_mutex | Unlock a mutex, and return immediately. |
| free_mutex | Free a mutex, and return immediately. |
| dbstl_startup | If there are multiple threads within a process that make use of dbstl, then this function should be called in a single thread mutual exclusively before any use of dbstl in a process; Otherwise, you don't need to call it, but are allowed to call it anyway. |

| Member | Description |
|---|--|
| dbstl_exit | This function releases any memory allocated in the heap by code of dbstl. |
| operator== | Operators to compare two Dbt objects. |
| set_global_dbfile_suffix_number | If exisiting random temporary database name generation mechanism is still causing name clashes, users can set this global suffix number which will be append to each temporary database file name and incremented after each append, and by default it is 0. |
| close_db_cursors | Close cursors opened in dbp1. |
| Operators that enable the n + itr expression. | Operators that enable the n + itr expression. |
| dbstl global functions for internal use only | dbstl global functions for internal use only |
| C++ iostream support for ElementHolder and | C++ iostream support for ElementHolder and |
| Assign functions used internally only. | Assign functions used internally only. |

Group

None

close_db

Function Details

```
void close_db(Db *pdb)
```

Close pdb regardless of reference count.

You must make sure pdb is not used by others before calling this method. You can close the underlying database of a container and assign another database with right configurations to it, if the configuration is not suitable for the container, there will be an [InvalidArgumentException](#) type of exception thrown. You can't use the container after you called close_db and before setting another valid database handle to the container via [db_container::set_db_handle\(\)](#) function.

Parameters

pdb

The database handle to close.

Group: Functions to close database/environments.

Normally you don't have to close any database or environment handles, they will be closed automatically.

Though you still have the following API to close them.

Class

[dbstl_global_functions](#)

close_all_dbs

Function Details

```
void close_all_dbs()
```

Close all open database handles regardless of reference count.

You can't use any container after you called `close_all_dbs` and before setting another valid database handle to the container via `db_container::set_db_handle()` function.

See Also

[close_db\(Db *\)](#) ;

Group: Functions to close database/environments.

Normally you don't have to close any database or environment handles, they will be closed automatically.

Though you still have the following API to close them.

Class

[dbstl_global_functions](#)

close_db_env

Function Details

```
void close_db_env(DbEnv *pdbenv)
```

Close specified database environment handle regardless of reference count.

Make sure the environment is not used by any other databases.

Parameters

pdbenv

The database environment handle to close.

Group: Functions to close database/environments.

Normally you don't have to close any database or environment handles, they will be closed automatically.

Though you still have the following API to close them.

Class

[dbstl_global_functions](#)

close_all_db_envs

Function Details

```
void close_all_db_envs()
```

Close all open database environment handles regardless of reference count.

You can't use the container after you called `close_db` and before setting another valid database handle to the container via [db_container::set_db_handle\(\)](#) function.

See Also

[close_db_env\(DbEnv *\)](#) ;

Group: Functions to close database/environments.

Normally you don't have to close any database or environment handles, they will be closed automatically.

Though you still have the following API to close them.

Class

[dbstl_global_functions](#)

begin_txn

Function Details

```
DbTxn* begin_txn(u_int32_t flags,  
                 DbEnv *env)
```

Begin a new transaction from the specified environment "env".

This function is called by dbstl user to begin an external transaction. The "flags" parameter is passed to DbEnv::txn_begin(). If a transaction created from the same database environment already exists and is unresolved, the new transaction is started as a child transaction of that transaction, and thus you can't specify the parent transaction.

Parameters

flags

It is set to DbEnv::txn_begin() function.

env

The environment to start a transaction from.

Return Value

The newly created transaction.

Group: Transaction control global functions.

dbstl transaction API.

You should call these API rather than DB C/C++ API to use Berkeley DB transaction features.

Class

[dbstl_global_functions](#)

commit_txn

Function Details

```
void commit_txn(DbEnv *env,
                u_int32_t flags=0)
```

Commit current transaction opened in the environment "env".

This function is called by user to commit an external explicit transaction.

Parameters

flags

It is set to DbTxn::commit() funcion.

env

The environment whose current transaction is to be committed.

See Also

[commit_txn\(DbEnv *, DbTxn *, u_int32_t\) ;](#)

```
void commit_txn(DbEnv *env, DbTxn *txn,
                u_int32_t flags=0)
```

Commit a specified transaction and all its child transactions.

Parameters

txn

The transaction to commit, can be a parent transaction of a nested transaction group, all un-aborted child transactions of it will be committed.

flags

It is passed to each DbTxn::commit() call.

env

The environment where txn is started from.

See Also

[commit_txn\(DbEnv *, u_int32_t\) ;](#)

Group: Transaction control global functions.

dbstl transaction API.

You should call these API rather than DB C/C++ API to use Berkeley DB transaction features.

Class

[dbstl_global_functions](#)

abort_txn

Function Details

```
void abort_txn(DbEnv *env)
```

Abort current transaction of environment "env".

This function is called by dbstl user to abort an outside explicit transaction.

Parameters

env

The environment whose current transaction is to be aborted.

See Also

[abort_txn\(DbEnv *, DbTxn *\)](#) ;

```
void abort_txn(DbEnv *env,  
               DbTxn *txn)
```

Abort specified transaction "txn" and all its child transactions.

That is, "txn" can be a parent transaction of a nested transaction group.

Parameters

txn

The transaction to abort, can be a parent transaction of a nested transaction group, all child transactions of it will be aborted.

env

The environment where txn is started from.

See Also

[abort_txn\(DbEnv *\)](#) ;

Group: Transaction control global functions.

dbstl transaction API.

You should call these API rather than DB C/C++ API to use Berkeley DB transaction features.

Class

[dbstl_global_functions](#)

current_txn

Function Details

```
DbTxn* current_txn(DbEnv *env)
```

Get current transaction of environment "env".

Parameters

env

The environment whose current transaction we want to get.

Return Value

Current transaction of env.

Group: Transaction control global functions.

dbstl transaction API.

You should call these API rather than DB C/C++ API to use Berkeley DB transaction features.

Class

[dbstl_global_functions](#)

set_current_txn_handle

Function Details

```
DbTxn* set_current_txn_handle(DbEnv *env,  
                              DbTxn *newtxn)
```

Set environment env's current transaction handle to be newtxn.

The original transaction handle returned without aborting or committing. This function is used for users to use one transaction among multiple threads.

Parameters

newtxn

The new transaction to be as the current transaction of env.

env

The environment whose current transaction to replace.

Return Value

The old current transaction of env. It is not resolved.

Group: Transaction control global functions.

dbstl transaction API.

You should call these API rather than DB C/C++ API to use Berkeley DB transaction features.

Class

[dbstl_global_functions](#)

register_db

Function Details

```
void register_db(Db *pdb1)
```

Register a Db handle "pdb1".

This handle and handles opened in it will be closed by [ResourceManager](#) , so application code must not try to close or delete it. Users can do enough configuration before opening the Db then register it via this function. All database handles should be registered via this function in each thread using the handle. The only exception is the database handle opened by [dbstl::open_db](#) should not be registered in the thread of the [dbstl::open_db](#) call.

Parameters

pdb1

The database handle to register into dbstl for current thread.

Class

[dbstl_global_functions](#)

register_db_env

Function Details

```
void register_db_env(DbEnv *env1)
```

Register a DbEnv handle env1, this handle and handles opened in it will be closed by [ResourceManager](#) .

Application code must not try to close or delete it. Users can do enough config before opening the DbEnv and then register it via this function. All environment handles should be registered via this function in each thread using the handle. The only exception is the environment handle opened by dbstl::open_db_env should not be registered in the thread of the dbstl::open_db_env call.

Parameters

env1

The environment to register into dbstl for current thread.

Class

[dbstl_global_functions](#)

open_db

Function Details

```
Db* open_db(DbEnv *penv, const char *filename, DBTYPE dbtype,
            u_int32_t oflags, u_int32_t set_flags, int mode=0644, DbTxn *txn=NULL,
            u_int32_t cflags=0,
            const char *dbname=NULL)
```

Helper function to open a database and register it into dbstl for the calling thread.

Users still need to register it in any other thread using it if it is shared by multiple threads, via [register_db\(\)](#) function. Users don't need to delete or free the memory of the returned object, dbstl will take care of that. When you don't use [dbstl::open_db\(\)](#) but explicitly call DB C++ API to open a database, you must new the Db object, rather than create it on stack, and you must delete the Db object by yourself.

Parameters

penv

The environment to open the database from.

txn

The transaction to open the database from, passed to Db::open.

dbtype

The database type, passed to Db::open.

oflags

The database open flags, passed to Db::open.

filename

The database file name, passed to Db::open.

mode

The database open mode, passed to Db::open.

cflags

The create flags passed to Db class constructor.

dbname

The database name, passed to Db::open.

set_flags

The flags to be set to the created database handle.

Return Value

The opened database handle.

See Also

[register_db\(Db *\)](#) ;

[open_db_env](#);

Class

[dbstl_global_functions](#)

open_env

Function Details

```
DbEnv* open_env(const char *env_home, u_int32_t set_flags,  
                u_int32_t oflags=DB_CREATE|DB_INIT_MPOOL, u_int32_t cachesize=4 *1024 *1024,  
                int mode=0644,  
                u_int32_t cflags=0)
```

Helper function to open an environment and register it into dbstl for the calling thread.

Users still need to register it in any other thread if it is shared by multiple threads, via [register_db_env\(\)](#) function above. Users don't need to delete or free the memory of the returned object, dbstl will take care of that.

When you don't use [dbstl::open_env\(\)](#) but explicitly call DB C++ API to open an environment, you must new the DbEnv object, rather than create it on stack, and you must delete the DbEnv object by yourself.

Parameters

oflags

Environment open flags, passed to DbEnv::open.

set_flags

Flags to set to the created environment before opening it.

mode

Environment region files mode, passed to DbEnv::open.

cflags

DbEnv constructor creation flags, passed to DbEnv::DbEnv.

cachesize

Environment cache size, by default 4M bytes.

env_home

Environment home directory, it must exist. Passed to DbEnv::open.

Return Value

The opened database environment handle.

See Also[register_db_env\(DbEnv *\)](#) ;[open_db](#) ;**Class**[dbstl_global_functions](#)

alloc_mutex

Function Details

```
db_mutex_t alloc_mutex()
```

Allocate a Berkeley DB mutex.

Return Value

Berkeley DB mutex handle.

Group: Mutex API based on Berkeley DB mutex.

These functions are in-process mutex support which uses Berkeley DB mutex mechanisms.

You can call these functions to do portable synchronization for your code.

Class

[dbstl_global_functions](#)

lock_mutex

Function Details

```
int lock_mutex(db_mutex_t mtx)
```

Lock a mutex, wait if it is held by another thread.

Parameters

mtx

The mutex handle to lock.

Return Value

0 if succeed, non-zero otherwise, call `db_strerror` to get message.

Group: Mutex API based on Berkeley DB mutex.

These functions are in-process mutex support which uses Berkeley DB mutex mechanisms.

You can call these functions to do portable synchronization for your code.

Class

[dbstl_global_functions](#)

unlock_mutex

Function Details

```
int unlock_mutex(db_mutex_t mtx)
```

Unlock a mutex, and return immediately.

Parameters

mtx

The mutex handle to unlock.

Return Value

0 if succeed, non-zero otherwise, call `db_strerror` to get message.

Group: Mutex API based on Berkeley DB mutex.

These functions are in-process mutex support which uses Berkeley DB mutex mechanisms.

You can call these functions to do portable synchronization for your code.

Class

[dbstl_global_functions](#)

free_mutex

Function Details

```
void free_mutex(db_mutex_t mtx)
```

Free a mutex, and return immediately.

Parameters

mtx

The mutex handle to free.

Return Value

0 if succeed, non-zero otherwise, call db_strerror to get message.

Group: Mutex API based on Berkeley DB mutex.

These functions are in-process mutex support which uses Berkeley DB mutex mechanisms.

You can call these functions to do portable synchronization for your code.

Class

[dbstl_global_functions](#)

dbstl_startup

Function Details

```
void dbstl_startup()
```

If there are multiple threads within a process that make use of dbstl, then this function should be called in a single thread mutual exclusively before any use of dbstl in a process; Otherwise, you don't need to call it, but are allowed to call it anyway.

Class

[dbstl_global_functions](#)

dbstl_exit

Function Details

```
void dbstl_exit()
```

This function releases any memory allocated in the heap by code of dbstl.

So you can only call [dbstl_exit\(\)](#) right before the entire process exits. It will release any memory allocated by dbstl that have to live during the entire process lifetime.

Class

[dbstl_global_functions](#)

operator==

Function Details

```
bool operator==(const Dbt &d1,  
                const Dbt &d2)
```

Operators to compare two Dbt objects.

Parameters

d2

Dbt object to compare.

d1

Dbt object to compare.

```
bool operator==(const DBT &d1,  
                const DBT &d2)
```

Operators to compare two DBT objects.

Parameters

d2

DBT object to compare.

d1

DBT object to compare.

Class

[dbstl_global_functions](#)

set_global_dbfile_suffix_number

Function Details

```
void set_global_dbfile_suffix_number(u_int32_t num)
```

If existing random temporary database name generation mechanism is still causing name clashes, users can set this global suffix number which will be append to each temporary database file name and incremented after each append, and by default it is 0.

Parameters

num

Starting number to append to each temporary db file name.

Class

[dbstl_global_functions](#)

close_db_cursors

Function Details

```
size_t close_db_cursors(Db *dbp1)
```

Close cursors opened in dbp1.

Parameters

dbp1

The database handle whose active cursors to close.

Return Value

The number of cursors closed by this call.

Class

[dbstl_global_functions](#)

Chapter 2. dbstl container classes

dbstl container classes

dbstl container classes

A dbstl container is very much like a C++ STL container.

It stores a collection of data items, or key/data pairs. Each container is backed by a Berkeley DB database created in an explicit database environment or an internal private environment; And the database itself can be created explicitly with all kinds of configurations, or by dbstl internally. For each type of container, some specific type of database and/or configurations must be used or specified to the database and its environment. dbstl will check the database and environment conform to the requirement. When users don't have a chance to specify a container's backing database and environment, like in copy constructors, dbstl will create proper databases and/or environment for it. There are two helper functions to make it easier to create/open an environment or database, they are [dbstl::open_db\(\)](#) and [dbstl::open_env\(\)](#) ;

See Also

[dbstl::open_db\(\)](#) [dbstl::open_env\(\)](#) [db_vector](#) [db_map](#) [db_multimap](#) [db_set](#) [db_multiset](#)

Public Members

| Member | Description |
|-------------------------------------|---------------------|
| db_map | db_map |
| db_multimap | db_multimap |
| db_set | db_set |
| db_multiset | db_multiset |
| db_vector | db_vector |
| db_container | db_container |
| BulkRetrievalOption | BulkRetrievalOption |

Group

None

Chapter 3. db_container

db_container

This class is the base class for all db container classes, you don't directly use this class, but all container classes inherit from this class, so you need to know the methods that can be accessed via concrete container classes.

This class is also used to support auto commit transactions. Autocommit is enabled when DB_AUTO_COMMIT is set to the database or database environment handle and the environment is transactional.

Inside dbctl, there are transactions begun and committed/aborted if the backing database and/or environment requires auto commit, and there are cursors opened internally, and you can set the flags used by the transaction and cursor functions via set functions of this class.

All dbctl containers are fully multi-threaded, you should not need any synchronization to use them in the correct way, but this class is not thread safe, access to its members are not protected by any mutex because the data members of this class are supposed to be set before they are used, and remain read only afterwards. If this is not the case, you must synchronize the access.

Public Members

| Member | Description |
|---------------------------------------|--|
| get_db_open_flags | Get the backing database's open flags. |
| get_db_set_flags | Get the backing database's flags that are set via Db::set_flags() function. |
| get_db_handle | Get the backing database's handle. |
| get_db_env_handle | Get the backing database environment's handle. |
| set_db_handle | Set the underlying database's handle, and optionally environment handle if the environment has also changed. |
| set_all_flags | Set the flags required by the Berkeley DB functions DbEnv::txn_begin(), DbTxn::commit() and DbEnv::cursor(). |
| set_txn_begin_flags | Set flag of DbEnv::txn_begin() call. |
| get_txn_begin_flags | Get flag of DbEnv::txn_begin() call. |
| set_commit_flags | Set flag of DbTxn::commit() call. |
| get_commit_flags | Get flag of DbTxn::commit() call. |
| get_cursor_open_flags | Get flag of Db::cursor() call. |
| set_cursor_open_flags | Set flag of Db::cursor() call. |
| db_container | Default constructor. |
| ~db_container | The backing database is not closed in this function. |

Group

[dbstl container classes](#)

get_db_open_flags

Function Details

```
u_int32_t get_db_open_flags() const
```

Get the backing database's open flags.

Return Value

The backing database's open flags.

Group: Get and set functions for data members.

Note that these functions are not thread safe, because all data members of [db_container](#) are supposed to be set on container construction and initialization, and remain read only afterwards.

Class

[db_container](#)

get_db_set_flags

Function Details

```
u_int32_t get_db_set_flags() const
```

Get the backing database's flags that are set via Db::set_flags() function.

Return Value

Flags set to this container's database handle.

Group: Get and set functions for data members.

Note that these functions are not thread safe, because all data members of [db_container](#) are supposed to be set on container construction and initialization, and remain read only afterwards.

Class

[db_container](#)

get_db_handle

Function Details

```
Db* get_db_handle() const
```

Get the backing database's handle.

Return Value

The backing database handle of this container.

Group: Get and set functions for data members.

Note that these functions are not thread safe, because all data members of [db_container](#) are supposed to be set on container construction and initialization, and remain read only afterwards.

Class

[db_container](#)

get_db_env_handle

Function Details

```
DbEnv* get_db_env_handle() const
```

Get the backing database environment's handle.

Return Value

The backing database environment handle of this container.

Group: Get and set functions for data members.

Note that these functions are not thread safe, because all data members of [db_container](#) are supposed to be set on container construction and initialization, and remain read only afterwards.

Class

[db_container](#)

set_db_handle

Function Details

```
void set_db_handle(Db *dbp,  
                  DbEnv *newenv=NULL)
```

Set the underlying database's handle, and optionally environment handle if the environment has also changed.

That is, users can change the container object's underlying database while the object is alive. dbstl will verify that the handles set conforms to the concrete container's requirement to Berkeley DB database/environment handles.

Parameters

dbp

The database handle to set.

newenv

The database environment handle to set.

Group: Get and set functions for data members.

Note that these functions are not thread safe, because all data members of [db_container](#) are supposed to be set on container construction and initialization, and remain read only afterwards.

Class

[db_container](#)

set_all_flags

Function Details

```
void set_all_flags(u_int32_t txn_begin_flags, u_int32_t commit_flags,  
                  u_int32_t cursor_open_flags)
```

Set the flags required by the Berkeley DB functions `DbEnv::txn_begin()`, `DbTxn::commit()` and `DbEnv::cursor()`.

These flags will be set to this container's auto commit member functions when auto commit transaction is used, except that `cursor_oflags` is set to the `Dbc::cursor` when creating an iterator for this container. By default the three flags are all zero. You can also set the values of the flags individually by using the appropriate set functions in this class. The corresponding get functions return the flags actually used.

Parameters

commit_flags

Flags to be set to `DbTxn::commit()`.

cursor_open_flags

Flags to be set to `Db::cursor()`.

txn_begin_flags

Flags to be set to `DbEnv::txn_begin()`.

Group: Get and set functions for data members.

Note that these functions are not thread safe, because all data members of [db_container](#) are supposed to be set on container construction and initialization, and remain read only afterwards.

Class

[db_container](#)

set_txn_begin_flags

Function Details

```
void set_txn_begin_flags(u_int32_t flag)
```

Set flag of DbEnv::txn_begin() call.

Parameters

flag

Flags to be set to DbEnv::txn_begin().

Group: Get and set functions for data members.

Note that these functions are not thread safe, because all data members of [db_container](#) are supposed to be set on container construction and initialization, and remain read only afterwards.

Class

[db_container](#)

get_txn_begin_flags

Function Details

```
u_int32_t get_txn_begin_flags() const
```

Get flag of DbEnv::txn_begin() call.

Return Value

Flags to be set to DbEnv::txn_begin().

Group: Get and set functions for data members.

Note that these functions are not thread safe, because all data members of [db_container](#) are supposed to be set on container construction and initialization, and remain read only afterwards.

Class

[db_container](#)

set_commit_flags

Function Details

```
void set_commit_flags(u_int32_t flag)
```

Set flag of DbTxn::commit() call.

Parameters

flag

Flags to be set to DbTxn::commit().

Group: Get and set functions for data members.

Note that these functions are not thread safe, because all data members of [db_container](#) are supposed to be set on container construction and initialization, and remain read only afterwards.

Class

[db_container](#)

get_commit_flags

Function Details

```
u_int32_t get_commit_flags() const
```

Get flag of DbTxn::commit() call.

Return Value

Flags to be set to DbTxn::commit().

Group: Get and set functions for data members.

Note that these functions are not thread safe, because all data members of [db_container](#) are supposed to be set on container construction and initialization, and remain read only afterwards.

Class

[db_container](#)

get_cursor_open_flags

Function Details

```
u_int32_t get_cursor_open_flags() const
```

Get flag of Db::cursor() call.

Return Value

Flags to be set to Db::cursor().

Group: Get and set functions for data members.

Note that these functions are not thread safe, because all data members of [db_container](#) are supposed to be set on container construction and initialization, and remain read only afterwards.

Class

[db_container](#)

set_cursor_open_flags

Function Details

```
void set_cursor_open_flags(u_int32_t flag)
```

Set flag of Db::cursor() call.

Parameters

flag

Flags to be set to Db::cursor().

Group: Get and set functions for data members.

Note that these functions are not thread safe, because all data members of [db_container](#) are supposed to be set on container construction and initialization, and remain read only afterwards.

Class

[db_container](#)

db_container

Function Details

```
db_container()
```

Default constructor.

```
db_container(const db_container &dbctnr)
```

Copy constructor.

The new container will be backed by another database within the same environment unless dbctnr's backing database is in its own internal private environment. The name of the database is coined based on current time and thread id and some random number. If this is still causing naming clashes, you can set a suffix number via "set_global_dbfile_suffix_number" function; And following db file will suffix this number in the file name for additional randomness. And the suffix will be incremented after each such use. You can change the file name via DbEnv::rename. If dbctnr is using an anonymous database, the newly constructed container will also use an anonymous one.

Parameters

dbctnr

The container to initialize this container.

```
db_container(Db *dbp,  
             DbEnv *envp)
```

This constructor is not directly called by the user, but invoked by constructors of concrete container classes.

The statement about the parameters applies to constructors of all container classes.

Parameters

dbp

Database handle. dbp is supposed to be opened inside envp. Each dbstl container is backed by a Berkeley DB database, so dbstl will create an internal anonymous database if dbp is NULL.

envp

Environment handle. And envp can also be NULL, meaning the dbp handle may be created in its internal private environment.

Class

[db_container](#)

~db_container

Function Details

```
virtual ~db_container()
```

The backing database is not closed in this function.

It is closed when current thread exits and the database is no longer referenced by any other container instances in this process. In order to make the reference counting work alright, you must call [register_db\(Db*\)](#) and [register_db_env\(DbEnv*\)](#) correctly.

See Also

[register_db\(Db*\)](#) [register_db_env\(DbEnv*\)](#)

Class

[db_container](#)

Chapter 4. db_vector

db_vector

The [db_vector](#) class has the union set of public member functions as `std::vector`, `std::deque` and `std::list`, and each method has identical default semantics to that in the std equivalent containers.

The difference is that the data is maintained using a Berkeley DB database as well as some Berkeley DB related extensions.

See Also

[db_container](#) [db_container\(Db*, DbEnv*\)](#) [db_container\(const db_container&\)](#)

Class Template Parameters

T

The type of data to store.

value_type_sub

If T is a class/struct type, do not specify anything for this parameter; Otherwise, specify `ElementHolder<T>` to it. `Database(dbp)` and `environment(penv)` handle requirement (applies for all constructors of this class template): `dbp` must meet the following requirement: 1. `dbp` must be a `DB_RECNO` type of database handle. 2. `DB_THREAD` must be set to `dbp`'s open flags. 3. An optional flag `DB_RENUMBER` is required if the container object is supposed to be a `std::vector` or `std::deque` equivalent; Not required if it is a `std::list` equivalent. But `dbstl` will not check whether `DB_RENUMBER` is set to this database handle. Setting `DB_RENUMBER` will cause the index values of all elements in the underlying database to be maintained consecutive and in order, which involves potentially a lot of work because many indices may be updated. See the [db_container\(Db*, DbEnv*\)](#) for more information about the two parameters.

Public Members

| Member | Description |
|----------------------------|---|
| begin | Create a read-write or read-only iterator. |
| end | Create an open boundary iterator. |
| rbegin | Create a reverse iterator. |
| rend | Create an open boundary iterator. |
| max_size | Get max size. |
| capacity | Get capacity. |
| operator[] | Index operator, can act as both a left value and a right value. |
| at | Index function. |

| Member | Description |
|------------------------------|--|
| front | Return a reference to the first element. |
| back | Return a reference to the last element. |
| operator== | Container equality comparison operator. |
| operator!= | Container in-equality comparison operator. |
| operator< | Container less than comparison operator. |
| assign | Assign a range [first, last) to this container. |
| push_front | Push an element x into the vector from front. |
| pop_front | Pop out the front element from the vector. |
| insert | Insert x before position pos. |
| erase | Erase element at position pos. |
| remove | Remove all elements whose values are "value" from the list. |
| remove_if | Remove all elements making "pred" return true. |
| merge | Merge content with another container. |
| unique | Remove consecutive duplicate values from this list. |
| sort | Sort this list. |
| reverse | Reverse this list. |
| splice | Moves elements from list x into this list. |
| size | Return the number of elements in this container. |
| empty | Returns whether this container is empty. |
| db_vector | Constructor. |
| ~db_vector | |
| operator= | Container assignment operator. |
| resize | Resize this container to specified size n, insert values t if need to enlarge the container. |
| reserve | Reserve space. |
| push_back | Push back an element into the vector. |
| pop_back | Pop out last element from the vector. |
| swap | Swap content with another vector vec. |
| clear | Remove all elements of the vector, make it an empty vector. |

Group

[dbstl container classes](#)

begin

Function Details

```
iterator begin(ReadModifyWriteOption rmw=
    ReadModifyWriteOption::no_read_modify_write(), bool readonly=false,
    BulkRetrievalOption bulk_read=BulkRetrievalOption::no_bulk_retrieval(),
    bool directdb_get=true)
```

Create a read-write or read-only iterator.

We allow users to create a readonly iterator here so that they don't have to use a const container to create a const_iterator. But using const_iterator is faster. The flags set via db_container::set_cursor_oflags() is used as the cursor open flags.

Parameters

directdb_get

Whether always read key/data pair from backing db rather than using the value cached in the iterator. The current key/data pair is cached in the iterator and always kept updated on iterator movement, but in some extreme conditions, errors can happen if you use cached key/data pairs without always refreshing them from database. By default we are always reading from database when we are accessing the data the iterator sits on, except when we are doing bulk retrievals. But your application can gain extra performance promotion if you can set this flag to false.

readonly

Whether the iterator is created as a readonly iterator. Read only iterators can not update its underlying key/data pair.

bulk_read

Whether read database key/data pairs in bulk, by specifying DB_MULTIPLE_KEY flag to underlying cursor's Dbc::get function. Only readonly iterators can do bulk retrieval, if iterator is not read only, this parameter is ignored. Bulk retrieval can accelerate reading speed because each database read operation will read many key/data pairs, thus saved many database read operations. The default bulk buffer size is 32KB, you can set your desired bulk buffer size by specifying BulkRetrievalOpt::bulk_retrieval(your_bulk_buffer_size); If you don't want bulk retrieval, set BulkRetrievalOpt::no_bulk_retrieval() as the real parameter.

rmw

Whether this iterator will open a Berkeley DB cursor with DB_RMW flag set. If the iterator is used to read a key/data pair, then update it and store back to db, it is good to set the DB_RMW flag, by specifying RMWltrOpt::read_modify_write() If you don't want to set the DB_RMW flag, specify RMWltrOpt::no_read_modify_write(), which is the default behavior.

Return Value

The created iterator.

See Also

`db_container::set_cursor_oflags();`

```
const_iterator begin(BulkRetrievalOption bulkretrieval=  
    (BulkRetrievalOption::no_bulk_retrieval()),  
    bool directdb_get=true) const
```

Create a const iterator.

The created iterator can only be used to read its referenced data element. Can only be called when using a const reference to the container object. The parameters have identical meanings and usage to those of the other non-const begin function.

Parameters**directdb_get**

Same as that of `begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

bulkretrieval

Same as that of `begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

Return Value

The created const iterator.

See Also

`begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

Class

[db_vector](#)

end

Function Details

```
iterator end()
```

Create an open boundary iterator.

Return Value

Returns an invalid iterator denoting the position after the last valid element of the container.

```
const_iterator end() const
```

Create an open boundary iterator.

Return Value

Returns an invalid const iterator denoting the position after the last valid element of the container.

Class

[db_vector](#)

rbegin

Function Details

```
reverse_iterator rbegin(ReadModifyWriteOption rmw=  
    ReadModifyWriteOption::no_read_modify_write(), bool readonly=false,  
    BulkRetrievalOption bulk_read=BulkRetrievalOption::no_bulk_retrieval(),  
    bool directdb_get=true)
```

Create a reverse iterator.

This function creates a reverse iterator initialized to sit on the last element in the underlying database, and can be used to read/write. The meaning and usage of its parameters are identical to the above `begin` function.

Parameters

directdb_get

Same as that of `begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

bulk_read

Same as that of `begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

rmw

Same as that of `begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

readonly

Same as that of `begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

Return Value

The created iterator.

See Also

`begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

```
const_reverse_iterator rbegin(BulkRetrievalOption bulkretrieval=  
    BulkRetrievalOption(BulkRetrievalOption::no_bulk_retrieval()),  
    bool directdb_get=true) const
```

Create a const reverse iterator.

This function creates a const reverse iterator initialized to sit on the last element in the backing database, and can only read the element, it is only available to const [db_vector](#) containers. The meaning and usage of its parameters are identical as above.

Parameters

directdb_get

Same as that of `begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

bulkretrieval

Same as that of `begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

Return Value

The created iterator.

See Also

`begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

Class

[db_vector](#)

rend

Function Details

```
reverse_iterator rend()
```

Create an open boundary iterator.

Return Value

Returns an invalid iterator denoting the position before the first valid element of the container.

```
const_reverse_iterator rend() const
```

Create an open boundary iterator.

Return Value

Returns an invalid const iterator denoting the position before the first valid element of the container.

Class

[db_vector](#)

max_size

Function Details

```
size_type max_size() const
```

Get max size.

The returned size is not the actual limit of database. See the Berkeley DB limits to get real max size.

Return Value

A meaningless huge number.

Group: Huge return

These two functions return 2^{30} , denoting a huge number that does not overflow, because dbstl does not have to manage memory space.

But the return value is not the real limit, see the Berkeley DB database limits for the limits.

Class

[db_vector](#)

capacity

Function Details

```
size_type capacity() const
```

Get capacity.

Group: Huge return

These two functions return 2^{30} , denoting a huge number that does not overflow, because `dbstl` does not have to manage memory space.

But the return value is not the real limit, see the Berkeley DB database limits for the limits.

Class

[db_vector](#)

operator[]

Function Details

```
reference operator[](index_type n)
```

Index operator, can act as both a left value and a right value.

Parameters

n

The valid index of the vector.

Return Value

The reference to the element at specified position.

See Also

[http://www.cplusplus.com/reference/stl/vector/operator\[\].html](http://www.cplusplus.com/reference/stl/vector/operator[].html)

```
const_reference operator[](index_type n) const
```

Read only index operator.

Only used as a right value, no need for assignment capability. The return value can't be used to update the element.

Parameters

n

The valid index of the vector.

Return Value

The const reference to the element at specified position.

See Also

[http://www.cplusplus.com/reference/stl/vector/operator\[\].html](http://www.cplusplus.com/reference/stl/vector/operator[].html)

Group: Element access functions.

The operator[] and [at\(\)](#) only come from std::vector and std::deque, If you are using [db_vector](#) as std::list, you don't have to set DB_RENUMBER flag to the backing database handle, and you get better performance, but at the same time you can't use these functions.

Otherwise if you have set the DB_RENUMBER flag to the backing database handle, you can use this function though it is an `std::list` equivalent.

Class

[db_vector](#)

at

Function Details

```
reference at(index_type n)
```

Index function.

Parameters

n

The valid index of the vector.

Return Value

The reference to the element at specified position, can act as both a left value and a right value.

See Also

<http://www.cplusplus.com/reference/stl/vector/at.html>

```
const_reference at(index_type n) const
```

Read only index function.

Only used as a right value, no need for assignment capability. The return value can't be used to update the element.

Parameters

n

The valid index of the vector.

Return Value

The const reference to the element at specified position.

See Also

<http://www.cplusplus.com/reference/stl/vector/at.html>

Group: Element access functions.

The operator[] and [at\(\)](#) only come from std::vector and std::deque, If you are using [db_vector](#) as std::list, you don't have to set DB_RENUMBER flag to the backing database handle, and you get better performance, but at the same time you can't use these functions.

Otherwise if you have set the DB_RENUMBER flag to the backing database handle, you can use this function though it is an `std::list` equivalent.

Class

[db_vector](#)

front

Function Details

```
reference front()
```

Return a reference to the first element.

Return Value

Return a reference to the first element.

See Also

<http://www.cplusplus.com/reference/stl/vector/front.html>

```
const_reference front() const
```

Return a const reference to the first element.

The return value can't be used to update the element.

Return Value

Return a const reference to the first element.

See Also

<http://www.cplusplus.com/reference/stl/vector/front.html>

Group: Element access functions.

The operator[] and [at\(\)](#) only come from std::vector and std::deque, If you are using [db_vector](#) as std::list, you don't have to set DB_RENUMBER flag to the backing database handle, and you get better performance, but at the same time you can't use these functions.

Otherwise if you have set the DB_RENUMBER flag to the backing database handle, you can use this function though it is an std::list equivalent.

Class

[db_vector](#)

back

Function Details

```
reference back()
```

Return a reference to the last element.

Return Value

Return a reference to the last element.

See Also

<http://www.cplusplus.com/reference/stl/vector/back.html>

```
const_reference back() const
```

Return a reference to the last element.

The return value can't be used to update the element.

Return Value

Return a reference to the last element.

See Also

<http://www.cplusplus.com/reference/stl/vector/back.html>

Group: Element access functions.

The operator[] and [at\(\)](#) only come from std::vector and std::deque, If you are using [db_vector](#) as std::list, you don't have to set DB_RENUMBER flag to the backing database handle, and you get better performance, but at the same time you can't use these functions.

Otherwise if you have set the DB_RENUMBER flag to the backing database handle, you can use this function though it is an std::list equivalent.

Class

[db_vector](#)

operator==

Function Details

```
bool operator==(const db_vector< T2,  
                T3 > &v2) const
```

Container equality comparison operator.

This function supports auto commit.

Parameters

v2

The vector to compare against.

Return Value

Compare two vectors, return true if they have identical sequences of elements, otherwise return false.

```
bool operator==(const self &v2) const
```

Container equality comparison operator.

This function supports auto commit.

Return Value

Compare two vectors, return true if they have identical elements, otherwise return false.

Group: Compare functions.

<http://www.sgi.com/tech/stl/Vector.html>

Class

[db_vector](#)

operator!=

Function Details

```
bool operator!=(const db_vector< T2,  
                T3 > &v2) const
```

Container in-equality comparison operator.

This function supports auto commit.

Parameters

v2

The vector to compare against.

Return Value

Returns false if elements in each slot of both containers equal; Returns true otherwise.

```
bool operator!=(const self &v2) const
```

Container in-equality comparison operator.

This function supports auto commit.

Parameters

v2

The vector to compare against.

Return Value

Returns false if elements in each slot of both containers equal; Returns true otherwise.

Group: Compare functions.

<http://www.sgi.com/tech/stl/Vector.html>

Class

[db_vector](#)

operator<

Function Details

```
bool operator<(const self &v2) const
```

Container less than comparison operator.

This function supports auto commit.

Parameters

v2

The container to compare against.

Return Value

Compare two vectors, return true if this is less than v2, otherwise return false.

Group: Compare functions.

<http://www.sgi.com/tech/stl/Vector.html>

Class

[db_vector](#)

assign

Function Details

```
void assign(InputIterator first, InputIterator last,
            bool b_truncate=true)
```

Assign a range [first, last) to this container.

Parameters

b_truncate

See its member group doc for details.

last

The range open boundary.

first

The range closed boundary.

```
void assign(const_iterator first, const_iterator last,
            bool b_truncate=true)
```

Assign a range [first, last) to this container.

Parameters

b_truncate

See its member group doc for details.

last

The range open boundary.

first

The range closed boundary.

```
void assign(size_type n, const T &u,
            bool b_truncate=true)
```

Assign n number of elements of value u into this container.

Parameters

b_truncate

See its member group doc for details. This function supports auto commit.

u

The value of elements to insert.

n

The number of elements in this container after the call.

Group: Assign functions

See the function documentation for the correct usage of b_truncate parameter.

The following four member functions have default parameter b_truncate, because they require all key/data pairs in the database be deleted before the real operation, and by default we use Db::truncate to truncate the database rather than delete the key/data pairs one by one, but Db::truncate requires no open cursors on the database handle, and the four member functions will close any open cursors of backing database handle in current thread, but can do nothing to cursors of other threads opened from the same database handle. So you must make sure there are no open cursors of the database handle in any other threads. On the other hand, users can specify "false" to the b_truncate parameter and thus the key/data pairs will be deleted one by one. Other than that, they have identical behaviors as their counterparts in std::vector.

<http://www.cplusplus.com/reference/stl/vector/assign.html>

Class

[db_vector](#)

push_front

Function Details

```
void push_front(const T &x)
```

Push an element *x* into the vector from front.

Parameters

x

The element to push into this vector. This function supports auto commit.

Group: Functions specific to deque and list

These functions come from `std::list` and `std::deque`, and have identical behaviors to their counterparts in `std::list/stddeque`.

http://www.cplusplus.com/reference/stl/deque/pop_front.html

http://www.cplusplus.com/reference/stl/deque/push_front.html

Class

[db_vector](#)

pop_front

Function Details

```
void pop_front()
```

Pop out the front element from the vector.

This function supports auto commit.

Group: Functions specific to deque and list

These functions come from `std::list` and `std::deque`, and have identical behaviors to their counterparts in `std::list/stddeque`.

http://www.cplusplus.com/reference/stl/deque/pop_front.html
http://www.cplusplus.com/reference/stl/deque/push_front.html

Class

[db_vector](#)

insert

Function Details

```
iterator insert(iterator pos,  
               const T &x)
```

Insert x before position pos.

Parameters

x

The element to insert.

pos

The position before which to insert.

```
void insert(iterator pos, size_type n,  
           const T &x)
```

Insert n number of elements x before position pos.

Parameters

x

The element to insert.

pos

The position before which to insert.

n

The number of elements to insert.

```
void insert(iterator pos, InputIterator first,  
           InputIterator last)
```

Range insertion.

Insert elements in range [first, last) into this vector before position pos.

Parameters**last**

The open boundary of the range.

pos

The position before which to insert.

first

The closed boundary of the range.

```
void insert(iterator pos, const_iterator first,  
            const_iterator last)
```

Range insertion.

Insert elements in range [first, last) into this vector before position pos.

Parameters**last**

The open boundary of the range.

pos

The position before which to insert.

first

The closed boundary of the range.

Group: Insert functions

The iterator pos in the functions must be a read-write iterator, can't be read only.

<http://www.cplusplus.com/reference/stl/vector/insert.html>

Class

[db_vector](#)

erase

Function Details

```
iterator erase(iterator pos)
```

Erase element at position pos.

Parameters

pos

The valid position in the container's range to erase.

Return Value

The next position after the erased element.

```
iterator erase(iterator first,  
              iterator last)
```

Erase elements in range [first, last).

Parameters

last

The open boundary of the range.

first

The closed boundary of the range.

Return Value

The next position after the erased elements.

Group: Erase functions

The iterator pos in the functions must be a read-write iterator, can't be read only.

<http://www.cplusplus.com/reference/stl/vector/erase.html>

Class

[db_vector](#)

remove

Function Details

```
void remove(const T &value)
```

Remove all elements whose values are "value" from the list.

This function supports auto commit.

Parameters

value

The target value to remove.

See Also

<http://www.cplusplus.com/reference/stl/list/remove/>

Group: **std::list** specific functions

<http://www.cplusplus.com/reference/stl/list/>

Class

[db_vector](#)

remove_if

Function Details

```
void remove_if(Predicate pred)
```

Remove all elements making "pred" return true.

This function supports auto commit.

Parameters

pred

The binary predicate judging elements in this list.

See Also

http://www.cplusplus.com/reference/stl/list/remove_if/

Group: std::list specific functions

<http://www.cplusplus.com/reference/stl/list/>

Class

[db_vector](#)

merge

Function Details

```
void merge(self &x)
```

Merge content with another container.

This function supports auto commit.

Parameters

x

The other list to merge with.

See Also

<http://www.cplusplus.com/reference/stl/list/merge/>

```
void merge(self &x,  
           Compare comp)
```

Merge content with another container.

This function supports auto commit.

Parameters

x

The other list to merge with.

comp

The compare function to determine insertion position.

See Also

<http://www.cplusplus.com/reference/stl/list/merge/>

Group: **std::list** specific functions

<http://www.cplusplus.com/reference/stl/list/>

Class

[db_vector](#)

unique

Function Details

```
void unique()
```

Remove consecutive duplicate values from this list.

This function supports auto commit.

See Also

<http://www.cplusplus.com/reference/stl/list/unique/>

```
void unique(BinaryPredicate binary_pred)
```

Remove consecutive duplicate values from this list.

This function supports auto commit.

Parameters

binary_pred

The compare predicate to determine uniqueness.

See Also

<http://www.cplusplus.com/reference/stl/list/unique/>

Group: **std::list** specific functions

<http://www.cplusplus.com/reference/stl/list/>

Class

[db_vector](#)

sort

Function Details

```
void sort()
```

Sort this list.

This function supports auto commit.

See Also

<http://www.cplusplus.com/reference/stl/list/sort/>

```
void sort(Compare comp)
```

Sort this list.

This function supports auto commit.

Parameters

comp

The compare operator to determine element order.

See Also

<http://www.cplusplus.com/reference/stl/list/sort/>

Group: **std::list** specific functions

<http://www.cplusplus.com/reference/stl/list/>

Class

[db_vector](#)

reverse

Function Details

```
void reverse()
```

Reverse this list.

This function supports auto commit.

See Also

<http://www.cplusplus.com/reference/stl/list/reverse/>

Group: **std::list** specific functions

<http://www.cplusplus.com/reference/stl/list/>

Class

[db_vector](#)

splice

Function Details

```
void splice(iterator position,  
            self &x)
```

Moves elements from list x into this list.

Moves all elements in list x into this list container at the specified position, effectively inserting the specified elements into the container and removing them from x. This function supports auto commit.

Parameters

position

Position within the container where the elements of x are inserted.

x

The other list container to splice from.

See Also

<http://www.cplusplus.com/reference/stl/list/splice/>

```
void splice(iterator position, self &x,  
            iterator i)
```

Moves elements from list x into this list.

Moves elements at position i of list x into this list container at the specified position, effectively inserting the specified elements into the container and removing them from x. This function supports auto commit.

Parameters

i

The position of element in x to move into this list.

position

Position within the container where the elements of x are inserted.

x

The other list container to splice from.

See Also

<http://www.cplusplus.com/reference/stl/list/splice/>

```
void splice(iterator position, self &x, iterator first,
            iterator last)
```

Moves elements from list x into this list.

Moves elements in range [first, last) of list x into this list container at the specified position, effectively inserting the specified elements into the container and removing them from x. This function supports auto commit.

Parameters**position**

Position within the container where the elements of x are inserted.

first

The range's closed boundary.

last

The range's open boundary.

x

The other list container to splice from.

See Also

<http://www.cplusplus.com/reference/stl/list/splice/>

Group: std::list specific functions

<http://www.cplusplus.com/reference/stl/list/>

Class

[db_vector](#)

size

Function Details

```
size_type size() const
```

Return the number of elements in this container.

See Also

<http://www.cplusplus.com/reference/stl/vector/size.html>

Class

[db_vector](#)

empty

Function Details

```
bool empty() const
```

Returns whether this container is empty.

Return Value

True if empty, false otherwise.

Class

[db_vector](#)

db_vector

Function Details

```
db_vector(Db *dbp=NULL,  
          DbEnv *penv=NULL)
```

Constructor.

Note that we do not need an allocator in db-stl container, but we need backing up Db* and DbEnv*, and we have to verify that the passed in bdb handles are valid for use by the container class. See class detail for handle requirement.

Parameters

dbp

The same as that of [db_container\(Db*, DbEnv*\)](#) ;

penv

The same as that of [db_container\(Db*, DbEnv*\)](#) ;

See Also

[db_container\(Db*, DbEnv*\)](#) ;

```
db_vector(size_type n, const T &val=T(), Db *dbp=NULL,  
          DbEnv *penv=NULL)
```

Constructor.

This function supports auto commit. Insert n elements of T type into the database, the value of the elements is the default value or user set value. See class detail for handle requirement.

Parameters

dbp

The same as that of [db_container\(Db*, DbEnv*\)](#) ;

penv

The same as that of [db_container\(Db*, DbEnv*\)](#) ;

val

The value of elements to insert.

n

The number of elements to insert.

See Also

[db_vector\(Db*, DbEnv*\)](#) ; [db_container\(Db*, DbEnv*\)](#) ;

```
db_vector(const self &x)
```

Copy constructor.

This function supports auto commit. Insert all elements in x into this container.

See Also

[db_container\(const db_container&\)](#)

```
db_vector(Db *dbp, DbEnv *penv, InputIterator first,
          InputIterator last)
```

Insert a range of elements into this container.

The range is [first, last), which contains elements that can be converted to type T automatically. See class detail for handle requirement.

Parameters**dbp**

The same as that of [db_container\(Db*, DbEnv*\)](#) ;

first

Range closed boundary.

last

Range open boundary.

penv

The same as that of [db_container\(Db*, DbEnv*\)](#) ;

See Also

[db_vector\(Db*, DbEnv*\)](#) ;

```
db_vector(const_iterator first, const_iterator last, Db *dbp=NULL,
```

```
DbEnv *penv=NULL)
```

Range constructor.

This function supports auto commit. Insert the range of elements in [first, last) into this container. See class detail for handle requirement.

Parameters

dbp

The same as that of [db_container\(Db*, DbEnv*\)](#) ;

first

Range closed boundary.

last

Range open boundary.

penv

The same as that of [db_container\(Db*, DbEnv*\)](#) ;

See Also

[db_vector\(Db*, DbEnv*\)](#) ;

Class

[db_vector](#)

~db_vector

Function Details

```
virtual ~db_vector()
```

Class

[db_vector](#)

operator=

Function Details

```
const self& operator=(const self &x)
```

Container assignment operator.

This function supports auto commit. This [db_vector](#) is assumed to be valid for use, only copy content of x into this container.

Parameters

x

The right value container.

Return Value

The container x's reference.

Class

[db_vector](#)

resize

Function Details

```
void resize(size_type n,  
            T t=T())
```

Resize this container to specified size *n*, insert values *t* if need to enlarge the container.

This function supports auto commit.

Parameters

t

The value to insert when enlarging the container.

n

The number of elements in this container after the call.

See Also

<http://www.cplusplus.com/reference/stl/vector/resize.html>

Class

[db_vector](#)

reserve

Function Details

```
void reserve(size_type)
```

Reserve space.

The vector is backed by Berkeley DB, we always have enough space. This function does nothing, because dbstdl does not have to manage memory space.

Class

[db_vector](#)

push_back

Function Details

```
void push_back(const T &x)
```

Push back an element into the vector.

This function supports auto commit.

Parameters

x

The value of element to push into this vector.

See Also

http://www.cplusplus.com/reference/stl/vector/push_back.html

Class

[db_vector](#)

pop_back

Function Details

```
void pop_back()
```

Pop out last element from the vector.

This function supports auto commit.

See Also

http://www.cplusplus.com/reference/stl/vector/pop_back.html

Class

[db_vector](#)

swap

Function Details

```
void swap(self &vec)
```

Swap content with another vector vec.

Parameters

vec

The other vector to swap content with. This function supports auto commit.

See Also

<http://www.cplusplus.com/reference/stl/vector/swap.html>

Class

[db_vector](#)

clear

Function Details

```
void clear(bool b_truncate=true)
```

Remove all elements of the vector, make it an empty vector.

This function supports auto commit.

Parameters

b_truncate

Same as that of [db_vector::assign\(\)](#) .

See Also

<http://www.cplusplus.com/reference/stl/vector/clear.html>

Class

[db_vector](#)

Chapter 5. db_map

db_map

[db_map](#) has identical methods to `std::map` and the semantics for each method is identical to its `std::map` counterpart, except that it stores data into underlying Berkeley DB btree or hash database.

Passing a database handle of btree or hash type creates a [db_map](#) equivalent to `std::map` and `std::hashmap` respectively. Database(*dbp*) and environment(*penv*) handle requirement(applyes to all constructors in this class template): 0. The *dbp* is opened inside the *penv* environment. Either one of the two handles can be NULL. If *dbp* is NULL, an anonymous database is created by `dbstl`. 1. Database type of *dbp* should be `DB_BTREE` or `DB_HASH`. 2. No `DB_DUP` or `DB_DUPSORT` flag set in *dbp*. 3. No `DB_RECNUM` flag set in *dbp*. 4. No `DB_TRUNCATE` specified in *dbp*'s database open flags. 5. `DB_THREAD` must be set if you are sharing the *dbp* across multiple threads directly, or indirectly by sharing the container object across multiple threads.

See Also

[db_container](#) [db_container\(Db*, DbEnv*\)](#) [db_container\(const db_container&\)](#)

Class Template Parameters

kdt

The key data type.

ddt

The data data type. [db_map](#) stores key/data pairs.

value_type_sub

Do not specify anything if *ddt* type is a class/struct type; Otherwise, specify `ElementHolder<ddt>` to it.

iterator_t

Never specify anything to this type parameter. It is only used internally.

Public Members

| Member | Description |
|-------------------------|--|
| db_map | Create a <code>std::map</code> / <code>hash_map</code> equivalent associative container. |
| ~db_map | |
| insert | Insert a single key/data pair if the key is not in the container. |

| Member | Description |
|------------------------------|--|
| begin | Begin a read-write or readonly iterator which sits on the first key/data pair of the database. |
| end | Create an open boundary iterator. |
| rbegin | Begin a read-write or readonly reverse iterator which sits on the first key/data pair of the database. |
| rend | Create an open boundary iterator. |
| is_hash | Get container category. |
| bucket_count | Only for std::hash_map, return number of hash bucket in use. |
| size | This function supports auto commit. |
| max_size | Get max size. |
| empty | Returns whether this container is empty. |
| erase | Erase a key/data pair at specified position. |
| find | Find the key/data pair with specified key x. |
| lower_bound | Find the greatest key less than or equal to x. |
| equal_range | Find the range within which all keys equal to specified key x. |
| count | Count the number of key/data pairs having specified key x. |
| upper_bound | Find the least key greater than x. |
| key_eq | Function to get key compare functor. |
| hash_funct | Function to get hash key generating functor. |
| value_comp | Function to get value compare functor. |
| key_comp | Function to get key compare functor. |
| operator= | Container content assignment operator. |
| operator[] | Retrieve data element by key. |
| swap | Swap content with container mp. |
| clear | Clear contents in this container. |
| operator== | Map content equality comparison operator. |
| operator!= | Container unequality comparison operator. |

Group

[dbstl container classes](#)

db_map

Function Details

```
db_map(Db *dbp=NULL,  
       DbEnv *envp=NULL)
```

Create a `std::map/hash_map` equivalent associative container.

See the handle requirement in class details to pass correct database/environment handles.

Parameters

dbp

The database handle.

envp

The database environment handle.

See Also

[db_container\(Db*, DbEnv*\)](#)

```
db_map(Db *dbp, DbEnv *envp, InputIterator first,  
       InputIterator last)
```

Iteration constructor.

Iterates between first and last, setting a copy of each of the sequence of elements as the content of the container object. Create a `std::map/hash_map` equivalent associative container. Insert a range of elements into the database. The range is `[first, last)`, which contains elements that can be converted to type `ddt` automatically. See the handle requirement in class details to pass correct database/environment handles. This function supports auto commit.

Parameters

dbp

The database handle.

envp

The database environment handle.

last

The open boundary of the range.

first

The closed boundary of the range.

See Also

[db_container\(Db*, DbEnv*\)](#)

```
db_map(const db_map< kdt, ddt, value_type_sub,
        iterator > &x)
```

Copy constructor.

Create an database and insert all key/data pairs in x into this container. x's data members are not copied. This function supports auto commit.

Parameters**x**

The other container to initialize this container.

See Also

[db_container\(const db_container&\)](#)

Class

[db_map](#)

~db_map

Function Details

```
virtual ~db_map()
```

Class

[db_map](#)

insert

Function Details

```
insert(const value_type &x)
```

Insert a single key/data pair if the key is not in the container.

Parameters

x

The key/data pair to insert.

Return Value

A pair P, if insert OK, i.e. the inserted key wasn't in the container, P.first will be the iterator sitting on the inserted key/data pair, and P.second is true; otherwise P.first is an invalid iterator and P.second is false.

```
iterator insert(iterator position,  
               const value_type &x)
```

Insert with hint position.

We ignore the hint position because Berkeley DB knows better where to insert.

Parameters

position

The hint position.

x

The key/data pair to insert.

Return Value

The iterator sitting on the inserted key/data pair, or an invalid iterator if the key was already in the container.

```
void insert(const db_map_base_iterator< kdt, realddt, ddt > &first,  
           const db_map_base_iterator< kdt, realddt,  
           ddt > &last)
```

Range insertion.

Insert a range [first, last) of key/data pairs into this container.

Parameters

last

The open boundary of the range.

first

The closed boundary of the range.

```
void insert(InputIterator first,
            InputIterator last)
```

Range insertion.

Insert a range [first, last) of key/data pairs into this container.

Parameters

last

The open boundary of the range.

first

The closed boundary of the range.

Group: Insert Functions

They have similar usage as their C++ STL equivalents.

Note that when secondary index is enabled, each [db_container](#) can create a [db_multimap](#) secondary container, but the insert function is not functional for secondary containers.

<http://www.cplusplus.com/reference/stl/map/insert/>

Class

[db_map](#)

begin

Function Details

```
iterator begin(ReadModifyWriteOption rmw=
    ReadModifyWriteOption::no_read_modify_write(), bool readonly=false,
    BulkRetrievalOption bulkretrieval=BulkRetrievalOption::no_bulk_retrieval(),
    bool directdb_get=true)
```

Begin a read-write or readonly iterator which sits on the first key/data pair of the database.

Parameters

directdb_get

Same as that of `db_vector::begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

readonly

Same as that of `db_vector::begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

rmw

Same as that of `db_vector::begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

bulkretrieval

Same as that of `db_vector::begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

Return Value

The created iterator.

See Also

[db_vector::begin](#) ([ReadModifyWriteOption](#) , bool, [BulkRetrievalOption](#) , bool)

```
const_iterator begin(BulkRetrievalOption bulkretrieval=
    BulkRetrievalOption::no_bulk_retrieval(),
    bool directdb_get=true) const
```

Begin a read-only iterator.

Parameters

directdb_get

Same as that of `begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

bulkretrieval

Same as that of `begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

Return Value

The created const iterator.

See Also

[db_vector::begin](#) (ReadModifyWrite, bool, [BulkRetrievalOption](#) , bool);

Group: Iterator Functions

The parameters in begin functions of this group have identical meaning to thoes in [db_vector::begin](#) , refer to those functions for details.

[db_vector::begin\(\)](#)

Class

[db_map](#)

end

Function Details

```
iterator end()
```

Create an open boundary iterator.

Return Value

Returns an invalid iterator denoting the position after the last valid element of the container.

See Also

[db_vector::end\(\)](#)

```
const_iterator end() const
```

Create an open boundary iterator.

Return Value

Returns an invalid const iterator denoting the position after the last valid element of the container.

See Also

[db_vector::end\(\) const](#)

Group: Iterator Functions

The parameters in begin functions of this group have identical meaning to thoes in [db_vector::begin](#) , refer to those functions for details.

[db_vector::begin\(\)](#)

Class

[db_map](#)

rbegin

Function Details

```
reverse_iterator rbegin(ReadModifyWriteOption rmw=  
    ReadModifyWriteOption::no_read_modify_write(), bool read_only=false,  
    BulkRetrievalOption bulkretrieval=BulkRetrievalOption::no_bulk_retrieval(),  
    bool directdb_get=true)
```

Begin a read-write or readonly reverse iterator which sits on the first key/data pair of the database.

Parameters

directdb_get

Same as that of `db_vector::begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

read_only

Same as that of `db_vector::begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

rmw

Same as that of `db_vector::begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

bulkretrieval

Same as that of `db_vector::begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

Return Value

The created iterator.

See Also

[db_vector::begin](#) ([ReadModifyWriteOption](#) , bool, [BulkRetrievalOption](#) , bool)

[db_vector::begin](#) (ReadModifyWrite, bool, [BulkRetrievalOption](#) , bool);

```
const_reverse_iterator rbegin(BulkRetrievalOption bulkretrieval=  
    BulkRetrievalOption::no_bulk_retrieval(),  
    bool directdb_get=true) const
```

Begin a read-only reverse iterator.

Parameters**directdb_get**

Same as that of `begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

bulkretrieval

Same as that of `begin(ReadModifyWrite, bool, BulkRetrievalOption, bool);`

Return Value

The created const iterator.

See Also

[db_vector::begin](#) (ReadModifyWrite, bool, [BulkRetrievalOption](#) , bool);

Group: Iterator Functions

The parameters in begin functions of this group have identical meaning to thoes in [db_vector::begin](#) , refer to those functions for details.

[db_vector::begin\(\)](#)

Class

[db_map](#)

rend

Function Details

```
reverse_iterator rend()
```

Create an open boundary iterator.

Return Value

Returns an invalid iterator denoting the position before the first valid element of the container.

See Also

[db_vector::rend\(\)](#)

```
const_reverse_iterator rend() const
```

Create an open boundary iterator.

Return Value

Returns an invalid const iterator denoting the position before the first valid element of the container.

See Also

[db_vector::rend\(\) const](#)

Group: Iterator Functions

The parameters in begin functions of this group have identical meaning to thoes in [db_vector::begin](#) , refer to those functions for details.

[db_vector::begin\(\)](#)

Class

[db_map](#)

is_hash

Function Details

```
bool is_hash() const
```

Get container category.

Determines whether this container object is a `std::map<>` equivalent (when returns false) or that of `hash_map<>` class (when returns true). This method is not in `stl`, but it may be called by users because some operations are not supported by both type (`map/hash_map`) of containers, you need to call this function to distinguish the two types. `dbstl` will not stop you from calling the wrong methods of this class.

Return Value

Returns true if this container is a hash container based on a Berkeley DB hash database; returns false if it is based on a Berkeley DB btree database.

Group: Metadata Functions

These functions return metadata about the container.

Class

[db_map](#)

bucket_count

Function Details

```
size_type bucket_count() const
```

Only for `std::hash_map`, return number of hash bucket in use.

This function supports auto commit.

Return Value

The number of hash buckets of the database.

Group: Metadata Functions

These functions return metadata about the container.

Class

[db_map](#)

size

Function Details

```
size_type size(bool accurate=true) const
```

This function supports auto commit.

Parameters

accurate

This function uses database's statistics to get the number of key/data pairs. The statistics mechanism will either scan the whole database to find the accurate number or use the number of last accurate scanning, and thus much faster. If there are millions of key/data pairs, the scanning can take some while, so in that case you may want to set the "accurate" parameter to false.

Return Value

Return the number of key/data pairs in the container.

Group: Metadata Functions

These functions return metadata about the container.

Class

[db_map](#)

max_size

Function Details

```
size_type max_size() const
```

Get max size.

The returned size is not the actual limit of database. See the Berkeley DB limits to get real max size.

Return Value

A meaningless huge number.

See Also

[db_vector::max_size\(\)](#)

Group: Metadata Functions

These functions return metadata about the container.

Class

[db_map](#)

empty

Function Details

```
bool empty() const
```

Returns whether this container is empty.

This function supports auto commit.

Return Value

True if empty, false otherwise.

Group: Metadata Functions

These functions return metadata about the container.

Class

[db_map](#)

erase

Function Details

```
void erase(iterator pos)
```

Erase a key/data pair at specified position.

Parameters

pos

An valid iterator of this container to erase.

```
size_type erase(const key_type &x)
```

Erase elements by key.

All key/data pairs with specified key x will be removed from underlying database. This function supports auto commit.

Parameters

x

The key to remove from the container.

Return Value

The number of key/data pairs removed.

```
void erase(iterator first,  
           iterator last)
```

Range erase.

Erase all key/data pairs within the valid range [first, last).

Parameters

last

The open boundary of the range.

first

The closed boundary of the range.

Group: Erase Functions

<http://www.cplusplus.com/reference/stl/map/erase/>

Class

[db_map](#)

find

Function Details

```
const_iterator find(const key_type &x) const
```

Find the key/data pair with specified key x.

Parameters

x

The target key to find.

Return Value

The valid const iterator sitting on the key x, or an invalid one.

See Also

<http://www.cplusplus.com/reference/stl/map/find/>

```
iterator find(const key_type &x,  
             bool readonly=false)
```

Find the key/data pair with specified key x.

Parameters

x

The target key to find.

readonly

Whether the returned iterator is readonly.

Return Value

The valid iterator sitting on the key x, or an invalid one.

See Also

<http://www.cplusplus.com/reference/stl/map/find/>

Group: Searching Functions

The following functions are returning iterators, and they by default return read-write iterators.

If you intend to use the returned iterator only to read, you should call the const version of each function using a const reference to this container. Using const iterators can potentially promote concurrency a lot. You can also set the readonly parameter to each non-const version of the functions to true if you don't use the returned iterator to write, which also promotes concurrency and overall performance.

Class

[db_map](#)

lower_bound

Function Details

```
const_iterator lower_bound(const key_type &x) const
```

Find the greatest key less than or equal to x.

Parameters

x

The target key to find.

Return Value

The valid const iterator sitting on the key, or an invalid one.

See Also

http://www.cplusplus.com/reference/stl/map/lower_bound/

```
iterator lower_bound(const key_type &x,  
    bool readonly=false)
```

Find the greatest key less than or equal to x.

Parameters

x

The target key to find.

readonly

Whether the returned iterator is readonly.

Return Value

The valid iterator sitting on the key, or an invalid one.

See Also

http://www.cplusplus.com/reference/stl/map/lower_bound/

Group: Searching Functions

The following functions are returning iterators, and they by default return read-write iterators.

If you intend to use the returned iterator only to read, you should call the const version of each function using a const reference to this container. Using const iterators can potentially promote concurrency a lot. You can also set the readonly parameter to each non-const version of the functions to true if you don't use the returned iterator to write, which also promotes concurrency and overall performance.

Class

[db_map](#)

equal_range

Function Details

```
equal_range(const key_type &x) const
```

Find the range within which all keys equal to specified key x.

Parameters

x

The target key to find.

Return Value

The range [first, last).

See Also

http://www.cplusplus.com/reference/stl/map/equal_range/

```
equal_range(const key_type &x,  
            bool readonly=false)
```

Find the range within which all keys equal to specified key x.

Parameters

x

The target key to find.

readonly

Whether the returned iterator is readonly.

Return Value

The range [first, last).

See Also

http://www.cplusplus.com/reference/stl/map/equal_range/

Group: Searching Functions

The following functions are returning iterators, and they by default return read-write iterators.

If you intend to use the returned iterator only to read, you should call the const version of each function using a const reference to this container. Using const iterators can potentially promote concurrency a lot. You can also set the readonly parameter to each non-const version of the functions to true if you don't use the returned iterator to write, which also promotes concurrency and overall performance.

Class

[db_map](#)

count

Function Details

```
size_type count(const key_type &x) const
```

Count the number of key/data pairs having specified key x.

Parameters

x

The key to count.

Return Value

The number of key/data pairs having x as key within the container.

See Also

<http://www.cplusplus.com/reference/stl/map/count/>

Group: Searching Functions

The following functions are returning iterators, and they by default return read-write iterators.

If you intend to use the returned iterator only to read, you should call the const version of each function using a const reference to this container. Using const iterators can potentially promote concurrency a lot. You can also set the readonly parameter to each non-const version of the functions to true if you don't use the returned iterator to write, which also promotes concurrency and overall performance.

Class

[db_map](#)

upper_bound

Function Details

```
const_iterator upper_bound(const key_type &x) const
```

Find the least key greater than x.

Parameters

x

The target key to find.

Return Value

The valid iterator sitting on the key, or an invalid one.

See Also

http://www.cplusplus.com/reference/stl/map/upper_bound/

```
iterator upper_bound(const key_type &x,  
    bool readonly=false)
```

Find the least key greater than x.

Parameters

x

The target key to find.

readonly

Whether the returned iterator is readonly.

Return Value

The valid iterator sitting on the key, or an invalid one.

See Also

http://www.cplusplus.com/reference/stl/map/upper_bound/

Group: Searching Functions

The following functions are returning iterators, and they by default return read-write iterators.

If you intend to use the returned iterator only to read, you should call the const version of each function using a const reference to this container. Using const iterators can potentially promote concurrency a lot. You can also set the readonly parameter to each non-const version of the functions to true if you don't use the returned iterator to write, which also promotes concurrency and overall performance.

Class

[db_map](#)

key_eq

Function Details

```
key_equal key_eq() const
```

Function to get key compare functor.

Used when this container is a hash_map, hash_multimap, hash_set or hash_multiset equivalent.

Return Value

[key_equal](#) type of compare functor.

See Also

http://www.sgi.com/tech/stl/hash_map.html

Class

[db_map](#)

hash_func

Function Details

```
hasher hash_func() const
```

Function to get hash key generating functor.

Used when this container is a hash_map, hash_multimap, hash_set or hash_multiset equivalent.

Return Value

The hash key generating functor.

See Also

http://www.sgi.com/tech/stl/hash_map.html

Class

[db_map](#)

value_comp

Function Details

```
value_compare value_comp() const
```

Function to get value compare functor.

Used when this container is a `std::map`, `std::multimap`, `std::set` or `std::multiset` equivalent.

Return Value

The value compare functor.

See Also

http://www.cplusplus.com/reference/stl/map/value_comp/

Class

[db_map](#)

key_comp

Function Details

```
key_compare key_comp() const
```

Function to get key compare functor.

Used when this container is a `std::map`, `std::multimap`, `std::set` or `std::multiset` equivalent.

Return Value

The key compare functor.

See Also

http://www.cplusplus.com/reference/stl/map/key_comp/

Class

[db_map](#)

operator=

Function Details

```
const self& operator=(const self &x)
```

Container content assignment operator.

This function supports auto commit.

Parameters

x

The other container whose key/data pairs will be inserted into this container. Old content in this containers are discarded.

See Also

<http://www.cplusplus.com/reference/stl/map/operator=/>

Class

[db_map](#)

operator[]

Function Details

```
data_type_wrap operator[](const key_type &x)
```

Retrieve data element by key.

This function returns an reference to the underlying data element of the specified key x. The returned object can be used to read or write the data element of the key/data pair. Do use a data_type_wrap of [db_map](#) or value_type::second_type(they are the same) type of variable to hold the return value of this function.

Parameters

x

The target key to get value from.

Return Value

Data element reference.

```
const ddt operator[](const key_type &x) const
```

Retrieve data element by key.

This function returns the value of the underlying data element of specified key x. You can only read the element, but unable to update the element via the return value of this function. And you need to use the container's const reference to call this method.

Parameters

x

The target key to get value from.

Return Value

Data element, read only, can't be used to modify it.

Class

[db_map](#)

swap

Function Details

```
void swap(db_map< kdt, ddt, value_type_sub > &mp,  
          bool b_truncate=true)
```

Swap content with container mp.

This function supports auto commit.

Parameters

b_truncate

See [db_vector::swap\(\)](#) for details.

mp

The container to swap content with.

See Also

<http://www.cplusplus.com/reference/stl/map/swap/> [db_vector::clear\(\)](#)

Class

[db_map](#)

clear

Function Details

```
void clear(bool b_truncate=true)
```

Clear contents in this container.

This function supports auto commit.

Parameters

b_truncate

See [db_vector::clear\(bool\)](#) for details.

See Also

[db_vector::clear\(bool\)](#)

Class

[db_map](#)

operator==

Function Details

```
bool operator==(const db_map< kdt, ddt,  
                value_type_sub > &m2) const
```

Map content equality comparison operator.

This function does not rely on key order. For a set of keys S1 in this container and another set of keys S2 of container m2, if set S1 contains S2 and S2 contains S1 (S1 equals to S2) and each data element of a key K in S1 from this container equals the data element of K in m2, the two db_map<> containers equal. Otherwise they are not equal.

Parameters

m2

The other container to compare against.

Return Value

Returns true if they have equal content, false otherwise.

Class

[db_map](#)

operator!=

Function Details

```
bool operator!=(const db_map< kdt, ddt,  
    value_type_sub > &m2) const
```

Container unequality comparison operator.

Parameters

m2

The container to compare against.

Return Value

Returns false if equal, true otherwise.

Class

[db_map](#)

Chapter 6. db_multimap

db_multimap

This class is the combination of `std::multimap` and `hash_multimap`.

By setting database handles as `DB_BTREE` or `DB_HASH` type respectively, you will be using an equivalent of `std::multimap` or `hash_multimap` respectively. Database(`dbp`) and environment(`penv`) handle requirement: The `dbp` handle must meet the following requirement: 1. Database type should be `DB_BTREE` or `DB_HASH`. 2. Either `DB_DUP` or `DB_DUPSORT` flag must be set. Note that so far Berkeley DB does not allow `DB_DUPSORT` be set and the database is storing identical key/data pairs, i.e. we can't store two (1, 2), (1, 2) pairs into a database D with `DB_DUPSORT` flag set, but only can do so with `DB_DUP` flag set; But we can store a (1, 2) pair and a (1, 3) pair into D with `DB_DUPSORT` flag set. So if your data set allows `DB_DUPSORT` flag, you should set it to gain a lot of performance promotion. 3. No `DB_RECNUM` flag set. 4. No `DB_TRUNCATE` specified in database open flags. 5. `DB_THREAD` must be set if you are sharing the database handle across multiple threads directly, or indirectly by sharing the container object across multiple threads.

See Also

[db_container](#) [db_map](#)

Class Template Parameters

kdt

The key data type.

ddt

The data data type. [db_multimap](#) stores key/data pairs.

value_type_sub

Do not specify anything if `ddt` type is a class/struct type; Otherwise, specify `ElementHolder<ddt>` to it.

iterator_t

Never specify anything to this type parameter. It is only used internally.

Public Members

| Member | Description |
|-----------------------------|--|
| insert | Range insertion. |
| erase | Erase elements by key. |
| equal_range | Find the range within which all keys equal to specified key x. |

| Member | Description |
|-------------------------------|---|
| equal_range_N | Find equal range and number of key/data pairs in the range. |
| count | Count the number of key/data pairs having specified key x. |
| upper_bound | Find the least key greater than x. |
| db_multimap | Constructor. |
| ~db_multimap | |
| operator= | Container content assignment operator. |
| swap | Swap content with another multimap container. |
| operator== | Returns whether the two containers have identical content. |
| operator!= | Container unequality comparison operator. |

Group[dbstl container classes](#)

insert

Function Details

```
void insert(InputIterator first,
            InputIterator last)
```

Range insertion.

Insert a range [first, last) of key/data pairs into this container.

Parameters

last

The open boundary of the range.

first

The closed boundary of the range.

```
void insert(const_iterator &first,
            const_iterator &last)
```

Range insertion.

Insert a range [first, last) of key/data pairs into this container.

Parameters

last

The open boundary of the range.

first

The closed boundary of the range.

```
iterator insert(const value_type &x)
```

Insert a single key/data pair if the key is not in the container.

Parameters

x

The key/data pair to insert.

Return Value

A pair P, if insert OK, i.e. the inserted key wasn't in the container, P.first will be the iterator sitting on the inserted key/data pair, and P.second is true; otherwise P.first is an invalid iterator and P.second is false.

Group: Insert Functions

<http://www.cplusplus.com/reference/stl/multimap/insert/>

Class

[db_multimap](#)

erase

Function Details

```
size_type erase(const key_type &x)
```

Erase elements by key.

All key/data pairs with specified key x will be removed from underlying database. This function supports auto commit.

Parameters

x

The key to remove from the container.

Return Value

The number of key/data pairs removed.

```
void erase(iterator pos)
```

Erase a key/data pair at specified position.

Parameters

pos

An valid iterator of this container to erase.

```
void erase(iterator first,  
           iterator last)
```

Range erase.

Erase all key/data pairs within the valid range [first, last).

Parameters

last

The open boundary of the range.

first

The closed boundary of the range.

Group: Erase Functions

<http://www.cplusplus.com/reference/stl/multimap/erase/>

Class

[db_multimap](#)

equal_range

Function Details

```
equal_range(const key_type &x) const
```

Find the range within which all keys equal to specified key x.

Parameters

x

The target key to find.

Return Value

The range [first, last).

See Also

http://www.cplusplus.com/reference/stl/multimap/equal_range/

```
equal_range(const key_type &x,  
            bool readonly=false)
```

Find the range within which all keys equal to specified key x.

Parameters

x

The target key to find.

readonly

Whether the returned iterator is readonly.

Return Value

The range [first, last).

See Also

http://www.cplusplus.com/reference/stl/multimap/equal_range/

Group: Searching Functions

See of db_map's searching functions group for details about iterator, function version and parameters.

[db_map](#)

Class

[db_multimap](#)

equal_range_N

Function Details

```
equal_range_N(const key_type &x,  
              size_t &nelem) const
```

Find equal range and number of key/data pairs in the range.

This function also returns the number of elements within the returned range via the out parameter nelem.

Parameters

x

The target key to find.

nelem

The output parameter to take back the number of key/data pair in the returned range.

See Also

http://www.cplusplus.com/reference/stl/multimap/equal_range/

```
equal_range_N(const key_type &x, size_t &nelem,  
              bool readonly=false)
```

Find equal range and number of key/data pairs in the range.

This function also returns the number of elements within the returned range via the out parameter nelem.

Parameters

x

The target key to find.

nelem

The output parameter to take back the number of key/data pair in the returned range.

readonly

Whether the returned iterator is readonly.

See Also

http://www.cplusplus.com/reference/stl/multimap/equal_range/

Group: Searching Functions

See of `db_map`'s searching functions group for details about iterator, function version and parameters.

[db_map](#)

Class

[db_multimap](#)

count

Function Details

```
size_type count(const key_type &x) const
```

Count the number of key/data pairs having specified key x.

Parameters

x

The key to count.

Return Value

The number of key/data pairs having x as key within the container.

See Also

<http://www.cplusplus.com/reference/stl/multimap/count/>

Group: Searching Functions

See of `db_map`'s searching functions group for details about iterator, function version and parameters.

[db_map](#)

Class

[db_multimap](#)

upper_bound

Function Details

```
const_iterator upper_bound(const key_type &x) const
```

Find the least key greater than x.

Parameters

x

The target key to find.

Return Value

The valid iterator sitting on the key, or an invalid one.

See Also

http://www.cplusplus.com/reference/stl/multimap/upper_bound/

```
iterator upper_bound(const key_type &x,  
    bool readonly=false)
```

Find the least key greater than x.

Parameters

x

The target key to find.

readonly

Whether the returned iterator is readonly.

Return Value

The valid iterator sitting on the key, or an invalid one.

See Also

http://www.cplusplus.com/reference/stl/multimap/upper_bound/

Group: Searching Functions

See of db_map's searching functions group for details about iterator, function version and parameters.

[db_map](#)

Class

[db_multimap](#)

db_multimap

Function Details

```
db_multimap(Db *dbp=NULL,  
            DbEnv *envp=NULL)
```

Constructor.

See class detail for handle requirement.

Parameters

dbp

The database handle.

envp

The database environment handle.

See Also

[db_map::db_map\(Db*, DbEnv*\)](#) [db_vector::db_vector\(Db*, DbEnv*\)](#)

```
db_multimap(Db *dbp, DbEnv *envp, InputIterator first,  
            InputIterator last)
```

Iteration constructor.

Iterates between first and last, setting a copy of each of the sequence of elements as the content of the container object. This function supports auto commit. See class detail for handle requirement.

Parameters

dbp

The database handle.

envp

The database environment handle.

last

The open boundary of the range.

first

The closed boundary of the range.

See Also

[db_map::db_map\(Db*, DbEnv*, InputIterator, InputIterator\)](#) [db_vector::db_vector\(Db*, DbEnv*\)](#)

```
db_multimap(const self &x)
```

Copy constructor.

Create an database and insert all key/data pairs in x into this container. x's data members are not copied. This function supports auto commit.

Parameters**x**

The other container to initialize this container.

See Also

[db_container\(const db_container&\)](#) [db_map\(const db_map&\)](#)

Class

[db_multimap](#)

~db_multimap

Function Details

```
virtual ~db_multimap()
```

Class

[db_multimap](#)

operator=

Function Details

```
const self& operator=(const self &x)
```

Container content assignment operator.

This function supports auto commit.

Parameters

x

The other container whose key/data pairs will be inserted into this container. Old content in this containers are discarded.

See Also

<http://www.cplusplus.com/reference/stl/multimap/operator=>

Class

[db_multimap](#)

swap

Function Details

```
void swap(db_multimap< kdt, ddt, value_type_sub > &mp,  
          bool b_truncate=true)
```

Swap content with another multimap container.

This function supports auto commit.

Parameters

b_truncate

See [db_map::swap\(\)](#) for details.

mp

The other container to swap content with.

See Also

[db_vector::clear\(\)](#)

Class

[db_multimap](#)

operator==

Function Details

```
bool operator==(const db_multimap< kdt, ddt,  
                value_type_sub > &m2) const
```

Returns whether the two containers have identical content.

This function does not rely on key order. For a set of keys *S1* in this container and another set of keys *S2* of container *m2*, if set *S1* contains *S2* and *S2* contains *S1* (*S1* equals to *S2*) and each set of data elements of any key *K* in *S1* from this container equals the set of data elements of *K* in *m2*, the two `db_multimap<>` containers equal. Otherwise they are not equal. Data element set comparison does not rely on order either.

Parameters

m2

The other container to compare against.

Return Value

Returns true if they are equal, false otherwise.

Class

[db_multimap](#)

operator!=

Function Details

```
bool operator!=(const db_multimap< kdt, ddt,  
    value_type_sub > &m2) const
```

Container unequality comparison operator.

Parameters

m2

The container to compare against.

Return Value

Returns false if equal, true otherwise.

Class

[db_multimap](#)

Chapter 7. db_set

db_set

This class is the combination of `std::set` and `hash_set`.

By setting database handles of `DB_BTREE` or `DB_HASH` type, you will be using an equivalent of `std::set` or `hash_set`. This container stores the key in the key element of a key/data pair in underlying database, and keeps the data element empty; Database and environment handle requirement: The same as that of [db_map](#).

See Also

[db_map](#) [db_container](#)

Class Template Parameters

kdt

The key data type.

value_type_sub

If `kdt` is a class/struct type, do not specify anything in this parameter; Otherwise specify `ElementHolder<kdt>`.

Public Members

| Member | Description |
|----------------------------|--|
| db_set | Create a <code>std::set</code> / <code>hash_set</code> equivalent associative container. |
| ~db_set | |
| insert | Insert a single key/data pair if the key is not in the container. |
| operator= | Container content assignment operator. |
| value_comp | Get value comparison functor. |
| swap | Swap content with another container. |
| operator== | Set content equality comparison operator. |
| operator!= | Unequality comparison operator. |

Group

[dbstl container classes](#)

db_set

Function Details

```
db_set(Db *dbp=NULL,  
       DbEnv *envp=NULL)
```

Create a `std::set/hash_set` equivalent associative container.

See the handle requirement in class details to pass correct database/environment handles.

Parameters

dbp

The database handle.

envp

The database environment handle.

See Also

[db_map\(Db*, DbEnv*\)](#) [db_container\(Db*, DbEnv*\)](#)

```
db_set(Db *dbp, DbEnv *envp, InputIterator first,  
       InputIterator last)
```

Iteration constructor.

Iterates between first and last, setting a copy of each of the sequence of elements as the content of the container object. Create a `std::set/hash_set` equivalent associative container. Insert a range of elements into the database. The range is `[first, last)`, which contains elements that can be converted to type `ddt` automatically. This function supports auto commit. See the handle requirement in class details to pass correct database/environment handles.

Parameters

dbp

The database handle.

envp

The database environment handle.

last

The open boundary of the range.

first

The closed boundary of the range.

See Also

[db_map\(Db*, DbEnv*, InputIterator, InputIterator\)](#)

```
db_set(const self &x)
```

Copy constructor.

Create an database and insert all key/data pairs in x into this container. x's data members are not copied. This function supports auto commit.

Parameters**x**

The other container to initialize this container.

See Also

[db_map\(const db_map&\) db_container\(const db_container&\)](#)

Class

[db_set](#)

~db_set

Function Details

```
virtual ~db_set()
```

Class

[db_set](#)

insert

Function Details

```
insert(const value_type &x)
```

Insert a single key/data pair if the key is not in the container.

Parameters

x

The key/data pair to insert.

Return Value

A pair P, if insert OK, i.e. the inserted key wasn't in the container, P.first will be the iterator sitting on the inserted key/data pair, and P.second is true; otherwise P.first is an invalid iterator and P.second is false.

```
void insert(const_iterator &first,  
            const_iterator &last)
```

Range insertion.

Insert a range [first, last) of key/data pairs into this container.

Parameters

last

The open boundary of the range.

first

The closed boundary of the range.

```
void insert(iterator &first,  
            iterator &last)
```

Range insertion.

Insert a range [first, last) of key/data pairs into this container.

Parameters**last**

The open boundary of the range.

first

The closed boundary of the range.

```
iterator insert(iterator position,
               const value_type &x)
```

Insert with hint position.

We ignore the hint position because Berkeley DB knows better where to insert.

Parameters**position**

The hint position.

x

The key/data pair to insert.

Return Value

The iterator sitting on the inserted key/data pair, or an invalid iterator if the key was already in the container.

```
void insert(InputIterator first,
            InputIterator last)
```

Range insertion.

Insert a range [first, last) of key/data pairs into this container.

Parameters**last**

The open boundary of the range.

first

The closed boundary of the range.

Group: Insert Functions

<http://www.cplusplus.com/reference/stl/set/insert/>

Class

[db_set](#)

operator=

Function Details

```
const self& operator=(const self &x)
```

Container content assignment operator.

This function supports auto commit.

Parameters

x

The other container whose key/data pairs will be inserted into this container. Old content in this containers are discarded.

Return Value

The container x.

See Also

<http://www.cplusplus.com/reference/stl/set/operator=/>

Class

[db_set](#)

value_comp

Function Details

```
value_compare value_comp() const
```

Get value comparison functor.

Return Value

The value comparison functor.

See Also

http://www.cplusplus.com/reference/stl/set/value_comp/

Class

[db_set](#)

swap

Function Details

```
void swap(db_set< kdt, value_type_sub > &mp,  
          bool b_truncate=true)
```

Swap content with another container.

This function supports auto commit.

Parameters

b_truncate

See [db_vector::swap](#) 's b_truncate parameter for details.

mp

The container to swap content with.

See Also

[db_map::swap\(\)](#) [db_vector::clear\(\)](#)

Class

[db_set](#)

operator==

Function Details

```
bool operator==(const db_set< kdt,  
                value_type_sub > &m2) const
```

Set content equality comparison operator.

Return if the two containers have identical content. This function does not rely on key order, it is doing a set equal comparison--- Two sets A and B are equal if and only if A contains B and B contains A.

Parameters

m2

The other container to compare against.

Return Value

Returns true if they have equal content, false otherwise.

Class

[db_set](#)

operator!=

Function Details

```
bool operator!=(const db_set< kdt,  
                value_type_sub > &m2) const
```

Unequality comparison operator.

Class

[db_set](#)

Chapter 8. db_multiset

db_multiset

This class is the combination of `std::multiset` and `hash_multiset`.

By setting database handles of `DB_BTREE` or `DB_HASH` type respectively, you will be using an equivalent of `std::multiset` or `hash_multiset` respectively. This container stores the key in the key element of a key/data pair in underlying database, and keep the data element empty; Database and environment handle requirement: The requirement to these handles is the same as that to [db_multimap](#) .

See Also

[db_multimap](#) [db_map](#) [db_container](#) [db_set](#)

Class Template Parameters

kdt

The key data type.

value_type_sub

If `kdt` is a class/struct type, do not specify anything in this parameter; Otherwise specify `ElementHolder<kdt>`.

Public Members

| Member | Description |
|------------------------------|--|
| db_multiset | Create a <code>std::multiset</code> / <code>hash_multiset</code> equivalent associative container. |
| ~db_multiset | |
| insert | Insert a single key if the key is not in the container. |
| erase | Erase elements by key. |
| operator= | Container content assignment operator. |
| swap | Swap content with another container. |
| operator== | Container content equality compare operator. |
| operator!= | Unequality comparison operator. |

Group

[dbstl container classes](#)

db_multiset

Function Details

```
db_multiset(Db *dbp=NULL,  
            DbEnv *envp=NULL)
```

Create a `std::multiset/hash_multiset` equivalent associative container.

See the handle requirement in class details to pass correct database/environment handles.

Parameters

dbp

The database handle.

envp

The database environment handle.

See Also

[db_multimap\(Db*, DbEnv*\)](#)

```
db_multiset(Db *dbp, DbEnv *envp, InputIterator first,  
            InputIterator last)
```

Iteration constructor.

Iterates between first and last, setting a copy of each of the sequence of elements as the content of the container object. Create a `std::multi/hash_multiset` equivalent associative container. Insert a range of elements into the database. The range is `[first, last)`, which contains elements that can be converted to type `ddt` automatically. This function supports auto commit. See the handle requirement in class details to pass correct database/environment handles.

Parameters

dbp

The database handle.

envp

The database environment handle.

last

The open boundary of the range.

first

The closed boundary of the range.

See Also

[db_multimap\(Db*, DbEnv*, InputIterator, InputIterator\)](#)

```
db_multiset(const self &x)
```

Copy constructor.

Create an database and insert all key/data pairs in x into this container. x's data members are not copied. This function supports auto commit.

Parameters**x**

The other container to initialize this container.

See Also

[db_multimap\(const db_multimap&\)](#) [db_container\(const db_container&\)](#)

Class

[db_multiset](#)

~db_multiset

Function Details

```
virtual ~db_multiset()
```

Class

[db_multiset](#)

insert

Function Details

```
iterator insert(const value_type &x)
```

Insert a single key if the key is not in the container.

Parameters

x

The key to insert.

Return Value

An iterator sitting on the newly inserted key, or an invalid one if the key x existed.

```
iterator insert(iterator position,  
               const value_type &x)
```

Insert a single key with hint if the key is not in the container.

The hint position is ignored because Berkeley DB controls where to insert the key.

Parameters

x

The key to insert.

position

The hint insert position, ignored.

Return Value

An iterator sitting on the newly inserted key, or an invalid one if the key x existed.

```
void insert(InputIterator first,  
           InputIterator last)
```

Range insertion.

Insert a range [first, last) of key/data pairs into this container.

Parameters**last**

The open boundary of the range.

first

The closed boundary of the range.

```
void insert(db_set_iterator< kdt, value_type_sub > &first,
            db_set_iterator< kdt,
            value_type_sub > &last)
```

Range insertion.

Insert a range [first, last) of key/data pairs into this container.

Parameters**last**

The open boundary of the range.

first

The closed boundary of the range.

```
void insert(db_set_base_iterator< kdt > &first,
            db_set_base_iterator< kdt > &last)
```

Range insertion.

Insert a range [first, last) of key/data pairs into this container.

Parameters**last**

The open boundary of the range.

first

The closed boundary of the range.

Group: Insert Functions

<http://www.cplusplus.com/reference/stl/multiset/insert/>

Class

`db_multiset`

erase

Function Details

```
size_type erase(const key_type &x)
```

Erase elements by key.

All key/data pairs with specified key x will be removed from underlying database. This function supports auto commit.

Parameters

x

The key to remove from the container.

Return Value

The number of key/data pairs removed.

```
void erase(iterator pos)
```

Erase a key/data pair at specified position.

Parameters

pos

An valid iterator of this container to erase.

```
void erase(iterator first,  
           iterator last)
```

Range erase.

Erase all key/data pairs within the valid range [first, last).

Parameters

last

The open boundary of the range.

first

The closed boundary of the range.

Group: Erase Functions

<http://www.cplusplus.com/reference/stl/multiset/erase/>

Class

[db_multiset](#)

operator=

Function Details

```
const self& operator=(const self &x)
```

Container content assignment operator.

This function supports auto commit.

Parameters

x

The other container whose key/data pairs will be inserted into this container. Old content in this containers are discarded.

Return Value

The container x.

See Also

<http://www.cplusplus.com/reference/stl/multiset/operator=/>

Class

[db_multiset](#)

swap

Function Details

```
void swap(db_multiset< kdt, value_type_sub > &mp,  
          bool b_truncate=true)
```

Swap content with another container.

This function supports auto commit.

Parameters

b_truncate

See [db_multimap::swap\(\)](#) for details.

mp

The other container to swap content with.

See Also

[db_map::swap\(\)](#) [db_vector::clear\(\)](#)

Class

[db_multiset](#)

operator==

Function Details

```
bool operator==(const self &m2) const
```

Container content equality compare operator.

This function does not rely on key order, it is doing a multiple set equal comparison---Two sets A and B are equal if and only if for each and every key K having n occurrences in A, K has n occurrences in B, and for each and every key K` having N occurrences in B, K` has n occurrences in A.

Parameters

m2

The other container to compare against.

Return Value

Returns true if they have equal content, false otherwise.

Class

[db_multiset](#)

operator!=

Function Details

```
bool operator!=(const self &m2) const
```

Unequality comparison operator.

Class

[db_multiset](#)

Chapter 9. dbstl iterator classes

dbstl iterator classes

dbstl iterator classes

Common information for all dbstl iterators:.

1. Each instance of a dbstl iterator uniquely owns a Berkeley DB cursor, so that the key/data pair it currently sits on is always valid before it moves elsewhere. It also caches the current key/data pair values in order for member functions like `operator*` / `operator->` to work properly, but caching is not compatible with standard C++ Stl behavior --- the C++ standard requires the iterator refer to a shared piece of memory where the data is stored, thus two iterators of the same container sitting on the same element should point to the same memory location, which is false for dbstl iterators.

2. There are some functions common to each child class of this class which have identical behaviors, so we will document them here.

This class is the base class for all dbstl iterators, there is no much to say about this class itself, and users are not supposed to directly use this class at all. So we will talk about some common functions of dbstl iterators in this section.

See Also

[db_vector_base_iterator](#) [db_vector_iterator](#) [db_map_base_iterator](#) [db_map_iterator](#) [db_set_base_iterator](#) [db_set_iterator](#)

Public Members

| Member | Description |
|--|--|
| db_base_iterator | db_base_iterator |
| db_reverse_iterator | db_reverse_iterator |
| Iterator classes for db_map and db_multimap. | Iterator classes for db_map and db_multimap. |
| Iterator classes for db_set and db_multiset. | Iterator classes for db_set and db_multiset. |
| Iterator classes for db_vector. | Iterator classes for db_vector. |

Group

None

Chapter 10. db_base_iterator

db_base_iterator

Public Members

| Member | Description |
|------------------------------------|---|
| refresh | Read data from underlying database via its cursor, and update its cached value. |
| close_cursor | Close its cursor. |
| set_bulk_buffer | Call this function to modify bulk buffer size. |
| get_bulk_bufsize | Return current bulk buffer size. |
| db_base_iterator | Default constructor. |
| operator= | Iterator assignment operator. |
| ~db_base_iterator | Destructor. |
| get_bulk_retrieval | Get bulk buffer size. |
| is_rmw | Get DB_RMW setting. |
| is_directdb_get | Get direct database get setting. |

Group

[dbstl iterator classes](#)

refresh

Function Details

```
int refresh(bool from_db=true)
```

Read data from underlying database via its cursor, and update its cached value.

Parameters

from_db

Whether retrieve data from database rather than using the cached data in this iterator.

Return Value

0 if succeeded. Otherwise an [DbstlException](#) exception will be thrown.

Class

[db_base_iterator](#)

close_cursor

Function Details

```
void close_cursor() const
```

Close its cursor.

If you are sure the iterator is no longer used, call this function so that its underlying cursor is closed before this iterator is destructed, potentially increase performance and concurrency. Note that the cursor is definitely closed at iterator destruction if you don't close it explicitly.

Class

[db_base_iterator](#)

set_bulk_buffer

Function Details

```
bool set_bulk_buffer(u_int32_t sz)
```

Call this function to modify bulk buffer size.

Bulk retrieval is enabled when creating an iterator, so users later can only modify the bulk buffer size to another value, but can't enable/disable bulk read while an iterator is already alive.

Parameters

sz

The new buffer size in bytes.

Return Value

true if succeeded, false otherwise.

Class

[db_base_iterator](#)

get_bulk_bufsize

Function Details

```
u_int32_t get_bulk_bufsize()
```

Return current bulk buffer size.

Returns 0 if bulk retrieval is not enabled.

Class

[db_base_iterator](#)

db_base_iterator

Function Details

```
db_base_iterator()
```

Default constructor.

```
db_base_iterator(db_container *powner, bool directdbget, bool b_read_only,  
                u_int32_t bulk,  
                bool rmw)
```

Constructor.

```
db_base_iterator(const db_base_iterator &bi)
```

Copy constructor. Copy all members of this class.

Class

[db_base_iterator](#)

operator=

Function Details

```
const self& operator=(const self &bi)
```

Iterator assignment operator.

Iterator assignment will cause the underlying cursor of the right iterator to be duplicated to the left iterator after its previous cursor is closed, to make sure each iterator owns one unique cursor. The key/data cached in the right iterator is copied to the left iterator. Consequently, the left iterator points to the same key/data pair in the database as the the right value after the assignment, and have identical cached key/data pair.

Parameters

bi

The other iterator to assign with.

Return Value

The iterator bi's reference.

Class

[db_base_iterator](#)

~db_base_iterator

Function Details

```
virtual ~db_base_iterator()
```

Destructor.

Class

[db_base_iterator](#)

get_bulk_retrieval

Function Details

```
u_int32_t get_bulk_retrieval() const
```

Get bulk buffer size.

Return bulk buffer size. If the size is 0, bulk retrieval is not enabled.

Class

[db_base_iterator](#)

is_rmw

Function Details

```
bool is_rmw() const
```

Get DB_RMW setting.

Return true if the iterator's cursor has DB_RMW flag set, false otherwise. DB_RMW flag causes a write lock to be acquired when reading a key/data pair, so that the transaction won't block later when writing back the updated value in a read-modify-write operation cycle.

Class

[db_base_iterator](#)

is_directdb_get

Function Details

```
bool is_directdb_get() const
```

Get direct database get setting.

Return true if every operation to retrieve the key/data pair the iterator points to will read from database rather than using the cached value, false otherwise.

Class

[db_base_iterator](#)

Chapter 11. iterator classes for db_vector

Iterator classes for db_vector.

Iterator classes for db_vector.

[db_vector](#) has two iterator classes --- [db_vector_base_iterator](#) and [db_vector_iterator](#) .

The differences between the two classes are that the [db_vector_base_iterator](#) can only be used to read its referenced value, so it is intended as db_vector's const iterator; While the other class allows both read and write access. If your access pattern is readonly, it is strongly recommended that you use the const iterator because it is faster and more efficient. The two classes have identical behaviors to `std::vector::const_iterator` and `std::vector::iterator` respectively. Note that the common public member function behaviors are described in the [db_base_iterator](#) section.

See Also

[db_base_iterator](#)

Public Members

| Member | Description |
|---|---|
| db_vector_base_iterator | db_vector_base_iterator |
| db_vector_iterator | db_vector_iterator |

Group

[dbstl iterator classes](#)

Chapter 12. db_vector_base_iterator

db_vector_base_iterator

This class is the const iterator class for [db_vector](#) , and it is inherited by the [db_vector_iterator](#) class, which is the iterator class for [db_vector](#) .

Public Members

| Member | Description |
|--|---|
| db_vector_base_iterator | |
| ~db_vector_base_iterator | |
| operator== | Equality comparison operator. |
| operator!= | Unequal compare, identical to !operator(==itr). |
| operator< | Less than comparison operator. |
| operator<= | Less equal comparison operator. |
| operator>= | Greater equal comparison operator. |
| operator> | Greater comparison operator. |
| operator++ | Pre-increment. |
| operator-- | Pre-decrement. |
| operator= | Assignment operator. |
| operator+ | Iterator movement operator. |
| operator+= | Move this iterator backward by n elements. |
| operator- | Iterator movement operator. |
| operator-= | Move this iterator forward by n elements. |
| operator * | Dereference operator. |
| operator-> | Arrow operator. |
| operator[] | Iterator index operator. |
| get_current_index | Get current index of within the vector. |
| move_to | Iterator movement function. |
| refresh | Refresh iterator cached value. |
| close_cursor | Close underlying Berkeley DB cursor of this iterator. |
| set_bulk_buffer | Modify bulk buffer size. |
| get_bulk_bufsize | Get bulk retrieval buffer size in bytes. |

Group

[iterator classes for db_vector](#)

db_vector_base_iterator

Function Details

```
db_vector_base_iterator(const db_vector_base_iterator< T > &vi)
```

```
db_vector_base_iterator(db_container *powner, u_int32_t b_bulk_retrieval=0,  
    bool rmw=false, bool directdbget=true,  
    bool readonly=false)
```

```
db_vector_base_iterator()
```

Group: Constructors and destructor

Do not construct iterators explicitly using these constructors, but call `db_vector::begin() const` to get an valid iterator.

`db_vector::begin() const`

Class

[db_vector_base_iterator](#)

~db_vector_base_iterator

Function Details

```
virtual ~db_vector_base_iterator()
```

Group: Constructors and destructor

Do not construct iterators explicitly using these constructors, but call `db_vector::begin() const` to get an valid iterator.

`db_vector::begin() const`

Class

[db_vector_base_iterator](#)

operator==

Function Details

```
bool operator==(const self &itr) const
```

Equality comparison operator.

Invalid iterators are equal; Valid iterators sitting on the same key/data pair equal; Otherwise not equal.

Parameters

itr

The iterator to compare against.

Return Value

True if this iterator equals to itr; False otherwise.

Group: Iterator comparison operators

The way to compare two iterators is to compare the index values of the two elements they point to.

The iterator sitting on an element with less index is regarded to be smaller. And the invalid iterator sitting after last element is greater than any other iterators, because it is assumed to have an index equal to last element's index plus one; The invalid iterator sitting before first element is less than any other iterators because it is assumed to have an index -1.

Class

[db_vector_base_iterator](#)

operator!=

Function Details

```
bool operator!=(const self &itr) const
```

Unequal compare, identical to !operator(==itr).

Parameters

itr

The iterator to compare against.

Return Value

False if this iterator equals to itr; True otherwise.

Group: Iterator comparison operators

The way to compare two iterators is to compare the index values of the two elements they point to.

The iterator sitting on an element with less index is regarded to be smaller. And the invalid iterator sitting after last element is greater than any other iterators, because it is assumed to have an index equal to last element's index plus one; The invalid iterator sitting before first element is less than any other iterators because it is assumed to have an index -1.

Class

[db_vector_base_iterator](#)

operator<

Function Details

```
bool operator<(const self &itr) const
```

Less than comparison operator.

Parameters

itr

The iterator to compare against.

Return Value

True if this iterator is less than itr.

Group: Iterator comparison operators

The way to compare two iterators is to compare the index values of the two elements they point to.

The iterator sitting on an element with less index is regarded to be smaller. And the invalid iterator sitting after last element is greater than any other iterators, because it is assumed to have an index equal to last element's index plus one; The invalid iterator sitting before first element is less than any other iterators because it is assumed to have an index -1.

Class

[db_vector_base_iterator](#)

operator<=

Function Details

```
bool operator<=(const self &itr) const
```

Less equal comparison operator.

Parameters

itr

The iterator to compare against.

Return Value

True if this iterator is less than or equal to itr.

Group: Iterator comparison operators

The way to compare two iterators is to compare the index values of the two elements they point to.

The iterator sitting on an element with less index is regarded to be smaller. And the invalid iterator sitting after last element is greater than any other iterators, because it is assumed to have an index equal to last element's index plus one; The invalid iterator sitting before first element is less than any other iterators because it is assumed to have an index -1.

Class

[db_vector_base_iterator](#)

operator>=

Function Details

```
bool operator>=(const self &itr) const
```

Greater equal comparison operator.

Parameters

itr

The iterator to compare against.

Return Value

True if this iterator is greater than or equal to itr.

Group: Iterator comparison operators

The way to compare two iterators is to compare the index values of the two elements they point to.

The iterator sitting on an element with less index is regarded to be smaller. And the invalid iterator sitting after last element is greater than any other iterators, because it is assumed to have an index equal to last element's index plus one; The invalid iterator sitting before first element is less than any other iterators because it is assumed to have an index -1.

Class

[db_vector_base_iterator](#)

operator>

Function Details

```
bool operator>(const self &itr) const
```

Greater comparison operator.

Parameters

itr

The iterator to compare against.

Return Value

True if this iterator is greater than itr.

Group: Iterator comparison operators

The way to compare two iterators is to compare the index values of the two elements they point to.

The iterator sitting on an element with less index is regarded to be smaller. And the invalid iterator sitting after last element is greater than any other iterators, because it is assumed to have an index equal to last element's index plus one; The invalid iterator sitting before first element is less than any other iterators because it is assumed to have an index -1.

Class

[db_vector_base_iterator](#)

operator++

Function Details

```
self& operator++()
```

Pre-increment.

Move the iterator one element backward, so that the element it sits on has a bigger index. Use ++iter rather than iter++ where possible to avoid two useless iterator copy constructions.

Return Value

This iterator after incremented.

```
self operator++(int)
```

Post-increment.

Move the iterator one element backward, so that the element it sits on has a bigger index. Use ++iter rather than iter++ where possible to avoid two useless iterator copy constructions.

Return Value

A new iterator not incremented.

Group: Iterator movement operators.

When we talk about iterator movement, we think the container is a uni-directional range, represented by [begin, end), and this is true no matter we are using iterators or reverse iterators.

When an iterator is moved closer to "begin", we say it is moved forward, otherwise we say it is moved backward.

Class

[db_vector_base_iterator](#)

operator--

Function Details

```
self& operator--()
```

Pre-decrement.

Move the iterator one element backward, so that the element it sits on has a smaller index. Use --iter rather than iter-- where possible to avoid two useless iterator copy constructions.

Return Value

This iterator after decremented.

```
self operator--(int)
```

Post-decrement.

Move the iterator one element backward, so that the element it sits on has a smaller index. Use --iter rather than iter-- where possible to avoid two useless iterator copy constructions.

Return Value

A new iterator not decremented.

Group: Iterator movement operators.

When we talk about iterator movement, we think the container is a uni-directional range, represented by [begin, end), and this is true no matter we are using iterators or reverse iterators.

When an iterator is moved closer to "begin", we say it is moved forward, otherwise we say it is moved backward.

Class

[db_vector_base_iterator](#)

operator=

Function Details

```
const self& operator=(const self &itr)
```

Assignment operator.

This iterator will point to the same key/data pair as itr, and have the same configurations as itr.

Parameters

itr

The right value of the assignment.

Return Value

This iterator's reference.

See Also

[db_base_iterator::operator=](#)

Group: Iterator movement operators.

When we talk about iterator movement, we think the container is a uni-directional range, represented by [begin, end), and this is true no matter we are using iterators or reverse iterators.

When an iterator is moved closer to "begin", we say it is moved forward, otherwise we say it is moved backward.

Class

[db_vector_base_iterator](#)

operator+

Function Details

```
self operator+(difference_type n) const
```

Iterator movement operator.

Return another iterator by moving this iterator forward by n elements.

Parameters

n

The amount and direction of movement. If negative, will move forward by |n| element.

Return Value

The new iterator at new position.

Group: Iterator movement operators.

When we talk about iterator movement, we think the container is a uni-directional range, represented by [begin, end), and this is true no matter we are using iterators or reverse iterators.

When an iterator is moved closer to "begin", we say it is moved forward, otherwise we say it is moved backward.

Class

[db_vector_base_iterator](#)

operator+=

Function Details

```
const self& operator+=(difference_type n)
```

Move this iterator backward by n elements.

Parameters

n

The amount and direction of movement. If negative, will move forward by |n| element.

Return Value

Reference to this iterator at new position.

Group: Iterator movement operators.

When we talk about iterator movement, we think the container is a uni-directional range, represented by [begin, end), and this is true no matter we are using iterators or reverse iterators.

When an iterator is moved closer to "begin", we say it is moved forward, otherwise we say it is moved backward.

Class

[db_vector_base_iterator](#)

operator-

Function Details

```
self operator-(difference_type n) const
```

Iterator movement operator.

Return another iterator by moving this iterator backward by n elements.

Parameters

n

The amount and direction of movement. If negative, will move backward by |n| element.

Return Value

The new iterator at new position.

```
difference_type operator-(const self &itr) const
```

Iterator distance operator.

Return the index difference of this iterator and itr, so if this iterator sits on an element with a smaller index, this call will return a negative number.

Parameters

itr

The other iterator to subtract. itr can be the invalid iterator after last element or before first element, their index will be regarded as last element's index + 1 and -1 respectively.

Return Value

The index difference.

Group: Iterator movement operators.

When we talk about iterator movement, we think the container is a uni-directional range, represented by [begin, end), and this is true no matter we are using iterators or reverse iterators.

When an iterator is moved closer to "begin", we say it is moved forward, otherwise we say it is moved backward.

Class

[db_vector_base_iterator](#)

operator--

Function Details

```
const self& operator--(difference_type n)
```

Move this iterator forward by n elements.

Parameters

n

The amount and direction of movement. If negative, will move backward by |n| element.

Return Value

Reference to this iterator at new position.

Group: Iterator movement operators.

When we talk about iterator movement, we think the container is a uni-directional range, represented by [begin, end), and this is true no matter we are using iterators or reverse iterators.

When an iterator is moved closer to "begin", we say it is moved forward, otherwise we say it is moved backward.

Class

[db_vector_base_iterator](#)

operator *

Function Details

```
reference operator *() const
```

Dereference operator.

Return the reference to the cached data element, which is an `ElementRef<T>` object if `T` is a class type or an `ElementHolder<T>` object if `T` is a C++ primitive data type. The returned value can only be used to read its referenced element.

Return Value

The reference to the element this iterator points to.

Class

[db_vector_base_iterator](#)

operator->

Function Details

```
pointer operator->>() const
```

Arrow operator.

Return the pointer to the cached data element, which is an `ElementRef<T>` object if `T` is a class type or an `ElementHolder<T>` object if `T` is a C++ primitive data type. The returned value can only be used to read its referenced element.

Return Value

The address of the referenced object.

Class

[db_vector_base_iterator](#)

operator[]

Function Details

```
value_type_wrap operator[](difference_type _Off) const
```

Iterator index operator.

If `_Off` not in a valid range, the returned value will be invalid. Note that you should use a `value_type_wrap` type to hold the returned value.

Parameters

`_Off`

The valid index relative to this iterator.

Return Value

Return the element which is at position `*this + _Off`. The returned value can only be used to read its referenced element.

Class

[db_vector_base_iterator](#)

get_current_index

Function Details

```
index_type get_current_index() const
```

Get current index of within the vector.

Return the iterators current element's index (0 based). Requires this iterator to be a valid iterator, not end_itr_.

Return Value

current index of the iterator.

Class

[db_vector_base_iterator](#)

move_to

Function Details

```
void move_to(index_type n) const
```

Iterator movement function.

Move this iterator to the index "n". If n is not in the valid range, this iterator will be an invalid iterator equal to end() iterator.

Parameters

n

target element's index.

See Also

[db_vector::end\(\)](#) ;

Class

[db_vector_base_iterator](#)

refresh

Function Details

```
virtual int refresh(bool from_db=true)
```

Refresh iterator cached value.

Parameters

from_db

If not doing direct database get and this parameter is true, we will retrieve data directly from db.

See Also

[db_base_iterator::refresh\(bool\)](#) .

Class

[db_vector_base_iterator](#)

close_cursor

Function Details

```
void close_cursor() const
```

Close underlying Berkeley DB cursor of this iterator.

See Also

[db_base_iterator::close_cursor\(\) const](#)

Class

[db_vector_base_iterator](#)

set_bulk_buffer

Function Details

```
bool set_bulk_buffer(u_int32_t sz)
```

Modify bulk buffer size.

Bulk read is enabled when creating an iterator, so you later can only modify the bulk buffer size to another value, but can't enable/disable bulk read while an iterator is already alive.

Parameters

sz

The new size of the bulk read buffer of this iterator.

Return Value

Returns true if succeeded, false otherwise.

See Also

[db_base_iterator::set_bulk_buffer\(u_int32_t sz\)](#)

Class

[db_vector_base_iterator](#)

get_bulk_bufsize

Function Details

```
u_int32_t get_bulk_bufsize()
```

Get bulk retrieval buffer size in bytes.

Return Value

Return current bulk buffer size, or 0 if bulk retrieval is not enabled.

See Also

[db_base_iterator::get_bulk_bufsize\(\)](#)

Class

[db_vector_base_iterator](#)

Chapter 13. db_vector_iterator

db_vector_iterator

Public Members

| Member | Description |
|-------------------------------------|--|
| db_vector_iterator | |
| ~db_vector_iterator | |
| operator++ | Pre-increment. |
| operator-- | Pre-decrement. |
| operator= | Assignment operator. |
| operator+ | Iterator movement operator. |
| operator+= | Move this iterator backward by n elements. |
| operator- | Iterator movement operator. |
| operator-= | Move this iterator forward by n elements. |
| operator * | Dereference operator. |
| operator-> | Arrow operator. |
| operator[] | Iterator index operator. |
| refresh | Refresh iterator cached value. |

Group

[iterator classes for db_vector](#)

db_vector_iterator

Function Details

```
db_vector_iterator(const db_vector_iterator< T,  
    value_type_sub > &vi)
```

```
db_vector_iterator(db_container *powner, u_int32_t b_bulk_retrieval=0,  
    bool brmw=false, bool directdbget=true,  
    bool b_read_only=false)
```

```
db_vector_iterator()
```

```
db_vector_iterator(const db_vector_base_iterator< T > &obj)
```

Group: Constructors and destructor

Do not construct iterators explicitly using these constructors, but call [db_vector::begin](#) to get an valid iterator.

[db_vector::begin](#)

Class

[db_vector_iterator](#)

~db_vector_iterator

Function Details

```
virtual ~db_vector_iterator()
```

Group: Constructors and destructor

Do not construct iterators explicitly using these constructors, but call [db_vector::begin](#) to get an valid iterator.

[db_vector::begin](#)

Class

[db_vector_iterator](#)

operator++

Function Details

```
self& operator++()
```

Pre-increment.

Return Value

This iterator after incremented.

See Also

[db_vector_base_iterator::operator++\(\)](#)

```
self operator++(int)
```

Post-increment.

Return Value

A new iterator not incremented.

See Also

[db_vector_base_iterator::operator++\(int\)](#)

Group: Iterator movement operators.

These functions have identical behaviors and semantics as those of [db_vector_base_iterator](#) , so please refer to equivalent in that class.

Class

[db_vector_iterator](#)

operator--

Function Details

```
self& operator--()
```

Pre-decrement.

Return Value

This iterator after decremented.

See Also

[db_vector_base_iterator::operator--\(\)](#)

```
self operator--(int)
```

Post-decrement.

Return Value

A new iterator not decremented.

See Also

[db_vector_base_iterator::operator--\(int\)](#)

Group: Iterator movement operators.

These functions have identical behaviors and semantics as those of [db_vector_base_iterator](#) , so please refer to equivalent in that class.

Class

[db_vector_iterator](#)

operator=

Function Details

```
const self& operator=(const self &itr)
```

Assignment operator.

This iterator will point to the same key/data pair as itr, and have the same configurations as itr.

Parameters

itr

The right value of the assignment.

Return Value

This iterator's reference.

See Also

[db_base_iterator::operator=\(const self&\)](#)

Group: Iterator movement operators.

These functions have identical behaviors and semantics as those of [db_vector_base_iterator](#) , so please refer to equivalent in that class.

Class

[db_vector_iterator](#)

operator+

Function Details

```
self operator+(difference_type n) const
```

Iterator movement operator.

Return another iterator by moving this iterator backward by n elements.

Parameters

n

The amount and direction of movement. If negative, will move forward by |n| element.

Return Value

The new iterator at new position.

See Also

[db_vector_base_iterator::operator+\(difference_type n\) const](#)

Group: Iterator movement operators.

These functions have identical behaviors and semantics as those of [db_vector_base_iterator](#) , so please refer to equivalent in that class.

Class

[db_vector_iterator](#)

operator+=

Function Details

```
const self& operator+=(difference_type n)
```

Move this iterator backward by n elements.

Parameters

n

The amount and direction of movement. If negative, will move forward by $|n|$ element.

Return Value

Reference to this iterator at new position.

See Also

[db_vector_base_iterator::operator+=\(difference_type n\)](#)

Group: Iterator movement operators.

These functions have identical behaviors and semantics as those of [db_vector_base_iterator](#) , so please refer to equivalent in that class.

Class

[db_vector_iterator](#)

operator-

Function Details

```
self operator-(difference_type n) const
```

Iterator movement operator.

Return another iterator by moving this iterator forward by n elements.

Parameters

n

The amount and direction of movement. If negative, will move backward by |n| element.

Return Value

The new iterator at new position.

See Also

[db_vector_base_iterator::operator-\(difference_type n\) const](#)

```
difference_type operator-(const self &itr) const
```

Iterator distance operator.

Return the index difference of this iterator and itr, so if this iterator sits on an element with a smaller index, this call will return a negative number.

Parameters

itr

The other iterator to subtract. itr can be the invalid iterator after last element or before first element, their index will be regarded as last element's index + 1 and -1 respectively.

Return Value

The index difference.

See Also

[db_vector_base_iterator::operator-\(const self& itr\) const](#)

Group: Iterator movement operators.

These functions have identical behaviors and semantics as those of [db_vector_base_iterator](#) , so please refer to equivalent in that class.

Class

[db_vector_iterator](#)

operator--

Function Details

```
const self& operator--(difference_type n)
```

Move this iterator forward by n elements.

Parameters

n

The amount and direction of movement. If negative, will move backward by |n| element.

Return Value

Reference to this iterator at new position.

See Also

[db_vector_base_iterator::operator--\(difference_type n\)](#)

Group: Iterator movement operators.

These functions have identical behaviors and semantics as those of [db_vector_base_iterator](#) , so please refer to equivalent in that class.

Class

[db_vector_iterator](#)

operator *

Function Details

```
reference operator *() const
```

Dereference operator.

Return the reference to the cached data element, which is an `ElementRef<T>` object if `T` is a class type or an `ElementHolder<T>` object if `T` is a C++ primitive data type. The returned value can be used to read or update its referenced element.

Return Value

The reference to the element this iterator points to.

Class

[db_vector_iterator](#)

operator->

Function Details

```
pointer operator->>() const
```

Arrow operator.

Return the pointer to the cached data element, which is an `ElementRef<T>` object if `T` is a class type or an `ElementHolder<T>` object if `T` is a C++ primitive data type. The returned value can be used to read or update its referenced element.

Return Value

The address of the referenced object.

Class

[db_vector_iterator](#)

operator[]

Function Details

```
value_type_wrap operator[](difference_type _Off) const
```

Iterator index operator.

If `_Off` not in a valid range, the returned value will be invalid. Note that you should use a `value_type_wrap` type to hold the returned value.

Parameters

`_Off`

The valid index relative to this iterator.

Return Value

Return the element which is at position `*this + _Off`, which is an `ElementRef<T>` object if `T` is a class type or an `ElementHolder<T>` object if `T` is a C++ primitive data type. The returned value can be used to read or update its referenced element.

Class

[db_vector_iterator](#)

refresh

Function Details

```
virtual int refresh(bool from_db=true)
```

Refresh iterator cached value.

Parameters

from_db

If not doing direct database get and this parameter is true, we will retrieve data directly from db.

See Also

[db_base_iterator::refresh\(bool\)](#)

Class

[db_vector_iterator](#)

Chapter 14. iterator classes for `db_map` and `db_multimap`

Iterator classes for `db_map` and `db_multimap`.

Iterator classes for `db_map` and `db_multimap`.

`db_map` has two iterator class templates -- `db_map_base_iterator` and `db_map_iterator` .

They are the const iterator class and iterator class for `db_map` and `db_multimap` . `db_map_iterator` inherits from `db_map_base_iterator` .

The two classes have identical behaviors to `std::map::const_iterator` and `std::map::iterator` respectively. Note that the common public member function behaviors are described in the `db_base_iterator` section.

The differences between the two classes are that the `db_map_base_iterator` can only be used to read its referenced value, while `db_map_iterator` allows both read and write access. If your access pattern is readonly, it is strongly recommended that you use the const iterator because it is faster and more efficient.

Public Members

| Member | Description |
|---|---|
| <code>assign_second0</code> | |
| <code>assign_second</code> | |
| <code>hash_default</code> | |
| <code>db_map_base_iterator</code> | <code>db_map_base_iterator</code> |
| <code>db_map_iterator</code> | <code>db_map_iterator</code> |
| <code>Assign functions used internally only.</code> | <code>Assign functions used internally only.</code> |

Group

`dbstl` iterator classes

assign_second0

Function Details

```
void assign_second0(pair< kdt, ddt > &v,  
    const datadt &d)
```

```
void assign_second0(pair< kdt, ddt > &v,  
    const _DB_STL_set_value< kdt > &)
```

```
void assign_second0(pair< kdt, value_type_sub > &v,  
    const datadt &d)
```

Class

[db_map_iterators](#)

assign_second

Function Details

```
void assign_second(pair< kdt, value_type_sub > &v,  
                  const datadt &d)
```

```
void assign_second(pair< kdt, value_type_sub > &v,  
                  const _DB_STL_set_value< kdt > &)
```

Class

[db_map_iterators](#)

hash_default

Function Details

```
u_int32_t hash_default(Db *dbp, const void *key,  
                      u_int32_t len)
```

Class

[db_map_iterators](#)

Chapter 15. db_map_base_iterator

db_map_base_iterator

Public Members

| Member | Description |
|---------------------------------------|---|
| db_map_base_iterator | Copy constructor. |
| ~db_map_base_iterator | Destructor. |
| operator++ | Pre-increment. |
| operator-- | Pre-decrement. |
| operator== | Equal comparison operator. |
| operator!= | Unequal comparison operator. |
| operator * | Dereference operator. |
| operator-> | Arrow operator. |
| refresh | Refresh iterator cached value. |
| close_cursor | Close underlying Berkeley DB cursor of this iterator. |
| move_to | Iterator movement function. |
| set_bulk_buffer | Modify bulk buffer size. |
| get_bulk_bufsize | Get bulk retrieval buffer size in bytes. |
| operator= | Assignment operator. |

Group

[iterator classes for db_map and db_multimap](#)

db_map_base_iterator

Function Details

```
db_map_base_iterator(const self &vi)
```

Copy constructor.

Parameters

vi

The other iterator of the same type to initialize this.

```
db_map_base_iterator(const base &vi)
```

Base copy constructor.

Parameters

vi

Initialize from a base class iterator.

```
db_map_base_iterator(db_container *powner, u_int32_t b_bulk_retrieval=0,  
    bool rmw=false, bool directdbget=true,  
    bool readonly=false)
```

Constructor.

Parameters

b_bulk_retrieval

The bulk read buffer size. 0 means bulk read disabled.

directdbget

Whether do direct database get rather than using key/data values cached in the iterator whenever read.

readonly

Whether open a read only cursor. Only effective when using Berkeley DB Concurrent Data Store.

powner

The container which creates this iterator.

rmw

Whether set DB_RMW flag in underlying cursor.

```
db_map_base_iterator()
```

Default constructor, dose not create the cursor for now.

Group: Constructors and destructor

Do not create iterators directly using these constructors, but call [db_map::begin](#) or `db_multimap_begin` to get instances of this class.

[db_map::begin\(\)](#) [db_multimap::begin\(\)](#)

Class

[db_map_base_iterator](#)

~db_map_base_iterator

Function Details

```
virtual ~db_map_base_iterator()
```

Destructor.

Group: Constructors and destructor

Do not create iterators directly using these constructors, but call [db_map::begin](#) or `db_multimap_begin` to get instances of this class.

[db_map::begin\(\)](#) [db_multimap::begin\(\)](#)

Class

[db_map_base_iterator](#)

operator++

Function Details

```
self& operator++()
```

Pre-increment.

Return Value

This iterator after incremented.

```
self operator++(int)
```

Post-increment.

Return Value

Another iterator having the old value of this iterator.

Group: Iterator increment movement functions.

The two functions moves the iterator one element backward, so that the element it sits on has a bigger key.

The btree/hash key comparison routine determines which key is greater. Use ++iter rather than iter++ where possible to avoid two useless iterator copy constructions.

Class

[db_map_base_iterator](#)

operator--

Function Details

```
self& operator--()
```

Pre-decrement.

Return Value

This iterator after decremented.

```
self operator--(int)
```

Post-decrement.

Return Value

Another iterator having the old value of this iterator.

Group: Iterator decrement movement functions.

The two functions moves the iterator one element forward, so that the element it sits on has a smaller key.

The btree/hash key comparison routine determines which key is greater. Use --iter rather than iter-- where possible to avoid two useless iterator copy constructions.

Class

[db_map_base_iterator](#)

operator==

Function Details

```
bool operator==(const self &itr) const
```

Equal comparison operator.

Parameters

itr

The iterator to compare against.

Return Value

Returns true if equal, false otherwise.

Group: Compare operators.

Only equal comparison is supported.

Class

[db_map_base_iterator](#)

operator!=

Function Details

```
bool operator!=(const self &itr) const
```

Unequal comparison operator.

Parameters

itr

The iterator to compare against.

Return Value

Returns false if equal, true otherwise.

See Also

bool [operator==\(const self&itr\) const](#)

Group: Compare operators.

Only equal comparison is supported.

Class

[db_map_base_iterator](#)

operator *

Function Details

```
reference operator *() const
```

Dereference operator.

Return the reference to the cached data element, which is an `pair<Key_type, T>`. You can only read its referenced data via this iterator but can not update it.

Return Value

Current data element reference object, i.e. [ElementHolder](#) or [ElementRef](#) object.

Class

[db_map_base_iterator](#)

operator->

Function Details

```
pointer operator->>() const
```

Arrow operator.

Return the pointer to the cached data element, which is an `pair<Key_type, T>`. You can only read its referenced data via this iterator but can not update it.

Return Value

Current data element reference object's address, i.e. address of [ElementHolder](#) or [ElementRef](#) object.

Class

[db_map_base_iterator](#)

refresh

Function Details

```
virtual int refresh(bool from_db=true) const
```

Refresh iterator cached value.

Parameters

from_db

If not doing direct database get and this parameter is true, we will retrieve data directly from db.

See Also

[db_base_iterator::refresh\(bool\)](#)

Class

[db_map_base_iterator](#)

close_cursor

Function Details

```
void close_cursor() const
```

Close underlying Berkeley DB cursor of this iterator.

See Also

[db_base_iterator::close_cursor\(\) const](#)

Class

[db_map_base_iterator](#)

move_to

Function Details

```
int move_to(const kdt &k,  
            int flag=DB_SET) const
```

Iterator movement function.

Move this iterator to the specified key k, by default moves exactly to k, and update cached data element, you can also specify DB_SET_RANGE, to move to the biggest key smaller than k. The btree/hash key comparison routine determines which key is bigger. When the iterator is on a multiple container, move_to will move itself to the first key/data pair of the identical keys.

Parameters

k

The target key value to move to.

flag

Flags available: DB_SET(default) or DB_SET_RANGE. DB_SET will move this iterator exactly at k; DB_SET_RANGE moves this iterator to k or the smallest key greater than k. If fail to find such a key, this iterator will become invalid.

Return Value

0 if succeed; non-0 otherwise, and this iterator becomes invalid. Call db_strerror with the return value to get the error message.

Class

[db_map_base_iterator](#)

set_bulk_buffer

Function Details

```
bool set_bulk_buffer(u_int32_t sz)
```

Modify bulk buffer size.

Bulk read is enabled when creating an iterator, so users later can only modify the bulk buffer size to another value, but can't enable/disable bulk read while an iterator is already alive.

Parameters

sz

The new size of the bulk read buffer of this iterator.

Return Value

Returns true if succeeded, false otherwise.

See Also

[db_base_iterator::set_bulk_buffer\(u_int32_t \)](#)

Class

[db_map_base_iterator](#)

get_bulk_bufsize

Function Details

```
u_int32_t get_bulk_bufsize()
```

Get bulk retrieval buffer size in bytes.

Return Value

Return current bulk buffer size or 0 if bulk retrieval is not enabled.

See Also

[db_base_iterator::get_bulk_bufsize\(\)](#)

Class

[db_map_base_iterator](#)

operator=

Function Details

```
const self& operator=(const self &itr)
```

Assignment operator.

This iterator will point to the same key/data pair as itr, and have the same configurations as itr.

Parameters

itr

The right value of assignment.

Return Value

The reference of itr.

See Also

[db_base_iterator::operator=\(const self&\)](#)

Class

[db_map_base_iterator](#)

Chapter 16. db_map_iterator

db_map_iterator

Public Members

| Member | Description |
|----------------------------------|--------------------------------|
| db_map_iterator | Copy constructor. |
| ~db_map_iterator | Destructor. |
| operator++ | Pre-increment. |
| operator-- | Pre-decrement. |
| operator * | Dereference operator. |
| operator-> | Arrow operator. |
| refresh | Refresh iterator cached value. |
| operator= | Assignment operator. |

Group

[iterator classes for db_map and db_multimap](#)

db_map_iterator

Function Details

```
db_map_iterator(const db_map_iterator< kdt, ddt,
                value_type_sub > &vi)
```

Copy constructor.

Parameters

vi

The other iterator of the same type to initialize this.

```
db_map_iterator(const db_map_base_iterator< kdt, realddt,
                ddt > &vi)
```

Base copy constructor.

Parameters

vi

Initialize from a base class iterator.

```
db_map_iterator(db_container *powner, u_int32_t b_bulk_retrieval=0,
                bool brmw=false, bool directdbget=true,
                bool b_read_only=false)
```

Constructor.

Parameters

b_bulk_retrieval

The bulk read buffer size. 0 means bulk read disabled.

brmw

Whether set DB_RMW flag in underlying cursor.

powner

The container which creates this iterator.

directdbget

Whether do direct database get rather than using key/data values cached in the iterator whenever read.

b_read_only

Whether open a read only cursor. Only effective when using Berkeley DB Concurrent Data Store.

```
db_map_iterator()
```

Default constructor, dose not create the cursor for now.

Group: Constructors and destructor

Do not create iterators directly using these constructors, but call [db_map::begin](#) or `db_multimap_begin` to get instances of this class.

[db_map::begin\(\)](#) [db_multimap::begin\(\)](#)

Class

[db_map_iterator](#)

~db_map_iterator

Function Details

```
virtual ~db_map_iterator()
```

Destructor.

Group: Constructors and destructor

Do not create iterators directly using these constructors, but call [db_map::begin](#) or `db_multimap_begin` to get instances of this class.

[db_map::begin\(\)](#) [db_multimap::begin\(\)](#)

Class

[db_map_iterator](#)

operator++

Function Details

```
self& operator++()
```

Pre-increment.

Return Value

This iterator after incremented.

See Also

[db_map_base_iterator::operator++\(\)](#)

```
self operator++(int)
```

Post-increment.

Return Value

Another iterator having the old value of this iterator.

See Also

[db_map_base_iterator::operator++\(int\)](#)

Class

[db_map_iterator](#)

operator--

Function Details

```
self& operator--()
```

Pre-decrement.

Return Value

This iterator after decremented.

See Also

[db_map_base_iterator::operator--\(\)](#)

```
self operator--(int)
```

Post-decrement.

Return Value

Another iterator having the old value of this iterator.

See Also

[db_map_base_iterator::operator--\(int\)](#)

Class

[db_map_iterator](#)

operator *

Function Details

```
reference operator *() const
```

Dereference operator.

Return the reference to the cached data element, which is an `pair<Key_type, ElementRef<T> >` object if T is a class type or an `pair<Key_type, ElementHolder<T> >` object if T is a C++ primitive data type.

Return Value

Current data element reference object, i.e. [ElementHolder](#) or [ElementRef](#) object.

Class

[db_map_iterator](#)

operator->

Function Details

```
pointer operator->>() const
```

Arrow operator.

Return the pointer to the cached data element, which is an `pair<Key_type, ElementRef<T> >` object if T is a class type or an `pair<Key_type, ElementHolder<T> >` object if T is a C++ primitive data type.

Return Value

Current data element reference object's address, i.e. address of [ElementHolder](#) or [ElementRef](#) object.

Class

[db_map_iterator](#)

refresh

Function Details

```
virtual int refresh(bool from_db=true) const
```

Refresh iterator cached value.

Parameters

from_db

If not doing direct database get and this parameter is true, we will retrieve data directly from db.

See Also

[db_base_iterator::refresh\(bool \)](#)

Class

[db_map_iterator](#)

operator=

Function Details

```
const self& operator=(const self &itr)
```

Assignment operator.

This iterator will point to the same key/data pair as itr, and have the same configurations as itr.

Parameters

itr

The right value of assignment.

Return Value

The reference of itr.

See Also

[db_base_iterator::operator=\(const self&\)](#)

Class

[db_map_iterator](#)

Chapter 17. iterator classes for `db_set` and `db_multiset`

Iterator classes for `db_set` and `db_multiset`.

Iterator classes for `db_set` and `db_multiset`.

[db_set_base_iterator](#) and [db_set_iterator](#) are the const iterator and iterator class for [db_set](#) and [db_multiset](#) .

They have identical behaviors to `std::set::const_iterator` and `std::set::iterator` respectively.

The difference between the two classes is that the [db_set_base_iterator](#) can only be used to read its referenced value, while [db_set_iterator](#) allows both read and write access. If the access pattern is readonly, it is strongly recommended that you use the const iterator because it is faster and more efficient.

The two classes inherit several functions from [db_map_base_iterator](#) and [db_map_iterator](#) respectively.

See Also

[db_map_base_iterator](#) [db_map_iterator](#)

Public Members

| Member | Description |
|--------------------------------------|-----------------------------------|
| db_set_base_iterator | <code>db_set_base_iterator</code> |
| db_set_iterator | <code>db_set_iterator</code> |

Group

[dbstl iterator classes](#)

Chapter 18. db_set_base_iterator

db_set_base_iterator

Public Members

| Member | Description |
|---------------------------------------|--------------------------------|
| ~db_set_base_iterator | Destructor. |
| db_set_base_iterator | Constructor. |
| operator++ | Post-increment. |
| operator-- | Post-decrement. |
| operator * | Dereference operator. |
| operator-> | Arrow operator. |
| refresh | Refresh iterator cached value. |

Group

[iterator classes for db_set and db_multiset](#)

~db_set_base_iterator

Function Details

```
virtual ~db_set_base_iterator()
```

Destructor.

Group: Constructors and destructor

Do not use these constructors to create iterators, but call `db_set::begin() const` or `db_multiset::begin() const` to create valid iterators.

Class

[db_set_base_iterator](#)

db_set_base_iterator

Function Details

```
db_set_base_iterator(db_container *powner, u_int32_t b_bulk_retrieval=0,  
    bool brmw=false, bool directdbget=true,  
    bool b_read_only=false)
```

Constructor.

Parameters

b_bulk_retrieval

The bulk read buffer size. 0 means bulk read disabled.

brmw

Whether set DB_RMW flag in underlying cursor.

powner

The container which creates this iterator.

directdbget

Whether do direct database get rather than using key/data values cached in the iterator whenever read.

b_read_only

Whether open a read only cursor. Only effective when using Berkeley DB Concurrent Data Store.

```
db_set_base_iterator()
```

Default constructor, dose not create the cursor for now.

```
db_set_base_iterator(const db_set_base_iterator &s)
```

Copy constructor.

Parameters

s

The other iterator of the same type to initialize this.

```
db_set_base_iterator(const base &bo)
```

Base copy constructor.

Parameters

bo

Initialize from a base class iterator.

Group: Constructors and destructor

Do not use these constructors to create iterators, but call `db_set::begin() const` or `db_multiset::begin() const` to create valid iterators.

Class

[db_set_base_iterator](#)

operator++

Function Details

```
self& operator++()
```

Post-increment.

Return Value

This iterator after incremented.

See Also

[db_map_base_iterator::operator++\(\)](#)

```
self operator++(int)
```

Pre-increment.

Return Value

Another iterator having the old value of this iterator.

See Also

[db_map_base_iterator::operator++\(int\)](#)

Group: Iterator movement operators.

These functions are identical to those of [db_map_base_iterator](#) and [db_map_iterator](#) and [db_set_iterator](#) .

Actually the iterator movement functions in the four classes are the same.

Class

[db_set_base_iterator](#)

operator--

Function Details

```
self& operator--()
```

Post-decrement.

Return Value

This iterator after decremented.

See Also

[db_map_base_iterator::operator--\(\)](#)

```
self operator--(int)
```

Pre-decrement.

Return Value

Another iterator having the old value of this iterator.

See Also

[db_map_base_iterator::operator--\(int\)](#)

Group: Iterator movement operators.

These functions are identical to those of [db_map_base_iterator](#) and [db_map_iterator](#) and [db_set_iterator](#).

Actually the iterator movement functions in the four classes are the same.

Class

[db_set_base_iterator](#)

operator *

Function Details

```
reference operator *()
```

Dereference operator.

Return the reference to the cached data element, which is an object of type T. You can only use the return value to read its referenced data element, can not update it.

Return Value

Current data element reference object, i.e. [ElementHolder](#) or [ElementRef](#) object.

Class

[db_set_base_iterator](#)

operator->

Function Details

```
pointer operator->>() const
```

Arrow operator.

Return the pointer to the cached data element, which is an object of type T. You can only use the return value to read its referenced data element, can not update it.

Return Value

Current data element reference object's address, i.e. address of [ElementHolder](#) or [ElementRef](#) object.

Class

[db_set_base_iterator](#)

refresh

Function Details

```
virtual int refresh(bool from_db=true) const
```

Refresh iterator cached value.

Parameters

from_db

If not doing direct database get and this parameter is true, we will retrieve data directly from db.

See Also

[db_base_iterator::refresh\(bool\)](#)

Class

[db_set_base_iterator](#)

Chapter 19. db_set_iterator

db_set_iterator

Public Members

| Member | Description |
|----------------------------------|--------------------------------|
| ~db_set_iterator | Destructor. |
| db_set_iterator | Constructor. |
| operator++ | Pre-increment. |
| operator-- | Pre-decrement. |
| operator * | Dereference operator. |
| operator-> | Arrow operator. |
| refresh | Refresh iterator cached value. |

Group

[iterator classes for db_set and db_multiset](#)

~db_set_iterator

Function Details

```
virtual ~db_set_iterator()
```

Destructor.

Group: Constructors and destructor

Do not use these constructors to create iterators, but call [db_set::begin\(\)](#) or [db_multiset::begin\(\)](#) to create valid ones.

Class

[db_set_iterator](#)

db_set_iterator

Function Details

```
db_set_iterator(db_container *powner, uint32_t b_bulk_retrieval=0,  
               bool brmw=false, bool directdbget=true,  
               bool b_read_only=false)
```

Constructor.

Parameters

b_bulk_retrieval

The bulk read buffer size. 0 means bulk read disabled.

brmw

Whether set DB_RMW flag in underlying cursor.

powner

The container which creates this iterator.

directdbget

Whether do direct database get rather than using key/data values cached in the iterator whenever read.

b_read_only

Whether open a read only cursor. Only effective when using Berkeley DB Concurrent Data Store.

```
db_set_iterator()
```

Default constructor, dose not create the cursor for now.

```
db_set_iterator(const db_set_iterator &s)
```

Copy constructor.

Parameters

s

The other iterator of the same type to initialize this.

```
db_set_iterator(const base &bo)
```

Base copy constructor.

Parameters

bo

Initialize from a base class iterator.

```
db_set_iterator(const db_set_base_iterator< kdt > &bs)
```

Sibling copy constructor.

Note that this class does not derive from [db_set_base_iterator](#) but from [db_map_iterator](#) .

Parameters

bs

Initialize from a base class iterator.

Group: Constructors and destructor

Do not use these constructors to create iterators, but call [db_set::begin\(\)](#) or [db_multiset::begin\(\)](#) to create valid ones.

Class

[db_set_iterator](#)

operator++

Function Details

```
self& operator++()
```

Pre-increment.

Identical to those of [db_map_iterator](#) .

Return Value

This iterator after incremented.

See Also

[db_map_iterator::operator++\(\)](#)

```
self operator++(int)
```

Post-increment.

Return Value

Another iterator having the old value of this iterator.

See Also

[db_map_iterator::operator++\(int\)](#)

Class

[db_set_iterator](#)

operator--

Function Details

```
self& operator--()
```

Pre-decrement.

Return Value

This iterator after decremented.

See Also

[db_map_iterator::operator--\(\)](#)

```
self operator--(int)
```

Post-decrement.

Return Value

Another iterator having the old value of this iterator.

See Also

[db_map_iterator::operator--\(int\)](#)

Class

[db_set_iterator](#)

operator *

Function Details

```
reference operator *()
```

Dereference operator.

Return the reference to the cached data element, which is an [ElementRef<T>](#) object if T is a class type or an [ElementHolder<T>](#) object if T is a C++ primitive data type.

Return Value

Current data element reference object, i.e. [ElementHolder](#) or [ElementRef](#) object.

Class

[db_set_iterator](#)

operator->

Function Details

```
pointer operator->>() const
```

Arrow operator.

Return the pointer to the cached data element, which is an [ElementRef<T>](#) object if T is a class type or an [ElementHolder<T>](#) object if T is a C++ primitive data type.

Return Value

Current data element reference object's address, i.e. address of [ElementHolder](#) or [ElementRef](#) object.

Class

[db_set_iterator](#)

refresh

Function Details

```
virtual int refresh(bool from_db=true) const
```

Refresh iterator cached value.

Parameters

from_db

If not doing direct database get and this parameter is true, we will retrieve data directly from db.

See Also

[db_base_iterator::refresh\(bool\)](#)

Class

[db_set_iterator](#)

Chapter 20. db_reverse_iterator

db_reverse_iterator

This class is the reverse class adaptor for all dbstl iterator classes.

It inherits from real iterator classes like [db_vector_iterator](#) , [db_map_iterator](#) or [db_set_iterator](#) .
When you call `container::rbegin()`, you will get an instance of this class.

See Also

[db_vector_base_iterator](#) [db_vector_iterator](#) [db_map_base_iterator](#) [db_map_iterator](#) [db_set_base_iterator](#) [db_set_iterator](#)

Public Members

| Member | Description |
|-------------------------------------|---|
| operator++ | Move this iterator forward by one element. |
| operator-- | Move this iterator backward by one element. |
| operator+ | Iterator shuffle operator. |
| operator- | Iterator shuffle operator. |
| operator+= | Iterator shuffle operator. |
| operator-= | Iterator shuffle operator. |
| operator< | Less compare operator. |
| operator> | Greater compare operator. |
| operator<= | Less equal compare operator. |
| operator>= | Greater equal compare operator. |
| db_reverse_iterator | Constructor. Construct from an iterator of wrapped type. |
| operator= | Assignment operator. |
| operator[] | Return the reference of the element which can be reached by moving this reverse iterator by Off times backward. |

Group

[dbstl iterator classes](#)

operator++

Function Details

```
self& operator++()
```

Move this iterator forward by one element.

Return Value

The moved iterator at new position.

```
self operator++(int)
```

Move this iterator forward by one element.

Return Value

The original iterator at old position.

Group: Reverse iterator movement functions

When we talk about reverse iterator movement, we think the container is a uni-directional range, represented by [begin, end), and this is true no matter we are using iterators or reverse iterators.

When an iterator is moved closer to "begin", we say it is moved forward, otherwise we say it is moved backward.

Class

[db_reverse_iterator](#)

operator--

Function Details

```
self& operator--()
```

Move this iterator backward by one element.

Return Value

The moved iterator at new position.

```
self operator--(int)
```

Move this iterator backward by one element.

Return Value

The original iterator at old position.

Group: Reverse iterator movement functions

When we talk about reverse iterator movement, we think the container is a uni-directional range, represented by [begin, end), and this is true no matter we are using iterators or reverse iterators.

When an iterator is moved closer to "begin", we say it is moved forward, otherwise we say it is moved backward.

Class

[db_reverse_iterator](#)

operator+

Function Details

```
self operator+(difference_type n) const
```

Iterator shuffle operator.

Return a new iterator by moving this iterator forward by n elements.

Parameters

n

The amount and direction of movement. If negative, will move towards reverse direction.

Return Value

A new iterator at new position.

Group: Operators for random reverse iterators

Methods below only applies to random iterators.

```
/////
```

Return a new iterator by moving this iterator backward or forward by n elements.

Class

[db_reverse_iterator](#)

operator-

Function Details

```
self operator-(difference_type n) const
```

Iterator shuffle operator.

Return a new iterator by moving this iterator backward by n elements.

Parameters

n

The amount and direction of movement. If negative, will move towards reverse direction.

Return Value

A new iterator at new position.

```
difference_type operator-(const self &itr) const
```

Return the negative value of the difference of indices of elements this iterator and itr are sitting on.

Parameters

itr

The other reverse iterator.

Return Value

itr.index - this->index.

Group: Operators for random reverse iterators

Methods below only applies to random iterators.

```
/////
```

Return a new iterator by moving this iterator backward or forward by n elements.

Class

[db_reverse_iterator](#)

operator+=

Function Details

```
const self& operator+=(difference_type n)
```

Iterator shuffle operator.

Move this iterator forward by n elements and then return it.

Parameters

n

The amount and direction of movement. If negative, will move towards reverse direction.

Return Value

This iterator at new position.

Group: Operators for random reverse iterators

Move this iterator backward or forward by n elements and then return it.

Class

[db_reverse_iterator](#)

operator--

Function Details

```
const self& operator--(difference_type n)
```

Iterator shuffle operator.

Move this iterator backward by n elements and then return it.

Parameters

n

The amount and direction of movement. If negative, will move towards reverse direction.

Return Value

This iterator at new position.

Group: Operators for random reverse iterators

Move this iterator backward or forward by n elements and then return it.

Class

[db_reverse_iterator](#)

operator<

Function Details

```
bool operator<(const self &itr) const
```

Less compare operator.

Group: Operators for random reverse iterators

Reverse iterator comparison against reverse iterator itr, the one sitting on elements with less index is returned to be greater.

Class

[db_reverse_iterator](#)

operator>

Function Details

```
bool operator>(const self &itr) const
```

Greater compare operator.

Group: Operators for random reverse iterators

Reverse iterator comparison against reverse iterator itr, the one sitting on elements with less index is returned to be greater.

Class

[db_reverse_iterator](#)

operator<=

Function Details

```
bool operator<=(const self &itr) const
```

Less equal compare operator.

Group: Operators for random reverse iterators

Reverse iterator comparison against reverse iterator itr, the one sitting on elements with less index is returned to be greater.

Class

[db_reverse_iterator](#)

operator>=

Function Details

```
bool operator>=(const self &itr) const
```

Greater equal compare operator.

Group: Operators for random reverse iterators

Reverse iterator comparison against reverse iterator itr, the one sitting on elements with less index is returned to be greater.

Class

[db_reverse_iterator](#)

db_reverse_iterator

Function Details

```
db_reverse_iterator(const iterator &vi)
```

Constructor. Construct from an iterator of wrapped type.

```
db_reverse_iterator(const self &ritr)
```

Copy constructor.

```
db_reverse_iterator(const db_reverse_iterator< twin_itr_t,  
    iterator > &ritr)
```

Copy constructor.

```
db_reverse_iterator()
```

Default constructor.

Class

[db_reverse_iterator](#)

operator=

Function Details

```
const self& operator=(const self &ri)
```

Assignment operator.

Parameters

ri

The iterator to assign with.

Return Value

The iterator ri.

See Also

[db_base_iterator::operator=\(const self&\)](#)

Class

[db_reverse_iterator](#)

operator[]

Function Details

```
value_type_wrap operator[](difference_type Off) const
```

Return the reference of the element which can be reached by moving this reverse iterator by Off times backward.

If Off is negative, the movement will be forward.

Class

[db_reverse_iterator](#)

Chapter 21. dbstl helper classes

dbstl helper classes

dbstl helper classes

Classes of this module help to achieve various features of dbstl.

Public Members

| Member | Description |
|--|--|
| DbstlElemTraits | DbstlElemTraits |
| DbstlDbt | DbstlDbt |
| BulkRetrievalOption | BulkRetrievalOption |
| ReadModifyWriteOption | ReadModifyWriteOption |
| ElementRef and ElementHolder wrappers. | ElementRef and ElementHolder wrappers. |

Group

None

Chapter 22. ElementRef and ElementHolder wrappers

ElementRef and ElementHolder wrappers.

ElementRef and ElementHolder wrappers.

[ElementRef](#) and [ElementHolder](#) are the data element pointed to by an iterator, each iterator object has an [ElementRef](#) or [ElementHolder](#) object to hold(store) the current data element that the iterator points to.

They not only hold current data element, but also references the underlying position in the database by referring to the iterator which sits on the key/data pair, so that they can also be used to update the data element that the iterator points to.

Thus the two classes are used as the stored data, for example, used in `iterator::operator*()`, as its return type, that is, `iterator::reference` is `ElementRef<ddt>&` or `ElementHolder<ddt>&`. Using one of the two types of return type enables `*itr` to act both as a left value and a right value. This is also true for `container::operator[]`.

The difference between [ElementRef](#) and [ElementHolder](#) is that [ElementRef](#) derives from type `ddt` but [ElementHolder](#) has a data member of type `ddt` to store the data element.

Deriving from type `ddt` will enable [ElementRef](#) users to access the members of the object stored in the container, such that `operator*()` has full std iterator semantics.

But for primitive types, we can't derive from them, so users have to use the [ElementHolder](#) wrapper template which stores the primitive type values, and you need to specify the element wrapper type explicitly like this: `db_vector <int, ElementHolder<int> >`, because by default the element wrapper type is [ElementRef](#) .

And in order not to clash with `ddt` type members, all members in [ElementRef](#) template are prefixed with `_DB_STL_` string, and the rest of `dbstl` does not know that there are actually two element wrapper classes---they are using the same set of method names, thus the two class templates have identical public method names and methods of the same name have identical behaviors.

An object of the classes corresponds to one iterator, to allow assigning value to the key/data pair that an iterator points to if it associates an iterator, and thus associates a key/data pair in the database. In most occasions the iterator "owns" the [ElementRef](#)/[ElementHolder](#) wrapper object, except this situation: in order to support methods like `db_vector<>::operator[]` and `db_map<>::operator[]`, which return data element references, the [ElementRef](#)/[ElementHolder](#) wrapper object has to "own" the iterator.

Public Members

| Member | Description |
|----------------------------|----------------------------|
| ElementRef | ElementRef |

| Member | Description |
|-------------------------------|---------------|
| ElementHolder | ElementHolder |

Group

[dbstl helper classes](#)

Chapter 23. ElementHolder

ElementHolder

The wrapper for primitive types, and it has identical usage and public interface to [ElementRef](#) .

See Also

[ElementRef](#) .

Public Members

| Member | Description |
|--------------------------------------|--|
| _DB_STL_CopyData | |
| _DB_STL_CopyData_int | |
| _DB_STL_GetIterator | |
| _DB_STL_GetData | |
| _DB_STL_SetIterator | |
| _DB_STL_SetData | |
| _DB_STL_SetDelIttr | |
| ElementHolder | Constructor. |
| ~ElementHolder | Destructor. |
| operator+= | |
| operator-= | |
| operator *= | |
| operator/= | |
| operator%= | |
| operator &= | |
| operator = | |
| operator^= | |
| operator>>= | |
| operator<<= | |
| operator++ | |
| operator-- | |
| operator= | |
| _DB_STL_value | Returns the data element this wrapper object wraps;. |
| _DB_STL_StoreElement | Store data element changes. |
| operator ptype | Type conversion operator. |

Group

[ElementRef and ElementHolder wappers](#)

_DB_STL_CopyData

Function Details

```
void _DB_STL_CopyData(const self &dt2)
```

Group: Private members that have to be public.

These members has to be public but dbstl users should never access them.

Class

[ElementHolder](#)

_DB_STL_CopyData_int

Function Details

```
void _DB_STL_CopyData_int(const T &src)
```

```
void _DB_STL_CopyData_int(T *const &src)
```

```
void _DB_STL_CopyData_int(const T *const &src)
```

```
void _DB_STL_CopyData_int(T *&src)
```

```
void _DB_STL_CopyData_int(const T *&src)
```

Group: Private members that have to be public.

These members has to be public but dbstl users should never access them.

Class

[ElementHolder](#)

_DB_STL_GetIterator

Function Details

```
iterator_type* _DB_STL_GetIterator() const
```

Group: Private members that have to be public.

These members has to be public but dbstl users should never access them.

Class

[ElementHolder](#)

_DB_STL_GetData

Function Details

```
int _DB_STL_GetData(pType &d) const
```

Group: Private members that have to be public.

These members has to be public but dbstl users should never access them.

Class

[ElementHolder](#)

_DB_STL_SetIterator

Function Details

```
void _DB_STL_SetIterator(iterator_type *pitr)
```

Group: Private members that have to be public.

These members has to be public but dbstl users should never access them.

Class

[ElementHolder](#)

_DB_STL_SetData

Function Details

```
void _DB_STL_SetData(const ptype &d)
```

Group: Private members that have to be public.

These members has to be public but dbstl users should never access them.

Class

[ElementHolder](#)

_DB_STL_SetDelItr

Function Details

```
void _DB_STL_SetDelItr()
```

Group: Private members that have to be public.

These members has to be public but dbstl users should never access them.

Class

[ElementHolder](#)

ElementHolder

Function Details

```
ElementHolder(iterator_type *pitr=NULL)
```

Constructor.

This constructor can optionally accept an iterator to associate its wrapped element with the underlying key/data pair in the database. If no iterator is specified, this object is only a wrapper and can't access the database.

Parameters

pitr

The iterator owning this object.

```
ElementHolder(const ptype &dt)
```

Constructor.

This constructor initializes an [ElementHolder](#) wrapper without an iterator, thus it can only be used to wrap data element in memory, can't access database.

Parameters

dt

The base class object to initialize this object.

```
ElementHolder(const self &other)
```

Copy constructor.

This constructor initializes an [ElementHolder](#) instance from an existing one, copying its wrapped element, and if the "other" object has a valid iterator, the constructor will duplicate the iterator and thus the underlying cursor, so that the new instance can access the database.

Parameters

other

The object to clone from.

Class

[ElementHolder](#)

~ElementHolder

Function Details

```
~ElementHolder()
```

Destructor.

Class

[ElementHolder](#)

operator+=

Function Details

```
const self& operator+=(const ElementHolder< T2 > &p2)
```

```
const self& operator+=(const self &p2)
```

Group: Math operators.

[ElementHolder](#) class templates also have all C/C++ self mutating operators for numeric primitive types, including: +=, -=, *=, /=, =, <=>, >=>, &=, |=, ^=, ++, --. These operators should not be used when ddt is a sequence pointer type like char* or wchar_t* or T*, otherwise the behavior is undefined.

These methods exist only to override default behavior to store the new updated value, otherwise, the type convert operator could have done all the job. As you know, some of them are not applicable to float or double types or [ElementHolder](#) wrapper types for float/double types. These operators not only modifies the cached data element, but also stores new value to database if it associates a database key/data pair.

Class

[ElementHolder](#)

operator-=

Function Details

```
const self& operator-=(const ElementHolder< T2 > &p2)
```

```
const self& operator-=(const self &p2)
```

Group: Math operators.

[ElementHolder](#) class templates also have all C/C++ self mutating operators for numeric primitive types, including: +=, -=, *=, /=, =, <=>, >=>, &=, |=, ^=, ++, --. These operators should not be used when ddt is a sequence pointer type like char* or wchar_t* or T*, otherwise the behavior is undefined.

These methods exist only to override default behavior to store the new updated value, otherwise, the type convert operator could have done all the job. As you know, some of them are not applicable to float or double types or [ElementHolder](#) wrapper types for float/double types. These operators not only modifies the cached data element, but also stores new value to database if it associates a database key/data pair.

Class

[ElementHolder](#)

operator *=

Function Details

```
const self& operator *=(const ElementHolder< T2 > &p2)
```

```
const self& operator *=(const self &p2)
```

Group: Math operators.

[ElementHolder](#) class templates also have all C/C++ self mutating operators for numeric primitive types, including: +=, -=, *=, /=, =, <=<=, >>=, &=, |=, ^=, ++, --. These operators should not be used when ddt is a sequence pointer type like char* or wchar_t* or T*, otherwise the behavior is undefined.

These methods exist only to override default behavior to store the new updated value, otherwise, the type convert operator could have done all the job. As you know, some of them are not applicable to float or double types or [ElementHolder](#) wrapper types for float/double types. These operators not only modifies the cached data element, but also stores new value to database if it associates a database key/data pair.

Class

[ElementHolder](#)

operator/=

Function Details

```
const self& operator/=(const ElementHolder< T2 > &p2)
```

```
const self& operator/=(const self &p2)
```

Group: Math operators.

[ElementHolder](#) class templates also have all C/C++ self mutating operators for numeric primitive types, including: +=, -=, *=, /=, =, <=, >=, &=, |=, ^=, ++, --. These operators should not be used when ddt is a sequence pointer type like char* or wchar_t* or T*, otherwise the behavior is undefined.

These methods exist only to override default behavior to store the new updated value, otherwise, the type convert operator could have done all the job. As you know, some of them are not applicable to float or double types or [ElementHolder](#) wrapper types for float/double types. These operators not only modifies the cached data element, but also stores new value to database if it associates a database key/data pair.

Class

[ElementHolder](#)

operator%=

Function Details

```
const self& operator%=(const ElementHolder< T2 > &p2)
```

```
const self& operator%=(const self &p2)
```

Group: Math operators.

[ElementHolder](#) class templates also have all C/C++ self mutating operators for numeric primitive types, including: +=, -=, *=, /=, =, <=<=, >>=, &=, |=, ^=, ++, --. These operators should not be used when ddt is a sequence pointer type like char* or wchar_t* or T*, otherwise the behavior is undefined.

These methods exist only to override default behavior to store the new updated value, otherwise, the type convert operator could have done all the job. As you know, some of them are not applicable to float or double types or [ElementHolder](#) wrapper types for float/double types. These operators not only modifies the cached data element, but also stores new value to database if it associates a database key/data pair.

Class

[ElementHolder](#)

operator &=

Function Details

```
const self& operator &=(const ElementHolder< T2 > &p2)
```

```
const self& operator &=(const self &p2)
```

Group: Math operators.

[ElementHolder](#) class templates also have all C/C++ self mutating operators for numeric primitive types, including: +=, -=, *=, /=, =, <=>, >=>, &=, |=, ^=, ++, --. These operators should not be used when ddt is a sequence pointer type like char* or wchar_t* or T*, otherwise the behavior is undefined.

These methods exist only to override default behavior to store the new updated value, otherwise, the type convert operator could have done all the job. As you know, some of them are not applicable to float or double types or [ElementHolder](#) wrapper types for float/double types. These operators not only modifies the cached data element, but also stores new value to database if it associates a database key/data pair.

Class

[ElementHolder](#)

operator|=

Function Details

```
const self& operator|=(const ElementHolder< T2 > &p2)
```

```
const self& operator|=(const self &p2)
```

Group: Math operators.

[ElementHolder](#) class templates also have all C/C++ self mutating operators for numeric primitive types, including: +=, -=, *=, /=, =, <=<=, >>=, &=, |=, ^=, ++, --. These operators should not be used when ddt is a sequence pointer type like char* or wchar_t* or T*, otherwise the behavior is undefined.

These methods exist only to override default behavior to store the new updated value, otherwise, the type convert operator could have done all the job. As you know, some of them are not applicable to float or double types or [ElementHolder](#) wrapper types for float/double types. These operators not only modifies the cached data element, but also stores new value to database if it associates a database key/data pair.

Class

[ElementHolder](#)

operator^=

Function Details

```
const self& operator^=(const ElementHolder< T2 > &p2)
```

```
const self& operator^=(const self &p2)
```

Group: Math operators.

[ElementHolder](#) class templates also have all C/C++ self mutating operators for numeric primitive types, including: +=, -=, *=, /=, =, <=, >=, &=, |=, ^=, ++, --. These operators should not be used when ddt is a sequence pointer type like char* or wchar_t* or T*, otherwise the behavior is undefined.

These methods exist only to override default behavior to store the new updated value, otherwise, the type convert operator could have done all the job. As you know, some of them are not applicable to float or double types or [ElementHolder](#) wrapper types for float/double types. These operators not only modifies the cached data element, but also stores new value to database if it associates a database key/data pair.

Class

[ElementHolder](#)

operator>>=

Function Details

```
const self& operator>>=(size_t n)
```

Group: Math operators.

[ElementHolder](#) class templates also have all C/C++ self mutating operators for numeric primitive types, including: +=, -=, *=, /=, =, <<=, >>=, &=, |=, ^=, ++, --. These operators should not be used when ddt is a sequence pointer type like `char*` or `wchar_t*` or `T*`, otherwise the behavior is undefined.

These methods exist only to override default behavior to store the new updated value, otherwise, the type convert operator could have done all the job. As you know, some of them are not applicable to float or double types or [ElementHolder](#) wrapper types for float/double types. These operators not only modifies the cached data element, but also stores new value to database if it associates a database key/data pair.

Class

[ElementHolder](#)

operator<<=

Function Details

```
const self& operator<<=(size_t n)
```

Group: Math operators.

[ElementHolder](#) class templates also have all C/C++ self mutating operators for numeric primitive types, including: +=, -=, *=, /=, =, <<=, >>=, &=, |=, ^=, ++, -- These operators should not be used when ddt is a sequence pointer type like char* or wchar_t* or T*, otherwise the behavior is undefined.

These methods exist only to override default behavior to store the new updated value, otherwise, the type convert operator could have done all the job. As you know, some of them are not applicable to float or double types or [ElementHolder](#) wrapper types for float/double types. These operators not only modifies the cached data element, but also stores new value to database if it associates a database key/data pair.

Class

[ElementHolder](#)

operator++

Function Details

```
self& operator++()
```

```
self operator++(int)
```

Group: Math operators.

[ElementHolder](#) class templates also have all C/C++ self mutating operators for numeric primitive types, including: +=, -=, *=, /=, =, <=, >=, &=, |=, ^=, ++, --. These operators should not be used when ddt is a sequence pointer type like char* or wchar_t* or T*, otherwise the behavior is undefined.

These methods exist only to override default behavior to store the new updated value, otherwise, the type convert operator could have done all the job. As you know, some of them are not applicable to float or double types or [ElementHolder](#) wrapper types for float/double types. These operators not only modifies the cached data element, but also stores new value to database if it associates a database key/data pair.

Class

[ElementHolder](#)

operator--

Function Details

```
self& operator--()
```

```
self operator--(int)
```

Group: Math operators.

[ElementHolder](#) class templates also have all C/C++ self mutating operators for numeric primitive types, including: +=, -=, *=, /=, =, <=<=, >>=, &=, |=, ^=, ++, --. These operators should not be used when ddt is a sequence pointer type like char* or wchar_t* or T*, otherwise the behavior is undefined.

These methods exist only to override default behavior to store the new updated value, otherwise, the type convert operator could have done all the job. As you know, some of them are not applicable to float or double types or [ElementHolder](#) wrapper types for float/double types. These operators not only modifies the cached data element, but also stores new value to database if it associates a database key/data pair.

Class

[ElementHolder](#)

operator=

Function Details

```
const ptype& operator=(const ptype &dt2)
```

```
const self& operator=(const self &dt2)
```

Group: Math operators.

[ElementHolder](#) class templates also have all C/C++ self mutating operators for numeric primitive types, including: +=, -=, *=, /=, =, <=<=, >>=, &=, |=, ^=, ++, --. These operators should not be used when ddt is a sequence pointer type like char* or wchar_t* or T*, otherwise the behavior is undefined.

These methods exist only to override default behavior to store the new updated value, otherwise, the type convert operator could have done all the job. As you know, some of them are not applicable to float or double types or [ElementHolder](#) wrapper types for float/double types. These operators not only modifies the cached data element, but also stores new value to database if it associates a database key/data pair.

Class

[ElementHolder](#)

_DB_STL_value

Function Details

```
const ptype& _DB_STL_value() const
```

Returns the data element this wrapper object wraps;.

```
ptype& _DB_STL_value()
```

Returns the data element this wrapper object wraps;.

Group: Element value read and write operations.

Functions to store or get the referenced value.

Class

[ElementHolder](#)

_DB_STL_StoreElement

Function Details

```
void _DB_STL_StoreElement()
```

Store data element changes.

This method should be called after this object is modified by calling methods of ddt or directly modifying its data members. Otherwise the changes is gone without going into database.

When db_base_iterator's directdb_get_ member is true, you should call this function after they make changes to ddt's data member and before they call the next operator* or operator-> otherwise the change is lost; If the change is done via ElementHolder<>::operator=(), you don't need to call this function.

Group: Element value read and write operations.

Functions to store or get the referenced value.

Class

[ElementHolder](#)

operator ptype

Function Details

```
operator ptype() const
```

Type conversion operator.

This function is a type converter. Where an automatic type conversion is needed, this function is called to convert this object into the primitive type it wraps.

Class

[ElementHolder](#)

Chapter 24. ElementRef

ElementRef

[ElementRef](#) element wrapper for classes and structs.

See Also

[ElementHolder](#)

Public Members

| Member | Description |
|--------------------------------------|--|
| ~ElementRef | Destructor. |
| ElementRef | Constructor. |
| operator= | Assignment Operator. |
| _DB_STL_StoreElement | Store data element changes. |
| _DB_STL_value | Returns the data element this wrapper object wraps;. |
| _DB_STL_SetDelIter | |
| _DB_STL_CopyData | |
| _DB_STL_GetIterator | |
| _DB_STL_GetData | |
| _DB_STL_SetIterator | |
| _DB_STL_SetData | |

Group

[ElementRef](#) and [ElementHolder](#) wrappers

~ElementRef

Function Details

```
~ElementRef()
```

Destructor.

Class

[ElementRef](#)

ElementRef

Function Details

```
ElementRef(iterator_type *pitr=NULL)
```

Constructor.

This constructor can optionally accept an iterator to associate its wrapped element with the underlying key/data pair in the database. If no iterator is specified, this object is only a wrapper and can't access the database.

Parameters

pitr

The iterator owning this object.

```
ElementRef(const ddt &dt)
```

Constructor.

This constructor initializes an [ElementRef](#) wrapper without an iterator, thus it can only be used to wrap data element in memory, can't access database.

Parameters

dt

The base class object to initialize this object.

```
ElementRef(const self &other)
```

Copy constructor.

This constructor initializes an [ElementRef](#) instance from an existing one, copying its wrapped element, and if the "other" object has a valid iterator, the constructor will duplicate the iterator and thus the underlying cursor, so that the new instance can access the database.

Parameters

other

The object to clone from.

Class[ElementRef](#)

operator=

Function Details

```
const ddt& operator=(const ddt &dt2)
```

Assignment Operator.

Parameters

dt2

The data value to assign with.

Return Value

The object dt2's reference.

```
const self& operator=(const self &me)
```

Assignment Operator.

Parameters

me

The object to assign with.

Return Value

The object me's reference.

Group: Assignment operators.

The operators are used not only to store right value into this object, but also store it into database if it associates a database key/data pair.

So if you modify the referenced data element via this method, you don't need to call [_DB_STL_StoreElement\(\)](#) again.

Class

[ElementRef](#)

_DB_STL_StoreElement

Function Details

```
void _DB_STL_StoreElement()
```

Store data element changes.

This method should be called after this object is modified by calling methods of ddt or directly modifying its data members. Otherwise the changes is gone without going into database.

When db_base_iterator's directdb_get_ member is true, you should call this function after they make changes to ddt's data member and before they call the next operator* or operator-> otherwise the change is lost; If the change is done via ElementHolder<>::operator=(), you don't need to call this function.

Group: Element value read and write functions.

Functions to store or get refered element value.

Class

[ElementRef](#)

_DB_STL_value

Function Details

```
const ddt& _DB_STL_value() const
```

Returns the data element this wrapper object wraps;.

```
ddt& _DB_STL_value()
```

Returns the data element this wrapper object wraps;.

Group: Element value read and write functions.

Functions to store or get referred element value.

Class

[ElementRef](#)

_DB_STL_SetDelItr

Function Details

```
void _DB_STL_SetDelItr()
```

Group: Private members that have to be public.

These members has to be public but dbstl users should never access them.

Class

[ElementRef](#)

_DB_STL_CopyData

Function Details

```
void _DB_STL_CopyData(const self &dt2)
```

```
void _DB_STL_CopyData(const ddt &dt2)
```

Group: Private members that have to be public.

These members has to be public but dbstl users should never access them.

Class

[ElementRef](#)

_DB_STL_GetIterator

Function Details

```
iterator_type* _DB_STL_GetIterator() const
```

Group: Private members that have to be public.

These members has to be public but dbstl users should never access them.

Class

[ElementRef](#)

_DB_STL_GetData

Function Details

```
int _DB_STL_GetData(ddt &d) const
```

Group: Private members that have to be public.

These members has to be public but dbstl users should never access them.

Class

[ElementRef](#)

_DB_STL_SetIterator

Function Details

```
void _DB_STL_SetIterator(iterator_type *pitr)
```

Group: Private members that have to be public.

These members has to be public but dbstl users should never access them.

Class

[ElementRef](#)

_DB_STL_SetData

Function Details

```
void _DB_STL_SetData(const ddt &d)
```

Group: Private members that have to be public.

These members has to be public but dbstl users should never access them.

Class

[ElementRef](#)

Chapter 25. DbstlDbt

DbstlDbt

You can persist all bytes in a chunk of contiguous memory by constructing an [DbstlDbt](#) object A (use malloc to allocate the required number of bytes for A.data and copy the bytes to be stored into A.data, set other fields as necessary) and store A into a container, e.g.

`db_vector<DbstlDbt>`, this stores the bytes rather than the object A into the underlying database. The [DbstlDbt](#) class can help you avoid memory leaks, so it is strongly recommended that you use [DbstlDbt](#) rather than `Dbt` class.

[DbstlDbt](#) derives from `Dbt` class, and it does a deep copy on copy construction and assignment --by calling malloc to allocate its own memory and then copying the bytes to it; Conversely the destructor will free the memory on destruction if the data pointer is non-NULL. The destructor assumes the memory is allocated via malloc, hence why you are required to call malloc to allocate memory in order to use [DbstlDbt](#).

[DbstlDbt](#) simply inherits all methods from `Dbt` with no extra new methods except the constructors/destructor and assignment operator, so it is easy to use.

In practice you rarely need to use [DbstlDbt](#) or `Dbt` because `dbstl` enables you to store any complex objects or primitive data. Only when you need to store raw bytes, e.g. a bitmap, do you need to use [DbstlDbt](#).

Hence, [DbstlDbt](#) is the right class to use to store any object into Berkeley DB via `dbstl` without memory leaks.

Don't free the memory referenced by [DbstlDbt](#) objects, it will be freed when the [DbstlDbt](#) object is destructed.

Please refer to the two examples using [DbstlDbt](#) in `TestAssoc::test_arbitrary_object_storage` and `TestAssoc::test_char_star_string_storage` member functions, which illustrate how to correctly use [DbstlDbt](#) in order to store raw bytes.

This class handles the task of allocating and de-allocating memory internally. Although it can be used to store data which cannot be handled by the [DbstlElemTraits](#) class, in practice, it is usually more convenient to register callbacks in the [DbstlElemTraits](#) class for the type you are storing/retrieving using `dbstl`.

Public Members

| Member | Description |
|---------------------------|--|
| DbstlDbt | Construct an object with an existing chunk of memory of size1 bytes, referred by data1,. |
| ~DbstlDbt | The memory will be free'd by the destructor. |
| operator= | The memory will be reallocated if necessary. |
| free_mem | Users don't need to call this function. |

Group

[dbstl helper classes](#)

DbstlDbt

Function Details

```
DbstlDbt(void *data1,  
         u_int32_t size1)
```

Construct an object with an existing chunk of memory of size1 bytes, referred by data1,.

```
DbstlDbt()
```

```
DbstlDbt(const DbstlDbt &d)
```

This copy constructor does a deep copy.

Class

[DbstlDbt](#)

~DbstlDbt

Function Details

```
~DbstlDbt()
```

The memory will be free'd by the destructor.

Class

[DbstlDbt](#)

operator=

Function Details

```
const DbstlDbt& operator=(const DbstlDbt &d)
```

The memory will be reallocated if neccessary.

Class

[DbstlDbt](#)

free_mem

Function Details

```
void free_mem()
```

Users don't need to call this function.

Class

[DbstlDbt](#)

Chapter 26. DbstlElemTraits

DbstlElemTraits

This class is used to register callbacks to manipulate an object of a complex type.

These callbacks are used by dbstl at runtime to manipulate the object.

A complex type is a type whose members are not located in a contiguous chunk of memory. For example, the following class A is a complex type because for any instance a of class A, a.b_ points to another object of type B, and dbstl treats the object that a.b_ points to as part of the data of the instance a. Hence, if the user needs to store a.b_ into a dbstl container, the user needs to register an appropriate callback to de-reference and store the object referenced by a.b. Similarly, the user also needs to register callbacks to marshall an array as well as to count the number of elements in such an array.

```
class A { int m; B *p_; }; class B { int n; };
```

The user also needs to register callbacks for i). returning an object; ii). size in bytes; iii). Marshalling and unmarshalling an object; iv). Copying a complex object and assigning an object to another object of the same type; v). Element comparison. vi). Compare two sequences of any type of objects; vii). Measuring the length of an object sequence and copy an object sequence.

Several elements located in a contiguous chunk of memory form a sequence. An element of a sequence may be a simple object located at a contiguous memory chunk, or a complex object, i.e. some of its members may contain references (pointers) to another region of memory. It is not necessary to store a special object to denote the end of the sequence. The callback to traverse the constituent elements of the sequence needs to be able to determine the end of the sequence.

Marshalling means packing the object's data members into a contiguous chunk of memory; unmarshalling is the opposite of marshalling. In other words, when you unmarshall an object, its data members are populated with values from a previously marshalled version of the object.

The callbacks need not be set to every type explicitly. . dbstl will check if a needed callback function of this type is provided. If one is available, dbstl will use the registered callback. If the appropriate callback is not provided, dbstl will use reasonable defaults to do the job.

For returning the size of an object, the default behavior is to use the sizeof() operator; For marshalling and unmarshalling, dbstl uses memcpy, so the default behavior is sufficient for simple types whose data reside in a contiguous chunk of memory; Dbstl uses >, == and < for comparison operations; For char* and wchar_t * strings, dbstl already provides the appropriate callbacks, so you do not need to register them. In general, if the default behavior is adequate, you don't need to register the corresponding callback.

If you have registered proper callbacks, the DbstlElemTraits<T> can also be used as the char_traits<T> class for std::basic_string<T, char_traits<T>, >, and you can enable your class T to form a basic_string<T, DbstlElemTraits<T>, >, and use basic_string's functionality and the algorithms to manipulate it.

Public Members

| Member | Description |
|---|---|
| assign | Assign one object to another. |
| eq | Check for equality of two objects. |
| lt | Less than comparison. |
| compare | Sequence comparison. |
| length | Returns the number of elements in sequence seq1. |
| copy | Copy first cnt number of elements from seq2 to seq1. |
| find | Find within the first cnt elements of sequence seq the position of element equal to elem. |
| move | Sequence movement. |
| to_char_type | |
| to_int_type | |
| eq_int_type | |
| eof | |
| not_eof | |
| set_restore_function | |
| get_restore_function | |
| set_assign_function | |
| get_assign_function | |
| get_size_function | |
| set_size_function | |
| get_copy_function | |
| set_copy_function | |
| set_sequence_len_function | |
| get_sequence_len_function | |
| get_sequence_copy_function | |
| set_sequence_copy_function | |
| set_compare_function | |
| get_compare_function | |
| set_sequence_compare_function | |
| get_sequence_compare_function | |
| set_sequence_n_compare_function | |
| get_sequence_n_compare_function | |

| Member | Description |
|----------------------------------|--|
| instance | Factory method to create a singleton instance of this class. |
| ~DbstlElemTraits | |
| DbstlElemTraits | |

Group

[dbstl helper classes](#)

assign

Function Details

```
static void assign(T &left,  
                  const T &right)
```

Assign one object to another.

```
static T* assign(T *seq, size_t cnt,  
                T elem)
```

Assign first cnt number of elements of sequence seq with the value of elem.

Group: Interface compatible with `std::string`'s `char_traits`.

Following are `char_traits` functions, which make this class `char_traits` compatible, so that it can be used in `std::basic_string` template, and be manipulated by the C++ STL algorithms.

Class

[DbstlElemTraits](#)

eq

Function Details

```
static bool eq(const T &left,
               const T &right)
```

Check for equality of two objects.

Group: Interface compatible with `std::string`'s `char_traits`.

Following are `char_traits` functions, which make this class `char_traits` compatible, so that it can be used in `std::basic_string` template, and be manipulated by the C++ STL algorithms.

Class

[DbstElemTraits](#)

lt

Function Details

```
static bool lt(const T &left,  
              const T &right)
```

Less than comparison.

Returns if object left is less than object right.

Group: Interface compatible with `std::string`'s `char_traits`.

Following are `char_traits` functions, which make this class `char_traits` compatible, so that it can be used in `std::basic_string` template, and be manipulated by the C++ STL algorithms.

Class

[DbstlElemTraits](#)

compare

Function Details

```
static int compare(const T *seq1, const T *seq2,
                  size_t cnt)
```

Sequence comparison.

Compares the first cnt number of elements in the two sequences seq1 and seq2, returns negative/0/positive if seq1 is less/equal/greater than seq2.

Group: Interface compatible with `std::string`'s `char_traits`.

Following are `char_traits` functions, which make this class `char_traits` compatible, so that it can be used in `std::basic_string` template, and be manipulated by the C++ STL algorithms.

Class

[DbstlElemTraits](#)

length

Function Details

```
static size_t length(const T *seq)
```

Returns the number of elements in sequence seq1.

Note that seq1 may or may not end with a trailing ", it is completely user's responsibility for this decision, though seq[0], seq[1],... seq[length - 1] are all sequence seq's memory.

Group: Interface compatible with std::string's char_traits.

Following are char_traits functions, which make this class char_traits compatible, so that it can be used in std::basic_string template, and be manipulated by the c++ stl algorithms.

Class

[DbstElemTraits](#)

copy

Function Details

```
static T* copy(T *seq1, const T *seq2,
              size_t cnt)
```

Copy first cnt number of elements from seq2 to seq1.

Group: Interface compatible with `std::string`'s `char_traits`.

Following are `char_traits` functions, which make this class `char_traits` compatible, so that it can be used in `std::basic_string` template, and be manipulated by the C++ STL algorithms.

Class

[DbstElemTraits](#)

find

Function Details

```
static const T* find(const T *seq, size_t cnt,
                    const T &elem)
```

Find within the first cnt elements of sequence seq the position of element equal to elem.

Group: Interface compatible with std::string's char_traits.

Following are char_traits functions, which make this class char_traits compatible, so that it can be used in std::basic_string template, and be manipulated by the c++ stl algorithms.

Class

[DbstElemTraits](#)

move

Function Details

```
static T* move(T *seq1, const T *seq2,
              size_t cnt)
```

Sequence movement.

Move first cnt number of elements from seq2 to seq1, seq1 and seq2 may or may not overlap.

Group: Interface compatible with `std::string`'s `char_traits`.

Following are `char_traits` functions, which make this class `char_traits` compatible, so that it can be used in `std::basic_string` template, and be manipulated by the C++ STL algorithms.

Class

[DbstlElemTraits](#)

to_char_type

Function Details

```
static T to_char_type(const int_type &meta_elem)
```

Group: Interface compatible with `std::string`'s `char_traits`.

Following are `char_traits` functions, which make this class `char_traits` compatible, so that it can be used in `std::basic_string` template, and be manipulated by the C++ STL algorithms.

Class

[DbstElemTraits](#)

to_int_type

Function Details

```
static int_type to_int_type(const T &elem)
```

Group: Interface compatible with `std::string`'s `char_traits`.

Following are `char_traits` functions, which make this class `char_traits` compatible, so that it can be used in `std::basic_string` template, and be manipulated by the C++ STL algorithms.

Class

[DbstElemTraits](#)

eq_int_type

Function Details

```
static bool eq_int_type(const int_type &left,
                        const int_type &right)
```

Group: Interface compatible with std::string's char_traits.

Following are char_traits functions, which make this class char_traits compatible, so that it can be used in std::basic_string template, and be manipulated by the C++ STL algorithms.

Class

[DbstElemTraits](#)

eof

Function Details

```
static int_type eof()
```

Group: Interface compatible with `std::string`'s `char_traits`.

Following are `char_traits` functions, which make this class `char_traits` compatible, so that it can be used in `std::basic_string` template, and be manipulated by the C++ STL algorithms.

Class

[DbstElemTraits](#)

not_eof

Function Details

```
static int_type not_eof(const int_type &meta_elem)
```

Group: Interface compatible with `std::string`'s `char_traits`.

Following are `char_traits` functions, which make this class `char_traits` compatible, so that it can be used in `std::basic_string` template, and be manipulated by the C++ STL algorithms.

Class

[DbstElemTraits](#)

set_restore_function

Function Details

```
void set_restore_function(ElemRstoreFunct f)
```

Group: Set/get functions for callback function pointers.

These are the setters and getters for each callback function pointers.

Class

[DbstElemTraits](#)

get_restore_function

Function Details

```
ElemRstoreFunct get_restore_function()
```

Group: Set/get functions for callback function pointers.

These are the setters and getters for each callback function pointers.

Class

[DbstElemTraits](#)

set_assign_function

Function Details

```
void set_assign_function(ElemAssignFunct f)
```

Group: Set/get functions for callback function pointers.

These are the setters and getters for each callback function pointers.

Class

[DbstElemTraits](#)

get_assign_function

Function Details

```
ElemAssignFunct get_assign_function()
```

Group: Set/get functions for callback function pointers.

These are the setters and getters for each callback function pointers.

Class

[DbstElemTraits](#)

get_size_function

Function Details

```
ElemSizeFunct get_size_function()
```

Group: Set/get functions for callback function pointers.

These are the setters and getters for each callback function pointers.

Class

[DbstElemTraits](#)

set_size_function

Function Details

```
void set_size_function(ElemSizeFunct f)
```

Group: Set/get functions for callback function pointers.

These are the setters and getters for each callback function pointers.

Class

[DbstElemTraits](#)

get_copy_function

Function Details

```
ElemCopyFunct get_copy_function()
```

Group: Set/get functions for callback function pointers.

These are the setters and getters for each callback function pointers.

Class

[DbstElemTraits](#)

set_copy_function

Function Details

```
void set_copy_function(ElemCopyFunct f)
```

Group: Set/get functions for callback function pointers.

These are the setters and getters for each callback function pointers.

Class

[DbstElemTraits](#)

set_sequence_len_function

Function Details

```
void set_sequence_len_function(SequenceLenFunct f)
```

Group: Set/get functions for callback function pointers.

These are the setters and getters for each callback function pointers.

Class

[DbstElemTraits](#)

get_sequence_len_function

Function Details

```
SequenceLenFunct get_sequence_len_function()
```

Group: Set/get functions for callback function pointers.

These are the setters and getters for each callback function pointers.

Class

[DbstElemTraits](#)

get_sequence_copy_function

Function Details

```
SequenceCopyFunct get_sequence_copy_function()
```

Group: Set/get functions for callback function pointers.

These are the setters and getters for each callback function pointers.

Class

[DbstElemTraits](#)

set_sequence_copy_function

Function Details

```
void set_sequence_copy_function(SequenceCopyFunct f)
```

Group: Set/get functions for callback function pointers.

These are the setters and getters for each callback function pointers.

Class

[DbstElemTraits](#)

set_compare_function

Function Details

```
void set_compare_function(ElemCompareFunct f)
```

Group: Set/get functions for callback function pointers.

These are the setters and getters for each callback function pointers.

Class

[DbstElemTraits](#)

get_compare_function

Function Details

```
ElemCompareFunct get_compare_function()
```

Group: Set/get functions for callback function pointers.

These are the setters and getters for each callback function pointers.

Class

[DbstElemTraits](#)

set_sequence_compare_function

Function Details

```
void set_sequence_compare_function(SequenceCompareFunct f)
```

Group: Set/get functions for callback function pointers.

These are the setters and getters for each callback function pointers.

Class

[DbstElemTraits](#)

get_sequence_compare_function

Function Details

```
SequenceCompareFunct get_sequence_compare_function()
```

Group: Set/get functions for callback function pointers.

These are the setters and getters for each callback function pointers.

Class

[DbstElemTraits](#)

set_sequence_n_compare_function

Function Details

```
void set_sequence_n_compare_function(SequenceNCompareFunct f)
```

Group: Set/get functions for callback function pointers.

These are the setters and getters for each callback function pointers.

Class

[DbstElemTraits](#)

get_sequence_n_compare_function

Function Details

```
SequenceNCompareFunct get_sequence_n_compare_function()
```

Group: Set/get functions for callback function pointers.

These are the setters and getters for each callback function pointers.

Class

[DbstElemTraits](#)

instance

Function Details

```
static DbstlElemTraits* instance()
```

Factory method to create a singleton instance of this class.

The created object will be deleted by dbstl upon process exit.

Class

[DbstlElemTraits](#)

~DbstlElemTraits

Function Details

```
~DbstlElemTraits()
```

Class

[DbstlElemTraits](#)

DbstlElemTraits

Function Details

```
DbstlElemTraits()
```

Class

[DbstlElemTraits](#)

Chapter 27. BulkRetrievalOption

BulkRetrievalOption

Bulk retrieval configuration helper class.

Used by the begin() function of a container.

Public Members

| Member | Description |
|-------------------------------------|---|
| BulkRetrievalOption | |
| operator== | Equality comparison. |
| operator= | Assignment operator. |
| bulk_buf_size | Return the buffer size set to this object. |
| bulk_retrieval | This function indicates that you need a bulk retrieval iterator, and it can be also used to optionally set the bulk read buffer size. |
| no_bulk_retrieval | This function indicates that you do not need a bulk retrieval iterator. |

Group

[dbstl helper classes](#)

BulkRetrievalOption

Function Details

```
BulkRetrievalOption(Option bulk_retrieve1,  
    u_int32_t bulk_buf_sz=DBSTL_BULK_BUF_SIZE)
```

Class

[BulkRetrievalOption](#)

operator==

Function Details

```
bool operator==(const BulkRetrievalOption &bro) const
```

Equality comparison.

Class

[BulkRetrievalOption](#)

operator=

Function Details

```
void operator=(BulkRetrievalOption::Option opt)
```

Assignment operator.

Class

[BulkRetrievalOption](#)

bulk_buf_size

Function Details

```
u_int32_t bulk_buf_size()
```

Return the buffer size set to this object.

Class

[BulkRetrievalOption](#)

bulk_retrieval

Function Details

```
static BulkRetrievalOption bulk_retrieval(u_int32_t bulk_buf_sz=  
    DBSTL_BULK_BUF_SIZE)
```

This function indicates that you need a bulk retrieval iterator, and it can be also used to optionally set the bulk read buffer size.

Class

[BulkRetrievalOption](#)

no_bulk_retrieval

Function Details

```
static BulkRetrievalOption no_bulk_retrieval()
```

This function indicates that you do not need a bulk retrieval iterator.

Class

[BulkRetrievalOption](#)

Chapter 28. ReadModifyWriteOption

ReadModifyWriteOption

Read-modify-write cursor configuration helper class.

Used by each `begin()` function of all containers.

Public Members

| Member | Description |
|--------------------------------------|---|
| operator= | Assignment operator. |
| operator== | Equality comparison. |
| read_modify_write | Call this function to tell the container's <code>begin()</code> function that you need a read-modify-write iterator. |
| no_read_modify_write | Call this function to tell the container's <code>begin()</code> function that you do not need a read-modify-write iterator. |

Group

[dbstl helper classes](#)

operator=

Function Details

```
void operator=(ReadModifyWriteOption::Option rmwl)
```

Assignment operator.

Class

[ReadModifyWriteOption](#)

operator==

Function Details

```
bool operator==(const ReadModifyWriteOption &rmwl) const
```

Equality comparison.

Class

[ReadModifyWriteOption](#)

read_modify_write

Function Details

```
static ReadModifyWriteOption read_modify_write()
```

Call this function to tell the container's `begin()` function that you need a read-modify-write iterator.

Class

[ReadModifyWriteOption](#)

no_read_modify_write

Function Details

```
static ReadModifyWriteOption no_read_modify_write()
```

Call this function to tell the container's `begin()` function that you do not need a read-modify-write iterator.

This is the default value for the parameter of any container's `begin()` function.

Class

[ReadModifyWriteOption](#)

Chapter 29. dbstl exception classes

dbstl exception classes

dbstl exception classes

dbstl throws several types of exceptions on several kinds of errors, the exception classes form a class hierarchy.

First, there is the [DbstlException](#), which is the base class for all types of dbstl specific concrete exception classes. [DbstlException](#) inherits from the class `DbException` of Berkeley DB C++ API. Since `DbException` class inherits from C++ STL exception base class `std::exception`, you can make use of all Berkeley DB C++ and dbstl API exceptions in the same way you use the C++ `std::exception` class.

Besides exceptions of [DbstlException](#) and its subclasses, dbstl may also throw exceptions of `DbException` and its subclasses, which happens when a Berkeley DB call failed. So you should use the same way you catch Berkeley DB C++ API exceptions when you want to catch exceptions throw by Berkeley DB operations.

When an exception occurs, dbstl initialize an local exception object on the stack and throws the exception object, so you should catch an exception like this:

```
try { dbstl operations } catch(DbstlException ex){ Exception handling throw ex; // Optionally throw ex again }
```

Public Members

| Member | Description |
|--|---------------------------------------|
| DbstlException | <code>DbstlException</code> |
| NotEnoughMemoryException | <code>NotEnoughMemoryException</code> |
| InvalidIteratorException | <code>InvalidIteratorException</code> |
| InvalidCursorException | <code>InvalidCursorException</code> |
| InvalidDbtException | <code>InvalidDbtException</code> |
| FailedAssertionException | <code>FailedAssertionException</code> |
| NoSuchKeyException | <code>NoSuchKeyException</code> |
| InvalidArgumentException | <code>InvalidArgumentException</code> |
| NotSupportedException | <code>NotSupportedException</code> |
| InvalidFunctionCall | <code>InvalidFunctionCall</code> |

Group

None

Chapter 30. DbstlException

DbstlException

Base class of all dbstl exception classes.

It is derived from Berkeley DB C++ API DbException class to maintain consistency with all Berkeley DB exceptions.

Public Members

| Member | Description |
|---------------------------------|-------------|
| DbstlException | |
| operator= | |
| ~DbstlException | |

Group

[dbstl exception classes](#)

DbstlException

Function Details

```
DbstlException(const char *msg)
```

```
DbstlException(const char *msg,  
               int err)
```

```
DbstlException(const DbstlException &ex)
```

```
DbstlException(int err)
```

```
DbstlException(const char *prefix, const char *msg,  
               int err)
```

Class

[DbstlException](#)

operator=

Function Details

```
const DbstlException& operator=(const DbstlException &exobj)
```

Class

[DbstlException](#)

~DbstlException

Function Details

```
virtual ~DbstlException()
```

Class

[DbstlException](#)

Chapter 31. InvalidDbtException

InvalidDbtException

The Dbt object has inconsistent status or has no valid data, it is unable to be used any more.

Public Members

| Member | Description |
|-------------------------------------|-------------|
| InvalidDbtException | |

Group

[dbstl exception classes](#)

InvalidDbtException

Function Details

```
InvalidDbtException()
```

```
InvalidDbtException(int error_code)
```

Class

[InvalidDbtException](#)

Chapter 32. FailedAssertionException

FailedAssertionException

The assertions inside dbstl failed.

The code file name and line number will be passed to the exception object of this class.

Public Members

| Member | Description |
|---|-------------|
| what | |
| FailedAssertionException | |
| ~FailedAssertionException | |

Group

[dbstl exception classes](#)

what

Function Details

```
virtual const char* what() const
```

Class

[FailedAssertionException](#)

FailedAssertionException

Function Details

```
FailedAssertionException(const char *fname, size_t lineno,  
                        const char *msg)
```

```
FailedAssertionException(const FailedAssertionException &ex)
```

Class

[FailedAssertionException](#)

~FailedAssertionException

Function Details

```
virtual ~FailedAssertionException()
```

Class

[FailedAssertionException](#)

Chapter 33. InvalidCursorException

InvalidCursorException

The cursor has inconsistent status, it is unable to be used any more.

Public Members

| Member | Description |
|--|-------------|
| InvalidCursorException | |

Group

[dbstl exception classes](#)

InvalidCursorException

Function Details

```
InvalidCursorException()
```

```
InvalidCursorException(int error_code)
```

Class

[InvalidCursorException](#)

Chapter 34. NoSuchKeyException

NoSuchKeyException

There is no such key in the database.

The key can't not be passed into the exception instance because this class has to be a class template for that to work.

Public Members

| Member | Description |
|------------------------------------|-------------|
| NoSuchKeyException | |

Group

[dbstl exception classes](#)

NoSuchKeyException

Function Details

```
NoSuchKeyException()
```

Class

[NoSuchKeyException](#)

Chapter 35. NotEnoughMemoryException

NotEnoughMemoryException

Failed to allocate memory because memory is not enough.

Public Members

| Member | Description |
|--|-------------|
| NotEnoughMemoryException | |

Group

[dbstl exception classes](#)

NotEnoughMemoryException

Function Details

```
NotEnoughMemoryException(const char *msg,  
                          size_t sz)
```

```
NotEnoughMemoryException(const NotEnoughMemoryException &ex)
```

Class

[NotEnoughMemoryException](#)

Chapter 36. NotSupportedException

NotSupportedException

The function called is not supported in this class.

Public Members

| Member | Description |
|---------------------------------------|-------------|
| NotSupportedException | |

Group

[dbstl exception classes](#)

NotSupportedException

Function Details

```
NotSupportedException(const char *str)
```

Class

[NotSupportedException](#)

Chapter 37. InvalidIteratorException

InvalidIteratorException

The iterator has inconsistent status, it is unable to be used any more.

Public Members

| Member | Description |
|--|-------------|
| InvalidIteratorException | |

Group

[dbstl exception classes](#)

InvalidIteratorException

Function Details

```
InvalidIteratorException()
```

```
InvalidIteratorException(int error_code)
```

Class

[InvalidIteratorException](#)

Chapter 38. InvalidFunctionCall

InvalidFunctionCall

The function can not be called in this context or in current configurations.

Public Members

| Member | Description |
|-------------------------------------|-------------|
| InvalidFunctionCall | |

Group

[dbstl exception classes](#)

InvalidFunctionCall

Function Details

```
InvalidFunctionCall(const char *str)
```

Class

[InvalidFunctionCall](#)

Chapter 39. InvalidArgumentException

InvalidArgumentException

Some argument of a function is invalid.

Public Members

| Member | Description |
|--|-------------|
| InvalidArgumentException | |

Group

[dbstl exception classes](#)

InvalidArgumentException

Function Details

```
InvalidArgumentException(const char *errmsg)
```

```
InvalidArgumentException(const char *argtype,  
    const char *arg)
```

Class

[InvalidArgumentException](#)

Chapter 40. Assign functions used internally only

Assign functions used internally only.

Assign functions used internally only.

Public Members

| Member | Description |
|--------|-------------|
|--------|-------------|

Group

[iterator classes for db_map and db_multimap](#)

Chapter 41. operators that enable the n + itr expression

Operators that enable the n + itr expression.

Operators that enable the n + itr expression.

These operators make "n + itr" expressions valid.

Without it, you can only use "itr + n"

Public Members

| Member | Description |
|---------------------------|-------------|
| operator+ | |

Group

[dbstl global public functions](#)

operator+

Function Details

```
difference_type n, db_reverse_iterator< iterator,  
    iterator2 > itr)
```

```
difference_type n, db_vector_iterator< T,  
    value_type_sub > itr)
```

```
difference_type n,  
    db_vector_base_iterator< T > itr)
```

Class

[global_vctitr_mv](#)

Chapter 42. C++ iostream support for ElementHolder and ElementRef

C++ iostream support for ElementHolder and

C++ iostream support for ElementHolder and

[ElementRef](#) .

These operators help reading from/writing to any iostreams, as long as the wrapped ddt type has iostream operators.

Public Members

| Member | Description |
|----------------------------------|-------------|
| operator<< | |
| operator>> | |

Group

[dbstl global public functions](#)

operator<<

Function Details

```
basic_ostream<_CharT,_Traits>& operator<<(basic_ostream< _CharT,  
    _Traits > &out,  
    const ElementHolder< ddt > &p)
```

```
basic_ostream<_CharT,_Traits>& operator<<(basic_ostream< _CharT,  
    _Traits > &out,  
    const ElementRef< ddt > &p)
```

Class

[iostream_sup](#)

operator>>

Function Details

```
basic_istream<_CharT,_Traits>& operator>>(basic_istream< _CharT,  
    _Traits > &in,  
    ElementHolder< ddt > &p)
```

```
basic_istream<_CharT,_Traits>& operator>>(basic_istream< _CharT,  
    _Traits > &in,  
    ElementRef< ddt > &p)
```

Class

[iostream_sup](#)

Chapter 43. dbstl global functions for internal use only

dbstl global functions for internal use only

dbstl global functions for internal use only

Public Members

| Member | Description |
|-------------------------------|-------------|
| dbstl_strcmp | |
| dbstl_strcpy | |
| dbstl_strlen | |
| dbstl_strncmp | |
| dbstl_wcscmp | |
| dbstl_wcscpy | |
| dbstl_wcslen | |
| dbstl_wcsncmp | |
| DbstlMalloc | |
| DbstlReAlloc | |
| hash_default | |

Group

[dbstl global public functions](#)

dbstl_strcmp

Function Details

```
int dbstl_strcmp(const char *s1,  
                const char *s2)
```

Class

[dbstl_glob_int_func](#)

dbstl_strcpy

Function Details

```
void dbstl_strcpy(char *dest, const char *src,  
                 size_t num)
```

Class

[dbstl_glob_int_func](#)

dbstl_strlen

Function Details

```
u_int32_t dbstl_strlen(const char *str)
```

Class

[dbstl_glob_int_func](#)

dbstl_strncmp

Function Details

```
int dbstl_strncmp(const char *s1, const char *s2,  
                 size_t num)
```

Class

[dbstl_glob_int_func](#)

dbstl_wcscmp

Function Details

```
int dbstl_wcscmp(const wchar_t *s1,  
                 const wchar_t *s2)
```

Class

[dbstl_glob_int_func](#)

dbstl_wcscpy

Function Details

```
void dbstl_wcscpy(wchar_t *dest, const wchar_t *src,  
                  size_t num)
```

Class

[dbstl_glob_int_func](#)

dbstl_wcslen

Function Details

```
u_int32_t dbstl_wcslen(const wchar_t *str)
```

Class

[dbstl_glob_int_func](#)

dbstl_wcsncmp

Function Details

```
int dbstl_wcsncmp(const wchar_t *s1, const wchar_t *s2,  
                  size_t num)
```

Class

[dbstl_glob_int_func](#)

DbstlMalloc

Function Details

```
void* DbstlMalloc(size_t size)
```

Class

[dbstl_glob_int_func](#)

DbstlReAlloc

Function Details

```
void* DbstlReAlloc(void *ptr,  
                  size_t size)
```

Class

[dbstl_glob_int_func](#)

hash_default

Function Details

```
u_int32_t hash_default(Db *, const void *key,  
                      u_int32_t len)
```

Class

[dbstl_glob_int_func](#)