

RT-Voice PRO

Hearing is understanding



API

© 2015-2019 **crosstailes** LLC
<https://www.crosstailes.com>

Date: 12.03.2019
Version: 2019.2.0

Contents

1	Namespace Index	1
1.1	Packages	1
2	Hierarchical Index	3
2.1	Class Hierarchy	3
3	Class Index	7
3.1	Class List	7
4	Namespace Documentation	13
4.1	Crosstales Namespace Reference	13
4.2	Crosstales.Common Namespace Reference	13
4.3	Crosstales.Common.EditorTask Namespace Reference	13
4.4	Crosstales.Common.EditorUtil Namespace Reference	14
4.5	Crosstales.Common.Model Namespace Reference	14
4.6	Crosstales.Common.Model.Enum Namespace Reference	14
4.6.1	Enumeration Type Documentation	14
4.6.1.1	Platform	14
4.6.1.2	SampleRate	14
4.7	Crosstales.Common.Util Namespace Reference	15
4.8	Crosstales.RTVoice Namespace Reference	15
4.9	Crosstales.RTVoice.AWSPolly Namespace Reference	16
4.9.1	Enumeration Type Documentation	17
4.9.1.1	Endpoint	17
4.10	Crosstales.RTVoice.Demo Namespace Reference	17

4.11	Crosstales.RTVoice.Demo.Util Namespace Reference	18
4.12	Crosstales.RTVoice.EditorExtension Namespace Reference	18
4.13	Crosstales.RTVoice.EditorIntegration Namespace Reference	18
4.14	Crosstales.RTVoice.EditorTask Namespace Reference	19
4.14.1	Enumeration Type Documentation	19
4.14.1.1	UpdateStatus	19
4.15	Crosstales.RTVoice.EditorUtil Namespace Reference	19
4.16	Crosstales.RTVoice.Klattersynth Namespace Reference	20
4.17	Crosstales.RTVoice.Model Namespace Reference	20
4.18	Crosstales.RTVoice.Model.Enum Namespace Reference	20
4.18.1	Enumeration Type Documentation	21
4.18.1.1	ESpeakModifiers	21
4.18.1.2	Gender	21
4.18.1.3	MaryTTSType	21
4.18.1.4	ProviderType	21
4.18.1.5	SpeakMode	21
4.19	Crosstales.RTVoice.PlayMaker Namespace Reference	21
4.20	Crosstales.RTVoice.Provider Namespace Reference	22
4.21	Crosstales.RTVoice.SALSA Namespace Reference	22
4.22	Crosstales.RTVoice.Tool Namespace Reference	22
4.23	Crosstales.RTVoice.UDEA2 Namespace Reference	23
4.24	Crosstales.RTVoice.Util Namespace Reference	23
4.24.1	Detailed Description	23
4.25	Crosstales.UI Namespace Reference	24
4.26	Crosstales.UI.Util Namespace Reference	24
4.27	HutongGames Namespace Reference	24
4.28	HutongGames.PlayMaker Namespace Reference	24
4.29	HutongGames.PlayMaker.Actions Namespace Reference	24

5	Class Documentation	27
5.1	HutongGames.PlayMaker.Actions.AudioFileGenerator Class Reference	27
5.1.1	Detailed Description	27
5.1.2	Member Data Documentation	28
5.1.2.1	Obj	28
5.2	Crosstales.RTVoice.Tool.AudioFileGenerator Class Reference	28
5.2.1	Detailed Description	29
5.2.2	Member Function Documentation	29
5.2.2.1	Generate()	29
5.2.3	Member Data Documentation	29
5.2.3.1	FileInsideAssets	29
5.2.3.2	GenerateOnStart	29
5.2.3.3	TextFiles	29
5.2.4	Property Documentation	29
5.2.4.1	OnAudioFileGeneratorComplete	29
5.2.4.2	OnAudioFileGeneratorStart	30
5.3	Crosstales.RTVoice.EditorExtension.AudioFileGeneratorEditor Class Reference	30
5.3.1	Detailed Description	30
5.4	Crosstales.RTVoice.PlayMaker.AudioFileGeneratorEditor Class Reference	30
5.4.1	Detailed Description	31
5.5	Crosstales.UI.Util.AudioFilterController Class Reference	31
5.5.1	Detailed Description	32
5.5.2	Member Function Documentation	32
5.5.2.1	FindAllAudioFilters()	32
5.5.2.2	ResetAudioFilters()	32
5.5.3	Member Data Documentation	32
5.5.3.1	FindAllAudioFiltersOnStart	32
5.6	Crosstales.UI.Util.AudioSourceController Class Reference	33
5.6.1	Detailed Description	33
5.6.2	Member Function Documentation	34

5.6.2.1	FindAllAudioSources()	34
5.6.2.2	ResetAllAudioSources()	34
5.6.3	Member Data Documentation	34
5.6.3.1	AudioSources	34
5.6.3.2	FindAllAudioSourcesOnStart	34
5.6.3.3	Loop	34
5.6.3.4	Mute	34
5.6.3.5	Pitch	34
5.6.3.6	ResetAudioSourcesOnStart	34
5.6.3.7	StereoPan	34
5.6.3.8	Volume	35
5.7	Crosstales.RTVoice.EditorTask.AutoInitialize Class Reference	35
5.7.1	Detailed Description	35
5.8	Crosstales.Common.Util.BackgroundController Class Reference	35
5.8.1	Detailed Description	36
5.8.2	Member Data Documentation	36
5.8.2.1	Objects	36
5.9	Crosstales.Common.EditorTask.BaseCompileDefines Class Reference	36
5.9.1	Detailed Description	36
5.10	Crosstales.Common.Util.BaseConstants Class Reference	37
5.10.1	Detailed Description	39
5.10.2	Member Data Documentation	39
5.10.2.1	ASSET_3P_PLAYMAKER	39
5.10.2.2	ASSET_AUTHOR	39
5.10.2.3	ASSET_AUTHOR_URL	39
5.10.2.4	ASSET_BWF	39
5.10.2.5	ASSET_CT_URL	39
5.10.2.6	ASSET_DJ	40
5.10.2.7	ASSET_FB	40
5.10.2.8	ASSET_OC	40

5.10.2.9 ASSET_RADIO	40
5.10.2.10 ASSET_RTV	40
5.10.2.11 ASSET_SOCIAL_DISCORD	40
5.10.2.12 ASSET_SOCIAL_FACEBOOK	40
5.10.2.13 ASSET_SOCIAL_LINKEDIN	40
5.10.2.14 ASSET_SOCIAL_TWITTER	40
5.10.2.15 ASSET_SOCIAL_XING	41
5.10.2.16 ASSET_SOCIAL_YOUTUBE	41
5.10.2.17 ASSET_TB	41
5.10.2.18 ASSET_TPB	41
5.10.2.19 ASSET_TPS	41
5.10.2.20 ASSET_TR	41
5.10.2.21 DEV_DEBUG	41
5.10.2.22 FACTOR_GB	41
5.10.2.23 FACTOR_KB	41
5.10.2.24 FACTOR_MB	42
5.10.2.25 FLOAT_32768	42
5.10.2.26 FORMAT_NO_DECIMAL_PLACES	42
5.10.2.27 FORMAT_PERCENT	42
5.10.2.28 FORMAT_TWO_DECIMAL_PLACES	42
5.10.2.29 PATH_DELIMITER_UNIX	42
5.10.2.30 PATH_DELIMITER_WINDOWS	42
5.10.2.31 PROCESS_KILL_TIME	42
5.10.2.32 SHOW_BWF_BANNER	42
5.10.2.33 SHOW_DJ_BANNER	42
5.10.2.34 SHOW_FB_BANNER	43
5.10.2.35 SHOW_OC_BANNER	43
5.10.2.36 SHOW_RADIO_BANNER	43
5.10.2.37 SHOW_RTV_BANNER	43
5.10.2.38 SHOW_TB_BANNER	43

5.10.2.39	SHOW_TPB_BANNER	43
5.10.2.40	SHOW_TPS_BANNER	43
5.10.2.41	SHOW_TR_BANNER	43
5.10.3	Property Documentation	43
5.10.3.1	APPLICATION_PATH	43
5.10.3.2	PREFIX_FILE	44
5.11	Crosstales.RTVoice.Provider.BaseCustomVoiceProvider Class Reference	44
5.11.1	Detailed Description	45
5.11.2	Member Function Documentation	45
5.11.2.1	Generate(Model.Wrapper wrapper)	45
5.11.2.2	Load()	46
5.11.2.3	Silence()	46
5.11.2.4	Silence(string uid)	46
5.11.2.5	Speak(Model.Wrapper wrapper)	46
5.11.2.6	SpeakNative(Model.Wrapper wrapper)	47
5.11.3	Property Documentation	47
5.11.3.1	OnErrorInfo	47
5.11.3.2	OnSpeakAudioGenerationComplete	47
5.11.3.3	OnSpeakAudioGenerationStart	47
5.11.3.4	OnSpeakComplete	47
5.11.3.5	OnSpeakCurrentPhoneme	47
5.11.3.6	OnSpeakCurrentViseme	47
5.11.3.7	OnSpeakCurrentWord	48
5.11.3.8	OnSpeakStart	48
5.11.3.9	OnVoicesReady	48
5.12	Crosstales.Common.EditorUtil.BaseEditorHelper Class Reference	48
5.12.1	Detailed Description	49
5.12.2	Member Function Documentation	49
5.12.2.1	getBuildNameFromBuildTarget(BuildTarget build)	49
5.12.2.2	getBuildTargetForBuildName(string build)	50

5.12.2.3	getCLIArgument(string name)	50
5.12.2.4	isValidBuildTarget(BuildTarget target)	50
5.12.2.5	ReadOnlyTextField(string label, string text)	51
5.12.2.6	RefreshAssetDatabase()	51
5.12.2.7	RestartUnity(string executeMethod="")	51
5.12.2.8	SeparatorUI(int space=12)	51
5.13	Crosstales.Common.EditorUtil.BaseGAApi Class Reference	51
5.13.1	Detailed Description	52
5.13.2	Member Function Documentation	52
5.13.2.1	Event(string name, string version, string category, string action, string label="", int value=0)	52
5.14	Crosstales.Common.Util.BaseHelper Class Reference	52
5.14.1	Detailed Description	55
5.14.2	Member Function Documentation	55
5.14.2.1	ClearLineEndings(string text)	55
5.14.2.2	ClearSpaces(string text)	55
5.14.2.3	ClearTags(string text)	55
5.14.2.4	CreateString(string replaceChars, int stringLength)	56
5.14.2.5	FileCopy(string inputFile, string outputFile, bool move=false)	56
5.14.2.6	FormatBytesToHRF(long bytes)	56
5.14.2.7	FormatSecondsToHourMinSec(double seconds)	56
5.14.2.8	hasActiveClip(AudioSource source)	57
5.14.2.9	HSVToRGB(float h, float s, float v, float a=1f)	57
5.14.2.10	IsValidURL(string url)	57
5.14.2.11	RemoteCertificateValidationCallback(System.Object sender, System.Security.Crypto- graphy.X509Certificates.X509Certificate certificate, System.Security.Crypto- graphy.X509Certificates.X509Chain chain, System.Net.Security.SslPolicyErrors sslPolicyErrors)	57
5.14.2.12	SplitStringToLines(string text, bool ignoreCommentedLines=true, int skipHeaderLines=0, int skipFooterLines=0)	58
5.14.2.13	ValidateFile(string path)	58
5.14.2.14	ValidatePath(string path, bool addEndDelimiter=true)	58
5.14.2.15	ValidURLFromFilePath(string path)	58

5.14.3	Property Documentation	59
5.14.3.1	CurrentPlatform	59
5.14.3.2	isAndroidPlatform	59
5.14.3.3	isAppleBasedPlatform	59
5.14.3.4	isEditor	59
5.14.3.5	isEditorMode	60
5.14.3.6	isInternetAvailable	60
5.14.3.7	isIOSPlatform	60
5.14.3.8	isLinuxPlatform	60
5.14.3.9	isMacOSPlatform	60
5.14.3.10	isStandalonePlatform	60
5.14.3.11	isWebGLPlatform	61
5.14.3.12	isWebPlatform	61
5.14.3.13	isWindowsBasedPlatform	61
5.14.3.14	isWindowsPlatform	61
5.14.3.15	isWSAPlatform	61
5.15	HutongGames.PlayMaker.Actions.BaseRTVAction Class Reference	62
5.15.1	Detailed Description	62
5.16	Crosstales.RTVoice.PlayMaker.BaseRTVEditor Class Reference	62
5.16.1	Detailed Description	62
5.17	Crosstales.Common.EditorTask.BaseSetupResources Class Reference	63
5.17.1	Detailed Description	63
5.18	Crosstales.RTVoice.Provider.BaseVoiceProvider Class Reference	63
5.18.1	Detailed Description	65
5.18.2	Constructor & Destructor Documentation	65
5.18.2.1	BaseVoiceProvider(MonoBehaviour obj)	65
5.18.3	Member Function Documentation	66
5.18.3.1	Generate(Model.Wrapper wrapper)	66
5.18.3.2	Silence()	66
5.18.3.3	Silence(string uid)	66

5.18.3.4	Speak(Model.Wrapper wrapper)	66
5.18.3.5	SpeakNative(Model.Wrapper wrapper)	67
5.18.4	Property Documentation	67
5.18.4.1	OnErrorInfo	67
5.18.4.2	OnSpeakAudioGenerationComplete	67
5.18.4.3	OnSpeakAudioGenerationStart	67
5.18.4.4	OnSpeakComplete	67
5.18.4.5	OnSpeakCurrentPhoneme	68
5.18.4.6	OnSpeakCurrentViseme	68
5.18.4.7	OnSpeakCurrentWord	68
5.18.4.8	OnSpeakStart	68
5.18.4.9	OnVoicesReady	68
5.19	Crosstales.RTVoice.SALSA.Bots Class Reference	68
5.19.1	Detailed Description	69
5.20	Crosstales.RTVoice.Tool.ChangeGender Class Reference	69
5.20.1	Detailed Description	69
5.20.2	Member Data Documentation	70
5.20.2.1	ESpeakOnly	70
5.20.2.2	NewGender	70
5.20.2.3	RefreshOnVoicesReady	70
5.21	Crosstales.RTVoice.EditorExtension.ChangeGenderEditor Class Reference	70
5.21.1	Detailed Description	70
5.22	Crosstales.RTVoice.EditorTask.CheckIL2CPP Class Reference	71
5.22.1	Detailed Description	71
5.23	Crosstales.RTVoice.EditorTask.CompileDefines Class Reference	71
5.23.1	Detailed Description	71
5.24	Crosstales.RTVoice.Util.Config Class Reference	71
5.24.1	Detailed Description	72
5.24.2	Member Function Documentation	73
5.24.2.1	Load()	73

5.24.2.2	Reset()	73
5.24.2.3	Save()	73
5.24.3	Member Data Documentation	73
5.24.3.1	ASSET_PATH	73
5.24.3.2	AUDIOFILE_AUTOMATIC_DELETE	73
5.24.3.3	DEBUG	73
5.24.3.4	ENFORCE_32BIT_WINDOWS	73
5.24.3.5	ENSURE_NAME	73
5.24.3.6	isLoading	73
5.24.3.7	TTS_LINUX	74
5.24.3.8	TTS_LINUX_DATA	74
5.24.3.9	TTS_MACOS	74
5.24.3.10	TTS_WINDOWS_BUILD	74
5.24.4	Property Documentation	74
5.24.4.1	AUDIOFILE_PATH	74
5.24.4.2	TTS_WINDOWS_EDITOR	74
5.24.4.3	TTS_WINDOWS_EDITOR_x86	74
5.25	Crosstales.RTVoice.EditorIntegration.ConfigBase Class Reference	74
5.25.1	Detailed Description	75
5.26	Crosstales.RTVoice.EditorTask.ConfigLoader Class Reference	75
5.26.1	Detailed Description	75
5.27	Crosstales.RTVoice.EditorIntegration.ConfigPreferences Class Reference	75
5.27.1	Detailed Description	76
5.28	Crosstales.RTVoice.EditorIntegration.ConfigWindow Class Reference	76
5.28.1	Detailed Description	77
5.29	Crosstales.RTVoice.Util.Constants Class Reference	77
5.29.1	Detailed Description	79
5.29.2	Member Data Documentation	79
5.29.2.1	ASSET_2019_URL	79
5.29.2.2	ASSET_3P_ADVENTURE_CREATOR	79

5.29.2.3	ASSET_3P_CINEMA_DIRECTOR	80
5.29.2.4	ASSET_3P_DIALOG_SYSTEM	80
5.29.2.5	ASSET_3P_DIALOGUE_ENGINE	80
5.29.2.6	ASSET_3P_LIPSYNC	80
5.29.2.7	ASSET_3P_LOCALIZED_DIALOGS	80
5.29.2.8	ASSET_3P_NPC_CHAT	80
5.29.2.9	ASSET_3P_QUEST_SYSTEM	80
5.29.2.10	ASSET_3P_SALSA	80
5.29.2.11	ASSET_3P_SLATE	80
5.29.2.12	ASSET_3P_URL	81
5.29.2.13	ASSET_3P_USEQUENCER	81
5.29.2.14	ASSET_API_URL	81
5.29.2.15	ASSET_BUILD	81
5.29.2.16	ASSET_CHANGED	81
5.29.2.17	ASSET_CONTACT	81
5.29.2.18	ASSET_CREATED	81
5.29.2.19	ASSET_FORUM_URL	81
5.29.2.20	ASSET_MANUAL_URL	81
5.29.2.21	ASSET_NAME	82
5.29.2.22	ASSET_PRO_URL	82
5.29.2.23	ASSET_UPDATE_CHECK_URL	82
5.29.2.24	ASSET_VERSION	82
5.29.2.25	ASSET_VIDEO_PROMO	82
5.29.2.26	ASSET_VIDEO_TUTORIAL	82
5.29.2.27	ASSET_WEB_URL	82
5.29.2.28	AUDIOFILE_PREFIX	82
5.29.2.29	ESPEAK_FEMALE_MODIFIER	82
5.29.2.30	RTVOICE_SCENE_OBJECT_NAME	82
5.29.2.31	SPEAK_CALL_SPEED	83
5.29.2.32	TTS_WINDOWS_SUBPATH	83

5.29.2.33 TTS_WINDOWS_x86_SUBPATH	83
5.30 Crosstales.Common.Util.CTPlayerPrefs Class Reference	83
5.30.1 Detailed Description	84
5.30.2 Member Function Documentation	84
5.30.2.1 DeleteAll()	84
5.30.2.2 DeleteKey(string key)	84
5.30.2.3 GetBool(string key)	84
5.30.2.4 GetDate(string key)	84
5.30.2.5 GetFloat(string key)	85
5.30.2.6 GetInt(string key)	85
5.30.2.7 GetString(string key)	85
5.30.2.8 HasKey(string key)	85
5.30.2.9 Save()	86
5.30.2.10 SetBool(string key, bool value)	86
5.30.2.11 SetDate(string key, System.DateTime value)	86
5.30.2.12 SetFloat(string key, float value)	86
5.30.2.13 SetInt(string key, int value)	86
5.30.2.14 SetString(string key, string value)	87
5.31 Crosstales.Common.Util.CTWebClient Class Reference	87
5.31.1 Detailed Description	87
5.31.2 Property Documentation	88
5.31.2.1 ConnectionLimit	88
5.31.2.2 Timeout	88
5.32 Crosstales.RTVoice.Demo.Dialog Class Reference	88
5.32.1 Detailed Description	89
5.33 Crosstales.RTVoice.EditorUtil.EditorConfig Class Reference	89
5.33.1 Detailed Description	90
5.33.2 Member Function Documentation	90
5.33.2.1 Load()	90
5.33.2.2 Reset()	90

5.33.2.3	Save()	90
5.33.3	Member Data Documentation	90
5.33.3.1	HIERARCHY_ICON	90
5.33.3.2	isLoading	90
5.33.3.3	PREFAB_AUTOLOAD	90
5.33.3.4	REMINDER_CHECK	90
5.33.3.5	TRACER	90
5.33.3.6	UPDATE_CHECK	91
5.33.4	Property Documentation	91
5.33.4.1	ASSET_PATH	91
5.33.4.2	PREFAB_PATH	91
5.34	Crosstales.RTVoice.EditorUtil.EditorConstants Class Reference	91
5.34.1	Detailed Description	92
5.34.2	Member Data Documentation	92
5.34.2.1	PREFAB_SUBPATH	92
5.34.3	Property Documentation	92
5.34.3.1	ASSET_ID	92
5.34.3.2	ASSET_UID	92
5.34.3.3	ASSET_URL	93
5.35	Crosstales.RTVoice.EditorUtil.EditorHelper Class Reference	93
5.35.1	Detailed Description	94
5.35.2	Member Function Documentation	94
5.35.2.1	BannerOC()	94
5.35.2.2	InstantiatePrefab(string prefabName)	94
5.35.2.3	NoVoicesUI()	94
5.35.3	Member Data Documentation	95
5.35.3.1	GO_ID	95
5.35.3.2	MENU_ID	95
5.35.4	Property Documentation	95
5.35.4.1	isRTVoiceInScene	95

5.36	Crosstales.ExtensionMethods Class Reference	95
5.36.1	Detailed Description	96
5.36.2	Member Function Documentation	96
5.36.2.1	CTAddRange< K, V >(this System.Collections.Generic.IDictionary< K, V > source, System.Collections.Generic.IDictionary< K, V > collection)	96
5.36.2.2	CTContains(this string str, string toCheck, System.StringComparison comp=↔ System.StringComparison.OrdinalIgnoreCase)	97
5.36.2.3	CTContainsAll(this string str, string searchTerms, char splitChar= ' ')	97
5.36.2.4	CTContainsAny(this string str, string searchTerms, char splitChar= ' ')	97
5.36.2.5	CTDump(this Quaternion[] array)	98
5.36.2.6	CTDump(this Vector2[] array)	98
5.36.2.7	CTDump(this Vector3[] array)	98
5.36.2.8	CTDump(this Vector4[] array)	98
5.36.2.9	CTDump(this System.Collections.Generic.IList< Quaternion > list)	99
5.36.2.10	CTDump(this System.Collections.Generic.IList< Vector2 > list)	99
5.36.2.11	CTDump(this System.Collections.Generic.IList< Vector3 > list)	99
5.36.2.12	CTDump(this System.Collections.Generic.IList< Vector4 > list)	100
5.36.2.13	CTDump< K, V >(this System.Collections.Generic.IDictionary< K, V > dict, string prefix="\"", string postfix="\"")	100
5.36.2.14	CTDump< T >(this T[] array, string prefix="\"", string postfix="\"")	100
5.36.2.15	CTDump< T >(this System.Collections.Generic.IList< T > list, string prefix="\"", string postfix="\"")	101
5.36.2.16	CTEquals(this string str, string toCheck, System.StringComparison comp=↔ System.StringComparison.OrdinalIgnoreCase)	101
5.36.2.17	CTIsVisibleFrom(this Renderer renderer, Camera camera)	101
5.36.2.18	CTReplace(this string str, string oldString, string newString, System.String↔ Comparison comp=System.StringComparison.OrdinalIgnoreCase)	102
5.36.2.19	CTReverse(this string str)	102
5.36.2.20	CTShuffle< T >(this T[] array, int seed=0)	102
5.36.2.21	CTShuffle< T >(this System.Collections.Generic.IList< T > list, int seed=0)	102
5.36.2.22	CTToString< T >(this T[] array)	103
5.36.2.23	CTToString< T >(this System.Collections.Generic.IList< T > list)	103
5.36.2.24	CTToTitleCase(this string str)	103

5.37	Crosstales.Common.Util.FFTAnalyzer Class Reference	103
5.37.1	Detailed Description	104
5.37.2	Member Data Documentation	104
5.37.2.1	Channel	104
5.37.2.2	Samples	104
5.38	Crosstales.UI.Util.FPSDisplay Class Reference	105
5.38.1	Detailed Description	105
5.38.2	Member Data Documentation	105
5.38.2.1	FPS	105
5.39	Crosstales.RTVoice.EditorUtil.GAApi Class Reference	105
5.39.1	Detailed Description	106
5.39.2	Member Function Documentation	106
5.39.2.1	Event(string category, string action, string label="", int value=0)	106
5.40	Crosstales.RTVoice.Demo.GUIAudioFilter Class Reference	106
5.40.1	Detailed Description	107
5.41	Crosstales.RTVoice.Demo.GUIDialog Class Reference	107
5.41.1	Detailed Description	108
5.42	Crosstales.RTVoice.Demo.GUIMain Class Reference	108
5.42.1	Detailed Description	109
5.43	Crosstales.RTVoice.Demo.GUIMultiAudioFilter Class Reference	109
5.43.1	Detailed Description	110
5.44	Crosstales.RTVoice.Demo.GUIScenes Class Reference	110
5.44.1	Detailed Description	111
5.45	Crosstales.RTVoice.Demo.GUISpeech Class Reference	111
5.45.1	Detailed Description	112
5.46	Crosstales.RTVoice.Util.Helper Class Reference	112
5.46.1	Detailed Description	113
5.46.2	Member Function Documentation	113
5.46.2.1	AppleVoiceNameToGender(string voiceName)	113
5.46.2.2	CleanText(string text, bool removeTags=true, bool clearSpaces=true, bool clear↔ LineEndings=true)	114

5.46.2.3	MarkSpokenText(string[] speechTextArray, int wordIndex, bool markAll↵ SpokenWords=false, string markPrefix=""<color=green>""", string mark↵ Postfix=""</color>""")	114
5.46.2.4	StringToGender(string gender)	114
5.46.2.5	WSAVoiceNameToGender(string voiceName)	115
5.46.3	Property Documentation	115
5.46.3.1	CurrentProviderType	115
5.46.3.2	hasBuiltInTTS	115
5.47	Crosstales.RTVoice.Demo.Util.iOSController Class Reference	115
5.47.1	Detailed Description	116
5.48	Crosstales.RTVoice.Provider.IVoiceProvider Interface Reference	116
5.48.1	Detailed Description	117
5.48.2	Member Function Documentation	117
5.48.2.1	Generate(Model.Wrapper wrapper)	117
5.48.2.2	Silence()	118
5.48.2.3	Silence(string uid)	118
5.48.2.4	Speak(Model.Wrapper wrapper)	118
5.48.2.5	SpeakNative(Model.Wrapper wrapper)	118
5.48.3	Property Documentation	119
5.48.3.1	AudioFileExtension	119
5.48.3.2	AudioFileType	119
5.48.3.3	Cultures	119
5.48.3.4	DefaultVoiceName	119
5.48.3.5	hasCoRoutines	119
5.48.3.6	isOnlineService	120
5.48.3.7	isPlatformSupported	120
5.48.3.8	isSpeakNativeSupported	120
5.48.3.9	isSpeakSupported	120
5.48.3.10	isSSMLSupported	120
5.48.3.11	isWorkingInEditor	120
5.48.3.12	MaxTextLength	121

5.48.3.13	Voices	121
5.49	Crosstales.RTVoice.EditorTask.Launch Class Reference	121
5.49.1	Detailed Description	121
5.50	Crosstales.RTVoice.LiveSpeaker Class Reference	121
5.50.1	Detailed Description	122
5.50.2	Member Function Documentation	122
5.50.2.1	SetState(string state)	122
5.50.2.2	SetVoices(string voices)	122
5.50.2.3	Silence()	123
5.50.2.4	Speak(Model.Wrapper wrapper)	123
5.50.2.5	Speak(string args)	123
5.50.2.6	Speak(string[] args)	123
5.50.2.7	SpeakNative(Model.Wrapper wrapper)	123
5.50.2.8	SpeakNative(string args)	124
5.50.2.9	SpeakNative(string[] args)	124
5.50.2.10	WordSpoken(string word)	124
5.51	Crosstales.RTVoice.Tool.Loudspeaker Class Reference	124
5.51.1	Detailed Description	125
5.51.2	Member Data Documentation	125
5.51.2.1	SilenceSource	125
5.51.2.2	Source	125
5.51.2.3	Synchronized	125
5.51.3	Property Documentation	126
5.51.3.1	isSilenceSource	126
5.51.3.2	isSynchronized	126
5.52	Crosstales.RTVoice.EditorExtension.LoudspeakerEditor Class Reference	126
5.52.1	Detailed Description	126
5.53	Crosstales.RTVoice.Demo.Util.MaterialChanger Class Reference	127
5.53.1	Detailed Description	127
5.54	Crosstales.RTVoice.Demo.NativeAudio Class Reference	127

5.54.1 Detailed Description	128
5.55 Crosstales.RTVoice.Demo.Util.NativeController Class Reference	128
5.55.1 Detailed Description	129
5.55.2 Member Data Documentation	129
5.55.2.1 Active	129
5.55.2.2 Objects	129
5.56 Crosstales.Common.EditorTask.NYCheck Class Reference	129
5.56.1 Detailed Description	129
5.57 Crosstales.RTVoice.Tool.Paralanguage Class Reference	129
5.57.1 Detailed Description	130
5.57.2 Member Function Documentation	131
5.57.2.1 Silence()	131
5.57.2.2 Speak()	131
5.57.3 Member Data Documentation	131
5.57.3.1 Clips	131
5.57.3.2 Delay	131
5.57.3.3 Mode	131
5.57.3.4 Pitch	131
5.57.3.5 PlayOnStart	131
5.57.3.6 Rate	131
5.57.3.7 Text	131
5.57.3.8 Voices	132
5.57.3.9 Volume	132
5.57.4 Property Documentation	132
5.57.4.1 CurrentPitch	132
5.57.4.2 CurrentRate	132
5.57.4.3 CurrentText	132
5.57.4.4 CurrentVolume	132
5.57.4.5 OnParalanguageComplete	132
5.57.4.6 OnParalanguageStart	132

5.58	HutongGames.PlayMaker.Actions.Paralanguage Class Reference	133
5.58.1	Detailed Description	133
5.58.2	Member Data Documentation	133
5.58.2.1	Obj	133
5.59	Crosstales.RTVoice.EditorExtension.ParalanguageEditor Class Reference	133
5.59.1	Detailed Description	134
5.60	Crosstales.RTVoice.PlayMaker.ParalanguageEditor Class Reference	134
5.60.1	Detailed Description	134
5.61	Crosstales.Common.Util.PlatformController Class Reference	135
5.61.1	Detailed Description	135
5.61.2	Member Data Documentation	135
5.61.2.1	Objects	135
5.61.2.2	Platforms	136
5.62	Crosstales.RTVoice.Demo.Util.PlatformController Class Reference	136
5.62.1	Detailed Description	136
5.63	Crosstales.RTVoice.Demo.PreGeneratedAudio Class Reference	137
5.63.1	Detailed Description	137
5.64	Crosstales.Common.Util.RandomColor Class Reference	137
5.64.1	Detailed Description	138
5.64.2	Member Data Documentation	138
5.64.2.1	AlphaRange	138
5.64.2.2	ChangeInterval	138
5.64.2.3	GrayScale	138
5.64.2.4	HueRange	138
5.64.2.5	Material	139
5.64.2.6	SaturationRange	139
5.64.2.7	UseInterval	139
5.64.2.8	ValueRange	139
5.65	Crosstales.Common.Util.RandomRotator Class Reference	139
5.65.1	Detailed Description	140

5.65.2	Member Data Documentation	140
5.65.2.1	ChangeInterval	140
5.65.2.2	SpeedMax	140
5.65.2.3	SpeedMin	140
5.65.2.4	UseInterval	140
5.66	Crosstales.Common.Util.RandomScaler Class Reference	141
5.66.1	Detailed Description	141
5.66.2	Member Data Documentation	141
5.66.2.1	ChangeInterval	141
5.66.2.2	ScaleMax	141
5.66.2.3	ScaleMin	142
5.66.2.4	Uniform	142
5.66.2.5	UseInterval	142
5.67	Crosstales.RTVoice.EditorTask.ReminderCheck Class Reference	142
5.67.1	Detailed Description	142
5.68	Crosstales.RTVoice.EditorIntegration.RTVoiceGameObject Class Reference	142
5.68.1	Detailed Description	143
5.69	RTVoiceIOSBridge Class Reference	143
5.69.1	Method Documentation	143
5.69.1.1	setVoices()	143
5.69.1.2	speak:text:rate:pitch:volume:(NSString *id,[text] NSString *text,[rate] float rate,[pitch] float pitch,[volume] float volume)	143
5.69.1.3	stop()	144
5.70	RTVoiceIOSBridge() Category Reference	144
5.71	Crosstales.RTVoice.EditorIntegration.RTVoiceMenu Class Reference	144
5.71.1	Detailed Description	144
5.72	Crosstales.UI.Util.ScrollRectHandler Class Reference	145
5.72.1	Detailed Description	145
5.73	Crosstales.RTVoice.Demo.SendMessage Class Reference	145
5.73.1	Detailed Description	146
5.74	Crosstales.RTVoice.Model.Sequence Class Reference	146

5.74.1	Detailed Description	146
5.74.2	Member Data Documentation	147
5.74.2.1	Mode	147
5.74.2.2	Pitch	147
5.74.2.3	Rate	147
5.74.2.4	Source	147
5.74.2.5	Text	147
5.74.2.6	Voices	147
5.74.2.7	Volume	147
5.75	Crosstales.RTVoice.Demo.SequenceCaller Class Reference	147
5.75.1	Detailed Description	148
5.76	Crosstales.RTVoice.Tool.Sequencer Class Reference	148
5.76.1	Detailed Description	149
5.76.2	Member Function Documentation	149
5.76.2.1	PlayAllSequences()	149
5.76.2.2	PlayNextSequence()	149
5.76.2.3	PlaySequence(int index=0)	149
5.76.2.4	StopAllSequences()	149
5.76.3	Member Data Documentation	149
5.76.3.1	Delay	150
5.76.3.2	PlayOnStart	150
5.76.3.3	Sequences	150
5.76.4	Property Documentation	150
5.76.4.1	CurrentSequence	150
5.77	Crosstales.RTVoice.EditorExtension.SequencerEditor Class Reference	150
5.77.1	Detailed Description	151
5.78	Crosstales.Common.Util.SerializableDictionary< TKey, TVal > Class Template Reference	151
5.78.1	Detailed Description	151
5.79	Crosstales.Common.Util.SerializeDeSerialize Class Reference	152
5.79.1	Detailed Description	152

5.79.2	Member Function Documentation	152
5.79.2.1	DeserializeFromByteArray< T >(byte[] data)	152
5.79.2.2	DeserializeFromFile< T >(string filename)	152
5.79.2.3	SerializeToByteArray< T >(T obj)	153
5.79.2.4	SerializeToFile< T >(T obj, string filename)	153
5.80	Crosstales.Common.EditorTask.SetApiLevel Class Reference	153
5.80.1	Detailed Description	153
5.81	Crosstales.Common.EditorTask.SetupResources Class Reference	154
5.81.1	Detailed Description	154
5.82	Crosstales.RTVoice.EditorTask.SetupResources Class Reference	154
5.82.1	Detailed Description	154
5.83	HutongGames.PlayMaker.Actions.Silence Class Reference	155
5.83.1	Detailed Description	155
5.84	Crosstales.RTVoice.PlayMaker.SilenceEditor Class Reference	155
5.84.1	Detailed Description	156
5.85	Crosstales.RTVoice.Demo.Simple Class Reference	156
5.85.1	Detailed Description	157
5.86	Crosstales.RTVoice.Demo.SimpleNative Class Reference	157
5.86.1	Detailed Description	158
5.87	Crosstales.UI.Social Class Reference	158
5.87.1	Detailed Description	158
5.88	Crosstales.RTVoice.SALSA.Speak Class Reference	158
5.89	HutongGames.PlayMaker.Actions.Speak Class Reference	159
5.89.1	Detailed Description	160
5.89.2	Member Data Documentation	160
5.89.2.1	Culture	160
5.89.2.2	RTVoiceNameAndroid	160
5.89.2.3	RTVoiceNameCustom	160
5.89.2.4	RTVoiceNameIOS	160
5.89.2.5	RTVoiceNameMac	161

5.89.2.6	RTVoiceNameMaryTTS	161
5.89.2.7	RTVoiceNameWindows	161
5.89.2.8	RTVoiceNameWSA	161
5.89.2.9	Text	161
5.90	Crosstales.RTVoice.SALSA.Speak2D Class Reference	161
5.91	HutongGames.PlayMaker.Actions.SpeakBase Class Reference	162
5.91.1	Detailed Description	163
5.91.2	Member Data Documentation	163
5.91.2.1	AudioSource	163
5.91.2.2	Mode	163
5.91.2.3	Pitch	163
5.91.2.4	Rate	163
5.91.2.5	Volume	163
5.92	Crosstales.RTVoice.PlayMaker.SpeakEditor Class Reference	164
5.92.1	Detailed Description	164
5.93	Crosstales.RTVoice.Speaker Class Reference	164
5.93.1	Detailed Description	168
5.93.2	Member Function Documentation	168
5.93.2.1	ApproximateSpeechLength(string text, float rate=1f, float wordsPerMinute=175f, float timeFactor=0.9f)	168
5.93.2.2	DeleteAudioFiles()	169
5.93.2.3	Generate(Model.Wrapper wrapper)	169
5.93.2.4	Generate(string text, string outputFile, Model.Voice voice=null, float rate=1f, float pitch=1f, float volume=1f, bool forceSSML=true)	169
5.93.2.5	isVoiceForCultureAvailable(string culture)	170
5.93.2.6	isVoiceForGenderAvailable(Model.Enum.Gender gender, string culture="")	170
5.93.2.7	isVoiceForNameAvailable(string name, bool isExact=false)	170
5.93.2.8	Pause(string uid)	171
5.93.2.9	ReloadProvider()	171
5.93.2.10	Reset()	171
5.93.2.11	Silence()	171

5.93.2.12 Silence(string uid)	171
5.93.2.13 Speak(string text, AudioSource source=null, Model.Voice voice=null, bool speakImmediately=true, float rate=1f, float pitch=1f, float volume=1f, string outputFile="","", bool forceSSML=true)	171
5.93.2.14 Speak(Model.Wrapper wrapper)	172
5.93.2.15 SpeakMarkedWordsWithUID(Model.Wrapper wrapper)	172
5.93.2.16 SpeakMarkedWordsWithUID(string uid, string text, AudioSource source, Model.Voice voice=null, float rate=1f, float pitch=1f, bool forceSSML=true)	172
5.93.2.17 SpeakNative(string text, Model.Voice voice=null, float rate=1f, float pitch=1f, float volume=1f, bool forceSSML=true)	172
5.93.2.18 SpeakNative(Model.Wrapper wrapper)	173
5.93.2.19 SpeakNativeWithUID(Model.Wrapper wrapper)	173
5.93.2.20 SpeakWithUID(Model.Wrapper wrapper)	173
5.93.2.21 UnPause(string uid)	173
5.93.2.22 VoiceForCulture(string culture, int index=0, string fallbackCulture="","", bool isFuzzy=true)	174
5.93.2.23 VoiceForGender(Model.Enum.Gender gender, string culture="","", int index=0, string fallbackCulture="","", bool isFuzzy=true)	174
5.93.2.24 VoiceForName(string name, bool isExact=false)	174
5.93.2.25 VoicesForCulture(string culture, bool isFuzzy=true)	175
5.93.2.26 VoicesForGender(Model.Enum.Gender gender, string culture="","", bool isFuzzy=true)	175
5.93.3 Member Data Documentation	175
5.93.3.1 AutoClearTags	175
5.93.3.2 CustomMode	175
5.93.3.3 CustomProvider	175
5.93.3.4 DontDestroy	176
5.93.3.5 ESpeakMode	176
5.93.3.6 ESpeakModifier	176
5.93.3.7 MaryTTSMMode	176
5.93.3.8 MaryTTSPassword	176
5.93.3.9 MaryTTSPort	176
5.93.3.10 MaryTTSType	176

5.93.3.11	MaryTTSUrl	176
5.93.3.12	MaryTTSUser	176
5.93.3.13	SilenceOnDisable	176
5.93.3.14	SilenceOnFocustLost	177
5.93.3.15	WindowsLegacy	177
5.93.4	Property Documentation	177
5.93.4.1	areVoicesReady	177
5.93.4.2	AudioFileExtension	177
5.93.4.3	BusyCount	177
5.93.4.4	Cultures	177
5.93.4.5	CustomVoiceProvider	177
5.93.4.6	DefaultVoiceName	178
5.93.4.7	ESpeakMod	178
5.93.4.8	hasCoRoutines	178
5.93.4.9	isAutoClearTags	178
5.93.4.10	isBusy	178
5.93.4.11	isCustomMode	178
5.93.4.12	isESpeakMode	178
5.93.4.13	isMaryMode	178
5.93.4.14	isOnlineService	179
5.93.4.15	isPlatformSupported	179
5.93.4.16	isSilenceOnDisable	179
5.93.4.17	isSilenceOnFocustLost	179
5.93.4.18	isSpeaking	179
5.93.4.19	isSpeakNativeSupported	179
5.93.4.20	isSpeakSupported	180
5.93.4.21	isSSMLSupported	180
5.93.4.22	isTTSAvailable	180
5.93.4.23	isWindowsLegacy	180
5.93.4.24	isWorkingInEditor	180

5.93.4.25	MaryPassword	180
5.93.4.26	MaryPort	180
5.93.4.27	MaryType	181
5.93.4.28	MaryUrl	181
5.93.4.29	MaryUser	181
5.93.4.30	MaxTextLength	181
5.93.4.31	OnErrorInfo	181
5.93.4.32	OnProviderChange	181
5.93.4.33	OnSpeakAudioGenerationComplete	181
5.93.4.34	OnSpeakAudioGenerationStart	181
5.93.4.35	OnSpeakComplete	181
5.93.4.36	OnSpeakCurrentPhoneme	182
5.93.4.37	OnSpeakCurrentViseme	182
5.93.4.38	OnSpeakCurrentWord	182
5.93.4.39	OnSpeakStart	182
5.93.4.40	OnVoicesReady	182
5.93.4.41	SpeechCount	182
5.93.4.42	Voices	182
5.94	Crosstales.RTVoice.EditorExtension.SpeakerEditor Class Reference	183
5.94.1	Detailed Description	183
5.95	Crosstales.RTVoice.SALSA.SpeakSimple Class Reference	183
5.96	HutongGames.PlayMaker.Actions.SpeakUI Class Reference	184
5.96.1	Detailed Description	184
5.96.2	Member Data Documentation	185
5.96.2.1	Culture	185
5.96.2.2	RTVoiceName	185
5.96.2.3	Text	185
5.97	Crosstales.RTVoice.PlayMaker.SpeakUIEditor Class Reference	185
5.97.1	Detailed Description	185
5.98	Crosstales.RTVoice.Demo.SpeakWrapper Class Reference	186

5.98.1 Detailed Description	186
5.99 Crosstales.Common.Util.SpectrumVisualizer Class Reference	186
5.99.1 Detailed Description	187
5.99.2 Member Data Documentation	187
5.99.2.1 Analyzer	187
5.99.2.2 Gain	187
5.99.2.3 LeftToRight	187
5.99.2.4 VisualPrefab	187
5.99.2.5 Width	188
5.100HutongGames.PlayMaker.Actions.SpeechText Class Reference	188
5.100.1 Detailed Description	188
5.100.2 Member Data Documentation	188
5.100.2.1 Obj	188
5.101Crosstales.RTVoice.Tool.SpeechText Class Reference	189
5.101.1 Detailed Description	190
5.101.2 Member Function Documentation	190
5.101.2.1 Silence()	190
5.101.2.2 Speak()	190
5.101.3 Member Data Documentation	190
5.101.3.1 Delay	190
5.101.3.2 FileInsideAssets	190
5.101.3.3 FileName	190
5.101.3.4 GenerateAudioFile	191
5.101.3.5 Mode	191
5.101.3.6 Pitch	191
5.101.3.7 PlayOnStart	191
5.101.3.8 Rate	191
5.101.3.9 Source	191
5.101.3.10Text	191
5.101.3.11Voices	191

5.101.3.12Volume	191
5.101.4 Property Documentation	191
5.101.4.1 CurrentPitch	191
5.101.4.2 CurrentRate	192
5.101.4.3 CurrentText	192
5.101.4.4 CurrentVolume	192
5.101.4.5 OnSpeechTextComplete	192
5.101.4.6 OnSpeechTextStart	192
5.102Crosstales.RTVoice.EditorExtension.SpeechTextEditor Class Reference	192
5.102.1 Detailed Description	193
5.103Crosstales.RTVoice.PlayMaker.SpeechTextEditor Class Reference	193
5.103.1 Detailed Description	193
5.104Crosstales.UI.StaticManager Class Reference	193
5.104.1 Detailed Description	194
5.104.2 Member Function Documentation	194
5.104.2.1 OpenCrosstales()	194
5.104.2.2 Quit()	194
5.105Crosstales.Common.Util.SurviveSceneSwitch Class Reference	194
5.105.1 Detailed Description	195
5.105.2 Member Data Documentation	195
5.105.2.1 Survivors	195
5.106Crosstales.RTVoice.AWSPolly.Switcher Class Reference	195
5.106.1 Detailed Description	195
5.107Crosstales.Common.Util.TakeScreenshot Class Reference	196
5.107.1 Detailed Description	196
5.107.2 Member Function Documentation	196
5.107.2.1 Update()	196
5.107.3 Member Data Documentation	196
5.107.3.1 Prefix	196
5.107.3.2 Scale	197

5.108Crosstales.RTVoice.Tool.TextFileSpeaker Class Reference	197
5.108.1 Detailed Description	198
5.108.2 Member Function Documentation	198
5.108.2.1 Next()	198
5.108.2.2 Next(bool random)	198
5.108.2.3 Previous()	199
5.108.2.4 Previous(bool random)	199
5.108.2.5 Reload()	199
5.108.2.6 Silence()	199
5.108.2.7 Speak()	199
5.108.2.8 SpeakAll()	199
5.108.2.9 SpeakText(int index=-1, bool random=false)	199
5.108.2.10StopAll()	200
5.108.3 Member Data Documentation	200
5.108.3.1 Delay	200
5.108.3.2 Mode	200
5.108.3.3 Pitch	200
5.108.3.4 PlayAllOnStart	200
5.108.3.5 PlayOnStart	200
5.108.3.6 Rate	200
5.108.3.7 Source	200
5.108.3.8 SpeakRandom	200
5.108.3.9 TextFiles	201
5.108.3.10Voices	201
5.108.3.11Volume	201
5.108.4 Property Documentation	201
5.108.4.1 CurrentPitch	201
5.108.4.2 CurrentRate	201
5.108.4.3 CurrentVolume	201
5.109HutongGames.PlayMaker.Actions.TextFileSpeaker Class Reference	201

5.109.1 Detailed Description	202
5.109.2 Member Data Documentation	202
5.109.2.1 Obj	202
5.110Crosstales.RTVoice.EditorExtension.TextFileSpeakerEditor Class Reference	202
5.110.1 Detailed Description	203
5.111Crosstales.RTVoice.PlayMaker.TextFileSpeakerEditor Class Reference	203
5.111.1 Detailed Description	203
5.112Crosstales.RTVoice.EditorTask.Tracer Class Reference	203
5.112.1 Detailed Description	203
5.113Crosstales.RTVoice.UDEA2.UDEAConnector Class Reference	204
5.113.1 Detailed Description	204
5.113.2 Member Data Documentation	204
5.113.2.1 Culture	204
5.113.2.2 Voices	204
5.114Crosstales.RTVoice.UDEA2.UDEAConnectorEditor Class Reference	205
5.114.1 Detailed Description	205
5.115Crosstales.RTVoice.UDEA2.UDEAVoiceWrapper Class Reference	205
5.115.1 Detailed Description	206
5.115.2 Member Data Documentation	206
5.115.2.1 IgnoreCharacter	206
5.115.2.2 Pitch	206
5.115.2.3 Rate	206
5.115.2.4 Source	206
5.115.2.5 UDEAVoiceName	206
5.115.2.6 Voices	206
5.115.2.7 Volume	206
5.116Crosstales.UI.UIDrag Class Reference	207
5.116.1 Detailed Description	207
5.116.2 Member Function Documentation	207
5.116.2.1 BeginDrag()	207

5.116.2.2 Start()	207
5.117Crosstales.UI.UIFocus Class Reference	207
5.117.1 Detailed Description	208
5.117.2 Member Function Documentation	208
5.117.2.1 Start()	208
5.117.3 Member Data Documentation	208
5.117.3.1 ManagerName	208
5.118Crosstales.UI.UIHint Class Reference	208
5.118.1 Detailed Description	209
5.118.2 Member Data Documentation	209
5.118.2.1 Delay	209
5.118.2.2 Disable	209
5.118.2.3 FadeAtStart	209
5.118.2.4 FadeTime	209
5.118.2.5 Group	210
5.119Crosstales.UI.UIResize Class Reference	210
5.119.1 Detailed Description	210
5.119.2 Member Data Documentation	210
5.119.2.1 MaxSize	210
5.119.2.2 MinSize	211
5.120Crosstales.UI.UIWindowManager Class Reference	211
5.120.1 Detailed Description	211
5.120.2 Member Function Documentation	211
5.120.2.1 Start()	211
5.120.3 Member Data Documentation	212
5.120.3.1 Windows	212
5.121Crosstales.RTVoice.EditorTask.UpdateCheck Class Reference	212
5.121.1 Detailed Description	212
5.122Crosstales.RTVoice.Model.Voice Class Reference	212
5.122.1 Detailed Description	213

5.122.2 Constructor & Destructor Documentation	213
5.122.2.1 Voice(string name, string description, Enum.Gender gender, string age, string culture, string id="","", string vendor=""unknown"")	213
5.122.3 Member Data Documentation	213
5.122.3.1 Age	213
5.122.3.2 Description	214
5.122.3.3 Gender	214
5.122.3.4 Identifier	214
5.122.3.5 Name	214
5.122.3.6 Vendor	214
5.122.4 Property Documentation	214
5.122.4.1 Culture	214
5.123Crosstales.RTVoice.Model.VoiceAlias Class Reference	214
5.123.1 Detailed Description	215
5.123.2 Member Data Documentation	215
5.123.2.1 Culture	215
5.123.2.2 Gender	215
5.123.2.3 VoiceNameAndroid	215
5.123.2.4 VoiceNameCustom	216
5.123.2.5 VoiceNameIOS	216
5.123.2.6 VoiceNameLinux	216
5.123.2.7 VoiceNameMac	216
5.123.2.8 VoiceNameMaryTTS	216
5.123.2.9 VoiceNameWindows	216
5.123.2.10VoiceNameWSA	216
5.123.3 Property Documentation	216
5.123.3.1 Voice	216
5.123.3.2 VoiceName	217
5.124Crosstales.RTVoice.Tool.VoiceInitializer Class Reference	217
5.124.1 Detailed Description	217
5.124.2 Member Data Documentation	218

5.124.2.1 AllVoices	218
5.124.2.2 DestroyWhenFinished	218
5.124.2.3 Provider	218
5.124.2.4 VoiceNames	218
5.125Crosstales.RTVoice.EditorExtension.VoiceInitializerEditor Class Reference	218
5.125.1 Detailed Description	218
5.126Crosstales.RTVoice.Provider.VoiceProviderAndroid Class Reference	219
5.126.1 Detailed Description	219
5.126.2 Constructor & Destructor Documentation	219
5.126.2.1 VoiceProviderAndroid(MonoBehaviour obj)	219
5.126.3 Member Function Documentation	220
5.126.3.1 Generate(Model.Wrapper wrapper)	220
5.126.3.2 Silence()	220
5.126.3.3 Speak(Model.Wrapper wrapper)	220
5.126.3.4 SpeakNative(Model.Wrapper wrapper)	220
5.127Crosstales.RTVoice.AWSPolly.VoiceProviderAWS Class Reference	221
5.127.1 Detailed Description	222
5.127.2 Member Function Documentation	222
5.127.2.1 Generate(Model.Wrapper wrapper)	222
5.127.2.2 Load()	222
5.127.2.3 Speak(Model.Wrapper wrapper)	222
5.127.2.4 SpeakNative(Model.Wrapper wrapper)	222
5.127.3 Member Data Documentation	223
5.127.3.1 CognitoCredentials	223
5.127.3.2 Endpoint	223
5.128Crosstales.RTVoice.AWSPolly.VoiceProviderAWSEditor Class Reference	223
5.128.1 Detailed Description	223
5.129Crosstales.RTVoice.AWSPolly.VoiceProviderAWSGameObject Class Reference	224
5.129.1 Detailed Description	224
5.130Crosstales.RTVoice.AWSPolly.VoiceProviderAWSMenu Class Reference	224

5.130.1 Detailed Description	224
5.131 Crosstales.RTVoice.VoiceProviderExample Class Reference	224
5.131.1 Detailed Description	225
5.131.2 Member Function Documentation	225
5.131.2.1 Generate(Model.Wrapper wrapper)	225
5.131.2.2 Load()	225
5.131.2.3 Speak(Model.Wrapper wrapper)	226
5.131.2.4 SpeakNative(Model.Wrapper wrapper)	226
5.132 Crosstales.RTVoice.Provider.VoiceProviderIOS Class Reference	226
5.132.1 Detailed Description	227
5.132.2 Constructor & Destructor Documentation	227
5.132.2.1 VoiceProviderIOS(MonoBehaviour obj)	227
5.132.3 Member Function Documentation	228
5.132.3.1 Generate(Model.Wrapper wrapper)	228
5.132.3.2 SetState(string state)	228
5.132.3.3 SetVoices(string voicesText)	228
5.132.3.4 Silence()	228
5.132.3.5 Speak(Model.Wrapper wrapper)	228
5.132.3.6 SpeakNative(Model.Wrapper wrapper)	229
5.132.3.7 WordSpoken()	229
5.133 Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynth Class Reference	229
5.133.1 Detailed Description	230
5.133.2 Member Function Documentation	230
5.133.2.1 Generate(Model.Wrapper wrapper)	230
5.133.2.2 Load()	230
5.133.2.3 Speak(Model.Wrapper wrapper)	231
5.133.2.4 SpeakNative(Model.Wrapper wrapper)	231
5.133.3 Member Data Documentation	231
5.133.3.1 SampleRate	231
5.133.3.2 Speeches	231

5.134Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynthEditor Class Reference	231
5.134.1 Detailed Description	232
5.135Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynthGameObject Class Reference	232
5.135.1 Detailed Description	232
5.136Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynthMenu Class Reference	232
5.136.1 Detailed Description	232
5.137Crosstales.RTVoice.Provider.VoiceProviderLinux Class Reference	233
5.137.1 Detailed Description	233
5.137.2 Constructor & Destructor Documentation	233
5.137.2.1 VoiceProviderLinux(MonoBehaviour obj)	233
5.137.3 Member Function Documentation	234
5.137.3.1 Generate(Model.Wrapper wrapper)	234
5.137.3.2 Speak(Model.Wrapper wrapper)	234
5.137.3.3 SpeakNative(Model.Wrapper wrapper)	234
5.138Crosstales.RTVoice.Provider.VoiceProviderMacOS Class Reference	235
5.138.1 Detailed Description	235
5.138.2 Constructor & Destructor Documentation	235
5.138.2.1 VoiceProviderMacOS(MonoBehaviour obj)	235
5.138.3 Member Function Documentation	236
5.138.3.1 Generate(Model.Wrapper wrapper)	236
5.138.3.2 Speak(Model.Wrapper wrapper)	236
5.138.3.3 SpeakNative(Model.Wrapper wrapper)	236
5.139Crosstales.RTVoice.Provider.VoiceProviderMary Class Reference	237
5.139.1 Detailed Description	237
5.139.2 Constructor & Destructor Documentation	237
5.139.2.1 VoiceProviderMary(MonoBehaviour obj, string url, int port, string user, string password)	237
5.139.3 Member Function Documentation	238
5.139.3.1 Generate(Model.Wrapper wrapper)	238
5.139.3.2 Silence()	238
5.139.3.3 Speak(Model.Wrapper wrapper)	238

5.139.3.4 SpeakNative(Model.Wrapper wrapper)	238
5.140Crosstales.RTVoice.Provider.VoiceProviderWindows Class Reference	239
5.140.1 Detailed Description	240
5.140.2 Constructor & Destructor Documentation	240
5.140.2.1 VoiceProviderWindows(MonoBehaviour obj)	240
5.140.3 Member Function Documentation	240
5.140.3.1 Generate(Model.Wrapper wrapper)	240
5.140.3.2 Speak(Model.Wrapper wrapper)	240
5.140.3.3 SpeakNative(Model.Wrapper wrapper)	240
5.141Crosstales.RTVoice.Provider.VoiceProviderWindowsLegacy Class Reference	241
5.141.1 Detailed Description	242
5.141.2 Constructor & Destructor Documentation	242
5.141.2.1 VoiceProviderWindowsLegacy(MonoBehaviour obj)	242
5.141.3 Member Function Documentation	242
5.141.3.1 Generate(Model.Wrapper wrapper)	242
5.141.3.2 Speak(Model.Wrapper wrapper)	242
5.141.3.3 SpeakNative(Model.Wrapper wrapper)	242
5.142Crosstales.RTVoice.Provider.VoiceProviderWSA Class Reference	243
5.142.1 Detailed Description	244
5.142.2 Constructor & Destructor Documentation	244
5.142.2.1 VoiceProviderWSA(MonoBehaviour obj)	244
5.142.3 Member Function Documentation	244
5.142.3.1 Generate(Model.Wrapper wrapper)	244
5.142.3.2 Silence()	244
5.142.3.3 Speak(Model.Wrapper wrapper)	244
5.142.3.4 SpeakNative(Model.Wrapper wrapper)	245
5.143Crosstales.RTVoice.Util.WavMaster Class Reference	245
5.143.1 Member Function Documentation	245
5.143.1.1 BitDepth(AudioClip audioClip)	245
5.143.1.2 FromAudioClip(AudioClip audioClip)	246

5.143.1.3 FromAudioClip(AudioClip audioClip, out string filepath, bool saveAsFile=true, string dirname=""rtv_audio"")	246
5.143.1.4 ToAudioClip(string filePath, string name=""wav"")	246
5.143.1.5 ToAudioClip(byte[] fileBytes, int offsetSamples=0, string name=""wav"")	247
5.144Crosstales.UI.WindowManager Class Reference	247
5.144.1 Detailed Description	248
5.144.2 Member Function Documentation	248
5.144.2.1 OpenPanel()	248
5.144.2.2 SwitchPanel()	248
5.144.2.3 Update()	248
5.144.3 Member Data Documentation	248
5.144.3.1 Dependencies	248
5.144.3.2 Speed	248
5.145Crosstales.RTVoice.Model.Wrapper Class Reference	248
5.145.1 Detailed Description	249
5.145.2 Constructor & Destructor Documentation	250
5.145.2.1 Wrapper()	250
5.145.2.2 Wrapper(string text, Voice voice=null, float rate=1f, float pitch=1f, float volume=1f, bool forceSSML=true)	250
5.145.2.3 Wrapper(string text, Voice voice=null, float rate=1f, float pitch=1f, float volume=1f, AudioSource source=null, bool speakImmediately=true, string outputFile="", bool forceSSML=true)	250
5.145.2.4 Wrapper(string uid, string text, Voice voice=null, float rate=1f, float pitch=1f, float volume=1f, AudioSource source=null, bool speakImmediately=true, string outputFile="", bool forceSSML=true)	250
5.145.3 Member Data Documentation	251
5.145.3.1 ForceSSML	251
5.145.3.2 OutputFile	251
5.145.3.3 Source	251
5.145.3.4 SpeakImmediately	251
5.145.3.5 Uid	251
5.145.3.6 Voice	251
5.145.4 Property Documentation	252

5.145.4.1 Created	252
5.145.4.2 Pitch	252
5.145.4.3 Rate	252
5.145.4.4 Text	252
5.145.4.5 Volume	252
5.146 Crosstales.Common.Util.XmlHelper Class Reference	252
5.146.1 Detailed Description	253
5.146.2 Member Function Documentation	253
5.146.2.1 DeserializeFromFile< T >(string filename, bool skipBOM=false)	253
5.146.2.2 DeserializeFromResource< T >(string resourceName, bool skipBOM=true)	253
5.146.2.3 DeserializeFromString< T >(string xmlAsString, bool skipBOM=true)	253
5.146.2.4 SerializeToFile< T >(T obj, string filename)	254
5.146.2.5 SerializeToString< T >(T obj)	254
6 More information	255
6.1 Homepage	255
6.2 AssetStore	255
6.3 Forum	255
6.4 Documentation	255
6.5 Discord	255
6.6 Demos	255
6.6.1 WebGL	255
6.6.2 Windows	256
6.6.3 macOS	256
6.6.4 Android	256
6.7 Videos	256
6.7.1 Promotion	256
6.7.2 Tutorial	256
Index	257

Chapter 1

Namespace Index

1.1 Packages

Here are the packages with brief descriptions (if available):

Crosstales	13
Crosstales.Common	13
Crosstales.Common.EditorTask	13
Crosstales.Common.EditorUtil	14
Crosstales.Common.Model	14
Crosstales.Common.Model.Enum	14
Crosstales.Common.Util	15
Crosstales.RTVoice	15
Crosstales.RTVoice.AWSPolly	16
Crosstales.RTVoice.Demo	17
Crosstales.RTVoice.Demo.Util	18
Crosstales.RTVoice.EditorExtension	18
Crosstales.RTVoice.EditorIntegration	18
Crosstales.RTVoice.EditorTask	19
Crosstales.RTVoice.EditorUtil	19
Crosstales.RTVoice.Klattersynth	20
Crosstales.RTVoice.Model	20
Crosstales.RTVoice.Model.Enum	20
Crosstales.RTVoice.PlayMaker	21
Crosstales.RTVoice.Provider	22
Crosstales.RTVoice.SALSA	22
Crosstales.RTVoice.Tool	22
Crosstales.RTVoice.UDEA2	23
Crosstales.RTVoice.Util	
WAV utility for recording and audio playback functions in Unity	23
Crosstales.UI	24
Crosstales.UI.Util	24
HutongGames	24
HutongGames.PlayMaker	24
HutongGames.PlayMaker.Actions	24

Chapter 2

Hierarchical Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Crosstales.RTVoice.EditorTask.AutoInitalize	35
<AVSpeechSynthesizerDelegate>	
RTVoiceIOSBridge()	144
Crosstales.Common.EditorTask.BaseCompileDefines	36
Crosstales.RTVoice.EditorTask.CompileDefines	71
Crosstales.Common.Util.BaseConstants	37
Crosstales.RTVoice.Util.Constants	77
Crosstales.Common.EditorUtil.BaseGAApi	51
Crosstales.RTVoice.EditorUtil.GAApi	105
Crosstales.Common.Util.BaseHelper	52
Crosstales.Common.EditorUtil.BaseEditorHelper	48
Crosstales.RTVoice.EditorUtil.EditorHelper	93
Crosstales.RTVoice.Util.Helper	112
Crosstales.Common.EditorTask.BaseSetupResources	63
Crosstales.Common.EditorTask.SetupResources	154
Crosstales.RTVoice.EditorTask.SetupResources	154
Crosstales.RTVoice.EditorTask.CheckIL2CPP	71
Crosstales.RTVoice.Util.Config	71
Crosstales.RTVoice.EditorTask.ConfigLoader	75
Crosstales.Common.Util.CTPlayerPrefs	83
CustomActionEditor	
Crosstales.RTVoice.PlayMaker.BaseRTVEditor	62
Crosstales.RTVoice.PlayMaker.AudioFileGeneratorEditor	30
Crosstales.RTVoice.PlayMaker.ParalanguageEditor	134
Crosstales.RTVoice.PlayMaker.SilenceEditor	155
Crosstales.RTVoice.PlayMaker.SpeechTextEditor	193
Crosstales.RTVoice.PlayMaker.TextFileSpeakerEditor	203
Crosstales.RTVoice.PlayMaker.SpeakEditor	164
Crosstales.RTVoice.PlayMaker.SpeakUIEditor	185
Dictionary	
Crosstales.Common.Util.SerializableDictionary< TKey, TVal >	151
Editor	
Crosstales.RTVoice.AWSPolly.VoiceProviderAWSEditor	223
Crosstales.RTVoice.EditorExtension.AudioFileGeneratorEditor	30

Crosstales.RTVoice.EditorExtension.ChangeGenderEditor	70
Crosstales.RTVoice.EditorExtension.LoudspeakerEditor	126
Crosstales.RTVoice.EditorExtension.ParalanguageEditor	133
Crosstales.RTVoice.EditorExtension.SequencerEditor	150
Crosstales.RTVoice.EditorExtension.SpeakerEditor	183
Crosstales.RTVoice.EditorExtension.SpeechTextEditor	192
Crosstales.RTVoice.EditorExtension.TextFileSpeakerEditor	202
Crosstales.RTVoice.EditorExtension.VoiceInitializerEditor	218
Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynthEditor	231
Crosstales.RTVoice.UDEA2.UDEAConnectorEditor	205
Crosstales.RTVoice.EditorUtil.EditorConfig	89
Crosstales.RTVoice.EditorUtil.EditorConstants	91
EditorWindow	
Crosstales.RTVoice.EditorIntegration.ConfigBase	74
Crosstales.RTVoice.EditorIntegration.ConfigPreferences	75
Crosstales.RTVoice.EditorIntegration.ConfigWindow	76
Crosstales.ExtensionMethods	95
FsmStateAction	
HutongGames.PlayMaker.Actions.BaseRTVAction	62
HutongGames.PlayMaker.Actions.AudioFileGenerator	27
HutongGames.PlayMaker.Actions.Paralanguage	133
HutongGames.PlayMaker.Actions.Silence	155
HutongGames.PlayMaker.Actions.SpeakBase	162
HutongGames.PlayMaker.Actions.Speak	159
HutongGames.PlayMaker.Actions.SpeakUI	184
HutongGames.PlayMaker.Actions.SpeechText	188
HutongGames.PlayMaker.Actions.TextFileSpeaker	201
IDragHandler	
Crosstales.UI.UIResize	210
IPointerDownHandler	
Crosstales.UI.UIResize	210
ISerializable	
Crosstales.Common.Util.SerializableDictionary< TKey, TVal >	151
Crosstales.RTVoice.Provider.IVoiceProvider	116
Crosstales.RTVoice.Provider.BaseCustomVoiceProvider	44
Crosstales.RTVoice.AWSPolly.VoiceProviderAWS	221
Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynth	229
Crosstales.RTVoice.VoiceProviderExample	224
Crosstales.RTVoice.Provider.BaseVoiceProvider	63
Crosstales.RTVoice.Provider.VoiceProviderAndroid	219
Crosstales.RTVoice.Provider.VoiceProviderIOS	226
Crosstales.RTVoice.Provider.VoiceProviderLinux	233
Crosstales.RTVoice.Provider.VoiceProviderMacOS	235
Crosstales.RTVoice.Provider.VoiceProviderMary	237
Crosstales.RTVoice.Provider.VoiceProviderWindows	239
Crosstales.RTVoice.Provider.VoiceProviderWindowsLegacy	241
Crosstales.RTVoice.Provider.VoiceProviderWSA	243
IXmlSerializable	
Crosstales.Common.Util.SerializableDictionary< TKey, TVal >	151
Crosstales.RTVoice.EditorTask.Launch	121
MonoBehaviour	
Crosstales.Common.Util.BackgroundController	35
Crosstales.Common.Util.FFTAnalyzer	103
Crosstales.Common.Util.PlatformController	135
Crosstales.RTVoice.Demo.Util.PlatformController	136
Crosstales.Common.Util.RandomColor	137
Crosstales.Common.Util.RandomRotator	139
Crosstales.Common.Util.RandomScaler	141

Crosstales.Common.Util.SpectrumVisualizer	186
Crosstales.Common.Util.SurviveSceneSwitch	194
Crosstales.Common.Util.TakeScreenshot	196
Crosstales.RTVoice.AWSPolly.Switcher	195
Crosstales.RTVoice.AWSPolly.VoiceProviderAWSGameObject	224
Crosstales.RTVoice.Demo.Dialog	88
Crosstales.RTVoice.Demo.GUIAudioFilter	106
Crosstales.RTVoice.Demo.GUIDialog	107
Crosstales.RTVoice.Demo.GUIMain	108
Crosstales.RTVoice.Demo.GUIMultiAudioFilter	109
Crosstales.RTVoice.Demo.GUIScenes	110
Crosstales.RTVoice.Demo.GUISpeech	111
Crosstales.RTVoice.Demo.NativeAudio	127
Crosstales.RTVoice.Demo.PreGeneratedAudio	137
Crosstales.RTVoice.Demo.SendMessage	145
Crosstales.RTVoice.Demo.SequenceCaller	147
Crosstales.RTVoice.Demo.Simple	156
Crosstales.RTVoice.Demo.SimpleNative	157
Crosstales.RTVoice.Demo.SpeakWrapper	186
Crosstales.RTVoice.Demo.Util.iOSController	115
Crosstales.RTVoice.Demo.Util.MaterialChanger	127
Crosstales.RTVoice.Demo.Util.NativeController	128
Crosstales.RTVoice.EditorIntegration.RTVoiceGameObject	142
Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynthGameObject	232
Crosstales.RTVoice.LiveSpeaker	121
Crosstales.RTVoice.Provider.BaseCustomVoiceProvider	44
Crosstales.RTVoice.SALSA.Bots	68
Crosstales.RTVoice.SALSA.Speak	158
Crosstales.RTVoice.SALSA.Speak2D	161
Crosstales.RTVoice.SALSA.SpeakSimple	183
Crosstales.RTVoice.Speaker	164
Crosstales.RTVoice.Tool.AudioFileGenerator	28
Crosstales.RTVoice.Tool.ChangeGender	69
Crosstales.RTVoice.Tool.Loudspeaker	124
Crosstales.RTVoice.Tool.Paralanguage	129
Crosstales.RTVoice.Tool.Sequencer	148
Crosstales.RTVoice.Tool.SpeechText	189
Crosstales.RTVoice.Tool.TextFileSpeaker	197
Crosstales.RTVoice.Tool.VoiceInitializer	217
Crosstales.RTVoice.UDEA2.UDEAConnector	204
Crosstales.UI.Social	158
Crosstales.UI.StaticManager	193
Crosstales.UI.UIDrag	207
Crosstales.UI.UIFocus	207
Crosstales.UI.UIHint	208
Crosstales.UI.UIResize	210
Crosstales.UI.UIWindowManager	211
Crosstales.UI.Util.AudioFilterController	31
Crosstales.UI.Util.AudioSourceController	33
Crosstales.UI.Util.FPSDisplay	105
Crosstales.UI.Util.ScrollRectHandler	145
Crosstales.UI.WindowManager	247
NSObject	
RTVoiceIOSBridge	143
Crosstales.Common.EditorTask.NYCheck	129
Crosstales.RTVoice.EditorTask.ReminderCheck	142
Crosstales.RTVoice.EditorIntegration.RTVoiceMenu	144
Crosstales.RTVoice.Model.Sequence	146

Crosstales.Common.Util.SerializableDictionary< string, string >	151
Crosstales.Common.Util.SerializeDeSerialize	152
Crosstales.Common.EditorTask.SetApiLevel	153
Crosstales.RTVoice.EditorTask.Tracer	203
Crosstales.RTVoice.UDEA2.UDEAVoiceWrapper	205
Crosstales.RTVoice.EditorTask.UpdateCheck	212
Crosstales.RTVoice.Model.Voice	212
Crosstales.RTVoice.Model.VoiceAlias	214
Crosstales.RTVoice.AWSPolly.VoiceProviderAWSMenu	224
Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynthMenu	232
Crosstales.RTVoice.Util.WavMaster	245
WebClient	
Crosstales.Common.Util.CTWebClient	87
Crosstales.RTVoice.Model.Wrapper	248
Crosstales.Common.Util.XmlHelper	252

Chapter 3

Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

HutongGames.PlayMaker.Actions.AudioFileGenerator	
AudioFileGenerator-action for PlayMaker.	27
Crosstales.RTVoice.Tool.AudioFileGenerator	
Process files with configured speeches.	28
Crosstales.RTVoice.EditorExtension.AudioFileGeneratorEditor	
Custom editor for the 'SpeechText'-class.	30
Crosstales.RTVoice.PlayMaker.AudioFileGeneratorEditor	
Custom editor for the AudioFileGenerator-action.	30
Crosstales.UI.Util.AudioFilterController	
Controller for audio filters.	31
Crosstales.UI.Util.AudioSourceController	
Controller for AudioSources.	33
Crosstales.RTVoice.EditorTask.AutoInitalize	
Automatically adds the neccessary RTVoice-prefabs to the current scene.	35
Crosstales.Common.Util.BackgroundController	
Enables or disable game objects on Android or iOS in the background.	35
Crosstales.Common.EditorTask.BaseCompileDefines	
Base for adding the given define symbols to PlayerSettings define symbols.	36
Crosstales.Common.Util.BaseConstants	
Base for collected constants of very general utility for the asset.	37
Crosstales.RTVoice.Provider.BaseCustomVoiceProvider	
Base class for custom voice providers (TTS-systems).	44
Crosstales.Common.EditorUtil.BaseEditorHelper	
Base for various Editor helper functions.	48
Crosstales.Common.EditorUtil.BaseGAApi	
Base GA-wrapper API.	51
Crosstales.Common.Util.BaseHelper	
Base for various helper functions.	52
HutongGames.PlayMaker.Actions.BaseRTVAction	
Base class for RT-Voice actions in PlayMaker.	62
Crosstales.RTVoice.PlayMaker.BaseRTVEditor	
Base class for RT-Voice custom editors in PlayMaker.	62
Crosstales.Common.EditorTask.BaseSetupResources	
Base for copying all resources to 'Editor Default Resources'.	63
Crosstales.RTVoice.Provider.BaseVoiceProvider	
Base class for voice providers.	63

Crosstales.RTVoice.SALSA.Bots	
This is class for conversations between two SALSA-Bots.	68
Crosstales.RTVoice.Tool.ChangeGender	
Change the gender of all voices (useful for eSpeak).	69
Crosstales.RTVoice.EditorExtension.ChangeGenderEditor	
Custom editor for the 'ChangeGender'-class.	70
Crosstales.RTVoice.EditorTask.CheckIL2CPP	
Checks if IL2CPP is enabled under standalone.	71
Crosstales.RTVoice.EditorTask.CompileDefines	
Adds the given define symbols to PlayerSettings define symbols.	71
Crosstales.RTVoice.Util.Config	
Configuration for the asset.	71
Crosstales.RTVoice.EditorIntegration.ConfigBase	
Base class for editor windows.	74
Crosstales.RTVoice.EditorTask.ConfigLoader	
Loads the configuration at startup.	75
Crosstales.RTVoice.EditorIntegration.ConfigPreferences	
Unity "Preferences" extension.	75
Crosstales.RTVoice.EditorIntegration.ConfigWindow	
Editor window extension.	76
Crosstales.RTVoice.Util.Constants	
Collected constants of very general utility for the asset.	77
Crosstales.Common.Util.CTPlayerPrefs	
Wrapper for the PlayerPrefs.	83
Crosstales.Common.Util.CTWebClient	
Specialized WebClient.	87
Crosstales.RTVoice.Demo.Dialog	
Simple dialog system with TTS voices.	88
Crosstales.RTVoice.EditorUtil.EditorConfig	
Editor configuration for the asset.	89
Crosstales.RTVoice.EditorUtil.EditorConstants	
Collected constants of very general utility for the asset.	91
Crosstales.RTVoice.EditorUtil.EditorHelper	
Editor helper class.	93
Crosstales.ExtensionMethods	
Various extension methods.	95
Crosstales.Common.Util.FFTAnalyzer	
FFT analyzer for an audio channel.	103
Crosstales.UI.Util.FPSDisplay	
Simple FPS-Counter.	105
Crosstales.RTVoice.EditorUtil.GAApi	
GA-wrapper API.	105
Crosstales.RTVoice.Demo.GUIAudioFilter	
Simple GUI for audio filters.	106
Crosstales.RTVoice.Demo.GUIDialog	
Simple GUI for runtime dialogs with all available OS voices.	107
Crosstales.RTVoice.Demo.GUIMain	
Main GUI component for all demo scenes.	108
Crosstales.RTVoice.Demo.GUIMultiAudioFilter	
Simple GUI for audio filters on multiple objects.	109
Crosstales.RTVoice.Demo.GUIScenes	
Main GUI scene manager for all demo scenes.	110
Crosstales.RTVoice.Demo.GUISpeech	
Simple GUI for runtime TTS with all available OS voices.	111
Crosstales.RTVoice.Util.Helper	
Various helper functions.	112
Crosstales.RTVoice.Demo.Util.iOSController	
Enables MaryTTS on iOS for specific scenes.	115

Crosstales.RTVoice.Provider.IVoiceProvider	
Interface for all voice providers.	116
Crosstales.RTVoice.EditorTask.Launch	
Show the configuration window on the first launch.	121
Crosstales.RTVoice.LiveSpeaker	
Wrapper of the main component from RTVoice for MonoBehaviour-access (like "SendMessage").	121
Crosstales.RTVoice.Tool.Loudspeaker	
Loudspeaker for an AudioSource.	124
Crosstales.RTVoice.EditorExtension.LoudspeakerEditor	
Custom editor for the 'Loudspeaker'-class.	126
Crosstales.RTVoice.Demo.Util.MaterialChanger	
Changes the material of a renderer while an AudioSource is playing.	127
Crosstales.RTVoice.Demo.NativeAudio	
Simple example with native audio for exact timing.	127
Crosstales.RTVoice.Demo.Util.NativeController	
Enables or disable game objects for native mode.	128
Crosstales.Common.EditorTask.NYCheck	
Checks if a 'Happy new year'-message must be displayed.	129
Crosstales.RTVoice.Tool.Paralanguage	
Para-language simulator with audio files.	129
HutongGames.PlayMaker.Actions.Paralanguage	
Paralanguage-action for PlayMaker.	133
Crosstales.RTVoice.EditorExtension.ParalanguageEditor	
Custom editor for the 'Paralanguage'-class.	133
Crosstales.RTVoice.PlayMaker.ParalanguageEditor	
Custom editor for the Paralanguage-action.	134
Crosstales.Common.Util.PlatformController	
Enables or disable game objects for a given platform.	135
Crosstales.RTVoice.Demo.Util.PlatformController	
Enables or disable game objects for a given platform.	136
Crosstales.RTVoice.Demo.PreGeneratedAudio	
Simple example with pre-generated audio for exact timing.	137
Crosstales.Common.Util.RandomColor	
Random color changer.	137
Crosstales.Common.Util.RandomRotator	
Random rotation changer.	139
Crosstales.Common.Util.RandomScaler	
Random scale changer.	141
Crosstales.RTVoice.EditorTask.ReminderCheck	
Reminds the customer to create an UAS review.	142
Crosstales.RTVoice.EditorIntegration.RTVoiceGameObject	
Editor component for the "Hierarchy"-menu.	142
RTVoiceIOSBridge	143
RTVoiceIOSBridge()	144
Crosstales.RTVoice.EditorIntegration.RTVoiceMenu	
Editor component for the "Tools"-menu.	144
Crosstales.UI.Util.ScrollRectHandler	
Changes the sensitivity of ScrollRects under various platforms.	145
Crosstales.RTVoice.Demo.SendMessage	
Simple "SendMessage" example.	145
Crosstales.RTVoice.Model.Sequence	
Model for a sequence.	146
Crosstales.RTVoice.Demo.SequenceCaller	
Simple Sequence caller example.	147
Crosstales.RTVoice.Tool.Sequencer	
Simple sequencer for dialogues.	148
Crosstales.RTVoice.EditorExtension.SequencerEditor	
Custom editor for the 'Sequencer'-class.	150

Crosstales.Common.Util.SerializableDictionary< TKey, TVal > Serializable Dictionary-class for XML.	151
Crosstales.Common.Util.SerializeDeSerialize Serialize and deserialize objects to/from binary files.	152
Crosstales.Common.EditorTask.SetApiLevel Sets the required .NET API level.	153
Crosstales.Common.EditorTask.SetupResources Copies all resources to 'Editor Default Resources'.	154
Crosstales.RTVoice.EditorTask.SetupResources Moves all needed resources to 'Editor Default Resources'.	154
HutongGames.PlayMaker.Actions.Silence Silence-action for PlayMaker.	155
Crosstales.RTVoice.PlayMaker.SilenceEditor Custom editor for the Silence-action.	155
Crosstales.RTVoice.Demo.Simple Simple TTS example.	156
Crosstales.RTVoice.Demo.SimpleNative Simple native TTS example.	157
Crosstales.UI.Social Crosstales social media links.	158
Crosstales.RTVoice.SALSA.Speak	158
HutongGames.PlayMaker.Actions.Speak Speak-action for PlayMaker.	159
Crosstales.RTVoice.SALSA.Speak2D	161
HutongGames.PlayMaker.Actions.SpeakBase Base for Speak-actions in PlayMaker.	162
Crosstales.RTVoice.PlayMaker.SpeakEditor Custom editor for the Speak-action.	164
Crosstales.RTVoice.Speaker Main component of RTVoice.	164
Crosstales.RTVoice.EditorExtension.SpeakerEditor Custom editor for the 'Speaker'-class.	183
Crosstales.RTVoice.SALSA.SpeakSimple	183
HutongGames.PlayMaker.Actions.SpeakUI Speak-action for UI-components in PlayMaker.	184
Crosstales.RTVoice.PlayMaker.SpeakUIEditor Custom editor for the SpeakUI-action.	185
Crosstales.RTVoice.Demo.SpeakWrapper Wrapper for the dynamic speakers.	186
Crosstales.Common.Util.SpectrumVisualizer Simple spectrum visualizer.	186
HutongGames.PlayMaker.Actions.SpeechText SpeechText-action for PlayMaker.	188
Crosstales.RTVoice.Tool.SpeechText Allows to speak and store generated audio.	189
Crosstales.RTVoice.EditorExtension.SpeechTextEditor Custom editor for the 'SpeechText'-class.	192
Crosstales.RTVoice.PlayMaker.SpeechTextEditor Custom editor for the SpeechText-action.	193
Crosstales.UI.StaticManager Static Button Manager.	193
Crosstales.Common.Util.SurviveSceneSwitch Allows any Unity gameobject to survive a scene switch. This is especially useful to keep the music playing while loading a new scene.	194
Crosstales.RTVoice.AWSPolly.Switcher Simple switcher to test the functionality of the AWS Polly provider.	195
Crosstales.Common.Util.TakeScreenshot Take screen shots inside an application.	196

Crosstales.RTVoice.Tool.TextFileSpeaker	
Allows to speak text files.	197
HutongGames.PlayMaker.Actions.TextFileSpeaker	
TextFileSpeaker-action for PlayMaker.	201
Crosstales.RTVoice.EditorExtension.TextFileSpeakerEditor	
Custom editor for the 'TextFileSpeaker'-class.	202
Crosstales.RTVoice.PlayMaker.TextFileSpeakerEditor	
Custom editor for the TextFileSpeaker-action.	203
Crosstales.RTVoice.EditorTask.Tracer	
Gather some tracing data for the asset.	203
Crosstales.RTVoice.UDEA2.UDEAConnector	
Connects UDEA and RT-Voice. Must be placed on a dialogue prefab.	204
Crosstales.RTVoice.UDEA2.UDEAConnectorEditor	
Custom editor for the 'UDEAConnector'-class.	205
Crosstales.RTVoice.UDEA2.UDEAVoiceWrapper	
Wrapper for an UDEA-character to an RT-Voice.	205
Crosstales.UI.UIDrag	
Allow to Drag the Windows arround.	207
Crosstales.UI.UIFocus	
Change the Focus on from a Window.	207
Crosstales.UI.UIHint	
Controls a UI group (hint).	208
Crosstales.UI.UIResize	
Resize a UI element.	210
Crosstales.UI.UIWindowManager	
Change the state of all Window panels.	211
Crosstales.RTVoice.EditorTask.UpdateCheck	
Checks for updates of the asset.	212
Crosstales.RTVoice.Model.Voice	
Model for a voice.	212
Crosstales.RTVoice.Model.VoiceAlias	
Alias for multiple voices on different platforms.	214
Crosstales.RTVoice.Tool.VoiceInitializer	
Allows to initalize voices (useful on Android).	217
Crosstales.RTVoice.EditorExtension.VoiceInitializerEditor	
Custom editor for the 'VoiceInitializer'-class.	218
Crosstales.RTVoice.Provider.VoiceProviderAndroid	
Android voice provider.	219
Crosstales.RTVoice.AWSPolly.VoiceProviderAWS	
AWS Polly voice provider.	221
Crosstales.RTVoice.AWSPolly.VoiceProviderAWSEditor	
Custom editor for the 'VoiceProviderAWS'-class.	223
Crosstales.RTVoice.AWSPolly.VoiceProviderAWSGameObject	
Editor component for for adding the prefabs from 'AWS Polly' in the "Hierarchy"-menu.	224
Crosstales.RTVoice.AWSPolly.VoiceProviderAWSMenu	
Editor component for for adding the prefabs from 'AWS Polly' in the "Tools"-menu.	224
Crosstales.RTVoice.VoiceProviderExample	
Example for a custom voice provider (TTS-system) with all callbacks (only for demonstration - it doesn't do anything). NOTE: please make sure you understand the Wrapper and its variables	224
Crosstales.RTVoice.Provider.VoiceProviderIOS	
iOS voice provider.	226
Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynth	
Klattersynth voice provider.	229
Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynthEditor	
Custom editor for the 'VoiceProviderKlattersynth'-class.	231
Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynthGameObject	
Editor component for for adding the prefabs from 'Klattersynth' in the "Hierarchy"-menu.	232

Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynthMenu	
Editor component for for adding the prefabs from 'Klattersynth' in the "Tools"-menu.	232
Crosstales.RTVoice.Provider.VoiceProviderLinux	
Linux voice provider. Note: needs eSpeak to work: => http://espeak.sourceforge.net/	233
Crosstales.RTVoice.Provider.VoiceProviderMacOS	
MacOS voice provider.	235
Crosstales.RTVoice.Provider.VoiceProviderMary	
MaryTTS voice provider.	237
Crosstales.RTVoice.Provider.VoiceProviderWindows	
Windows voice provider.	239
Crosstales.RTVoice.Provider.VoiceProviderWindowsLegacy	
Windows voice provider (Legacy).	241
Crosstales.RTVoice.Provider.VoiceProviderWSA	
WSA (UWP) voice provider.	243
Crosstales.RTVoice.Util.WavMaster	245
Crosstales.UI.WindowManager	
Manager for a Window.	247
Crosstales.RTVoice.Model.Wrapper	
Wrapper for "Speak"-function calls.	248
Crosstales.Common.Util.XmlHelper	
Helper-class for XML.	252

Chapter 4

Namespace Documentation

4.1 Crosstales Namespace Reference

Namespaces

Classes

- class ExtensionMethods
Various extension methods.

4.2 Crosstales.Common Namespace Reference

Namespaces

4.3 Crosstales.Common.EditorTask Namespace Reference

Classes

- class BaseCompileDefines
Base for adding the given define symbols to PlayerSettings define symbols.
- class BaseSetupResources
Base for copying all resources to 'Editor Default Resources'.
- class NYCheck
Checks if a 'Happy new year'-message must be displayed.
- class SetApiLevel
Sets the required .NET API level.
- class SetupResources
Copies all resources to 'Editor Default Resources'.

4.4 Crosstales.Common.EditorUtil Namespace Reference

Classes

- class BaseEditorHelper
Base for various Editor helper functions.
- class BaseGAApi
Base GA-wrapper API.

4.5 Crosstales.Common.Model Namespace Reference

Namespaces

4.6 Crosstales.Common.Model.Enum Namespace Reference

Enumerations

- enum Platform {
Windows, OSX, Linux, IOS,
Android, WSA, Web, Unsupported,
MaryTTS }
All available platforms.
- enum SampleRate {
_8000Hz = 8000, _11025Hz = 11025, _22050Hz = 22050, _44100Hz = 44100,
_48000Hz = 48000 }
Typical audio sample rates.

4.6.1 Enumeration Type Documentation

4.6.1.1 enum Crosstales.Common.Model.Enum.Platform [strong]

All available platforms.

4.6.1.2 enum Crosstales.Common.Model.Enum.SampleRate [strong]

Typical audio sample rates.

4.7 Crosstales.Common.Util Namespace Reference

Classes

- class BackgroundController
Enables or disable game objects on Android or iOS in the background.
- class BaseConstants
Base for collected constants of very general utility for the asset.
- class BaseHelper
Base for various helper functions.
- class CTPlayerPrefs
Wrapper for the PlayerPrefs.
- class CTWebClient
Specialized WebClient.
- class FFTAnalyzer
FFT analyzer for an audio channel.
- class PlatformController
Enables or disable game objects for a given platform.
- class RandomColor
Random color changer.
- class RandomRotator
Random rotation changer.
- class RandomScaler
Random scale changer.
- class SerializableDictionary
Serializable Dictionary-class for XML.
- class SerializeDeSerialize
Serialize and deserialize objects to/from binary files.
- class SpectrumVisualizer
Simple spectrum visualizer.
- class SurviveSceneSwitch
Allows any Unity gameobject to survive a scene switch. This is especially useful to keep the music playing while loading a new scene.
- class TakeScreenshot
Take screen shots inside an application.
- class XmlHelper
Helper-class for XML.

4.8 Crosstales.RTVoice Namespace Reference

Namespaces

- namespace Util
WAV utility for recording and audio playback functions in Unity.

Classes

- class LiveSpeaker
Wrapper of the main component from RTVoice for MonoBehaviour-access (like "SendMessage").
- class Speaker
Main component of RTVoice.
- class VoiceProviderExample
*Example for a custom voice provider (TTS-system) with all callbacks (only for demonstration - it doesn't do anything).
NOTE: please make sure you understand the Wrapper and its variables*

Functions

- delegate void **VoicesReady** ()
- delegate void **SpeakStart** (Model.Wrapper wrapper)
- delegate void **SpeakComplete** (Model.Wrapper wrapper)
- delegate void **SpeakCurrentWord** (Model.Wrapper wrapper, string[] speechTextArray, int wordIndex)
- delegate void **SpeakCurrentPhoneme** (Model.Wrapper wrapper, string phoneme)
- delegate void **SpeakCurrentViseme** (Model.Wrapper wrapper, string viseme)
- delegate void **SpeakAudioGenerationStart** (Model.Wrapper wrapper)
- delegate void **SpeakAudioGenerationComplete** (Model.Wrapper wrapper)
- delegate void **ErrorInfo** (Model.Wrapper wrapper, string info)
- delegate void **ProviderChange** (string provider)
- delegate void **AudioFileGeneratorStart** ()
- delegate void **AudioFileGeneratorComplete** ()
- delegate void **ParalanguageStart** ()
- delegate void **ParalanguageComplete** ()
- delegate void **SpeechTextStart** ()
- delegate void **SpeechTextComplete** ()

4.9 Crosstales.RTVoice.AWSPolly Namespace Reference

Classes

- class Switcher
Simple switcher to test the functionality of the AWS Polly provider.
- class VoiceProviderAWS
AWS Polly voice provider.
- class VoiceProviderAWSEditor
Custom editor for the 'VoiceProviderAWS'-class.
- class VoiceProviderAWSGameObject
Editor component for for adding the prefabs from 'AWS Polly' in the "Hierarchy"-menu.
- class VoiceProviderAWSMenu
Editor component for for adding the prefabs from 'AWS Polly' in the "Tools"-menu.

Enumerations

- enum Endpoint {
 APNortheast1, APNortheast2, APSouth1, APSoutheast1,
 APSoutheast2, CACentral1, CNNorth1, EUCentral1,
 EUWest1, EUWest2, SAEast1, USEast1,
 USEast2, USGovCloudWest1, USWest1, USWest2 }
All available AWS Polly endpoints.

4.9.1 Enumeration Type Documentation

4.9.1.1 enum Crosstales.RTVoice.AWSPolly.Endpoint [strong]

All available AWS Polly endpoints.

4.10 Crosstales.RTVoice.Demo Namespace Reference

Namespaces

Classes

- class Dialog
Simple dialog system with TTS voices.
- class GUIAudioFilter
Simple GUI for audio filters.
- class GUIDialog
Simple GUI for runtime dialogs with all available OS voices.
- class GUIMain
Main GUI component for all demo scenes.
- class GUIMultiAudioFilter
Simple GUI for audio filters on multiple objects.
- class GUIScenes
Main GUI scene manager for all demo scenes.
- class GUISpeech
Simple GUI for runtime TTS with all available OS voices.
- class NativeAudio
Simple example with native audio for exact timing.
- class PreGeneratedAudio
Simple example with pre-generated audio for exact timing.
- class SendMessage
Simple "SendMessage" example.
- class SequenceCaller
Simple Sequence caller example.
- class Simple
Simple TTS example.
- class SimpleNative
Simple native TTS example.
- class SpeakWrapper
Wrapper for the dynamic speakers.

4.11 Crosstales.RTVoice.Demo.Util Namespace Reference

Classes

- class iOSController
Enables MaryTTS on iOS for specific scenes.
- class MaterialChanger
Changes the material of a renderer while an AudioSource is playing.
- class NativeController
Enables or disable game objects for native mode.
- class PlatformController
Enables or disable game objects for a given platform.

4.12 Crosstales.RTVoice.EditorExtension Namespace Reference

Classes

- class AudioFileGeneratorEditor
Custom editor for the 'SpeechText'-class.
- class ChangeGenderEditor
Custom editor for the 'ChangeGender'-class.
- class LoudspeakerEditor
Custom editor for the 'Loudspeaker'-class.
- class ParalanguageEditor
Custom editor for the 'Paralanguage'-class.
- class SequencerEditor
Custom editor for the 'Sequencer'-class.
- class SpeakerEditor
Custom editor for the 'Speaker'-class.
- class SpeechTextEditor
Custom editor for the 'SpeechText'-class.
- class TextFileSpeakerEditor
Custom editor for the 'TextFileSpeaker'-class.
- class VoiceInitalizerEditor
Custom editor for the 'VoiceInitalizer'-class.

4.13 Crosstales.RTVoice.EditorIntegration Namespace Reference

Classes

- class ConfigBase
Base class for editor windows.
- class ConfigPreferences
Unity "Preferences" extension.
- class ConfigWindow
Editor window extension.
- class RTVoiceGameObject
Editor component for the "Hierarchy"-menu.
- class RTVoiceMenu
Editor component for the "Tools"-menu.

4.14 Crosstales.RTVoice.EditorTask Namespace Reference

Classes

- class AutoInitialize
Automatically adds the necessary RTVoice-prefabs to the current scene.
- class CheckIL2CPP
Checks if IL2CPP is enabled under standalone.
- class CompileDefines
Adds the given define symbols to PlayerSettings define symbols.
- class ConfigLoader
Loads the configuration at startup.
- class Launch
Show the configuration window on the first launch.
- class ReminderCheck
Reminds the customer to create an UAS review.
- class SetupResources
Moves all needed resources to 'Editor Default Resources'.
- class Tracer
Gather some tracing data for the asset.
- class UpdateCheck
Checks for updates of the asset.

Enumerations

- enum UpdateStatus {
 NOT_CHECKED, NO_UPDATE, UPDATE, UPDATE_PRO,
 UPDATE_VERSION, DEPRECATED, V2019 }
All possible update stati.

4.14.1 Enumeration Type Documentation

4.14.1.1 enum **Crosstales.RTVoice.EditorTask.UpdateStatus** [strong]

All possible update stati.

4.15 Crosstales.RTVoice.EditorUtil Namespace Reference

Classes

- class EditorConfig
Editor configuration for the asset.
- class EditorConstants
Collected constants of very general utility for the asset.
- class EditorHelper
Editor helper class.
- class GAApi
GA-wrapper API.

4.16 Crosstales.RTVoice.Klattersynth Namespace Reference

Classes

- class VoiceProviderKlattersynth
Klattersynth voice provider.
- class VoiceProviderKlattersynthEditor
Custom editor for the 'VoiceProviderKlattersynth'-class.
- class VoiceProviderKlattersynthGameObject
Editor component for for adding the prefabs from 'Klattersynth' in the "Hierarchy"-menu.
- class VoiceProviderKlattersynthMenu
Editor component for for adding the prefabs from 'Klattersynth' in the "Tools"-menu.

4.17 Crosstales.RTVoice.Model Namespace Reference

Namespaces

Classes

- class Sequence
Model for a sequence.
- class Voice
Model for a voice.
- class VoiceAlias
Alias for multiple voices on different platforms.
- class Wrapper
Wrapper for "Speak"-function calls.

4.18 Crosstales.RTVoice.Model.Enum Namespace Reference

Enumerations

- enum ESpeakModifiers {
none, m1, m2, m3,
m4, m5, m6, f1,
f2, f3, f4, croak,
whisper }
The modifiers for eSpeak voices (m1-m6 = male, f1-f4 = female).
- enum Gender { **MALE, FEMALE, UNKNOWN** }
The genders for voices.
- enum MaryTTSType { **RAWMARYXML, EMOTIONML, SSML, TEXT** }
The different MaryTTS input types.
- enum ProviderType {
Windows, macOS, Android, iOS,
WSA, MaryTTS, Linux }
Available provider types.
- enum SpeakMode { **Speak, SpeakNative** }
Available Speak-modes.

4.18.1 Enumeration Type Documentation

4.18.1.1 enum `Crosstales.RTVoice.Model.Enum.ESpeakModifiers` `[strong]`

The modifiers for eSpeak voices (m1-m6 = male, f1-f4 = female).

4.18.1.2 enum `Crosstales.RTVoice.Model.Enum.Gender` `[strong]`

The genders for voices.

4.18.1.3 enum `Crosstales.RTVoice.Model.Enum.MaryTTSType` `[strong]`

The different MaryTTS input types.

4.18.1.4 enum `Crosstales.RTVoice.Model.Enum.ProviderType` `[strong]`

Available provider types.

4.18.1.5 enum `Crosstales.RTVoice.Model.Enum.SpeakMode` `[strong]`

Available Speak-modes.

4.19 Crosstales.RTVoice.PlayMaker Namespace Reference

Classes

- class `AudioFileGeneratorEditor`
Custom editor for the AudioFileGenerator-action.
- class `BaseRTVEditor`
Base class for RT-Voice custom editors in PlayMaker.
- class `ParalanguageEditor`
Custom editor for the Paralanguage-action.
- class `SilenceEditor`
Custom editor for the Silence-action.
- class `SpeakEditor`
Custom editor for the Speak-action.
- class `SpeakUIEditor`
Custom editor for the SpeakUI-action.
- class `SpeechTextEditor`
Custom editor for the SpeechText-action.
- class `TextFileSpeakerEditor`
Custom editor for the TextFileSpeaker-action.

4.20 Crosstales.RTVoice.Provider Namespace Reference

Classes

- class BaseCustomVoiceProvider
Base class for custom voice providers (TTS-systems).
- class BaseVoiceProvider
Base class for voice providers.
- interface IVoiceProvider
Interface for all voice providers.
- class VoiceProviderAndroid
Android voice provider.
- class VoiceProviderIOS
iOS voice provider.
- class VoiceProviderLinux
Linux voice provider. Note: needs eSpeak to work: => <http://espeak.sourceforge.net/>
- class VoiceProviderMacOS
MacOS voice provider.
- class VoiceProviderMary
MaryTTS voice provider.
- class VoiceProviderWindows
Windows voice provider.
- class VoiceProviderWindowsLegacy
Windows voice provider (Legacy).
- class VoiceProviderWSA
WSA (UWP) voice provider.

4.21 Crosstales.RTVoice.SALSA Namespace Reference

Classes

- class Bots
This is class for conversations between two SALSA-Bots.
- class Speak
- class Speak2D
- class SpeakSimple

4.22 Crosstales.RTVoice.Tool Namespace Reference

Classes

- class AudioFileGenerator
Process files with configured speeches.
- class ChangeGender
Change the gender of all voices (useful for eSpeak).
- class Loudspeaker
Loudspeaker for an AudioSource.

- class Paralanguage
Para-language simulator with audio files.
- class Sequencer
Simple sequencer for dialogues.
- class SpeechText
Allows to speak and store generated audio.
- class TextFileSpeaker
Allows to speak text files.
- class VoiceInitalizer
Allows to initalize voices (useful on Android).

4.23 Crosstales.RTVoice.UDEA2 Namespace Reference

Classes

- class UDEAConnector
Connects UDEA and RT-Voice. Must be placed on a dialogue prefab.
- class UDEAConnectorEditor
Custom editor for the 'UDEAConnector'-class.
- class UDEAVoiceWrapper
Wrapper for an UDEA-character to an RT-Voice.

4.24 Crosstales.RTVoice.Util Namespace Reference

WAV utility for recording and audio playback functions in Unity.

Classes

- class Config
Configuration for the asset.
- class Constants
Collected constants of very general utility for the asset.
- class Helper
Various helper functions.
- class WavMaster

4.24.1 Detailed Description

WAV utility for recording and audio playback functions in Unity.

- Use "ToAudioClip" method for loading wav file / bytes. Loads .wav (PCM uncompressed) files at 8,16,24 and 32 bits and converts data to Unity's AudioClip.
- Use "FromAudioClip" method for saving wav file / bytes. Converts an AudioClip's float data into wav byte array at 16 bit.

Partially based on: <https://github.com/deadlyfingers/UnityWav>

4.25 Crosstales.UI Namespace Reference

Namespaces

Classes

- class Social
Crosstales social media links.
- class StaticManager
Static Button Manager.
- class UIDrag
Allow to Drag the Windows around.
- class UIFocus
Change the Focus on from a Window.
- class UIHint
Controls a UI group (hint).
- class UIResize
Resize a UI element.
- class UIWindowManager
Change the state of all Window panels.
- class WindowManager
Manager for a Window.

4.26 Crosstales.UI.Util Namespace Reference

Classes

- class AudioFilterController
Controller for audio filters.
- class AudioSourceController
Controller for AudioSources.
- class FPSDisplay
Simple FPS-Counter.
- class ScrollRectHandler
Changes the sensitivity of ScrollRects under various platforms.

4.27 HutongGames Namespace Reference

Namespaces

4.28 HutongGames.PlayMaker Namespace Reference

Namespaces

4.29 HutongGames.PlayMaker.Actions Namespace Reference

Classes

- class AudioFileGenerator

- AudioFileGenerator-action for PlayMaker.*
- class BaseRTVAction
 - Base class for RT-Voice actions in PlayMaker.*
- class Paralanguage
 - Paralanguage-action for PlayMaker.*
- class Silence
 - Silence-action for PlayMaker.*
- class Speak
 - Speak-action for PlayMaker.*
- class SpeakBase
 - Base for Speak-actions in PlayMaker.*
- class SpeakUI
 - Speak-action for UI-components in PlayMaker.*
- class SpeechText
 - SpeechText-action for PlayMaker.*
- class TextFileSpeaker
 - TextFileSpeaker-action for PlayMaker.*


Chapter 5

Class Documentation

5.1 HutongGames.PlayMaker.Actions.AudioFileGenerator Class Reference

AudioFileGenerator-action for PlayMaker.

Inheritance diagram for HutongGames.PlayMaker.Actions.AudioFileGenerator:



Public Member Functions

- override void **OnEnter** ()
- override void **OnExit** ()

Public Attributes

- Crosstales.RTVoice.Tool.AudioFileGenerator Obj
Add a AudioFileGenerator (default: first object in scene).

5.1.1 Detailed Description

AudioFileGenerator-action for PlayMaker.

5.1.2 Member Data Documentation

5.1.2.1 Crosstales.RTVoice.Tool.AudioFileGenerator HutongGames.PlayMaker.Actions.AudioFileGenerator.Obj

Add a AudioFileGenerator (default: first object in scene).


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/PlayMaker/Scripts/AudioFileGenerator.cs

5.2 Crosstales.RTVoice.Tool.AudioFileGenerator Class Reference

Process files with configured speeches.

Inheritance diagram for Crosstales.RTVoice.Tool.AudioFileGenerator:



Public Member Functions

- void **OnEnable** ()
- void **OnDisable** ()
- void **OnValidate** ()
- void **Generate** ()
Generate the audio files from the text files.
- IEnumerator **generate** ()
- void **Normalize** (string inputFile)
- float **GetMaxPeak** (string inputFile)

Public Attributes

- TextAsset[] **TextFiles**
Text files to generate.
- bool **FileInsideAssets** = true
Are the specified file paths inside the Assets-folder (current project)? If this option is enabled, it prefixes the path with 'Application.dataPath' (default: true).
- bool **isNormalize** = false
- bool **GenerateOnStart** = false
Enable generating of the texts on start (default: false).

Properties

- **AudioFileGeneratorStart** `OnAudioFileGeneratorStart`
An event triggered whenever a `AudioFileGenerator` 'Generate' is started.
- **AudioFileGeneratorComplete** `OnAudioFileGeneratorComplete`
An event triggered whenever a `AudioFileGenerator` 'Generate' is completed.

5.2.1 Detailed Description

Process files with configured speeches.

5.2.2 Member Function Documentation

5.2.2.1 `void Crosstales.RTVoice.Tool.AudioFileGenerator.Generate ()`

Generate the audio files from the text files.

5.2.3 Member Data Documentation

5.2.3.1 `bool Crosstales.RTVoice.Tool.AudioFileGenerator.FileInsideAssets = true`

Are the specified file paths inside the Assets-folder (current project)? If this option is enabled, it prefixes the path with 'Application.dataPath' (default: true).

5.2.3.2 `bool Crosstales.RTVoice.Tool.AudioFileGenerator.GenerateOnStart = false`

Enable generating of the texts on start (default: false).

5.2.3.3 `TextAsset [] Crosstales.RTVoice.Tool.AudioFileGenerator.TextFiles`

Text files to generate.

5.2.4 Property Documentation

5.2.4.1 `AudioFileGeneratorComplete` `Crosstales.RTVoice.Tool.AudioFileGenerator.OnAudioFileGeneratorComplete` `[add]`, `[remove]`

An event triggered whenever a `AudioFileGenerator` 'Generate' is completed.

5.2.4.2 AudioFileGeneratorStart Crosstales.RTVoice.Tool.AudioFileGenerator.OnAudioFileGeneratorStart [add], [remove]

An event triggered whenever a AudioFileGenerator 'Generate' is started.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Tool/AudioFileGenerator.cs

5.3 Crosstales.RTVoice.EditorExtension.AudioFileGeneratorEditor Class Reference

Custom editor for the 'SpeechText'-class.

Inheritance diagram for Crosstales.RTVoice.EditorExtension.AudioFileGeneratorEditor:



Public Member Functions

- void **OnEnable** ()
- override void **OnInspectorGUI** ()

5.3.1 Detailed Description

Custom editor for the 'SpeechText'-class.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Editor/Extension/AudioFileGeneratorEditor.cs

5.4 Crosstales.RTVoice.PlayMaker.AudioFileGeneratorEditor Class Reference

Custom editor for the AudioFileGenerator-action.

Inheritance diagram for Crosstales.RTVoice.PlayMaker.AudioFileGeneratorEditor:



Additional Inherited Members

5.4.1 Detailed Description

Custom editor for the AudioFileGenerator-action.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/PlayMaker/Editor/AudioFileGeneratorEditor.cs

5.5 Crosstales.UI.Util.AudioFilterController Class Reference

Controller for audio filters.

Inheritance diagram for Crosstales.UI.Util.AudioFilterController:



Public Member Functions

- void **Start** ()
- void **Update** ()
- void **FindAllAudioFilters** ()
Finds all audio filters in the scene.
- void **ResetAudioFilters** ()
Resets all audio filters.
- void **ReverbFilterDropdownChanged** (System.Int32 index)
- void **ChorusFilterEnabled** (bool enabled)
- void **EchoFilterEnabled** (bool enabled)
- void **DistortionFilterEnabled** (bool enabled)
- void **DistortionFilterChanged** (float value)
- void **LowPassFilterEnabled** (bool enabled)
- void **LowPassFilterChanged** (float value)
- void **HighPassFilterEnabled** (bool enabled)
- void **HighPassFilterChanged** (float value)

Public Attributes

- bool **FindAllAudioFiltersOnStart** = true
Searches for all audio filters in the whole scene (default: true).
- AudioReverbFilter[] **ReverbFilters**
- AudioChorusFilter[] **ChorusFilters**
- AudioEchoFilter[] **EchoFilters**
- AudioDistortionFilter[] **DistortionFilters**
- AudioLowPassFilter[] **LowPassFilters**
- AudioHighPassFilter[] **HighPassFilters**
- bool **ResetAudioFiltersOnStart** = true
- bool **ChorusFilter** = false
- bool **EchoFilter** = false
- bool **DistortionFilter** = false
- float **DistortionFilterValue** = 0.5f
- bool **LowpassFilter** = false
- float **LowpassFilterValue** = 5000f
- bool **HighpassFilter** = false
- float **HighpassFilterValue** = 5000f
- Dropdown **ReverbFilterDropdown**
- Text **DistortionText**
- Text **LowpassText**
- Text **HighpassText**

5.5.1 Detailed Description

Controller for audio filters.

5.5.2 Member Function Documentation

5.5.2.1 void Crosstales.UI.Util.AudioFilterController.FindAllAudioFilters ()

Finds all audio filters in the scene.

5.5.2.2 void Crosstales.UI.Util.AudioFilterController.ResetAudioFilters ()

Resets all audio filters.

5.5.3 Member Data Documentation

5.5.3.1 bool Crosstales.UI.Util.AudioFilterController.FindAllAudioFiltersOnStart = true

Searches for all audio filters in the whole scene (default: true).


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/UI/Scripts/Util/AudioFilterController.cs

5.6 Crosstales.UI.Util.AudioSourceController Class Reference

Controller for AudioSources.

Inheritance diagram for Crosstales.UI.Util.AudioSourceController:



Public Member Functions

- void **Update** ()
- void FindAllAudioSources ()
Finds all audio sources in the scene.
- void ResetAllAudioSources ()
Resets all audio sources.
- void **MuteEnabled** (bool enabled)
- void **LoopEnabled** (bool enabled)
- void **VolumeChanged** (float value)
- void **PitchChanged** (float value)
- void **StereoPanChanged** (float value)

Public Attributes

- bool FindAllAudioSourcesOnStart = true
Searches for all AudioSource in the whole scene (default: true).
- AudioSource[] AudioSources
Active controlled AudioSources.
- bool ResetAudioSourcesOnStart = true
Resets all active AudioSources (default: true).
- bool Mute = false
Mute on/off (default: false).
- bool Loop = false
Loop on/off (default: false).
- float Volume = 1f
Volume of the audio (default: 1)
- float Pitch = 1f
Pitch of the audio (default: 1).
- float StereoPan = 0f
Stereo pan of the audio (default: 0).
- Text **VolumeText**
- Text **PitchText**
- Text **StereoPanText**

5.6.1 Detailed Description

Controller for AudioSources.

5.6.2 Member Function Documentation

5.6.2.1 void Crosstales.UI.Util.AudioSourceController.FindAllAudioSources ()

Finds all audio sources in the scene.

5.6.2.2 void Crosstales.UI.Util.AudioSourceController.ResetAllAudioSources ()

Resets all audio sources.

5.6.3 Member Data Documentation

5.6.3.1 AudioSource [] Crosstales.UI.Util.AudioSourceController.AudioSources

Active controlled AudioSources.

5.6.3.2 bool Crosstales.UI.Util.AudioSourceController.FindAllAudioSourcesOnStart = true

Searches for all AudioSource in the whole scene (default: true).

5.6.3.3 bool Crosstales.UI.Util.AudioSourceController.Loop = false

Loop on/off (default: false).

5.6.3.4 bool Crosstales.UI.Util.AudioSourceController.Mute = false

Mute on/off (default: false).

5.6.3.5 float Crosstales.UI.Util.AudioSourceController.Pitch = 1f

Pitch of the audio (default: 1).

5.6.3.6 bool Crosstales.UI.Util.AudioSourceController.ResetAudioSourcesOnStart = true

Resets all active AudioSources (default: true).

5.6.3.7 float Crosstales.UI.Util.AudioSourceController.StereoPan = 0f

Stereo pan of the audio (default: 0).

5.6.3.8 float Crosstales.UI.Util.AudioSourceController.Volume = 1f

Volume of the audio (default: 1)

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ UI/Scripts/Util/AudioSourceController.cs

5.7 Crosstales.RTVoice.EditorTask.AutoInitalize Class Reference

Automatically adds the neccessary RTVoice-prefabs to the current scene.

5.7.1 Detailed Description

Automatically adds the neccessary RTVoice-prefabs to the current scene.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Editor/Task/AutoInitalize.cs

5.8 Crosstales.Common.Util.BackgroundController Class Reference

Enables or disable game objects on Android or iOS in the background.

Inheritance diagram for Crosstales.Common.Util.BackgroundController:



Public Member Functions

- void **Start** ()

Public Attributes

- GameObject[] Objects

Selected objects to disable in the background for the controller.

5.8.1 Detailed Description

Enables or disable game objects on Android or iOS in the background.

5.8.2 Member Data Documentation

5.8.2.1 GameObject [] Crosstales.Common.Util.BackgroundController.Objects

Selected objects to disable in the background for the controller.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ Scripts/Util/BackgroundController.cs

5.9 Crosstales.Common.EditorTask.BaseCompileDefines Class Reference

Base for adding the given define symbols to PlayerSettings define symbols.

Inheritance diagram for Crosstales.Common.EditorTask.BaseCompileDefines:



Static Protected Member Functions

- static void **setCompileDefines** (string[] symbols)

5.9.1 Detailed Description

Base for adding the given define symbols to PlayerSettings define symbols.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ Editor/Task/BaseCompileDefines.cs

5.10 Crosstales.Common.Util.BaseConstants Class Reference

Base for collected constants of very general utility for the asset.

Inheritance diagram for Crosstales.Common.Util.BaseConstants:



Public Attributes

- const string ASSET_AUTHOR = "crosstales LLC"
Author of the asset.
- const string ASSET_AUTHOR_URL = "https://www.crosstales.com"
URL of the asset author.
- const string ASSET_CT_URL = "https://goo.gl/qwtXyb"
URL of the crosstales assets in UAS.
- const string ASSET_SOCIAL_DISCORD = "https://discord.gg/ZbZ2sh4"
URL of the crosstales Discord-channel.
- const string ASSET_SOCIAL_FACEBOOK = "https://www.facebook.com/crosstales/"
URL of the crosstales Facebook-profile.
- const string ASSET_SOCIAL_TWITTER = "https://twitter.com/crosstales"
URL of the crosstales Twitter-profile.
- const string ASSET_SOCIAL_YOUTUBE = "https://www.youtube.com/c/Crosstales"
URL of the crosstales Youtube-profile.
- const string ASSET_SOCIAL_LINKEDIN = "https://www.linkedin.com/company/crosstales"
URL of the crosstales LinkedIn-profile.
- const string ASSET_SOCIAL_XING = "https://www.xing.com/companies/crosstales"
URL of the crosstales XING-profile.
- const string ASSET_3P_PLAYMAKER = "https://www.assetstore.unity3d.com/#!/content/368?aid=1011INGT"
URL of the 3rd party asset "PlayMaker".
- const string ASSET_BWF = "https://www.assetstore.unity3d.com/#!/content/26255?aid=1011INGT"
URL of the "Badword Filter" asset.
- const string ASSET_DJ = "https://www.assetstore.unity3d.com/#!/content/41993?aid=1011INGT"
URL of the "DJ" asset.
- const string ASSET_FB = "https://www.assetstore.unity3d.com/#!/content/98713?aid=1011INGT"
URL of the "File Browser" asset.
- const string ASSET_OC = "https://www.assetstore.unity3d.com/#!/content/74688?aid=1011INGT"
URL of the "Online Check" asset.
- const string ASSET_RADIO = "https://www.assetstore.unity3d.com/#!/content/32034?aid=1011INGT"
URL of the "Radio" asset.
- const string ASSET_RTV = "https://www.assetstore.unity3d.com/#!/content/41068?aid=1011INGT"
URL of the "RT-Voice" asset.
- const string ASSET_TB = "https://www.assetstore.unity3d.com/#!/content/98711?aid=1011INGT"
URL of the "Turbo Backup" asset.
- const string ASSET_TPB = "https://www.assetstore.unity3d.com/#!/content/98714?aid=1011INGT"

- URL of the "Turbo Builder" asset.*
- const string ASSET_TPS = "https://www.assetstore.unity3d.com/#!/content/60040?aid=1011INGT"
- URL of the "Turbo Switch" asset.*
- const string ASSET_TR = "https://www.assetstore.unity3d.com/#!/content/61617?aid=1011INGT"
- URL of the "True Random" asset.*
- const int FACTOR_KB = 1024
- Factor for kilo bytes.*
- const int FACTOR_MB = FACTOR_KB * 1024
- Factor for mega bytes.*
- const int FACTOR_GB = FACTOR_MB * 1024
- Factor for giga bytes.*
- const float FLOAT_32768 = 32768f
- Float value of 32768.*
- const string FORMAT_TWO_DECIMAL_PLACES = "0.00"
- ToString for two decimal places.*
- const string FORMAT_NO_DECIMAL_PLACES = "0"
- ToString for no decimal places.*
- const string FORMAT_PERCENT = "0%"
- ToString for percent.*
- const bool **DEFAULT_DEBUG** = false
- const string PATH_DELIMITER_WINDOWS = @"\"
- Path delimiter for Windows.*
- const string PATH_DELIMITER_UNIX = "/"
- Path delimiter for Unix.*

Static Public Attributes

- static bool DEV_DEBUG = false
- Development debug logging for the asset.*
- static string **TEXT_TOSTRING_START** = "{"
- static string **TEXT_TOSTRING_END** = "}"
- static string **TEXT_TOSTRING_DELIMITER** = ",", "
- static string **TEXT_TOSTRING_DELIMITER_END** = ""
- static string **PREFIX_HTTP** = "http://"
- static string **PREFIX_HTTPS** = "https://"
- static int PROCESS_KILL_TIME = 5000
- Kill processes after 5000 milliseconds.*
- static bool SHOW_BWF_BANNER = true
- Show the BWF banner.*
- static bool SHOW_DJ_BANNER = true
- Show the DJ banner.*
- static bool SHOW_FB_BANNER = true
- Show the FB banner.*
- static bool SHOW_OC_BANNER = true
- Show the OC banner.*
- static bool SHOW_RADIO_BANNER = true
- Show the Radio banner.*
- static bool SHOW_RTV_BANNER = true
- Show the RTV banner.*
- static bool SHOW_TB_BANNER = true

Show the TB banner.

- static bool SHOW_TP_BANNER = false

Show the TPB banner.

- static bool SHOW_TPS_BANNER = true

Show the TPS banner.

- static bool SHOW_TR_BANNER = true

Show the TR banner.

Properties

- static string PREFIX_FILE [get]

URL prefix for files.

- static string APPLICATION_PATH [get]

Application path.

5.10.1 Detailed Description

Base for collected constants of very general utility for the asset.

5.10.2 Member Data Documentation

- 5.10.2.1 `const string Crosstales.Common.Util.BaseConstants.ASSET_3P_PLAYMAKER = "https://www.assetstore.unity3d.com/#!/content/368?aid=1011INGT"`

URL of the 3rd party asset "PlayMaker".

- 5.10.2.2 `const string Crosstales.Common.Util.BaseConstants.ASSET_AUTHOR = "crosstales LLC"`

Author of the asset.

- 5.10.2.3 `const string Crosstales.Common.Util.BaseConstants.ASSET_AUTHOR_URL = "https://www.crosstales.com"`

URL of the asset author.

- 5.10.2.4 `const string Crosstales.Common.Util.BaseConstants.ASSET_BWF = "https://www.assetstore.unity3d.com/#!/content/26255?aid=1011INGT"`

URL of the "Badword Filter" asset.

- 5.10.2.5 `const string Crosstales.Common.Util.BaseConstants.ASSET_CT_URL = "https://goo.gl/qwtXyb"`

URL of the crosstales assets in UAS.

5.10.2.6 `const string Crosstales.Common.Util.BaseConstants.ASSET_DJ = "https://www.assetstore.unity3d.com/#!/content/41993?aid=1011INGT"`

URL of the "DJ" asset.

5.10.2.7 `const string Crosstales.Common.Util.BaseConstants.ASSET_FB = "https://www.assetstore.unity3d.com/#!/content/98713?aid=1011INGT"`

URL of the "File Browser" asset.

5.10.2.8 `const string Crosstales.Common.Util.BaseConstants.ASSET_OC = "https://www.assetstore.unity3d.com/#!/content/74688?aid=1011INGT"`

URL of the "Online Check" asset.

5.10.2.9 `const string Crosstales.Common.Util.BaseConstants.ASSET_RADIO = "https://www.assetstore.unity3d.com/#!/content/32034?aid=1011INGT"`

URL of the "Radio" asset.

5.10.2.10 `const string Crosstales.Common.Util.BaseConstants.ASSET_RTV = "https://www.assetstore.unity3d.com/#!/content/41068?aid=1011INGT"`

URL of the "RT-Voice" asset.

5.10.2.11 `const string Crosstales.Common.Util.BaseConstants.ASSET_SOCIAL_DISCORD = "https://discord.gg/ZbZ2sh4"`

URL of the crosstales Discord-channel.

5.10.2.12 `const string Crosstales.Common.Util.BaseConstants.ASSET_SOCIAL_FACEBOOK = "https://www.facebook.com/crosstales/"`

URL of the crosstales Facebook-profile.

5.10.2.13 `const string Crosstales.Common.Util.BaseConstants.ASSET_SOCIAL_LINKEDIN = "https://www.linkedin.com/company/crosstales"`

URL of the crosstales LinkedIn-profile.

5.10.2.14 `const string Crosstales.Common.Util.BaseConstants.ASSET_SOCIAL_TWITTER = "https://twitter.com/crosstales"`

URL of the crosstales Twitter-profile.

5.10.2.15 `const string Crosstales.Common.Util.BaseConstants.ASSET_SOCIAL_XING = "https://www.xing.↵
com/companies/crosstales"`

URL of the crosstales XING-profile.

5.10.2.16 `const string Crosstales.Common.Util.BaseConstants.ASSET_SOCIAL_YOUTUBE =
"https://www.youtube.com/c/Crosstales"`

URL of the crosstales Youtube-profile.

5.10.2.17 `const string Crosstales.Common.Util.BaseConstants.ASSET_TB = "https://www.assetstore.unity3d.↵
com/#!/content/98711?aid=1011INGT"`

URL of the "Turbo Backup" asset.

5.10.2.18 `const string Crosstales.Common.Util.BaseConstants.ASSET_TPB = "https://www.assetstore.unity3d.↵
com/#!/content/98714?aid=1011INGT"`

URL of the "Turbo Builder" asset.

5.10.2.19 `const string Crosstales.Common.Util.BaseConstants.ASSET_TPS = "https://www.assetstore.unity3d.↵
com/#!/content/60040?aid=1011INGT"`

URL of the "Turbo Switch" asset.

5.10.2.20 `const string Crosstales.Common.Util.BaseConstants.ASSET_TR = "https://www.assetstore.unity3d.↵
com/#!/content/61617?aid=1011INGT"`

URL of the "True Random" asset.

5.10.2.21 `bool Crosstales.Common.Util.BaseConstants.DEV_DEBUG = false [static]`

Development debug logging for the asset.

5.10.2.22 `const int Crosstales.Common.Util.BaseConstants.FACTOR_GB = FACTOR_MB * 1024`

Factor for giga bytes.

5.10.2.23 `const int Crosstales.Common.Util.BaseConstants.FACTOR_KB = 1024`

Factor for kilo bytes.

5.10.2.24 `const int Crosstales.Common.Util.BaseConstants.FACTOR_MB = FACTOR_KB * 1024`

Factor for mega bytes.

5.10.2.25 `const float Crosstales.Common.Util.BaseConstants.FLOAT_32768 = 32768f`

Float value of 32768.

5.10.2.26 `const string Crosstales.Common.Util.BaseConstants.FORMAT_NO_DECIMAL_PLACES = "0"`

ToString for no decimal places.

5.10.2.27 `const string Crosstales.Common.Util.BaseConstants.FORMAT_PERCENT = "0%"`

ToString for percent.

5.10.2.28 `const string Crosstales.Common.Util.BaseConstants.FORMAT_TWO_DECIMAL_PLACES = "0.00"`

ToString for two decimal places.

5.10.2.29 `const string Crosstales.Common.Util.BaseConstants.PATH_DELIMITER_UNIX = "/"`

Path delimiter for Unix.

5.10.2.30 `const string Crosstales.Common.Util.BaseConstants.PATH_DELIMITER_WINDOWS = @"\"`

Path delimiter for Windows.

5.10.2.31 `int Crosstales.Common.Util.BaseConstants.PROCESS_KILL_TIME = 5000` `[static]`

Kill processes after 5000 milliseconds.

5.10.2.32 `bool Crosstales.Common.Util.BaseConstants.SHOW_BWF_BANNER = true` `[static]`

Show the BWF banner.

5.10.2.33 `bool Crosstales.Common.Util.BaseConstants.SHOW_DJ_BANNER = true` `[static]`

Show the DJ banner.

5.10.2.34 `bool Crosstales.Common.Util.BaseConstants.SHOW_FB_BANNER = true` `[static]`

Show the FB banner.

5.10.2.35 `bool Crosstales.Common.Util.BaseConstants.SHOW_OC_BANNER = true` `[static]`

Show the OC banner.

5.10.2.36 `bool Crosstales.Common.Util.BaseConstants.SHOW_RADIO_BANNER = true` `[static]`

Show the Radio banner.

5.10.2.37 `bool Crosstales.Common.Util.BaseConstants.SHOW_RTV_BANNER = true` `[static]`

Show the RTV banner.

5.10.2.38 `bool Crosstales.Common.Util.BaseConstants.SHOW_TB_BANNER = true` `[static]`

Show the TB banner.

5.10.2.39 `bool Crosstales.Common.Util.BaseConstants.SHOW_TPB_BANNER = false` `[static]`

Show the TPB banner.

5.10.2.40 `bool Crosstales.Common.Util.BaseConstants.SHOW_TPS_BANNER = true` `[static]`

Show the TPS banner.

5.10.2.41 `bool Crosstales.Common.Util.BaseConstants.SHOW_TR_BANNER = true` `[static]`

Show the TR banner.

5.10.3 Property Documentation

5.10.3.1 `string Crosstales.Common.Util.BaseConstants.APPLICATION_PATH` `[static]`, `[get]`

Application path.

5.10.3.2 string Crosstales.Common.Util.BaseConstants.PREFIX_FILE [static], [get]

URL prefix for files.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/Scripts/Util/BaseConstants.cs

5.11 Crosstales.RTVoice.Provider.BaseCustomVoiceProvider Class Reference

Base class for custom voice providers (TTS-systems).

Inheritance diagram for Crosstales.RTVoice.Provider.BaseCustomVoiceProvider:



Public Member Functions

- virtual void Silence ()
Silence all active TTS-providers.
- virtual void Silence (string uid)
Silence the current TTS-provider (native mode).
- abstract IEnumerator SpeakNative (Model.Wrapper wrapper)
The current provider speaks a text with a given voice (native mode).
- abstract IEnumerator Speak (Model.Wrapper wrapper)
The current provider speaks a text with a given voice.
- abstract IEnumerator Generate (Model.Wrapper wrapper)
The current provider generates an audio file from a text with a given voice.
- abstract void Load ()
Load the provider (e.g. all voices).

Protected Member Functions

- string **getOutputFile** (string uid, bool isPersistentData=false)
- virtual IEnumerator **playAudioFile** (Model.Wrapper wrapper, string url, string outputFile, AudioType type=AudioType.WAV, bool isNative=false, bool isLocalFile=true, System.Collections.Generic.Dictionary<string, string> headers=null)
- virtual void **copyAudioFile** (Model.Wrapper wrapper, string outputFile, bool isLocalFile=true, byte[] data=null)
- virtual void **processAudioFile** (Model.Wrapper wrapper, string outputFile, bool isLocalFile=true, byte[] data=null)
- virtual string **getVoiceName** (Model.Wrapper wrapper)
- void **onVoicesReady** ()
- void **onSpeakStart** (Model.Wrapper wrapper)
- void **onSpeakComplete** (Model.Wrapper wrapper)
- void **onSpeakCurrentWord** (Model.Wrapper wrapper, string[] speechTextArray, int wordIndex)
- void **onSpeakCurrentPhoneme** (Model.Wrapper wrapper, string phoneme)
- void **onSpeakCurrentViseme** (Model.Wrapper wrapper, string viseme)
- void **onSpeakAudioGenerationStart** (Model.Wrapper wrapper)
- void **onSpeakAudioGenerationComplete** (Model.Wrapper wrapper)
- void **onErrorInfo** (Model.Wrapper wrapper, string info)

Protected Attributes

- System.Collections.Generic.List< Model.Voice > **cachedVoices** = new System.Collections.Generic.List<Model.Voice>()
- bool **silence** = false

Static Protected Attributes

- static char[] **splitCharWords** = new char[] { ' ' }

Properties

- VoicesReady OnVoicesReady
An event triggered whenever the voices of a provider are ready.
- SpeakStart OnSpeakStart
An event triggered whenever a speak is started.
- SpeakComplete OnSpeakComplete
An event triggered whenever a speak is completed.
- SpeakCurrentWord OnSpeakCurrentWord
An event triggered whenever a new word is spoken (native, Windows and iOS only).
- SpeakCurrentPhoneme OnSpeakCurrentPhoneme
An event triggered whenever a new phoneme is spoken (native mode, Windows only).
- SpeakCurrentViseme OnSpeakCurrentViseme
An event triggered whenever a new viseme is spoken (native mode, Windows only).
- SpeakAudioGenerationStart OnSpeakAudioGenerationStart
An event triggered whenever a speak audio generation is started.
- SpeakAudioGenerationComplete OnSpeakAudioGenerationComplete
An event triggered whenever a speak audio generation is completed.
- ErrorInfo OnErrorInfo
An event triggered whenever an error occurs.
- bool **isActive** [get, set]
- abstract string **AudioFileExtension** [get]
- abstract AudioType **AudioFileType** [get]
- abstract string **DefaultVoiceName** [get]
- virtual System.Collections.Generic.List< Model.Voice > **Voices** [get]
- abstract bool **isWorkingInEditor** [get]
- abstract int **MaxTextLength** [get]
- abstract bool **isSpeakNativeSupported** [get]
- abstract bool **isSpeakSupported** [get]
- abstract bool **isPlatformSupported** [get]
- abstract bool **isSSMLSupported** [get]
- abstract bool **isOnlineService** [get]
- abstract bool **hasCoRoutines** [get]
- System.Collections.Generic.List< string > **Cultures** [get]

5.11.1 Detailed Description

Base class for custom voice providers (TTS-systems).

5.11.2 Member Function Documentation

- 5.11.2.1 abstract IEnumerator Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.Generate (Model.Wrapper wrapper)
[pure virtual]

The current provider generates an audio file from a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.IVoiceProvider.

Implemented in Crosstales.RTVoice.AWSPolly.VoiceProviderAWS, Crosstales.RTVoice.VoiceProviderExample, and Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynth.

5.11.2.2 abstract void Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.Load () [pure virtual]

Load the provider (e.g. all voices).

Implemented in Crosstales.RTVoice.AWSPolly.VoiceProviderAWS, Crosstales.RTVoice.VoiceProviderExample, and Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynth.

5.11.2.3 virtual void Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.Silence () [virtual]

Silence all active TTS-providers.

Implements Crosstales.RTVoice.Provider.IVoiceProvider.

5.11.2.4 virtual void Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.Silence (string uid) [virtual]

Silence the current TTS-provider (native mode).

Parameters

<i>uid</i>	UID of the speaker
------------	--------------------

Implements Crosstales.RTVoice.Provider.IVoiceProvider.

5.11.2.5 abstract IEnumerator Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.Speak (Model.Wrapper wrapper) [pure virtual]

The current provider speaks a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.IVoiceProvider.

Implemented in Crosstales.RTVoice.AWSPolly.VoiceProviderAWS, Crosstales.RTVoice.VoiceProviderExample, and Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynth.

5.11.2.6 **abstract IEnumerator Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.SpeakNative (Model.Wrapper wrapper)** `[pure virtual]`

The current provider speaks a text with a given voice (native mode).

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.IVoiceProvider.

Implemented in Crosstales.RTVoice.AWSPolly.VoiceProviderAWS, Crosstales.RTVoice.VoiceProviderExample, and Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynth.

5.11.3 Property Documentation

5.11.3.1 **ErrorInfo Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.OnErrorInfo** `[add], [remove]`

An event triggered whenever an error occurs.

5.11.3.2 **SpeakAudioGenerationComplete Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.OnSpeakAudioGenerationComplete** `[add], [remove]`↵

An event triggered whenever a speak audio generation is completed.

5.11.3.3 **SpeakAudioGenerationStart Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.OnSpeakAudioGenerationStart** `[add], [remove]`

An event triggered whenever a speak audio generation is started.

5.11.3.4 **SpeakComplete Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.OnSpeakComplete** `[add], [remove]`

An event triggered whenever a speak is completed.

5.11.3.5 **SpeakCurrentPhoneme Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.OnSpeakCurrentPhoneme** `[add], [remove]`

An event triggered whenever a new phoneme is spoken (native mode, Windows only).

5.11.3.6 **SpeakCurrentViseme Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.OnSpeakCurrentViseme** `[add], [remove]`

An event triggered whenever a new viseme is spoken (native mode, Windows only).

5.11.3.7 **SpeakCurrentWord** Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.OnSpeakCurrentWord [add], [remove]

An event triggered whenever a new word is spoken (native, Windows and iOS only).

5.11.3.8 **SpeakStart** Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.OnSpeakStart [add], [remove]

An event triggered whenever a speak is started.

5.11.3.9 **VoicesReady** Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.OnVoicesReady [add], [remove]

An event triggered whenever the voices of a provider are ready.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Provider/BaseCustomVoiceProvider.cs

5.12 Crosstales.Common.EditorUtil.BaseEditorHelper Class Reference

Base for various Editor helper functions.

Inheritance diagram for Crosstales.Common.EditorUtil.BaseEditorHelper:



Static Public Member Functions

- static void RestartUnity (string executeMethod="")
Restart Unity.
- static void SeparatorUI (int space=12)
Shows a separator-UI.
- static void ReadOnlyTextField (string label, string text)
Generates a read-only text field with a label.
- static void RefreshAssetDatabase ()
Refreshes the asset database.
- static void **InvokeMethod** (string className, string methodName, params object[] parameters)
- static bool isValidBuildTarget (BuildTarget target)
Returns the true if the BuildTarget is installed in Unity.
- static string getCLIArgument (string name)
Returns an argument for a name from the command line.
- static BuildTarget getBuildTargetForBuildName (string build)
Returns the BuildTarget for a build name, like 'win64'.
- static string getBuildNameFromBuildTarget (BuildTarget build)
Returns the build name for a BuildTarget.

Properties

- static Texture2D **Logo_Asset_BWF** [get]
- static Texture2D **Logo_Asset_DJ** [get]
- static Texture2D **Logo_Asset_FB** [get]
- static Texture2D **Logo_Asset_OC** [get]
- static Texture2D **Logo_Asset_Radio** [get]
- static Texture2D **Logo_Asset_RTV** [get]
- static Texture2D **Logo_Asset_TB** [get]
- static Texture2D **Logo_Asset_TPB** [get]
- static Texture2D **Logo_Asset_TPS** [get]
- static Texture2D **Logo_Asset_TR** [get]
- static Texture2D **Logo_CT** [get]
- static Texture2D **Logo_Unity** [get]
- static Texture2D **Icon_Save** [get]
- static Texture2D **Icon_Reset** [get]
- static Texture2D **Icon_Refresh** [get]
- static Texture2D **Icon_Delete** [get]
- static Texture2D **Icon_Folder** [get]
- static Texture2D **Icon_Plus** [get]
- static Texture2D **Icon_Minus** [get]
- static Texture2D **Icon_Manual** [get]
- static Texture2D **Icon_API** [get]
- static Texture2D **Icon_Forum** [get]
- static Texture2D **Icon_Product** [get]
- static Texture2D **Icon_Check** [get]
- static Texture2D **Social_Discord** [get]
- static Texture2D **Social_Facebook** [get]
- static Texture2D **Social_Twitter** [get]
- static Texture2D **Social_Youtube** [get]
- static Texture2D **Social_Linkedin** [get]
- static Texture2D **Social_Xing** [get]
- static Texture2D **Video_Promo** [get]
- static Texture2D **Video_Tutorial** [get]
- static Texture2D **Icon_Videos** [get]
- static Texture2D **Icon_3p_Assets** [get]
- static Texture2D **Asset_PlayMaker** [get]

Additional Inherited Members

5.12.1 Detailed Description

Base for various Editor helper functions.

5.12.2 Member Function Documentation

5.12.2.1 **static string** `Crosstales.Common.EditorUtil.BaseEditorHelper.getBuildNameFromBuildTarget (BuildTarget build)`
[static]

Returns the build name for a BuildTarget.

Parameters

<i>build</i>	BuildTarget for a build name
--------------	------------------------------

Returns

The build name for a BuildTarget.

5.12.2.2 `static BuildTarget Crosstales.Common.EditorUtil.BaseEditorHelper.getBuildTargetForBuildName (string build)`
[static]

Returns the BuildTarget for a build name, like 'win64'.

Parameters

<i>build</i>	Build name, like 'win64'
--------------	--------------------------

Returns

The BuildTarget for a build name.

5.12.2.3 `static string Crosstales.Common.EditorUtil.BaseEditorHelper.getCLIArgument (string name)` [static]

Returns an argument for a name from the command line.

Parameters

<i>name</i>	Name for the argument
-------------	-----------------------

Returns

True if the BuildTarget is installed in Unity.

5.12.2.4 `static bool Crosstales.Common.EditorUtil.BaseEditorHelper.isValidBuildTarget (BuildTarget target)` [static]

Returns the true if the BuildTarget is installed in Unity.

Parameters

<i>target</i>	BuildTarget to test
---------------	---------------------

Returns

True if the BuildTarget is installed in Unity.

5.12.2.5 `static void Crosstales.Common.EditorUtil.BaseEditorHelper.ReadOnlyTextField (string label, string text)`
`[static]`

Generates a read-only text field with a label.

5.12.2.6 `static void Crosstales.Common.EditorUtil.BaseEditorHelper.RefreshAssetDatabase ()` `[static]`

Refreshes the asset database.

5.12.2.7 `static void Crosstales.Common.EditorUtil.BaseEditorHelper.RestartUnity (string executeMethod = " ")`
`[static]`

Restart Unity.

Parameters

<i>executeMethod</i>	Executed method after the restart (optional)
----------------------	--

5.12.2.8 `static void Crosstales.Common.EditorUtil.BaseEditorHelper.SeparatorUI (int space = 12)` `[static]`

Shows a separator-UI.

Parameters

<i>space</i>	Space in pixels between the component and the separator line (default: 12, optional).
--------------	---


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ Editor/Util/BaseEditorHelper.cs

5.13 Crosstales.Common.EditorUtil.BaseGAApi Class Reference

Base GA-wrapper API.

Inheritance diagram for Crosstales.Common.EditorUtil.BaseGAApi:



Static Public Member Functions

- static void **Event** (string name, string version, string category, string action, string label="", int value=0)
Tracks an event from the asset.

Static Protected Attributes

- static readonly string **clientId** = SystemInfo.deviceUniqueIdentifier
- static readonly string **screenResolution** = Screen.currentResolution.ToString()
- static readonly string **userLanguage** = System.Threading.Thread.CurrentThread.CurrentCulture.Name
- static readonly string **unityVersion** = Application.unityVersion
- static readonly string **os** = SystemInfo.operatingSystem
- static readonly string **cpu** = SystemInfo.processorType
- static readonly int **cpuCores** = SystemInfo.processorCount
- static readonly int **cpuFrequency** = SystemInfo.processorFrequency
- static readonly string **productName** = Application.productName
- static readonly string **companyName** = Application.companyName
- static readonly int **memory** = SystemInfo.systemMemorySize
- static readonly string **gpu** = SystemInfo.graphicsDeviceName
- static readonly int **gpuMemory** = SystemInfo.graphicsMemorySize
- static readonly int **gpuShaderLevel** = SystemInfo.graphicsShaderLevel

5.13.1 Detailed Description

Base GA-wrapper API.

5.13.2 Member Function Documentation

5.13.2.1 static void **Crosstales.Common.EditorUtil.BaseGAApi.Event** (string name, string version, string category, string action, string label = " ", int value = 0) [static]

Tracks an event from the asset.

Parameters

<i>category</i>	Specifies the event category.
<i>action</i>	Specifies the event action.
<i>label</i>	Specifies the event label.
<i>value</i>	Specifies the event value.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ Editor/Util/BaseGAApi.cs

5.14 Crosstales.Common.Util.BaseHelper Class Reference

Base for various helper functions.

Inheritance diagram for Crosstales.Common.Util.BaseHelper:



Static Public Member Functions

- static string CreateString (string replaceChars, int stringLength)
Creates a string of characters with a given length.
- static bool hasActiveClip (AudioSource source)
Determines if an AudioSource has an active clip.
- static bool RemoteCertificateValidationCallback (System.Object sender, System.Security.Cryptography.X509Certificates.X509Certificate certificate, System.Security.Cryptography.X509Certificates.X509Chain chain, System.Net.Security.SslPolicyErrors sslPolicyErrors)
HTTPS-certification callback.
- static string ValidatePath (string path, bool addEndDelimiter=true)
Validates a given path and add missing slash.
- static string ValidateFile (string path)
Validates a given file.
- static string ValidURLFromFilePath (string path)
Validates a given file.
- static string CleanUrl (string url, bool removeProtocol=true, bool removeWWW=true, bool removeSlash=true)
Cleans a given URL.

Parameters

url	<i>URL to clean</i>
removeProtocol	<i>Remove the protocol, e.g. http:// (default: true, optional).</i>
removeWWW	<i>Remove www (default: true, optional).</i>
removeSlash	<i>Remove slash at the end (default: true, optional)</i>

Returns

Clean URL

- static string ClearTags (string text)
Cleans a given text from tags.
- static string ClearSpaces (string text)
Cleans a given text from multiple spaces.
- static string ClearLineEndings (string text)
Cleans a given text from line endings.
- static System.Collections.Generic.List< string > SplitStringToLines (string text, bool ignoreCommentedLines=true, int skipHeaderLines=0, int skipFooterLines=0)
Split the given text to lines and return it as list.
- static string FormatBytesToHRF (long bytes)
Format byte-value to Human-Readable-Form.
- static string FormatSecondsToHourMinSec (double seconds)
Format seconds to Human-Readable-Form.

- static Color HSVToRGB (float h, float s, float v, float a=1f)
Generate nice HSV colors. Based on <https://gist.github.com/rje/6206099>
- static bool isValidURL (string url)
Checks if the URL is valid.
- static void FileCopy (string inputFile, string outputFile, bool move=false)
Copy or move a file.

Static Public Attributes

- static readonly System.Globalization.CultureInfo **BaseCulture** = new System.Globalization.CultureInfo("en-US")

Protected Attributes

- const string **file_prefix** = "file://"

Static Protected Attributes

- static readonly System.Text.RegularExpressions.Regex **lineEndingsRegex** = new System.Text.RegularExpressions.Regex(@"\r\n|\r|\n")
- static readonly System.Text.RegularExpressions.Regex **cleanSpacesRegex** = new System.Text.RegularExpressions.Regex(@"\s+")
- static readonly System.Text.RegularExpressions.Regex **cleanTagsRegex** = new System.Text.RegularExpressions.Regex(@"<.*?>")
- static readonly System.Random **rnd** = new System.Random()

Properties

- static bool isInternetAvailable [get]
Checks if an Internet connection is available.
- static bool isWindowsPlatform [get]
Checks if the current platform is Windows.
- static bool isMacOSPlatform [get]
Checks if the current platform is OSX.
- static bool isLinuxPlatform [get]
Checks if the current platform is Linux.
- static bool isStandalonePlatform [get]
Checks if the current platform is standalone (Windows, macOS or Linux).
- static bool isAndroidPlatform [get]
Checks if the current platform is Android.
- static bool isIOSPlatform [get]
Checks if the current platform is iOS.
- static bool isWSAPlatform [get]
Checks if the current platform is WSA.
- static bool isWebGLPlatform [get]
Checks if the current platform is WebGL.
- static bool isWebPlatform [get]
Checks if the current platform is Web (WebPlayer or WebGL).
- static bool isWindowsBasedPlatform [get]

- Checks if the current platform is Windows-based (Windows standalone or WSA).*
 - static bool isAppleBasedPlatform [get]
- Checks if the current platform is Apple-based (macOS standalone or iOS).*
 - static bool isEditor [get]
- Checks if we are inside the Editor.*
 - static bool isEditorMode [get]
- Checks if we are in Editor mode.*
 - static Model.Enum.Platform CurrentPlatform [get]
- Returns the current platform.*

5.14.1 Detailed Description

Base for various helper functions.

5.14.2 Member Function Documentation

5.14.2.1 static string Crosstales.Common.Util.BaseHelper.ClearLineEndings (string text) [static]

Cleans a given text from line endings.

Parameters

<i>text</i>	Text to clean.
-------------	----------------

Returns

Clean text without line endings.

5.14.2.2 static string Crosstales.Common.Util.BaseHelper.ClearSpaces (string text) [static]

Cleans a given text from multiple spaces.

Parameters

<i>text</i>	Text to clean.
-------------	----------------

Returns

Clean text without multiple spaces.

5.14.2.3 static string Crosstales.Common.Util.BaseHelper.ClearTags (string text) [static]

Cleans a given text from tags.

Parameters

<i>text</i>	Text to clean.
-------------	----------------

Returns

Clean text without tags.

5.14.2.4 static string Crosstales.Common.Util.BaseHelper.CreateString (string *replaceChars*, int *stringLength*) [static]

Creates a string of characters with a given length.

Parameters

<i>chars</i>	Characters to generate the string (if more than one character is used, the generated string will be a randomized result of all characters)
<i>stringLength</i>	Length of the generated string

Returns

Generated string

5.14.2.5 static void Crosstales.Common.Util.BaseHelper.FileCopy (string *inputFile*, string *outputFile*, bool *move* = false) [static]

Copy or move a file.

Parameters

<i>inputFile</i>	Input file path
<i>outputFile</i>	Output file path
<i>move</i>	Move file instead of copy (default: false, optional)

5.14.2.6 static string Crosstales.Common.Util.BaseHelper.FormatBytesToHRF (long *bytes*) [static]

Format byte-value to Human-Readable-Form.

Returns

Formatted byte-value in Human-Readable-Form.

5.14.2.7 static string Crosstales.Common.Util.BaseHelper.FormatSecondsToHourMinSec (double *seconds*) [static]

Format seconds to Human-Readable-Form.

Returns

Formatted seconds in Human-Readable-Form.

5.14.2.8 static bool Crosstales.Common.Util.BaseHelper.hasActiveClip (AudioSource *source*) [static]

Determines if an AudioSource has an active clip.

Parameters

<i>source</i>	AudioSource to check.
---------------	-----------------------

Returns

True if the AudioSource has an active clip.

5.14.2.9 static Color Crosstales.Common.Util.BaseHelper.HSVToRGB (float *h*, float *s*, float *v*, float *a* = 1f) [static]

Generate nice HSV colors. Based on <https://gist.github.com/rje/6206099>

Parameters

<i>h</i>	Hue
<i>s</i>	Saturation
<i>v</i>	Value
<i>a</i>	Alpha (optional)

Returns

True if the current platform is supported.

5.14.2.10 static bool Crosstales.Common.Util.BaseHelper.isValidURL (string *url*) [static]

Checks if the URL is valid.

Parameters

<i>url</i>	URL to check
------------	--------------

Returns

True if the URL is valid.

5.14.2.11 static bool Crosstales.Common.Util.BaseHelper.RemoteCertificateValidationCallback (System.Object *sender*, System.Security.Cryptography.X509Certificates.X509Certificate *certificate*, System.Security.Cryptographic.X509Certificates.X509Chain *chain*, System.Net.Security.SslPolicyErrors *sslPolicyErrors*) [static]

HTTPS-certification callback.

5.14.2.12 `static System.Collections.Generic.List<string> Crosstales.Common.Util.BaseHelper.SplitStringToLines (string text, bool ignoreCommentedLines = true, int skipHeaderLines = 0, int skipFooterLines = 0) [static]`

Split the given text to lines and return it as list.

Parameters

<i>text</i>	Complete text fragment
<i>ignoreCommentedLines</i>	Ignore commente lines (default: true, optional)
<i>skipHeaderLines</i>	Number of skipped header lines (default: 0, optional)
<i>skipFooterLines</i>	Number of skipped footer lines (default: 0, optional)

Returns

Splitted lines as array

5.14.2.13 `static string Crosstales.Common.Util.BaseHelper.ValidateFile (string path) [static]`

Validates a given file.

Parameters

<i>path</i>	File to validate
-------------	------------------

Returns

Valid file path

5.14.2.14 `static string Crosstales.Common.Util.BaseHelper.ValidatePath (string path, bool addEndDelimiter = true) [static]`

Validates a given path and add missing slash.

Parameters

<i>path</i>	Path to validate
<i>addEndDelimiter</i>	Add delimiter at the end of the path (optional, default: true)

Returns

Valid path

5.14.2.15 `static string Crosstales.Common.Util.BaseHelper.ValidURLFromFilePath (string path) [static]`

Validates a given file.

Parameters

<i>path</i>	File to validate
-------------	------------------

Returns

Valid file path

5.14.3 Property Documentation

5.14.3.1 `Model.Enum.Platform Crosstales.Common.Util.BaseHelper.CurrentPlatform` `[static], [get]`

Returns the current platform.

Returns

The current platform.

5.14.3.2 `bool Crosstales.Common.Util.BaseHelper.isAndroidPlatform` `[static], [get]`

Checks if the current platform is Android.

Returns

True if the current platform is Android.

5.14.3.3 `bool Crosstales.Common.Util.BaseHelper.isAppleBasedPlatform` `[static], [get]`

Checks if the current platform is Apple-based (macOS standalone or iOS).

Returns

True if the current platform is Apple-based (macOS standalone or iOS).

5.14.3.4 `bool Crosstales.Common.Util.BaseHelper.isEditor` `[static], [get]`

Checks if we are inside the Editor.

Returns

True if we are inside the Editor.

5.14.3.5 `bool Crosstales.Common.Util.BaseHelper.isEditorMode` `[static], [get]`

Checks if we are in Editor mode.

Returns

True if in Editor mode.

5.14.3.6 `bool Crosstales.Common.Util.BaseHelper.isInternetAvailable` `[static], [get]`

Checks if an Internet connection is available.

Returns

True if an Internet connection is available.

5.14.3.7 `bool Crosstales.Common.Util.BaseHelper.isiOSPlatform` `[static], [get]`

Checks if the current platform is iOS.

Returns

True if the current platform is iOS.

5.14.3.8 `bool Crosstales.Common.Util.BaseHelper.isLinuxPlatform` `[static], [get]`

Checks if the current platform is Linux.

Returns

True if the current platform is Linux.

5.14.3.9 `bool Crosstales.Common.Util.BaseHelper.isMacOSPlatform` `[static], [get]`

Checks if the current platform is OSX.

Returns

True if the current platform is OSX.

5.14.3.10 `bool Crosstales.Common.Util.BaseHelper.isStandalonePlatform` `[static], [get]`

Checks if the current platform is standalone (Windows, macOS or Linux).

Returns

True if the current platform is standalone (Windows, macOS or Linux).

5.14.3.11 bool Crosstales.Common.Util.BaseHelper.isWebGLPlatform [static], [get]

Checks if the current platform is WebGL.

Returns

True if the current platform is WebGL.

5.14.3.12 bool Crosstales.Common.Util.BaseHelper.isWebPlatform [static], [get]

Checks if the current platform is Web (WebPlayer or WebGL).

Returns

True if the current platform is Web (WebPlayer or WebGL).

5.14.3.13 bool Crosstales.Common.Util.BaseHelper.isWindowsBasedPlatform [static], [get]

Checks if the current platform is Windows-based (Windows standalone or WSA).

Returns

True if the current platform is Windows-based (Windows standalone or WSA).

5.14.3.14 bool Crosstales.Common.Util.BaseHelper.isWindowsPlatform [static], [get]

Checks if the current platform is Windows.

Returns

True if the current platform is Windows.

5.14.3.15 bool Crosstales.Common.Util.BaseHelper.isWSAPlatform [static], [get]

Checks if the current platform is WSA.

Returns

True if the current platform is WSA.

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ Scripts/Util/BaseHelper.cs

5.15 HutongGames.PlayMaker.Actions.BaseRTVAction Class Reference

Base class for RT-Voice actions in PlayMaker.

Inheritance diagram for HutongGames.PlayMaker.Actions.BaseRTVAction:



Public Attributes

- FsmEvent **sendEvent**

5.15.1 Detailed Description

Base class for RT-Voice actions in PlayMaker.

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstailes/RTVoice/3rd party/PlayMaker/Scripts/BaseRTVAction.cs

5.16 Crosstailes.RTVoice.PlayMaker.BaseRTVEditor Class Reference

Base class for RT-Voice custom editors in PlayMaker.

Inheritance diagram for Crosstailes.RTVoice.PlayMaker.BaseRTVEditor:



Public Member Functions

- override bool **OnGUI** ()

5.16.1 Detailed Description

Base class for RT-Voice custom editors in PlayMaker.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstailes/RTVoice/3rd party/PlayMaker/Editor/BaseRTVEditor.cs

5.17 Crosstales.Common.EditorTask.BaseSetupResources Class Reference

Base for copying all resources to 'Editor Default Resources'.

Inheritance diagram for Crosstales.Common.EditorTask.BaseSetupResources:



Static Protected Member Functions

- static void **setupResources** (string source, string sourceFolder, string target, string targetFolder, string metafile)

5.17.1 Detailed Description

Base for copying all resources to 'Editor Default Resources'.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ Editor/Task/BaseSetupResources.cs

5.18 Crosstales.RTVoice.Provider.BaseVoiceProvider Class Reference

Base class for voice providers.

Inheritance diagram for Crosstales.RTVoice.Provider.BaseVoiceProvider:



Public Member Functions

- **BaseVoiceProvider** (MonoBehaviour obj)
Constructor for a VoiceProvider.
- virtual void **Silence** ()
Silence all active TTS-providers.
- virtual void **Silence** (string uid)
Silence the current TTS-provider (native mode).
- abstract IEnumerator **SpeakNative** (Model.Wrapper wrapper)
The current provider speaks a text with a given voice (native mode).
- abstract IEnumerator **Speak** (Model.Wrapper wrapper)
The current provider speaks a text with a given voice.
- abstract IEnumerator **Generate** (Model.Wrapper wrapper)
The current provider generates an audio file from a text with a given voice.

Protected Member Functions

- string **getOutputFile** (string uid, bool isPersistentData=false)
- virtual IEnumerator **playAudioFile** (Model.Wrapper wrapper, string url, string outputFile, AudioType type=AudioType.WAV, bool isNative=false, bool isLocalFile=true, System.Collections.Generic.Dictionary<string, string> headers=null)
- virtual void **copyAudioFile** (Model.Wrapper wrapper, string outputFile, bool isLocalFile=true, byte[] data=null)
- virtual void **processAudioFile** (Model.Wrapper wrapper, string outputFile, bool isLocalFile=true, byte[] data=null)
- virtual string **getVoiceName** (Model.Wrapper wrapper)

Static Protected Member Functions

- static void **onVoicesReady** ()
- static void **onSpeakStart** (Model.Wrapper wrapper)
- static void **onSpeakComplete** (Model.Wrapper wrapper)
- static void **onSpeakCurrentWord** (Model.Wrapper wrapper, string[] speechTextArray, int wordIndex)
- static void **onSpeakCurrentPhoneme** (Model.Wrapper wrapper, string phoneme)
- static void **onSpeakCurrentViseme** (Model.Wrapper wrapper, string viseme)
- static void **onSpeakAudioGenerationStart** (Model.Wrapper wrapper)
- static void **onSpeakAudioGenerationComplete** (Model.Wrapper wrapper)
- static void **onErrorInfo** (Model.Wrapper wrapper, string info)

Protected Attributes

- System.Collections.Generic.List< Model.Voice > **cachedVoices** = new System.Collections.Generic.List<Model.Voice>()
- System.Collections.Generic.Dictionary< string, System.Diagnostics.Process > **processes** = new System.Collections.Generic.Dictionary<string, System.Diagnostics.Process>()
- bool **silence** = false
- MonoBehaviour **speakerObj**

Static Protected Attributes

- static char[] **splitCharWords** = new char[] { ' ' }

Properties

- static VoicesReady OnVoicesReady
An event triggered whenever the voices of a provider are ready.
- static SpeakStart OnSpeakStart
An event triggered whenever a speak is started.
- static SpeakComplete OnSpeakComplete
An event triggered whenever a speak is completed.
- static SpeakCurrentWord OnSpeakCurrentWord
An event triggered whenever a new word is spoken (native, Windows and iOS only).
- static SpeakCurrentPhoneme OnSpeakCurrentPhoneme
An event triggered whenever a new phoneme is spoken (native mode, Windows only).
- static SpeakCurrentViseme OnSpeakCurrentViseme
An event triggered whenever a new viseme is spoken (native mode, Windows only).
- static SpeakAudioGenerationStart OnSpeakAudioGenerationStart
An event triggered whenever a speak audio generation is started.
- static SpeakAudioGenerationComplete OnSpeakAudioGenerationComplete
An event triggered whenever a speak audio generation is completed.
- static ErrorInfo OnErrorInfo
An event triggered whenever an error occurs.
- abstract string **AudioFileExtension** [get]
- abstract AudioType **AudioFileType** [get]
- abstract string **DefaultVoiceName** [get]
- virtual System.Collections.Generic.List< Model.Voice > **Voices** [get]
- abstract bool **isWorkingInEditor** [get]
- abstract int **MaxTextLength** [get]
- abstract bool **isSpeakNativeSupported** [get]
- abstract bool **isSpeakSupported** [get]
- abstract bool **isPlatformSupported** [get]
- abstract bool **isSSMLSupported** [get]
- abstract bool **isOnlineService** [get]
- abstract bool **hasCoRoutines** [get]
- System.Collections.Generic.List< string > **Cultures** [get]

5.18.1 Detailed Description

Base class for voice providers.

5.18.2 Constructor & Destructor Documentation

5.18.2.1 Crosstales.RTVoice.Provider.BaseVoiceProvider.BaseVoiceProvider (MonoBehaviour obj)

Constructor for a VoiceProvider.

Parameters

<i>obj</i>	Instance of the speaker
------------	-------------------------

5.18.3 Member Function Documentation

5.18.3.1 `abstract IEnumerator Crosstales.RTVoice.Provider.BaseVoiceProvider.Generate (Model.Wrapper wrapper)` `[pure virtual]`

The current provider generates an audio file from a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements `Crosstales.RTVoice.Provider.IVoiceProvider`.

Implemented in `Crosstales.RTVoice.Provider.VoiceProviderWindowsLegacy`, `Crosstales.RTVoice.Provider.VoiceProviderLinux`, `Crosstales.RTVoice.Provider.VoiceProviderMacOS`, `Crosstales.RTVoice.Provider.VoiceProviderIOS`, `Crosstales.RTVoice.Provider.VoiceProviderAndroid`, `Crosstales.RTVoice.Provider.VoiceProviderWindows`, `Crosstales.RTVoice.Provider.VoiceProviderMary`, and `Crosstales.RTVoice.Provider.VoiceProviderWSA`.

5.18.3.2 `virtual void Crosstales.RTVoice.Provider.BaseVoiceProvider.Silence ()` `[virtual]`

Silence all active TTS-providers.

Implements `Crosstales.RTVoice.Provider.IVoiceProvider`.

Reimplemented in `Crosstales.RTVoice.Provider.VoiceProviderAndroid`, `Crosstales.RTVoice.Provider.VoiceProviderMary`, `Crosstales.RTVoice.Provider.VoiceProviderIOS`, and `Crosstales.RTVoice.Provider.VoiceProviderWSA`.

5.18.3.3 `virtual void Crosstales.RTVoice.Provider.BaseVoiceProvider.Silence (string uid)` `[virtual]`

Silence the current TTS-provider (native mode).

Parameters

<i>uid</i>	UID of the speaker
------------	--------------------

Implements `Crosstales.RTVoice.Provider.IVoiceProvider`.

5.18.3.4 `abstract IEnumerator Crosstales.RTVoice.Provider.BaseVoiceProvider.Speak (Model.Wrapper wrapper)` `[pure virtual]`

The current provider speaks a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements `Crosstales.RTVoice.Provider.IVoiceProvider`.

Implemented in `Crosstales.RTVoice.Provider.VoiceProviderWindowsLegacy`, `Crosstales.RTVoice.Provider.VoiceProviderIOS`, `Crosstales.RTVoice.Provider.VoiceProviderLinux`, `Crosstales.RTVoice.Provider.VoiceProviderMacOS`, `Crosstales.RTVoice.Provider.VoiceProviderAndroid`, `Crosstales.RTVoice.Provider.VoiceProviderWindows`, `Crosstales.RTVoice.Provider.VoiceProviderMary`, and `Crosstales.RTVoice.Provider.VoiceProviderWSA`.

5.18.3.5 `abstract IEnumerator Crosstales.RTVoice.Provider.BaseVoiceProvider.SpeakNative (Model Wrapper wrapper)` [pure virtual]

The current provider speaks a text with a given voice (native mode).

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements `Crosstales.RTVoice.Provider.IVoiceProvider`.

Implemented in `Crosstales.RTVoice.Provider.VoiceProviderIOS`, `Crosstales.RTVoice.Provider.VoiceProviderWindowsLegacy`, `Crosstales.RTVoice.Provider.VoiceProviderMary`, `Crosstales.RTVoice.Provider.VoiceProviderLinux`, `Crosstales.RTVoice.Provider.VoiceProviderWindows`, `Crosstales.RTVoice.Provider.VoiceProviderWSA`, `Crosstales.RTVoice.Provider.VoiceProviderMacOS`, and `Crosstales.RTVoice.Provider.VoiceProviderAndroid`.

5.18.4 Property Documentation

5.18.4.1 `ErrorInfo Crosstales.RTVoice.Provider.BaseVoiceProvider.OnErrorInfo` [static], [add], [remove]

An event triggered whenever an error occurs.

5.18.4.2 `SpeakAudioGenerationComplete Crosstales.RTVoice.Provider.BaseVoiceProvider.OnSpeakAudioGenerationComplete` [static], [add], [remove]

An event triggered whenever a speak audio generation is completed.

5.18.4.3 `SpeakAudioGenerationStart Crosstales.RTVoice.Provider.BaseVoiceProvider.OnSpeakAudioGenerationStart` [static], [add], [remove]

An event triggered whenever a speak audio generation is started.

5.18.4.4 `SpeakComplete Crosstales.RTVoice.Provider.BaseVoiceProvider.OnSpeakComplete` [static], [add], [remove]

An event triggered whenever a speak is completed.

5.18.4.5 SpeakCurrentPhoneme `Crosstales.RTVoice.Provider.BaseVoiceProvider.OnSpeakCurrentPhoneme` `[static], [add], [remove]`

An event triggered whenever a new phoneme is spoken (native mode, Windows only).

5.18.4.6 SpeakCurrentViseme `Crosstales.RTVoice.Provider.BaseVoiceProvider.OnSpeakCurrentViseme` `[static], [add], [remove]`

An event triggered whenever a new viseme is spoken (native mode, Windows only).

5.18.4.7 SpeakCurrentWord `Crosstales.RTVoice.Provider.BaseVoiceProvider.OnSpeakCurrentWord` `[static], [add], [remove]`

An event triggered whenever a new word is spoken (native, Windows and iOS only).

5.18.4.8 SpeakStart `Crosstales.RTVoice.Provider.BaseVoiceProvider.OnSpeakStart` `[static], [add], [remove]`

An event triggered whenever a speak is started.

5.18.4.9 VoicesReady `Crosstales.RTVoice.Provider.BaseVoiceProvider.OnVoicesReady` `[static], [add], [remove]`

An event triggered whenever the voices of a provider are ready.


The documentation for this class was generated from the following file:

- `D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Provider/BaseVoiceProvider.cs`

5.19 Crosstales.RTVoice.SALSA.Bots Class Reference

This is class for conversations between two SALSA-Bots.

Inheritance diagram for `Crosstales.RTVoice.SALSA.Bots`:



Public Member Functions

- void **OnEnable** ()
- void **OnDisable** ()
- void **Update** ()

Public Attributes

- AudioSource **SourceA**
- AudioSource **SourceB**
- string[] **ConverstationsA**
- string[] **ConverstationsB**

5.19.1 Detailed Description

This is class for conversations between two SALSA-Bots.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/SALSA/Scripts/Bots.cs

5.20 Crosstales.RTVoice.Tool.ChangeGender Class Reference

Change the gender of all voices (useful for eSpeak).

Inheritance diagram for Crosstales.RTVoice.Tool.ChangeGender:



Public Member Functions

- void **Start** ()
- void **OnDestroy** ()
- void **GenderChanged** (System.Int32 index)
- void **Change** ()

Public Attributes

- Model.Enum.Gender NewGender
The new gender for all voices.
- bool RefreshOnVoicesReady = true
Refresh on voices ready (default: true).
- bool ESpeakOnly = true
Change voices only when eSpeak is used (default: true).

5.20.1 Detailed Description

Change the gender of all voices (useful for eSpeak).

5.20.2 Member Data Documentation

5.20.2.1 bool Crosstales.RTVoice.Tool.ChangeGender.ESpeakOnly = true

Change voices only when eSpeak is used (default: true).

5.20.2.2 Model.Enum.Gender Crosstales.RTVoice.Tool.ChangeGender.NewGender

The new gender for all voices.

5.20.2.3 bool Crosstales.RTVoice.Tool.ChangeGender.RefreshOnVoicesReady = true

Refresh on voices ready (default: true).


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Scripts/Tool/ChangeGender.cs

5.21 Crosstales.RTVoice.EditorExtension.ChangeGenderEditor Class Reference

Custom editor for the 'ChangeGender'-class.

Inheritance diagram for Crosstales.RTVoice.EditorExtension.ChangeGenderEditor:



Public Member Functions

- void **OnEnable** ()
- override void **OnInspectorGUI** ()

5.21.1 Detailed Description

Custom editor for the 'ChangeGender'-class.

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Editor/Extension/ChangeGenderEditor.cs

5.22 Crosstales.RTVoice.EditorTask.CheckIL2CPP Class Reference

Checks if IL2CPP is enabled under standalone.

5.22.1 Detailed Description

Checks if IL2CPP is enabled under standalone.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Editor/Task/CheckIL2CPP.cs

5.23 Crosstales.RTVoice.EditorTask.CompileDefines Class Reference

Adds the given define symbols to PlayerSettings define symbols.

Inheritance diagram for Crosstales.RTVoice.EditorTask.CompileDefines:



Additional Inherited Members

5.23.1 Detailed Description

Adds the given define symbols to PlayerSettings define symbols.

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Editor/Task/CompileDefines.cs

5.24 Crosstales.RTVoice.Util.Config Class Reference

Configuration for the asset.

Static Public Member Functions

- static void Reset ()
Resets all changable variables to their default value.
- static void Load ()
Loads all changable variables.
- static void Save ()
Saves all changable variables.

Static Public Attributes

- static string ASSET_PATH = "/Plugins/crosstales/RTVoice/"
Path to the asset inside the Unity project.
- static bool DEBUG = Constants.DEFAULT_DEBUG
Enable or disable debug logging for the asset.
- static bool AUDIOFILE_AUTOMATIC_DELETE = Constants.DEFAULT_AUDIOFILE_AUTOMATIC_DELETE
Automatically delete the generated audio files.
- static bool ENFORCE_32BIT_WINDOWS = Constants.DEFAULT_ENFORCE_32BIT_WINDOWS
Enforce 32bit versions of voices under Windows.
- static string TTS_WINDOWS_BUILD = Constants.DEFAULT_TTS_WINDOWS_BUILD
Location of the TTS-wrapper under Windows (stand-alone).
- static string TTS_MACOS = Constants.DEFAULT_TTS_MACOS
Location of the TTS-system under MacOS.
- static string TTS_LINUX = Constants.DEFAULT_TTS_LINUX
Location of the TTS-system under Linux.
- static string TTS_LINUX_DATA = Constants.DEFAULT_TTS_LINUX_DATA
Location of the data for the TTS-system under Linux.
- static bool ENSURE_NAME = Constants.DEFAULT_ENSURE_NAME
Enable or disable the ensuring the name of the RTVoice gameobject.
- static bool isLoading = false
Is the configuration loaded?

Properties

- static string AUDIOFILE_PATH [get, set]
Path to the generated audio files.
- static string TTS_WINDOWS_EDITOR [get]
Location of the TTS-wrapper under Windows (Editor).
- static string TTS_WINDOWS_EDITOR_x86 [get]
Location of the TTS-wrapper (32bit) under Windows (Editor).

5.24.1 Detailed Description

Configuration for the asset.

5.24.2 Member Function Documentation

5.24.2.1 static void Crosstales.RTVoice.Util.Config.Load () [static]

Loads all changable variables.

5.24.2.2 static void Crosstales.RTVoice.Util.Config.Reset () [static]

Resets all changable variables to their default value.

5.24.2.3 static void Crosstales.RTVoice.Util.Config.Save () [static]

Saves all changable variables.

5.24.3 Member Data Documentation

5.24.3.1 string Crosstales.RTVoice.Util.Config.ASSET_PATH = "/Plugins/crosstales/RTVoice/" [static]

Path to the asset inside the Unity project.

5.24.3.2 bool Crosstales.RTVoice.Util.Config.AUDIOFILE_AUTOMATIC_DELETE = Constants.DEFAULT_AUDIOFILE_AUTOMATIC_DELETE [static]

Automatically delete the generated audio files.

5.24.3.3 bool Crosstales.RTVoice.Util.Config.DEBUG = Constants.DEFAULT_DEBUG [static]

Enable or disable debug logging for the asset.

5.24.3.4 bool Crosstales.RTVoice.Util.Config.ENFORCE_32BIT_WINDOWS = Constants.DEFAULT_ENFORCE_32BIT_WINDOWS [static]

Enforce 32bit versions of voices under Windows.

5.24.3.5 bool Crosstales.RTVoice.Util.Config.ENSURE_NAME = Constants.DEFAULT_ENSURE_NAME [static]

Enable or disable the ensuring the name of the RTVoice gameobject.

5.24.3.6 bool Crosstales.RTVoice.Util.Config.isLoaded = false [static]

Is the configuration loaded?

5.24.3.7 `string Crosstales.RTVoice.Util.Config.TTS_LINUX = Constants.DEFAULT_TTS_LINUX` `[static]`

Location of the TTS-system under Linux.

5.24.3.8 `string Crosstales.RTVoice.Util.Config.TTS_LINUX_DATA = Constants.DEFAULT_TTS_LINUX_DATA` `[static]`

Location of the data for the TTS-system under Linux.

5.24.3.9 `string Crosstales.RTVoice.Util.Config.TTS_MACOS = Constants.DEFAULT_TTS_MACOS` `[static]`

Location of the TTS-system under MacOS.

5.24.3.10 `string Crosstales.RTVoice.Util.Config.TTS_WINDOWS_BUILD = Constants.DEFAULT_TTS_WINDOWS_BUILD`
`[static]`

Location of the TTS-wrapper under Windows (stand-alone).

5.24.4 Property Documentation

5.24.4.1 `string Crosstales.RTVoice.Util.Config.AUDIOFILE_PATH` `[static]`, `[get]`, `[set]`

Path to the generated audio files.

5.24.4.2 `string Crosstales.RTVoice.Util.Config.TTS_WINDOWS_EDITOR` `[static]`, `[get]`

Location of the TTS-wrapper under Windows (Editor).

5.24.4.3 `string Crosstales.RTVoice.Util.Config.TTS_WINDOWS_EDITOR_x86` `[static]`, `[get]`

Location of the TTS-wrapper (32bit) under Windows (Editor).


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Util/Config.cs

5.25 Crosstales.RTVoice.EditorIntegration.ConfigBase Class Reference

Base class for editor windows.

Inheritance diagram for Crosstales.RTVoice.EditorIntegration.ConfigBase:



Protected Member Functions

- void **showConfiguration** ()
- void **showHelp** ()
- void **showAbout** ()

Static Protected Member Functions

- static void **save** ()

5.25.1 Detailed Description

Base class for editor windows.

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Editor/Integration/ConfigBase.cs

5.26 Crosstales.RTVoice.EditorTask.ConfigLoader Class Reference

Loads the configuration at startup.

5.26.1 Detailed Description

Loads the configuration at startup.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Editor/Task/ConfigLoader.cs

5.27 Crosstales.RTVoice.EditorIntegration.ConfigPreferences Class Reference

Unity "Preferences" extension.

Inheritance diagram for Crosstales.RTVoice.EditorIntegration.ConfigPreferences:



Additional Inherited Members

5.27.1 Detailed Description

Unity "Preferences" extension.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Editor/Integration/ConfigPreferences.cs

5.28 Crosstales.RTVoice.EditorIntegration.ConfigWindow Class Reference

Editor window extension.

Inheritance diagram for Crosstales.RTVoice.EditorIntegration.ConfigWindow:



Public Member Functions

- delegate void **StopPlayback** ()
- void **OnEnable** ()
- void **OnDisable** ()
- void **OnGUI** ()
- void **OnInspectorUpdate** ()

Static Public Member Functions

- static void **ShowWindow** ()
- static void **ShowWindow** (int tab)

Events

- static StopPlayback **OnStopPlayback**

Additional Inherited Members

5.28.1 Detailed Description

Editor window extension.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Editor/Integration/ConfigWindow.cs

5.29 Crosstales.RTVoice.Util.Constants Class Reference

Collected constants of very general utility for the asset.

Inheritance diagram for Crosstales.RTVoice.Util.Constants:



Public Attributes

- const string ASSET_NAME = "RT-Voice PRO"
Name of the asset.
- const string ASSET_VERSION = "2019.2.0"
Version of the asset.
- const int ASSET_BUILD = 20190312
Build number of the asset.
- const string ASSET_PRO_URL = "https://www.assetstore.unity3d.com/#!/content/41068?aid=1011INGT&pubref=" + ASSET_NAME
URL of the PRO asset in UAS.
- const string ASSET_2019_URL = "https://www.assetstore.unity3d.com/#!/content/41068?aid=1011INGT&pubref=" + ASSET_NAME
URL of the 2019 asset in UAS.
- const string ASSET_3P_URL = "https://www.assetstore.unity3d.com/#!/list/42209-rt-voice-friends?aid=1011INGT&pubref=" + ASSET_NAME
URL of the 3rd party assets in UAS.
- const string ASSET_UPDATE_CHECK_URL = "https://www.crosstales.com/media/assets/rtvoice_versions.txt"
URL for update-checks of the asset
- const string ASSET_CONTACT = "rtvoice@crosstales.com"
Contact to the owner of the asset.
- const string ASSET_MANUAL_URL = "https://www.crosstales.com/media/data/assets/rtvoice/RTVoice-doc.pdf"
URL of the asset manual.
- const string ASSET_API_URL = "http://goo.gl/6w4Fy0"

- URL of the asset API.*
- const string ASSET_FORUM_URL = "http://goo.gl/Z6MZMI"
- URL of the asset forum.*
- const string ASSET_WEB_URL = "https://www.crosstales.com/en/portfolio/rtvoice/"
- URL of the asset in crosstales.*
- const string ASSET_VIDEO_PROMO = "https://youtu.be/iVhTWDLY7g8?list=PLgtonlOr6Tb41XTMee↵Z836tjHIKgoO84S"
- URL of the promotion video of the asset (Youtube).*
- const string ASSET_VIDEO_TUTORIAL = "https://youtu.be/OJyVgCmX3wU?list=PLgtonlOr6Tb41XTMee↵Z836tjHIKgoO84S"
- URL of the tutorial video of the asset (Youtube).*
- const string ASSET_3P_ADVENTURE_CREATOR = "https://www.assetstore.unity3d.com/#!/content/11896?aid=1011l↵NGT&pubref=" + ASSET_NAME
- URL of the 3rd party asset "Adventure Creator".*
- const string ASSET_3P_CINEMA_DIRECTOR = "https://www.assetstore.unity3d.com/#!/content/19779?aid=1011l↵NGT&pubref=" + ASSET_NAME
- URL of the 3rd party asset "Cinema Director".*
- const string ASSET_3P_DIALOG_SYSTEM = "https://www.assetstore.unity3d.com/#!/content/11672?aid=1011l↵NGT&pubref=" + ASSET_NAME
- URL of the 3rd party asset "Dialogue System".*
- const string ASSET_3P_LOCALIZED_DIALOGS = "https://www.assetstore.unity3d.com/#!/content/5020?aid=1011l↵NGT&pubref=" + ASSET_NAME
- URL of the 3rd party asset "Localized Dialogs".*
- const string ASSET_3P_LIPSYNC = "https://www.assetstore.unity3d.com/#!/content/32117?aid=1011l↵NGT&pubref=" + ASSET_NAME
- URL of the 3rd party asset "LipSync Pro".*
- const string ASSET_3P_NPC_CHAT = "https://www.assetstore.unity3d.com/#!/content/9723?aid=1011l↵NGT&pubref=" + ASSET_NAME
- URL of the 3rd party asset "NPC Chat".*
- const string ASSET_3P_QUEST_SYSTEM = "https://www.assetstore.unity3d.com/#!/content/63460?aid=1011l↵NGT&pubref=" + ASSET_NAME
- URL of the 3rd party asset "Quest System Pro".*
- const string ASSET_3P_SALSA = "https://www.assetstore.unity3d.com/#!/content/16944?aid=1011l↵NGT&pubref=" + ASSET_NAME
- URL of the 3rd party asset "SALSA".*
- const string ASSET_3P_SLATE = "https://www.assetstore.unity3d.com/#!/content/56558?aid=1011l↵NGT&pubref=" + ASSET_NAME
- URL of the 3rd party asset "SLATE".*
- const string ASSET_3P_DIALOGUE_ENGINE = "https://www.assetstore.unity3d.com/#!/content/42467?aid=1011l↵NGT&pubref=" + ASSET_NAME
- URL of the 3rd party asset "THE Dialogue Engine".*
- const string ASSET_3P_USEQUENCER = "https://www.assetstore.unity3d.com/#!/content/3666?aid=1011l↵NGT&pubref=" + ASSET_NAME
- URL of the 3rd party asset "uSequencer".*
- const string KEY_PREFIX = "RTVOICE_CFG_"
- const string KEY_ASSET_PATH = KEY_PREFIX + "ASSET_PATH"
- const string KEY_DEBUG = KEY_PREFIX + "DEBUG"
- const string KEY_AUDIOFILE_PATH = KEY_PREFIX + "AUDIOFILE_PATH"
- const string KEY_AUDIOFILE_AUTOMATIC_DELETE = KEY_PREFIX + "AUDIOFILE_AUTOMATIC_DE↵LETE"
- const string KEY_ENFORCE_32BIT_WINDOWS = KEY_PREFIX + "ENFORCE_32BIT_WINDOWS"
- const string KEY_ENSURE_NAME = KEY_PREFIX + "ENSURE_NAME"
- const bool DEFAULT_AUDIOFILE_AUTOMATIC_DELETE = true

- const bool **DEFAULT_ENFORCE_32BIT_WINDOWS** = false
- const string **DEFAULT_TTS_WINDOWS_BUILD** = @"/RTVoiceTTSWrapper.exe"
- const string **DEFAULT_TTS_MACOS** = "say"
- const string **DEFAULT_TTS_LINUX** = "espeak"
- const string **DEFAULT_TTS_LINUX_DATA** = ""
- const int **DEFAULT_TTS_KILL_TIME** = 7000
- const bool **DEFAULT_ENSURE_NAME** = true
- const string **RTVOICE_SCENE_OBJECT_NAME** = "RTVoice"

RTVoice prefab scene name.

Static Public Attributes

- static readonly System.DateTime **ASSET_CREATED** = new System.DateTime(2015, 4, 29)
Create date of the asset (YYYY, MM, DD).
- static readonly System.DateTime **ASSET_CHANGED** = new System.DateTime(2019, 3, 12)
Change date of the asset (YYYY, MM, DD).
- static readonly string **DEFAULT_AUDIOFILE_PATH** = Helper.ValidatePath(Application.temporaryCachePath)
- static string **TTS_WINDOWS_SUBPATH** = "Wrapper/Windows/RTVoiceTTSWrapper.exe"
Sub-path to the TTS-wrapper under Windows (Editor).
- static string **TTS_WINDOWS_x86_SUBPATH** = "Wrapper/Windows/RTVoiceTTSWrapper_x86.exe"
Sub-path to the TTS-wrapper (32bit) under Windows (Editor).
- static string **ESPEAK_FEMALE_MODIFIER** = "+f3"
Female modifier for eSpeak.
- static string **AUDIOFILE_PREFIX** = "rtvoice_"
Audio file prefix to identify the files.
- static float **SPEAK_CALL_SPEED** = 0.5f
Defines the speed of 'Speak'-calls in seconds.

Additional Inherited Members

5.29.1 Detailed Description

Collected constants of very general utility for the asset.

5.29.2 Member Data Documentation

- 5.29.2.1 const string Crosstales.RTVoice.Util.Constants.ASSET_2019_URL = "https://www.assetstore.unity3d.com/#!/content/41068?aid=1011INGT&pubref=" + ASSET_NAME

URL of the 2019 asset in UAS.

- 5.29.2.2 const string Crosstales.RTVoice.Util.Constants.ASSET_3P_ADVENTURE_CREATOR = "https://www.assetstore.unity3d.com/#!/content/11896?aid=1011INGT&pubref=" + ASSET_NAME

URL of the 3rd party asset "Adventure Creator".

5.29.2.3 `const string Crosstales.RTVoice.Util.Constants.ASSET_3P_CINEMA_DIRECTOR = "https://www.assetstore.unity3d.com/#!/content/19779?aid=1011INGT&pubref=" + ASSET_NAME`

URL of the 3rd party asset "Cinema Director".

5.29.2.4 `const string Crosstales.RTVoice.Util.Constants.ASSET_3P_DIALOG_SYSTEM = "https://www.assetstore.unity3d.com/#!/content/11672?aid=1011INGT&pubref=" + ASSET_NAME`

URL of the 3rd party asset "Dialogue System".

5.29.2.5 `const string Crosstales.RTVoice.Util.Constants.ASSET_3P_DIALOGUE_ENGINE = "https://www.assetstore.unity3d.com/#!/content/42467?aid=1011INGT&pubref=" + ASSET_NAME`

URL of the 3rd party asset "THE Dialogue Engine".

5.29.2.6 `const string Crosstales.RTVoice.Util.Constants.ASSET_3P_LIPSYNC = "https://www.assetstore.unity3d.com/#!/content/32117?aid=1011INGT&pubref=" + ASSET_NAME`

URL of the 3rd party asset "LipSync Pro".

5.29.2.7 `const string Crosstales.RTVoice.Util.Constants.ASSET_3P_LOCALIZED_DIALOGS = "https://www.assetstore.unity3d.com/#!/content/5020?aid=1011INGT&pubref=" + ASSET_NAME`

URL of the 3rd party asset "Localized Dialogs".

5.29.2.8 `const string Crosstales.RTVoice.Util.Constants.ASSET_3P_NPC_CHAT = "https://www.assetstore.unity3d.com/#!/content/9723?aid=1011INGT&pubref=" + ASSET_NAME`

URL of the 3rd party asset "NPC Chat".

5.29.2.9 `const string Crosstales.RTVoice.Util.Constants.ASSET_3P_QUEST_SYSTEM = "https://www.assetstore.unity3d.com/#!/content/63460?aid=1011INGT&pubref=" + ASSET_NAME`

URL of the 3rd party asset "Quest System Pro".

5.29.2.10 `const string Crosstales.RTVoice.Util.Constants.ASSET_3P_SALSA = "https://www.assetstore.unity3d.com/#!/content/16944?aid=1011INGT&pubref=" + ASSET_NAME`

URL of the 3rd party asset "SALSA".

5.29.2.11 `const string Crosstales.RTVoice.Util.Constants.ASSET_3P_SLATE = "https://www.assetstore.unity3d.com/#!/content/56558?aid=1011INGT&pubref=" + ASSET_NAME`

URL of the 3rd party asset "SLATE".

5.29.2.12 `const string Crosstales.RTVoice.Util.Constants.ASSET_3P_URL = "https://www.assetstore.unity3d.com/#!/list/42209-rt-voice-friends?aid=1011INGT&pubref=" + ASSET_NAME`

URL of the 3rd party assets in UAS.

5.29.2.13 `const string Crosstales.RTVoice.Util.Constants.ASSET_3P_USEQUENCER = "https://www.assetstore.unity3d.com/#!/content/3666?aid=1011INGT&pubref=" + ASSET_NAME`

URL of the 3rd party asset "uSequencer".

5.29.2.14 `const string Crosstales.RTVoice.Util.Constants.ASSET_API_URL = "http://goo.gl/6w4Fy0"`

URL of the asset API.

5.29.2.15 `const int Crosstales.RTVoice.Util.Constants.ASSET_BUILD = 20190312`

Build number of the asset.

5.29.2.16 `readonly System.DateTime Crosstales.RTVoice.Util.Constants.ASSET_CHANGED = new System.DateTime(2019, 3, 12)`
`[static]`

Change date of the asset (YYYY, MM, DD).

5.29.2.17 `const string Crosstales.RTVoice.Util.Constants.ASSET_CONTACT = "rtvoice@crosstales.com"`

Contact to the owner of the asset.

5.29.2.18 `readonly System.DateTime Crosstales.RTVoice.Util.Constants.ASSET_CREATED = new System.DateTime(2015, 4, 29)`
`[static]`

Create date of the asset (YYYY, MM, DD).

5.29.2.19 `const string Crosstales.RTVoice.Util.Constants.ASSET_FORUM_URL = "http://goo.gl/Z6MZMI"`

URL of the asset forum.

5.29.2.20 `const string Crosstales.RTVoice.Util.Constants.ASSET_MANUAL_URL = "https://www.crosstales.com/media/data/assets/rtvoice/RTVoice-doc.pdf"`

URL of the asset manual.

5.29.2.21 `const string Crosstales.RTVoice.Util.Constants.ASSET_NAME = "RT-Voice PRO"`

Name of the asset.

5.29.2.22 `const string Crosstales.RTVoice.Util.Constants.ASSET_PRO_URL = "https://www.assetstore.unity3d.com/#!/content/41068?aid=1011INGT&pubref=" + ASSET_NAME`

URL of the PRO asset in UAS.

5.29.2.23 `const string Crosstales.RTVoice.Util.Constants.ASSET_UPDATE_CHECK_URL = "https://www.crosstales.com/media/assets/rtvoice_versions.txt"`

URL for update-checks of the asset

5.29.2.24 `const string Crosstales.RTVoice.Util.Constants.ASSET_VERSION = "2019.2.0"`

Version of the asset.

5.29.2.25 `const string Crosstales.RTVoice.Util.Constants.ASSET_VIDEO_PROMO = "https://youtu.be/iVhTWDLY7g8?list=PLgtonlOr6Tb41XTMeeZ836tjHIKgOO84S"`

URL of the promotion video of the asset (Youtube).

5.29.2.26 `const string Crosstales.RTVoice.Util.Constants.ASSET_VIDEO_TUTORIAL = "https://youtu.be/OJyVgCmX3wU?list=PLgtonlOr6Tb41XTMeeZ836tjHIKgOO84S"`

URL of the tutorial video of the asset (Youtube).

5.29.2.27 `const string Crosstales.RTVoice.Util.Constants.ASSET_WEB_URL = "https://www.crosstales.com/en/portfolio/rtvoice/"`

URL of the asset in crosstales.

5.29.2.28 `string Crosstales.RTVoice.Util.Constants.AUDIOFILE_PREFIX = "rtvoice_" [static]`

Audio file prefix to identify the files.

5.29.2.29 `string Crosstales.RTVoice.Util.Constants.ESPEAK_FEMALE_MODIFIER = "+f3" [static]`

Female modifier for eSpeak.

5.29.2.30 `const string Crosstales.RTVoice.Util.Constants.RTVOICE_SCENE_OBJECT_NAME = "RTVoice"`

RTVoice prefab scene name.

5.29.2.31 float Crosstales.RTVoice.Util.Constants.SPEAK_CALL_SPEED = 0.5f [static]

Defines the speed of 'Speak'-calls in seconds.

5.29.2.32 string Crosstales.RTVoice.Util.Constants.TTS_WINDOWS_SUBPATH = "Wrapper/Windows/RTVoiceTTSWrapper.exe" [static]

Sub-path to the TTS-wrapper under Windows (Editor).

5.29.2.33 string Crosstales.RTVoice.Util.Constants.TTS_WINDOWS_x86_SUBPATH = "Wrapper/Windows/RTVoiceTTSWrapper_x86.exe" [static]

Sub-path to the TTS-wrapper (32bit) under Windows (Editor).

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Util/Constants.cs

5.30 Crosstales.Common.Util.CTPlayerPrefs Class Reference

Wrapper for the PlayerPrefs.

Static Public Member Functions

- static bool HasKey (string key)
Exists the key?
- static void DeleteAll ()
Deletes all keys.
- static void DeleteKey (string key)
Delete the key.
- static void Save ()
Saves all modifications.
- static string GetString (string key)
Allows to get a string from a key.
- static float GetFloat (string key)
Allows to get a float from a key.
- static int GetInt (string key)
Allows to get an int from a key.
- static bool GetBool (string key)
Allows to get a bool from a key.
- static System.DateTime GetDate (string key)
Allows to get a DateTime from a key.
- static void SetString (string key, string value)
Allows to set a string for a key.
- static void SetFloat (string key, float value)
Allows to set a float for a key.
- static void SetInt (string key, int value)
Allows to set an int for a key.
- static void SetBool (string key, bool value)
Allows to set a bool for a key.
- static void SetDate (string key, System.DateTime value)
Allows to set a DateTime for a key.

5.30.1 Detailed Description

Wrapper for the PlayerPrefs.

5.30.2 Member Function Documentation

5.30.2.1 `static void Crosstales.Common.Util.CTPlayerPrefs.DeleteAll () [static]`

Deletes all keys.

5.30.2.2 `static void Crosstales.Common.Util.CTPlayerPrefs.DeleteKey (string key) [static]`

Delete the key.

Parameters

<i>key</i>	Key to delete in the PlayerPrefs.
------------	-----------------------------------

5.30.2.3 `static bool Crosstales.Common.Util.CTPlayerPrefs.GetBool (string key) [static]`

Allows to get a bool from a key.

Parameters

<i>key</i>	Key for the PlayerPrefs.
------------	--------------------------

Returns

Value for the key.

5.30.2.4 `static System.DateTime Crosstales.Common.Util.CTPlayerPrefs.GetDate (string key) [static]`

Allows to get a DateTime from a key.

Parameters

<i>key</i>	Key for the PlayerPrefs.
------------	--------------------------

Returns

Value for the key.

5.30.2.5 static float Crosstales.Common.Util.CTPlayerPrefs.GetFloat (string *key*) [static]

Allows to get a float from a key.

Parameters

<i>key</i>	Key for the PlayerPrefs.
------------	--------------------------

Returns

Value for the key.

5.30.2.6 static int Crosstales.Common.Util.CTPlayerPrefs.GetInt (string *key*) [static]

Allows to get an int from a key.

Parameters

<i>key</i>	Key for the PlayerPrefs.
------------	--------------------------

Returns

Value for the key.

5.30.2.7 static string Crosstales.Common.Util.CTPlayerPrefs.GetString (string *key*) [static]

Allows to get a string from a key.

Parameters

<i>key</i>	Key for the PlayerPrefs.
------------	--------------------------

Returns

Value for the key.

5.30.2.8 static bool Crosstales.Common.Util.CTPlayerPrefs.HasKey (string *key*) [static]

Exists the key?

Parameters

<i>key</i>	Key for the PlayerPrefs.
------------	--------------------------

Returns

Value for the key.

5.30.2.9 static void Crosstales.Common.Util.CTPlayerPrefs.Save () [static]

Saves all modifications.

5.30.2.10 static void Crosstales.Common.Util.CTPlayerPrefs.SetBool (string *key*, bool *value*) [static]

Allows to set a bool for a key.

Parameters

<i>key</i>	Key for the PlayerPrefs.
<i>value</i>	Value for the PlayerPrefs.

5.30.2.11 static void Crosstales.Common.Util.CTPlayerPrefs.SetDate (string *key*, System.DateTime *value*) [static]

Allows to set a DateTime for a key.

Parameters

<i>key</i>	Key for the PlayerPrefs.
<i>value</i>	Value for the PlayerPrefs.

5.30.2.12 static void Crosstales.Common.Util.CTPlayerPrefs.SetFloat (string *key*, float *value*) [static]

Allows to set a float for a key.

Parameters

<i>key</i>	Key for the PlayerPrefs.
<i>value</i>	Value for the PlayerPrefs.

5.30.2.13 static void Crosstales.Common.Util.CTPlayerPrefs.SetInt (string *key*, int *value*) [static]

Allows to set an int for a key.

Parameters

<i>key</i>	Key for the PlayerPrefs.
<i>value</i>	Value for the PlayerPrefs.

5.30.2.14 static void Crosstales.Common.Util.CTPlayerPrefs.SetString (string *key*, string *value*) [static]

Allows to set a string for a key.

Parameters

<i>key</i>	Key for the PlayerPrefs.
<i>value</i>	Value for the PlayerPrefs.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/Scripts/Util/CTPlayerPrefs.cs

5.31 Crosstales.Common.Util.CTWebClient Class Reference

Specialized WebClient.

Inheritance diagram for Crosstales.Common.Util.CTWebClient:



Public Member Functions

- **CTWebClient** (int timeout, int connectionLimit=20)
- System.Net.WebRequest **CTGetWebRequest** (string uri)

Protected Member Functions

- override System.Net.WebRequest **GetWebRequest** (System.Uri uri)

Properties

- int Timeout [get, set]
Timeout in milliseconds
- int ConnectionLimit [get, set]
Connection limit for all WebClients

5.31.1 Detailed Description

Specialized WebClient.

5.31.2 Property Documentation

5.31.2.1 `int Crosstales.Common.Util.CTWebClient.ConnectionLimit` `[get]`, `[set]`

Connection limit for all WebClients

5.31.2.2 `int Crosstales.Common.Util.CTWebClient.Timeout` `[get]`, `[set]`

Timeout in milliseconds


The documentation for this class was generated from the following file:

- `D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/Scripts/Util/CTWebClient.cs`

5.32 Crosstales.RTVoice.Demo.Dialog Class Reference

Simple dialog system with TTS voices.

Inheritance diagram for `Crosstales.RTVoice.Demo.Dialog`:



Public Member Functions

- void **OnEnable** ()
- void **OnDisable** ()
- IEnumerator **DialogSequence** ()

Public Attributes

- string **CultureA** = "en"
- string **CultureB** = "en"
- float **RateA** = 1f
- float **RateB** = 1f
- float **PitchA** = 1f
- float **PitchB** = 1f
- float **VolumeA** = 1f
- float **VolumeB** = 1f
- Model.Enum.Gender **GenderA** = Model.Enum.Gender.UNKNOWN
- Model.Enum.Gender **GenderB** = Model.Enum.Gender.UNKNOWN
- AudioSource **AudioPersonA**
- AudioSource **AudioPersonB**
- Model.Enum.SpeakMode **ModeA** = Model.Enum.SpeakMode.Speak
- Model.Enum.SpeakMode **ModeB** = Model.Enum.SpeakMode.Speak
- string[] **DialogPersonA**
- string[] **DialogPersonB**
- string **CurrentDialogA** = string.Empty
- string **CurrentDialogB** = string.Empty
- bool **Running** = false

5.32.1 Detailed Description

Simple dialog system with TTS voices.

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Demo/Scripts/Dialog.cs

5.33 Crosstales.RTVoice.EditorUtil.EditorConfig Class Reference

Editor configuration for the asset.

Static Public Member Functions

- static void Reset ()
Resets all changable variables to their default value.
- static void Load ()
Loads all changable variables.
- static void Save ()
Saves all changable variables.

Static Public Attributes

- static bool UPDATE_CHECK = EditorConstants.DEFAULT_UPDATE_CHECK
Enable or disable update-checks for the asset.
- static bool REMINDER_CHECK = EditorConstants.DEFAULT_REMINDER_CHECK
Enable or disable reminder-checks for the asset.
- static bool TRACER = EditorConstants.DEFAULT_TRACER
Enable or disable anonymous tracer data.
- static bool PREFAB_AUTOLOAD = EditorConstants.DEFAULT_PREFAB_AUTOLOAD
Automatically load and add the prefabs to the scene.
- static bool HIERARCHY_ICON = EditorConstants.DEFAULT_HIERARCHY_ICON
Enable or disable the icon in the hierarchy.
- static bool isLoading = false
Is the configuration loaded?

Properties

- static string ASSET_PATH [get]
Returns the path to the asset inside the Unity project.
- static string PREFAB_PATH [get]
Returns the path of the prefabs.

5.33.1 Detailed Description

Editor configuration for the asset.

5.33.2 Member Function Documentation

5.33.2.1 `static void Crosstales.RTVoice.EditorUtil.EditorConfig.Load () [static]`

Loads all changable variables.

5.33.2.2 `static void Crosstales.RTVoice.EditorUtil.EditorConfig.Reset () [static]`

Resets all changable variables to their default value.

5.33.2.3 `static void Crosstales.RTVoice.EditorUtil.EditorConfig.Save () [static]`

Saves all changable variables.

5.33.3 Member Data Documentation

5.33.3.1 `bool Crosstales.RTVoice.EditorUtil.EditorConfig.HIERARCHY_ICON = EditorConstants.DEFAULT_HIERARCHY_ICON [static]`

Enable or disable the icon in the hierarchy.

5.33.3.2 `bool Crosstales.RTVoice.EditorUtil.EditorConfig.isLoaded = false [static]`

Is the configuration loaded?

5.33.3.3 `bool Crosstales.RTVoice.EditorUtil.EditorConfig.PREFAB_AUTOLOAD = EditorConstants.DEFAULT_PREFAB_AUTOLOAD [static]`

Automatically load and add the prefabs to the scene.

5.33.3.4 `bool Crosstales.RTVoice.EditorUtil.EditorConfig.REMINDER_CHECK = EditorConstants.DEFAULT_REMINDER_CHECK [static]`

Enable or disable reminder-checks for the asset.

5.33.3.5 `bool Crosstales.RTVoice.EditorUtil.EditorConfig.TRACER = EditorConstants.DEFAULT_TRACER [static]`

Enable or disable anonymous tracer data.

5.33.3.6 **bool** Crosstales.RTVoice.EditorUtil.EditorConfig.UPDATE_CHECK = EditorConstants.DEFAULT_UPDATE_CHECK
[static]

Enable or disable update-checks for the asset.

5.33.4 Property Documentation

5.33.4.1 **string** Crosstales.RTVoice.EditorUtil.EditorConfig.ASSET_PATH [static], [get]

Returns the path to the asset inside the Unity project.

Returns

The path to the asset inside the Unity project.

5.33.4.2 **string** Crosstales.RTVoice.EditorUtil.EditorConfig.PREFAB_PATH [static], [get]

Returns the path of the prefabs.

Returns

The path of the prefabs.

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Editor/Util/EditorConfig.cs

5.34 Crosstales.RTVoice.EditorUtil.EditorConstants Class Reference

Collected constants of very general utility for the asset.

Public Attributes

- const string **KEY_UPDATE_CHECK** = Util.Constants.KEY_PREFIX + "UPDATE_CHECK"
- const string **KEY_REMINDER_CHECK** = Util.Constants.KEY_PREFIX + "REMINDER_CHECK"
- const string **KEY_TRACER** = Util.Constants.KEY_PREFIX + "TRACER"
- const string **KEY_PREFAB_AUTOLOAD** = Util.Constants.KEY_PREFIX + "PREFAB_AUTOLOAD"
- const string **KEY_HIERARCHY_ICON** = Util.Constants.KEY_PREFIX + "HIERARCHY_ICON"
- const string **KEY_UPDATE_DATE** = Util.Constants.KEY_PREFIX + "UPDATE_DATE"
- const string **KEY_REMINDER_DATE** = Util.Constants.KEY_PREFIX + "REMINDER_DATE"
- const string **KEY_REMINDER_COUNT** = Util.Constants.KEY_PREFIX + "REMINDER_COUNT"
- const string **KEY_UNITY_DATE** = Util.Constants.KEY_PREFIX + "UNITY_DATE"
- const string **KEY_LAUNCH** = Util.Constants.KEY_PREFIX + "LAUNCH"
- const string **KEY_TRACER_DATE** = Util.Constants.KEY_PREFIX + "TRACER_DATE"
- const string **DEFAULT_ASSET_PATH** = "/Plugins/crosstales/RTVoice/"
- const bool **DEFAULT_UPDATE_CHECK** = true
- const bool **DEFAULT_UPDATE_OPEN_UAS** = false
- const bool **DEFAULT_REMINDER_CHECK** = true
- const bool **DEFAULT_TRACER** = true
- const bool **DEFAULT_PREFAB_AUTOLOAD** = false
- const bool **DEFAULT_HIERARCHY_ICON** = true

Static Public Attributes

- static string PREFAB_SUBPATH = "Prefabs/"
Sub-path to the prefabs.

Properties

- static string ASSET_URL [get]
Returns the URL of the asset in UAS.
- static string ASSET_ID [get]
Returns the ID of the asset in UAS.
- static System.Guid ASSET_UID [get]
Returns the UID of the asset.

5.34.1 Detailed Description

Collected constants of very general utility for the asset.

5.34.2 Member Data Documentation

5.34.2.1 string Crosstales.RTVoice.EditorUtil.EditorConstants.PREFAB_SUBPATH = "Prefabs/" [static]

Sub-path to the prefabs.

5.34.3 Property Documentation

5.34.3.1 string Crosstales.RTVoice.EditorUtil.EditorConstants.ASSET_ID [static],[get]

Returns the ID of the asset in UAS.

Returns

The ID of the asset in UAS.

5.34.3.2 System.Guid Crosstales.RTVoice.EditorUtil.EditorConstants.ASSET_UID [static],[get]

Returns the UID of the asset.

Returns

The UID of the asset.

5.34.3.3 string Crosstales.RTVoice.EditorUtil.EditorConstants.ASSET_URL [static], [get]

Returns the URL of the asset in UAS.

Returns

The URL of the asset in UAS.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Editor/Util/EditorConstants.cs

5.35 Crosstales.RTVoice.EditorUtil.EditorHelper Class Reference

Editor helper class.

Inheritance diagram for Crosstales.RTVoice.EditorUtil.EditorHelper:



Static Public Member Functions

- static void NoVoicesUI ()
Shows the "no voices found"-UI.
- static void InstantiatePrefab (string prefabName)
Instantiates a prefab.
- static void BannerOC ()
Shows a banner for "Online Check".

Public Attributes

- const int GO_ID = 20
Start index inside the "GameObject"-menu.
- const int MENU_ID = 11820
Start index inside the "Tools"-menu.

Properties

- static Texture2D **Logo_Asset** [get]
- static Texture2D **Logo_Asset_Small** [get]
- static Texture2D **Icon_Speak** [get]
- static Texture2D **Icon_Silence** [get]
- static Texture2D **Icon_Next** [get]
- static Texture2D **Icon_Previous** [get]
- static Texture2D **Store_AdventureCreator** [get]
- static Texture2D **Store_CinemaDirector** [get]
- static Texture2D **Store_DialogueSystem** [get]
- static Texture2D **Store_LDC** [get]
- static Texture2D **Store_LipSync** [get]
- static Texture2D **Store_NPC_Chat** [get]
- static Texture2D **Store_QuestSystem** [get]
- static Texture2D **Store_SALSA** [get]
- static Texture2D **Store_SLATE** [get]
- static Texture2D **Store_THE_Dialogue_Engine** [get]
- static Texture2D **Store_uSequencer** [get]
- static bool **isRTVoiceInScene** [get]

Checks if the 'RTVoice'-prefab is in the scene.

Additional Inherited Members

5.35.1 Detailed Description

Editor helper class.

5.35.2 Member Function Documentation

5.35.2.1 static void Crosstales.RTVoice.EditorUtil.EditorHelper.BannerOC () [static]

Shows a banner for "Online Check".

5.35.2.2 static void Crosstales.RTVoice.EditorUtil.EditorHelper.InstantiatePrefab (string *prefabName*) [static]

Instantiates a prefab.

Parameters

<i>prefabName</i>	Name of the prefab.
-------------------	---------------------

5.35.2.3 static void Crosstales.RTVoice.EditorUtil.EditorHelper.NoVoicesUI () [static]

Shows the "no voices found"-UI.

5.35.3 Member Data Documentation

5.35.3.1 `const int Crosstales.RTVoice.EditorUtil.EditorHelper.GO_ID = 20`

Start index inside the "GameObject"-menu.

5.35.3.2 `const int Crosstales.RTVoice.EditorUtil.EditorHelper.MENU_ID = 11820`

Start index inside the "Tools"-menu.

5.35.4 Property Documentation

5.35.4.1 `bool Crosstales.RTVoice.EditorUtil.EditorHelper.isRTVoiceInScene` `[static], [get]`

Checks if the 'RTVoice'-prefab is in the scene.

Returns

True if the 'RTVoice'-prefab is in the scene.

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔
Editor/Util/EditorHelper.cs

5.36 Crosstales.ExtensionMethods Class Reference

Various extension methods.

Static Public Member Functions

- static string CTTToTitleCase (this string str)
Extension method for strings. Converts a string to title case (first letter uppercase).
- static string CTReverse (this string str)
Extension method for strings. Reverses a string.
- static string CTReplace (this string str, string oldString, string newString, System.StringComparison comp=System.StringComparison.OrdinalIgnoreCase)
Extension method for strings. Case insensitive 'Replace'.
- static bool CTEquals (this string str, string toCheck, System.StringComparison comp=System.String↔
Comparison.OrdinalIgnoreCase)
Extension method for strings. Case insensitive 'Equals'.
- static bool CTContains (this string str, string toCheck, System.StringComparison comp=System.String↔
Comparison.OrdinalIgnoreCase)
Extension method for strings. Case insensitive 'Contains'.
- static bool CTContainsAny (this string str, string searchTerms, char splitChar= ' ')
Extension method for strings. Contains any given string.

- static bool CTContainsAll (this string str, string searchTerms, char splitChar= ' ')
Extension method for strings. Contains all given strings.
- static void CTShuffle< T > (this T[] array, int seed=0)
Extension method for Arrays. Shuffles an Array.
- static string CTDump< T > (this T[] array, string prefix="", string postfix="")
Extension method for Arrays. Dumps an array to a string.
- static string CTDump (this Quaternion[] array)
Extension method for Quaternion-Arrays. Dumps an array to a string.
- static string CTDump (this Vector2[] array)
Extension method for Vector2-Arrays. Dumps an array to a string.
- static string CTDump (this Vector3[] array)
Extension method for Vector3-Arrays. Dumps an array to a string.
- static string CTDump (this Vector4[] array)
Extension method for Vector4-Arrays. Dumps an array to a string.
- static string[] CTTToString< T > (this T[] array)
Extension method for Arrays. Generates a string array with all entries (via ToString).
- static void CTShuffle< T > (this System.Collections.Generic.IList< T > list, int seed=0)
Extension method for IList. Shuffles a List.
- static string CTDump< T > (this System.Collections.Generic.IList< T > list, string prefix="", string postfix="")
Extension method for IList. Dumps a list to a string.
- static string CTDump (this System.Collections.Generic.IList< Quaternion > list)
Extension method for Quaternion-IList. Dumps a list to a string.
- static string CTDump (this System.Collections.Generic.IList< Vector2 > list)
Extension method for Vector2-IList. Dumps a list to a string.
- static string CTDump (this System.Collections.Generic.IList< Vector3 > list)
Extension method for Vector3-IList. Dumps a list to a string.
- static string CTDump (this System.Collections.Generic.IList< Vector4 > list)
Extension method for Vector4-IList. Dumps a list to a string.
- static System.Collections.Generic.List< string > CTTToString< T > (this System.Collections.Generic.IList< T > list)
Extension method for IList. Generates a string list with all entries (via ToString).
- static string CTDump< K, V > (this System.Collections.Generic.IDictionary< K, V > dict, string prefix="", string postfix="")
Extension method for IDictionary. Dumps a dictionary to a string.
- static void CTAddRange< K, V > (this System.Collections.Generic.IDictionary< K, V > source, System.Collections.Generic.IDictionary< K, V > collection)
Extension method for IDictionary. Adds a dictionary to an existing one.
- static bool CTIsVisibleFrom (this Renderer renderer, Camera camera)
Extension method for Renderer. Determines if the renderer is visible from a certain camera.

5.36.1 Detailed Description

Various extension methods.

5.36.2 Member Function Documentation

- 5.36.2.1 static void Crosstales.ExtensionMethods.CTAddRange< K, V > (this System.Collections.Generic.IDictionary< K, V > *source*, System.Collections.Generic.IDictionary< K, V > *collection*) [static]

Extension method for IDictionary. Adds a dictionary to an existing one.

Parameters

<i>source</i>	IDictionary-instance.
<i>collection</i>	Dictionary to add.

5.36.2.2 `static bool Crosstales.ExtensionMethods.CTContains (this string str, string toCheck, System.StringComparison comp = System.StringComparison.OrdinalIgnoreCase) [static]`

Extension method for strings. Case insensitive 'Contains'.

Parameters

<i>str</i>	String-instance.
<i>toCheck</i>	String to check.
<i>comp</i>	StringComparison-method (default: StringComparison.OrdinalIgnoreCase, optional)

Returns

True if the string contains the given string.

5.36.2.3 `static bool Crosstales.ExtensionMethods.CTContainsAll (this string str, string searchTerms, char splitChar = ' ') [static]`

Extension method for strings. Contains all given strings.

Parameters

<i>str</i>	String-instance.
<i>searchTerms</i>	Search terms separated by the given split-character.
<i>splitChar</i>	Split-character (default: ' ', optional)

Returns

True if the string contains all parts of the given string.

5.36.2.4 `static bool Crosstales.ExtensionMethods.CTContainsAny (this string str, string searchTerms, char splitChar = ' ') [static]`

Extension method for strings. Contains any given string.

Parameters

<i>str</i>	String-instance.
<i>searchTerms</i>	Search terms separated by the given split-character.
<i>splitChar</i>	Split-character (default: ' ', optional)

Returns

True if the string contains any parts of the given string.

5.36.2.5 static string Crosstales.ExtensionMethods.CTDump (this Quaternion[] array) [static]

Extension method for Quaternion-Arrays. Dumps an array to a string.

Parameters

<i>array</i>	Quaternion-Array-instance to dump.
--------------	------------------------------------

Returns

String with lines for all array entries.

5.36.2.6 static string Crosstales.ExtensionMethods.CTDump (this Vector2[] array) [static]

Extension method for Vector2-Arrays. Dumps an array to a string.

Parameters

<i>array</i>	Vector2-Array-instance to dump.
--------------	---------------------------------

Returns

String with lines for all array entries.

5.36.2.7 static string Crosstales.ExtensionMethods.CTDump (this Vector3[] array) [static]

Extension method for Vector3-Arrays. Dumps an array to a string.

Parameters

<i>array</i>	Vector3-Array-instance to dump.
--------------	---------------------------------

Returns

String with lines for all array entries.

5.36.2.8 static string Crosstales.ExtensionMethods.CTDump (this Vector4[] array) [static]

Extension method for Vector4-Arrays. Dumps an array to a string.

Parameters

<i>array</i>	Vector4-Array-instance to dump.
--------------	---------------------------------

Returns

String with lines for all array entries.

5.36.2.9 `static string Crosstales.ExtensionMethods.CTDump (this System.Collections.Generic.ICollection< Quaternion > list)`
[static]

Extension method for Quaternion-ICollection. Dumps a list to a string.

Parameters

<i>list</i>	Quaternion-ICollection-instance to dump.
-------------	--

Returns

String with lines for all list entries.

5.36.2.10 `static string Crosstales.ExtensionMethods.CTDump (this System.Collections.Generic.ICollection< Vector2 > list)`
[static]

Extension method for Vector2-ICollection. Dumps a list to a string.

Parameters

<i>list</i>	Vector2-ICollection-instance to dump.
-------------	---------------------------------------

Returns

String with lines for all list entries.

5.36.2.11 `static string Crosstales.ExtensionMethods.CTDump (this System.Collections.Generic.ICollection< Vector3 > list)`
[static]

Extension method for Vector3-ICollection. Dumps a list to a string.

Parameters

<i>list</i>	Vector3-ICollection-instance to dump.
-------------	---------------------------------------

Returns

String with lines for all list entries.

5.36.2.12 `static string Crosstales.ExtensionMethods.CTDump (this System.Collections.Generic.ICollection< Vector4 > list)`
[static]

Extension method for Vector4-ICollection. Dumps a list to a string.

Parameters

<i>list</i>	Vector4-ICollection-instance to dump.
-------------	---------------------------------------

Returns

String with lines for all list entries.

5.36.2.13 `static string Crosstales.ExtensionMethods.CTDump< K, V > (this System.Collections.Generic.IDictionary< K, V > dict, string prefix = " ", string postfix = " ")` [static]

Extension method for IDictionary. Dumps a dictionary to a string.

Parameters

<i>dict</i>	IDictionary-instance to dump.
<i>prefix</i>	Prefix for every element (default: empty, optional).
<i>postfix</i>	Postfix for every element (default: empty, optional).

Returns

String with lines for all dictionary entries.

5.36.2.14 `static string Crosstales.ExtensionMethods.CTDump< T > (this T[] array, string prefix = " ", string postfix = " ")` [static]

Extension method for Arrays. Dumps an array to a string.

Parameters

<i>array</i>	Array-instance to dump.
<i>prefix</i>	Prefix for every element (default: empty, optional).
<i>postfix</i>	Postfix for every element (default: empty, optional).

Returns

String with lines for all array entries.

5.36.2.15 static string **Crosstales.ExtensionMethods.CTDump**< T > (this System.Collections.Generic.ICollection< T > *list*, string *prefix* = " ", string *postfix* = " ") [static]

Extension method for ICollection. Dumps a list to a string.

Parameters

<i>list</i>	ICollection-instance to dump.
<i>prefix</i>	Prefix for every element (default: empty, optional).
<i>postfix</i>	Postfix for every element (default: empty, optional).

Returns

String with lines for all list entries.

5.36.2.16 static bool **Crosstales.ExtensionMethods.CTEquals** (this string *str*, string *toCheck*, System.StringComparison *comp* = System.StringComparison.OrdinalIgnoreCase) [static]

Extension method for strings. Case insensitive 'Equals'.

Parameters

<i>str</i>	String-instance.
<i>toCheck</i>	String to check.
<i>comp</i>	StringComparison-method (default: StringComparison.OrdinalIgnoreCase, optional)

Returns

True if the string contains the given string.

5.36.2.17 static bool **Crosstales.ExtensionMethods.CTIsVisibleFrom** (this Renderer *renderer*, Camera *camera*) [static]

Extension method for Renderer. Determines if the renderer is visible from a certain camera.

Parameters

<i>renderer</i>	Renderer to test the visibility.
<i>camera</i>	Camera for the test.

Returns

True if the renderer is visible by the given camera.

5.36.2.18 `static string Crosstales.ExtensionMethods.CTReplace (this string str, string oldString, string newString, System.StringComparison comp = System.StringComparison.OrdinalIgnoreCase)`
[static]

Extension method for strings. Case insensitive 'Replace'.

Parameters

<i>str</i>	String-instance.
<i>oldString</i>	String to replace.
<i>newString</i>	New replacement string.
<i>comp</i>	StringComparison-method (default: StringComparison.OrdinalIgnoreCase, optional)

Returns

Replaced string.

5.36.2.19 `static string Crosstales.ExtensionMethods.CTReverse (this string str)` [static]

Extension method for strings. Reverses a string.

Parameters

<i>str</i>	String-instance.
------------	------------------

Returns

Reversed string.

5.36.2.20 `static void Crosstales.ExtensionMethods.CTShuffle< T > (this T[] array, int seed = 0)` [static]

Extension method for Arrays. Shuffles an Array.

Parameters

<i>array</i>	Array-instance to shuffle.
<i>seed</i>	Seed for the PRNG (default: 0 (=standard), optional)

5.36.2.21 `static void Crosstales.ExtensionMethods.CTShuffle< T > (this System.Collections.Generic.IList< T > list, int seed = 0)` [static]

Extension method for IList. Shuffles a List.

Parameters

<i>list</i>	IList-instance to shuffle.
<i>seed</i>	Seed for the PRNG (default: 0 (=standard), optional)

5.36.2.22 `static string [] Crosstales.ExtensionMethods.CTToString< T > (this T[] array) [static]`

Extension method for Arrays. Generates a string array with all entries (via ToString).

Parameters

<i>array</i>	Array-instance to ToString.
--------------	-----------------------------

Returns

String array with all entries (via ToString).

5.36.2.23 `static System.Collections.Generic.List<string> Crosstales.ExtensionMethods.CTToString< T > (this System.Collections.Generic.IList< T > list) [static]`

Extension method for IList. Generates a string list with all entries (via ToString).

Parameters

<i>list</i>	IList-instance to ToString.
-------------	-----------------------------

Returns

String list with all entries (via ToString).

5.36.2.24 `static string Crosstales.ExtensionMethods.CTToTitleCase (this string str) [static]`

Extension method for strings. Converts a string to title case (first letter uppercase).

Parameters

<i>str</i>	String-instance.
------------	------------------

Returns

Converted string in title case.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↵ Scripts/ExtensionMethods.cs

5.37 Crosstales.Common.Util.FFTAnalyzer Class Reference

FFT analyzer for an audio channel.

Inheritance diagram for Crosstales.Common.Util.FFTAnalyzer:



Public Member Functions

- void **Update** ()

Public Attributes

- float[] Samples = new float[256]
Array for the samples. More samples mean better accuracy but it also needs more performance (default: 256).
- int Channel = 0
summary> FFT-algorithm to analyze the audio (default: BlackmanHarris).
- FFTWindow **FFTMode** = FFTWindow.BlackmanHarris

5.37.1 Detailed Description

FFT analyzer for an audio channel.

5.37.2 Member Data Documentation

5.37.2.1 int Crosstales.Common.Util.FFTAnalyzer.Channel = 0

summary> FFT-algorithm to analyze the audio (default: BlackmanHarris).

5.37.2.2 float[] Crosstales.Common.Util.FFTAnalyzer.Samples = new float[256]

Array for the samples. More samples mean better accuracy but it also needs more performance (default: 256).

summary> Analyzed channel (0 = right, 1 = left, default: 0).


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ Scripts/Util/FFTAnalyzer.cs

5.38 Crosstales.UI.Util.FPSDisplay Class Reference

Simple FPS-Counter.

Inheritance diagram for Crosstales.UI.Util.FPSDisplay:



Public Member Functions

- void **Update** ()

Public Attributes

- Text FPS
Text component to display the FPS.

5.38.1 Detailed Description

Simple FPS-Counter.

5.38.2 Member Data Documentation

5.38.2.1 Text Crosstales.UI.Util.FPSDisplay.FPS

Text component to display the FPS.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ UI/Scripts/Util/FPSDisplay.cs

5.39 Crosstales.RTVoice.EditorUtil.GAApi Class Reference

GA-wrapper API.

Inheritance diagram for Crosstales.RTVoice.EditorUtil.GAApi:



Static Public Member Functions

- static void Event (string category, string action, string label="", int value=0)
Tracks an event from the asset.

Additional Inherited Members

5.39.1 Detailed Description

GA-wrapper API.

5.39.2 Member Function Documentation

5.39.2.1 static void Crosstales.RTVoice.EditorUtil.GAApi.Event (string *category*, string *action*, string *label* = " ", int *value* = 0) [static]

Tracks an event from the asset.

Parameters

<i>category</i>	Specifies the event category.
<i>action</i>	Specifies the event action.
<i>label</i>	Specifies the event label.
<i>value</i>	Specifies the event value.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Editor/Util/GAApi.cs

5.40 Crosstales.RTVoice.Demo.GUIAudioFilter Class Reference

Simple GUI for audio filters.

Inheritance diagram for Crosstales.RTVoice.Demo.GUIAudioFilter:



Public Member Functions

- void **Start** ()
- void **ResetFilters** ()
- void **ReverbFilterDropdownChanged** (System.Int32 index)
- void **ChorusFilterEnabled** (bool enabled)
- void **EchoFilterEnabled** (bool enabled)
- void **DistortionFilterEnabled** (bool enabled)
- void **DistortionFilterChanged** (float value)
- void **LowPassFilterEnabled** (bool enabled)
- void **LowPassFilterChanged** (float value)
- void **HighPassFilterEnabled** (bool enabled)
- void **HighPassFilterChanged** (float value)
- void **VolumeChanged** (float value)
- void **PitchChanged** (float value)

Public Attributes

- AudioSource **Source**
- AudioReverbFilter **ReverbFilter**
- AudioChorusFilter **ChorusFilter**
- AudioEchoFilter **EchoFilter**
- AudioDistortionFilter **DistortionFilter**
- AudioLowPassFilter **LowPassFilter**
- AudioHighPassFilter **HighPassFilter**
- Text **Distortion**
- Text **Lowpass**
- Text **Highpass**
- Text **Volume**
- Text **Pitch**
- Dropdown **ReverbFilterDropdown**

5.40.1 Detailed Description

Simple GUI for audio filters.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Demo/Scripts/GUIAudioFilter.cs

5.41 Crosstales.RTVoice.Demo.GUIDialog Class Reference

Simple GUI for runtime dialogs with all available OS voices.

Inheritance diagram for Crosstales.RTVoice.Demo.GUIDialog:



Public Member Functions

- void **Start** ()
- void **Update** ()
- void **StartDialog** ()
- void **Silence** ()
- void **ChangeRateA** (float value)
- void **ChangeRateB** (float value)
- void **ChangePitchA** (float value)
- void **ChangePitchB** (float value)
- void **ChangeVolumeA** (float value)
- void **ChangeVolumeB** (float value)
- void **GenderAChanged** (System.Int32 index)
- void **GenderBChanged** (System.Int32 index)

Public Attributes

- Dialog **DialogScript**
- Color32 **SpeakerColor** = new Color32(0, 255, 0, 192)
- Image **PanelPersonA**
- Image **PanelPersonB**
- Text **PersonA**
- Text **PersonB**

5.41.1 Detailed Description

Simple GUI for runtime dialogs with all available OS voices.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Demo/Scripts/GUIDialog.cs

5.42 Crosstales.RTVoice.Demo.GUIMain Class Reference

Main GUI component for all demo scenes.

Inheritance diagram for Crosstales.RTVoice.Demo.GUIMain:



Public Member Functions

- void **Start** ()
- void **Update** ()
- void **OnEnable** ()
- void **OnDisable** ()
- void **OpenAssetURL** ()
- void **OpenCTURL** ()
- void **Silence** ()
- void **Quit** ()

Public Attributes

- Text **Name**
- Text **Version**
- Text **Scene**
- GameObject **NoVoices**
- Text **Errors**

5.42.1 Detailed Description

Main GUI component for all demo scenes.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Demo/Scripts/GUIMain.cs

5.43 Crosstales.RTVoice.Demo.GUIMultiAudioFilter Class Reference

Simple GUI for audio filters on multiple objects.

Inheritance diagram for Crosstales.RTVoice.Demo.GUIMultiAudioFilter:



Public Member Functions

- void **Start** ()
- void **ResetFilters** ()
- void **ClearFilters** ()
- void **ReverbFilterDropdownChanged** (System.Int32 index)
- void **ChorusFilterEnabled** (bool enabled)
- void **EchoFilterEnabled** (bool enabled)
- void **DistortionFilterEnabled** (bool enabled)
- void **DistortionFilterChanged** (float value)
- void **LowPassFilterEnabled** (bool enabled)
- void **LowPassFilterChanged** (float value)
- void **HighPassFilterEnabled** (bool enabled)
- void **HighPassFilterChanged** (float value)
- void **VolumeChanged** (float value)
- void **PitchChanged** (float value)

Public Attributes

- System.Collections.Generic.List< AudioSource > **Sources** = new System.Collections.Generic.List<AudioSource>()
- System.Collections.Generic.List< AudioReverbFilter > **ReverbFilters** = new System.Collections.Generic.List<AudioReverbFilter>()
- System.Collections.Generic.List< AudioChorusFilter > **ChorusFilters** = new System.Collections.Generic.List<AudioChorusFilter>()
- System.Collections.Generic.List< AudioEchoFilter > **EchoFilters** = new System.Collections.Generic.List<AudioEchoFilter>()
- System.Collections.Generic.List< AudioDistortionFilter > **DistortionFilters** = new System.Collections.Generic.List<AudioDistortionFilter>()
- System.Collections.Generic.List< AudioLowPassFilter > **LowPassFilters** = new System.Collections.Generic.List<AudioLowPassFilter>()
- System.Collections.Generic.List< AudioHighPassFilter > **HighPassFilters** = new System.Collections.Generic.List<AudioHighPassFilter>()
- Text **Distortion**
- Text **Lowpass**
- Text **Highpass**
- Text **Volume**
- Text **Pitch**
- Dropdown **ReverbFilterDropdown**

5.43.1 Detailed Description

Simple GUI for audio filters on multiple objects.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstailes/RTVoice/Demo/Scripts/GUIMultiAudioFilter.cs

5.44 Crosstailes.RTVoice.Demo.GUIScenes Class Reference

Main GUI scene manager for all demo scenes.

Inheritance diagram for Crosstailes.RTVoice.Demo.GUIScenes:



Public Member Functions

- void **LoadPrevoiusScene** ()
- void **LoadNextScene** ()

Public Attributes

- string **PreviousScene**
- string **PreviousSceneWebGL**
- string **NextScene**
- string **NextSceneWebGL**

5.44.1 Detailed Description

Main GUI scene manager for all demo scenes.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Demo/Scripts/GUIScenes.cs

5.45 Crosstales.RTVoice.Demo.GUISpeech Class Reference

Simple GUI for runtime TTS with all available OS voices.

Inheritance diagram for Crosstales.RTVoice.Demo.GUISpeech:



Public Member Functions

- void **Start** ()
- void **Update** ()
- void **OnEnable** ()
- void **OnDisable** ()
- void **OnDestroy** ()
- void **Silence** ()
- void **ChangeRate** (float rate)
- void **ChangeVolume** (float volume)
- void **ChangePitch** (float pitch)
- void **ChangeNative** (bool native)
- void **ChangeMaryTTS** (bool maryTTS)
- void **GenderChanged** (System.Int32 index)

Public Attributes

- bool **StartAsNative** = false
- GUIMultiAudioFilter **AudioFilter**
- GameObject **ItemPrefab**
- GameObject **Target**
- Scrollbar **Scroll**
- int **ColumnCount** = 1
- Vector2 **SpaceWidth** = new Vector2(8, 8)
- Vector2 **SpaceHeight** = new Vector2(8, 8)
- InputField **Input**
- InputField **Culture**
- Text **Cultures**
- Toggle **MaryToogle**
- Text **Voices**

Static Public Attributes

- static float **Rate** = 1f
- static float **Pitch** = 1f
- static float **Volume** = 1f
- static bool **isNative** = false

5.45.1 Detailed Description

Simple GUI for runtime TTS with all available OS voices.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Demo/Scripts/GUISpeech.cs

5.46 Crosstales.RTVoice.Util.Helper Class Reference

Various helper functions.

Inheritance diagram for Crosstales.RTVoice.Util.Helper:



Static Public Member Functions

- static Model.Enum.Gender StringToGender (string gender)
Converts a string to a Gender.
- static Model.Enum.Gender AppleVoiceNameToGender (string voiceName)
Converts an Apple voice name to a Gender.
- static Model.Enum.Gender WSAVoiceNameToGender (string voiceName)
Converts an WSA voice name to a Gender.
- static string CleanText (string text, bool removeTags=true, bool clearSpaces=true, bool clearLine↵ Endings=true)
Cleans a given text to contain only letters or digits.
- static string MarkSpokenText (string[] speechTextArray, int wordIndex, bool markAllSpokenWords=false, string markPrefix="<color=green>", string markPostfix="</color>")
Marks the current word or all spoken words from a given text array.

Static Public Attributes

- static System.Collections.Generic.Dictionary< int, string > **LocaleCodes** = new System.Collections.↵ Generic.Dictionary<int, string>(161)

Properties

- static bool hasBuiltInTTS [get]
Checks if the current platform has built-in TTS.
- static Model.Enum.ProviderType CurrentProviderType [get]
The current provider type.

Additional Inherited Members

5.46.1 Detailed Description

Various helper functions.

5.46.2 Member Function Documentation

5.46.2.1 static Model.Enum.Gender Crosstales.RTVoice.Util.Helper.AppleVoiceNameToGender (string voiceName) [static]

Converts an Apple voice name to a Gender.

Parameters

<i>voiceName</i>	Voice name.
------------------	-------------

Returns

Gender from the given Apple voice name.

5.46.2.2 `static string Crosstales.RTVoice.Util.Helper.CleanText (string text, bool removeTags = true, bool clearSpaces = true, bool clearLineEndings = true) [static]`

Cleans a given text to contain only letters or digits.

Parameters

<i>text</i>	Text to clean.
<i>removeTags</i>	Removes tags from text (default: true, optional).
<i>clearSpaces</i>	Clears multiple spaces from text (default: true, optional).
<i>clearLineEndings</i>	Clears line endings from text (default: true, optional).

Returns

Clean text with only letters and digits.

5.46.2.3 `static string Crosstales.RTVoice.Util.Helper.MarkSpokenText (string[] speechTextArray, int wordIndex, bool markAllSpokenWords = false, string markPrefix = "<color=green>", string markPostfix = "</color>") [static]`

Marks the current word or all spoken words from a given text array.

Parameters

<i>speechTextArray</i>	Array with all text fragments
<i>wordIndex</i>	Current word index
<i>markAllSpokenWords</i>	Mark the spoken words (default: false, optional)
<i>markPrefix</i>	Prefix for every marked word (default: green, optional)
<i>markPostfix</i>	Postfix for every marked word (default: green, optional)

Returns

Marked current word or all spoken words.

5.46.2.4 `static Model.Enum.Gender Crosstales.RTVoice.Util.Helper.StringToGender (string gender) [static]`

Converts a string to a Gender.

Parameters

<i>gender</i>	Gender as text.
---------------	-----------------

Returns

Gender from the given string.

5.46.2.5 static Model.Enum.Gender Crosstales.RTVoice.Util.Helper.WSAVoiceNameToGender (string *voiceName*)
[static]

Converts an WSA voice name to a Gender.

Parameters

<i>voiceName</i>	Voice name.
------------------	-------------

Returns

Gender from the given WSA voice name.

5.46.3 Property Documentation

5.46.3.1 Model.Enum.ProviderType Crosstales.RTVoice.Util.Helper.CurrentProviderType [static], [get]

The current provider type.

Returns

Current provider type.

5.46.3.2 bool Crosstales.RTVoice.Util.Helper.hasBuiltInTTS [static], [get]

Checks if the current platform has built-in TTS.

Returns

True if the current platform has built-in TTS.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Scripts/Util/Helper.cs

5.47 Crosstales.RTVoice.Demo.Util.iOSController Class Reference

Enables MaryTTS on iOS for specific scenes.

Inheritance diagram for Crosstales.RTVoice.Demo.Util.iOSController:



Public Member Functions

- void **Start** ()
- void **OnDestroy** ()

5.47.1 Detailed Description

Enables MaryTTS on iOS for specific scenes.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Demo/Scripts/Util/iOSController.cs

5.48 Crosstales.RTVoice.Provider.IVoiceProvider Interface Reference

Interface for all voice providers.

Inheritance diagram for Crosstales.RTVoice.Provider.IVoiceProvider:



Public Member Functions

- void **Silence** ()
Silence all active TTS-providers.
- void **Silence** (string uid)
Silence the current TTS-provider (native mode).
- IEnumerator **SpeakNative** (Model.Wrapper wrapper)
The current provider speaks a text with a given voice (native mode).
- IEnumerator **Speak** (Model.Wrapper wrapper)
The current provider speaks a text with a given voice.
- IEnumerator **Generate** (Model.Wrapper wrapper)
The current provider generates an audio file from a text with a given voice.

Properties

- string AudioFileExtension [get]
Returns the extension of the generated audio files.
- AudioType AudioFileType [get]
Returns the type of the generated audio files.
- string DefaultVoiceName [get]
Returns the default voice name of the current TTS-provider.
- System.Collections.Generic.List< Model.Voice > Voices [get]
Get all available voices from the current TTS-provider and fills it into a given list.
- int MaxTextLength [get]
Maximal length of the speech text (in characters).
- bool isWorkingInEditor [get]
Indicates if this provider is working directly inside the Unity Editor (without 'Play'-mode).
- bool isSpeakNativeSupported [get]
Indicates if this provider is supporting SpeakNative.
- bool isSpeakSupported [get]
Indicates if this provider is supporting Speak.
- bool isPlatformSupported [get]
Indicates if this provider is supporting the current platform.
- bool isSSMLSupported [get]
Indicates if this provider is supporting SSML.
- bool isOnlineService [get]
Indicates if this provider is an online service like MaryTTS or AWS Polly.
- bool hasCoRoutines [get]
Indicates if this provider uses co-routines.
- System.Collections.Generic.List< string > Cultures [get]
Get all available cultures from the current provider (ISO 639-1).

5.48.1 Detailed Description

Interface for all voice providers.

5.48.2 Member Function Documentation

5.48.2.1 IEnumerator Crosstales.RTVoice.Provider.IVoiceProvider.Generate (Model.Wrapper wrapper)

The current provider generates an audio file from a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implemented in Crosstales.RTVoice.Provider.VoiceProviderWindowsLegacy, Crosstales.RTVoice.Provider.VoiceProviderLinux, Crosstales.RTVoice.Provider.VoiceProviderMacOS, Crosstales.RTVoice.Provider.VoiceProviderIOS, Crosstales.RTVoice.Provider.VoiceProviderAndroid, Crosstales.RTVoice.Provider.BaseVoiceProvider, Crosstales.RTVoice.AWSPolly.VoiceProviderAWS, Crosstales.RTVoice.Provider.BaseCustomVoiceProvider, Crosstales.RTVoice.Provider.VoiceProviderWindows, Crosstales.RTVoice.Provider.VoiceProviderMary,

Crosstales.RTVoice.Provider.VoiceProviderWSA, Crosstales.RTVoice.VoiceProviderExample, and Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynth.

5.48.2.2 void Crosstales.RTVoice.Provider.IVoiceProvider.Silence ()

Silence all active TTS-providers.

Implemented in Crosstales.RTVoice.Provider.VoiceProviderAndroid, Crosstales.RTVoice.Provider.VoiceProviderMary, Crosstales.RTVoice.Provider.VoiceProviderIOS, Crosstales.RTVoice.Provider.BaseCustomVoiceProvider, Crosstales.RTVoice.Provider.BaseVoiceProvider, and Crosstales.RTVoice.Provider.VoiceProviderWSA.

5.48.2.3 void Crosstales.RTVoice.Provider.IVoiceProvider.Silence (string uid)

Silence the current TTS-provider (native mode).

Parameters

<i>uid</i>	UID of the speaker
------------	--------------------

Implemented in Crosstales.RTVoice.Provider.BaseVoiceProvider, and Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.

5.48.2.4 IEnumerable Crosstales.RTVoice.Provider.IVoiceProvider.Speak (Model.Wrapper wrapper)

The current provider speaks a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implemented in Crosstales.RTVoice.AWSPolly.VoiceProviderAWS, Crosstales.RTVoice.Provider.VoiceProviderWindowsLegacy, Crosstales.RTVoice.Provider.VoiceProviderIOS, Crosstales.RTVoice.Provider.BaseVoiceProvider, Crosstales.RTVoice.Provider.BaseCustomVoiceProvider, Crosstales.RTVoice.Provider.VoiceProviderLinux, Crosstales.RTVoice.Provider.VoiceProviderMacOS, Crosstales.RTVoice.Provider.VoiceProviderAndroid, Crosstales.RTVoice.VoiceProviderExample, Crosstales.RTVoice.Provider.VoiceProviderWindows, Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynth, Crosstales.RTVoice.Provider.VoiceProviderMary, and Crosstales.RTVoice.Provider.VoiceProviderWSA.

5.48.2.5 IEnumerable Crosstales.RTVoice.Provider.IVoiceProvider.SpeakNative (Model.Wrapper wrapper)

The current provider speaks a text with a given voice (native mode).

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implemented in Crosstales.RTVoice.AWSPolly.VoiceProviderAWS, Crosstales.RTVoice.Provider.VoiceProviderIOS,

OS, Crosstales.RTVoice.VoiceProviderExample, Crosstales.RTVoice.Provider.BaseVoiceProvider, Crosstales.RTVoice.Provider.BaseCustomVoiceProvider, Crosstales.RTVoice.Provider.VoiceProviderWindowsLegacy, Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynth, Crosstales.RTVoice.Provider.VoiceProviderMary, Crosstales.RTVoice.Provider.VoiceProviderLinux, Crosstales.RTVoice.Provider.VoiceProviderWindows, Crosstales.RTVoice.Provider.VoiceProviderWSA, Crosstales.RTVoice.Provider.VoiceProviderMacOS, and Crosstales.RTVoice.Provider.VoiceProviderAndroid.

5.48.3 Property Documentation

5.48.3.1 `string Crosstales.RTVoice.Provider.IVoiceProvider.AudioFileExtension` [get]

Returns the extension of the generated audio files.

Returns

Extension of the generated audio files.

5.48.3.2 `AudioType Crosstales.RTVoice.Provider.IVoiceProvider.AudioFileType` [get]

Returns the type of the generated audio files.

Returns

Type of the generated audio files.

5.48.3.3 `System.Collections.Generic.List<string> Crosstales.RTVoice.Provider.IVoiceProvider.Cultures` [get]

Get all available cultures from the current provider (ISO 639-1).

Returns

All available cultures (alphabetically ordered by 'Culture') as a list.

5.48.3.4 `string Crosstales.RTVoice.Provider.IVoiceProvider.DefaultVoiceName` [get]

Returns the default voice name of the current TTS-provider.

Returns

Default voice name of the current TTS-provider.

5.48.3.5 `bool Crosstales.RTVoice.Provider.IVoiceProvider.hasCoRoutines` [get]

Indicates if this provider uses co-routines.

Returns

Provider uses co-routines.

5.48.3.6 bool Crosstales.RTVoice.Provider.IVoiceProvider.isOnlineService [get]

Indicates if this provider is an online service like MaryTTS or AWS Polly.

Returns

Provider is an online service.

5.48.3.7 bool Crosstales.RTVoice.Provider.IVoiceProvider.isPlatformSupported [get]

Indicates if this provider is supporting the current platform.

Returns

Provider supports current platform.

5.48.3.8 bool Crosstales.RTVoice.Provider.IVoiceProvider.isSpeakNativeSupported [get]

Indicates if this provider is supporting SpeakNative.

Returns

Provider supports SpeakNative.

5.48.3.9 bool Crosstales.RTVoice.Provider.IVoiceProvider.isSpeakSupported [get]

Indicates if this provider is supporting Speak.

Returns

Provider supports Speak.

5.48.3.10 bool Crosstales.RTVoice.Provider.IVoiceProvider.isSSMLSupported [get]

Indicates if this provider is supporting SSML.

Returns

Provider supports SSML.

5.48.3.11 bool Crosstales.RTVoice.Provider.IVoiceProvider.isWorkingInEditor [get]

Indicates if this provider is working directly inside the Unity Editor (without 'Play'-mode).

Returns

The provider is working directly inside the Unity Editor.

5.48.3.12 `int Crosstales.RTVoice.Provider.IVoiceProvider.MaxLength` [get]

Maximal length of the speech text (in characters).

Returns

The maximal length of the speech text.

5.48.3.13 `System.Collections.Generic.List<Model.Voice> Crosstales.RTVoice.Provider.IVoiceProvider.Voices` [get]

Get all available voices from the current TTS-provider and fills it into a given list.

Returns

All available voices (alphabetically ordered by 'Name') as a list.

The documentation for this interface was generated from the following file:

- `D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Provider/IVoiceProvider.cs`

5.49 Crosstales.RTVoice.EditorTask.Launch Class Reference

Show the configuration window on the first launch.

5.49.1 Detailed Description

Show the configuration window on the first launch.


The documentation for this class was generated from the following file:

- `D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Editor/Task/Launch.cs`

5.50 Crosstales.RTVoice.LiveSpeaker Class Reference

Wrapper of the main component from RTVoice for MonoBehaviour-access (like "SendMessage").

Inheritance diagram for Crosstales.RTVoice.LiveSpeaker:



Public Member Functions

- void SpeakNative (Model.Wrapper wrapper)
Speaks a text with a given wrapper -> native mode.
- void SpeakNative (string args)
Speaks a text with a given array of arguments (native mode).
- void SpeakNative (string[] args)
Speaks a text with a given array of arguments (native mode).
- void Speak (Model.Wrapper wrapper)
Speaks a text with a given wrapper.
- void Speak (string args)
Speaks a text with a given array of arguments.
- void Speak (string[] args)
Speaks a text with a given array of arguments.
- void Silence ()
Silence all active TTS-voices.
- void SetVoices (string voices)
Sets all voices from iOS.
- void WordSpoken (string word)
The current spoken word from iOS.
- void SetState (string state)
Sets the state from iOS.

5.50.1 Detailed Description

Wrapper of the main component from RTVoice for MonoBehaviour-access (like "SendMessage").

5.50.2 Member Function Documentation

5.50.2.1 void Crosstales.RTVoice.LiveSpeaker.SetState (string state)

Sets the state from iOS.

Parameters

<i>voices</i>	State from iOS.
---------------	-----------------

5.50.2.2 void Crosstales.RTVoice.LiveSpeaker.SetVoices (string voices)

Sets all voices from iOS.

Parameters

<i>voices</i>	All voices from iOS.
---------------	----------------------

5.50.2.3 void Crosstales.RTVoice.LiveSpeaker.Silence ()

Silence all active TTS-voices.

5.50.2.4 void Crosstales.RTVoice.LiveSpeaker.Speak (**Model.Wrapper** *wrapper*)

Speaks a text with a given wrapper.

Parameters

<i>wrapper</i>	Wrapper with the speech details.
----------------	----------------------------------

5.50.2.5 void Crosstales.RTVoice.LiveSpeaker.Speak (string *args*)

Speaks a text with a given array of arguments.

Important: you can't specify the AudioSource with this method!

Parameters

<i>args</i>	Argument string delimited by ';': 0 = text, 1 = culture (optional), 2 = voiceName (optional), 3 = rate (optional), 4 = volume (optional), 5 = pitch (optional).
-------------	---

5.50.2.6 void Crosstales.RTVoice.LiveSpeaker.Speak (string[] *args*)

Speaks a text with a given array of arguments.

Important: you can't specify the AudioSource with this method!

Parameters

<i>args</i>	Argument index: 0 = text, 1 = culture (optional), 2 = voiceName (optional), 3 = rate (optional), 4 = pitch (optional), 5 = volume (optional).
-------------	---

5.50.2.7 void Crosstales.RTVoice.LiveSpeaker.SpeakNative (**Model.Wrapper** *wrapper*)

Speaks a text with a given wrapper -> native mode.

Parameters

<i>wrapper</i>	Wrapper with the speech details.
----------------	----------------------------------

5.50.2.8 void Crosstales.RTVoice.LiveSpeaker.SpeakNative (string *args*)

Speaks a text with a given array of arguments (native mode).

Parameters

<i>args</i>	Argument string delimited by ';': 0 = text, 1 = culture (optional), 2 = voiceName (optional), 3 = rate (optional), 4 = volume (optional), 5 = pitch (optional).
-------------	---

5.50.2.9 void Crosstales.RTVoice.LiveSpeaker.SpeakNative (string[] *args*)

Speaks a text with a given array of arguments (native mode).

Parameters

<i>args</i>	Argument index: 0 = text, 1 = culture (optional), 2 = voiceName (optional), 3 = rate (optional), 4 = pitch (optional), 5 = volume (optional).
-------------	---

5.50.2.10 void Crosstales.RTVoice.LiveSpeaker.WordSpoken (string *word*)

The current spoken word from iOS.

Parameters

<i>voices</i>	Current spoken word from iOS.
---------------	-------------------------------


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Scripts/LiveSpeaker.cs

5.51 Crosstales.RTVoice.Tool.Loudspeaker Class Reference

Loudspeaker for an AudioSource.

Inheritance diagram for Crosstales.RTVoice.Tool.Loudspeaker:



Public Member Functions

- void **Awake** ()
- void **Start** ()
- void **Update** ()
- void **FixedUpdate** ()
- void **OnDisable** ()

Public Attributes

- AudioSource Source
Origin AudioSource.
- bool Synchronized = false
Synchronize with the origin (default: false).
- bool SilenceSource = true
Silence the origin (default: true).

Properties

- bool isSynchronized [get, set]
Synchronize with the origin (main use is for UI).
- bool isSilenceSource [get, set]
Silence the origin (main use is for UI).

5.51.1 Detailed Description

Loudspeaker for an AudioSource.

5.51.2 Member Data Documentation

5.51.2.1 bool Crosstales.RTVoice.Tool.Loudspeaker.SilenceSource = true

Silence the origin (default: true).

5.51.2.2 AudioSource Crosstales.RTVoice.Tool.Loudspeaker.Source

Origin AudioSource.

5.51.2.3 bool Crosstales.RTVoice.Tool.Loudspeaker.Synchronized = false

Synchronize with the origin (default: false).

5.51.3 Property Documentation

5.51.3.1 `bool Crosstales.RTVoice.Tool.Loudspeaker.isSilenceSource` `[get]`, `[set]`

Silence the origin (main use is for UI).

5.51.3.2 `bool Crosstales.RTVoice.Tool.Loudspeaker.isSynchronized` `[get]`, `[set]`

Synchronize with the origin (main use is for UI).


The documentation for this class was generated from the following file:

- `D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↵Scripts/Tool/Loudspeaker.cs`

5.52 Crosstales.RTVoice.EditorExtension.LoudspeakerEditor Class Reference

Custom editor for the 'Loudspeaker'-class.

Inheritance diagram for `Crosstales.RTVoice.EditorExtension.LoudspeakerEditor`:



Public Member Functions

- void **OnEnable** ()
- override void **OnInspectorGUI** ()

5.52.1 Detailed Description

Custom editor for the 'Loudspeaker'-class.


The documentation for this class was generated from the following file:

- `D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↵Editor/Extension/LoudspeakerEditor.cs`

5.53 Crosstales.RTVoice.Demo.Util.MaterialChanger Class Reference

Changes the material of a renderer while an AudioSource is playing.

Inheritance diagram for Crosstales.RTVoice.Demo.Util.MaterialChanger:



Public Member Functions

- void **Start** ()
- void **Update** ()

Public Attributes

- AudioSource **Source**
- Material **ActiveMaterial**

5.53.1 Detailed Description

Changes the material of a renderer while an AudioSource is playing.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Demo/Scripts/Util/MaterialChanger.cs

5.54 Crosstales.RTVoice.Demo.NativeAudio Class Reference

Simple example with native audio for exact timing.

Inheritance diagram for Crosstales.RTVoice.Demo.NativeAudio:



Public Member Functions

- void **Start** ()
- void **OnEnable** ()
- void **OnDisable** ()
- void **StartTTS** ()
- void **Silence** ()

Public Attributes

- string **SpeechText** = "This is an example with native audio for exact timing (e.g. animations)."
- bool **PlayOnStart** = false
- float **Delay** = 1f

5.54.1 Detailed Description

Simple example with native audio for exact timing.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔
Demo/Scripts/NativeAudio.cs

5.55 Crosstales.RTVoice.Demo.Util.NativeController Class Reference

Enables or disable game objects for native mode.

Inheritance diagram for Crosstales.RTVoice.Demo.Util.NativeController:



Public Member Functions

- void **Update** ()

Public Attributes

- bool **Active** = true
Enable or disable the 'Objects' for native mode (default: true).
- GameObject[] **Objects**
Selected objects for the controller.

5.55.1 Detailed Description

Enables or disable game objects for native mode.

5.55.2 Member Data Documentation

5.55.2.1 `bool Crosstales.RTVoice.Demo.Util.NativeController.Active = true`

Enable or disable the 'Objects' for native mode (default: true).

5.55.2.2 `GameObject [] Crosstales.RTVoice.Demo.Util.NativeController.Objects`

Selected objects for the controller.

The documentation for this class was generated from the following file:

- `D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Demo/Scripts/Util/NativeController.cs`

5.56 Crosstales.Common.EditorTask.NYCheck Class Reference

Checks if a 'Happy new year'-message must be displayed.

5.56.1 Detailed Description

Checks if a 'Happy new year'-message must be displayed.


The documentation for this class was generated from the following file:

- `D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ Editor/Task/NYCheck.cs`

5.57 Crosstales.RTVoice.Tool.Paralanguage Class Reference

Para-language simulator with audio files.

Inheritance diagram for `Crosstales.RTVoice.Tool.Paralanguage`:



Public Member Functions

- void **Awake** ()
- void **Start** ()
- void **OnDestroy** ()
- void **OnValidate** ()
- void **Speak** ()
Speak the text.
- void **Silence** ()
Silence the speech.

Public Attributes

- string Text = string.Empty
Text to speak.
- Model.VoiceAlias Voices
Voices for the speech.
- Model.Enum.SpeakMode Mode = Model.Enum.SpeakMode.Speak
Speak mode (default: 'Speak').
- AudioClip[] Clips
Audio clips to play.
- float Rate = 1f
Speech rate of the speaker in percent (1 = 100%, default: 1, optional).
- float Pitch = 1f
Speech pitch of the speaker in percent (1 = 100%, default: 1, optional, mobile only).
- float Volume = 1f
Volume of the speaker in percent (1 = 100%, default: 1, optional, Windows only).
- bool PlayOnStart = false
Enable speaking of the text on start (default: false).
- float Delay = 0f
Delay until the speech for this text starts (default: 0).

Properties

- ParalanguageStart OnParalanguageStart
An event triggered whenever a Paralanguage 'Speak' is started.
- ParalanguageComplete OnParalanguageComplete
An event triggered whenever a Paralanguage 'Speak' is completed.
- string CurrentText [get, set]
Text to speak (main use is for UI).
- float CurrentRate [get, set]
Speech rate of the speaker in percent (main use is for UI).
- float CurrentPitch [get, set]
Speech pitch of the speaker in percent (main use is for UI).
- float CurrentVolume [get, set]
Volume of the speaker in percent (main use is for UI).

5.57.1 Detailed Description

Para-language simulator with audio files.

5.57.2 Member Function Documentation

5.57.2.1 void Crosstales.RTVoice.Tool.Paralanguage.Silence ()

Silence the speech.

5.57.2.2 void Crosstales.RTVoice.Tool.Paralanguage.Speak ()

Speak the text.

5.57.3 Member Data Documentation

5.57.3.1 AudioClip [] Crosstales.RTVoice.Tool.Paralanguage.Clips

Audio clips to play.

5.57.3.2 float Crosstales.RTVoice.Tool.Paralanguage.Delay = 0f

Delay until the speech for this text starts (default: 0).

5.57.3.3 Model.Enum.SpeakMode Crosstales.RTVoice.Tool.Paralanguage.Mode = Model.Enum.SpeakMode.Speak

Speak mode (default: 'Speak').

5.57.3.4 float Crosstales.RTVoice.Tool.Paralanguage.Pitch = 1f

Speech pitch of the speaker in percent (1 = 100%, default: 1, optional, mobile only).

5.57.3.5 bool Crosstales.RTVoice.Tool.Paralanguage.PlayOnStart = false

Enable speaking of the text on start (default: false).

5.57.3.6 float Crosstales.RTVoice.Tool.Paralanguage.Rate = 1f

Speech rate of the speaker in percent (1 = 100%, default: 1, optional).

5.57.3.7 string Crosstales.RTVoice.Tool.Paralanguage.Text = string.Empty

Text to speak.

5.57.3.8 Model.VoiceAlias Crosstales.RTVoice.Tool.Paralanguage.Voices

Voices for the speech.

5.57.3.9 float Crosstales.RTVoice.Tool.Paralanguage.Volume = 1f

Volume of the speaker in percent (1 = 100%, default: 1, optional, Windows only).

5.57.4 Property Documentation

5.57.4.1 float Crosstales.RTVoice.Tool.Paralanguage.CurrentPitch [get], [set]

Speech pitch of the speaker in percent (main use is for UI).

5.57.4.2 float Crosstales.RTVoice.Tool.Paralanguage.CurrentRate [get], [set]

Speech rate of the speaker in percent (main use is for UI).

5.57.4.3 string Crosstales.RTVoice.Tool.Paralanguage.CurrentText [get], [set]

Text to speak (main use is for UI).

5.57.4.4 float Crosstales.RTVoice.Tool.Paralanguage.CurrentVolume [get], [set]

Volume of the speaker in percent (main use is for UI).

5.57.4.5 ParalanguageComplete Crosstales.RTVoice.Tool.Paralanguage.OnParalanguageComplete [add], [remove]

An event triggered whenever a Paralanguage 'Speak' is completed.

5.57.4.6 ParalanguageStart Crosstales.RTVoice.Tool.Paralanguage.OnParalanguageStart [add], [remove]

An event triggered whenever a Paralanguage 'Speak' is started.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↵
Scripts/Tool/Paralanguage.cs

5.58 HutongGames.PlayMaker.Actions.Paralanguage Class Reference

Paralanguage-action for PlayMaker.

Inheritance diagram for HutongGames.PlayMaker.Actions.Paralanguage:



Public Member Functions

- override void **OnEnter** ()
- override void **OnExit** ()

Public Attributes

- Crosstailes.RTVoice.Tool.Paralanguage Obj
Add a Paralanguage (default: first object in scene).

5.58.1 Detailed Description

Paralanguage-action for PlayMaker.

5.58.2 Member Data Documentation

5.58.2.1 Crosstailes.RTVoice.Tool.Paralanguage HutongGames.PlayMaker.Actions.Paralanguage.Obj

Add a Paralanguage (default: first object in scene).


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstailes/RTVoice/3rd party/PlayMaker/Scripts/Paralanguage.cs

5.59 Crosstailes.RTVoice.EditorExtension.ParalanguageEditor Class Reference

Custom editor for the 'Paralanguage'-class.

Inheritance diagram for Crosstailes.RTVoice.EditorExtension.ParalanguageEditor:



Public Member Functions

- void **OnEnable** ()
- void **OnDisable** ()
- override void **OnInspectorGUI** ()

5.59.1 Detailed Description

Custom editor for the 'Paralanguage'-class.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Editor/Extension/ParalanguageEditor.cs

5.60 Crosstales.RTVoice.PlayMaker.ParalanguageEditor Class Reference

Custom editor for the Paralanguage-action.

Inheritance diagram for Crosstales.RTVoice.PlayMaker.ParalanguageEditor:



Additional Inherited Members

5.60.1 Detailed Description

Custom editor for the Paralanguage-action.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/PlayMaker/Editor/ParalanguageEditor.cs

5.61 Crosstales.Common.Util.PlatformController Class Reference

Enables or disable game objects for a given platform.

Inheritance diagram for Crosstales.Common.Util.PlatformController:



Public Member Functions

- virtual void **Start** ()

Public Attributes

- System.Collections.Generic.List< Model.Enum.Platform > Platforms
Selected platforms for the controller.
- bool **Active** = true
- GameObject[] Objects
Selected objects for the controller.

Protected Member Functions

- void **selectPlatform** ()
- void **activateGO** ()

Protected Attributes

- Model.Enum.Platform **currentPlatform**

5.61.1 Detailed Description

Enables or disable game objects for a given platform.

5.61.2 Member Data Documentation

5.61.2.1 GameObject [] Crosstales.Common.Util.PlatformController.Objects

Selected objects for the controller.

5.61.2.2 System.Collections.Generic.List<Model.Enum.Platform> Crosstales.Common.Util.PlatformController.Platforms

Selected platforms for the controller.

summary>Enable or disable the 'Objects' for the selected 'Platforms' (default: true).


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ Scripts/Util/PlatformController.cs

5.62 Crosstales.RTVoice.Demo.Util.PlatformController Class Reference

Enables or disable game objects for a given platform.

Inheritance diagram for Crosstales.RTVoice.Demo.Util.PlatformController:



Public Member Functions

- override void **Start** ()
- void **OnEnable** ()
- void **OnDisable** ()

Additional Inherited Members

5.62.1 Detailed Description

Enables or disable game objects for a given platform.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Demo/Scripts/Util/PlatformController.cs

5.63 Crosstales.RTVoice.Demo.PreGeneratedAudio Class Reference

Simple example with pre-generated audio for exact timing.

Inheritance diagram for Crosstales.RTVoice.Demo.PreGeneratedAudio:



Public Member Functions

- void **Start** ()
- void **Update** ()
- void **OnEnable** ()
- void **OnDisable** ()
- void **Play** ()
- void **Silence** ()
- void **Stop** ()

Public Attributes

- string **SpeechText** = "This is an example with pre-generated audio for exact timing (e.g. animations)."
- bool **PlayOnStart** = false

5.63.1 Detailed Description

Simple example with pre-generated audio for exact timing.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Demo/Scripts/PreGeneratedAudio.cs

5.64 Crosstales.Common.Util.RandomColor Class Reference

Random color changer.

Inheritance diagram for Crosstales.Common.Util.RandomColor:



Public Member Functions

- void **Start** ()
- void **Update** ()

Public Attributes

- bool UseInterval = true
Use intervals to change the color (default: true).
- Vector2 ChangeInterval = new Vector2(5, 10)
summary>Random hue range between min (= x) and max (= y) (default: x = 0, y = 1).
- Vector2 HueRange = new Vector2(0f, 1f)
summary>Random saturation range between min (= x) and max (= y) (default: x = 1, y = 1).
- Vector2 SaturationRange = new Vector2(1f, 1f)
summary>Random value range between min (= x) and max (= y) (default: x = 1, y = 1).
- Vector2 ValueRange = new Vector2(1f, 1f)
summary>Random alpha range between min (= x) and max (= y) (default: x = 1, y = 1).
- Vector2 AlphaRange = new Vector2(1f, 1f)
summary>Use gray scale colors (default: false).
- bool GrayScale = false
summary>Modify the color of a material instead of the Renderer (default: not set, optional).
- Material Material
summary>Set the object to a random color at Start (default: false).
- bool **RandomColorAtStart** = false

5.64.1 Detailed Description

Random color changer.

5.64.2 Member Data Documentation

5.64.2.1 Vector2 Crosstales.Common.Util.RandomColor.AlphaRange = new Vector2(1f, 1f)

summary>Use gray scale colors (default: false).

5.64.2.2 Vector2 Crosstales.Common.Util.RandomColor.ChangeInterval = new Vector2(5, 10)

summary>Random hue range between min (= x) and max (= y) (default: x = 0, y = 1).

5.64.2.3 bool Crosstales.Common.Util.RandomColor.GrayScale = false

summary>Modify the color of a material instead of the Renderer (default: not set, optional).

5.64.2.4 Vector2 Crosstales.Common.Util.RandomColor.HueRange = new Vector2(0f, 1f)

summary>Random saturation range between min (= x) and max (= y) (default: x = 1, y = 1).

5.64.2.5 Material Crosstales.Common.Util.RandomColor.Material

summary>Set the object to a random color at Start (default: false).

5.64.2.6 Vector2 Crosstales.Common.Util.RandomColor.SaturationRange = new Vector2(1f, 1f)

summary>Random value range between min (= x) and max (= y) (default: x = 1, y = 1).

5.64.2.7 bool Crosstales.Common.Util.RandomColor.UseInterval = true

Use intervals to change the color (default: true).

summary>Random change interval between min (= x) and max (= y) in seconds (default: x = 5, y = 10).

5.64.2.8 Vector2 Crosstales.Common.Util.RandomColor.ValueRange = new Vector2(1f, 1f)

summary>Random alpha range between min (= x) and max (= y) (default: x = 1, y = 1).


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/Scripts/Util/RandomColor.cs

5.65 Crosstales.Common.Util.RandomRotator Class Reference

Random rotation changer.

Inheritance diagram for Crosstales.Common.Util.RandomRotator:



Public Member Functions

- void **Start** ()
- void **Update** ()

Public Attributes

- bool UseInterval = true
Use intervals to change the rotation (default: true).
- Vector2 ChangeInterval = new Vector2(10, 20)
summary> Minimum rotation speed per axis (default: 5 for all axis).
- Vector3 SpeedMin = new Vector3(5, 5, 5)
summary> Maximum rotation speed per axis (default: 15 for all axis).
- Vector3 SpeedMax = new Vector3(15, 15, 15)
summary> Set the object to a random rotation at Start (default: false).
- bool **RandomRotationAtStart** = false

5.65.1 Detailed Description

Random rotation changer.

5.65.2 Member Data Documentation

5.65.2.1 Vector2 Crosstales.Common.Util.RandomRotator.ChangeInterval = new Vector2(10, 20)

summary> Minimum rotation speed per axis (default: 5 for all axis).

5.65.2.2 Vector3 Crosstales.Common.Util.RandomRotator.SpeedMax = new Vector3(15, 15, 15)

summary> Set the object to a random rotation at Start (default: false).

5.65.2.3 Vector3 Crosstales.Common.Util.RandomRotator.SpeedMin = new Vector3(5, 5, 5)

summary> Maximum rotation speed per axis (default: 15 for all axis).

5.65.2.4 bool Crosstales.Common.Util.RandomRotator.UseInterval = true

Use intervals to change the rotation (default: true).

summary> Random change interval between min (= x) and max (= y) in seconds (default: x = 10, y = 20).


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ Scripts/Util/RandomRotator.cs

5.66 Crosstales.Common.Util.RandomScaler Class Reference

Random scale changer.

Inheritance diagram for Crosstales.Common.Util.RandomScaler:



Public Member Functions

- void **Start** ()
- void **Update** ()

Public Attributes

- bool UseInterval = true
Use intervals to change the scale (default: true).
- Vector2 ChangeInterval = new Vector2(10, 20)
summary> Minimum scale per axis (default: 0.1 for all axis).
- Vector3 ScaleMin = new Vector3(0.1f, 0.1f, 0.1f)
summary> Maximum scale per axis (default: 0.1 for all axis).
- Vector3 ScaleMax = new Vector3(3, 3, 3)
summary> Uniform scaling for all axis (x-axis values will be used, default: true).
- bool Uniform = true
summary> Set the object to a random scale at Start (default: false).
- bool **RandomScaleAtStart** = false

5.66.1 Detailed Description

Random scale changer.

5.66.2 Member Data Documentation

5.66.2.1 Vector2 Crosstales.Common.Util.RandomScaler.ChangeInterval = new Vector2(10, 20)

summary> Minimum scale per axis (default: 0.1 for all axis).

5.66.2.2 Vector3 Crosstales.Common.Util.RandomScaler.ScaleMax = new Vector3(3, 3, 3)

summary> Uniform scaling for all axis (x-axis values will be used, default: true).

5.66.2.3 **Vector3** `Crosstales.Common.Util.RandomScaler.ScaleMin = new Vector3(0.1f, 0.1f, 0.1f)`

summary>Maximum scale per axis (default: 0.1 for all axis).

5.66.2.4 **bool** `Crosstales.Common.Util.RandomScaler.Uniform = true`

summary>Set the object to a random scale at Start (default: false).

5.66.2.5 **bool** `Crosstales.Common.Util.RandomScaler.UseInterval = true`

Use intervals to change the scale (default: true).

summary>Random change interval between min (= x) and max (= y) in seconds (default: x = 10, y = 20).

The documentation for this class was generated from the following file:

- `D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/Scripts/Util/RandomScaler.cs`

5.67 Crosstales.RTVoice.EditorTask.ReminderCheck Class Reference

Reminds the customer to create an UAS review.

5.67.1 Detailed Description

Reminds the customer to create an UAS review.


The documentation for this class was generated from the following file:

- `D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Editor/Task/ReminderCheck.cs`

5.68 Crosstales.RTVoice.EditorIntegration.RTVoiceGameObject Class Reference

Editor component for the "Hierarchy"-menu.

Inheritance diagram for `Crosstales.RTVoice.EditorIntegration.RTVoiceGameObject`:



5.68.1 Detailed Description


Editor component for the "Hierarchy"-menu.

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Editor/Integration/RTVoiceGameObject.cs

5.69 RTVoiceIOSBridge Class Reference

Inheritance diagram for RTVoiceIOSBridge:



Instance Methods

- (void) - setVoices
- (void) - speak:text:rate:pitch:volume:
- (void) - stop

5.69.1 Method Documentation

5.69.1.1 - (void) setVoices

Collects and sends all voices to RTVoice.

5.69.1.2 - (void) speak: (NSString *) id text:(NSString *) text rate:(float) rate pitch:(float) pitch volume:(float) volume

Speaks the string with a given rate, pitch, volume and culture.

Parameters

<i>name</i>	Name of the voice to speak
<i>text</i>	Text to speak
<i>rate</i>	Speech rate of the speaker in percent
<i>pitch</i>	Pitch of the speech in percent
<i>volume</i>	Volume of the speaker in percent

5.69.1.3 - (void) stop


Stops speaking

The documentation for this class was generated from the following files:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstailes/RTVoice/↔ Wrapper/iOS/RTVoiceIOSBridge.h
- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstailes/RTVoice/↔ Wrapper/iOS/RTVoiceIOSBridge.mm

5.70 RTVoiceIOSBridge() Category Reference

Inheritance diagram for RTVoiceIOSBridge():



Properties

- AVSpeechSynthesizer * **synthesizer**

The documentation for this category was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstailes/RTVoice/↔ Wrapper/iOS/RTVoiceIOSBridge.mm

5.71 Crosstailes.RTVoice.EditorIntegration.RTVoiceMenu Class Reference

Editor component for the "Tools"-menu.

5.71.1 Detailed Description

Editor component for the "Tools"-menu.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstailes/RTVoice/↔ Editor/Integration/RTVoiceMenu.cs

5.72 Crosstales.UI.Util.ScrollRectHandler Class Reference

Changes the sensitivity of ScrollRects under various platforms.

Inheritance diagram for Crosstales.UI.Util.ScrollRectHandler:



Public Member Functions

- void **Start** ()

Public Attributes

- ScrollRect **Scroll**

5.72.1 Detailed Description

Changes the sensitivity of ScrollRects under various platforms.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ UI/Scripts/Util/ScrollRectHandler.cs

5.73 Crosstales.RTVoice.Demo.SendMessage Class Reference

Simple "SendMessage" example.

Inheritance diagram for Crosstales.RTVoice.Demo.SendMessage:



Public Member Functions

- void **Start** ()
- void **Play** ()
- void **SpeakerA** ()
- IEnumerator **SpeakerB** ()
- void **Silence** ()

Public Attributes

- string **TextA** = "RT-Voice works great with PlayMaker, SALSA, Localized Dialogs/Cutscenes, Dialogue System for Unity and THE Dialogue Engine - that's awesome!"
- string **TextB** = "Absolutely true! RT-Voice is fantastic."
- float **DelayTextB** = 12.2f
- bool **PlayOnStart** = false

5.73.1 Detailed Description

Simple "SendMessage" example.

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↵ Demo/Scripts/SendMessage.cs

5.74 Crosstales.RTVoice.Model.Sequence Class Reference

Model for a sequence.

Public Member Functions

- override string **ToString** ()

Public Attributes

- string **Text** = string.Empty
Text to speak.
- Model.VoiceAlias **Voices**
Voices for the speech.
- Enum.SpeakMode **Mode** = Enum.SpeakMode.Speak
Speak mode (default: 'Speak').
- AudioSource **Source**
AudioSource for the output (optional).
- float **Rate** = 1f
Speech rate of the speaker in percent (1 = 100%, default: 1, optional).
- float **Pitch** = 1f
Speech pitch of the speaker in percent (1 = 100%, default: 1, optional, mobile only).
- float **Volume** = 1f
Volume of the speaker in percent (1 = 100%, default: 1, optional, Windows only).
- bool **initialized** = false

5.74.1 Detailed Description

Model for a sequence.

5.74.2 Member Data Documentation

5.74.2.1 Enum.SpeakMode Crosstales.RTVoice.Model.Sequence.Mode = Enum.SpeakMode.Speak

Speak mode (default: 'Speak').

5.74.2.2 float Crosstales.RTVoice.Model.Sequence.Pitch = 1f

Speech pitch of the speaker in percent (1 = 100%, default: 1, optional, mobile only).

5.74.2.3 float Crosstales.RTVoice.Model.Sequence.Rate = 1f

Speech rate of the speaker in percent (1 = 100%, default: 1, optional).

5.74.2.4 AudioSource Crosstales.RTVoice.Model.Sequence.Source

AudioSource for the output (optional).

5.74.2.5 string Crosstales.RTVoice.Model.Sequence.Text = string.Empty

Text to speak.

5.74.2.6 Model.VoiceAlias Crosstales.RTVoice.Model.Sequence.Voices

Voices for the speech.

5.74.2.7 float Crosstales.RTVoice.Model.Sequence.Volume = 1f

Volume of the speaker in percent (1 = 100%, default: 1, optional, Windows only).


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Model/Sequence.cs

5.75 Crosstales.RTVoice.Demo.SequenceCaller Class Reference

Simple Sequence caller example.

Inheritance diagram for Crosstales.RTVoice.Demo.SequenceCaller:



Public Member Functions

- void **Start** ()

Public Attributes

- GameObject **receiver**
- int **NumberOfSequences**
- float **SequenceDelay** = 1f

5.75.1 Detailed Description

Simple Sequence caller example.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Demo/Scripts/SequenceCaller.cs

5.76 Crosstales.RTVoice.Tool.Sequencer Class Reference

Simple sequencer for dialogues.

Inheritance diagram for Crosstales.RTVoice.Tool.Sequencer:



Public Member Functions

- void **Start** ()
- void **OnDestroy** ()
- void **OnValidate** ()
- void PlaySequence (int index=0)
Plays a Sequence with a given index.
- void PlayNextSequence ()
Plays the next Sequence in the array.
- void PlayAllSequences ()
Plays all Sequences.
- void StopAllSequences ()
Stops and silences all active Sequences.

Public Attributes

- Model.Sequence[] Sequences
All available sequences.
- float Delay = 0f
Delay in seconds before the Sequencer starts processing (default: 0).
- bool PlayOnStart = false
Enable the Sequencer on start (default: false).

Properties

- Model.Sequence CurrentSequence [get]
Returns the current Sequence.

5.76.1 Detailed Description

Simple sequencer for dialogues.

5.76.2 Member Function Documentation

5.76.2.1 void Crosstales.RTVoice.Tool.Sequencer.PlayAllSequences ()

Plays all Sequences.

5.76.2.2 void Crosstales.RTVoice.Tool.Sequencer.PlayNextSequence ()

Plays the next Sequence in the array.

5.76.2.3 void Crosstales.RTVoice.Tool.Sequencer.PlaySequence (int *index* = 0)

Plays a Sequence with a given index.

Parameters

<i>index</i>	Index of the Sequence (default: 0, optional).
--------------	---

5.76.2.4 void Crosstales.RTVoice.Tool.Sequencer.StopAllSequences ()

Stops and silences all active Sequences.

5.76.3 Member Data Documentation

5.76.3.1 float Crosstales.RTVoice.Tool.Sequencer.Delay = 0f

Delay in seconds before the Sequencer starts processing (default: 0).

5.76.3.2 bool Crosstales.RTVoice.Tool.Sequencer.PlayOnStart = false

Enable the Sequencer on start (default: false).

5.76.3.3 Model.Sequence [] Crosstales.RTVoice.Tool.Sequencer.Sequences

All available sequences.

5.76.4 Property Documentation

5.76.4.1 Model.Sequence Crosstales.RTVoice.Tool.Sequencer.CurrentSequence [get]

Returns the current Sequence.

Returns

The current Sequence.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Tool/Sequencer.cs

5.77 Crosstales.RTVoice.EditorExtension.SequencerEditor Class Reference

Custom editor for the 'Sequencer'-class.

Inheritance diagram for Crosstales.RTVoice.EditorExtension.SequencerEditor:



Public Member Functions

- void **OnEnable** ()
- override void **OnInspectorGUI** ()

5.77.1 Detailed Description

Custom editor for the 'Sequencer'-class.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Editor/Extension/SequencerEditor.cs

5.78 Crosstales.Common.Util.SerializableDictionary< TKey, TVal > Class Template Reference

Serializable Dictionary-class for XML.

Inheritance diagram for Crosstales.Common.Util.SerializableDictionary< TKey, TVal >:



Public Member Functions

- **SerializableDictionary** (System.Collections.Generic.IDictionary< TKey, TVal > dictionary)
- **SerializableDictionary** (System.Collections.Generic.IEqualityComparer< TKey > comparer)
- **SerializableDictionary** (int capacity)
- **SerializableDictionary** (System.Collections.Generic.IDictionary< TKey, TVal > dictionary, System.Collections.Generic.IEqualityComparer< TKey > comparer)
- **SerializableDictionary** (int capacity, System.Collections.Generic.IEqualityComparer< TKey > comparer)

Protected Member Functions

- **SerializableDictionary** (System.Runtime.Serialization.SerializationInfo info, System.Runtime.Serialization.StreamingContext context)

Properties

- System.Xml.Serialization.XmlSerializer **ValueSerializer** [get]

5.78.1 Detailed Description

Serializable Dictionary-class for XML.

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ Scripts/Util/SerializableDictionary.cs

5.79 Crosstales.Common.Util.SerializeDeSerialize Class Reference

Serialize and deserialize objects to/from binary files.

Static Public Member Functions

- static void SerializeToFile< T > (T obj, string filename)
Serialize an object to a byte-array.
- static byte[] SerializeToByteArray< T > (T obj)
Serialize an object to a byte-array.
- static T DeserializeFromFile< T > (string filename)
Deserialize a binary-file to an object.
- static T DeserializeFromByteArray< T > (byte[] data)
Deserialize a byte-array to an object.

5.79.1 Detailed Description

Serialize and deserialize objects to/from binary files.

5.79.2 Member Function Documentation

5.79.2.1 static T Crosstales.Common.Util.SerializeDeSerialize.DeserializeFromByteArray< T > (byte[] data) [static]

Deserialize a byte-array to an object.

Parameters

<i>filename</i>	Byte-array of the object
-----------------	--------------------------

Returns

Object

5.79.2.2 static T Crosstales.Common.Util.SerializeDeSerialize.DeserializeFromFile< T > (string filename) [static]

Deserialize a binary-file to an object.

Parameters

<i>filename</i>	Binary-file of the object
-----------------	---------------------------

Returns

Object

5.79.2.3 `static byte [] Crosstales.Common.Util.SerializeDeSerialize.SerializeToByteArray< T > (T obj) [static]`

Serialize an object to a byte-array.

Parameters

<i>obj</i>	Object to serialize.
------------	----------------------

Returns

Byte-array of the object

5.79.2.4 `static void Crosstales.Common.Util.SerializeDeSerialize.SerializeToFile< T > (T obj, string filename) [static]`

Serialize an object to a byte-array.

Parameters

<i>obj</i>	Object to serialize.
<i>filename</i>	Binary-file for the object

Returns

Byte-array of the object

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ Scripts/Util/SerializeDeSerialize.cs

5.80 Crosstales.Common.EditorTask.SetApiLevel Class Reference

Sets the required .NET API level.

5.80.1 Detailed Description

Sets the required .NET API level.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ Editor/Task/SetApiLevel.cs

5.81 Crosstales.Common.EditorTask.SetupResources Class Reference

Copies all resources to 'Editor Default Resources'.

Inheritance diagram for Crosstales.Common.EditorTask.SetupResources:



Additional Inherited Members

5.81.1 Detailed Description

Copies all resources to 'Editor Default Resources'.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ Editor/Task/SetupResources.cs

5.82 Crosstales.RTVoice.EditorTask.SetupResources Class Reference

Moves all needed resources to 'Editor Default Resources'.

Inheritance diagram for Crosstales.RTVoice.EditorTask.SetupResources:



Additional Inherited Members

5.82.1 Detailed Description

Moves all needed resources to 'Editor Default Resources'.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Editor/Task/SetupResources.cs

5.83 HutongGames.PlayMaker.Actions.Silence Class Reference

Silence-action for PlayMaker.

Inheritance diagram for HutongGames.PlayMaker.Actions.Silence:



Public Member Functions

- override void **OnEnter** ()

Additional Inherited Members

5.83.1 Detailed Description

Silence-action for PlayMaker.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstailes/RTVoice/3rd party/PlayMaker/Scripts/Silence.cs

5.84 Crosstailes.RTVoice.PlayMaker.SilenceEditor Class Reference

Custom editor for the Silence-action.

Inheritance diagram for Crosstailes.RTVoice.PlayMaker.SilenceEditor:



Additional Inherited Members

5.84.1 Detailed Description

Custom editor for the Silence-action.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstailes/RTVoice/3rd party/PlayMaker/Editor/SilenceEditor.cs

5.85 Crosstailes.RTVoice.Demo.Simple Class Reference

Simple TTS example.

Inheritance diagram for Crosstailes.RTVoice.Demo.Simple:



Public Member Functions

- void **Start** ()
- void **OnEnable** ()
- void **OnDisable** ()
- void **Play** ()
- void **SpeakerA** ()
- void **SpeakerB** ()
- void **Silence** ()

Public Attributes

- AudioSource **SourceA**
- AudioSource **SourceB**
- float **RateSpeakerA** = 1.25f
- float **RateSpeakerB** = 1.75f
- bool **PlayOnStart** = false
- Text **TextSpeakerA**
- Text **TextSpeakerB**
- Text **PhonemeSpeakerA**
- Text **PhonemeSpeakerB**
- Text **VisemeSpeakerA**
- Text **VisemeSpeakerB**

5.85.1 Detailed Description

Simple TTS example.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Demo/Scripts/Simple.cs

5.86 Crosstales.RTVoice.Demo.SimpleNative Class Reference

Simple native TTS example.

Inheritance diagram for Crosstales.RTVoice.Demo.SimpleNative:



Public Member Functions

- void **Start** ()
- void **OnEnable** ()
- void **OnDisable** ()
- void **Play** ()
- void **SpeakerA** ()
- void **SpeakerB** ()
- void **SpeakerC** ()
- void **Silence** ()

Public Attributes

- float **RateSpeakerA** = 1.25f
- float **RateSpeakerB** = 1.75f
- float **RateSpeakerC** = 2.5f
- bool **PlayOnStart** = false
- Text **TextSpeakerA**
- Text **TextSpeakerB**
- Text **TextSpeakerC**
- Text **PhonemeSpeakerA**
- Text **PhonemeSpeakerB**
- Text **PhonemeSpeakerC**
- Text **VisemeSpeakerA**
- Text **VisemeSpeakerB**
- Text **VisemeSpeakerC**

5.86.1 Detailed Description

Simple native TTS example.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstailes/RTVoice/↔ Demo/Scripts/SimpleNative.cs

5.87 Crosstailes.UI.Social Class Reference

Crosstailes social media links.

Inheritance diagram for Crosstailes.UI.Social:



Public Member Functions

- void **Facebook** ()
- void **Twitter** ()
- void **LinkedIn** ()
- void **Xing** ()
- void **Youtube** ()
- void **Discord** ()

5.87.1 Detailed Description


Crosstailes social media links.

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstailes/Common/↔ UI/Scripts/Social.cs

5.88 Crosstailes.RTVoice.SALSA.Speak Class Reference

Inheritance diagram for Crosstailes.RTVoice.SALSA.Speak:



Public Member Functions

- void **Start** ()
- void **OnEnable** ()
- void **OnDisable** ()
- void **Talk** ()

Public Attributes

- AudioSource **Source**
- CrazyMinnow.SALSA.Salsa3D **Salsa**
- InputField **EnterText**
- Slider **RateSlider**
- Slider **PitchSlider**


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstailes/RTVoice/3rd party/SALSA/Scripts/Speak.cs ↩↪

5.89 HutongGames.PlayMaker.Actions.Speak Class Reference

Speak-action for PlayMaker.

Inheritance diagram for HutongGames.PlayMaker.Actions.Speak:



Public Member Functions

- override void **OnEnter** ()

Public Attributes

- FsmString Text = "Hello world!"
Text to speak.
- FsmString RTVoiceNameWindows = "David"
Name of the RT-Voice under Windows.
- FsmString RTVoiceNameMac = "Alex"
Name of the RT-Voice under macOS.
- FsmString RTVoiceNameAndroid = "en"
Name of the RT-Voice under Android.
- FsmString RTVoiceNameIOS = "Daniel"
Name of the RT-Voice under iOS.
- FsmString RTVoiceNameWSA = "David"
Name of the RT-Voice under WSA.
- FsmString RTVoiceNameMaryTTS = "cms-rms-hsmm"
Name of the RT-Voice under MaryTTS.
- FsmString RTVoiceNameCustom = string.Empty
Name of the RT-Voice in a custom provider.
- FsmString Culture = "en"
Fallback culture (e.g. 'en', optional).

Additional Inherited Members

5.89.1 Detailed Description

Speak-action for PlayMaker.

5.89.2 Member Data Documentation

5.89.2.1 FsmString HutongGames.PlayMaker.Actions.Speak.Culture = "en"

Fallback culture (e.g. 'en', optional).

5.89.2.2 FsmString HutongGames.PlayMaker.Actions.Speak.RTVoiceNameAndroid = "en"

Name of the RT-Voice under Android.

5.89.2.3 FsmString HutongGames.PlayMaker.Actions.Speak.RTVoiceNameCustom = string.Empty

Name of the RT-Voice in a custom provider.

5.89.2.4 FsmString HutongGames.PlayMaker.Actions.Speak.RTVoiceNameIOS = "Daniel"

Name of the RT-Voice under iOS.

5.89.2.5 `FsmString HutongGames.PlayMaker.Actions.Speak.RTVoiceNameMac = "Alex"`

Name of the RT-Voice under macOS.

5.89.2.6 `FsmString HutongGames.PlayMaker.Actions.Speak.RTVoiceNameMaryTTS = "cms-rms-hsmm"`

Name of the RT-Voice under MaryTTS.

5.89.2.7 `FsmString HutongGames.PlayMaker.Actions.Speak.RTVoiceNameWindows = "David"`

Name of the RT-Voice under Windows.

5.89.2.8 `FsmString HutongGames.PlayMaker.Actions.Speak.RTVoiceNameWSA = "David"`

Name of the RT-Voice under WSA.

5.89.2.9 `FsmString HutongGames.PlayMaker.Actions.Speak.Text = "Hello world!"`


Text to speak.

The documentation for this class was generated from the following file:

- `D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/PlayMaker/Scripts/Speak.cs`

5.90 Crosstales.RTVoice.SALSA.Speak2D Class Reference

Inheritance diagram for Crosstales.RTVoice.SALSA.Speak2D:



Public Member Functions

- void **Start** ()
- void **OnEnable** ()
- void **OnDisable** ()
- void **Talk** ()

Public Attributes

- AudioSource **Source**
- CrazyMinnow.SALSA.Salsa2D **Salsa**
- InputField **EnterText**
- Slider **RateSlider**
- Slider **PitchSlider**


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/SALSA/Scripts/Speak2D.cs

5.91 HutongGames.PlayMaker.Actions.SpeakBase Class Reference

Base for Speak-actions in PlayMaker.

Inheritance diagram for HutongGames.PlayMaker.Actions.SpeakBase:



Public Member Functions

- override void **OnEnter** ()
- override void **OnExit** ()

Public Attributes

- Crosstales.RTVoice.Model.Enum.SpeakMode Mode
Speak mode (default: 'Speak').
- FsmGameObject AudioSource
AudioSource for the output (optional).
- FsmFloat Rate = 1
Speech rate of the speaker in percent (1 = 100%, default: 1, optional).
- FsmFloat Pitch = 1f
Speech pitch of the speaker in percent (1 = 100%, default: 1, optional, mobile only).
- FsmFloat Volume = 1
Volume of the speaker in percent (1 = 100%, default: 1, optional).

Protected Member Functions

- void **subscribeEvents** ()
- void **unsubscribeEvents** ()

Protected Attributes

- string **uid**

5.91.1 Detailed Description

Base for Speak-actions in PlayMaker.

5.91.2 Member Data Documentation

5.91.2.1 FsmGameObject HutongGames.PlayMaker.Actions.SpeakBase.AudioSource

AudioSource for the output (optional).

5.91.2.2 Crosstales.RTVoice.Model.Enum.SpeakMode HutongGames.PlayMaker.Actions.SpeakBase.Mode

Speak mode (default: 'Speak').

5.91.2.3 FsmFloat HutongGames.PlayMaker.Actions.SpeakBase.Pitch = 1f

Speech pitch of the speaker in percent (1 = 100%, default: 1, optional, mobile only).

5.91.2.4 FsmFloat HutongGames.PlayMaker.Actions.SpeakBase.Rate = 1

Speech rate of the speaker in percent (1 = 100%, default: 1, optional).

5.91.2.5 FsmFloat HutongGames.PlayMaker.Actions.SpeakBase.Volume = 1

Volume of the speaker in percent (1 = 100%, default: 1, optional).


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/PlayMaker/Scripts/SpeakBase.cs

5.92 Crosstales.RTVoice.PlayMaker.SpeakEditor Class Reference

Custom editor for the Speak-action.

Inheritance diagram for Crosstales.RTVoice.PlayMaker.SpeakEditor:



Public Member Functions

- override void **OnEnable** ()
- override bool **OnGUI** ()

5.92.1 Detailed Description

Custom editor for the Speak-action.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/PlayMaker/Editor/SpeakEditor.cs

5.93 Crosstales.RTVoice.Speaker Class Reference

Main component of RTVoice.

Inheritance diagram for Crosstales.RTVoice.Speaker:



Public Member Functions

- void **Awake** ()
- void **OnEnable** ()
- void **Update** ()
- void **OnDisable** ()
- void **OnApplicationQuit** ()
- void **OnApplicationFocus** (bool hasFocus)

Static Public Member Functions

- static void Reset ()
Resets this object.
- static float ApproximateSpeechLength (string text, float rate=1f, float wordsPerMinute=175f, float time↵Factor=0.9f)
Approximates the speech length in seconds of a given text and rate. Note: This is an experimental method and doesn't provide an exact value; +/- 15% is "normal"!
- static bool isVoiceForGenderAvailable (Model.Enum.Gender gender, string culture="")
Is a voice available for a given gender and optional culture from the current TTS-system?
- static System.Collections.Generic.List< Model.Voice > VoicesForGender (Model.Enum.Gender gender, string culture="", bool isFuzzy=true)
Get all available voices for a given gender and optional culture from the current TTS-system.
- static Model.Voice VoiceForGender (Model.Enum.Gender gender, string culture="", int index=0, string fallbackCulture="", bool isFuzzy=true)
Get a voice from for a given gender and optional culture and optional index from the current TTS-system.
- static bool isVoiceForCultureAvailable (string culture)
Is a voice available for a given culture from the current TTS-system?
- static System.Collections.Generic.List< Model.Voice > VoicesForCulture (string culture, bool isFuzzy=true)
Get all available voices for a given culture from the current TTS-system.
- static Model.Voice VoiceForCulture (string culture, int index=0, string fallbackCulture="", bool isFuzzy=true)
Get a voice from for a given culture and optional index from the current TTS-system.
- static bool isVoiceForNameAvailable (string name, bool isExact=false)
Is a voice available for a given name from the current TTS-system?
- static Model.Voice VoiceForName (string name, bool isExact=false)
Get a voice for a given name from the current TTS-system.
- static string SpeakNative (string text, Model.Voice voice=null, float rate=1f, float pitch=1f, float volume=1f, bool forceSSML=true)
Speaks a text with a given voice (native mode).
- static void SpeakNativeWithUID (Model.Wrapper wrapper)
Speaks a text with a given voice (native mode).
- static string SpeakNative (Model.Wrapper wrapper)
Speaks a text with a given wrapper (native mode).
- static string Speak (string text, AudioSource source=null, Model.Voice voice=null, bool speak↵Immediately=true, float rate=1f, float pitch=1f, float volume=1f, string outputFile="", bool forceSSML=true)
Speaks a text with a given voice.
- static void SpeakWithUID (Model.Wrapper wrapper)
Speaks a text with a given voice.
- static string Speak (Model.Wrapper wrapper)
Speaks a text with a given wrapper.
- static void SpeakMarkedWordsWithUID (Model.Wrapper wrapper)
Speaks and marks a text with a given wrapper.
- static void SpeakMarkedWordsWithUID (string uid, string text, AudioSource source, Model.Voice voice=null, float rate=1f, float pitch=1f, bool forceSSML=true)
Speaks and marks a text with a given voice and tracks the word position.
- static string Generate (Model.Wrapper wrapper)
Generates an audio file from a given wrapper.
- static string Generate (string text, string outputFile, Model.Voice voice=null, float rate=1f, float pitch=1f, float volume=1f, bool forceSSML=true)
Generates an audio file from a text with a given voice.
- static void Silence ()
Silence all active TTS-voices.

- static void Silence (string uid)
Silence an active TTS-voice with a UID.
- static void Pause (string uid)
Pause an active TTS-voice with a UID (only for 'Speak'-calls).
- static void UnPause (string uid)
Un-Pause an active TTS-voice with a UID (only for 'Speak'-calls).
- static void ReloadProvider ()
Reloads the provider.
- static void DeleteAudioFiles ()
Deletes all generated audio files.

Public Attributes

- Provider.BaseCustomVoiceProvider CustomProvider
Custom provider for RT-Voice.
- bool CustomMode = false
Enables or disables the custom provider (default: false).
- bool MaryTTSMODE = false
Enables or disables MaryTTS (default: false).
- string MaryTTSUrl = "http://mary.dfki.de"
Server URL for MaryTTS.
- int MaryTTSPort = 59125
Server port for MaryTTS (default: 59125).
- string MaryTTSUser = string.Empty
User name for MaryTTS (default: empty).
- string MaryTTSPassword = string.Empty
User password for MaryTTS (default: empty).
- Model.Enum.MaryTTSType MaryTTSType = Model.Enum.MaryTTSType.RAWMARYXML
Input type for MaryTTS (default: MaryTTSType.RAWMARYXML).
- bool ESpeakMode = false
Enable or disable eSpeak for standalone platforms (default: false).
- Model.Enum.ESpeakModifiers ESpeakModifier = Model.Enum.ESpeakModifiers.none
Active modifier for all eSpeak voices (default: none, m1-m6 = male, f1-f4 = female).
- bool AutoClearTags = false
Automatically clear tags from speeches depending on the capabilities of the current TTS-system (default: false).
- bool WindowsLegacy = false
Enable or disable the legacy Windows provider (default: false).
- bool SilenceOnDisable = false
Silence any speeches if this component gets disabled (default: false).
- bool SilenceOnFocusLost = true
Silence any speeches if the application loses the focus (default: true).
- bool DontDestroy = true
Don't destroy gameobject during scene switches (default: true).

Properties

- static VoicesReady OnVoicesReady
An event triggered whenever the voices of a provider are ready.
- static SpeakStart OnSpeakStart
An event triggered whenever a speak is started.
- static SpeakComplete OnSpeakComplete
An event triggered whenever a speak is completed.
- static SpeakCurrentWord OnSpeakCurrentWord
An event triggered whenever a new word is spoken (native, Windows and iOS only).
- static SpeakCurrentPhoneme OnSpeakCurrentPhoneme
An event triggered whenever a new phoneme is spoken (native, Windows only).
- static SpeakCurrentViseme OnSpeakCurrentViseme
An event triggered whenever a new viseme is spoken (native, Windows only).
- static SpeakAudioGenerationStart OnSpeakAudioGenerationStart
An event triggered whenever a speak audio generation is started.
- static SpeakAudioGenerationComplete OnSpeakAudioGenerationComplete
An event triggered whenever a speak audio generation is completed.
- static ProviderChange OnProviderChange
An event triggered whenever a provider changes (e.g. Windows to MaryTTS).
- static ErrorInfo OnErrorInfo
An event triggered whenever an error occurs.
- static int SpeechCount [get]
Number of active speeches.
- static int BusyCount [get]
Number of activities.
- static bool areVoicesReady [get]
Are all voices ready to speak?
- static Provider.BaseCustomVoiceProvider CustomVoiceProvider [get, set]
Enables or disables MaryTTS.
- static bool isCustomMode [get, set]
Enables or disables the custom voice provider.
- static bool isMaryMode [get, set]
Enables or disables MaryTTS.
- static string MaryUrl [get, set]
Server URL for MaryTTS.
- static int MaryPort [get, set]
Server port for MaryTTS.
- static string MaryUser [get, set]
User name for MaryTTS.
- static string MaryPassword [set]
Password for MaryTTS.
- static Model.Enum.MaryTTSType MaryType [get, set]
Input type for MaryTTS.
- static bool isESpeakMode [get, set]
Enable or disable eSpeak for standalone platforms.
- static Model.Enum.ESpeakModifiers ESpeakMod [get, set]
Active modifier for all eSpeak voices (m1-m6 = male, f1-f4 = female).
- static bool isWindowsLegacy [get, set]
Enable or disable the legacy Windows provider.
- static bool isAutoClearTags [get, set]

- Automatically clear tags from speeches depending on the capabilities of the current TTS-system.*
- static bool isSilenceOnDisable [get, set]
 - Silence any speeches if this component gets disabled.*
- static bool isSilenceOnFocusLost [get, set]
 - Silence any speeches if the application loses the focus.*
- static bool isTTSAvailable [get]
 - Checks if TTS is available on this system.*
- static bool isSpeaking [get]
 - Checks if RT-Voice is speaking on this system.*
- static bool isBusy [get]
 - Checks if RT-Voice is busy on this system.*
- static string AudioFileExtension [get]
 - Returns the extension of the generated audio files.*
- static string DefaultVoiceName [get]
 - Returns the default voice name of the current TTS-provider.*
- static System.Collections.Generic.List< Model.Voice > Voices [get]
 - Get all available voices from the current TTS-system.*
- static bool isWorkingInEditor [get]
 - Indicates if this TTS-system is working directly inside the Unity Editor (without 'Play'-mode).*
- static int MaxTextLength [get]
 - Maximal length of the speech text (in characters) for the current TTS-system.*
- static bool isSpeakNativeSupported [get]
 - Indicates if this TTS-system is supporting SpeakNative.*
- static bool isSpeakSupported [get]
 - Indicates if this TTS-system is supporting Speak.*
- static bool isPlatformSupported [get]
 - Indicates if this TTS-system is supporting the current platform.*
- static bool isSSMLSupported [get]
 - Indicates if this TTS-system is supporting SSML.*
- static bool isOnlineService [get]
 - Indicates if this TTS-system is an online service like MaryTTS or AWS Polly.*
- static bool hasCoRoutines [get]
 - Indicates if this TTS-system uses co-routines.*
- static System.Collections.Generic.List< string > Cultures [get]
 - Get all available cultures from the current TTS-system (ISO 639-1).*

5.93.1 Detailed Description

Main component of RTVoice.

5.93.2 Member Function Documentation

- 5.93.2.1 static float Crosstales.RTVoice.Speaker.ApproximateSpeechLength (string text, float rate = 1f, float wordsPerMinute = 175f, float timeFactor = 0.9f) [static]

Approximates the speech length in seconds of a given text and rate. Note: This is an experimental method and doesn't provide an exact value; +/- 15% is "normal"!

Parameters

<i>text</i>	Text for the length approximation.
<i>rate</i>	Speech rate of the speaker in percent for the length approximation (1 = 100%, default: 1, optional).
<i>wordsPerMinute</i>	Words per minute (default: 175, optional).
<i>timeFactor</i>	Time factor for the calculated value (default: 0.9, optional).

Returns

Approximated speech length in seconds of the given text and rate.

5.93.2.2 `static void Crosstales.RTVoice.Speaker.DeleteAudioFiles () [static]`

Deletes all generated audio files.

5.93.2.3 `static string Crosstales.RTVoice.Speaker.Generate (Model.Wrapper wrapper) [static]`

Generates an audio file from a given wrapper.

Parameters

<i>wrapper</i>	Speak wrapper.
----------------	----------------

Returns

UID of the generator.

5.93.2.4 `static string Crosstales.RTVoice.Speaker.Generate (string text, string outputFile, Model.Voice voice = null, float rate = 1f, float pitch = 1f, float volume = 1f, bool forceSSML = true) [static]`

Generates an audio file from a text with a given voice.

Parameters

<i>text</i>	Text to generate.
<i>outputFile</i>	Saves the generated audio to an output file (without extension).
<i>voice</i>	Voice to speak (optional).
<i>rate</i>	Speech rate of the speaker in percent (1 = 100%, values: 0-3, default: 1, optional).
<i>pitch</i>	Pitch of the speech in percent (1 = 100%, values: 0-2, default: 1, optional).
<i>volume</i>	Volume of the speaker in percent (1 = 100%, values: 0-1, default: 1, optional).
<i>forceSSML</i>	Force SSML on supported platforms (default: true, optional).

Returns

UID of the generator.

5.93.2.5 `static bool Crosstales.RTVoice.Speaker.isVoiceForCultureAvailable (string culture) [static]`

Is a voice available for a given culture from the current TTS-system?

Parameters

<i>culture</i>	Culture of the voice (e.g. "en")
----------------	----------------------------------

Returns

True if a voice is available for a given culture.

5.93.2.6 `static bool Crosstales.RTVoice.Speaker.isVoiceForGenderAvailable (Model.Enum.Gender gender, string culture = "") [static]`

Is a voice available for a given gender and optional culture from the current TTS-system?

Parameters

<i>gender</i>	Gender of the voice
<i>culture</i>	Culture of the voice (e.g. "en", optional)

Returns

True if a voice is available for a given gender and culture.

5.93.2.7 `static bool Crosstales.RTVoice.Speaker.isVoiceForNameAvailable (string name, bool isExact = false) [static]`

Is a voice available for a given name from the current TTS-system?

Parameters

<i>name</i>	Name of the voice (e.g. "Alex")
<i>isExact</i>	Exact match for the voice name (default: false, optional)

Returns

True if a voice is available for a given name.

5.93.2.8 `static void Crosstales.RTVoice.Speaker.Pause (string uid) [static]`

Pause an active TTS-voice with a UID (only for 'Speak'-calls).

Parameters

<i>uid</i>	UID of the speaker
------------	--------------------

5.93.2.9 `static void Crosstales.RTVoice.Speaker.ReloadProvider () [static]`

Reloads the provider.

5.93.2.10 `static void Crosstales.RTVoice.Speaker.Reset () [static]`

Resets this object.

5.93.2.11 `static void Crosstales.RTVoice.Speaker.Silence () [static]`

Silence all active TTS-voices.

5.93.2.12 `static void Crosstales.RTVoice.Speaker.Silence (string uid) [static]`

Silence an active TTS-voice with a UID.

Parameters

<i>uid</i>	UID of the speaker
------------	--------------------

5.93.2.13 `static string Crosstales.RTVoice.Speaker.Speak (string text, AudioSource source = null, Model.Voice voice = null, bool speakImmediately = true, float rate = 1f, float pitch = 1f, float volume = 1f, string outputFile = "", bool forceSSML = true) [static]`

Speaks a text with a given voice.

Parameters

<i>text</i>	Text to speak.
<i>source</i>	AudioSource for the output (optional).
<i>voice</i>	Voice to speak (optional).
<i>speakImmediately</i>	Speak the text immediately (default: true). Only works if 'Source' is not null.
<i>rate</i>	Speech rate of the speaker in percent (1 = 100%, values: 0-3, default: 1, optional).
<i>pitch</i>	Pitch of the speech in percent (1 = 100%, values: 0-2, default: 1, optional).
<i>volume</i>	Volume of the speaker in percent (1 = 100%, values: 0-1, default: 1, optional).
<i>outputFile</i>	Saves the generated audio to an output file (without extension, optional).
<i>forceSSML</i>	Force SSML on supported platforms (default: true, optional).

Returns

UID of the speaker.

5.93.2.14 `static string Crosstales.RTVoice.Speaker.Speak (Model.Wrapper wrapper) [static]`

Speaks a text with a given wrapper.

Parameters

<i>wrapper</i>	Speak wrapper.
----------------	----------------

Returns

UID of the speaker.

5.93.2.15 `static void Crosstales.RTVoice.Speaker.SpeakMarkedWordsWithUID (Model.Wrapper wrapper) [static]`

Speaks and marks a text with a given wrapper.

Parameters

<i>wrapper</i>	Speak wrapper.
----------------	----------------

5.93.2.16 `static void Crosstales.RTVoice.Speaker.SpeakMarkedWordsWithUID (string uid, string text, AudioSource source, Model.Voice voice = null, float rate = 1f, float pitch = 1f, bool forceSSML = true) [static]`

Speaks and marks a text with a given voice and tracks the word position.

Parameters

<i>uid</i>	UID of the speaker
<i>text</i>	Text to speak.
<i>source</i>	AudioSource for the output.
<i>voice</i>	Voice to speak (optional).
<i>rate</i>	Speech rate of the speaker in percent (1 = 100%, values: 0-3, default: 1, optional).
<i>pitch</i>	Pitch of the speech in percent (1 = 100%, values: 0-2, default: 1, optional).
<i>forceSSML</i>	Force SSML on supported platforms (default: true, optional).

5.93.2.17 `static string Crosstales.RTVoice.Speaker.SpeakNative (string text, Model.Voice voice = null, float rate = 1f, float pitch = 1f, float volume = 1f, bool forceSSML = true) [static]`

Speaks a text with a given voice (native mode).

Parameters

<i>text</i>	Text to speak.
<i>voice</i>	Voice to speak (optional).
<i>rate</i>	Speech rate of the speaker in percent (1 = 100%, values: 0-3, default: 1, optional).
<i>pitch</i>	Pitch of the speech in percent (1 = 100%, values: 0-2, default: 1, optional).
<i>volume</i>	Volume of the speaker in percent (1 = 100%, values: 0-1, default: 1, optional).
<i>forceSSML</i>	Force SSML on supported platforms (default: true, optional).

Returns

UID of the speaker.

5.93.2.18 `static string Crosstales.RTVoice.Speaker.SpeakNative (Model.Wrapper wrapper)` `[static]`

Speaks a text with a given wrapper (native mode).

Parameters

<i>wrapper</i>	Speak wrapper.
----------------	----------------

Returns

UID of the speaker.

5.93.2.19 `static void Crosstales.RTVoice.Speaker.SpeakNativeWithUID (Model.Wrapper wrapper)` `[static]`

Speaks a text with a given voice (native mode).

Parameters

<i>wrapper</i>	Speak wrapper.
----------------	----------------

5.93.2.20 `static void Crosstales.RTVoice.Speaker.SpeakWithUID (Model.Wrapper wrapper)` `[static]`

Speaks a text with a given voice.

Parameters

<i>wrapper</i>	Speak wrapper.
----------------	----------------

5.93.2.21 `static void Crosstales.RTVoice.Speaker.UnPause (string uid)` `[static]`

Un-Pause an active TTS-voice with a UID (only for 'Speak'-calls).

Parameters

<i>uid</i>	UID of the speaker
------------	--------------------

5.93.2.22 `static Model.Voice Crosstales.RTVoice.Speaker.VoiceForCulture (string culture, int index = 0, string fallbackCulture = " ", bool isFuzzy = true) [static]`

Get a voice from for a given culture and optional index from the current TTS-system.

Parameters

<i>culture</i>	Culture of the voice (e.g. "en")
<i>index</i>	Index of the voice (default: 0, optional)
<i>index</i>	Fallback culture of the voice (e.g. "en", default "", optional)
<i>isFuzzy</i>	Always returns voices if there is no match with the culture (default: true, optional)

Returns

Voice for the given culture and index.

5.93.2.23 `static Model.Voice Crosstales.RTVoice.Speaker.VoiceForGender (Model.Enum.Gender gender, string culture = " ", int index = 0, string fallbackCulture = " ", bool isFuzzy = true) [static]`

Get a voice from for a given gender and optional culture and optional index from the current TTS-system.

Parameters

<i>gender</i>	Gender of the voice
<i>culture</i>	Culture of the voice (e.g. "en", optional)
<i>index</i>	Index of the voice (default: 0, optional)
<i>index</i>	Fallback culture of the voice (e.g. "en", default "", optional)
<i>isFuzzy</i>	Always returns voices if there is no match with the gender and/or culture (default: true, optional)

Returns

Voice for the given culture and index.

5.93.2.24 `static Model.Voice Crosstales.RTVoice.Speaker.VoiceForName (string name, bool isExact = false) [static]`

Get a voice for a given name from the current TTS-system.

Parameters

<i>name</i>	Name of the voice (e.g. "Alex")
<i>isExact</i>	Exact match for the voice name (default: false, optional)

Returns

Voice for the given name or null if not found.

5.93.2.25 `static System.Collections.Generic.List<Model.Voice> Crosstales.RTVoice.Speaker.VoicesForCulture (string culture, bool isFuzzy = true) [static]`

Get all available voices for a given culture from the current TTS-system.

Parameters

<i>culture</i>	Culture of the voice (e.g. "en")
<i>isFuzzy</i>	Always returns voices if there is no match with the culture (default: true, optional)

Returns

All available voices (alphabetically ordered by 'Name') for a given culture as a list.

5.93.2.26 `static System.Collections.Generic.List<Model.Voice> Crosstales.RTVoice.Speaker.VoicesForGender (Model.Enum.Gender gender, string culture = " ", bool isFuzzy = true) [static]`

Get all available voices for a given gender and optional culture from the current TTS-system.

Parameters

<i>gender</i>	Gender of the voice
<i>culture</i>	Culture of the voice (e.g. "en", optional)
<i>isFuzzy</i>	Always returns voices if there is no match with the gender and/or culture (default: true, optional)

Returns

All available voices (alphabetically ordered by 'Name') for a given gender and culture as a list.

5.93.3 Member Data Documentation

5.93.3.1 `bool Crosstales.RTVoice.Speaker.AutoClearTags = false`

Automatically clear tags from speeches depending on the capabilities of the current TTS-system (default: false).

5.93.3.2 `bool Crosstales.RTVoice.Speaker.CustomMode = false`

Enables or disables the custom provider (default: false).

5.93.3.3 `Provider.BaseCustomVoiceProvider Crosstales.RTVoice.Speaker.CustomProvider`

Custom provider for RT-Voice.

5.93.3.4 **bool** Crosstales.RTVoice.Speaker.DontDestroy = true

Don't destroy gameobject during scene switches (default: true).

5.93.3.5 **bool** Crosstales.RTVoice.Speaker.ESpeakMode = false

Enable or disable eSpeak for standalone platforms (default: false).

5.93.3.6 **Model.Enum.ESpeakModifiers** Crosstales.RTVoice.Speaker.ESpeakModifier = Model.Enum.ESpeakModifiers.none

Active modifier for all eSpeak voices (default: none, m1-m6 = male, f1-f4 = female).

5.93.3.7 **bool** Crosstales.RTVoice.Speaker.MaryTTSMode = false

Enables or disables MaryTTS (default: false).

5.93.3.8 **string** Crosstales.RTVoice.Speaker.MaryTTSPassword = string.Empty

User password for MaryTTS (default: empty).

5.93.3.9 **int** Crosstales.RTVoice.Speaker.MaryTTSPort = 59125

Server port for MaryTTS (default: 59125).

5.93.3.10 **Model.Enum.MaryTTSType** Crosstales.RTVoice.Speaker.MaryTTSType = Model.Enum.MaryTTSType.RAWMAR↵
YXML

Input type for MaryTTS (default: MaryTTSType.RAWMARYXML).

5.93.3.11 **string** Crosstales.RTVoice.Speaker.MaryTTSUrl = "http://mary.dfki.de"

Server URL for MaryTTS.

5.93.3.12 **string** Crosstales.RTVoice.Speaker.MaryTTSUser = string.Empty

User name for MaryTTS (default: empty).

5.93.3.13 **bool** Crosstales.RTVoice.Speaker.SilenceOnDisable = false

Silence any speeches if this component gets disabled (default: false).

5.93.3.14 `bool Crosstales.RTVoice.Speaker.SilenceOnFocusLost = true`

Silence any speeches if the application loses the focus (default: true).

5.93.3.15 `bool Crosstales.RTVoice.Speaker.WindowsLegacy = false`

Enable or disable the legacy Windows provider (default: false).

5.93.4 Property Documentation

5.93.4.1 `bool Crosstales.RTVoice.Speaker.areVoicesReady` `[static], [get]`

Are all voices ready to speak?

5.93.4.2 `string Crosstales.RTVoice.Speaker.AudioFileExtension` `[static], [get]`

Returns the extension of the generated audio files.

Returns

Extension of the generated audio files.

5.93.4.3 `int Crosstales.RTVoice.Speaker.BusyCount` `[static], [get]`

Number of activities.

5.93.4.4 `System.Collections.Generic.List<string> Crosstales.RTVoice.Speaker.Cultures` `[static], [get]`

Get all available cultures from the current TTS-system (ISO 639-1).

Returns

All available cultures (alphabetically ordered by 'Culture') as a list.

5.93.4.5 `Provider.BaseCustomVoiceProvider Crosstales.RTVoice.Speaker.CustomVoiceProvider` `[static], [get], [set]`

Enables or disables MaryTTS.

5.93.4.6 `string Crosstales.RTVoice.Speaker.DefaultVoiceName` `[static], [get]`

Returns the default voice name of the current TTS-provider.

Returns

Default voice name of the current TTS-provider.

5.93.4.7 `Model.Enum.ESpeakModifiers Crosstales.RTVoice.Speaker.ESpeakMod` `[static], [get], [set]`

Active modifier for all eSpeak voices (m1-m6 = male, f1-f4 = female).

5.93.4.8 `bool Crosstales.RTVoice.Speaker.hasCoRoutines` `[static], [get]`

Indicates if this TTS-system uses co-routines.

Returns

TTS-system uses co-routines.

5.93.4.9 `bool Crosstales.RTVoice.Speaker.isAutoClearTags` `[static], [get], [set]`

Automatically clear tags from speeches depending on the capabilities of the current TTS-system.

5.93.4.10 `bool Crosstales.RTVoice.Speaker.isBusy` `[static], [get]`

Checks if RT-Voice is busy on this system.

Returns

True if RT-Voice is busy on this system.

5.93.4.11 `bool Crosstales.RTVoice.Speaker.isCustomMode` `[static], [get], [set]`

Enables or disables the custom voice provider.

5.93.4.12 `bool Crosstales.RTVoice.Speaker.isESpeakMode` `[static], [get], [set]`

Enable or disable eSpeak for standalone platforms.

5.93.4.13 `bool Crosstales.RTVoice.Speaker.isMaryMode` `[static], [get], [set]`

Enables or disables MaryTTS.

5.93.4.14 `bool Crosstales.RTVoice.Speaker.isOnlineService` `[static], [get]`

Indicates if this TTS-system is an online service like MaryTTS or AWS Polly.

Returns

TTS-system is an online service.

5.93.4.15 `bool Crosstales.RTVoice.Speaker.isPlatformSupported` `[static], [get]`

Indicates if this TTS-system is supporting the current platform.

Returns

TTS-system supports current platform.

5.93.4.16 `bool Crosstales.RTVoice.Speaker.isSilenceOnDisable` `[static], [get], [set]`

Silence any speeches if this component gets disabled.

5.93.4.17 `bool Crosstales.RTVoice.Speaker.isSilenceOnFocustLost` `[static], [get], [set]`

Silence any speeches if the application loses the focus.

5.93.4.18 `bool Crosstales.RTVoice.Speaker.isSpeaking` `[static], [get]`

Checks if RT-Voice is speaking on this system.

Returns

True if RT-Voice is speaking on this system.

5.93.4.19 `bool Crosstales.RTVoice.Speaker.isSpeakNativeSupported` `[static], [get]`

Indicates if this TTS-system is supporting SpeakNative.

Returns

TTS-system supports SpeakNative.

5.93.4.20 `bool Crosstales.RTVoice.Speaker.isSpeakSupported` `[static], [get]`

Indicates if this TTS-system is supporting Speak.

Returns

TTS-system supports Speak.

5.93.4.21 `bool Crosstales.RTVoice.Speaker.isSSMLSupported` `[static], [get]`

Indicates if this TTS-system is supporting SSML.

Returns

TTS-system supports SSML.

5.93.4.22 `bool Crosstales.RTVoice.Speaker.isTTSAvailable` `[static], [get]`

Checks if TTS is available on this system.

Returns

True if TTS is available on this system.

5.93.4.23 `bool Crosstales.RTVoice.Speaker.isWindowsLegacy` `[static], [get], [set]`

Enable or disable the legacy Windows provider.

5.93.4.24 `bool Crosstales.RTVoice.Speaker.isWorkingInEditor` `[static], [get]`

Indicates if this TTS-system is working directly inside the Unity Editor (without 'Play'-mode).

Returns

The TTS-system is working directly inside the Unity Editor.

5.93.4.25 `string Crosstales.RTVoice.Speaker.MaryPassword` `[static], [set]`

Password for MaryTTS.

5.93.4.26 `int Crosstales.RTVoice.Speaker.MaryPort` `[static], [get], [set]`

Server port for MaryTTS.

5.93.4.27 `Model.Enum.MaryTTSType` `Crosstales.RTVoice.Speaker.MaryType` `[static], [get], [set]`

Input type for MaryTTS.

5.93.4.28 `string` `Crosstales.RTVoice.Speaker.MaryUrl` `[static], [get], [set]`

Server URL for MaryTTS.

5.93.4.29 `string` `Crosstales.RTVoice.Speaker.MaryUser` `[static], [get], [set]`

User name for MaryTTS.

5.93.4.30 `int` `Crosstales.RTVoice.Speaker.MaxTextLength` `[static], [get]`

Maximal length of the speech text (in characters) for the current TTS-system.

Returns

The maximal length of the speech text.

5.93.4.31 `ErrorInfo` `Crosstales.RTVoice.Speaker.OnErrorInfo` `[static], [add], [remove]`

An event triggered whenever an error occurs.

5.93.4.32 `ProviderChange` `Crosstales.RTVoice.Speaker.OnProviderChange` `[static], [add], [remove]`

An event triggered whenever a provider changes (e.g. Windows to MaryTTS).

5.93.4.33 `SpeakAudioGenerationComplete` `Crosstales.RTVoice.Speaker.OnSpeakAudioGenerationComplete` `[static], [add], [remove]`

An event triggered whenever a speak audio generation is completed.

5.93.4.34 `SpeakAudioGenerationStart` `Crosstales.RTVoice.Speaker.OnSpeakAudioGenerationStart` `[static], [add], [remove]`

An event triggered whenever a speak audio generation is started.

5.93.4.35 `SpeakComplete` `Crosstales.RTVoice.Speaker.OnSpeakComplete` `[static], [add], [remove]`

An event triggered whenever a speak is completed.

5.93.4.36 SpeakCurrentPhoneme `Crosstales.RTVoice.Speaker.OnSpeakCurrentPhoneme` `[static], [add], [remove]`

An event triggered whenever a new phoneme is spoken (native, Windows only).

5.93.4.37 SpeakCurrentViseme `Crosstales.RTVoice.Speaker.OnSpeakCurrentViseme` `[static], [add], [remove]`

An event triggered whenever a new viseme is spoken (native, Windows only).

5.93.4.38 SpeakCurrentWord `Crosstales.RTVoice.Speaker.OnSpeakCurrentWord` `[static], [add], [remove]`

An event triggered whenever a new word is spoken (native, Windows and iOS only).

5.93.4.39 SpeakStart `Crosstales.RTVoice.Speaker.OnSpeakStart` `[static], [add], [remove]`

An event triggered whenever a speak is started.

5.93.4.40 VoicesReady `Crosstales.RTVoice.Speaker.OnVoicesReady` `[static], [add], [remove]`

An event triggered whenever the voices of a provider are ready.

5.93.4.41 int `Crosstales.RTVoice.Speaker.SpeechCount` `[static], [get]`

Number of active speeches.

5.93.4.42 System.Collections.Generic.List<Model.Voice> `Crosstales.RTVoice.Speaker.Voices` `[static], [get]`

Get all available voices from the current TTS-system.

Returns

All available voices (alphabetically ordered by 'Name') as a list.


The documentation for this class was generated from the following file:

- `D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↵ Scripts/Speaker.cs`

5.94 Crosstales.RTVoice.EditorExtension.SpeakerEditor Class Reference

Custom editor for the 'Speaker'-class.

Inheritance diagram for Crosstales.RTVoice.EditorExtension.SpeakerEditor:



Public Member Functions

- void **OnEnable** ()
- void **OnDisable** ()
- override bool **RequiresConstantRepaint** ()
- override void **OnInspectorGUI** ()

5.94.1 Detailed Description


Custom editor for the 'Speaker'-class.

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Editor/Extension/SpeakerEditor.cs

5.95 Crosstales.RTVoice.SALSA.SpeakSimple Class Reference

Inheritance diagram for Crosstales.RTVoice.SALSA.SpeakSimple:



Public Member Functions

- void **Silence** ()
- void **Talk** ()

Public Attributes

- AudioSource **Source**
- InputField **EnterText**
- Slider **RateSlider**
- Slider **PitchSlider**


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/SALSA/Scripts/SpeakSimple.cs

5.96 HutongGames.PlayMaker.Actions.SpeakUI Class Reference

Speak-action for UI-components in PlayMaker.

Inheritance diagram for HutongGames.PlayMaker.Actions.SpeakUI:



Public Member Functions

- override void **OnEnter** ()

Public Attributes

- InputField Text
Text to speak.
- InputField RTVoiceName
Name of the RT-Voice.
- FsmString Culture = "en"
Fallback culture (e.g. 'en', optional).

Additional Inherited Members

5.96.1 Detailed Description

Speak-action for UI-components in PlayMaker.

5.96.2 Member Data Documentation

5.96.2.1 FsmString HutongGames.PlayMaker.Actions.SpeakUI.Culture = "en"

Fallback culture (e.g. 'en', optional).

5.96.2.2 InputField HutongGames.PlayMaker.Actions.SpeakUI.RTVoiceName

Name of the RT-Voice.

5.96.2.3 InputField HutongGames.PlayMaker.Actions.SpeakUI.Text

Text to speak.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/PlayMaker/Scripts/SpeakUI.cs

5.97 Crosstales.RTVoice.PlayMaker.SpeakUIEditor Class Reference

Custom editor for the SpeakUI-action.

Inheritance diagram for Crosstales.RTVoice.PlayMaker.SpeakUIEditor:



Public Member Functions

- override void **OnEnable** ()
- override bool **OnGUI** ()

5.97.1 Detailed Description

Custom editor for the SpeakUI-action.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/PlayMaker/Editor/SpeakUIEditor.cs

5.98 Crosstales.RTVoice.Demo.SpeakWrapper Class Reference

Wrapper for the dynamic speakers.

Inheritance diagram for Crosstales.RTVoice.Demo.SpeakWrapper:



Public Member Functions

- void **Start** ()
- void **Speak** ()

Public Attributes

- Voice **SpeakerVoice**
- InputField **Input**
- Text **Label**
- AudioSource **Audio**

5.98.1 Detailed Description

Wrapper for the dynamic speakers.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Demo/Scripts/SpeakWrapper.cs

5.99 Crosstales.Common.Util.SpectrumVisualizer Class Reference

Simple spectrum visualizer.

Inheritance diagram for Crosstales.Common.Util.SpectrumVisualizer:



Public Member Functions

- void **Start** ()
- void **Update** ()

Public Attributes

- FFTAnalyzer Analyzer
FFT-analyzer with the spectrum data.
- GameObject VisualPrefab
summary> Width per prefab.
- float Width = 0.075f
summary> Gain-power for the frequency.
- float Gain = 70f
summary> Frequency band from left-to-right (default: true).
- bool LeftToRight = true
summary> Opacity of the material of the prefab (default: 1).
- float **Opacity** = 1f

5.99.1 Detailed Description

Simple spectrum visualizer.

5.99.2 Member Data Documentation

5.99.2.1 FFTAnalyzer Crosstales.Common.Util.SpectrumVisualizer.Analyzer

FFT-analyzer with the spectrum data.

*summary>*Prefab for the frequency representation.

5.99.2.2 float Crosstales.Common.Util.SpectrumVisualizer.Gain = 70f

*summary>*Frequency band from left-to-right (default: true).

5.99.2.3 bool Crosstales.Common.Util.SpectrumVisualizer.LeftToRight = true

*summary>*Opacity of the material of the prefab (default: 1).

5.99.2.4 GameObject Crosstales.Common.Util.SpectrumVisualizer.VisualPrefab

*summary>*Width per prefab.

5.99.2.5 float `Crosstales.Common.Util.SpectrumVisualizer.Width` = 0.075f

summary>Gain-power for the frequency.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/Scripts/Util/SpectrumVisualizer.cs

5.100 HutongGames.PlayMaker.Actions.SpeechText Class Reference

SpeechText-action for PlayMaker.

Inheritance diagram for HutongGames.PlayMaker.Actions.SpeechText:



Public Member Functions

- override void **OnEnter** ()
- override void **OnExit** ()

Public Attributes

- `Crosstales.RTVoice.Tool.SpeechText Obj`
Add a SpeechText (default: first object in scene).

5.100.1 Detailed Description

SpeechText-action for PlayMaker.

5.100.2 Member Data Documentation

5.100.2.1 `Crosstales.RTVoice.Tool.SpeechText` HutongGames.PlayMaker.Actions.SpeechText.Obj

Add a SpeechText (default: first object in scene).


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/PlayMaker/Scripts/SpeechText.cs

5.101 Crosstales.RTVoice.Tool.SpeechText Class Reference

Allows to speak and store generated audio.

Inheritance diagram for Crosstales.RTVoice.Tool.SpeechText:



Public Member Functions

- void **Start** ()
- void **OnDestroy** ()
- void **OnValidate** ()
- void **Speak** ()
Speak the text.
- void **Silence** ()
Silence the speech.

Public Attributes

- string **Text** = string.Empty
Text to speak.
- Model.VoiceAlias **Voices**
Voices for the speech.
- Model.Enum.SpeakMode **Mode** = Model.Enum.SpeakMode.Speak
Speak mode (default: 'Speak').
- AudioSource **Source**
AudioSource for the output (optional).
- float **Rate** = 1f
Speech rate of the speaker in percent (1 = 100%, default: 1, optional).
- float **Pitch** = 1f
Speech pitch of the speaker in percent (1 = 100%, default: 1, optional, mobile only).
- float **Volume** = 1f
Volume of the speaker in percent (1 = 100%, default: 1, optional, Windows only).
- bool **PlayOnStart** = false
Enable speaking of the text on start (default: false).
- float **Delay** = 0f
Delay in seconds until the speech for this text starts (default: 0).
- bool **GenerateAudioFile** = false
Generate audio file on/off (default: false).
- string **FileName** = @"_generatedAudio/Speech01"
File name (incl. path) for the generated audio.
- bool **FileInsideAssets** = true
Is the generated file path inside the Assets-folder (current project)? If this option is enabled, it prefixes the path with 'Application.dataPath'.

Properties

- **SpeechTextStart OnSpeechTextStart**
An event triggered whenever a SpeechText 'Speak' is started.
- **SpeechTextComplete OnSpeechTextComplete**
An event triggered whenever a SpeechText 'Speak' is completed.
- **string CurrentText** [get, set]
Text to speak (main use is for UI).
- **float CurrentRate** [get, set]
Speech rate of the speaker in percent (main use is for UI).
- **float CurrentPitch** [get, set]
Speech pitch of the speaker in percent (main use is for UI).
- **float CurrentVolume** [get, set]
Volume of the speaker in percent (main use is for UI).

5.101.1 Detailed Description

Allows to speak and store generated audio.

5.101.2 Member Function Documentation

5.101.2.1 void Crosstales.RTVoice.Tool.SpeechText.Silence ()

Silence the speech.

5.101.2.2 void Crosstales.RTVoice.Tool.SpeechText.Speak ()

Speak the text.

5.101.3 Member Data Documentation

5.101.3.1 float Crosstales.RTVoice.Tool.SpeechText.Delay = 0f

Delay in seconds until the speech for this text starts (default: 0).

5.101.3.2 bool Crosstales.RTVoice.Tool.SpeechText.FileInsideAssets = true

Is the generated file path inside the Assets-folder (current project)? If this option is enabled, it prefixes the path with 'Application.dataPath'.

5.101.3.3 string Crosstales.RTVoice.Tool.SpeechText.FileName = @"_generatedAudio/Speech01"

File name (incl. path) for the generated audio.

5.101.3.4 **bool** Crosstales.RTVoice.Tool.SpeechText.GenerateAudioFile = false

Generate audio file on/off (default: false).

5.101.3.5 **Model.Enum.SpeakMode** Crosstales.RTVoice.Tool.SpeechText.Mode = Model.Enum.SpeakMode.Speak

Speak mode (default: 'Speak').

5.101.3.6 **float** Crosstales.RTVoice.Tool.SpeechText.Pitch = 1f

Speech pitch of the speaker in percent (1 = 100%, default: 1, optional, mobile only).

5.101.3.7 **bool** Crosstales.RTVoice.Tool.SpeechText.PlayOnStart = false

Enable speaking of the text on start (default: false).

5.101.3.8 **float** Crosstales.RTVoice.Tool.SpeechText.Rate = 1f

Speech rate of the speaker in percent (1 = 100%, default: 1, optional).

5.101.3.9 **AudioSource** Crosstales.RTVoice.Tool.SpeechText.Source

AudioSource for the output (optional).

5.101.3.10 **string** Crosstales.RTVoice.Tool.SpeechText.Text = string.Empty

Text to speak.

5.101.3.11 **Model.VoiceAlias** Crosstales.RTVoice.Tool.SpeechText.Voices

Voices for the speech.

5.101.3.12 **float** Crosstales.RTVoice.Tool.SpeechText.Volume = 1f

Volume of the speaker in percent (1 = 100%, default: 1, optional, Windows only).

5.101.4 Property Documentation

5.101.4.1 **float** Crosstales.RTVoice.Tool.SpeechText.CurrentPitch [get], [set]

Speech pitch of the speaker in percent (main use is for UI).

5.101.4.2 float `Crosstales.RTVoice.Tool.SpeechText.CurrentRate` `[get]`, `[set]`

Speech rate of the speaker in percent (main use is for UI).

5.101.4.3 string `Crosstales.RTVoice.Tool.SpeechText.CurrentText` `[get]`, `[set]`

Text to speak (main use is for UI).

5.101.4.4 float `Crosstales.RTVoice.Tool.SpeechText.CurrentVolume` `[get]`, `[set]`

Volume of the speaker in percent (main use is for UI).

5.101.4.5 `SpeechTextComplete` `Crosstales.RTVoice.Tool.SpeechText.OnSpeechTextComplete` `[add]`, `[remove]`

An event triggered whenever a `SpeechText` 'Speak' is completed.

5.101.4.6 `SpeechTextStart` `Crosstales.RTVoice.Tool.SpeechText.OnSpeechTextStart` `[add]`, `[remove]`

An event triggered whenever a `SpeechText` 'Speak' is started.


The documentation for this class was generated from the following file:

- `D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Tool/SpeechText.cs`

5.102 Crosstales.RTVoice.EditorExtension.SpeechTextEditor Class Reference

Custom editor for the 'SpeechText'-class.

Inheritance diagram for `Crosstales.RTVoice.EditorExtension.SpeechTextEditor`:



Public Member Functions

- void **OnEnable** ()
- void **OnDisable** ()
- override void **OnInspectorGUI** ()

5.102.1 Detailed Description

Custom editor for the 'SpeechText'-class.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Editor/Extension/SpeechTextEditor.cs

5.103 Crosstales.RTVoice.PlayMaker.SpeechTextEditor Class Reference

Custom editor for the SpeechText-action.

Inheritance diagram for Crosstales.RTVoice.PlayMaker.SpeechTextEditor:



Additional Inherited Members

5.103.1 Detailed Description

Custom editor for the SpeechText-action.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/PlayMaker/Editor/SpeechTextEditor.cs

5.104 Crosstales.UI.StaticManager Class Reference

Static Button Manager.

Inheritance diagram for Crosstales.UI.StaticManager:



Public Member Functions

- void **Quit** ()
Quit the application (stop playing inside the Editor).
- void **OpenCrosstales** ()
summary>Open the Unity AssetStore homepage.
- void **OpenAssetstore** ()

5.104.1 Detailed Description

Static Button Manager.

5.104.2 Member Function Documentation

5.104.2.1 void Crosstales.UI.StaticManager.OpenCrosstales ()

summary>Open the Unity AssetStore homepage.

5.104.2.2 void Crosstales.UI.StaticManager.Quit ()

Quit the application (stop playing inside the Editor).

summary>Open the crosstales homepage.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ UI/Scripts/StaticManager.cs

5.105 Crosstales.Common.Util.SurviveSceneSwitch Class Reference

Allows any Unity gameobject to survive a scene switch. This is especially useful to keep the music playing while loading a new scene.

Inheritance diagram for Crosstales.Common.Util.SurviveSceneSwitch:



Public Member Functions

- void **Awake** ()
- void **Start** ()
- void **Update** ()

Public Attributes

- `GameObject[] Survivors`
Objects which have to survive a scene switch.

5.105.1 Detailed Description

Allows any Unity gameobject to survive a scene switch. This is especially useful to keep the music playing while loading a new scene.

5.105.2 Member Data Documentation

5.105.2.1 `GameObject [] Crosstailes.Common.Util.SurviveSceneSwitch.Survivors`

Objects which have to survive a scene switch.


The documentation for this class was generated from the following file:

- `D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstailes/Common/Scripts/Tool/SurviveSceneSwitch.cs`

5.106 Crosstailes.RTVoice.AWSPolly.Switcher Class Reference

Simple switcher to test the functionality of the AWS Polly provider.

Inheritance diagram for `Crosstailes.RTVoice.AWSPolly.Switcher`:



Public Member Functions

- `void OnEnable ()`
- `void OnDisable ()`
- `void Switch ()`

5.106.1 Detailed Description

Simple switcher to test the functionality of the AWS Polly provider.


The documentation for this class was generated from the following file:

- `D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstailes/RTVoice/3rd party/AWS Polly/Demo/Scripts/Switcher.cs`

5.107 Crosstales.Common.Util.TakeScreenshot Class Reference

Take screen shots inside an application.

Inheritance diagram for Crosstales.Common.Util.TakeScreenshot:



Public Member Functions

- void **Start** ()
- void Update ()
summary> Capture the screen.
- void **Capture** ()

Public Attributes

- string Prefix = "CT_Screenshot"
Prefix for the generate file names.
- int Scale = 1
summary> Key-press to capture the screen (default: F8).
- KeyCode **KeyCode** = KeyCode.F8

5.107.1 Detailed Description

Take screen shots inside an application.

5.107.2 Member Function Documentation

5.107.2.1 void Crosstales.Common.Util.TakeScreenshot.Update ()

summary> Capture the screen.

5.107.3 Member Data Documentation

5.107.3.1 string Crosstales.Common.Util.TakeScreenshot.Prefix = "CT_Screenshot"

Prefix for the generate file names.

summary> Factor by which to increase resolution (default: 1).

5.107.3.2 int Crosstales.Common.Util.TakeScreenshot.Scale = 1

summary>Key-press to capture the screen (default: F8).


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/Scripts/Tool/TakeScreenshot.cs

5.108 Crosstales.RTVoice.Tool.TextFileSpeaker Class Reference

Allows to speak text files.

Inheritance diagram for Crosstales.RTVoice.Tool.TextFileSpeaker:



Public Member Functions

- void **Start** ()
- void **Update** ()
- void **OnDestroy** ()
- void **OnValidate** ()
- void **SpeakAll** ()
Speaks all texts until StopAll is called.
- void **StopAll** ()
Stops speaking all texts.
- void **Next** ()
Speaks the next text (main use for UI).
- void **Next** (bool random)
Speaks the next text.
- void **Previous** ()
Speaks the previous text (main use for UI).
- void **Previous** (bool random)
Speaks the previous text.
- void **Speak** ()
Speaks a text (main use for UI).
- string **SpeakText** (int index=-1, bool random=false)
Speaks a text with an optional index.
- void **Silence** ()
Silence the speech.
- void **Reload** ()
Reloads all text files (e.g. when new text files were added during runtime).

Public Attributes

- TextAsset[] TextFiles
Text files to speak.
- Model.VoiceAlias Voices
Voices for the speech.
- Model.Enum.SpeakMode Mode = Model.Enum.SpeakMode.Speak
Speak mode (default: 'Speak').
- bool PlayOnStart = false
Enable speaking of a random text file on start (default: false).
- bool PlayAllOnStart = false
Enable speaking of a all random text files on start (default: false). NOTE: this can only be stopped with the "StopAll"-method
- bool SpeakRandom = false
Speaks the text files in random order (default: false).
- float Delay = 0f
Delay until the speech for this text starts (default: 0).
- AudioSource Source
AudioSource for the output (optional).
- float Rate = 1f
Speech rate of the speaker in percent (1 = 100%, default: 1, optional).
- float Pitch = 1f
Speech pitch of the speaker in percent (1 = 100%, default: 1, optional, mobile only).
- float Volume = 1f
Volume of the speaker in percent (1 = 100%, default: 1, optional, Windows only).

Properties

- float CurrentRate [get, set]
Speech rate of the speaker in percent (main use is for UI).
- float CurrentPitch [get, set]
Speech pitch of the speaker in percent (main use is for UI).
- float CurrentVolume [get, set]
Volume of the speaker in percent (main use is for UI).

5.108.1 Detailed Description

Allows to speak text files.

5.108.2 Member Function Documentation

5.108.2.1 void Crosstales.RTVoice.Tool.TextFileSpeaker.Next ()

Speaks the next text (main use for UI).

5.108.2.2 void Crosstales.RTVoice.Tool.TextFileSpeaker.Next (bool random)

Speaks the next text.

Parameters

<i>random</i>	Speak a random text
---------------	---------------------

5.108.2.3 void Crosstales.RTVoice.Tool.TextFileSpeaker.Previous ()

Speaks the previous text (main use for UI).

5.108.2.4 void Crosstales.RTVoice.Tool.TextFileSpeaker.Previous (bool *random*)

Speaks the previous text.

Parameters

<i>random</i>	Speak a random text
---------------	---------------------

5.108.2.5 void Crosstales.RTVoice.Tool.TextFileSpeaker.Reload ()

Reloads all text files (e.g. when new text files were added during runtime).

5.108.2.6 void Crosstales.RTVoice.Tool.TextFileSpeaker.Silence ()

Silence the speech.

5.108.2.7 void Crosstales.RTVoice.Tool.TextFileSpeaker.Speak ()

Speaks a text (main use for UI).

5.108.2.8 void Crosstales.RTVoice.Tool.TextFileSpeaker.SpeakAll ()

Speaks all texts until StopAll is called.

5.108.2.9 string Crosstales.RTVoice.Tool.TextFileSpeaker.SpeakText (int *index* = -1, bool *random* = false)

Speaks a text with an optional index.

Parameters

<i>index</i>	Index of the text (default: -1 (random), optional).
<i>random</i>	Speak a random text (default: false, optional)

Returns

UID of the speaker.

5.108.2.10 void Crosstales.RTVoice.Tool.TextFileSpeaker.StopAll ()

Stops speaking all texts.

5.108.3 Member Data Documentation

5.108.3.1 float Crosstales.RTVoice.Tool.TextFileSpeaker.Delay = 0f

Delay until the speech for this text starts (default: 0).

5.108.3.2 Model.Enum.SpeakMode Crosstales.RTVoice.Tool.TextFileSpeaker.Mode = Model.Enum.SpeakMode.Speak

Speak mode (default: 'Speak').

5.108.3.3 float Crosstales.RTVoice.Tool.TextFileSpeaker.Pitch = 1f

Speech pitch of the speaker in percent (1 = 100%, default: 1, optional, mobile only).

5.108.3.4 bool Crosstales.RTVoice.Tool.TextFileSpeaker.PlayAllOnStart = false

Enable speaking of a all random text files on start (default: false). NOTE: this can only be stopped with the "Stop↵All"-method

5.108.3.5 bool Crosstales.RTVoice.Tool.TextFileSpeaker.PlayOnStart = false

Enable speaking of a random text file on start (default: false).

5.108.3.6 float Crosstales.RTVoice.Tool.TextFileSpeaker.Rate = 1f

Speech rate of the speaker in percent (1 = 100%, default: 1, optional).

5.108.3.7 AudioSource Crosstales.RTVoice.Tool.TextFileSpeaker.Source

AudioSource for the output (optional).

5.108.3.8 bool Crosstales.RTVoice.Tool.TextFileSpeaker.SpeakRandom = false

Speaks the text files in random order (default: false).

5.108.3.9 TextAsset [] Crosstales.RTVoice.Tool.TextFileSpeaker.TextFiles

Text files to speak.

5.108.3.10 Model.VoiceAlias Crosstales.RTVoice.Tool.TextFileSpeaker.Voices

Voices for the speech.

5.108.3.11 float Crosstales.RTVoice.Tool.TextFileSpeaker.Volume = 1f

Volume of the speaker in percent (1 = 100%, default: 1, optional, Windows only).

5.108.4 Property Documentation

5.108.4.1 float Crosstales.RTVoice.Tool.TextFileSpeaker.CurrentPitch [get], [set]

Speech pitch of the speaker in percent (main use is for UI).

5.108.4.2 float Crosstales.RTVoice.Tool.TextFileSpeaker.CurrentRate [get], [set]

Speech rate of the speaker in percent (main use is for UI).

5.108.4.3 float Crosstales.RTVoice.Tool.TextFileSpeaker.CurrentVolume [get], [set]

Volume of the speaker in percent (main use is for UI).


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Tool/TextFileSpeaker.cs

5.109 HutongGames.PlayMaker.Actions.TextFileSpeaker Class Reference

TextFileSpeaker-action for PlayMaker.

Inheritance diagram for HutongGames.PlayMaker.Actions.TextFileSpeaker:



Public Member Functions

- override void **OnEnter** ()

Public Attributes

- Crosstales.RTVoice.Tool.TextFileSpeaker Obj
Add a TextFileSpeaker (default: first object in scene).

5.109.1 Detailed Description

TextFileSpeaker-action for PlayMaker.

5.109.2 Member Data Documentation

5.109.2.1 Crosstales.RTVoice.Tool.TextFileSpeaker HutongGames.PlayMaker.Actions.TextFileSpeaker.Obj

Add a TextFileSpeaker (default: first object in scene).


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/PlayMaker/Scripts/TextFileSpeaker.cs

5.110 Crosstales.RTVoice.EditorExtension.TextFileSpeakerEditor Class Reference

Custom editor for the 'TextFileSpeaker'-class.

Inheritance diagram for Crosstales.RTVoice.EditorExtension.TextFileSpeakerEditor:



Public Member Functions

- void **OnEnable** ()
- void **OnDisable** ()
- override void **OnInspectorGUI** ()

5.110.1 Detailed Description

Custom editor for the 'TextFileSpeaker'-class.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↵
Editor/Extension/TextFileSpeakerEditor.cs

5.111 Crosstales.RTVoice.PlayMaker.TextFileSpeakerEditor Class Reference

Custom editor for the TextFileSpeaker-action.

Inheritance diagram for Crosstales.RTVoice.PlayMaker.TextFileSpeakerEditor:



Additional Inherited Members

5.111.1 Detailed Description

Custom editor for the TextFileSpeaker-action.

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RT↵
Voice/3rd party/PlayMaker/Editor/TextFileSpeakerEditor.cs

5.112 Crosstales.RTVoice.EditorTask.Tracer Class Reference

Gather some tracing data for the asset.

5.112.1 Detailed Description

Gather some tracing data for the asset.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↵
Editor/Task/Tracer.cs

5.113 Crosstales.RTVoice.UDEA2.UDEAConnector Class Reference

Connects UDEA and RT-Voice. Must be placed on a dialogue prefab.

Inheritance diagram for Crosstales.RTVoice.UDEA2.UDEAConnector:



Public Member Functions

- void **Start** ()
- void **OnDestroy** ()
- void **OnValidate** ()
- void **SpeakRT** ()

Public Attributes

- UDEAVoiceWrapper[] Voices
Voices for the UDEA-characters (optional).
- string Culture
Fallback culture for all sequences (e.g. 'en', optional).

5.113.1 Detailed Description

Connects UDEA and RT-Voice. Must be placed on a dialogue prefab.

5.113.2 Member Data Documentation

5.113.2.1 string Crosstales.RTVoice.UDEA2.UDEAConnector.Culture

Fallback culture for all sequences (e.g. 'en', optional).

5.113.2.2 UDEAVoiceWrapper [] Crosstales.RTVoice.UDEA2.UDEAConnector.Voices

Voices for the UDEA-characters (optional).


The documentation for this class was generated from the following file:

- D:/slauberberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/THE Dialogue Engine/Scripts/UDEAConnector.cs

5.114 Crosstales.RTVoice.UDEA2.UDEAConnectorEditor Class Reference

Custom editor for the 'UDEAConnector'-class.

Inheritance diagram for Crosstales.RTVoice.UDEA2.UDEAConnectorEditor:



Public Member Functions

- override void **OnInspectorGUI** ()

5.114.1 Detailed Description

Custom editor for the 'UDEAConnector'-class.

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/THE Dialogue Engine/Editor/UDEAConnectorEditor.cs

5.115 Crosstales.RTVoice.UDEA2.UDEAVoiceWrapper Class Reference

Wrapper for an UDEA-character to an RT-Voice.

Public Member Functions

- override string **ToString** ()

Public Attributes

- string UDEAVoiceName = string.Empty
"Name of the UDEA-character on-screen."
- Model.VoiceAlias Voices
Voices for the speech.
- AudioSource Source
Origin AudioSource (optional).
- float Rate = 1f
Speech rate of the speaker in percent (1 = 100%, default: 1, optional).
- float Pitch = 1f
Speech pitch of the speaker in percent (1 = 100%, default: 1, optional, mobile only).
- float Volume = 1f
Volume of the speaker in percent (1 = 100%, default: 1, optional).
- bool IgnoreCharacter = false
Ignore this character (default: false).
- bool **initialized** = false

5.115.1 Detailed Description

Wrapper for an UDEA-character to an RT-Voice.

5.115.2 Member Data Documentation

5.115.2.1 bool Crosstales.RTVoice.UDEA2.UDEAVoiceWrapper.IgnoreCharacter = false

Ignore this character (default: false).

5.115.2.2 float Crosstales.RTVoice.UDEA2.UDEAVoiceWrapper.Pitch = 1f

Speech pitch of the speaker in percent (1 = 100%, default: 1, optional, mobile only).

5.115.2.3 float Crosstales.RTVoice.UDEA2.UDEAVoiceWrapper.Rate = 1f

Speech rate of the speaker in percent (1 = 100%, default: 1, optional).

5.115.2.4 AudioSource Crosstales.RTVoice.UDEA2.UDEAVoiceWrapper.Source

Origin AudioSource (optional).

5.115.2.5 string Crosstales.RTVoice.UDEA2.UDEAVoiceWrapper.UDEAVoiceName = string.Empty

"Name of the UDEA-character on-screen.

5.115.2.6 Model.VoiceAlias Crosstales.RTVoice.UDEA2.UDEAVoiceWrapper.Voices

Voices for the speech.

5.115.2.7 float Crosstales.RTVoice.UDEA2.UDEAVoiceWrapper.Volume = 1f

Volume of the speaker in percent (1 = 100%, default: 1, optional).


The documentation for this class was generated from the following file:

- D:/slauberberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/THE Dialogue Engine/Scripts/UDEAVoiceWrapper.cs

5.116 Crosstailes.UI.UIDrag Class Reference

Allow to Drag the Windows arround.

Inheritance diagram for Crosstailes.UI.UIDrag:



Public Member Functions

- void Start ()
summary> Drag started.
- void BeginDrag ()
summary> While dragging.
- void **OnDrag** ()

5.116.1 Detailed Description

Allow to Drag the Windows arround.

5.116.2 Member Function Documentation

5.116.2.1 void Crosstailes.UI.UIDrag.BeginDrag ()

summary> While dragging.

5.116.2.2 void Crosstailes.UI.UIDrag.Start ()

summary> Drag started.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstailes/Common/↔ UI/Scripts/UIDrag.cs

5.117 Crosstailes.UI.UIFocus Class Reference

Change the Focus on from a Window.

Inheritance diagram for Crosstailes.UI.UIFocus:



Public Member Functions

- void Start ()
summary>Panel entered.
- void **OnPanelEnter** ()

Public Attributes

- string ManagerName = "Canvas"
Name of the gameobject containing the UIWindowManager.

5.117.1 Detailed Description

Change the Focus on from a Window.

5.117.2 Member Function Documentation

5.117.2.1 void Crosstales.UI.UIFocus.Start ()

summary>Panel entered.

5.117.3 Member Data Documentation

5.117.3.1 string Crosstales.UI.UIFocus.ManagerName = "Canvas"

Name of the gameobject containing the UIWindowManager.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/UI/Scripts/UIFocus.cs

5.118 Crosstales.UI.UIHint Class Reference

Controls a UI group (hint).

Inheritance diagram for Crosstales.UI.UIHint:



Public Member Functions

- void **Start** ()
- void **FadeUp** ()
- void **FadeDown** ()

Public Attributes

- CanvasGroup Group
Group to fade.
- float Delay = 2f
Delay in seconds before fading (default: 2).
- float FadeTime = 2f
Fade time in seconds (default: 2).
- bool Disable = true
Disable UI element after the fade (default: true).
- bool FadeAtStart = true
Fade at Start (default: true).

5.118.1 Detailed Description

Controls a UI group (hint).

5.118.2 Member Data Documentation

5.118.2.1 float Crosstales.UI.UIHint.Delay = 2f

Delay in seconds before fading (default: 2).

5.118.2.2 bool Crosstales.UI.UIHint.Disable = true

Disable UI element after the fade (default: true).

5.118.2.3 bool Crosstales.UI.UIHint.FadeAtStart = true

Fade at Start (default: true).

5.118.2.4 float Crosstales.UI.UIHint.FadeTime = 2f

Fade time in seconds (default: 2).

5.118.2.5 CanvasGroup Crosstales.UI.UIHint.Group

Group to fade.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/UI/Scripts/UIHint.cs

5.119 Crosstales.UI.UIResize Class Reference

Resize a UI element.

Inheritance diagram for Crosstales.UI.UIResize:



Public Member Functions

- void **Awake** ()
- void **OnPointerDown** (PointerEventData data)
- void **OnDrag** (PointerEventData data)

Public Attributes

- Vector2 MinSize = new Vector2(300, 160)
Minimum size of the UI element.
- Vector2 MaxSize = new Vector2(800, 600)
Maximum size of the UI element.

5.119.1 Detailed Description

Resize a UI element.

5.119.2 Member Data Documentation

5.119.2.1 Vector2 Crosstales.UI.UIResize.MaxSize = new Vector2(800, 600)

Maximum size of the UI element.

5.119.2.2 Vector2 Crosstailes.UI.UIResize.MinSize = new Vector2(300, 160)

Minimum size of the UI element.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstailes/Common/UI/Scripts/UIResize.cs

5.120 Crosstailes.UI.UIWindowManager Class Reference

Change the state of all Window panels.

Inheritance diagram for Crosstailes.UI.UIWindowManager:



Public Member Functions

- void Start ()
- void **ChangeState** (GameObject active)

Public Attributes

- GameObject[] Windows
All Windows of the scene.

5.120.1 Detailed Description

Change the state of all Window panels.

5.120.2 Member Function Documentation

5.120.2.1 void Crosstailes.UI.UIWindowManager.Start ()

summary>Change the state of all windows.

Parameters

<i>active</i>	Active window.
---------------	----------------

5.120.3 Member Data Documentation

5.120.3.1 GameObject [] Crosstales.UI.UIWindowManager.Windows

All Windows of the scene.

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ UI/Scripts/UIWindowManager.cs

5.121 Crosstales.RTVoice.EditorTask.UpdateCheck Class Reference

Checks for updates of the asset.

Static Public Member Functions

- static void **UpdateCheckForEditor** (out string result, out UpdateStatus st)

Public Attributes

- const string **TEXT_NOT_CHECKED** = "Not checked."
- const string **TEXT_NO_UPDATE** = "No update available - you are using the latest version."

5.121.1 Detailed Description

Checks for updates of the asset.

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Editor/Task/UpdateCheck.cs

5.122 Crosstales.RTVoice.Model.Voice Class Reference

Model for a voice.

Public Member Functions

- Voice (string name, string description, Enum.Gender gender, string age, string culture, string id="", string vendor="unknown")
Instantiate the class.
- override string **ToStrong** ()

Public Attributes

- string Name
Name of the voice.
- string Description
Description of the voice.
- Enum.Gender Gender
Gender of the voice.
- string Age
Age of the voice.
- string Identifier = string.Empty
Identifier of the voice.
- string Vendor = string.Empty
Vendor of the voice.

Properties

- string Culture [get, set]
Culture of the voice (ISO 639-1).

5.122.1 Detailed Description

Model for a voice.

5.122.2 Constructor & Destructor Documentation

5.122.2.1 **Crosstales.RTVoice.Model.Voice.Voice** (string *name*, string *description*, Enum.Gender *gender*, string *age*, string *culture*, string *id* = " ", string *vendor* = "unknown")

Instantiate the class.

Parameters

<i>name</i>	Name of the voice.
<i>description</i>	Description of the voice.
<i>gender</i>	Gender of the voice.
<i>age</i>	Age of the voice.
<i>culture</i>	Culture of the voice.
<i>id</i>	Identifier of the voice (optional).
<i>vendor</i>	Vendor of the voice (optional).

5.122.3 Member Data Documentation

5.122.3.1 string **Crosstales.RTVoice.Model.Voice.Age**

Age of the voice.

5.122.3.2 string Crosstales.RTVoice.Model.Voice.Description

Description of the voice.

5.122.3.3 Enum.Gender Crosstales.RTVoice.Model.Voice.Gender

Gender of the voice.

5.122.3.4 string Crosstales.RTVoice.Model.Voice.Identifier = string.Empty

Identifier of the voice.

5.122.3.5 string Crosstales.RTVoice.Model.Voice.Name

Name of the voice.

5.122.3.6 string Crosstales.RTVoice.Model.Voice.Vendor = string.Empty

Vendor of the voice.

5.122.4 Property Documentation

5.122.4.1 string Crosstales.RTVoice.Model.Voice.Culture [get], [set]

Culture of the voice (ISO 639-1).

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Scripts/Model/Voice.cs

5.123 Crosstales.RTVoice.Model.VoiceAlias Class Reference

Alias for multiple voices on different platforms.

Public Member Functions

- override string **ToString** ()

Public Attributes

- string VoiceNameWindows = "David"
Name of the voice under Windows.
- string VoiceNameMac = "Alex"
Name of the voice under macOS.
- string VoiceNameLinux = "en"
Name of the voice under Linux and for eSpeak.
- string VoiceNameAndroid = "en"
Name of the voice under Android.
- string VoiceNameIOS = "Daniel"
Name of the voice under iOS.
- string VoiceNameWSA = "David"
Name of the voice under WSA.
- string VoiceNameMaryTTS = "cmu-rms-hsmm"
Name of the voice under MaryTTS.
- string VoiceNameCustom = string.Empty
Name of the voice for custom TTS-systems.
- string Culture = "en"
Fallback culture for the text (e.g. 'en', optional).
- Enum.Gender Gender = Enum.Gender.UNKNOWN
Fallback gender for the text.

Properties

- string VoiceName [get]
Returns the name of the voice for the current platform.
- Voice Voice [get]
Returns the voice for the current platform.

5.123.1 Detailed Description

Alias for multiple voices on different platforms.

5.123.2 Member Data Documentation

5.123.2.1 string Crosstales.RTVoice.Model.VoiceAlias.Culture = "en"

Fallback culture for the text (e.g. 'en', optional).

5.123.2.2 Enum.Gender Crosstales.RTVoice.Model.VoiceAlias.Gender = Enum.Gender.UNKNOWN

Fallback gender for the text.

5.123.2.3 string Crosstales.RTVoice.Model.VoiceAlias.VoiceNameAndroid = "en"

Name of the voice under Android.

5.123.2.4 `string Crosstales.RTVoice.Model.VoiceAlias.VoiceNameCustom = string.Empty`

Name of the voice for custom TTS-systems.

5.123.2.5 `string Crosstales.RTVoice.Model.VoiceAlias.VoiceNameIOS = "Daniel"`

Name of the voice under iOS.

5.123.2.6 `string Crosstales.RTVoice.Model.VoiceAlias.VoiceNameLinux = "en"`

Name of the voice under Linux and for eSpeak.

5.123.2.7 `string Crosstales.RTVoice.Model.VoiceAlias.VoiceNameMac = "Alex"`

Name of the voice under macOS.

5.123.2.8 `string Crosstales.RTVoice.Model.VoiceAlias.VoiceNameMaryTTS = "cmu-rms-hsmm"`

Name of the voice under MaryTTS.

5.123.2.9 `string Crosstales.RTVoice.Model.VoiceAlias.VoiceNameWindows = "David"`

Name of the voice under Windows.

5.123.2.10 `string Crosstales.RTVoice.Model.VoiceAlias.VoiceNameWSA = "David"`

Name of the voice under WSA.

5.123.3 Property Documentation

5.123.3.1 **Voice** `Crosstales.RTVoice.Model.VoiceAlias.Voice` [get]

Returns the voice for the current platform.

Returns

The voice for the current platform.

5.123.3.2 string Crosstales.RTVoice.Model.VoiceAlias.VoiceName [get]

Returns the name of the voice for the current platform.

Returns

The name of the voice for the current platform.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Model/VoiceAlias.cs

5.124 Crosstales.RTVoice.Tool.VoiceInitializer Class Reference

Allows to initialize voices (useful on Android).

Inheritance diagram for Crosstales.RTVoice.Tool.VoiceInitializer:



Public Member Functions

- void **Start** ()
- void **OnEnable** ()
- void **OnDisable** ()

Public Attributes

- Model.Enum.ProviderType Provider = Model.Enum.ProviderType.Android
Selected provider to initialize the voices (default: Android).
- string[] VoiceNames
Initialize voices by name.
- bool AllVoices = false
Initialize all voices (default: false).
- bool DestroyWhenFinished = true
Destroy the gameobject after initialize (default: true).

5.124.1 Detailed Description

Allows to initialize voices (useful on Android).

5.124.2 Member Data Documentation

5.124.2.1 bool Crosstales.RTVoice.Tool.VoiceInitializer.AllVoices = false

Initialize all voices (default: false).

5.124.2.2 bool Crosstales.RTVoice.Tool.VoiceInitializer.DestroyWhenFinished = true

Destroy the gameobject after initialize (default: true).

5.124.2.3 Model.Enum.ProviderType Crosstales.RTVoice.Tool.VoiceInitializer.Provider = Model.Enum.ProviderType.Android

Selected provider to initialize the voices (default: Android).

5.124.2.4 string [] Crosstales.RTVoice.Tool.VoiceInitializer.VoiceNames

Initialize voices by name.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Tool/VoiceInitializer.cs

5.125 Crosstales.RTVoice.EditorExtension.VoiceInitializerEditor Class Reference

Custom editor for the 'VoiceInitializer'-class.

Inheritance diagram for Crosstales.RTVoice.EditorExtension.VoiceInitializerEditor:



Public Member Functions

- void **OnEnable** ()
- override void **OnInspectorGUI** ()

5.125.1 Detailed Description

Custom editor for the 'VoiceInitializer'-class.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Editor/Extension/VoiceInitializerEditor.cs

5.126 Crosstales.RTVoice.Provider.VoiceProviderAndroid Class Reference

Android voice provider.

Inheritance diagram for Crosstales.RTVoice.Provider.VoiceProviderAndroid:



Public Member Functions

- VoiceProviderAndroid (MonoBehaviour obj)
Constructor for VoiceProviderAndroid.
- override IEnumerator SpeakNative (Model.Wrapper wrapper)
The current provider speaks a text with a given voice (native mode).
- override IEnumerator Speak (Model.Wrapper wrapper)
The current provider speaks a text with a given voice.
- override IEnumerator Generate (Model.Wrapper wrapper)
The current provider generates an audio file from a text with a given voice.
- override void Silence ()
Silence all active TTS-providers.
- void **ShutdownTTS** ()

Properties

- override string **AudioFileExtension** [get]
- override AudioType **AudioFileType** [get]
- override string **DefaultVoiceName** [get]
- override bool **isWorkingInEditor** [get]
- override int **MaxTextLength** [get]
- override bool **isSpeakNativeSupported** [get]
- override bool **isSpeakSupported** [get]
- override bool **isPlatformSupported** [get]
- override bool **isSSMLSupported** [get]
- override bool **isOnlineService** [get]
- override bool **hasCoRoutines** [get]

Additional Inherited Members

5.126.1 Detailed Description

Android voice provider.

5.126.2 Constructor & Destructor Documentation

5.126.2.1 Crosstales.RTVoice.Provider.VoiceProviderAndroid.VoiceProviderAndroid (MonoBehaviour obj)

Constructor for VoiceProviderAndroid.

Parameters

<i>obj</i>	Instance of the speaker
------------	-------------------------

5.126.3 Member Function Documentation

5.126.3.1 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderAndroid.Generate (**Model.Wrapper wrapper**)
[virtual]

The current provider generates an audio file from a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.

5.126.3.2 override void Crosstales.RTVoice.Provider.VoiceProviderAndroid.Silence () [virtual]

Silence all active TTS-providers.

Reimplemented from Crosstales.RTVoice.Provider.BaseVoiceProvider.

5.126.3.3 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderAndroid.Speak (**Model.Wrapper wrapper**)
[virtual]

The current provider speaks a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.

5.126.3.4 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderAndroid.SpeakNative (**Model.Wrapper wrapper**)
[virtual]

The current provider speaks a text with a given voice (native mode).

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Provider/VoiceProviderAndroid.cs

5.127 Crosstales.RTVoice.AWSPolly.VoiceProviderAWS Class Reference

AWS Polly voice provider.

Inheritance diagram for Crosstales.RTVoice.AWSPolly.VoiceProviderAWS:



Public Member Functions

- void **Awake** ()
- override void **Load** ()
Load the provider (e.g. all voices).
- override IEnumerator **Generate** (Model.Wrapper wrapper)
The current provider generates an audio file from a text with a given voice.
- override IEnumerator **SpeakNative** (Model.Wrapper wrapper)
The current provider speaks a text with a given voice (native mode).
- override IEnumerator **Speak** (Model.Wrapper wrapper)
The current provider speaks a text with a given voice.

Public Attributes

- string **CognitoCredentials** = string.Empty
Cognito credentials to access AWS Polly.
- Endpoint **Endpoint** = Endpoint.EUCentral1
AWS endpoint for the connection.

Properties

- override string **AudioFileExtension** [get]
- override AudioType **AudioFileType** [get]
- override string **DefaultVoiceName** [get]
- override bool **isWorkingInEditor** [get]
- override bool **isPlatformSupported** [get]
- override int **MaxTextLength** [get]
- override bool **isSpeakNativeSupported** [get]
- override bool **isSpeakSupported** [get]
- override bool **isSSMLSupported** [get]
- override bool **isOnlineService** [get]
- override bool **hasCoRoutines** [get]
- Amazon.RegionEndpoint **getAWSEndpoint** [get]

Additional Inherited Members

5.127.1 Detailed Description

AWS Polly voice provider.

5.127.2 Member Function Documentation

5.127.2.1 `override IEnumerator Crosstales.RTVoice.AWSPolly.VoiceProviderAWS.Generate (Model.Wrapper wrapper)`
[virtual]

The current provider generates an audio file from a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements `Crosstales.RTVoice.Provider.BaseCustomVoiceProvider`.

5.127.2.2 `override void Crosstales.RTVoice.AWSPolly.VoiceProviderAWS.Load ()` [virtual]

Load the provider (e.g. all voices).

Implements `Crosstales.RTVoice.Provider.BaseCustomVoiceProvider`.

5.127.2.3 `override IEnumerator Crosstales.RTVoice.AWSPolly.VoiceProviderAWS.Speak (Model.Wrapper wrapper)`
[virtual]

The current provider speaks a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements `Crosstales.RTVoice.Provider.BaseCustomVoiceProvider`.

5.127.2.4 `override IEnumerator Crosstales.RTVoice.AWSPolly.VoiceProviderAWS.SpeakNative (Model.Wrapper wrapper)`
[virtual]

The current provider speaks a text with a given voice (native mode).

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.

5.127.3 Member Data Documentation

5.127.3.1 `string Crosstales.RTVoice.AWSPolly.VoiceProviderAWS.CognitoCredentials = string.Empty`

Cognito credentials to access AWS Polly.

5.127.3.2 `Endpoint Crosstales.RTVoice.AWSPolly.VoiceProviderAWS.Endpoint = Endpoint.EUCentral1`

AWS endpoint for the connection.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/AWS Polly/Scripts/VoiceProviderAWS.cs

5.128 Crosstales.RTVoice.AWSPolly.VoiceProviderAWSEditor Class Reference

Custom editor for the 'VoiceProviderAWS'-class.

Inheritance diagram for Crosstales.RTVoice.AWSPolly.VoiceProviderAWSEditor:



Public Member Functions

- void **OnEnable** ()
- override void **OnInspectorGUI** ()

5.128.1 Detailed Description

Custom editor for the 'VoiceProviderAWS'-class.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/AWS Polly/Editor/VoiceProviderAWSEditor.cs

5.129 Crosstales.RTVoice.AWSPolly.VoiceProviderAWSGameObject Class Reference

Editor component for for adding the prefabs from 'AWS Polly' in the "Hierarchy"-menu.

Inheritance diagram for Crosstales.RTVoice.AWSPolly.VoiceProviderAWSGameObject:



5.129.1 Detailed Description

Editor component for for adding the prefabs from 'AWS Polly' in the "Hierarchy"-menu.

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/AWS Polly/Editor/VoiceProviderAWSGameObject.cs

5.130 Crosstales.RTVoice.AWSPolly.VoiceProviderAWSMenu Class Reference

Editor component for for adding the prefabs from 'AWS Polly' in the "Tools"-menu.

5.130.1 Detailed Description

Editor component for for adding the prefabs from 'AWS Polly' in the "Tools"-menu.

The documentation for this class was generated from the following file:


- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/AWS Polly/Editor/VoiceProviderAWSMenu.cs

5.131 Crosstales.RTVoice.VoiceProviderExample Class Reference

Example for a custom voice provider (TTS-system) with all callbacks (only for demonstration - it doesn't do anything).

NOTE: please make sure you understand the Wrapper and its variables

Inheritance diagram for Crosstales.RTVoice.VoiceProviderExample:



Public Member Functions

- override void Load ()
Load the provider (e.g. all voices).
- override IEnumerator Generate (Model.Wrapper wrapper)
The current provider generates an audio file from a text with a given voice.
- override IEnumerator Speak (Model.Wrapper wrapper)
The current provider speaks a text with a given voice.
- override IEnumerator SpeakNative (Model.Wrapper wrapper)
The current provider speaks a text with a given voice (native mode).

Properties

- override string **AudioFileExtension** [get]
- override AudioType **AudioFileType** [get]
- override string **DefaultVoiceName** [get]
- override bool **isWorkingInEditor** [get]
- override bool **isPlatformSupported** [get]
- override int **MaxTextLength** [get]
- override bool **isSpeakNativeSupported** [get]
- override bool **isSpeakSupported** [get]
- override bool **isSSMLSupported** [get]
- override bool **isOnlineService** [get]
- override bool **hasCoRoutines** [get]

Additional Inherited Members

5.131.1 Detailed Description

Example for a custom voice provider (TTS-system) with all callbacks (only for demonstration - it doesn't do anything).
NOTE: please make sure you understand the Wrapper and its variables

5.131.2 Member Function Documentation

5.131.2.1 override IEnumerator Crosstales.RTVoice.VoiceProviderExample.Generate (**Model.Wrapper** *wrapper*)
[virtual]

The current provider generates an audio file from a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.

5.131.2.2 override void Crosstales.RTVoice.VoiceProviderExample.Load () [virtual]

Load the provider (e.g. all voices).

Implements Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.

5.131.2.3 **override IEnumerator Crosstales.RTVoice.VoiceProviderExample.Speak (Model.Wrapper wrapper)**
[virtual]

The current provider speaks a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.

5.131.2.4 **override IEnumerator Crosstales.RTVoice.VoiceProviderExample.SpeakNative (Model.Wrapper wrapper)**
[virtual]

The current provider speaks a text with a given voice (native mode).

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/VoiceProviderExample.cs

5.132 Crosstales.RTVoice.Provider.VoiceProviderIOS Class Reference

iOS voice provider.

Inheritance diagram for Crosstales.RTVoice.Provider.VoiceProviderIOS:



Public Member Functions

- VoiceProviderIOS (MonoBehaviour obj)
Constructor for VoiceProviderIOS.
- override IEnumerator SpeakNative (Model.Wrapper wrapper)
The current provider speaks a text with a given voice (native mode).
- override IEnumerator Speak (Model.Wrapper wrapper)
The current provider speaks a text with a given voice.
- override IEnumerator Generate (Model.Wrapper wrapper)
The current provider generates an audio file from a text with a given voice.
- override void Silence ()
Silence all active TTS-providers.

Static Public Member Functions

- static void SetVoices (string voicesText)
Receives all voices
- static void SetState (string state)
Receives the state of the speaker.
- static void WordSpoken ()
Called everytime a new word is spoken.

Properties

- override string **AudioFileExtension** [get]
- override AudioType **AudioFileType** [get]
- override string **DefaultVoiceName** [get]
- override bool **isWorkingInEditor** [get]
- override int **MaxTextLength** [get]
- override bool **isSpeakNativeSupported** [get]
- override bool **isSpeakSupported** [get]
- override bool **isPlatformSupported** [get]
- override bool **isSSMLSupported** [get]
- override bool **isOnlineService** [get]
- override bool **hasCoRoutines** [get]

Additional Inherited Members

5.132.1 Detailed Description

iOS voice provider.

5.132.2 Constructor & Destructor Documentation

5.132.2.1 Crosstales.RTVoice.Provider.VoiceProviderIOS.VoiceProviderIOS (MonoBehaviour obj)

Constructor for VoiceProviderIOS.

Parameters

<i>obj</i>	Instance of the speaker
------------	-------------------------

5.132.3 Member Function Documentation

5.132.3.1 `override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderIOS.Generate (Model.Wrapper wrapper)`
[virtual]

The current provider generates an audio file from a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements `Crosstales.RTVoice.Provider.BaseVoiceProvider`.

5.132.3.2 `static void Crosstales.RTVoice.Provider.VoiceProviderIOS.SetState (string state)` [static]

Receives the state of the speaker.

Parameters

<i>state</i>	The state of the speaker.
--------------	---------------------------

5.132.3.3 `static void Crosstales.RTVoice.Provider.VoiceProviderIOS.SetVoices (string voicesText)` [static]

Receives all voices

Parameters

<i>voicesText</i>	All voices as text string.
-------------------	----------------------------

5.132.3.4 `override void Crosstales.RTVoice.Provider.VoiceProviderIOS.Silence ()` [virtual]

Silence all active TTS-providers.

Reimplemented from `Crosstales.RTVoice.Provider.BaseVoiceProvider`.

5.132.3.5 `override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderIOS.Speak (Model.Wrapper wrapper)`
[virtual]

The current provider speaks a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.

5.132.3.6 **override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderIOS.SpeakNative (Model.Wrapper wrapper)**
[virtual]

The current provider speaks a text with a given voice (native mode).

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.

5.132.3.7 **static void Crosstales.RTVoice.Provider.VoiceProviderIOS.WordSpoken ()** [static]

Called everytime a new word is spoken.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Provider/VoiceProviderIOS.cs

5.133 Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynth Class Reference

Klattersynth voice provider.

Inheritance diagram for Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynth:



Public Member Functions

- override void Load ()
Load the provider (e.g. all voices).
- override IEnumerator Generate (Model.Wrapper wrapper)
The current provider generates an audio file from a text with a given voice.
- override IEnumerator SpeakNative (Model.Wrapper wrapper)
The current provider speaks a text with a given voice (native mode).
- override IEnumerator Speak (Model.Wrapper wrapper)
The current provider speaks a text with a given voice.

Public Attributes

- `Speech[]` Speeches
All available speeches (=voice configurations) from Klattersynth.
- `Common.Model.Enum.SampleRate SampleRate = Common.Model.Enum.SampleRate._11025Hz`
Desired sample rate (default: 11025).

Properties

- override string **AudioFileExtension** [get]
- override AudioType **AudioFileType** [get]
- override string **DefaultVoiceName** [get]
- override bool **isWorkingInEditor** [get]
- override bool **isPlatformSupported** [get]
- override int **MaxTextLength** [get]
- override bool **isSpeakNativeSupported** [get]
- override bool **isSpeakSupported** [get]
- override bool **isSSMLSupported** [get]
- override bool **isOnlineService** [get]
- override bool **hasCoRoutines** [get]

Additional Inherited Members

5.133.1 Detailed Description

Klattersynth voice provider.

5.133.2 Member Function Documentation

- 5.133.2.1 override IEnumerator Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynth.Generate (**Model.Wrapper wrapper**) [virtual]

The current provider generates an audio file from a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.

- 5.133.2.2 override void Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynth.Load () [virtual]

Load the provider (e.g. all voices).

Implements Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.

5.133.2.3 **override IEnumerator** Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynth.Speak (**Model.Wrapper** *wrapper*) [virtual]

The current provider speaks a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.

5.133.2.4 **override IEnumerator** Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynth.SpeakNative (**Model.Wrapper** *wrapper*) [virtual]

The current provider speaks a text with a given voice (native mode).

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseCustomVoiceProvider.

5.133.3 Member Data Documentation

5.133.3.1 **Common.Model.Enum.SampleRate** Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynth.SampleRate = Common.Model.Enum.SampleRate._11025Hz

Desired sample rate (default: 11025).

5.133.3.2 **Speech []** Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynth.Speeches

All available speeches (=voice configurations) from Klattersynth.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/Klattersynth/Scripts/VoiceProviderKlattersynth.cs

5.134 Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynthEditor Class Reference

Custom editor for the 'VoiceProviderKlattersynth'-class.

Inheritance diagram for Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynthEditor:



Public Member Functions

- void **OnEnable** ()
- override void **OnInspectorGUI** ()

5.134.1 Detailed Description

Custom editor for the 'VoiceProviderKlattersynth'-class.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/Klattersynth/Editor/VoiceProviderKlattersynthEditor.cs

5.135 Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynthGameObject Class Reference

Editor component for for adding the prefabs from 'Klattersynth' in the "Hierarchy"-menu.

Inheritance diagram for Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynthGameObject:



5.135.1 Detailed Description

Editor component for for adding the prefabs from 'Klattersynth' in the "Hierarchy"-menu.

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/Klattersynth/Editor/VoiceProviderKlattersynthGameObject.cs

5.136 Crosstales.RTVoice.Klattersynth.VoiceProviderKlattersynthMenu Class Reference

Editor component for for adding the prefabs from 'Klattersynth' in the "Tools"-menu.

5.136.1 Detailed Description

Editor component for for adding the prefabs from 'Klattersynth' in the "Tools"-menu.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/3rd party/Klattersynth/Editor/VoiceProviderKlattersynthMenu.cs

5.137 Crosstales.RTVoice.Provider.VoiceProviderLinux Class Reference

Linux voice provider. Note: needs eSpeak to work: => <http://espeak.sourceforge.net/>

Inheritance diagram for Crosstales.RTVoice.Provider.VoiceProviderLinux:



Public Member Functions

- VoiceProviderLinux (MonoBehaviour obj)
Constructor for VoiceProviderLinux.
- override IEnumerator SpeakNative (Model.Wrapper wrapper)
The current provider speaks a text with a given voice (native mode).
- override IEnumerator Speak (Model.Wrapper wrapper)
The current provider speaks a text with a given voice.
- override IEnumerator Generate (Model.Wrapper wrapper)
The current provider generates an audio file from a text with a given voice.

Protected Member Functions

- override string **getVoiceName** (Model.Wrapper wrapper)

Properties

- override string **AudioFileExtension** [get]
- override AudioType **AudioFileType** [get]
- override string **DefaultVoiceName** [get]
- override bool **isWorkingInEditor** [get]
- override int **MaxTextLength** [get]
- override bool **isSpeakNativeSupported** [get]
- override bool **isSpeakSupported** [get]
- override bool **isPlatformSupported** [get]
- override bool **isSSMLSupported** [get]
- override bool **isOnlineService** [get]
- override bool **hasCoRoutines** [get]

Additional Inherited Members

5.137.1 Detailed Description

Linux voice provider. Note: needs eSpeak to work: => <http://espeak.sourceforge.net/>

5.137.2 Constructor & Destructor Documentation

5.137.2.1 Crosstales.RTVoice.Provider.VoiceProviderLinux.VoiceProviderLinux (MonoBehaviour obj)

Constructor for VoiceProviderLinux.

Parameters

<i>obj</i>	Instance of the speaker
------------	-------------------------

5.137.3 Member Function Documentation

5.137.3.1 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderLinux.Generate (**Model.Wrapper** *wrapper*) [virtual]

The current provider generates an audio file from a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.

5.137.3.2 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderLinux.Speak (**Model.Wrapper** *wrapper*) [virtual]

The current provider speaks a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.

5.137.3.3 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderLinux.SpeakNative (**Model.Wrapper** *wrapper*) [virtual]

The current provider speaks a text with a given voice (native mode).

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↵ Scripts/Provider/VoiceProviderLinux.cs

5.138 Crosstales.RTVoice.Provider.VoiceProviderMacOS Class Reference

MacOS voice provider.

Inheritance diagram for Crosstales.RTVoice.Provider.VoiceProviderMacOS:



Public Member Functions

- VoiceProviderMacOS (MonoBehaviour obj)
Constructor for VoiceProviderMacOS.
- override IEnumerator SpeakNative (Model.Wrapper wrapper)
The current provider speaks a text with a given voice (native mode).
- override IEnumerator Speak (Model.Wrapper wrapper)
The current provider speaks a text with a given voice.
- override IEnumerator Generate (Model.Wrapper wrapper)
The current provider generates an audio file from a text with a given voice.

Properties

- override string **AudioFileExtension** [get]
- override AudioType **AudioFileType** [get]
- override string **DefaultVoiceName** [get]
- override bool **isWorkingInEditor** [get]
- override int **MaxTextLength** [get]
- override bool **isSpeakNativeSupported** [get]
- override bool **isSpeakSupported** [get]
- override bool **isPlatformSupported** [get]
- override bool **isSSMLSupported** [get]
- override bool **isOnlineService** [get]
- override bool **hasCoRoutines** [get]

Additional Inherited Members

5.138.1 Detailed Description

MacOS voice provider.

5.138.2 Constructor & Destructor Documentation

5.138.2.1 Crosstales.RTVoice.Provider.VoiceProviderMacOS.VoiceProviderMacOS (MonoBehaviour obj)

Constructor for VoiceProviderMacOS.

Parameters

<i>obj</i>	Instance of the speaker
------------	-------------------------

5.138.3 Member Function Documentation

5.138.3.1 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderMacOS.Generate (Model.Wrapper *wrapper*) [virtual]

The current provider generates an audio file from a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.

5.138.3.2 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderMacOS.Speak (Model.Wrapper *wrapper*) [virtual]

The current provider speaks a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.

5.138.3.3 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderMacOS.SpeakNative (Model.Wrapper *wrapper*) [virtual]

The current provider speaks a text with a given voice (native mode).

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/↔ Scripts/Provider/VoiceProviderMacOS.cs

5.139 Crosstales.RTVoice.Provider.VoiceProviderMary Class Reference

MaryTTS voice provider.

Inheritance diagram for Crosstales.RTVoice.Provider.VoiceProviderMary:



Public Member Functions

- VoiceProviderMary (MonoBehaviour obj, string url, int port, string user, string password)
Constructor for VoiceProviderMary. Needed to pass IP and Port of the MaryTTS server to the Provider.
- override IEnumerator SpeakNative (Model.Wrapper wrapper)
The current provider speaks a text with a given voice (native mode).
- override IEnumerator Speak (Model.Wrapper wrapper)
The current provider speaks a text with a given voice.
- override IEnumerator Generate (Model.Wrapper wrapper)
The current provider generates an audio file from a text with a given voice.
- override void Silence ()
Silence all active TTS-providers.

Properties

- override string **AudioFileExtension** [get]
- override AudioType **AudioFileType** [get]
- override string **DefaultVoiceName** [get]
- override bool **isWorkingInEditor** [get]
- override int **MaxTextLength** [get]
- override bool **isSpeakNativeSupported** [get]
- override bool **isSpeakSupported** [get]
- override bool **isPlatformSupported** [get]
- override bool **isSSMLSupported** [get]
- override bool **isOnlineService** [get]
- override bool **hasCoRoutines** [get]

Additional Inherited Members

5.139.1 Detailed Description

MaryTTS voice provider.

5.139.2 Constructor & Destructor Documentation

5.139.2.1 Crosstales.RTVoice.Provider.VoiceProviderMary.VoiceProviderMary (MonoBehaviour obj, string url, int port, string user, string password)

Constructor for VoiceProviderMary. Needed to pass IP and Port of the MaryTTS server to the Provider.

Parameters

<i>obj</i>	Instance of the speaker
<i>url</i>	IP-Address of the MaryTTS-server
<i>port</i>	Port to connect to on the MaryTTS-server

5.139.3 Member Function Documentation

5.139.3.1 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderMary.Generate (Model.Wrapper wrapper) [virtual]

The current provider generates an audio file from a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.

5.139.3.2 override void Crosstales.RTVoice.Provider.VoiceProviderMary.Silence () [virtual]

Silence all active TTS-providers.

Reimplemented from Crosstales.RTVoice.Provider.BaseVoiceProvider.

5.139.3.3 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderMary.Speak (Model.Wrapper wrapper) [virtual]

The current provider speaks a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.

5.139.3.4 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderMary.SpeakNative (Model.Wrapper wrapper) [virtual]

The current provider speaks a text with a given voice (native mode).

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Provider/VoiceProviderMary.cs

5.140 Crosstales.RTVoice.Provider.VoiceProviderWindows Class Reference

Windows voice provider.

Inheritance diagram for Crosstales.RTVoice.Provider.VoiceProviderWindows:



Public Member Functions

- `VoiceProviderWindows (MonoBehaviour obj)`
Constructor for VoiceProviderWindows.
- `override IEnumerator SpeakNative (Model.Wrapper wrapper)`
The current provider speaks a text with a given voice (native mode).
- `override IEnumerator Speak (Model.Wrapper wrapper)`
The current provider speaks a text with a given voice.
- `override IEnumerator Generate (Model.Wrapper wrapper)`
The current provider generates an audio file from a text with a given voice.

Properties

- `override string AudioFileExtension [get]`
- `override AudioType AudioFileType [get]`
- `override string DefaultVoiceName [get]`
- `override bool isWorkingInEditor [get]`
- `override int MaxTextLength [get]`
- `override bool isSpeakNativeSupported [get]`
- `override bool isSpeakSupported [get]`
- `override bool isPlatformSupported [get]`
- `override bool isSSMLSupported [get]`
- `override bool isOnlineService [get]`
- `override bool hasCoRoutines [get]`

Additional Inherited Members

5.140.1 Detailed Description

Windows voice provider.

5.140.2 Constructor & Destructor Documentation

5.140.2.1 Crosstales.RTVoice.Provider.VoiceProviderWindows.VoiceProviderWindows (MonoBehaviour *obj*)

Constructor for VoiceProviderWindows.

Parameters

<i>obj</i>	Instance of the speaker
------------	-------------------------

5.140.3 Member Function Documentation

5.140.3.1 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderWindows.Generate (Model.Wrapper *wrapper*) [virtual]

The current provider generates an audio file from a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.

5.140.3.2 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderWindows.Speak (Model.Wrapper *wrapper*) [virtual]

The current provider speaks a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.

5.140.3.3 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderWindows.SpeakNative (Model.Wrapper *wrapper*) [virtual]

The current provider speaks a text with a given voice (native mode).

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Provider/VoiceProviderWindows.cs

5.141 Crosstales.RTVoice.Provider.VoiceProviderWindowsLegacy Class Reference

Windows voice provider (Legacy).

Inheritance diagram for Crosstales.RTVoice.Provider.VoiceProviderWindowsLegacy:



Public Member Functions

- VoiceProviderWindowsLegacy (MonoBehaviour obj)
Constructor for VoiceProviderWindowsLegacy.
- override IEnumerator SpeakNative (Model.Wrapper wrapper)
The current provider speaks a text with a given voice (native mode).
- override IEnumerator Speak (Model.Wrapper wrapper)
The current provider speaks a text with a given voice.
- override IEnumerator Generate (Model.Wrapper wrapper)
The current provider generates an audio file from a text with a given voice.

Properties

- override string **AudioFileExtension** [get]
- override AudioType **AudioFileType** [get]
- override string **DefaultVoiceName** [get]
- override bool **isWorkingInEditor** [get]
- override int **MaxTextLength** [get]
- override bool **isSpeakNativeSupported** [get]
- override bool **isSpeakSupported** [get]
- override bool **isPlatformSupported** [get]
- override bool **isSSMLSupported** [get]
- override bool **isOnlineService** [get]
- override bool **hasCoRoutines** [get]

Additional Inherited Members

5.141.1 Detailed Description

Windows voice provider (Legacy).

5.141.2 Constructor & Destructor Documentation

5.141.2.1 Crosstales.RTVoice.Provider.VoiceProviderWindowsLegacy.VoiceProviderWindowsLegacy (MonoBehaviour *obj*)

Constructor for VoiceProviderWindowsLegacy.

Parameters

<i>obj</i>	Instance of the speaker
------------	-------------------------

5.141.3 Member Function Documentation

5.141.3.1 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderWindowsLegacy.Generate (Model.Wrapper *wrapper*) [virtual]

The current provider generates an audio file from a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.

5.141.3.2 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderWindowsLegacy.Speak (Model.Wrapper *wrapper*) [virtual]

The current provider speaks a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.

5.141.3.3 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderWindowsLegacy.SpeakNative (Model.Wrapper *wrapper*) [virtual]

The current provider speaks a text with a given voice (native mode).

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Provider/VoiceProviderWindowsLegacy.cs

5.142 Crosstales.RTVoice.Provider.VoiceProviderWSA Class Reference

WSA (UWP) voice provider.

Inheritance diagram for Crosstales.RTVoice.Provider.VoiceProviderWSA:



Public Member Functions

- VoiceProviderWSA (MonoBehaviour obj)
Constructor for VoiceProviderWSA.
- override IEnumerator SpeakNative (Model.Wrapper wrapper)
The current provider speaks a text with a given voice (native mode).
- override IEnumerator Speak (Model.Wrapper wrapper)
The current provider speaks a text with a given voice.
- override IEnumerator Generate (Model.Wrapper wrapper)
The current provider generates an audio file from a text with a given voice.
- override void Silence ()
Silence all active TTS-providers.

Properties

- override string **AudioFileExtension** [get]
- override AudioType **AudioFileType** [get]
- override string **DefaultVoiceName** [get]
- override bool **isWorkingInEditor** [get]
- override int **MaxTextLength** [get]
- override bool **isSpeakNativeSupported** [get]
- override bool **isSpeakSupported** [get]
- override bool **isPlatformSupported** [get]
- override bool **isSSMLSupported** [get]
- override bool **isOnlineService** [get]
- override bool **hasCoRoutines** [get]

Additional Inherited Members

5.142.1 Detailed Description

WSA (UWP) voice provider.

5.142.2 Constructor & Destructor Documentation

5.142.2.1 Crosstales.RTVoice.Provider.VoiceProviderWSA.VoiceProviderWSA (MonoBehaviour *obj*)

Constructor for VoiceProviderWSA.

Parameters

<i>obj</i>	Instance of the speaker
------------	-------------------------

5.142.3 Member Function Documentation

5.142.3.1 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderWSA.Generate (Model.Wrapper *wrapper*) [virtual]

The current provider generates an audio file from a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements Crosstales.RTVoice.Provider.BaseVoiceProvider.

5.142.3.2 override void Crosstales.RTVoice.Provider.VoiceProviderWSA.Silence () [virtual]

Silence all active TTS-providers.

Reimplemented from Crosstales.RTVoice.Provider.BaseVoiceProvider.

5.142.3.3 override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderWSA.Speak (Model.Wrapper *wrapper*) [virtual]

The current provider speaks a text with a given voice.

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements `Crosstales.RTVoice.Provider.BaseVoiceProvider`.

5.142.3.4 `override IEnumerator Crosstales.RTVoice.Provider.VoiceProviderWSA.SpeakNative (Model.Wrapper wrapper)`
[virtual]

The current provider speaks a text with a given voice (native mode).

Parameters

<i>wrapper</i>	Wrapper containing the data.
----------------	------------------------------

Implements `Crosstales.RTVoice.Provider.BaseVoiceProvider`.

The documentation for this class was generated from the following file:

- `D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Provider/VoiceProviderWSA.cs`

5.143 Crosstales.RTVoice.Util.WavMaster Class Reference

Static Public Member Functions

- static `AudioClip ToAudioClip (string filePath, string name="wav")`
*Load PCM format *.wav audio file (using Unity's Application data path) and convert to AudioClip.*
- static `AudioClip ToAudioClip (byte[] fileBytes, int offsetSamples=0, string name="wav")`
Load PCM format byte-array and convert to AudioClip.
- static `byte[] FromAudioClip (AudioClip audioClip)`
Convert an AudioClip to a byte-array.
- static `byte[] FromAudioClip (AudioClip audioClip, out string filepath, bool saveAsFile=true, string dirname="rtv_audio")`
Convert an AudioClip to a byte-array and save it to a file.
- static `ushort BitDepth (AudioClip audioClip)`
Calculates the bit depth of an AudioClip.

5.143.1 Member Function Documentation

5.143.1.1 `static ushort Crosstales.RTVoice.Util.WavMaster.BitDepth (AudioClip audioClip)` [static]

Calculates the bit depth of an AudioClip.

Parameters

<i>audioClip</i>	Audio clip.
------------------	-------------

Returns

The bit depth. Should be 8 or 16 or 32 bit.

5.143.1.2 `static byte [] Crosstales.RTVoice.Util.WavMaster.FromAudioClip (AudioClip audioClip) [static]`

Convert an AudioClip to a byte-array.

Parameters

<i>audioClip</i>	AudioClip to convert
------------------	----------------------

Returns

AudioClip as byte-array.

5.143.1.3 `static byte [] Crosstales.RTVoice.Util.WavMaster.FromAudioClip (AudioClip audioClip, out string filepath, bool saveAsFile = true, string dirname = "rtv_audio") [static]`

Convert an AudioClip to a byte-array and save it to a file.

Parameters

<i>audioClip</i>	AudioClip to save
<i>filepath</i>	File path
<i>saveAsFile</i>	Save the file (default: true, optional)
<i>dirname</i>	Directory name for the files (default: rtv_audio, optional)

Returns

AudioClip as byte-array.

5.143.1.4 `static AudioClip Crosstales.RTVoice.Util.WavMaster.ToAudioClip (string filePath, string name = "wav") [static]`

Load PCM format *.wav audio file (using Unity's Application data path) and convert to AudioClip.

Parameters

<i>filePath</i>	Local file path to .wav file
<i>name</i>	Name of the AudioClip (default: wav, optional)

Returns

AudioClip from the byte-array.

5.143.1.5 `static AudioClip Crosstales.RTVoice.Util.WavMaster.ToAudioClip (byte[] fileBytes, int offsetSamples = 0, string name = "wav") [static]`

Load PCM format byte-array and convert to AudioClip.

Parameters

<i>fileBytes</i>	Byte array with the PCM data
<i>offsetSamples</i>	Offset samples inside the byte-array (default: 0, optional)
<i>name</i>	Name of the AudioClip (default: wav, optional)

Returns

AudioClip from the byte-array.


The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Util/WavMaster.cs

5.144 Crosstales.UI.WindowManager Class Reference

Manager for a Window.

Inheritance diagram for Crosstales.UI.WindowManager:



Public Member Functions

- void **Start** ()
- void Update ()
summary> Switch between open and close.
- void SwitchPanel ()
summary> Open the panel.
- void OpenPanel ()
summary> Close the panel.
- void **ClosePanel** ()

Public Attributes

- float Speed = 3f
Window movement speed (default: 3).
- GameObject[] Dependencies
Dependent GameObjects (active == open).

5.144.1 Detailed Description

Manager for a Window.

5.144.2 Member Function Documentation

5.144.2.1 void Crosstales.UI.WindowManager.OpenPanel ()

summary>Close the panel.

5.144.2.2 void Crosstales.UI.WindowManager.SwitchPanel ()

summary>Open the panel.

5.144.2.3 void Crosstales.UI.WindowManager.Update ()

summary>Switch between open and close.

5.144.3 Member Data Documentation

5.144.3.1 GameObject [] Crosstales.UI.WindowManager.Dependencies

Dependent GameObjects (active == open).

5.144.3.2 float Crosstales.UI.WindowManager.Speed = 3f

Window movement speed (default: 3).

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↵ UI/Scripts/WindowManager.cs

5.145 Crosstales.RTVoice.Model.Wrapper Class Reference

Wrapper for "Speak"-function calls.

Public Member Functions

- Wrapper ()
Default.
- Wrapper (string text, Voice voice=null, float rate=1f, float pitch=1f, float volume=1f, bool forceSSML=true)
Instantiate the class.
- Wrapper (string text, Voice voice=null, float rate=1f, float pitch=1f, float volume=1f, AudioSource source=null, bool speakImmediately=true, string outputFile="", bool forceSSML=true)
Instantiate the class.
- Wrapper (string uid, string text, Voice voice=null, float rate=1f, float pitch=1f, float volume=1f, AudioSource source=null, bool speakImmediately=true, string outputFile="", bool forceSSML=true)
Instantiate the class.
- override string **ToString** ()

Public Attributes

- string Uid
UID of the speech.
- AudioSource Source
AudioSource for the speech.
- Voice Voice
Voice for the speech.
- bool SpeakImmediately = true
Speak immediately after the audio generation. Only works if 'Source' is not null.
- string OutputFile
Output file (without extension) for the generated audio.
- bool ForceSSML = true
Force SSML on supported platforms.

Properties

- string Text [get, set]
Text for the speech.
- float Rate [get, set]
Rate of the speech (values: 0-3).
- float Pitch [get, set]
Pitch of the speech (values: 0-2).
- float Volume [get, set]
Volume of the speech (values: 0-1).
- System.DateTime Created [get]
Returns the creation time of the RecordInfo.

5.145.1 Detailed Description

Wrapper for "Speak"-function calls.

5.145.2 Constructor & Destructor Documentation

5.145.2.1 Crosstales.RTVoice.Model.Wrapper.Wrapper ()

Default.

5.145.2.2 Crosstales.RTVoice.Model.Wrapper.Wrapper (string *text*, Voice *voice* = null, float *rate* = 1f, float *pitch* = 1f, float *volume* = 1f, bool *forceSSML* = true)

Instantiate the class.

Parameters

<i>text</i>	Text for the speech.
<i>voice</i>	Voice for the speech (default: null, optional).
<i>rate</i>	Rate of the speech (values: 0-3, default: 1, optional).
<i>pitch</i>	Pitch of the speech (values: 0-2, default: 1, optional).
<i>volume</i>	Volume of the speech (values: 0-1, default: 1, optional).
<i>forceSSML</i>	Force SSML on supported platforms (default: true, optional).

5.145.2.3 Crosstales.RTVoice.Model.Wrapper.Wrapper (string *text*, Voice *voice* = null, float *rate* = 1f, float *pitch* = 1f, float *volume* = 1f, AudioSource *source* = null, bool *speakImmediately* = true, string *outputFile* = "", bool *forceSSML* = true)

Instantiate the class.

Parameters

<i>text</i>	Text for the speech.
<i>voice</i>	Voice for the speech (default: null, optional).
<i>rate</i>	Rate of the speech (values: 0-3, default: 1, optional).
<i>pitch</i>	Pitch of the speech (values: 0-2, default: 1, optional).
<i>volume</i>	Volume of the speech (values: 0-1, default: 1, optional).
<i>source</i>	AudioSource for the speech (default: null, optional).
<i>speakImmediately</i>	Speak immediately after the audio generation. Only works if 'Source' is not null (default: true, optional).
<i>outputFile</i>	Output file (without extension) for the generated audio (default: empty, optional).
<i>forceSSML</i>	Force SSML on supported platforms (default: true, optional).

5.145.2.4 Crosstales.RTVoice.Model.Wrapper.Wrapper (string *uid*, string *text*, Voice *voice* = null, float *rate* = 1f, float *pitch* = 1f, float *volume* = 1f, AudioSource *source* = null, bool *speakImmediately* = true, string *outputFile* = "", bool *forceSSML* = true)

Instantiate the class.

Parameters

<i>uid</i>	UID of the speech.
<i>voice</i>	Voice for the speech (default: null, optional).
<i>rate</i>	Rate of the speech (values: 0-3, default: 1, optional).
<i>pitch</i>	Pitch of the speech (values: 0-2, default: 1, optional).
<i>volume</i>	Volume of the speech (values: 0-1, default: 1, optional).
<i>source</i>	AudioSource for the speech (default: null, optional).
<i>speakImmediately</i>	Speak immediately after the audio generation. Only works if 'Source' is not null (default: true, optional).
<i>outputFile</i>	Output file (without extension) for the generated audio (default: empty, optional).
<i>forceSSML</i>	Force SSML on supported platforms (default: true, optional).

5.145.3 Member Data Documentation

5.145.3.1 bool Crosstales.RTVoice.Model.Wrapper.ForceSSML = true

Force SSML on supported platforms.

5.145.3.2 string Crosstales.RTVoice.Model.Wrapper.OutputFile

Output file (without extension) for the generated audio.

5.145.3.3 AudioSource Crosstales.RTVoice.Model.Wrapper.Source

AudioSource for the speech.

5.145.3.4 bool Crosstales.RTVoice.Model.Wrapper.SpeakImmediately = true

Speak immediately after the audio generation. Only works if 'Source' is not null.

5.145.3.5 string Crosstales.RTVoice.Model.Wrapper.Uid

UID of the speech.

5.145.3.6 Voice Crosstales.RTVoice.Model.Wrapper.Voice

Voice for the speech.

5.145.4 Property Documentation

5.145.4.1 System.DateTime Crosstales.RTVoice.Model.Wrapper.Created [get]

Returns the creation time of the RecordInfo.

Returns

Creation time of the RecordInfo.

5.145.4.2 float Crosstales.RTVoice.Model.Wrapper.Pitch [get], [set]

Pitch of the speech (values: 0-2).

5.145.4.3 float Crosstales.RTVoice.Model.Wrapper.Rate [get], [set]

Rate of the speech (values: 0-3).

5.145.4.4 string Crosstales.RTVoice.Model.Wrapper.Text [get], [set]

Text for the speech.

5.145.4.5 float Crosstales.RTVoice.Model.Wrapper.Volume [get], [set]

Volume of the speech (values: 0-1).

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/RTVoice/Scripts/Model/Wrapper.cs

5.146 Crosstales.Common.Util.XmlHelper Class Reference

Helper-class for XML.

Static Public Member Functions

- static void SerializeToFile< T > (T obj, string filename)
Serialize an object to an XML-file.
- static T DeserializeFromFile< T > (string filename, bool skipBOM=false)
Deserialize a XML-file to an object.
- static string SerializeToString< T > (T obj)
Serialize an object to an XML-string.
- static T DeserializeFromString< T > (string xmlAsString, bool skipBOM=true)
Deserialize a XML-string to an object.
- static T DeserializeFromResource< T > (string resourceName, bool skipBOM=true)
Deserialize a Unity XML resource (TextAsset) to an object.

5.146.1 Detailed Description

Helper-class for XML.

5.146.2 Member Function Documentation

5.146.2.1 `static T Crosstales.Common.Util.XmlHelper.DeserializeFromFile< T > (string filename, bool skipBOM = false)`
[static]

Deserialize a XML-file to an object.

Parameters

<i>filename</i>	XML-file of the object
<i>skipBOM</i>	Skip BOM (optional, default: false)

Returns

Object

5.146.2.2 `static T Crosstales.Common.Util.XmlHelper.DeserializeFromResource< T > (string resourceName, bool skipBOM = true)` [static]

Deserialize a Unity XML resource (TextAsset) to an object.

Parameters

<i>resourceName</i>	Name of the resource
<i>skipBOM</i>	Skip BOM (optional, default: true)

Returns

Object

5.146.2.3 `static T Crosstales.Common.Util.XmlHelper.DeserializeFromString< T > (string xmlAsString, bool skipBOM = true)` [static]

Deserialize a XML-string to an object.

Parameters

<i>xmlAsString</i>	XML of the object
<i>skipBOM</i>	Skip BOM (optional, default: true)

Returns

Object

5.146.2.4 `static void Crosstales.Common.Util.XmlHelper.SerializeToFile< T > (T obj, string filename) [static]`

Serialize an object to an XML-file.

Parameters

<i>obj</i>	Object to serialize.
<i>filename</i>	File name of the XML.

5.146.2.5 `static string Crosstales.Common.Util.XmlHelper.SerializeToString< T > (T obj) [static]`

Serialize an object to an XML-string.

Parameters

<i>obj</i>	Object to serialize.
------------	----------------------

Returns

Object as XML-stringValid path

The documentation for this class was generated from the following file:

- D:/slaubenberger/git/assets/RTVoicePro/3rd party/RTVoice_3rd_party/Assets/Plugins/crosstales/Common/↔ Scripts/Util/XmlHelper.cs

Chapter 6

More information

6.1 Homepage

<https://www.crosstales.com/en/portfolio/rtvoice/>

6.2 AssetStore

<https://goo.gl/qwtXyb>

6.3 Forum

<http://goo.gl/Z6MZM1>

6.4 Documentation

<https://www.crosstales.com/media/data/assets/rtvoice/RTVoice-doc.pdf>

6.5 Discord

<https://discord.gg/ZbZ2sh4>

6.6 Demos

6.6.1 WebGL

<https://www.crosstales.com/media/data/assets/rtvoice/webgl/>

6.6.2 Windows

https://www.crosstales.com/media/data/assets/rtvoice/downloads/RTVoice_demo_win.zip

6.6.3 macOS

https://www.crosstales.com/media/data/assets/rtvoice/downloads/RTVoice_demo_mac.zip

6.6.4 Android

<https://www.crosstales.com/media/rtvoice/RTVoice.apk>

6.7 Videos

<https://www.youtube.com/c/Crosstales>

6.7.1 Promotion

<https://youtu.be/iVhTWDLY7g8?list=PLgtonIO6Tb41XTMeeZ836tjHlKg0084S>

6.7.2 Tutorial

<https://youtu.be/OJyVgCmX3wU?list=PLgtonIO6Tb41XTMeeZ836tjHlKg0084S>

Index

APPLICATION_PATH
 Crosstales::Common::Util::BaseConstants, 43
ASSET_2019_URL
 Crosstales::RTVoice::Util::Constants, 79
ASSET_3P_ADVENTURE_CREATOR
 Crosstales::RTVoice::Util::Constants, 79
ASSET_3P_CINEMA_DIRECTOR
 Crosstales::RTVoice::Util::Constants, 79
ASSET_3P_DIALOG_SYSTEM
 Crosstales::RTVoice::Util::Constants, 80
ASSET_3P_DIALOGUE_ENGINE
 Crosstales::RTVoice::Util::Constants, 80
ASSET_3P_LIPSYNC
 Crosstales::RTVoice::Util::Constants, 80
ASSET_3P_LOCALIZED_DIALOGS
 Crosstales::RTVoice::Util::Constants, 80
ASSET_3P_NPC_CHAT
 Crosstales::RTVoice::Util::Constants, 80
ASSET_3P_PLAYMAKER
 Crosstales::Common::Util::BaseConstants, 39
ASSET_3P_QUEST_SYSTEM
 Crosstales::RTVoice::Util::Constants, 80
ASSET_3P_SALSA
 Crosstales::RTVoice::Util::Constants, 80
ASSET_3P_SLATE
 Crosstales::RTVoice::Util::Constants, 80
ASSET_3P_URL
 Crosstales::RTVoice::Util::Constants, 80
ASSET_3P_USEQUENCER
 Crosstales::RTVoice::Util::Constants, 81
ASSET_API_URL
 Crosstales::RTVoice::Util::Constants, 81
ASSET_AUTHOR_URL
 Crosstales::Common::Util::BaseConstants, 39
ASSET_AUTHOR
 Crosstales::Common::Util::BaseConstants, 39
ASSET_BUILD
 Crosstales::RTVoice::Util::Constants, 81
ASSET_BWF
 Crosstales::Common::Util::BaseConstants, 39
ASSET_CHANGED
 Crosstales::RTVoice::Util::Constants, 81
ASSET_CONTACT
 Crosstales::RTVoice::Util::Constants, 81
ASSET_CREATED
 Crosstales::RTVoice::Util::Constants, 81
ASSET_CT_URL
 Crosstales::Common::Util::BaseConstants, 39
ASSET_DJ
 Crosstales::Common::Util::BaseConstants, 39
ASSET_FORUM_URL
 Crosstales::RTVoice::Util::Constants, 81
ASSET_FB
 Crosstales::Common::Util::BaseConstants, 40
ASSET_ID
 Crosstales::RTVoice::EditorUtil::EditorConstants, 92
ASSET_MANUAL_URL
 Crosstales::RTVoice::Util::Constants, 81
ASSET_NAME
 Crosstales::RTVoice::Util::Constants, 81
ASSET_OC
 Crosstales::Common::Util::BaseConstants, 40
ASSET_PATH
 Crosstales::RTVoice::EditorUtil::EditorConfig, 91
 Crosstales::RTVoice::Util::Config, 73
ASSET_PRO_URL
 Crosstales::RTVoice::Util::Constants, 82
ASSET_RADIO
 Crosstales::Common::Util::BaseConstants, 40
ASSET_RTV
 Crosstales::Common::Util::BaseConstants, 40
ASSET_SOCIAL_DISCORD
 Crosstales::Common::Util::BaseConstants, 40
ASSET_SOCIAL_FACEBOOK
 Crosstales::Common::Util::BaseConstants, 40
ASSET_SOCIAL_LINKEDIN
 Crosstales::Common::Util::BaseConstants, 40
ASSET_SOCIAL_TWITTER
 Crosstales::Common::Util::BaseConstants, 40
ASSET_SOCIAL_XING
 Crosstales::Common::Util::BaseConstants, 40
ASSET_SOCIAL_YOUTUBE
 Crosstales::Common::Util::BaseConstants, 41
ASSET_TPB
 Crosstales::Common::Util::BaseConstants, 41
ASSET_TPS
 Crosstales::Common::Util::BaseConstants, 41
ASSET_TB
 Crosstales::Common::Util::BaseConstants, 41
ASSET_TR
 Crosstales::Common::Util::BaseConstants, 41
ASSET_UID
 Crosstales::RTVoice::EditorUtil::EditorConstants, 92
ASSET_UPDATE_CHECK_URL
 Crosstales::RTVoice::Util::Constants, 82
ASSET_URL

- Crosstales::RTVoice::EditorUtil::EditorConstants, 92
- ASSET_VERSION
 - Crosstales::RTVoice::Util::Constants, 82
- ASSET_VIDEO_PROMO
 - Crosstales::RTVoice::Util::Constants, 82
- ASSET_VIDEO_TUTORIAL
 - Crosstales::RTVoice::Util::Constants, 82
- ASSET_WEB_URL
 - Crosstales::RTVoice::Util::Constants, 82
- AUDIOFILE_AUTOMATIC_DELETE
 - Crosstales::RTVoice::Util::Config, 73
- AUDIOFILE_PATH
 - Crosstales::RTVoice::Util::Config, 74
- AUDIOFILE_PREFIX
 - Crosstales::RTVoice::Util::Constants, 82
- Active
 - Crosstales::RTVoice::Demo::Util::NativeController, 129
- Age
 - Crosstales::RTVoice::Model::Voice, 213
- AllVoices
 - Crosstales::RTVoice::Tool::VoiceInitializer, 218
- AlphaRange
 - Crosstales::Common::Util::RandomColor, 138
- Analyzer
 - Crosstales::Common::Util::SpectrumVisualizer, 187
- AppleVoiceNameToGender
 - Crosstales::RTVoice::Util::Helper, 113
- ApproximateSpeechLength
 - Crosstales::RTVoice::Speaker, 168
- areVoicesReady
 - Crosstales::RTVoice::Speaker, 177
- AudioFileExtension
 - Crosstales::RTVoice::Provider::IVoiceProvider, 119
 - Crosstales::RTVoice::Speaker, 177
- AudioFileType
 - Crosstales::RTVoice::Provider::IVoiceProvider, 119
- AudioSource
 - HutongGames::PlayMaker::Actions::SpeakBase, 163
- AudioSources
 - Crosstales::UI::Util::AudioSourceController, 34
- AutoClearTags
 - Crosstales::RTVoice::Speaker, 175
- BannerOC
 - Crosstales::RTVoice::EditorUtil::EditorHelper, 94
- BaseVoiceProvider
 - Crosstales::RTVoice::Provider::BaseVoice↔Provider, 65
- BeginDrag
 - Crosstales::UI::UIDrag, 207
- BitDepth
 - Crosstales::RTVoice::Util::WavMaster, 245
- BusyCount
 - Crosstales::RTVoice::Speaker, 177
- CTAddRange< K, V >
 - Crosstales::ExtensionMethods, 96
- CTContains
 - Crosstales::ExtensionMethods, 97
- CTContainsAll
 - Crosstales::ExtensionMethods, 97
- CTContainsAny
 - Crosstales::ExtensionMethods, 97
- CTDump
 - Crosstales::ExtensionMethods, 98–100
- CTDump< K, V >
 - Crosstales::ExtensionMethods, 100
- CTDump< T >
 - Crosstales::ExtensionMethods, 100
- CTEquals
 - Crosstales::ExtensionMethods, 101
- CTIsVisibleFrom
 - Crosstales::ExtensionMethods, 101
- CTReplace
 - Crosstales::ExtensionMethods, 101
- CTReverse
 - Crosstales::ExtensionMethods, 102
- CTShuffle< T >
 - Crosstales::ExtensionMethods, 102
- CTToString< T >
 - Crosstales::ExtensionMethods, 103
- CTToTitleCase
 - Crosstales::ExtensionMethods, 103
- ChangeInterval
 - Crosstales::Common::Util::RandomColor, 138
 - Crosstales::Common::Util::RandomRotator, 140
 - Crosstales::Common::Util::RandomScaler, 141
- Channel
 - Crosstales::Common::Util::FFTAlyzer, 104
- CleanText
 - Crosstales::RTVoice::Util::Helper, 114
- ClearLineEndings
 - Crosstales::Common::Util::BaseHelper, 55
- ClearSpaces
 - Crosstales::Common::Util::BaseHelper, 55
- ClearTags
 - Crosstales::Common::Util::BaseHelper, 55
- Clips
 - Crosstales::RTVoice::Tool::Paralanguage, 131
- CognitoCredentials
 - Crosstales::RTVoice::AWS Polly::VoiceProviderA↔WS, 223
- ConnectionLimit
 - Crosstales::Common::Util::CTWebClient, 88
- CreateString
 - Crosstales::Common::Util::BaseHelper, 56
- Created
 - Crosstales::RTVoice::Model::Wrapper, 252
- Crosstales, 13
- Crosstales.Common, 13
- Crosstales.Common.EditorTask, 13
- Crosstales.Common.EditorTask.BaseCompileDefines, 36

- Crosstales.Common.EditorTask.BaseSetupResources, 63
- Crosstales.Common.EditorTask.NYCheck, 129
- Crosstales.Common.EditorTask.SetApiLevel, 153
- Crosstales.Common.EditorTask.SetupResources, 154
- Crosstales.Common.EditorUtil, 14
- Crosstales.Common.EditorUtil.BaseEditorHelper, 48
- Crosstales.Common.EditorUtil.BaseGAApi, 51
- Crosstales.Common.Model, 14
- Crosstales.Common.Model.Enum, 14
- Crosstales.Common.Util, 15
- Crosstales.Common.Util.BackgroundController, 35
- Crosstales.Common.Util.BaseConstants, 37
- Crosstales.Common.Util.BaseHelper, 52
- Crosstales.Common.Util.CTPlayerPrefs, 83
- Crosstales.Common.Util.CTWebClient, 87
- Crosstales.Common.Util.FFTAnalyzer, 103
- Crosstales.Common.Util.PlatformController, 135
- Crosstales.Common.Util.RandomColor, 137
- Crosstales.Common.Util.RandomRotator, 139
- Crosstales.Common.Util.RandomScaler, 141
- Crosstales.Common.Util.SerializableDictionary< TKey, TVal >, 151
- Crosstales.Common.Util.SerializeDeSerialize, 152
- Crosstales.Common.Util.SpectrumVisualizer, 186
- Crosstales.Common.Util.SurviveSceneSwitch, 194
- Crosstales.Common.Util.TakeScreenshot, 196
- Crosstales.Common.Util.XmlHelper, 252
- Crosstales.ExtensionMethods, 95
- Crosstales.RTVoice, 15
- Crosstales.RTVoice.AWSPolly, 16
- Crosstales.RTVoice.AWSPolly.Switcher, 195
- Crosstales.RTVoice.AWSPolly.VoiceProviderAWS↔ Editor, 223
- Crosstales.RTVoice.AWSPolly.VoiceProviderAWS↔ GameObject, 224
- Crosstales.RTVoice.AWSPolly.VoiceProviderAWS↔ Menu, 224
- Crosstales.RTVoice.AWSPolly.VoiceProviderAWS, 221
- Crosstales.RTVoice.Demo, 17
- Crosstales.RTVoice.Demo.Dialog, 88
- Crosstales.RTVoice.Demo.GUIAudioFilter, 106
- Crosstales.RTVoice.Demo.GUIDialog, 107
- Crosstales.RTVoice.Demo.GUIMain, 108
- Crosstales.RTVoice.Demo.GUIMultiAudioFilter, 109
- Crosstales.RTVoice.Demo.GUIScenes, 110
- Crosstales.RTVoice.Demo.GUISpeech, 111
- Crosstales.RTVoice.Demo.NativeAudio, 127
- Crosstales.RTVoice.Demo.PreGeneratedAudio, 137
- Crosstales.RTVoice.Demo.SendMessage, 145
- Crosstales.RTVoice.Demo.SequenceCaller, 147
- Crosstales.RTVoice.Demo.Simple, 156
- Crosstales.RTVoice.Demo.SimpleNative, 157
- Crosstales.RTVoice.Demo.SpeakWrapper, 186
- Crosstales.RTVoice.Demo.Util, 18
- Crosstales.RTVoice.Demo.Util.iOSController, 115
- Crosstales.RTVoice.Demo.Util.MaterialChanger, 127
- Crosstales.RTVoice.Demo.Util.NativeController, 128
- Crosstales.RTVoice.Demo.Util.PlatformController, 136
- Crosstales.RTVoice.EditorExtension, 18
- Crosstales.RTVoice.EditorExtension.AudioFileGenerator↔ Editor, 30
- Crosstales.RTVoice.EditorExtension.ChangeGender↔ Editor, 70
- Crosstales.RTVoice.EditorExtension.Loudspeaker↔ Editor, 126
- Crosstales.RTVoice.EditorExtension.Paralanguage↔ Editor, 133
- Crosstales.RTVoice.EditorExtension.SequencerEditor, 150
- Crosstales.RTVoice.EditorExtension.SpeakerEditor, 183
- Crosstales.RTVoice.EditorExtension.SpeechTextEditor, 192
- Crosstales.RTVoice.EditorExtension.TextFileSpeaker↔ Editor, 202
- Crosstales.RTVoice.EditorExtension.VoiceInitializer↔ Editor, 218
- Crosstales.RTVoice.EditorIntegration, 18
- Crosstales.RTVoice.EditorIntegration.ConfigBase, 74
- Crosstales.RTVoice.EditorIntegration.ConfigPreferences, 75
- Crosstales.RTVoice.EditorIntegration.ConfigWindow, 76
- Crosstales.RTVoice.EditorIntegration.RTVoiceGame↔ Object, 142
- Crosstales.RTVoice.EditorIntegration.RTVoiceMenu, 144
- Crosstales.RTVoice.EditorTask, 19
- Crosstales.RTVoice.EditorTask.AutoInitialize, 35
- Crosstales.RTVoice.EditorTask.CheckIL2CPP, 71
- Crosstales.RTVoice.EditorTask.CompileDefines, 71
- Crosstales.RTVoice.EditorTask.ConfigLoader, 75
- Crosstales.RTVoice.EditorTask.Launch, 121
- Crosstales.RTVoice.EditorTask.ReminderCheck, 142
- Crosstales.RTVoice.EditorTask.SetupResources, 154
- Crosstales.RTVoice.EditorTask.Tracer, 203
- Crosstales.RTVoice.EditorTask.UpdateCheck, 212
- Crosstales.RTVoice.EditorUtil, 19
- Crosstales.RTVoice.EditorUtil.EditorConfig, 89
- Crosstales.RTVoice.EditorUtil.EditorConstants, 91
- Crosstales.RTVoice.EditorUtil.EditorHelper, 93
- Crosstales.RTVoice.EditorUtil.GAApi, 105
- Crosstales.RTVoice.Klattersynth, 20
- Crosstales.RTVoice.Klattersynth.VoiceProvider↔ Klattersynth, 229
- Crosstales.RTVoice.Klattersynth.VoiceProvider↔ KlattersynthEditor, 231
- Crosstales.RTVoice.Klattersynth.VoiceProvider↔ KlattersynthGameObject, 232
- Crosstales.RTVoice.Klattersynth.VoiceProvider↔ KlattersynthMenu, 232
- Crosstales.RTVoice.LiveSpeaker, 121
- Crosstales.RTVoice.Model, 20
- Crosstales.RTVoice.Model.Enum, 20
- Crosstales.RTVoice.Model.Sequence, 146
- Crosstales.RTVoice.Model.Voice, 212

- Crosstales.RTVoice.Model.VoiceAlias, 214
- Crosstales.RTVoice.Model Wrapper, 248
- Crosstales.RTVoice.PlayMaker, 21
- Crosstales.RTVoice.PlayMaker.AudioFileGenerator↔
Editor, 30
- Crosstales.RTVoice.PlayMaker.BaseRTVEditor, 62
- Crosstales.RTVoice.PlayMaker.ParalanguageEditor,
134
- Crosstales.RTVoice.PlayMaker.SilenceEditor, 155
- Crosstales.RTVoice.PlayMaker.SpeakEditor, 164
- Crosstales.RTVoice.PlayMaker.SpeakUIEditor, 185
- Crosstales.RTVoice.PlayMaker.SpeechTextEditor, 193
- Crosstales.RTVoice.PlayMaker.TextFileSpeakerEditor,
203
- Crosstales.RTVoice.Provider, 22
- Crosstales.RTVoice.Provider.BaseCustomVoice↔
Provider, 44
- Crosstales.RTVoice.Provider.BaseVoiceProvider, 63
- Crosstales.RTVoice.Provider.IVoiceProvider, 116
- Crosstales.RTVoice.Provider.VoiceProviderAndroid, 219
- Crosstales.RTVoice.Provider.VoiceProviderIOS, 226
- Crosstales.RTVoice.Provider.VoiceProviderLinux, 233
- Crosstales.RTVoice.Provider.VoiceProviderMacOS, 235
- Crosstales.RTVoice.Provider.VoiceProviderMary, 237
- Crosstales.RTVoice.Provider.VoiceProviderWSA, 243
- Crosstales.RTVoice.Provider.VoiceProviderWindows,
239
- Crosstales.RTVoice.Provider.VoiceProviderWindows↔
Legacy, 241
- Crosstales.RTVoice.SALSA.Bots, 68
- Crosstales.RTVoice.SALSA.Speak, 158
- Crosstales.RTVoice.SALSA.Speak2D, 161
- Crosstales.RTVoice.SALSA.SpeakSimple, 183
- Crosstales.RTVoice.SALSA, 22
- Crosstales.RTVoice.Speaker, 164
- Crosstales.RTVoice.Tool, 22
- Crosstales.RTVoice.Tool.AudioFileGenerator, 28
- Crosstales.RTVoice.Tool.ChangeGender, 69
- Crosstales.RTVoice.Tool.Loudspeaker, 124
- Crosstales.RTVoice.Tool.Paralanguage, 129
- Crosstales.RTVoice.Tool.Sequencer, 148
- Crosstales.RTVoice.Tool.SpeechText, 189
- Crosstales.RTVoice.Tool.TextFileSpeaker, 197
- Crosstales.RTVoice.Tool.VoiceInitializer, 217
- Crosstales.RTVoice.UDEA2, 23
- Crosstales.RTVoice.UDEA2.UDEAConnector, 204
- Crosstales.RTVoice.UDEA2.UDEAConnectorEditor,
205
- Crosstales.RTVoice.UDEA2.UDEAVoiceWrapper, 205
- Crosstales.RTVoice.Util, 23
- Crosstales.RTVoice.Util.Config, 71
- Crosstales.RTVoice.Util.Constants, 77
- Crosstales.RTVoice.Util.Helper, 112
- Crosstales.RTVoice.Util.WavMaster, 245
- Crosstales.RTVoice.VoiceProviderExample, 224
- Crosstales.UI.Social, 158
- Crosstales.UI.StaticManager, 193
- Crosstales.UI.UIDrag, 207
- Crosstales.UI.UIFocus, 207
- Crosstales.UI.UIHint, 208
- Crosstales.UI.UIResize, 210
- Crosstales.UI.UIWindowManager, 211
- Crosstales.UI.Util, 24
- Crosstales.UI.Util.AudioFilterController, 31
- Crosstales.UI.Util.AudioSourceController, 33
- Crosstales.UI.Util.FPSDisplay, 105
- Crosstales.UI.Util.ScrollRectHandler, 145
- Crosstales.UI.WindowManager, 247
- Crosstales.UI, 24
- Crosstales::Common::EditorUtil::BaseEditorHelper
 - getBuildNameFromBuildTarget, 49
 - getBuildTargetForBuildName, 50
 - getCLIArgument, 50
 - isValidBuildTarget, 50
 - ReadOnlyTextField, 50
 - RefreshAssetDatabase, 51
 - RestartUnity, 51
 - SeparatorUI, 51
- Crosstales::Common::EditorUtil::BaseGAApi
 - Event, 52
- Crosstales::Common::Model::Enum
 - Platform, 14
 - SampleRate, 14
- Crosstales::Common::Util::BackgroundController
 - Objects, 36
- Crosstales::Common::Util::BaseConstants
 - APPLICATION_PATH, 43
 - ASSET_3P_PLAYMAKER, 39
 - ASSET_AUTHOR_URL, 39
 - ASSET_AUTHOR, 39
 - ASSET_BWF, 39
 - ASSET_CT_URL, 39
 - ASSET_DJ, 39
 - ASSET_FB, 40
 - ASSET_OC, 40
 - ASSET_RADIO, 40
 - ASSET_RTV, 40
 - ASSET_SOCIAL_DISCORD, 40
 - ASSET_SOCIAL_FACEBOOK, 40
 - ASSET_SOCIAL_LINKEDIN, 40
 - ASSET_SOCIAL_TWITTER, 40
 - ASSET_SOCIAL_XING, 40
 - ASSET_SOCIAL_YOUTUBE, 41
 - ASSET_TPB, 41
 - ASSET_TPS, 41
 - ASSET_TB, 41
 - ASSET_TR, 41
 - DEV_DEBUG, 41
 - FACTOR_GB, 41
 - FACTOR_KB, 41
 - FACTOR_MB, 41
 - FLOAT_32768, 42
 - FORMAT_NO_DECIMAL_PLACES, 42
 - FORMAT_PERCENT, 42
 - FORMAT_TWO_DECIMAL_PLACES, 42
 - PATH_DELIMITER_UNIX, 42

- PATH_DELIMITER_WINDOWS, 42
- PREFIX_FILE, 43
- PROCESS_KILL_TIME, 42
- SHOW_BWF_BANNER, 42
- SHOW_DJ_BANNER, 42
- SHOW_FB_BANNER, 42
- SHOW_OC_BANNER, 43
- SHOW_RADIO_BANNER, 43
- SHOW_RTV_BANNER, 43
- SHOW_TB_BANNER, 43
- SHOW_TPB_BANNER, 43
- SHOW_TPS_BANNER, 43
- SHOW_TR_BANNER, 43
- Crosstales::Common::Util::BaseHelper
 - ClearLineEndings, 55
 - ClearSpaces, 55
 - ClearTags, 55
 - CreateString, 56
 - CurrentPlatform, 59
 - FileCopy, 56
 - FormatBytesToHRF, 56
 - FormatSecondsToHourMinSec, 56
 - HSVToRGB, 57
 - hasActiveClip, 56
 - isAndroidPlatform, 59
 - isAppleBasedPlatform, 59
 - isEditor, 59
 - isEditorMode, 59
 - isIOSPlatform, 60
 - isInternetAvailable, 60
 - isLinuxPlatform, 60
 - isMacOSPlatform, 60
 - isStandalonePlatform, 60
 - isValidURL, 57
 - isWSAPlatform, 61
 - isWebGLPlatform, 60
 - isWebPlatform, 61
 - isWindowsBasedPlatform, 61
 - isWindowsPlatform, 61
 - RemoteCertificateValidationCallback, 57
 - SplitStringToLines, 57
 - ValidURLFromFilePath, 58
 - ValidateFile, 58
 - ValidatePath, 58
- Crosstales::Common::Util::CTPlayerPrefs
 - DeleteAll, 84
 - DeleteKey, 84
 - GetBool, 84
 - GetDate, 84
 - GetFloat, 84
 - GetInt, 85
 - GetString, 85
 - HasKey, 85
 - Save, 86
 - SetBool, 86
 - SetDate, 86
 - SetFloat, 86
 - SetInt, 86
 - SetString, 87
- Crosstales::Common::Util::CTWebClient
 - ConnectionLimit, 88
 - Timeout, 88
- Crosstales::Common::Util::FFTAnalyzer
 - Channel, 104
 - Samples, 104
- Crosstales::Common::Util::PlatformController
 - Objects, 135
 - Platforms, 135
- Crosstales::Common::Util::RandomColor
 - AlphaRange, 138
 - ChangeInterval, 138
 - GrayScale, 138
 - HueRange, 138
 - Material, 138
 - SaturationRange, 139
 - UseInterval, 139
 - ValueRange, 139
- Crosstales::Common::Util::RandomRotator
 - ChangeInterval, 140
 - SpeedMax, 140
 - SpeedMin, 140
 - UseInterval, 140
- Crosstales::Common::Util::RandomScaler
 - ChangeInterval, 141
 - ScaleMax, 141
 - ScaleMin, 141
 - Uniform, 142
 - UseInterval, 142
- Crosstales::Common::Util::SerializeDeSerialize
 - DeserializeFromByteArray< T >, 152
 - DeserializeFromFile< T >, 152
 - SerializeToByteArray< T >, 152
 - SerializeToFile< T >, 153
- Crosstales::Common::Util::SpectrumVisualizer
 - Analyzer, 187
 - Gain, 187
 - LeftToRight, 187
 - VisualPrefab, 187
 - Width, 187
- Crosstales::Common::Util::SurviveSceneSwitch
 - Survivors, 195
- Crosstales::Common::Util::TakeScreenshot
 - Prefix, 196
 - Scale, 196
 - Update, 196
- Crosstales::Common::Util::XmlHelper
 - DeserializeFromFile< T >, 253
 - DeserializeFromResource< T >, 253
 - DeserializeFromString< T >, 253
 - SerializeToFile< T >, 254
 - SerializeToString< T >, 254
- Crosstales::ExtensionMethods
 - CTAddRange< K, V >, 96
 - CTContains, 97
 - CTContainsAll, 97
 - CTContainsAny, 97

- CTDump, 98–100
- CTDump< K, V >, 100
- CTDump< T >, 100
- CTEquals, 101
- CTIsVisibleFrom, 101
- CTReplace, 101
- CTReverse, 102
- CTShuffle< T >, 102
- CTToString< T >, 103
- CTToTitleCase, 103
- Crosstales::RTVoice::AWSPolly
 - Endpoint, 17
- Crosstales::RTVoice::AWSPolly::VoiceProviderAWS
 - CognitoCredentials, 223
 - Endpoint, 223
 - Generate, 222
 - Load, 222
 - Speak, 222
 - SpeakNative, 222
- Crosstales::RTVoice::Demo::Util::NativeController
 - Active, 129
 - Objects, 129
- Crosstales::RTVoice::EditorTask
 - UpdateStatus, 19
- Crosstales::RTVoice::EditorUtil::EditorConfig
 - ASSET_PATH, 91
 - HIERARCHY_ICON, 90
 - isLoading, 90
 - Load, 90
 - PREFAB_AUTOLOAD, 90
 - PREFAB_PATH, 91
 - REMINDER_CHECK, 90
 - Reset, 90
 - Save, 90
 - TRACER, 90
 - UPDATE_CHECK, 90
- Crosstales::RTVoice::EditorUtil::EditorConstants
 - ASSET_ID, 92
 - ASSET_UID, 92
 - ASSET_URL, 92
 - PREFAB_SUBPATH, 92
- Crosstales::RTVoice::EditorUtil::EditorHelper
 - BannerOC, 94
 - GO_ID, 95
 - InstantiatePrefab, 94
 - isRTVoiceInScene, 95
 - MENU_ID, 95
 - NoVoicesUI, 94
- Crosstales::RTVoice::EditorUtil::GAApi
 - Event, 106
- Crosstales::RTVoice::Klattersynth::VoiceProvider↔
 - Klattersynth
 - Generate, 230
 - Load, 230
 - SampleRate, 231
 - Speak, 230
 - SpeakNative, 231
 - Speeches, 231
- Crosstales::RTVoice::LiveSpeaker
 - SetState, 122
 - SetVoices, 122
 - Silence, 122
 - Speak, 123
 - SpeakNative, 123, 124
 - WordSpoken, 124
- Crosstales::RTVoice::Model::Enum
 - ESpeakModifiers, 21
 - Gender, 21
 - MaryTTSType, 21
 - ProviderType, 21
 - SpeakMode, 21
- Crosstales::RTVoice::Model::Sequence
 - Mode, 147
 - Pitch, 147
 - Rate, 147
 - Source, 147
 - Text, 147
 - Voices, 147
 - Volume, 147
- Crosstales::RTVoice::Model::Voice
 - Age, 213
 - Culture, 214
 - Description, 213
 - Gender, 214
 - Identifier, 214
 - Name, 214
 - Vendor, 214
 - Voice, 213
- Crosstales::RTVoice::Model::VoiceAlias
 - Culture, 215
 - Gender, 215
 - Voice, 216
 - VoiceName, 216
 - VoiceNameAndroid, 215
 - VoiceNameCustom, 215
 - VoiceNameIOS, 216
 - VoiceNameLinux, 216
 - VoiceNameMac, 216
 - VoiceNameMaryTTS, 216
 - VoiceNameWSA, 216
 - VoiceNameWindows, 216
- Crosstales::RTVoice::Model::Wrapper
 - Created, 252
 - ForceSSML, 251
 - OutputFile, 251
 - Pitch, 252
 - Rate, 252
 - Source, 251
 - SpeakImmediately, 251
 - Text, 252
 - Uid, 251
 - Voice, 251
 - Volume, 252
 - Wrapper, 250
- Crosstales::RTVoice::Provider::BaseCustomVoice↔
 - Provider

- Generate, 45
- Load, 46
- OnErrorInfo, 47
- OnSpeakAudioGenerationComplete, 47
- OnSpeakAudioGenerationStart, 47
- OnSpeakComplete, 47
- OnSpeakCurrentPhoneme, 47
- OnSpeakCurrentViseme, 47
- OnSpeakCurrentWord, 47
- OnSpeakStart, 48
- OnVoicesReady, 48
- Silence, 46
- Speak, 46
- SpeakNative, 46
- Crosstales::RTVoice::Provider::BaseVoiceProvider
 - BaseVoiceProvider, 65
 - Generate, 66
 - OnErrorInfo, 67
 - OnSpeakAudioGenerationComplete, 67
 - OnSpeakAudioGenerationStart, 67
 - OnSpeakComplete, 67
 - OnSpeakCurrentPhoneme, 67
 - OnSpeakCurrentViseme, 68
 - OnSpeakCurrentWord, 68
 - OnSpeakStart, 68
 - OnVoicesReady, 68
 - Silence, 66
 - Speak, 66
 - SpeakNative, 67
- Crosstales::RTVoice::Provider::IVoiceProvider
 - AudioFileExtension, 119
 - AudioFileType, 119
 - Cultures, 119
 - DefaultVoiceName, 119
 - Generate, 117
 - hasCoRoutines, 119
 - isOnlineService, 119
 - isPlatformSupported, 120
 - isSSMLSupported, 120
 - isSpeakNativeSupported, 120
 - isSpeakSupported, 120
 - isWorkingInEditor, 120
 - MaxTextLength, 120
 - Silence, 118
 - Speak, 118
 - SpeakNative, 118
 - Voices, 121
- Crosstales::RTVoice::Provider::VoiceProviderAndroid
 - Generate, 220
 - Silence, 220
 - Speak, 220
 - SpeakNative, 220
 - VoiceProviderAndroid, 219
- Crosstales::RTVoice::Provider::VoiceProviderIOS
 - Generate, 228
 - SetState, 228
 - SetVoices, 228
 - Silence, 228
 - Speak, 228
 - SpeakNative, 229
 - VoiceProviderIOS, 227
 - WordSpoken, 229
- Crosstales::RTVoice::Provider::VoiceProviderLinux
 - Generate, 234
 - Speak, 234
 - SpeakNative, 234
 - VoiceProviderLinux, 233
- Crosstales::RTVoice::Provider::VoiceProviderMacOS
 - Generate, 236
 - Speak, 236
 - SpeakNative, 236
 - VoiceProviderMacOS, 235
- Crosstales::RTVoice::Provider::VoiceProviderMary
 - Generate, 238
 - Silence, 238
 - Speak, 238
 - SpeakNative, 238
 - VoiceProviderMary, 237
- Crosstales::RTVoice::Provider::VoiceProviderWSA
 - Generate, 244
 - Silence, 244
 - Speak, 244
 - SpeakNative, 245
 - VoiceProviderWSA, 244
- Crosstales::RTVoice::Provider::VoiceProviderWindows
 - Generate, 240
 - Speak, 240
 - SpeakNative, 240
 - VoiceProviderWindows, 240
- Crosstales::RTVoice::Provider::VoiceProviderWindows↔
 - Legacy
 - Generate, 242
 - Speak, 242
 - SpeakNative, 242
 - VoiceProviderWindowsLegacy, 242
- Crosstales::RTVoice::Speaker
 - ApproximateSpeechLength, 168
 - areVoicesReady, 177
 - AudioFileExtension, 177
 - AutoClearTags, 175
 - BusyCount, 177
 - Cultures, 177
 - CustomMode, 175
 - CustomProvider, 175
 - CustomVoiceProvider, 177
 - DefaultVoiceName, 177
 - DeleteAudioFiles, 169
 - DontDestroy, 175
 - ESpeakMod, 178
 - ESpeakMode, 176
 - ESpeakModifier, 176
 - Generate, 169
 - hasCoRoutines, 178
 - isAutoClearTags, 178
 - isBusy, 178
 - isCustomMode, 178

- isESpeakMode, 178
- isMaryMode, 178
- isOnlineService, 178
- isPlatformSupported, 179
- isSSMLSupported, 180
- isSilenceOnDisable, 179
- isSilenceOnFocustLost, 179
- isSpeakNativeSupported, 179
- isSpeakSupported, 179
- isSpeaking, 179
- isTTSAvailable, 180
- isVoiceForCultureAvailable, 170
- isVoiceForGenderAvailable, 170
- isVoiceForNameAvailable, 170
- isWindowsLegacy, 180
- isWorkingInEditor, 180
- MaryPassword, 180
- MaryPort, 180
- MaryTTSMMode, 176
- MaryTTSPassword, 176
- MaryTTSPort, 176
- MaryTTSType, 176
- MaryTTSUrl, 176
- MaryTTSUser, 176
- MaryType, 180
- MaryUrl, 181
- MaryUser, 181
- MaxTextLength, 181
- OnErrorInfo, 181
- OnProviderChange, 181
- OnSpeakAudioGenerationComplete, 181
- OnSpeakAudioGenerationStart, 181
- OnSpeakComplete, 181
- OnSpeakCurrentPhoneme, 181
- OnSpeakCurrentViseme, 182
- OnSpeakCurrentWord, 182
- OnSpeakStart, 182
- OnVoicesReady, 182
- Pause, 170
- ReloadProvider, 171
- Reset, 171
- Silence, 171
- SilenceOnDisable, 176
- SilenceOnFocustLost, 176
- Speak, 171, 172
- SpeakMarkedWordsWithUID, 172
- SpeakNative, 172, 173
- SpeakNativeWithUID, 173
- SpeakWithUID, 173
- SpeechCount, 182
- UnPause, 173
- VoiceForCulture, 174
- VoiceForGender, 174
- VoiceForName, 174
- Voices, 182
- VoicesForCulture, 175
- VoicesForGender, 175
- WindowsLegacy, 177
- Crosstales::RTVoice::Tool::AudioFileGenerator
 - FileInsideAssets, 29
 - Generate, 29
 - GenerateOnStart, 29
 - OnAudioFileGeneratorComplete, 29
 - OnAudioFileGeneratorStart, 29
 - TextFiles, 29
- Crosstales::RTVoice::Tool::ChangeGender
 - ESpeakOnly, 70
 - NewGender, 70
 - RefreshOnVoicesReady, 70
- Crosstales::RTVoice::Tool::Loudspeaker
 - isSilenceSource, 126
 - isSynchronized, 126
 - SilenceSource, 125
 - Source, 125
 - Synchronized, 125
- Crosstales::RTVoice::Tool::Paralanguage
 - Clips, 131
 - CurrentPitch, 132
 - CurrentRate, 132
 - CurrentText, 132
 - CurrentVolume, 132
 - Delay, 131
 - Mode, 131
 - OnParalanguageComplete, 132
 - OnParalanguageStart, 132
 - Pitch, 131
 - PlayOnStart, 131
 - Rate, 131
 - Silence, 131
 - Speak, 131
 - Text, 131
 - Voices, 131
 - Volume, 132
- Crosstales::RTVoice::Tool::Sequencer
 - CurrentSequence, 150
 - Delay, 149
 - PlayAllSequences, 149
 - PlayNextSequence, 149
 - PlayOnStart, 150
 - PlaySequence, 149
 - Sequences, 150
 - StopAllSequences, 149
- Crosstales::RTVoice::Tool::SpeechText
 - CurrentPitch, 191
 - CurrentRate, 191
 - CurrentText, 192
 - CurrentVolume, 192
 - Delay, 190
 - FileInsideAssets, 190
 - FileName, 190
 - GenerateAudioFile, 190
 - Mode, 191
 - OnSpeechTextComplete, 192
 - OnSpeechTextStart, 192
 - Pitch, 191
 - PlayOnStart, 191

- Rate, 191
- Silence, 190
- Source, 191
- Speak, 190
- Text, 191
- Voices, 191
- Volume, 191
- Crosstales::RTVoice::Tool::TextFileSpeaker
 - CurrentPitch, 201
 - CurrentRate, 201
 - CurrentVolume, 201
 - Delay, 200
 - Mode, 200
 - Next, 198
 - Pitch, 200
 - PlayAllOnStart, 200
 - PlayOnStart, 200
 - Previous, 199
 - Rate, 200
 - Reload, 199
 - Silence, 199
 - Source, 200
 - Speak, 199
 - SpeakAll, 199
 - SpeakRandom, 200
 - SpeakText, 199
 - StopAll, 200
 - TextFiles, 200
 - Voices, 201
 - Volume, 201
- Crosstales::RTVoice::Tool::VoiceInitializer
 - AllVoices, 218
 - DestroyWhenFinished, 218
 - Provider, 218
 - VoiceNames, 218
- Crosstales::RTVoice::UDEA2::UDEAConnector
 - Culture, 204
 - Voices, 204
- Crosstales::RTVoice::UDEA2::UDEAVoiceWrapper
 - IgnoreCharacter, 206
 - Pitch, 206
 - Rate, 206
 - Source, 206
 - UDEAVoiceName, 206
 - Voices, 206
 - Volume, 206
- Crosstales::RTVoice::Util::Config
 - ASSET_PATH, 73
 - AUDIOFILE_AUTOMATIC_DELETE, 73
 - AUDIOFILE_PATH, 74
 - DEBUG, 73
 - ENFORCE_32BIT_WINDOWS, 73
 - ENSURE_NAME, 73
 - isLoaded, 73
 - Load, 73
 - Reset, 73
 - Save, 73
 - TTS_LINUX_DATA, 74
 - TTS_LINUX, 73
 - TTS_MACOS, 74
 - TTS_WINDOWS_BUILD, 74
 - TTS_WINDOWS_EDITOR_x86, 74
 - TTS_WINDOWS_EDITOR, 74
- Crosstales::RTVoice::Util::Constants
 - ASSET_2019_URL, 79
 - ASSET_3P_ADVENTURE_CREATOR, 79
 - ASSET_3P_CINEMA_DIRECTOR, 79
 - ASSET_3P_DIALOG_SYSTEM, 80
 - ASSET_3P_DIALOGUE_ENGINE, 80
 - ASSET_3P_LIPSYNC, 80
 - ASSET_3P_LOCALIZED_DIALOGS, 80
 - ASSET_3P_NPC_CHAT, 80
 - ASSET_3P_QUEST_SYSTEM, 80
 - ASSET_3P_SALSA, 80
 - ASSET_3P_SLATE, 80
 - ASSET_3P_URL, 80
 - ASSET_3P_USEQUENCER, 81
 - ASSET_API_URL, 81
 - ASSET_BUILD, 81
 - ASSET_CHANGED, 81
 - ASSET_CONTACT, 81
 - ASSET_CREATED, 81
 - ASSET_FORUM_URL, 81
 - ASSET_MANUAL_URL, 81
 - ASSET_NAME, 81
 - ASSET_PRO_URL, 82
 - ASSET_UPDATE_CHECK_URL, 82
 - ASSET_VERSION, 82
 - ASSET_VIDEO_PROMO, 82
 - ASSET_VIDEO_TUTORIAL, 82
 - ASSET_WEB_URL, 82
 - AUDIOFILE_PREFIX, 82
 - ESPEAK_FEMALE_MODIFIER, 82
 - RTVOICE_SCENE_OBJECT_NAME, 82
 - SPEAK_CALL_SPEED, 82
 - TTS_WINDOWS_SUBPATH, 83
 - TTS_WINDOWS_x86_SUBPATH, 83
- Crosstales::RTVoice::Util::Helper
 - AppleVoiceNameToGender, 113
 - CleanText, 114
 - CurrentProviderType, 115
 - hasBuiltInTTS, 115
 - MarkSpokenText, 114
 - StringToGender, 114
 - WSAVoiceNameToGender, 115
- Crosstales::RTVoice::Util::WavMaster
 - BitDepth, 245
 - FromAudioClip, 246
 - ToAudioClip, 246
- Crosstales::RTVoice::VoiceProviderExample
 - Generate, 225
 - Load, 225
 - Speak, 226
 - SpeakNative, 226
- Crosstales::UI::StaticManager
 - OpenCrosstales, 194

- Quit, 194
- Crosstales::UI::UIDrag
 - BeginDrag, 207
 - Start, 207
- Crosstales::UI::UIFocus
 - ManagerName, 208
 - Start, 208
- Crosstales::UI::UIHint
 - Delay, 209
 - Disable, 209
 - FadeAtStart, 209
 - FadeTime, 209
 - Group, 209
- Crosstales::UI::UIResize
 - MaxSize, 210
 - MinSize, 210
- Crosstales::UI::UIWindowManager
 - Start, 211
 - Windows, 212
- Crosstales::UI::Util::AudioFilterController
 - FindAllAudioFilters, 32
 - FindAllAudioFiltersOnStart, 32
 - ResetAudioFilters, 32
- Crosstales::UI::Util::AudioSourceController
 - AudioSources, 34
 - FindAllAudioSources, 34
 - FindAllAudioSourcesOnStart, 34
 - Loop, 34
 - Mute, 34
 - Pitch, 34
 - ResetAllAudioSources, 34
 - ResetAudioSourcesOnStart, 34
 - StereoPan, 34
 - Volume, 34
- Crosstales::UI::Util::FPSDisplay
 - FPS, 105
- Crosstales::UI::WindowManager
 - Dependencies, 248
 - OpenPanel, 248
 - Speed, 248
 - SwitchPanel, 248
 - Update, 248
- Culture
 - Crosstales::RTVoice::Model::Voice, 214
 - Crosstales::RTVoice::Model::VoiceAlias, 215
 - Crosstales::RTVoice::UDEA2::UDEAConnector, 204
 - HutongGames::PlayMaker::Actions::Speak, 160
 - HutongGames::PlayMaker::Actions::SpeakUI, 185
- Cultures
 - Crosstales::RTVoice::Provider::IVoiceProvider, 119
 - Crosstales::RTVoice::Speaker, 177
- CurrentPitch
 - Crosstales::RTVoice::Tool::Paralanguage, 132
 - Crosstales::RTVoice::Tool::SpeechText, 191
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 201
- CurrentPlatform
 - Crosstales::Common::Util::BaseHelper, 59
- CurrentProviderType
 - Crosstales::RTVoice::Util::Helper, 115
- CurrentRate
 - Crosstales::RTVoice::Tool::Paralanguage, 132
 - Crosstales::RTVoice::Tool::SpeechText, 191
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 201
- CurrentSequence
 - Crosstales::RTVoice::Tool::Sequencer, 150
- CurrentText
 - Crosstales::RTVoice::Tool::Paralanguage, 132
 - Crosstales::RTVoice::Tool::SpeechText, 192
- CurrentVolume
 - Crosstales::RTVoice::Tool::Paralanguage, 132
 - Crosstales::RTVoice::Tool::SpeechText, 192
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 201
- CustomMode
 - Crosstales::RTVoice::Speaker, 175
- CustomProvider
 - Crosstales::RTVoice::Speaker, 175
- CustomVoiceProvider
 - Crosstales::RTVoice::Speaker, 177
- DEBUG
 - Crosstales::RTVoice::Util::Config, 73
- DEV_DEBUG
 - Crosstales::Common::Util::BaseConstants, 41
- DefaultVoiceName
 - Crosstales::RTVoice::Provider::IVoiceProvider, 119
 - Crosstales::RTVoice::Speaker, 177
- Delay
 - Crosstales::RTVoice::Tool::Paralanguage, 131
 - Crosstales::RTVoice::Tool::Sequencer, 149
 - Crosstales::RTVoice::Tool::SpeechText, 190
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 200
 - Crosstales::UI::UIHint, 209
- DeleteAll
 - Crosstales::Common::Util::CTPlayerPrefs, 84
- DeleteAudioFiles
 - Crosstales::RTVoice::Speaker, 169
- DeleteKey
 - Crosstales::Common::Util::CTPlayerPrefs, 84
- Dependencies
 - Crosstales::UI::WindowManager, 248
- Description
 - Crosstales::RTVoice::Model::Voice, 213
- DeserializeFromByteArray< T >
 - Crosstales::Common::Util::SerializeDeSerialize, 152
- DeserializeFromFile< T >
 - Crosstales::Common::Util::SerializeDeSerialize, 152
 - Crosstales::Common::Util::XmlHelper, 253
- DeserializeFromResource< T >
 - Crosstales::Common::Util::XmlHelper, 253
- DeserializeFromString< T >
 - Crosstales::Common::Util::XmlHelper, 253
- DestroyWhenFinished
 - Crosstales::RTVoice::Tool::VoiceInitializer, 218
- Disable

- Crosstales::UI::UIHint, 209
- DontDestroy
 - Crosstales::RTVoice::Speaker, 175
- ENFORCE_32BIT_WINDOWS
 - Crosstales::RTVoice::Util::Config, 73
- ENSURE_NAME
 - Crosstales::RTVoice::Util::Config, 73
- ESPEAK_FEMALE_MODIFIER
 - Crosstales::RTVoice::Util::Constants, 82
- ESpeakMod
 - Crosstales::RTVoice::Speaker, 178
- ESpeakMode
 - Crosstales::RTVoice::Speaker, 176
- ESpeakModifier
 - Crosstales::RTVoice::Speaker, 176
- ESpeakModifiers
 - Crosstales::RTVoice::Model::Enum, 21
- ESpeakOnly
 - Crosstales::RTVoice::Tool::ChangeGender, 70
- Endpoint
 - Crosstales::RTVoice::AWSPolly, 17
 - Crosstales::RTVoice::AWSPolly::VoiceProviderA↔WS, 223
- Event
 - Crosstales::Common::EditorUtil::BaseGAApi, 52
 - Crosstales::RTVoice::EditorUtil::GAApi, 106
- FACTOR_GB
 - Crosstales::Common::Util::BaseConstants, 41
- FACTOR_KB
 - Crosstales::Common::Util::BaseConstants, 41
- FACTOR_MB
 - Crosstales::Common::Util::BaseConstants, 41
- FLOAT_32768
 - Crosstales::Common::Util::BaseConstants, 42
- FORMAT_NO_DECIMAL_PLACES
 - Crosstales::Common::Util::BaseConstants, 42
- FORMAT_PERCENT
 - Crosstales::Common::Util::BaseConstants, 42
- FORMAT_TWO_DECIMAL_PLACES
 - Crosstales::Common::Util::BaseConstants, 42
- FPS
 - Crosstales::UI::Util::FPSDisplay, 105
- FadeAtStart
 - Crosstales::UI::UIHint, 209
- FadeTime
 - Crosstales::UI::UIHint, 209
- FileCopy
 - Crosstales::Common::Util::BaseHelper, 56
- FileInsideAssets
 - Crosstales::RTVoice::Tool::AudioFileGenerator, 29
 - Crosstales::RTVoice::Tool::SpeechText, 190
- FileName
 - Crosstales::RTVoice::Tool::SpeechText, 190
- FindAllAudioFilters
 - Crosstales::UI::Util::AudioFilterController, 32
- FindAllAudioFiltersOnStart
 - Crosstales::UI::Util::AudioFilterController, 32
- FindAllAudioSources
 - Crosstales::UI::Util::AudioSourceController, 34
- FindAllAudioSourcesOnStart
 - Crosstales::UI::Util::AudioSourceController, 34
- ForceSSML
 - Crosstales::RTVoice::Model::Wrapper, 251
- FormatBytesToHRF
 - Crosstales::Common::Util::BaseHelper, 56
- FormatSecondsToHourMinSec
 - Crosstales::Common::Util::BaseHelper, 56
- FromAudioClip
 - Crosstales::RTVoice::Util::WavMaster, 246
- GO_ID
 - Crosstales::RTVoice::EditorUtil::EditorHelper, 95
- Gain
 - Crosstales::Common::Util::SpectrumVisualizer, 187
- Gender
 - Crosstales::RTVoice::Model::Enum, 21
 - Crosstales::RTVoice::Model::Voice, 214
 - Crosstales::RTVoice::Model::VoiceAlias, 215
- Generate
 - Crosstales::RTVoice::AWSPolly::VoiceProviderA↔WS, 222
 - Crosstales::RTVoice::Klattersynth::VoiceProvider↔Klattersynth, 230
 - Crosstales::RTVoice::Provider::BaseCustom↔VoiceProvider, 45
 - Crosstales::RTVoice::Provider::BaseVoice↔Provider, 66
 - Crosstales::RTVoice::Provider::IVoiceProvider, 117
 - Crosstales::RTVoice::Provider::VoiceProvider↔Android, 220
 - Crosstales::RTVoice::Provider::VoiceProviderIOS, 228
 - Crosstales::RTVoice::Provider::VoiceProvider↔Linux, 234
 - Crosstales::RTVoice::Provider::VoiceProvider↔MacOS, 236
 - Crosstales::RTVoice::Provider::VoiceProviderMary, 238
 - Crosstales::RTVoice::Provider::VoiceProviderW↔SA, 244
 - Crosstales::RTVoice::Provider::VoiceProvider↔Windows, 240
 - Crosstales::RTVoice::Provider::VoiceProvider↔WindowsLegacy, 242
 - Crosstales::RTVoice::Speaker, 169
 - Crosstales::RTVoice::Tool::AudioFileGenerator, 29
 - Crosstales::RTVoice::VoiceProviderExample, 225
- GenerateAudioFile
 - Crosstales::RTVoice::Tool::SpeechText, 190
- GenerateOnStart
 - Crosstales::RTVoice::Tool::AudioFileGenerator, 29
- GetBool
 - Crosstales::Common::Util::CTPlayerPrefs, 84
- getBuildNameFromBuildTarget

- Crosstales::Common::EditorUtil::BaseEditor↔
 - Helper, 49
- getBuildTargetForBuildName
 - Crosstales::Common::EditorUtil::BaseEditor↔
 - Helper, 50
- getCLIArgument
 - Crosstales::Common::EditorUtil::BaseEditor↔
 - Helper, 50
- GetDate
 - Crosstales::Common::Util::CTPlayerPrefs, 84
- GetFloat
 - Crosstales::Common::Util::CTPlayerPrefs, 84
- GetInt
 - Crosstales::Common::Util::CTPlayerPrefs, 85
- GetString
 - Crosstales::Common::Util::CTPlayerPrefs, 85
- GrayScale
 - Crosstales::Common::Util::RandomColor, 138
- Group
 - Crosstales::UI::UIHint, 209
- HIERARCHY_ICON
 - Crosstales::RTVoice::EditorUtil::EditorConfig, 90
- HSVToRGB
 - Crosstales::Common::Util::BaseHelper, 57
- hasActiveClip
 - Crosstales::Common::Util::BaseHelper, 56
- hasBuiltInTTS
 - Crosstales::RTVoice::Util::Helper, 115
- hasCoRoutines
 - Crosstales::RTVoice::Provider::IVoiceProvider, 119
 - Crosstales::RTVoice::Speaker, 178
- HasKey
 - Crosstales::Common::Util::CTPlayerPrefs, 85
- HueRange
 - Crosstales::Common::Util::RandomColor, 138
- HutongGames, 24
- HutongGames.PlayMaker, 24
- HutongGames.PlayMaker.Actions, 24
- HutongGames.PlayMaker.Actions.AudioFileGenerator, 27
- HutongGames.PlayMaker.Actions.BaseRTVAction, 62
- HutongGames.PlayMaker.Actions.Paralanguage, 133
- HutongGames.PlayMaker.Actions.Silence, 155
- HutongGames.PlayMaker.Actions.Speak, 159
- HutongGames.PlayMaker.Actions.SpeakBase, 162
- HutongGames.PlayMaker.Actions.SpeakUI, 184
- HutongGames.PlayMaker.Actions.SpeechText, 188
- HutongGames.PlayMaker.Actions.TextFileSpeaker, 201
- HutongGames::PlayMaker::Actions::AudioFileGenerator
 - Obj, 28
- HutongGames::PlayMaker::Actions::Paralanguage
 - Obj, 133
- HutongGames::PlayMaker::Actions::Speak
 - Culture, 160
 - RTVoiceNameAndroid, 160
 - RTVoiceNameCustom, 160
 - RTVoiceNameIOS, 160
 - RTVoiceNameMac, 160
 - RTVoiceNameMaryTTS, 161
 - RTVoiceNameWSA, 161
 - RTVoiceNameWindows, 161
 - Text, 161
- HutongGames::PlayMaker::Actions::SpeakBase
 - AudioSource, 163
 - Mode, 163
 - Pitch, 163
 - Rate, 163
 - Volume, 163
- HutongGames::PlayMaker::Actions::SpeakUI
 - Culture, 185
 - RTVoiceName, 185
 - Text, 185
- HutongGames::PlayMaker::Actions::SpeechText
 - Obj, 188
- HutongGames::PlayMaker::Actions::TextFileSpeaker
 - Obj, 202
- Identifier
 - Crosstales::RTVoice::Model::Voice, 214
- IgnoreCharacter
 - Crosstales::RTVoice::UDEA2::UDEAVoice↔
 - Wrapper, 206
- InstantiatePrefab
 - Crosstales::RTVoice::EditorUtil::EditorHelper, 94
- isAndroidPlatform
 - Crosstales::Common::Util::BaseHelper, 59
- isAppleBasedPlatform
 - Crosstales::Common::Util::BaseHelper, 59
- isAutoClearTags
 - Crosstales::RTVoice::Speaker, 178
- isBusy
 - Crosstales::RTVoice::Speaker, 178
- isCustomMode
 - Crosstales::RTVoice::Speaker, 178
- isESpeakMode
 - Crosstales::RTVoice::Speaker, 178
- isEditor
 - Crosstales::Common::Util::BaseHelper, 59
- isEditorMode
 - Crosstales::Common::Util::BaseHelper, 59
- isIOSPlatform
 - Crosstales::Common::Util::BaseHelper, 60
- isInternetAvailable
 - Crosstales::Common::Util::BaseHelper, 60
- isLinuxPlatform
 - Crosstales::Common::Util::BaseHelper, 60
- isLoaded
 - Crosstales::RTVoice::EditorUtil::EditorConfig, 90
 - Crosstales::RTVoice::Util::Config, 73
- isMacOSPlatform
 - Crosstales::Common::Util::BaseHelper, 60
- isMaryMode
 - Crosstales::RTVoice::Speaker, 178
- isOnlineService
 - Crosstales::RTVoice::Provider::IVoiceProvider, 119
 - Crosstales::RTVoice::Speaker, 178
- isPlatformSupported

- Crosstales::RTVoice::Provider::IVoiceProvider, 120
- Crosstales::RTVoice::Speaker, 179
- isRTVoiceInScene
 - Crosstales::RTVoice::EditorUtil::EditorHelper, 95
- isSSMLSupported
 - Crosstales::RTVoice::Provider::IVoiceProvider, 120
 - Crosstales::RTVoice::Speaker, 180
- isSilenceOnDisable
 - Crosstales::RTVoice::Speaker, 179
- isSilenceOnFocusLost
 - Crosstales::RTVoice::Speaker, 179
- isSilenceSource
 - Crosstales::RTVoice::Tool::Loudspeaker, 126
- isSpeakNativeSupported
 - Crosstales::RTVoice::Provider::IVoiceProvider, 120
 - Crosstales::RTVoice::Speaker, 179
- isSpeakSupported
 - Crosstales::RTVoice::Provider::IVoiceProvider, 120
 - Crosstales::RTVoice::Speaker, 179
- isSpeaking
 - Crosstales::RTVoice::Speaker, 179
- isStandalonePlatform
 - Crosstales::Common::Util::BaseHelper, 60
- isSynchronized
 - Crosstales::RTVoice::Tool::Loudspeaker, 126
- isTTSAvailable
 - Crosstales::RTVoice::Speaker, 180
- isValidBuildTarget
 - Crosstales::Common::EditorUtil::BaseEditor↔
Helper, 50
- isValidURL
 - Crosstales::Common::Util::BaseHelper, 57
- isVoiceForCultureAvailable
 - Crosstales::RTVoice::Speaker, 170
- isVoiceForGenderAvailable
 - Crosstales::RTVoice::Speaker, 170
- isVoiceForNameAvailable
 - Crosstales::RTVoice::Speaker, 170
- isWSAPlatform
 - Crosstales::Common::Util::BaseHelper, 61
- isWebGLPlatform
 - Crosstales::Common::Util::BaseHelper, 60
- isWebPlatform
 - Crosstales::Common::Util::BaseHelper, 61
- isWindowsBasedPlatform
 - Crosstales::Common::Util::BaseHelper, 61
- isWindowsLegacy
 - Crosstales::RTVoice::Speaker, 180
- isWindowsPlatform
 - Crosstales::Common::Util::BaseHelper, 61
- isWorkingInEditor
 - Crosstales::RTVoice::Provider::IVoiceProvider, 120
 - Crosstales::RTVoice::Speaker, 180
- LeftToRight
 - Crosstales::Common::Util::SpectrumVisualizer,
187
- Load
 - Crosstales::RTVoice::AWSPolly::VoiceProviderA↔
WS, 222
 - Crosstales::RTVoice::EditorUtil::EditorConfig, 90
 - Crosstales::RTVoice::Klattersynth::VoiceProvider↔
Klattersynth, 230
 - Crosstales::RTVoice::Provider::BaseCustom↔
VoiceProvider, 46
 - Crosstales::RTVoice::Util::Config, 73
 - Crosstales::RTVoice::VoiceProviderExample, 225
- Loop
 - Crosstales::UI::Util::AudioSourceController, 34
- MENU_ID
 - Crosstales::RTVoice::EditorUtil::EditorHelper, 95
- ManagerName
 - Crosstales::UI::UIFocus, 208
- MarkSpokenText
 - Crosstales::RTVoice::Util::Helper, 114
- MaryPassword
 - Crosstales::RTVoice::Speaker, 180
- MaryPort
 - Crosstales::RTVoice::Speaker, 180
- MaryTTSMODE
 - Crosstales::RTVoice::Speaker, 176
- MaryTTSPassword
 - Crosstales::RTVoice::Speaker, 176
- MaryTTSPort
 - Crosstales::RTVoice::Speaker, 176
- MaryTTSType
 - Crosstales::RTVoice::Model::Enum, 21
 - Crosstales::RTVoice::Speaker, 176
- MaryTTSUrl
 - Crosstales::RTVoice::Speaker, 176
- MaryTTSUser
 - Crosstales::RTVoice::Speaker, 176
- MaryType
 - Crosstales::RTVoice::Speaker, 180
- MaryUrl
 - Crosstales::RTVoice::Speaker, 181
- MaryUser
 - Crosstales::RTVoice::Speaker, 181
- Material
 - Crosstales::Common::Util::RandomColor, 138
- MaxSize
 - Crosstales::UI::UIResize, 210
- MaxTextLength
 - Crosstales::RTVoice::Provider::IVoiceProvider, 120
 - Crosstales::RTVoice::Speaker, 181
- MinSize
 - Crosstales::UI::UIResize, 210
- Mode
 - Crosstales::RTVoice::Model::Sequence, 147
 - Crosstales::RTVoice::Tool::Paralanguage, 131
 - Crosstales::RTVoice::Tool::SpeechText, 191
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 200
 - HutongGames::PlayMaker::Actions::SpeakBase,
163
- Mute
 - Crosstales::UI::Util::AudioSourceController, 34

- Name
 - Crosstales::RTVoice::Model::Voice, 214
- NewGender
 - Crosstales::RTVoice::Tool::ChangeGender, 70
- Next
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 198
- NoVoicesUI
 - Crosstales::RTVoice::EditorUtil::EditorHelper, 94
- Obj
 - HutongGames::PlayMaker::Actions::AudioFile↔
Generator, 28
 - HutongGames::PlayMaker::Actions::Paralanguage,
133
 - HutongGames::PlayMaker::Actions::SpeechText,
188
 - HutongGames::PlayMaker::Actions::TextFile↔
Speaker, 202
- Objects
 - Crosstales::Common::Util::BackgroundController,
36
 - Crosstales::Common::Util::PlatformController, 135
 - Crosstales::RTVoice::Demo::Util::NativeController,
129
- OnAudioFileGeneratorComplete
 - Crosstales::RTVoice::Tool::AudioFileGenerator, 29
- OnAudioFileGeneratorStart
 - Crosstales::RTVoice::Tool::AudioFileGenerator, 29
- OnErrorInfo
 - Crosstales::RTVoice::Provider::BaseCustom↔
VoiceProvider, 47
 - Crosstales::RTVoice::Provider::BaseVoice↔
Provider, 67
 - Crosstales::RTVoice::Speaker, 181
- OnParalanguageComplete
 - Crosstales::RTVoice::Tool::Paralanguage, 132
- OnParalanguageStart
 - Crosstales::RTVoice::Tool::Paralanguage, 132
- OnProviderChange
 - Crosstales::RTVoice::Speaker, 181
- OnSpeakAudioGenerationComplete
 - Crosstales::RTVoice::Provider::BaseCustom↔
VoiceProvider, 47
 - Crosstales::RTVoice::Provider::BaseVoice↔
Provider, 67
 - Crosstales::RTVoice::Speaker, 181
- OnSpeakAudioGenerationStart
 - Crosstales::RTVoice::Provider::BaseCustom↔
VoiceProvider, 47
 - Crosstales::RTVoice::Provider::BaseVoice↔
Provider, 67
 - Crosstales::RTVoice::Speaker, 181
- OnSpeakComplete
 - Crosstales::RTVoice::Provider::BaseCustom↔
VoiceProvider, 47
 - Crosstales::RTVoice::Provider::BaseVoice↔
Provider, 67
 - Crosstales::RTVoice::Speaker, 181
- OnSpeakCurrentPhoneme
 - Crosstales::RTVoice::Provider::BaseCustom↔
VoiceProvider, 47
 - Crosstales::RTVoice::Provider::BaseVoice↔
Provider, 67
 - Crosstales::RTVoice::Speaker, 181
- OnSpeakCurrentViseme
 - Crosstales::RTVoice::Provider::BaseCustom↔
VoiceProvider, 47
 - Crosstales::RTVoice::Provider::BaseVoice↔
Provider, 68
 - Crosstales::RTVoice::Speaker, 182
- OnSpeakCurrentWord
 - Crosstales::RTVoice::Provider::BaseCustom↔
VoiceProvider, 47
 - Crosstales::RTVoice::Provider::BaseVoice↔
Provider, 68
 - Crosstales::RTVoice::Speaker, 182
- OnSpeakStart
 - Crosstales::RTVoice::Provider::BaseCustom↔
VoiceProvider, 48
 - Crosstales::RTVoice::Provider::BaseVoice↔
Provider, 68
 - Crosstales::RTVoice::Speaker, 182
- OnSpeechTextComplete
 - Crosstales::RTVoice::Tool::SpeechText, 192
- OnSpeechTextStart
 - Crosstales::RTVoice::Tool::SpeechText, 192
- OnVoicesReady
 - Crosstales::RTVoice::Provider::BaseCustom↔
VoiceProvider, 48
 - Crosstales::RTVoice::Provider::BaseVoice↔
Provider, 68
 - Crosstales::RTVoice::Speaker, 182
- OpenCrosstales
 - Crosstales::UI::StaticManager, 194
- OpenPanel
 - Crosstales::UI::WindowManager, 248
- OutputFile
 - Crosstales::RTVoice::Model::Wrapper, 251
- PATH_DELIMITER_UNIX
 - Crosstales::Common::Util::BaseConstants, 42
- PATH_DELIMITER_WINDOWS
 - Crosstales::Common::Util::BaseConstants, 42
- PREFAB_AUTOLOAD
 - Crosstales::RTVoice::EditorUtil::EditorConfig, 90
- PREFAB_PATH
 - Crosstales::RTVoice::EditorUtil::EditorConfig, 91
- PREFAB_SUBPATH
 - Crosstales::RTVoice::EditorUtil::EditorConstants,
92
- PREFIX_FILE
 - Crosstales::Common::Util::BaseConstants, 43
- PROCESS_KILL_TIME
 - Crosstales::Common::Util::BaseConstants, 42
- Pause
 - Crosstales::RTVoice::Speaker, 170
- Pitch
 - Crosstales::RTVoice::Model::Sequence, 147

- Crosstales::RTVoice::Model::Wrapper, 252
- Crosstales::RTVoice::Tool::Paralanguage, 131
- Crosstales::RTVoice::Tool::SpeechText, 191
- Crosstales::RTVoice::Tool::TextFileSpeaker, 200
- Crosstales::RTVoice::UDEA2::UDEAVoice↔
Wrapper, 206
- Crosstales::UI::Util::AudioSourceController, 34
- HutongGames::PlayMaker::Actions::SpeakBase, 163
- Platform
 - Crosstales::Common::Model::Enum, 14
- Platforms
 - Crosstales::Common::Util::PlatformController, 135
- PlayAllOnStart
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 200
- PlayAllSequences
 - Crosstales::RTVoice::Tool::Sequencer, 149
- PlayNextSequence
 - Crosstales::RTVoice::Tool::Sequencer, 149
- PlayOnStart
 - Crosstales::RTVoice::Tool::Paralanguage, 131
 - Crosstales::RTVoice::Tool::Sequencer, 150
 - Crosstales::RTVoice::Tool::SpeechText, 191
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 200
- PlaySequence
 - Crosstales::RTVoice::Tool::Sequencer, 149
- Prefix
 - Crosstales::Common::Util::TakeScreenshot, 196
- Previous
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 199
- Provider
 - Crosstales::RTVoice::Tool::VoiceInitalizer, 218
- ProviderType
 - Crosstales::RTVoice::Model::Enum, 21
- Quit
 - Crosstales::UI::StaticManager, 194
- REMINDER_CHECK
 - Crosstales::RTVoice::EditorUtil::EditorConfig, 90
- RTVOICE_SCENE_OBJECT_NAME
 - Crosstales::RTVoice::Util::Constants, 82
- RTVoiceIOSBridge, 143
 - setVoices, 143
 - speak:text:rate:pitch:volume:, 143
 - stop, 143
- RTVoiceIOSBridge(), 144
- RTVoiceName
 - HutongGames::PlayMaker::Actions::SpeakUI, 185
- RTVoiceNameAndroid
 - HutongGames::PlayMaker::Actions::Speak, 160
- RTVoiceNameCustom
 - HutongGames::PlayMaker::Actions::Speak, 160
- RTVoiceNameIOS
 - HutongGames::PlayMaker::Actions::Speak, 160
- RTVoiceNameMac
 - HutongGames::PlayMaker::Actions::Speak, 160
- RTVoiceNameMaryTTS
 - HutongGames::PlayMaker::Actions::Speak, 161
- RTVoiceNameWSA
 - HutongGames::PlayMaker::Actions::Speak, 161
- RTVoiceNameWindows
 - HutongGames::PlayMaker::Actions::Speak, 161
- Rate
 - Crosstales::RTVoice::Model::Sequence, 147
 - Crosstales::RTVoice::Model::Wrapper, 252
 - Crosstales::RTVoice::Tool::Paralanguage, 131
 - Crosstales::RTVoice::Tool::SpeechText, 191
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 200
 - Crosstales::RTVoice::UDEA2::UDEAVoice↔
Wrapper, 206
 - HutongGames::PlayMaker::Actions::SpeakBase, 163
- ReadOnlyTextField
 - Crosstales::Common::EditorUtil::BaseEditor↔
Helper, 50
- RefreshAssetDatabase
 - Crosstales::Common::EditorUtil::BaseEditor↔
Helper, 51
- RefreshOnVoicesReady
 - Crosstales::RTVoice::Tool::ChangeGender, 70
- Reload
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 199
- ReloadProvider
 - Crosstales::RTVoice::Speaker, 171
- RemoteCertificateValidationCallback
 - Crosstales::Common::Util::BaseHelper, 57
- Reset
 - Crosstales::RTVoice::EditorUtil::EditorConfig, 90
 - Crosstales::RTVoice::Speaker, 171
 - Crosstales::RTVoice::Util::Config, 73
- ResetAllAudioSources
 - Crosstales::UI::Util::AudioSourceController, 34
- ResetAudioFilters
 - Crosstales::UI::Util::AudioFilterController, 32
- ResetAudioSourcesOnStart
 - Crosstales::UI::Util::AudioSourceController, 34
- RestartUnity
 - Crosstales::Common::EditorUtil::BaseEditor↔
Helper, 51
- SHOW_BWF_BANNER
 - Crosstales::Common::Util::BaseConstants, 42
- SHOW_DJ_BANNER
 - Crosstales::Common::Util::BaseConstants, 42
- SHOW_FB_BANNER
 - Crosstales::Common::Util::BaseConstants, 42
- SHOW_OC_BANNER
 - Crosstales::Common::Util::BaseConstants, 43
- SHOW_RADIO_BANNER
 - Crosstales::Common::Util::BaseConstants, 43
- SHOW_RTV_BANNER
 - Crosstales::Common::Util::BaseConstants, 43
- SHOW_TB_BANNER
 - Crosstales::Common::Util::BaseConstants, 43
- SHOW_TPB_BANNER
 - Crosstales::Common::Util::BaseConstants, 43
- SHOW_TPS_BANNER
 - Crosstales::Common::Util::BaseConstants, 43

- Crosstales::Common::Util::BaseConstants, 43
- SHOW_TR_BANNER
 - Crosstales::Common::Util::BaseConstants, 43
- SPEAK_CALL_SPEED
 - Crosstales::RTVoice::Util::Constants, 82
- SampleRate
 - Crosstales::Common::Model::Enum, 14
 - Crosstales::RTVoice::Klattersynth::VoiceProvider↔
Klattersynth, 231
- Samples
 - Crosstales::Common::Util::FFTAnalyzer, 104
- SaturationRange
 - Crosstales::Common::Util::RandomColor, 139
- Save
 - Crosstales::Common::Util::CTPlayerPrefs, 86
 - Crosstales::RTVoice::EditorUtil::EditorConfig, 90
 - Crosstales::RTVoice::Util::Config, 73
- Scale
 - Crosstales::Common::Util::TakeScreenshot, 196
- ScaleMax
 - Crosstales::Common::Util::RandomScaler, 141
- ScaleMin
 - Crosstales::Common::Util::RandomScaler, 141
- SeparatorUI
 - Crosstales::Common::EditorUtil::BaseEditor↔
Helper, 51
- Sequences
 - Crosstales::RTVoice::Tool::Sequencer, 150
- SerializeToByteArray< T >
 - Crosstales::Common::Util::SerializeDeSerialize,
152
- SerializeToFile< T >
 - Crosstales::Common::Util::SerializeDeSerialize,
153
 - Crosstales::Common::Util::XmlHelper, 254
- SerializeToString< T >
 - Crosstales::Common::Util::XmlHelper, 254
- SetBool
 - Crosstales::Common::Util::CTPlayerPrefs, 86
- SetDate
 - Crosstales::Common::Util::CTPlayerPrefs, 86
- SetFloat
 - Crosstales::Common::Util::CTPlayerPrefs, 86
- SetInt
 - Crosstales::Common::Util::CTPlayerPrefs, 86
- SetState
 - Crosstales::RTVoice::LiveSpeaker, 122
 - Crosstales::RTVoice::Provider::VoiceProviderIOS,
228
- SetString
 - Crosstales::Common::Util::CTPlayerPrefs, 87
- SetVoices
 - Crosstales::RTVoice::LiveSpeaker, 122
 - Crosstales::RTVoice::Provider::VoiceProviderIOS,
228
- setVoices
 - RTVoiceIOSBridge, 143
- Silence
 - Crosstales::RTVoice::LiveSpeaker, 122
 - Crosstales::RTVoice::Provider::BaseCustom↔
VoiceProvider, 46
 - Crosstales::RTVoice::Provider::BaseVoice↔
Provider, 66
 - Crosstales::RTVoice::Provider::IVoiceProvider, 118
 - Crosstales::RTVoice::Provider::VoiceProvider↔
Android, 220
 - Crosstales::RTVoice::Provider::VoiceProviderIOS,
228
 - Crosstales::RTVoice::Provider::VoiceProviderMary,
238
 - Crosstales::RTVoice::Provider::VoiceProviderW↔
SA, 244
 - Crosstales::RTVoice::Speaker, 171
 - Crosstales::RTVoice::Tool::Paralanguage, 131
 - Crosstales::RTVoice::Tool::SpeechText, 190
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 199
- SilenceOnDisable
 - Crosstales::RTVoice::Speaker, 176
- SilenceOnFocustLost
 - Crosstales::RTVoice::Speaker, 176
- SilenceSource
 - Crosstales::RTVoice::Tool::Loudspeaker, 125
- Source
 - Crosstales::RTVoice::Model::Sequence, 147
 - Crosstales::RTVoice::Model::Wrapper, 251
 - Crosstales::RTVoice::Tool::Loudspeaker, 125
 - Crosstales::RTVoice::Tool::SpeechText, 191
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 200
 - Crosstales::RTVoice::UDEA2::UDEAVoice↔
Wrapper, 206
- Speak
 - Crosstales::RTVoice::AWSPolly::VoiceProviderA↔
WS, 222
 - Crosstales::RTVoice::Klattersynth::VoiceProvider↔
Klattersynth, 230
 - Crosstales::RTVoice::LiveSpeaker, 123
 - Crosstales::RTVoice::Provider::BaseCustom↔
VoiceProvider, 46
 - Crosstales::RTVoice::Provider::BaseVoice↔
Provider, 66
 - Crosstales::RTVoice::Provider::IVoiceProvider, 118
 - Crosstales::RTVoice::Provider::VoiceProvider↔
Android, 220
 - Crosstales::RTVoice::Provider::VoiceProviderIOS,
228
 - Crosstales::RTVoice::Provider::VoiceProvider↔
Linux, 234
 - Crosstales::RTVoice::Provider::VoiceProvider↔
MacOS, 236
 - Crosstales::RTVoice::Provider::VoiceProviderMary,
238
 - Crosstales::RTVoice::Provider::VoiceProviderW↔
SA, 244
 - Crosstales::RTVoice::Provider::VoiceProvider↔
Windows, 240
 - Crosstales::RTVoice::Provider::VoiceProvider↔

- WindowsLegacy, 242
- Crosstales::RTVoice::Speaker, 171, 172
- Crosstales::RTVoice::Tool::Paralanguage, 131
- Crosstales::RTVoice::Tool::SpeechText, 190
- Crosstales::RTVoice::Tool::TextFileSpeaker, 199
- Crosstales::RTVoice::VoiceProviderExample, 226
- speak:text:rate:pitch:volume:
 - RTVoiceIOSBridge, 143
- SpeakAll
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 199
- SpeakImmediately
 - Crosstales::RTVoice::Model::Wrapper, 251
- SpeakMarkedWordsWithUID
 - Crosstales::RTVoice::Speaker, 172
- SpeakMode
 - Crosstales::RTVoice::Model::Enum, 21
- SpeakNative
 - Crosstales::RTVoice::AWSPolly::VoiceProviderA↔WS, 222
 - Crosstales::RTVoice::Klattersynth::VoiceProvider↔Klattersynth, 231
 - Crosstales::RTVoice::LiveSpeaker, 123, 124
 - Crosstales::RTVoice::Provider::BaseCustom↔VoiceProvider, 46
 - Crosstales::RTVoice::Provider::BaseVoice↔Provider, 67
 - Crosstales::RTVoice::Provider::IVoiceProvider, 118
 - Crosstales::RTVoice::Provider::VoiceProvider↔Android, 220
 - Crosstales::RTVoice::Provider::VoiceProviderIOS, 229
 - Crosstales::RTVoice::Provider::VoiceProvider↔Linux, 234
 - Crosstales::RTVoice::Provider::VoiceProvider↔MacOS, 236
 - Crosstales::RTVoice::Provider::VoiceProviderMary, 238
 - Crosstales::RTVoice::Provider::VoiceProviderW↔SA, 245
 - Crosstales::RTVoice::Provider::VoiceProvider↔Windows, 240
 - Crosstales::RTVoice::Provider::VoiceProvider↔WindowsLegacy, 242
 - Crosstales::RTVoice::Speaker, 172, 173
 - Crosstales::RTVoice::VoiceProviderExample, 226
- SpeakNativeWithUID
 - Crosstales::RTVoice::Speaker, 173
- SpeakRandom
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 200
- SpeakText
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 199
- SpeakWithUID
 - Crosstales::RTVoice::Speaker, 173
- SpeechCount
 - Crosstales::RTVoice::Speaker, 182
- Speeches
 - Crosstales::RTVoice::Klattersynth::VoiceProvider↔Klattersynth, 231
- Speed
 - Crosstales::UI::WindowManager, 248
- SpeedMax
 - Crosstales::Common::Util::RandomRotator, 140
- SpeedMin
 - Crosstales::Common::Util::RandomRotator, 140
- SplitStringToLines
 - Crosstales::Common::Util::BaseHelper, 57
- Start
 - Crosstales::UI::UIDrag, 207
 - Crosstales::UI::UIFocus, 208
 - Crosstales::UI::UIWindowManager, 211
- StereoPan
 - Crosstales::UI::Util::AudioSourceController, 34
- stop
 - RTVoiceIOSBridge, 143
- StopAll
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 200
- StopAllSequences
 - Crosstales::RTVoice::Tool::Sequencer, 149
- StringToGender
 - Crosstales::RTVoice::Util::Helper, 114
- Survivors
 - Crosstales::Common::Util::SurviveSceneSwitch, 195
- SwitchPanel
 - Crosstales::UI::WindowManager, 248
- Synchronized
 - Crosstales::RTVoice::Tool::Loudspeaker, 125
- TRACER
 - Crosstales::RTVoice::EditorUtil::EditorConfig, 90
- TTS_LINUX_DATA
 - Crosstales::RTVoice::Util::Config, 74
- TTS_LINUX
 - Crosstales::RTVoice::Util::Config, 73
- TTS_MACOS
 - Crosstales::RTVoice::Util::Config, 74
- TTS_WINDOWS_BUILD
 - Crosstales::RTVoice::Util::Config, 74
- TTS_WINDOWS_EDITOR_x86
 - Crosstales::RTVoice::Util::Config, 74
- TTS_WINDOWS_EDITOR
 - Crosstales::RTVoice::Util::Config, 74
- TTS_WINDOWS_SUBPATH
 - Crosstales::RTVoice::Util::Constants, 83
- TTS_WINDOWS_x86_SUBPATH
 - Crosstales::RTVoice::Util::Constants, 83
- Text
 - Crosstales::RTVoice::Model::Sequence, 147
 - Crosstales::RTVoice::Model::Wrapper, 252
 - Crosstales::RTVoice::Tool::Paralanguage, 131
 - Crosstales::RTVoice::Tool::SpeechText, 191
 - HutongGames::PlayMaker::Actions::Speak, 161
 - HutongGames::PlayMaker::Actions::SpeakUI, 185
- TextFiles
 - Crosstales::RTVoice::Tool::AudioFileGenerator, 29
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 200
- Timeout

- Crosstales::Common::Util::CTWebClient, 88
- ToAudioClip
 - Crosstales::RTVoice::Util::WavMaster, 246
- UDEAVoiceName
 - Crosstales::RTVoice::UDEA2::UDEAVoice↔Wrapper, 206
- UPDATE_CHECK
 - Crosstales::RTVoice::EditorUtil::EditorConfig, 90
- Uid
 - Crosstales::RTVoice::Model::Wrapper, 251
- UnPause
 - Crosstales::RTVoice::Speaker, 173
- Uniform
 - Crosstales::Common::Util::RandomScaler, 142
- Update
 - Crosstales::Common::Util::TakeScreenshot, 196
 - Crosstales::UI::WindowManager, 248
- UpdateStatus
 - Crosstales::RTVoice::EditorTask, 19
- UseInterval
 - Crosstales::Common::Util::RandomColor, 139
 - Crosstales::Common::Util::RandomRotator, 140
 - Crosstales::Common::Util::RandomScaler, 142
- ValidURLFromFilePath
 - Crosstales::Common::Util::BaseHelper, 58
- ValidateFile
 - Crosstales::Common::Util::BaseHelper, 58
- ValidatePath
 - Crosstales::Common::Util::BaseHelper, 58
- ValueRange
 - Crosstales::Common::Util::RandomColor, 139
- Vendor
 - Crosstales::RTVoice::Model::Voice, 214
- VisualPrefab
 - Crosstales::Common::Util::SpectrumVisualizer, 187
- Voice
 - Crosstales::RTVoice::Model::Voice, 213
 - Crosstales::RTVoice::Model::VoiceAlias, 216
 - Crosstales::RTVoice::Model::Wrapper, 251
- VoiceForCulture
 - Crosstales::RTVoice::Speaker, 174
- VoiceForGender
 - Crosstales::RTVoice::Speaker, 174
- VoiceForName
 - Crosstales::RTVoice::Speaker, 174
- VoiceName
 - Crosstales::RTVoice::Model::VoiceAlias, 216
- VoiceNameAndroid
 - Crosstales::RTVoice::Model::VoiceAlias, 215
- VoiceNameCustom
 - Crosstales::RTVoice::Model::VoiceAlias, 215
- VoiceNameIOS
 - Crosstales::RTVoice::Model::VoiceAlias, 216
- VoiceNameLinux
 - Crosstales::RTVoice::Model::VoiceAlias, 216
- VoiceNameMac
 - Crosstales::RTVoice::Model::VoiceAlias, 216
- VoiceNameMaryTTS
 - Crosstales::RTVoice::Model::VoiceAlias, 216
- VoiceNameWSA
 - Crosstales::RTVoice::Model::VoiceAlias, 216
- VoiceNameWindows
 - Crosstales::RTVoice::Model::VoiceAlias, 216
- VoiceNames
 - Crosstales::RTVoice::Tool::VoiceInitializer, 218
- VoiceProviderAndroid
 - Crosstales::RTVoice::Provider::VoiceProvider↔Android, 219
- VoiceProviderIOS
 - Crosstales::RTVoice::Provider::VoiceProviderIOS, 227
- VoiceProviderLinux
 - Crosstales::RTVoice::Provider::VoiceProvider↔Linux, 233
- VoiceProviderMacOS
 - Crosstales::RTVoice::Provider::VoiceProvider↔MacOS, 235
- VoiceProviderMary
 - Crosstales::RTVoice::Provider::VoiceProviderMary, 237
- VoiceProviderWSA
 - Crosstales::RTVoice::Provider::VoiceProviderW↔SA, 244
- VoiceProviderWindows
 - Crosstales::RTVoice::Provider::VoiceProvider↔Windows, 240
- VoiceProviderWindowsLegacy
 - Crosstales::RTVoice::Provider::VoiceProvider↔WindowsLegacy, 242
- Voices
 - Crosstales::RTVoice::Model::Sequence, 147
 - Crosstales::RTVoice::Provider::IVoiceProvider, 121
 - Crosstales::RTVoice::Speaker, 182
 - Crosstales::RTVoice::Tool::Paralanguage, 131
 - Crosstales::RTVoice::Tool::SpeechText, 191
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 201
 - Crosstales::RTVoice::UDEA2::UDEAConnector, 204
 - Crosstales::RTVoice::UDEA2::UDEAVoice↔Wrapper, 206
- VoicesForCulture
 - Crosstales::RTVoice::Speaker, 175
- VoicesForGender
 - Crosstales::RTVoice::Speaker, 175
- Volume
 - Crosstales::RTVoice::Model::Sequence, 147
 - Crosstales::RTVoice::Model::Wrapper, 252
 - Crosstales::RTVoice::Tool::Paralanguage, 132
 - Crosstales::RTVoice::Tool::SpeechText, 191
 - Crosstales::RTVoice::Tool::TextFileSpeaker, 201
 - Crosstales::RTVoice::UDEA2::UDEAVoice↔Wrapper, 206
 - Crosstales::UI::Util::AudioSourceController, 34
 - HutongGames::PlayMaker::Actions::SpeakBase,

163

WSAVoiceNameToGender

Crosstales::RTVoice::Util::Helper, 115

Width

Crosstales::Common::Util::SpectrumVisualizer,
187

Windows

Crosstales::UI::UIWindowManager, 212

WindowsLegacy

Crosstales::RTVoice::Speaker, 177

WordSpoken

Crosstales::RTVoice::LiveSpeaker, 124

Crosstales::RTVoice::Provider::VoiceProviderIOS,
229

Wrapper

Crosstales::RTVoice::Model::Wrapper, 250