

- 1-Log files are essential in daily operations, such as monitoring system activity, troubleshooting issues, enhancing security and performance, and ensuring system compliance.
- 2- Most log files are stored in the `/var/log` directory.
- 3- These files include information about authentication and security events, such as login attempts, authentication logs, and security alerts.
- 4- The `lastlog` command reads the contents of `/var/log/lastlog` and presents information in a human-readable format.
- 5- Familiarity with `rsyslogd` is crucial as it provides features to manage log data effectively.
- 6- `rsyslogd` centralizes logging on many Linux systems, with capabilities to manage and process large log datasets. Configuration is done through `/etc/rsyslog.conf` and `/etc/rsyslog.d/`.
- 7- Remote logging with secure channels, like TLS, enhances communication with remote servers, improves security, prevents tampering, and facilitates incident detection.
- 8- Syslog protocol uses facilities and levels to classify and prioritize log data, indicating the log's source and importance.
- 9- The logger "test message" command allows users to log custom messages, which can be integrated into automated processes.
- 10- The `grep` command is used to filter and search logs efficiently.
- 11- Log rotation utilities in Linux manage log files by rotating, compressing, archiving, or deleting old logs, freeing up disk space.
- 12- Policies can define log rotation frequency (e.g., daily or hourly), compression methods, and size limits.
- 13- `lastlog -u <username>` command provides login information for a specific user.
- 14- Logging systems centralize and streamline log data management, offering unified access and searchability.
- 15- `journalctl -k` command displays kernel logs.
- 16- Missing `systemd` or its packages may require reading logs directly with `less /var/log/...`
- 17- `journalctl -p err` or `journalctl -p 3` to view logs by priority.
- 18- Tagging logs enhances categorization, simplifying search and monitoring.

- 19- journalctl provides insights into system boot processes, including errors or warnings.
- 20- journalctl -u cron to view logs related to the cron service.
- 21 systemd manages and initializes system components during startup and runtime.
- 22- Commands like systemctl start <service> are used to start specific services.
- 23- systemctl status <service.name>.service to check a service's status.
- 24- Systemd configuration files manage components like services, devices, and timers.
- 25- Reload service configurations without stopping them using systemctl reload <service>.
- 26- The difference between restart and try-restart is that restart starts a service if it is stopped, while try-restart does nothing if the service is stopped.
- 27- SysVinit was the predecessor of systemd.
- 28- Systemd offers advantages like unified tools (systemctl), better dependency management, faster boot times, and improved logging for troubleshooting.
- 29- Use systemctl is-enabled <service_name.service> to check if a service starts automatically on boot.
- 30- Commands to enable or disable services define their behavior during system startup.
- 31- Systemd maintains backward compatibility with older systems and tools.
- 32- systemctl stop <service_name>.service command stops a service.
- 33- Use systemctl list-units to list active processes managed by systemd.
- 34- View available targets with systemctl list-units --type=target. Use systemctl isolate <target> for temporary changes or systemctl set-default <target> for permanent ones.
- 35- systemctl halt stops processes and unmounts filesystems, leaving the system powered on. systemctl poweroff shuts down the computer entirely.
- 36- Traditional SysVinit runlevels, like single-user or multi-user modes, are replaced by systemd targets.
- 37- Use systemctl list-units --type=target to list loaded targets.
- 38- Runlevels 2, 3, and 4 map to the multi-user target in systemd.
- 39- Use systemctl poweroff to power off the system.
- 40- systemctl is-active <service_name> command checks if a service is currently running.

Khalil altowhi / logger och system

40- Using the command `< systemctl is-active name.service >`