OrbitX

PHOEBE BULKHEAD IP65 INTEGRATED SURFACE MOUNT LED LIGHT

OrbitX Direct Drive Technology Onboard

Available in white and black IP65 rated



Dimensions



height 86mm

ø 280mm

Configurations





Guarantee

Operational Guarantee (365d x 24h) 8 years Light Output Guarantee (365d x 24h) 5 years

Lifetime

Nominal Lifetime (L70) IES LM-80, TM-21 70 000 hours

Photometric Data

Luminous Efficacy 113 lm/W

Correlated Colour Temperature (CCT) 5000K (options available)

Colour Rendering Index (CRI)
Gamut Area Index (GAI)

Light Quality

Type A compliant (Lighting Research Centre, New York)

Beam Angle

160°

83

96

Electrical Data

Power See Configurations on previous page

Power Factor >0.98

Operating Voltage 220-240V AC

Minimum Sustained Voltage No minimum limit, operational from 150V

Maximum Sustained Voltage 250V for 2 minutes

On/Off Switching Unlimited
Delay to Full Brightness Immediate

Temperature

T Ambient (max) +30°C
T Ambient (min) -40°C

Safety

Risk of Breakage Low, polycarbonate housing extruded to 1mm (no glass)

Electrical IEC60598-1, IEC60598-2-5 compliant

Surge Protection 1.5kV

Fire Rating UL-94 V2 compliant

IP Rating IP65

Interference Compliance

Wifi, Barcode Scanner, Radio Frequency Interference No interference, IEC 61547, SANS 215 (CISPR15) compliant

Total Harmonic Distortion IEC 61000-3-2 Class D Compliant

Additional

Optional Battery Backup

Optional Radar Motion Sensor

Optional Day/Night Sensor


Battery output: 1000lm for 4h, 6h charge time, 1y guarantee.

Programmable sensitivity (distance). Programmable time on.


Light switches on during dusk and switches off at dawn

Specification tolerance ±10%

Rate of Reduction in Light Output




Light Survival Rate



1.00 0.75 0.50 0.25 0.00 360 nm 485 nm 610 nm 735 nm Wavelength

Type A Lighting*



 $^{\star}\mbox{Type}$ A Lighting as defined by the Lighting Research Centre, New York

Model Code	Colour of Housing	Power Rating	Units per Box	Box Dimensions (I x w x h) mm	Weight (Kg)	IES Files
OXPH280155B	Black	15W	1	290 x 290 x 90	1.4	Click to download
OXPH280155W	White	15W	1	290 x 290 x 90	1.4	Click to download