

HF 360

COM1 - in-ceiling installation
EAN 4007841 079512
Article number 079512



high frequency
sensor 360°



max. Ø 12 m

2000 W

max. 2000 W



IP20



ideal 2,5 - 3,5 m



indoor sensor

iQ

iQ-mode

Teach

Teach mode

5 years

manufacturer's
warranty steinel.de/
garantie



CE

Function description

Doesn't miss a thing. HF-presence detector Presence Control PRO HF 360 COM1 for indoors, ideal for WCs with toilet cubicles, changing rooms, stairwells, multi-storey car parks, kitchens, installation height up to 3.5 m, for switching light 'ON' and 'OFF', 1 – 12 m reach, reach is electronically adjustable and can be limited in two directions, detection regardless of temperature, HF-sensor technology also detects movement through glass, wood and stud walls.

Technical specifications

Dimensions (L x W x H)	94 x 120 x 120 mm
Manufacturer's Warranty	5 years
Settings via	Remote control, DIP switches, Potentiometers, Smart Remote
With remote control	No
Version	COM1 - in-ceiling installation
PU1, EAN	4007841079512
Type	Presence detector
Application, place	Indoors
Application, room	function room / ancillary room, kitchenette, stairwell, WC / washroom, Indoors
Colour	white
Colour, RAL	9010
Includes corner wall mount	No
Installation site	ceiling
Package content	1
Installation	In-ceiling installation, Ceiling

Optimum mounting height	2,8 m
HF-system	5,8 GHz
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	140 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	Ø 12 m (113 m²)
Reach, tangential	Ø 12 m (113 m²)
Transmitter power	< 1 mW
Functions	Normal / test mode, Semi-/fully automatic, Pushbutton / switch mode, Manual ON / ON-OFF
Twilight setting	10 – 1000 lx

HF 360

COM1 - in-ceiling installation
EAN 4007841 079512
Article number 079512



Technical specifications

IP-rating	IP20
Ambient temperature	from -25 up to 55 °C
Material	Plastic
Mains power supply	230 V / 50 – 60 Hz
Technology, sensors	High frequency, Mixed light metering
Voltage range (min)	230 V
Voltage range (max)	230 V
Mounting height	2,50 – 3,50 m
Mounting height max.	3,50 m

Time setting	30 s – 30 Min.
Basic light level function	No
Main light adjustable	No
Twilight setting TEACH	Yes
Constant-lighting control	No
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
Interconnection via	Cable
Product category	Presence detector

Accessories

EAN 4007841 003036	Control PRO guard cage
EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 559410	Service remote control RC8


HF 360

COM1 - in-ceiling installation

EAN 4007841 079512

Article number 079512


Detection Zone




Possible mounting height: 2,50 m – 3,50 m

Orange: radial and tangential


Dimension Drawing 1



Dimension Drawing 2




Master circuit diagram



HF 360

COM1 - in-ceiling installation
EAN 4007841 079512
Article number 079512

Master/master interconnection circuit diagram



Master/slave interconnection circuit diagram

