

LINEAR LIGHTING

Puck Profile 40x43

32-64
POWER**4-8k lm**
LUMENS**—**
RATING

OVERVIEW

40x43mm integrated seamless linear LED system with a thin end-cap line under 3mm, direct-drive operation (no external driver) and a seamless look when mounted end-to-end. Made from polycarbonate and manufactured locally.

APPLICATIONS

COMMERCIAL

RESIDENTIAL

RETAIL

PHYSICAL

Dimensions (mm)	40mm x 43mm
Weight	Length Dependent
Housing	Polycarbonate
Mounting	Surface / Suspended / Recessed

COMPLIANCE

Certifications	CE / RoHS / IEC 60598
Class Rating	Class II
Warranty	6 Years

DIMENSION DRAWING



PRODUCT INFORMATION

Lumen Output	4000 / 8000 lm
Lumen Efficacy	110 lm/W
Colour Temperature	5000K (options available)
CRI	83
Beam Angle	160°
Operating Temp	+30 ~ -40 °C
Lifespan	60 000 hours
Luminaire Colour	White

ELECTRICAL

Wattage	32W (1200mm) / 64W (2400mm)
Input Voltage	220-240V AC
Power Factor	>0.98
Surge Protection	1.5kV
Dimmable	Direct drive - no driver required
Flicker	Flicker-free

	LED Lumens (lm)	Luminaire Lumens (lm)	Length (mm)
32W	4000	4000	1200
64W	8000	8000	2400

- E & O.E (Errors And Omissions Excepted)
- Due to the rapid development in LED technology the performance values, power consumption and lumen output levels stated above are subject to change without prior notice.
- Due to the interoperability of LED modules and drivers, up to a 10% deviation in these values is possible.
- Nominal flux values are stated at 25° C, based on LED manufacturer's data.
- Installation environmental conditions may impact the performance and efficiency of the luminaire.