

TRACKSPOTS AND TRACKS

TRACK SPOT

35W
POWER

3500lm
LUMENS

IP20
RATING


OVERVIEW

Dynamic Dual Heat Sink ensuring longevity and the reduction in lumen Depreciation. Elegant, sophisticated look bringing style to your application. Deep reflector (36°) helps in the reduction of glare whilst not impacting lumen output. Matt black or chique white trendy powder coated finish. 3kV built in surge protection designed to withstand the toughest Environments.

APPLICATIONS

COMMERCIAL

RESIDENTIAL

RETAIL


PHYSICAL

Dimensions (mm)	Φ90 x 130mm
Weight	460 g
Housing	Aluminium
Mounting	3 Wire Track

COMPLIANCE

Certifications	CE / RoHS / IEC 60598
Class Rating	Class II
Warranty	5 Years

DIMENSION DRAWING



PRODUCT INFORMATION

Lumen Output	3500 lm
Lumen Efficacy	100 lm/W
Colour Temperature	3000K / 4000K / 6000K
CRI	>83
Beam Angle	36 °
UGR	24
IP Rating	IP 20
Operating Temp	-15 ~ 45 °C
Lifespan	L80B10 @ 50 000 hrs

ELECTRICAL

Wattage	35 W
Input Voltage	200-265V AC
Frequency	50-60 Hz
Power Factor	>0.9
Surge Protection	3kV
Dimmable	Dimmable with optional driver
Flicker	Flicker-free

- E & O.E (Errors And Omissions Excepted)
- Due to the rapid development in LED technology the performance values, power consumption and lumen output levels stated above are subject to change without prior notice.
- Due to the interoperability of LED modules and drivers, up to a 10% deviation in these values is possible.
- Nominal flux values are stated at 25° C, based on LED manufacturer's data.
- Installation environmental conditions may impact the performance and efficiency of the luminaire.