

DOWNLIGHTS

SURFACE DOWNLIGHT

9_W
POWER**1250_{lm}**
LUMENS**IP20**
RATING

OVERVIEW

This surface mount Downlight is a compact, COB LED luminaire engineered for commercial and retail environments where clean aesthetics and reliable performance are essential. Offering 8–11 W power consumption with CRI >80, it delivers consistent, anti-glare illumination across offices, corridors, and reception areas. Dimmable and emergency-ready options make it a versatile, energy-efficient solution for any professional interior.

APPLICATIONS

COMMERCIAL

RESIDENTIAL

RETAIL


PHYSICAL

Dimensions (mm)	Φ118mm x 120mm
Weight	540 g
Housing	Die-Case Aluminium
Mounting	Surface

COMPLIANCE

Certifications	CE / RoHS / IEC 60598
Class Rating	Class II
Warranty	5 Years

DIMENSION DRAWING



PRODUCT INFORMATION

Lumen Output	1250 lm
Lumen Efficacy	125 lm/W
Colour Temperature	3000K / 3500K / 4000K / 5000K
CRI	>80
Beam Angle	45 °
UGR	<19
IP Rating	IP 20
Operating Temp	-15 ~ 35 °C
Lifespan	L80B10 @ 50 000 hrs
Luminaire Colour	White / Black

ELECTRICAL

Wattage	9 W
Input Voltage	220-240V AC
Frequency	50-60 Hz
Power Factor	>0.9
Surge Protection	3kV
Dimmable	Dimmable with optional driver
Flicker	Flicker-free

- E & O.E (Errors And Omissions Excepted)
- Due to the rapid development in LED technology the performance values, power consumption and lumen output levels stated above are subject to change without prior notice.
- Due to the interoperability of LED modules and drivers, up to a 10% deviation in these values is possible.
- Nominal flux values are stated at 25° C, based on LED manufacturer's data.
- Installation environmental conditions may impact the performance and efficiency of the luminaire.