

BULKHEADS

ALU BULKHEAD

12-18_W
POWER**1560-2340_{lm}**
LUMENS**IP65**
RATING

OVERVIEW

This bulkhead has a die-cast aluminium body with a durable polycarbonate diffuser. Its simple, modern design combined with reliable LED performance makes it ideal for any application.

APPLICATIONS

COMMERCIAL

RESIDENTIAL

INDUSTRIAL


PHYSICAL

Dimensions (mm)	Dia 280mm x 105mm
Weight	1450 g
Housing	Die-Case Aluminium
Mounting	Surface

COMPLIANCE

Certifications	CE / RoHS / IEC 60598
Class Rating	Class II
Warranty	5 Years

DIMENSION DRAWING



PRODUCT INFORMATION

Lumen Output	See table below
Lumen Efficacy	120 lm/W
Colour Temperature	4000K
CRI	>80
Beam Angle	100 °
UGR	<20
IP Rating	IP 40
Operating Temp	-20 ~ 35 °C
Lifespan	L70B10 @ 50 000 hrs
Luminaire Colour	White

ELECTRICAL

Wattage	See table below
Input Voltage	220-240V AC
Frequency	50-60 Hz
Power Factor	>0.9
Surge Protection	1.5kV
Dimmable	Dimmable with optional driver
Flicker	Flicker-free

	Lumens (lm)
12W	1560
16W	2080
18W	2340