

DOWNLIGHTS

LEAN 153

17-25
POWER**2000-3450lm**
LUMENS**IP20**
RATING

OVERVIEW

The Lean 153 is a fully adjustable recessed downlight designed for a 153mm cutout. Combining flexibility with a sleek, modern form, it allows precise directional lighting while maintaining excellent visual comfort.

APPLICATIONS

COMMERCIAL
OFFICE

RETAIL

DATA CENTRE

PHYSICAL

Dimensions (mm)	Ø164 x 86mm (Ø153mm cutout)
Weight	—
Housing	Powder-coated die-cast aluminium
Mounting	Recessed, adjustable tilt/rotate

COMPLIANCE

Certifications	—
Class Rating	—
Warranty	—

PRODUCT INFORMATION

Lumen Output	See table below
Lumen Efficacy	Up to 138 lm/W
Colour Temperature	2700-5000K (5 options)
CRI	80+/90+/97+
Beam Angle	15°/20°/30°/50°
UGR	—
IP Rating	IP20
Operating Temp	-20°C to 35°C
Lifespan	L80B10 @ 50 000 hrs
Luminaire Colour	White/Black/Silver

ELECTRICAL

Wattage	See table below
Input Voltage	220-240V AC
Frequency	50-60Hz
Power Factor	—
Surge Protection	—
Dimmable	1-10V/DALI/BLU (on request)
Flicker	—

Power	Lumens (lm)
17W	2425
25W	3350