

VAPOUR PROOF

NEPTUNE

9-96
POWER**1k-12k lm**
LUMENS**IP65**
RATING

OVERVIEW

Integrated IP65 linear LED light with OrbitX Direct Drive Technology onboard.
Dust proof, moisture proof, vapour proof.

APPLICATIONS

INDUSTRIAL

COMMERCIAL

WET AREAS

PHYSICAL

Dimensions (mm)	92mm x 92mm cross-section (600-2400mm lengths)
Weight	—
Housing	Polycarbonate
Mounting	—

COMPLIANCE

Certifications	IEC60598-1/-2-5, UL-94 V0, SABS
Class Rating	—
Warranty	8 Yr Operational / 5 Yr Light Output

DIMENSION DRAWING



PRODUCT INFORMATION

Lumen Output	See table below
Lumen Efficacy	135 lm/W
Colour Temperature	5000K
CRI	83
Beam Angle	120°
UGR	—
IP Rating	IP65
Operating Temp	-40°C to +35°C
Lifespan	L70 @ 70 000 hrs
Luminaire Colour	—

ELECTRICAL

Wattage	See table below
Input Voltage	220-240V AC
Frequency	—
Power Factor	>0.98
Surge Protection	1.5kV
Dimmable	—
Flicker	80% flicker-free

Power	Lumens (lm)
32W	4000
64W	8000
96W	12000