

LINEAR LIGHTING

Puck Profile 70x36

52-104
POWER

6-12k lm
LUMENS

—
RATING



OVERVIEW

70x36mm integrated seamless linear LED system with a thin end-cap line under 3mm, direct-drive operation (no external driver) and a seamless look when mounted end-to-end. Made from polycarbonate and manufactured locally.

APPLICATIONS

- COMMERCIAL
- RESIDENTIAL
- RETAIL

PHYSICAL

Dimensions (mm)	70mm x 36mm
Weight	Length Dependent
Housing	Polycarbonate
Mounting	Surface / Suspended / Recessed

COMPLIANCE

Certifications	CE / RoHS / IEC 60598
Class Rating	Class II
Warranty	6 Years

DIMENSION DRAWING



PRODUCT INFORMATION

Lumen Output	6000 / 12000 lm
Lumen Efficacy	110 lm/W
Colour Temperature	5000K (options available)
CRI	83
Beam Angle	160°
Operating Temp	+30 ~ -40 °C
Lifespan	60 000 hours
Luminaire Colour	White

ELECTRICAL

Wattage	52W (1200mm) / 104W (2400mm)
Input Voltage	220-240V AC
Power Factor	>0.98
Surge Protection	1.5kV
Dimmable	Direct drive - no driver required
Flicker	Flicker-free

	LED Lumens (lm)	Luminaire Lumens (lm)	Length (mm)
52W	6000	6000	1200
104W	12000	12000	2400

(All Omissions Excepted)
Development in LED technology the performance values, power consumption and lumen output levels stated above are subject to change without prior notice.
• Due to the interoperability of LED modules and drivers, up to a 10% deviation in these values is possible.
• Nominal flux values are stated at 25° C, based on LED manufacturer's data.
• Installation environmental conditions may impact the performance and efficiency of the luminaire.