

TRACK SPOTS AND TRACKS

TRACK SPOT

35W 3-wire track spot · dual heat sink · 36° deep reflector

35 W

POWER

3500 lm

LUMENS

IP20

IP RATING



OVERVIEW

Dynamic Dual Heat Sink ensuring longevity and the reduction in lumen depreciation. Elegant, sophisticated look bringing style to your application. Deep reflector (36°) helps in the reduction of glare whilst not impacting lumen output. Matt black or chic white trendy powder coated finish. 3kV built in surge protection designed to withstand the toughest environments.

APPLICATIONS

COMMERCIAL

RESIDENTIAL

RETAIL

PHYSICAL

Dimensions (mm) **Φ90 × 130mm**Weight **460 g**Housing **Aluminium**Mounting **3 Wire Track**

COMPLIANCE

Certifications **CE / RoHS / IEC 60598**Class Rating **Class II**Warranty **5 Years**

PRODUCT INFORMATION

Lumen Output **3500 lm**Lumen Efficacy **100 lm/W**Colour Temperature **3000K / 4000K / 6000K**CRI **>83**Beam Angle **36°**UGR **24**IP Rating **IP20**Operating Temp **-15 ~ 45 °C**Lifespan **L80B10 @ 50 000 hrs**

ELECTRICAL

Wattage **35 W**Input Voltage **200-265V AC**Frequency **50-60 Hz**Power Factor **>0.9**Surge Protection **3kV**Dimmable **Dimmable with optional driver**Flicker **Flicker-free**

DIMENSION DRAWING



- E & O.E (Errors And Omissions Excepted).
- Due to the rapid development in LED technology the performance values, power consumption and lumen output levels stated above are subject to change without prior notice.
- Due to the interoperability of LED modules and drivers, up to a 10% deviation in these values is possible.
- Nominal flux values are stated at 25° C, based on LED manufacturer's data.
- Installation environmental conditions may impact the performance and efficiency of the luminaire.