

LINEAR LIGHTING

LF55x80

5-26W/

m

600-4000lm/

m

IP20

RATING



OVERVIEW

The LF55x80 is a high-output 55x80mm Light Frame linear for controlled illumination. With surface, suspended and P2000 mounting options, its ideal for warehouses, racking and production lines for higher general lighting. Features High-Output 55x80mm Profile Excellent Thermal Management Surface And Suspended Mounting.

APPLICATIONS

WAREHOUSES

PRODUCTION

WORKSPACES

INDUSTRIAL

PHYSICAL

Dimensions (mm)	55mm x 80mm
Weight	Length Dependent
Housing	Aluminium
Mounting	Surface / Suspended / P2000

COMPLIANCE

Certifications	CE / RoHS / IEC 60598
Class Rating	Class II
Warranty	5 Years

DIMENSION DRAWING

PRODUCT INFORMATION

Lumen Output	600-4000 lm/m
Lumen Efficacy	Up to 136 lm/W
Colour Temperature	3000K / 3500K / 4000K / 5000K
CRI	>80
Beam Angle	90 °
UGR	20
IP Rating	IP 20
Operating Temp	-20 ~ 35 °C
Lifespan	L80B10 @ 50 000 hrs
Luminaire Colour	White / Black / Silver

ELECTRICAL

Wattage	5-26W/m
Input Voltage	200-265V AC
Frequency	50-60 Hz
Power Factor	>0.9
Surge Protection	1.5kV
Dimmable	Optional DALI or Phase cut
Flicker	Flicker-free

• E & O.E (Errors And Omissions Excepted)
• Due to the rapid development in LED technology the performance values, power consumption and lumen output levels stated above are subject to change without prior notice.
• Due to the interoperability of LED modules and drivers, up to a 10% deviation in these values is possible.
• Nominal flux values are stated at 25° C, based on LED manufacturer's data.
• Installation environmental conditions may impact the performance and efficiency of the luminaire.