

DOWNLIGHTS

COB-DR

7W –
35W—
LUMENSIP20
RATING

OVERVIEW

Round COB recessed downlight range with a deep-recessed reflector for glare control, CRI90 options and flexible dimming control.

APPLICATIONS

COMMERCIAL

RESIDENTIAL

RETAIL

PHYSICAL

Dimensions (mm)	Ceiling cut-out
Weight	—
Housing	Aluminium
Mounting	Ceiling cut-out

COMPLIANCE


Certifications	CE / RoHS / IEC 60598
Class Rating	Class II
Warranty	5 Years

PRODUCT INFORMATION

Lumen Output	—
Lumen Efficacy	—
Colour Temperature	3000K / 4000K
CRI	>83
Beam Angle	-
UGR	-
IP Rating	IP 66
Operating Temp	—
Lifespan	L80B10 @ 50 000 hrs

ELECTRICAL

Wattage	60 W
Input Voltage	200-265V AC
Frequency	50-60 Hz
Power Factor	—
Surge Protection	10kV
Dimmable	Non-dim / phase-cut / DALI / Bluetooth
Flicker	Flicker-free

 Ø 85mm

• E & O.E (Errors And Omissions Excepted)
• Due to the rapid development in LED technology the performance values, power consumption and lumen output levels stated above are subject to change without prior notice.
• Due to the interoperability of LED modules and drivers, up to a 10% deviation in these values is possible.
• Nominal flux values are stated at 25° C, based on LED manufacturer's data.
• Installation environmental conditions may impact the performance and efficiency of the luminaire.