

VAPOUR PROOF

TITAN

VAR.
POWER—
LUMENSIP65
RATING

OVERVIEW

Integrated IP65 linear LED light with vapour-proof construction, optional battery backup and radar motion sensing for industrial applications.

APPLICATIONS

COMMERCIAL

RESIDENTIAL

RETAIL

PHYSICAL

Dimensions (mm)	Linear vapour-proof profile
Weight	—
Housing	Aluminium
Mounting	Surface / suspended mounting

COMPLIANCE

Certifications	CE / RoHS / IEC 60598
Class Rating	Class II
Warranty	5 Years

PRODUCT INFORMATION

Lumen Output	—
Lumen Efficacy	135 lm/W
Colour Temperature	5000K
CRI	>83
Beam Angle	-
UGR	-
IP Rating	IP 66
Operating Temp	-40 ~ 30 °C
Lifespan	L80B10 @ 50 000 hrs

ELECTRICAL

Wattage	60 W
Input Voltage	200-265V AC
Frequency	50-60 Hz
Power Factor	>0.98
Surge Protection	10kV
Dimmable	Optional battery backup / radar sensor
Flicker	Flicker-free



See Configurations

- E & O.E (Errors And Omissions Excepted)
- Due to the rapid development in LED technology the performance values, power consumption and lumen output levels stated above are subject to change without prior notice.
- Due to the interoperability of LED modules and drivers, up to a 10% deviation in these values is possible.
- Nominal flux values are stated at 25° C, based on LED manufacturer's data.
- Installation environmental conditions may impact the performance and efficiency of the luminaire.