Proyecto SimulacroCocktail

Archivo: .\app\src\androidTest\java\com\example\simulacrococtail\ExampleInstrumentedTest.java

``java package com.example.simulacroCocktail;

import android.content.Context;

import androidx.test.platform.app.InstrumentationRegistry; import androidx.test.ext.junit.runners.AndroidJUnit4;

import org.junit.Test; import org.junit.runner.RunWith;

import static org.junit.Assert.*;

/**

- Instrumented test, which will execute on an Android device.
-
- @see Testing documentation */ @RunWith(AndroidJUnit4.class) public class ExampleInstrumentedTest { @Test public void useAppContext() { // Context of the app under test. Context appContext = InstrumentationRegistry.getInstrumentation().getTargetContext(); assertEquals("com.example.simulacroCocktail", appContext.getPackageName()); } } ``

Archivo: .\app\src\main\java\com\example\simulacroCocktail\adapters\ApiAdapter.java

``java package com.example.simulacroCocktail.adapters;

import android.view.LayoutInflater; import android.view.View; import android.view.ViewGroup; import android.widget.ImageButton; import android.widget.ImageView; import android.widget.TextView; import androidx.annotation.NonNull; import androidx.recyclerview.widget.RecyclerView; import com.example.simulacroCocktail.R; import com.example.simulacroCocktail.models.Cocktail; import com.squareup.picasso.Picasso; import java.util.List;

public class ApiAdapter extends RecyclerView.Adapter<ApiAdapter.MyViewHolder> {

```
private List<Cocktail> lista;
private OnItemClickListener listener;

public interface OnItemClickListener {
    void onFavoritoClick(Cocktail cocktail);
}

public ApiAdapter(List<Cocktail> lista, OnItemClickListener listener) {
    this.lista = lista;
    this.listener = listener;
}

@NonNull
@Override
public MyViewHolder onCreateViewHolder(@NonNull ViewGroup parent, int viewType) {
    View v = LayoutInflater.from(parent.getContext()).inflate(R.layout.item_elemento, parent, false);
    return new MyViewHolder(v);
}

@Override
public void onBindViewHolder(@NonNull MyViewHolder holder, int position) {
    Cocktail c = lista.get(position);
    holder.tvNombre.setText(c.getAtriString1());

    if (c.getAtriString2() != null && !c.getAtriString2().isEmpty()) {
        Picasso.get().load(c.getAtriString2()).into(holder.ivFoto);
    }

    holder.btnFav.setOnClickListener(v -> {
        holder.btnFav.setImageResource(android.R.drawable.btn_star_big_on);
        if (listener != null) {
            listener.onFavoritoClick(c);
        }
    });
}
```

```
@Override
public int getItemCount() { return lista.size(); }

public void actualizarLista(List<Cocktail> nuevaLista) {
    this.lista = nuevaLista;
    notifyDataSetChanged();
}

public static class MyViewHolder extends RecyclerView.ViewHolder {
    ImageView ivFoto;
    TextView tvNombre;
    ImageButton btnFav;

    public MyViewHolder(@NonNull View v) {
        super(v);
        ivFoto = v.findViewById(R.id.ivCocktail);
        tvNombre = v.findViewById(R.id.tvNombreCocktail);
        btnFav = v.findViewById(R.id.btnFavorito);
    }
}
```

}``

Archivo: .\app\src\main\java\com\example\simulacroCocktail\adapters\FavoritosAdapter.java

``java package com.example.simulacroCocktail.adapters;

import android.content.Context; import android.content.SharedPreferences; import android.view.LayoutInflater; import android.view.View; import android.view.ViewGroup; import android.widget.ImageButton; import android.widget.ImageView; import android.widget.TextView; import androidx.annotation.NonNull; import androidx.recyclerview.widget.RecyclerView;

import com.example.simulacroCocktail.R; import com.example.simulacroCocktail.models.Cocktail; import com.squareup.picasso.Picasso; import java.util.List;

public class FavoritosAdapter extends RecyclerView.Adapter<FavoritosAdapter.ViewHolder> {

```
private List<Cocktail> lista;
private OnItemClickListener listener;

public interface OnItemClickListener {
    void onItemClick(Cocktail cocktail);
}

public FavoritosAdapter(List<Cocktail> lista, OnItemClickListener listener) {
    this.lista = lista;
    this.listener = listener;
}

@NonNull
@Override
public ViewHolder onCreateViewHolder(@NonNull ViewGroup parent, int viewType) {
    View v = LayoutInflater.from(parent.getContext()).inflate(R.layout.item_elemento, parent, false);
    return new ViewHolder(v);
}

@Override
public void onBindViewHolder(@NonNull ViewHolder holder, int position) {
    Cocktail e = lista.get(position);

    holder.tvNombre.setText(e.getAtriString1());

    SharedPreferences prefs = holder.itemView.getContext().getSharedPreferences("AjustesApp", Context.MODE_PRIVATE);
    float tamanoLetra = prefs.getFloat("TAMANO_LETRA", 18f);
    holder.tvNombre.setTextSize(tamanoLetra);

    if (e.getAtriString2() != null && !e.getAtriString2().isEmpty()) {
        Picasso.get().load(e.getAtriString2()).into(holder.ivFoto);
    }
```

```
    holder.btnEstrella.setImageResource(android.R.drawable.btn_star_big_on);

    holder.itemView.setOnClickListener(v -> {
        if (listener != null) {
            listener.onItemClick(e);
        }
    });
}

@Override
public int getItemCount() {
    return lista.size();
}

public void actualizar(List<Cocktail> nuevaLista) {
    this.lista = nuevaLista;
    notifyDataSetChanged();
}

public static class ViewHolder extends RecyclerView.ViewHolder {
    ImageView ivFoto;
    TextView tvNombre;
    ImageButton btnEstrella;

    public ViewHolder(@NonNull View itemView) {
        super(itemView);
        ivFoto = itemView.findViewById(R.id.ivCocktail);
        tvNombre = itemView.findViewById(R.id.tvNombreCocktail);
        btnEstrella = itemView.findViewById(R.id.btnFavorito);
    }
}
```

} ``

Archivo: .\app\src\main\java\com\example\simulacroCocktail\api\ApiService.java

``java package com.example.simulacroCocktail.api;

import retrofit2.Call; import retrofit2.http.GET;

public interface ApiService { // Nombre corregido para que coincida con el Fragment @GET("filter.php?a=Alcoholic") Call getElementos(); } ``

Archivo: .\app\src\main\java\com\example\simulacroCocktail\api\CocktailResponse.java

``java package com.example.simulacroCocktail.api;

import java.util.List; import com.example.simulacroCocktail.models.Cocktail; import com.google.gson.annotations.SerializedName;

public class CocktailResponse {

```
// @SerializedName("drinks") es OBLIGATORIO porque así se llama en el JSON de la API
@SerializedName("drinks")
private List<Cocktail> drinks;

// Cambiamos el nombre del getter para que coincida con lo que usas en el Fragment
public List<Cocktail> getListaCocktail() {
    return drinks;
}

public void setListaElementos(List<Cocktail> drinks) {
    this.drinks = drinks;
}
```

} ``

Archivo: .\app\src\main\java\com\example\simulacroCocktail\api\RetrofitClient.java

``java package com.example.simulacroCocktail.api;

import retrofit2.Retrofit; import retrofit2.converter.gson.GsonConverterFactory;

public class RetrofitClient {

```
private static final String BASE_URL = "https://www.thecocktaildb.com/api/json/v1/1/";
private static Retrofit retrofit = null;

public static Retrofit getClient() {
    if (retrofit == null) {
        retrofit = new Retrofit.Builder()
                .baseUrl(BASE_URL)
                .addConverterFactory(GsonConverterFactory.create())
                .build();
    }
    return retrofit;
}

// Método añadido para que RetrofitClient.getApiService() funcione en el Fragment
public static ApiService getApiService() {
    return getClient().create(ApiService.class);
}
```

} ``

Archivo: .\app\src\main\java\com\example\simulacroCocktail\database\CocktailDAO.java

``java package com.example.simulacroCocktail.database;

import android.content.ContentValues; import android.content.Context; import android.database.Cursor; import android.database.sqlite.SQLiteDatabase; import com.example.simulacroCocktail.models.Cocktail; import java.util.ArrayList;

public class CocktailDAO { private DbHelper helper; public CocktailDAO(Context c) { helper = new DbHelper(c); }

```
public long insertar(Cocktail e) {
    SQLiteDatabase db = helper.getWritableDatabase();
    ContentValues v = new ContentValues();
    v.put("atriString1", e.getAtriString1());
    v.put("atriString2", e.getAtriString2());
    v.put("atriBoolean1", e.isAtriBoolean1() ? 1 : 0);
    long id = db.insert(DbHelper.TABLE, null, v);
    db.close();
    return id;
}

public ArrayList<Cocktail> obtenerTodos() {
    ArrayList<Cocktail> lista = new ArrayList<>();
    SQLiteDatabase db = helper.getReadableDatabase();
    Cursor c = db.rawQuery("SELECT * FROM " + DbHelper.TABLE, null);
    if (c.moveToFirst()) {
        do {
            Cocktail e = new Cocktail();
            e.setId(c.getInt(0));
            e.setAtriString1(c.getString(1));
            e.setAtriString2(c.getString(2));
            e.setAtriBoolean1(c.getInt(3) == 1);
            lista.add(e);
        } while (c.moveToNext());
    }
    c.close();
    db.close();
    return lista;
}

public void borrarTodos() {
    SQLiteDatabase db = helper.getWritableDatabase();
    db.delete(DbHelper.TABLE, null, null);
    db.close();
}
```

} ``

Archivo: .\app\src\main\java\com\example\simulacroCocktail\database\DbHelper.java

``java package com.example.simulacroCocktail.database;

import android.content.Context; import android.database.sqlite.SQLiteDatabase; import android.database.sqlite.SQLiteOpenHelper;

public class DbHelper extends SQLiteOpenHelper { public static final String DB_NAME = "examen.db"; public static final int DB_VERSION = 1; public static final String TABLE = "tabla_elementos";

```
private static final String CREATE_TABLE = "CREATE TABLE " + TABLE + " (" +
        "id INTEGER PRIMARY KEY AUTOINCREMENT, " +
        "atriString1 TEXT, " +
        "atriString2 TEXT, " +
        "atriBoolean1 INTEGER)";

public DbHelper(Context context) { super(context, DB_NAME, null, DB_VERSION); }

@Override
public void onCreate(SQLiteDatabase db) { db.execSQL(CREATE_TABLE); }

@Override
public void onUpgrade(SQLiteDatabase db, int old, int n) {
    db.execSQL("DROP TABLE IF EXISTS " + TABLE);
    onCreate(db);
}
```

} ``

Archivo: .\app\src\main\java\com\example\simulacroCocktail\fragments\ApiFragment.java

``java package com.example.simulacroCocktail.fragments;

import android.os.Bundle; import android.view.LayoutInflater; import android.view.View; import android.view.ViewGroup; import android.widget.Toast; import androidx.annotation.NonNull; import androidx.annotation.Nullable; import androidx.fragment.app.Fragment; import androidx.recyclerview.widget.LinearLayoutManager; import androidx.recyclerview.widget.RecyclerView;

import com.example.simulacroCocktail.api.CocktailResponse; import com.example.simulacroCocktail.MainActivity; import com.example.simulacroCocktail.R; import com.example.simulacroCocktail.api.RetrofitClient; import com.example.simulacroCocktail.adapters.ApiAdapter; import com.example.simulacroCocktail.database.CocktailDAO; import com.example.simulacroCocktail.database.DbHelper; import com.example.simulacroCocktail.models.Cocktail;

import java.util.ArrayList; import java.util.List; import retrofit2.Call; import retrofit2.Callback; import retrofit2.Response;

public class ApiFragment extends Fragment {

```
private RecyclerView recyclerView;
private ApiAdapter adaptador;
private List<Cocktail> listaElementos = new ArrayList<>();
private CocktailDAO dao;

public ApiFragment() {}

@Nullable
@Override
public View onCreateView(@NonNull LayoutInflater inflater, @Nullable ViewGroup container, @Nullable Bundle
savedInstanceState) {
    View view = inflater.inflate(R.layout.fragment_api, container, false);

    // 1. Inicializar DAO
    dao = new CocktailDAO(getContext());

    // 2. Configurar RecyclerView
    recyclerView = view.findViewById(R.id.rvElementosApi);
    recyclerView.setLayoutManager(new LinearLayoutManager(getContext()));

    // 3. Configurar Adaptador con el listener para la estrella
    adaptador = new ApiAdapter(listaElementos, new ApiAdapter.OnItemClickListener() {
        @Override
```

```
        public void onFavoritoClick(Cocktail elemento) {
            // GUARDAR EN SQLITE
            dao.insertar(elemento);
            Toast.makeText(getContext(), elemento.getAtriString1() + " añadido a favoritos", Toast.LENGTH_SHORT).show();

            // AVISAR AL PADRE (MainActivity) para que refresque el fragment de abajo
            if (getActivity() instanceof MainActivity) {
                ((MainActivity) getActivity()).actualizarListaFavoritos();
            }
        }
    });

    recyclerView.setAdapter(adaptador);

    // 4. Lanzar la descarga de datos
    cargarDatosDeInternet();

    return view;
}

private void cargarDatosDeInternet() {
    // Llamada usando el RetrofitClient y la interfaz ApiService
    RetrofitClient.getApiService().getElementos().enqueue(new Callback<CocktailResponse>() {
        @Override
        public void onResponse(Call<CocktailResponse> call, Response<CocktailResponse> response) {
            if (response.isSuccessful() && response.body() != null) {
                // Actualizar la lista con los datos que vienen de la API ("drinks")
                List<Cocktail> descargados = response.body().getListaCocktail();
                adaptador.actualizarLista(descargados);
            } else {
                Toast.makeText(getContext(), "Error en la respuesta del servidor", Toast.LENGTH_SHORT).show();
            }
        }

        @Override
        public void onFailure(Call<CocktailResponse> call, Throwable t) {
            Toast.makeText(getContext(), "Fallo de red: " + t.getMessage(), Toast.LENGTH_SHORT).show();
        }
    });
}
```

} ``

Archivo: .\app\src\main\java\com\example\simulacroCocktail\fragments\ListaFragment.java

``java package com.example.simulacroCocktail.fragments;

import android.os.Bundle; import android.view.LayoutInflater; import android.view.View; import android.view.ViewGroup; import android.widget.Toast; import androidx.annotation.NonNull; import androidx.annotation.Nullable; import androidx.fragment.app.Fragment; import androidx.recyclerview.widget.LinearLayoutManager; import androidx.recyclerview.widget.RecyclerView;

import com.example.simulacroCocktail.adapters.FavoritosAdapter; import com.example.simulacroCocktail.R; import com.example.simulacroCocktail.database.CocktailDAO; import com.example.simulacroCocktail.models.Cocktail;

import java.util.List;

public class ListaFragment extends Fragment {

```
private RecyclerView recyclerView;
private FavoritosAdapter adapter;
private CocktailDAO dao;
private List<Cocktail> listaFavoritos;

@Nullable
@Override
public View onCreateView(@NonNull LayoutInflater inflater, @Nullable ViewGroup container, @Nullable Bundle
savedInstanceState) {
    View view = inflater.inflate(R.layout.fragment_lista, container, false);
```

```
    recyclerView = view.findViewById(R.id.recyclerView);
    recyclerView.setLayoutManager(new LinearLayoutManager(getContext()));

    dao = new CocktailDAO(getContext());
    listaFavoritos = dao.obtenerTodos();

    adapter = new FavoritosAdapter(listaFavoritos, cocktail -> {
        Toast.makeText(getContext(), "Favorito: " + cocktail.getAtriString1(), Toast.LENGTH_SHORT).show();
    });

    recyclerView.setAdapter(adapter);

    return view;
}

public void cargarDatos() {
    if (dao != null && adapter != null) {
        listaFavoritos = dao.obtenerTodos();
        adapter.actualizar(listaFavoritos);
    }
}
```

} ``

Archivo: .\app\src\main\java\com\example\simulacroCocktail\models\Cocktail.java

``java package com.example.simulacroCocktail.models;

import com.google.gson.annotations.SerializedName;

public class Cocktail {

```
private int id;

@SerializedName("strDrink")
private String atriString1;

@SerializedName("strDrinkThumb")
private String atriString2;

private boolean atriBoolean1;

public Cocktail() {}

public Cocktail(String atriString1, String atriString2, boolean atriBoolean1) {
    this.atriString1 = atriString1;
    this.atriString2 = atriString2;
    this.atriBoolean1 = atriBoolean1;
}

public int getId() { return id; }
public void setId(int id) { this.id = id; }

public String getAtriString1() { return atriString1; }
public void setAtriString1(String atriString1) { this.atriString1 = atriString1; }

public String getAtriString2() { return atriString2; }
public void setAtriString2(String atriString2) { this.atriString2 = atriString2; }

public boolean isAtriBoolean1() { return atriBoolean1; }
public void setAtriBoolean1(boolean atriBoolean1) { this.atriBoolean1 = atriBoolean1; }
```

} ``

Archivo: .\app\src\main\java\com\example\simulacroCocktail\DetalleActivity.java

``java package com.example.simulacroCocktail;

import android.os.Bundle;

import androidx.activity.EdgeToEdge; import androidx.appcompat.app.AppCompatActivity; import androidx.core.graphics.Insets; import androidx.core.view.ViewCompat; import androidx.core.view.WindowInsetsCompat;

public class DetalleActivity extends AppCompatActivity {

```
@Override
protected void onCreate(Bundle savedInstanceState) {
    super.onCreate(savedInstanceState);
    EdgeToEdge.enable(this);
    setContentView(R.layout.activity_detalle);

    ViewCompat.setOnApplyWindowInsetsListener(findViewById(R.id.main), (v, insets) -> {
        Insets systemBars = insets.getInsets(WindowInsetsCompat.Type.systemBars());
        v.setPadding(systemBars.left, systemBars.top, systemBars.right, systemBars.bottom);
        return insets;
    });
}
```

} ``

Archivo: .\app\src\main\java\com\example\simulacroCocktail\MainActivity.java

``java package com.example.simulacroCocktail;

import android.content.Context; import android.content.SharedPreferences; import android.os.Bundle; import android.view.Menu; import android.view.MenuItem; import androidx.activity.EdgeToEdge; import androidx.appcompat.app.AppCompatActivity; import androidx.core.graphics.Insets; import androidx.core.view.ViewCompat; import androidx.core.view.WindowInsetsCompat; import androidx.fragment.app.Fragment; import com.example.simulacroCocktail.fragments.ApiFragment; import com.example.simulacroCocktail.fragments.ListaFragment;

public class MainActivity extends AppCompatActivity {

```
SharedPreferences prefs = getSharedPreferences("AjustesApp", Context.MODE_PRIVATE);
SharedPreferences.Editor editor = prefs.edit();


@Override
protected void onCreate(Bundle savedInstanceState) {
    super.onCreate(savedInstanceState);
    EdgeToEdge.enable(this);
    setContentView(R.layout.activity_main);

    ViewCompat.setOnApplyWindowInsetsListener(findViewById(R.id.main), (v, insets) -> {
        Insets systemBars = insets.getInsets(WindowInsetsCompat.Type.systemBars());
        v.setPadding(systemBars.left, systemBars.top, systemBars.right, systemBars.bottom);
        return insets;
    });

    if (savedInstanceState == null) {
        Fragment superior = new ApiFragment();
        Fragment inferior = new ListaFragment();

        getSupportFragmentManager().beginTransaction()
                .replace(R.id.container_fragment_1, superior)
                .replace(R.id.container_fragment_2, inferior, "TAG_LISTA_FRAGMENT")
                .commit();
    }
}

// 1. Inflar el menú (hacer que aparezca en la barra)
@Override
public boolean onCreateOptionsMenu(Menu menu) {
    getMenuInflater().inflate(R.menu.menu_principal, menu);
    return true;
}

// 2. Darle funcionalidad a los botones del menú
@Override
public boolean onOptionsItemSelected(MenuItem item) {
    int id = item.getItemId();
```

```
    if (id == R.id.action_changetext) {


        // Acción al pulsar Añadir

        return true;
    } else if (id == R.id.action_back) {

        //  Acción al pulsar atras
        finish();


        return true;
    }
    return super.onOptionsItemSelected(item);
}

public void actualizarListaFavoritos() {
    Fragment fragment = getSupportFragmentManager().findFragmentByTag("TAG_LISTA_FRAGMENT");
    if (fragment instanceof ListaFragment) {
        ((ListaFragment) fragment).cargarDatos();
    }
}
```

}``

Archivo: .\app\src\main\res\layout\activity_detalle.xml

``xml <androidx.cardview.widget.CardView xmlns:android="http://schemas.android.com/apk/res/android" xmlns:app="http://schemas.android.com/apk/res-auto" xmlns:tools="http://schemas.android.com/tools" android:layout_width="match_parent" android:layout_height="wrap_content" android:layout_margin="8dp" app:cardElevation="4dp" app:cardCornerRadius="8dp">

```
<androidx.constraintlayout.widget.ConstraintLayout
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:padding="16dp">

    <TextView
        android:id="@+id/tvString1"
        android:layout_width="0dp"
        android:layout_height="wrap_content"
        android:text="Nombre Elemento"
        android:textSize="18sp"
        android:textStyle="bold"
        app:layout_constraintStart_toStartOf="parent"
        app:layout_constraintTop_toTopOf="parent" />

    <TextView
        android:id="@+id/tvString2"
        android:layout_width="0dp"
        android:layout_height="wrap_content"
        android:layout_marginTop="4dp"
        android:alpha="0.7"
        android:text="Descripción o subtítulo aquí"
        app:layout_constraintBottom_toBottomOf="parent"
        app:layout_constraintEnd_toEndOf="parent"
        app:layout_constraintHorizontal_bias="0.0"
        app:layout_constraintStart_toStartOf="parent"
        app:layout_constraintTop_toBottomOf="@+id/tvString1"
        app:layout_constraintVertical_bias="0.195" />

    <ImageView
        android:id="@+id/imageView"
        android:layout_width="78dp"
        android:layout_height="90dp"
        tools:layout_editor_absoluteX="286dp"
        tools:layout_editor_absoluteY="-5dp"
```

```
        tools:srcCompat="@tools:sample/avatars" />

    <Button
        android:id="@+id/button"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Eliminar de Favoritos"
        tools:layout_editor_absoluteX="87dp"
        tools:layout_editor_absoluteY="71dp" />

</androidx.constraintlayout.widget.ConstraintLayout>
```

</androidx.cardview.widget.CardView> ``

Archivo: .\app\src\main\res\layout\activity_main.xml

``xml

```
<!-- Contenedor para el primer Fragment -->
<androidx.fragment.app.FragmentContainerView
    android:id="@+id/container_fragment_1"
    android:name="com.example.simulacroCocktail.fragments.ApiFragment"
    android:layout_width="match_parent"
    android:layout_height="0dp"
    android:layout_weight="1" />

<!-- Contenedor para el segundo Fragment -->
<androidx.fragment.app.FragmentContainerView
    android:id="@+id/container_fragment_2"
    android:name="com.example.simulacroCocktail.fragments.ListaFragment"
    android:layout_width="match_parent"
    android:layout_height="0dp"
    android:layout_weight="1" />
```

``

Archivo: .\app\src\main\res\layout\fragment_api.xml

``xml <androidx.constraintlayout.widget.ConstraintLayout xmlns:android="http://schemas.android.com/apk/res/android" xmlns:app="http://schemas.android.com/apk/res-auto" xmlns:tools="http://schemas.android.com/tools" android:layout_width="match_parent" android:layout_height="match_parent" android:orientation="vertical">

```
<TextView
    android:id="@+id/textView"
    android:layout_width="match_parent"
    android:layout_height="wrap_content"
    android:gravity="center"
    android:padding="10dp"
    android:text="Elementos Disponibles"
    android:textSize="20sp"
    android:textStyle="bold"
    tools:layout_editor_absoluteX="0dp"
    tools:layout_editor_absoluteY="0dp"
    app:layout_constraintBottom_toTopOf="@+id/rvElementosApi"/>

<androidx.recyclerview.widget.RecyclerView
    android:id="@+id/rvElementosApi"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    app:layout_constraintTop_toBottomOf="@+id/textView"
    tools:layout_editor_absoluteX="0dp" />
```

</androidx.constraintlayout.widget.ConstraintLayout> ``

Archivo: .\app\src\main\res\layout\fragment_lista.xml

``xml

```
<androidx.recyclerview.widget.RecyclerView
    android:id="@+id/recyclerView"
    android:layout_width="match_parent"
    android:layout_height="match_parent"
    android:padding="8dp" />
```

``

Archivo: .\app\src\main\res\layout\item_elemento.xml

``xml

```
<ImageView
    android:id="@+id/ivCocktail"
    android:layout_width="80dp"
    android:layout_height="80dp"
    android:scaleType="centerCrop"
    android:src="@mipmap/ic_launcher" />

<TextView
    android:id="@+id/tvNombreCocktail"
    android:layout_width="0dp"
    android:layout_height="wrap_content"
    android:layout_weight="1"
    android:layout_marginStart="15dp"
    android:text="Nombre del Cocktail"
    android:textSize="18sp"
    android:textStyle="bold"
    android:textColor="@android:color/black" />

<ImageButton
    android:id="@+id/btnFavorito"
    android:layout_width="48dp"
    android:layout_height="48dp"
    android:background="?attr/selectableItemBackgroundBorderless"
    android:src="@android:drawable/btn_star_big_off"
    android:contentDescription="Favorito" />
```

``

Archivo: .\app\src\main\res\menu\menu_principal.xml

``xml XML

```
<item
    android:id="@+id/action_changetext"
    android:title="Añadir"
    android:icon="@android:drawable/ic_menu_add"
    app:showAsAction="ifRoom" />

<item
    android:id="@+id/action_back"
    android:icon="@android:drawable/ic_menu_revert"
    android:title="Añadir"
    app:showAsAction="ifRoom" />
```

``

Archivo: .\app\src\main\res\values\colors.xml

`xml <?xml version="1.0" encoding="utf-8"?> <resources> <color name="black">#FF000000</color> <color name="white">#FFFFFFFF</color> </resources>`

Archivo: .\app\src\main\res\values\strings.xml

`xml <resources> <string name="app_name">SimulacroCoctail</string> </resources>`

Archivo: .\app\src\main\res\values\themes.xml

``xml

```
<style name="Theme.SimulacroCoctail" parent="Base.Theme.SimulacroCoctail" />
```

``

Archivo: .\app\src\main\res\values-night\themes.xml

`xml <resources xmlns:tools="http://schemas.android.com/tools"> <!-- Base application theme. --> <style name="Base.Theme.SimulacroCoctail" parent="Theme.Material3.DayNight.NoActionBar"> <!-- Customize your dark theme here. --> <!- - <item name="colorPrimary">@color/my_dark_primary</item> --> </style> </resources>`

Archivo: .\app\src\main\AndroidManifest.xml

``xml

```
<uses-permission android:name="android.permission.INTERNET" />

<application
    android:allowBackup="true"
    android:dataExtractionRules="@xml/data_extraction_rules"
    android:fullBackupContent="@xml/backup_rules"
    android:icon="@mipmap/ic_launcher"
    android:label="@string/app_name"
    android:roundIcon="@mipmap/ic_launcher_round"
    android:supportsRtl="true"
    android:theme="@style/Theme.SimulacroCoctail">
    <activity
        android:name=".DetalleActivity"
        android:exported="false" />
    <activity
        android:name=".MainActivity"
        android:exported="true">
        <intent-filter>
            <action android:name="android.intent.action.MAIN" />

            <category android:name="android.intent.category.LAUNCHER" />
        </intent-filter>
    </activity>
</application>
```

``

Archivo: .\app\src\test\java\com\example\simulacrococtail\ExampleUnitTest.java

``java package com.example.simulacroCocktail;

import org.junit.Test;

import static org.junit.Assert.*;

/**

- Example local unit test, which will execute on the development machine (host).
-
- @see Testing documentation */ public class ExampleUnitTest { @Test public void addition_isCorrect() { assertEquals(4, 2 + 2); } } ``

Archivo: .\app\build.gradle.kts

``kotlin plugins { alias(libs.plugins.android.application) }

android { namespace = "com.example.simulacroCocktail" compileSdk = 36

```
defaultConfig {
    applicationId = "com.example.simulacroCocktail"
    minSdk = 26
    targetSdk = 36
    versionCode = 1
    versionName = "1.0"

    testInstrumentationRunner = "androidx.test.runner.AndroidJUnitRunner"
```

```
}

buildTypes {
    release {
        isMinifyEnabled = false
        proguardFiles(
            getDefaultProguardFile("proguard-android-optimize.txt"),
            "proguard-rules.pro"
        )
    }
}
compileOptions {
    sourceCompatibility = JavaVersion.VERSION_11
    targetCompatibility = JavaVersion.VERSION_11
}
```

}

dependencies { // 🌐 Retrofit + GSON implementation("com.squareup.retrofit2:retrofit:2.9.0") implementation("com.squareup.retrofit2:converter-gson:2.9.0")

```
// 🖼️ Picasso (Para cargar imágenes desde URL)
implementation("com.squareup.picasso:picasso:2.71828")

implementation(libs.appcompat)
implementation(libs.material)
implementation(libs.activity)
implementation(libs.constraintlayout)
implementation(libs.fragment)
testImplementation(libs.junit)
androidTestImplementation(libs.ext.junit)
androidTestImplementation(libs.espresso.core)
```

} ``

Archivo: .\gradle\libs.versions.toml

``properties [versions] agp = "8.13.2" junit = "4.13.2" junitVersion = "1.3.0" espressoCore = "3.7.0" appcompat = "1.7.1" material = "1.13.0" activity = "1.13.0" constraintlayout = "2.2.1" fragment = "1.8.9"

[libraries] junit = { group = "junit", name = "junit", version.ref = "junit" } ext-junit = { group = "androidx.test.ext", name = "junit", version.ref = "junitVersion" } espresso-core = { group = "androidx.test.espresso", name = "espresso-core", version.ref = "espressoCore" } appcompat = { group = "androidx.appcompat", name = "appcompat", version.ref = "appcompat" } material = { group = "com.google.android.material", name = "material", version.ref = "material" } activity = { group = "androidx.activity", name = "activity", version.ref = "activity" } constraintlayout = { group = "androidx.constraintlayout", name = "constraintlayout", version.ref = "constraintlayout" } fragment = { group = "androidx.fragment", name = "fragment", version.ref = "fragment" }

[plugins] android-application = { id = "com.android.application", version.ref = "agp" }

``

Archivo: .\build.gradle.kts

`kotlin // Top-level build file where you can add configuration options common to all sub-projects/modules. plugins { alias(libs.plugins.android.application) apply false }`

Archivo: .\gradle.properties

``properties

Project-wide Gradle settings.

IDE (e.g. Android Studio) users:

Gradle settings configured through the IDE *will override*

any settings specified in this file.

For more details on how to configure your build environment visit

http://www.gradle.org/docs/current/userguide/build_environment.html

Specifies the JVM arguments used for the daemon process.

The setting is particularly useful for tweaking memory settings.

org.gradle.jvmargs=-Xmx2048m -Dfile.encoding=UTF-8

When configured, Gradle will run in incubating parallel mode.

This option should only be used with decoupled projects. For more details, visit

https://developer.android.com/r/tools/gradle-multi-project-decoupled-projects

org.gradle.parallel=true

AndroidX package structure to make it clearer which packages are bundled with the

Android operating system, and which are packaged with your app's APK

https://developer.android.com/topic/libraries/support-library/androidx-rn

android.useAndroidX=true

Enables namespacing of each library's R class so that its R class includes only the

resources declared in the library itself and none from the library's dependencies,

thereby reducing the size of the R class for that library

android.nonTransitiveRClass=true ``

Archivo: .\local.properties

``properties

This file is automatically generated by Android Studio.

Do not modify this file -- YOUR CHANGES WILL BE ERASED!

This file should *NOT* be checked into Version Control Systems,

as it contains information specific to your local configuration.

Location of the SDK. This is only used by Gradle.

For customization when using a Version Control System, please read the

header note.

sdk.dir=C:\Users\alvar\AppData\Local\Android\Sdk ``

Archivo: .\settings.gradle.kts

``kotlin pluginManagement { repositories { google { content { includeGroupByRegex("com\.android.") *includeGroupByRegex("com\.google.")* includeGroupByRegex("androidx.*") } } mavenCentral() gradlePluginPortal() } } dependencyResolutionManagement { repositoriesMode.set(RepositoriesMode.FAIL_ON_PROJECT_REPOS) repositories { google() mavenCentral() } }

rootProject.name = "SimulacroCocktail" include(":app") ``