Cuadro Oficina

SECCION comercial	120,00	4,00	4,00	2,50	2,50	2,50	190,00	190,00
col	19,52	0,81	0,81	0,51	0,51	0,51	38,42	38,42
Calibre Aut.	250,00	16	16	16	16	16	100	80
lmax	256	24	24	19	19	19	162	162
Fc	06'0	06'0	06'0	06'0	06'0	06'0	06'0	06'0
Itab	284,0	27	27	21	21	21	180	180
Ical	151,50	6,57	6,57	6,26	4,70	5,32	79,57	59,72
% cdt Acum	0,42	2,35	2,35	3,36	2,62	2,92	0,76	0,67
Conductor	0,6/1kV Cu 4x120+PE	450/750V Cu 2x4+PE	450/750V Cu 2x4+PE	450/750V Cu 2x2,5+PE	450/750V Cu 2x2,5+PE	450/750V Cu 2x2,5+PE	450/750V Cu 4x190+PE	450/750V Cu 4x190+PE
FP	0,80	1,00	1,00	1,00	1,00	1,00	0,80	08'0
P (W)	83.968	1.512	1.512	1.440	1.080	1.224	44.100	33.100
(m)	20	20	02	02	02	02	120	120
U (V)	400	230	230	230	230	230	400	400
Denominación	Línea General	ALO1	ALO2	TC01	ALO3	ALO4	тс02	TCS