

project_bundle.txt - Part 1 of 3

Created: 2026-05-19 00:04:45

FILE: .gitignore

```
./node_modules
```

FILE: index.html

```
<!doctype html>
<html lang="en" class="dark">
  <head>
    <meta charset="UTF-8" />
    <link rel="icon" type="image/svg+xml" href="/vite.svg" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0, viewport-fit=cover" />
    <meta name="theme-color" content="#000000" />
    <title>SmartLearn - Offline Smart Learning System</title>
    <meta name="description" content="Learn anywhere, anytime even without internet connection" />
  </head>
  <body>
    <div id="root"></div>
    <script type="module" src="/src/main.jsx"></script>
  </body>
</html>
```

FILE: netlify.toml

```
[build]
  base = "/"
  command = "npm run build"
  publish = "dist"

[build.environment]
  NODE_VERSION = "18"

[[redirects]]
  from = "/*"
  to = "/index.html"
  status = 200
```

FILE: package.json

```
{
  "name": "offline-smart-learning",
  "private": true,
  "version": "1.0.0",
  "type": "module",
  "scripts": {
    "dev": "vite",
    "build": "node ./node_modules/vite/bin/vite.js build",
    "preview": "vite preview"
  },
  "dependencies": {
    "react": "^18.2.0",
    "react-dom": "^18.2.0",
    "react-router-dom": "^6.20.0",
    "framer-motion": "^10.16.4",
    "lucide-react": "^0.294.0",
    "react-intersection-observer": "^9.5.3",
    "recharts": "^2.10.3"
  },
  "devDependencies": {
    "@types/react": "^18.2.43",
    "@types/react-dom": "^18.2.17",
    "@vitejs/plugin-react": "^4.2.1",
    "autoprefixer": "^10.4.16",
    "postcss": "^8.4.32",
    "tailwindcss": "^3.3.6",
    "vite": "^5.0.8"
  }
}
```

FILE: postcss.config.js

```
export default {
  plugins: {
    tailwindcss: {},
    autoprefixer: {},
  },
}
```

FILE: tailwind.config.js

```
/** @type {import('tailwindcss').Config} */
export default {
  content: [
    "./index.html",
    "./src/**/*.{js,ts,jsx,tsx}",
  ],
  darkMode: 'class',
  theme: {
    extend: {
      colors: {
        primary: {
          50: '#f0f9ff',
          100: '#e0f2fe',
          200: '#bae6fd',
          300: '#7dd3fc',
          400: '#38bdf8',
          500: '#0ea5e9',
          600: '#0284c7',
          700: '#0369a1',
          800: '#075985',
          900: '#0c4a6e',
        },
      },
      fontFamily: {
        sans: ['Inter', 'system-ui', 'sans-serif'],
      },
      animation: {
        'float': 'float 6s ease-in-out infinite',
        'glow': 'glow 2s ease-in-out infinite',
        'slide-up': 'slideUp 0.5s ease-out',
        'slide-down': 'slideDown 0.5s ease-out',
        'slide-left': 'slideLeft 0.5s ease-out',
        'slide-right': 'slideRight 0.5s ease-out',
      },
      keyframes: {
        float: {
          '0%', '100%': { transform: 'translateY(0px)' },
          '50%': { transform: 'translateY(-20px)' },
        },
        glow: {
          '0%', '100%': { opacity: 1 },
          '50%': { opacity: 0.5 },
        },
        slideUp: {
          '0%': { transform: 'translateY(100px)', opacity: '0' },
          '100%': { transform: 'translateY(0)', opacity: '1' },
        },
        slideDown: {
          '0%': { transform: 'translateY(-100px)', opacity: '0' },
          '100%': { transform: 'translateY(0)', opacity: '1' },
        },
        slideLeft: {
          '0%': { transform: 'translateX(100px)', opacity: '0' },
          '100%': { transform: 'translateX(0)', opacity: '1' },
        },
        slideRight: {
          '0%': { transform: 'translateX(-100px)', opacity: '0' },
          '100%': { transform: 'translateX(0)', opacity: '1' },
        },
      },
      backdropBlur: {
        xs: '2px',
      },
    },
  },
  plugins: [],
}
```

FILE: vite.config.js

```
import { defineConfig } from 'vite'
import react from '@vitejs/plugin-react'

export default defineConfig({
  plugins: [react()],
  server: {
    port: 3000,
    open: true,
  },
})
```

FILE: public/placeholder-image.svg

FILE: src/App.jsx

```
import React from 'react';
import { Routes, Route } from 'react-router-dom';
import { motion, AnimatePresence } from 'framer-motion';

import Navbar from './components/layout/Navbar';
import Footer from './components/layout/Footer';
import Home from './pages/Home/Home';
import Dashboard from './pages/Dashboard/Dashboard';
import Courses from './pages/Courses/Courses';
import CourseDetails from './pages/CourseDetails/CourseDetails';
import Offline from './pages/Offline/Offline';
import AIAssistant from './pages/AI/AIAssistant';
import Login from './pages/Auth/Login';
import Register from './pages/Auth/Register';
import Profile from './pages/Profile/Profile';
import Settings from './pages/Settings/Settings';
import About from './pages/About/About.jsx';
import NotFound from './pages/NotFound/NotFound';

function App() {
  return (
    <AnimatePresence mode="wait">
      <motion.div
        initial={{ opacity: 0 }}
        animate={{ opacity: 1 }}
        exit={{ opacity: 0 }}
        className="min-h-screen bg-gradient-to-br from-black via-gray-900 to-black"
      >
        <Navbar />
        <main className="pt-16 min-h-screen">
          <Routes>
            <Route path="/" element={<Home />} />
            <Route path="/dashboard" element={<Dashboard />} />
            <Route path="/courses" element={<Courses />} />
            <Route path="/course/:id" element={<CourseDetails />} />
            <Route path="/offline" element={<Offline />} />
            <Route path="/ai-assistant" element={<AIAssistant />} />
            <Route path="/login" element={<Login />} />
            <Route path="/register" element={<Register />} />
            <Route path="/profile" element={<Profile />} />
            <Route path="/settings" element={<Settings />} />
            <Route path="/about" element={<About />} />
            <Route path="*" element={<NotFound />} />
          </Routes>
        </main>
        <Footer />
      </motion.div>
    </AnimatePresence>
  );
}

export default App;
```

FILE: src/main.jsx

```
import React from 'react'
import ReactDOM from 'react-dom/client'
import App from './App.jsx'
import './styles/globals.css'
import { BrowserRouter } from 'react-router-dom'

// Simple context providers without complex dependencies
const ThemeProvider = ({ children }) => {
  const [darkMode, setDarkMode] = React.useState(true)

  React.useEffect(() => {
    if (darkMode) {
      document.documentElement.classList.add('dark')
    } else {
      document.documentElement.classList.remove('dark')
    }
  }, [darkMode])

  return (
    <ThemeContext.Provider value={{ darkMode, setDarkMode }}>
      {children}
    </ThemeContext.Provider>
  )
}

const ThemeContext = React.createContext()
```

```

export const useTheme = () => React.useContext(ThemeContext)

const AuthProvider = ({ children }) => {
  const [user, setUser] = React.useState(null)
  const [loading, setLoading] = React.useState(true)

  React.useEffect(() => {
    const savedUser = localStorage.getItem('user')
    if (savedUser) {
      setUser(JSON.parse(savedUser))
    }
    setLoading(false)
  }, [])

  const login = async (email, password) => {
    const user = { id: 1, email, name: 'John Doe' }
    setUser(user)
    localStorage.setItem('user', JSON.stringify(user))
    return true
  }

  const logout = () => {
    setUser(null)
    localStorage.removeItem('user')
  }

  const register = async (name, email, password) => {
    const user = { id: 1, email, name }
    setUser(user)
    localStorage.setItem('user', JSON.stringify(user))
    return true
  }

  return (
    <AuthContext.Provider value={{ user, loading, login, logout, register }}>
      {children}
    </AuthContext.Provider>
  )
}

const AuthContext = React.createContext()
export const useAuth = () => React.useContext(AuthContext)

ReactDOM.createRoot(document.getElementById('root')).render(
  <React.StrictMode>
    <BrowserRouter>
      <ThemeProvider>
        <AuthProvider>
          <App />
        </AuthProvider>
      </ThemeProvider>
    </BrowserRouter>
  </React.StrictMode>,
)

```

FILE: src/components/animations/AnimatedNumber.jsx

```

import React from 'react';
import { motion, useSpring, useTransform } from 'framer-motion';

const AnimatedNumber = ({ value, format = (v) => v, duration = 0.5 }) => {
  const spring = useSpring(0, {
    stiffness: 100,
    damping: 30,
    duration: duration * 1000
  });

  const display = useTransform(spring, (current) => format(Math.floor(current)));

  React.useEffect(() => {
    spring.set(value);
  }, [spring, value]);

  return <motion.span>{display}</motion.span>;
};

export default AnimatedNumber;

```

FILE: src/components/animations/FadeIn.jsx

```

import React from 'react';
import { motion } from 'framer-motion';
import { useInView } from 'react-intersection-observer';

const FadeIn = ({

```

```

children,
delay = 0,
direction = 'up',
duration = 0.5,
className = '',
threshold = 0.1,
once = true
}) => {
  const [ref, inView] = useInView({
    threshold,
    triggerOnce: once
  });

  const directions = {
    up: { y: 40, x: 0 },
    down: { y: -40, x: 0 },
    left: { x: 40, y: 0 },
    right: { x: -40, y: 0 },
    none: { x: 0, y: 0 }
  };

  return (
    <motion.div
      ref={ref}
      initial={{ opacity: 0, ...directions[direction] }}
      animate={inView ? { opacity: 1, x: 0, y: 0 } : {}}
      transition={{ duration, delay }}
      className={className}
    >
      {children}
    </motion.div>
  );
};

export default FadeIn;

```

FILE: src/components/animations/StaggerChildren.jsx

```

import React from 'react';
import { motion } from 'framer-motion';

const StaggerChildren = ({ children, className = '', staggerDelay = 0.1, delayChildren = 0.2 }) => {
  const containerVariants = {
    hidden: { opacity: 0 },
    visible: {
      opacity: 1,
      transition: {
        staggerChildren: staggerDelay,
        delayChildren: delayChildren
      }
    }
  };

  const itemVariants = {
    hidden: { opacity: 0, y: 20 },
    visible: { opacity: 1, y: 0 }
  };

  return (
    <motion.div
      variants={containerVariants}
      initial="hidden"
      animate="visible"
      className={className}
    >
      {React.Children.map(children, child => (
        <motion.div variants={itemVariants}>
          {child}
        </motion.div>
      ))}
    </motion.div>
  );
};

export default StaggerChildren;

```

FILE: src/components/dashboard/ActivityItem.jsx

```

import React from 'react';
import { motion } from 'framer-motion';
import { PlayCircle, Download, Award, BookOpen, CheckCircle, Clock } from 'lucide-react';
import Badge from '../../ui/Badge';

const ActivityItem = ({ activity, time, type, details }) => {
  const icons = {

```

```

    lesson: PlayCircle,
    download: Download,
    achievement: Award,
    course: BookOpen,
    quiz: CheckCircle
  };

  const Icon = icons[type] || Clock;

  const colors = {
    lesson: 'text-blue-400 bg-blue-500/20',
    download: 'text-green-400 bg-green-500/20',
    achievement: 'text-purple-400 bg-purple-500/20',
    course: 'text-orange-400 bg-orange-500/20',
    quiz: 'text-yellow-400 bg-yellow-500/20'
  };

  return (
    <motion.div
      initial={{ opacity: 0, x: -20 }}
      animate={{ opacity: 1, x: 0 }}
      whileHover={{ x: 5 }}
      className="flex items-center space-x-3 p-4 glass rounded-xl hover:bg-white/5 transition-all"
    >
      <div className={`p-2 rounded-lg ${colors[type]}`>
        <Icon className="w-5 h-5" />
      </div>
      <div className="flex-1">
        <p className="text-sm font-medium">{activity}</p>
        {details && <p className="text-xs text-gray-500">{details}</p>}
      </div>
      <div className="text-right">
        <Badge variant="primary" size="sm">{time}</Badge>
      </div>
    </motion.div>
  );
};

export default ActivityItem;

```

FILE: src/components/dashboard/StatsCard.jsx

```

import React from 'react';
import { motion } from 'framer-motion';
import Card from '../ui/Card';

const StatsCard = ({ icon: Icon, label, value, change, color = 'blue', trend = 'up' }) => {
  const colors = {
    blue: 'from-blue-500 to-blue-600',
    purple: 'from-purple-500 to-purple-600',
    green: 'from-green-500 to-green-600',
    orange: 'from-orange-500 to-orange-600',
    red: 'from-red-500 to-red-600'
  };

  return (
    <motion.div
      whileHover={{ y: -5 }}
      transition={{ duration: 0.2 }}
    >
      <Card className="p-6">
        <div className="flex items-center justify-between mb-4">
          <div className={`p-3 bg-gradient-to-r ${colors[color]} rounded-xl shadow-lg`} >
            <Icon className="w-6 h-6 text-white" />
          </div>
          <div className="text-right">
            <div className="text-2xl font-bold gradient-text">{value}</div>
            <div className={`text-xs ${trend === 'up' ? 'text-green-400' : 'text-red-400'} flex items-center`} >
              {trend === 'up' ? '↑' : '↓'} {change}
            </div>
          </div>
        </div>
        <h3 className="text-gray-400 text-sm">{label}</h3>
      </Card>
    </motion.div>
  );
};

export default StatsCard;

```

FILE: src/components/layout/Footer.jsx

```

import React from 'react';
import { Link } from 'react-router-dom';

```

```

import { motion } from 'framer-motion';
import { Facebook, Twitter, Instagram, Github, Mail, MapPin, Phone, Heart } from 'lucide-react';

const Footer = () => {
  const currentYear = new Date().getFullYear();

  const footerLinks = {
    Platform: [
      { name: 'Courses', href: '/courses' },
      { name: 'Offline Learning', href: '/offline' },
      { name: 'AI Assistant', href: '/ai-assistant' },
      { name: 'Dashboard', href: '/dashboard' }
    ],
    Company: [
      { name: 'About Us', href: '/about' },
      { name: 'Blog', href: '#' },
      { name: 'Careers', href: '#' },
      { name: 'Press', href: '#' }
    ],
    Resources: [
      { name: 'Help Center', href: '#' },
      { name: 'Community', href: '#' },
      { name: 'Status', href: '#' },
      { name: 'API Docs', href: '#' }
    ],
    Legal: [
      { name: 'Privacy Policy', href: '#' },
      { name: 'Terms of Service', href: '#' },
      { name: 'Cookie Policy', href: '#' },
      { name: 'Security', href: '#' }
    ]
  };

  const socialIcons = [
    { icon: Twitter, href: '#', label: 'Twitter' },
    { icon: Facebook, href: '#', label: 'Facebook' },
    { icon: Instagram, href: '#', label: 'Instagram' },
    { icon: Github, href: '#', label: 'GitHub' }
  ];

  return (
    <footer className="bg-black/50 border-t border-white/10 mt-20">
      <div className="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 py-12">
        <div className="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-6 gap-8">
          { /* Brand Column */ }
          <div className="lg:col-span-2">
            <div className="flex items-center space-x-2 mb-4">
              <div className="w-10 h-10 bg-gradient-to-r from-blue-500 to-purple-500 rounded-xl" />
              <span className="text-2xl font-bold gradient-text">SmartLearn</span>
            </div>
            <p className="text-gray-400 mb-4 leading-relaxed">
              Empowering education through offline-first technology. Learn anywhere, anytime, without
              boundaries.
            </p>
            <div className="flex space-x-3">
              {socialIcons.map((social, index) => (
                <motion.a
                  key={index}
                  href={social.href}
                  whileHover={{ y: -3 }}
                  className="p-2 glass rounded-lg hover:bg-white/10 transition-colors"
                  aria-label={social.label}
                >
                  <social.icon className="w-5 h-5" />
                </motion.a>
              ))}
            </div>
          </div>
          { /* Links Columns */ }
          {Object.entries(footerLinks).map(([category, links]) => (
            <div key={category}>
              <h4 className="font-semibold mb-4 text-white">{category}</h4>
              <ul className="space-y-2">
                {links.map((link) => (
                  <li key={link.name}>
                    <Link
                      to={link.href}
                      className="text-gray-400 hover:text-white transition-colors text-sm"
                    >
                      {link.name}
                    </Link>
                  </li>
                ))}
              </ul>
            </div>
          ))}
        </div>
      </div>
    </footer>
  );
};

```

```

</div>

{/* Contact Info */}
<div className="grid md:grid-cols-3 gap-4 mt-8 pt-8 border-t border-white/10">
  <div className="flex items-center space-x-3 text-gray-400">
    <Mail className="w-5 h-5" />
    <span className="text-sm">support@smartlearn.com</span>
  </div>
  <div className="flex items-center space-x-3 text-gray-400">
    <Phone className="w-5 h-5" />
    <span className="text-sm">+1 (555) 123-4567</span>
  </div>
  <div className="flex items-center space-x-3 text-gray-400">
    <MapPin className="w-5 h-5" />
    <span className="text-sm">San Francisco, CA</span>
  </div>
</div>

{/* Copyright */}
<div className="mt-8 pt-8 border-t border-white/10 text-center text-gray-400 text-sm">
  <p>
    © {currentYear} SmartLearn. All rights reserved.
    Made with <Heart className="w-4 h-4 inline text-red-500 animate-pulse" /> for learners worldwide.
  </p>
</div>
</div>
</footer>
);
};

export default Footer;

```

FILE: src/components/layout/Navbar.jsx

```

import React, { useState, useEffect } from 'react';
import { Link, useNavigate, useLocation } from 'react-router-dom';
import { motion, AnimatePresence } from 'framer-motion';
import {
  Menu, X, BookOpen, User, Sun, Moon, Bell,
  Search, Download, Sparkles, Home, LayoutDashboard,
  Info, Logout, Settings, UserCircle, ChevronDown,
  Brain, Award
} from 'lucide-react';

// Simple theme context
const useTheme = () => {
  const [darkMode, setDarkMode] = React.useState(true);
  React.useEffect(() => {
    if (darkMode) {
      document.documentElement.classList.add('dark');
    } else {
      document.documentElement.classList.remove('dark');
    }
  }, [darkMode]);
  return { darkMode, toggleDarkMode: () => setDarkMode(!darkMode) };
};

// Simple auth context
const useAuth = () => {
  const [user, setUser] = React.useState(null);
  React.useEffect(() => {
    const savedUser = localStorage.getItem('user');
    if (savedUser) setUser(JSON.parse(savedUser));
  }, []);
  const logout = () => {
    setUser(null);
    localStorage.removeItem('user');
  };
  return { user, logout };
};

const Navbar = () => {
  const [isScrolled, setIsScrolled] = useState(false);
  const [isMobileMenuOpen, setIsMobileMenuOpen] = useState(false);
  const [isSearchOpen, setIsSearchOpen] = useState(false);
  const [isProfileOpen, setIsProfileOpen] = useState(false);
  const { darkMode, toggleDarkMode } = useTheme();
  const { user, logout } = useAuth();
  const navigate = useNavigate();
  const location = useLocation();

  useEffect(() => {
    const handleScroll = () => setIsScrolled(window.scrollY > 20);
    window.addEventListener('scroll', handleScroll);
    return () => window.removeEventListener('scroll', handleScroll);
  }, []);

```

```

useEffect(() => {
  setIsMobileMenuOpen(false);
  setIsProfileOpen(false);
}, [location]);

// ALL NAVIGATION LINKS - Complete list
const navLinks = [
  { to: '/', label: 'Home', icon: Home },
  { to: '/dashboard', label: 'Dashboard', icon: LayoutDashboard },
  { to: '/courses', label: 'Courses', icon: BookOpen },
  { to: '/offline', label: 'Offline', icon: Download },
  { to: '/ai-assistant', label: 'AI Assistant', icon: Brain },
  { to: '/about', label: 'About', icon: Info }
];

const handleLogout = () => {
  logout();
  navigate('/');
  setIsProfileOpen(false);
};

return (
  <>
    <motion.nav
      initial={{ y: -100 }}
      animate={{ y: 0 }}
      className={`fixed top-0 left-0 right-0 z-50 transition-all duration-300 ${
        isScrolled ? 'bg-black/80 backdrop-blur-lg border-b border-white/10' : 'bg-transparent'
      }`}
    >
      <div className="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8">
        <div className="flex justify-between items-center h-16 md:h-20">
          {/* Logo */}
          <Link to="/" className="flex items-center space-x-2 group z-10">
            <motion.div
              whileHover={{ rotate: 360 }}
              transition={{ duration: 0.5 }}
              className="w-8 h-8 md:w-10 md:h-10 bg-gradient-to-r from-blue-500 to-purple-500 rounded-lg md:rounded-xl"
            />
            <span className="text-lg md:text-xl font-bold bg-gradient-to-r from-blue-500 to-purple-500 bg-clip-text text-transparent">
              SmartLearn
            </span>
          </Link>

          {/* Desktop Navigation - ALL LINKS SHOWN HERE */}
          <div className="hidden lg:flex items-center space-x-1">
            {navLinks.map((link) => (
              <Link
                key={link.to}
                to={link.to}
                className={`flex items-center space-x-2 px-3 py-2 rounded-lg transition-all duration-200 text-sm
                  ${location.pathname === link.to
                    ? 'bg-gradient-to-r from-blue-600/20 to-purple-600/20 text-white'
                    : 'text-gray-300 hover:text-white hover:bg-white/10'
                  }`}
              >
                <link.icon className="w-4 h-4" />
                <span>{link.label}</span>
              </Link>
            ))}
          </div>

          {/* Right side actions */}
          <div className="flex items-center space-x-1 sm:space-x-2 md:space-x-3">
            {/* Search Button */}
            <button
              onClick={() => setIsSearchOpen(true)}
              className="p-2 rounded-lg hover:bg-white/10 transition-colors"
            >
              <Search className="w-4 h-4 md:w-5 md:h-5" />
            </button>

            {/* Notifications */}
            <button className="p-2 rounded-lg hover:bg-white/10 transition-colors relative">
              <Bell className="w-4 h-4 md:w-5 md:h-5" />
              <span className="absolute top-1 right-1 w-2 h-2 bg-red-500 rounded-full" />
            </button>

            {/* Theme Toggle */}
            <button
              onClick={toggleDarkMode}
              className="p-2 rounded-lg hover:bg-white/10 transition-colors"
            >
              {darkMode ? <Sun className="w-4 h-4 md:w-5 md:h-5" /> : <Moon className="w-4 h-4 md:w-5

```

```

        md:h-5" />}
    </button>

    {/* User Menu */}
    {user ? (
        <div className="relative hidden lg:block">
            <button
                onClick={() => setIsProfileOpen(!isProfileOpen)}
                className="flex items-center space-x-2 p-2 rounded-lg hover:bg-white/10 transition-colors"
            >
                <div className="w-8 h-8 bg-gradient-to-r from-blue-500 to-purple-500 rounded-full flex
                    items-center justify-center">
                    <User className="w-4 h-4" />
                </div>
                <span className="text-sm hidden xl:inline">{user.name?.split(' ')[0] || 'User'}</span>
                <ChevronDown className="w-4 h-4" />
            </button>

            <AnimatePresence>
                {isProfileOpen && (
                    <motion.div
                        initial={{ opacity: 0, y: -10 }}
                        animate={{ opacity: 1, y: 0 }}
                        exit={{ opacity: 0, y: -10 }}
                        className="absolute right-0 mt-2 w-56 bg-black/90 backdrop-blur-lg rounded-xl border
                            border-white/10 shadow-xl z-50"
                    >
                        <div className="p-3 border-b border-white/10">
                            <p className="font-semibold">{user.name}</p>
                            <p className="text-xs text-gray-400 truncate">{user.email}</p>
                        </div>
                        <Link to="/profile" className="flex items-center px-4 py-2 hover:bg-white/10
                            transition-colors">
                            <UserCircle className="w-4 h-4 mr-2" />
                            Profile
                        </Link>
                        <Link to="/settings" className="flex items-center px-4 py-2 hover:bg-white/10
                            transition-colors">
                            <Settings className="w-4 h-4 mr-2" />
                            Settings
                        </Link>
                        <button
                            onClick={handleLogout}
                            className="flex items-center w-full px-4 py-2 hover:bg-white/10 transition-colors
                                text-red-400"
                        >
                            <Logout className="w-4 h-4 mr-2" />
                            Logout
                        </button>
                    </motion.div>
                )}
            </AnimatePresence>
        </div>
    ) : (
        <div className="hidden md:flex items-center space-x-2">
            <Link to="/login">
                <button className="px-3 py-1.5 md:px-4 md:py-2 rounded-lg text-sm hover:bg-white/10
                    transition-colors">
                    Login
                </button>
            </Link>
            <Link to="/register">
                <button className="px-3 py-1.5 md:px-4 md:py-2 bg-gradient-to-r from-blue-600
                    to-purple-600 rounded-lg text-sm font-semibold">
                    Sign Up
                </button>
            </Link>
        </div>
    )}

    {/* Mobile Menu Button */}
    <button
        onClick={() => setIsMobileMenuOpen(!isMobileMenuOpen)}
        className="lg:hidden p-2 rounded-lg hover:bg-white/10 transition-colors"
    >
        {isMobileMenuOpen ? <X className="w-5 h-5" /> : <Menu className="w-5 h-5" />}
    </button>
</div>
</div>
</div>

{/* Mobile Menu - ALL LINKS HERE */}
<AnimatePresence>
    {isMobileMenuOpen && (
        <motion.div
            initial={{ opacity: 0, height: 0 }}
            animate={{ opacity: 1, height: 'auto' }}

```

```

    exit={{ opacity: 0, height: 0 }}
    className="lg:hidden bg-black/90 backdrop-blur-lg border-b border-white/10 overflow-hidden"
  >
  <div className="px-4 py-3 space-y-1">
    {navLinks.map((link) => (
      <Link
        key={link.to}
        to={link.to}
        onClick={() => setIsMobileMenuOpen(false)}
        className={`flex items-center space-x-3 px-3 py-3 rounded-lg transition-colors
          ${location.pathname === link.to
            ? 'bg-gradient-to-r from-blue-600/20 to-purple-600/20 text-white'
            : 'text-gray-300 hover:text-white hover:bg-white/10'}
          `}
      >
        <link.icon className="w-5 h-5" />
        <span className="flex-1">{link.label}</span>
      </Link>
    ))}

    {!user ? (
      <div className="pt-3 space-y-2">
        <Link to="/login" onClick={() => setIsMobileMenuOpen(false)}>
          <button className="w-full px-4 py-3 bg-white/5 rounded-lg text-center">
            Login
          </button>
        </Link>
        <Link to="/register" onClick={() => setIsMobileMenuOpen(false)}>
          <button className="w-full px-4 py-3 bg-gradient-to-r from-blue-600 to-purple-600
            rounded-lg text-center font-semibold">
            Sign Up
          </button>
        </Link>
      </div>
    ) : (
      <div className="pt-3 space-y-2">
        <Link to="/profile" onClick={() => setIsMobileMenuOpen(false)}>
          <button className="w-full px-4 py-3 bg-white/5 rounded-lg text-center flex items-center
            justify-center space-x-2">
            <UserCircle className="w-4 h-4" />
            <span>Profile</span>
          </button>
        </Link>
        <Link to="/settings" onClick={() => setIsMobileMenuOpen(false)}>
          <button className="w-full px-4 py-3 bg-white/5 rounded-lg text-center flex items-center
            justify-center space-x-2">
            <Settings className="w-4 h-4" />
            <span>Settings</span>
          </button>
        </Link>
        <button
          onClick={handleLogout}
          className="w-full px-4 py-3 bg-white/5 rounded-lg text-center text-red-400 flex
            items-center justify-center space-x-2"
        >
          <LogOut className="w-4 h-4" />
          <span>Logout</span>
        </button>
      </div>
    )}
  </div>
</motion.div>
)}
</AnimatePresence>
</motion.nav>

{/* Search Modal */}
<AnimatePresence>
  {isSearchOpen && (
    <motion.div
      initial={{ opacity: 0 }}
      animate={{ opacity: 1 }}
      exit={{ opacity: 0 }}
      className="fixed inset-0 bg-black/90 backdrop-blur-md z-50 flex items-start justify-center p-4"
      onClick={() => setIsSearchOpen(false)}
    >
      <motion.div
        initial={{ scale: 0.9, y: -20 }}
        animate={{ scale: 1, y: 0 }}
        exit={{ scale: 0.9, y: -20 }}
        className="w-full max-w-lg md:max-w-2xl mt-20"
        onClick={(e) => e.stopPropagation()}
      >
        <div className="bg-white/5 backdrop-blur-lg rounded-2xl border border-white/10 p-4">
          <div className="flex items-center space-x-3">
            <Search className="w-5 h-5 text-gray-400 flex-shrink-0" />
            <input

```

```

        type="text"
        placeholder="Search courses, lessons, or topics..."
        className="flex-1 bg-transparent outline-none text-white text-sm md:text-base"
        autoFocus
      />
      <button onClick={() => setIsSearchOpen(false)} className="p-1">
        <X className="w-5 h-5" />
      </button>
    </div>
    <div className="mt-4 pt-4 border-t border-white/10">
      <p className="text-xs text-gray-400">Popular searches:</p>
      <div className="flex flex-wrap gap-2 mt-2">
        <span className="px-2 py-1 bg-white/5 rounded-lg text-xs">React</span>
        <span className="px-2 py-1 bg-white/5 rounded-lg text-xs">Machine Learning</span>
        <span className="px-2 py-1 bg-white/5 rounded-lg text-xs">UI/UX Design</span>
      </div>
    </div>
  </motion.div>
</motion.div>
  )}
</AnimatePresence>
</>
);
};

export default Navbar;

```

FILE: src/components/layout/Sidebar.jsx

```

import React from 'react';
import { NavLink } from 'react-router-dom';
import { motion, AnimatePresence } from 'framer-motion';
import {
  LayoutDashboard, BookOpen, Download, Brain, User, Settings,
  TrendingUp, Award, Calendar, HelpCircle, Logout, Star
} from 'lucide-react';
import { useAuth } from '../../../context/AuthContext';
import Button from '../../ui/Button';

const Sidebar = ({ isOpen, onClose }) => {
  const { user, logout } = useAuth();

  const navItems = [
    { to: '/dashboard', icon: LayoutDashboard, label: 'Dashboard' },
    { to: '/courses', icon: BookOpen, label: 'Courses' },
    { to: '/offline', icon: Download, label: 'Offline Learning' },
    { to: '/ai-assistant', icon: Brain, label: 'AI Assistant' },
    { to: '/profile', icon: User, label: 'Profile' },
    { to: '/settings', icon: Settings, label: 'Settings' }
  ];

  const quickStats = [
    { icon: TrendingUp, value: '15', label: 'Day Streak', color: 'orange' },
    { icon: Award, value: '8', label: 'Achievements', color: 'purple' },
    { icon: Star, value: '127h', label: 'Learned', color: 'blue' }
  ];

  return (
    <>
      { /* Mobile Overlay */ }
      <AnimatePresence>
        {isOpen && (
          <motion.div
            initial={{ opacity: 0 }}
            animate={{ opacity: 1 }}
            exit={{ opacity: 0 }}
            className="fixed inset-0 bg-black/50 z-40 lg:hidden"
            onClick={onClose}
          />
        )}
      </AnimatePresence>

      { /* Sidebar */ }
      <motion.aside
        initial={{ x: -280 }}
        animate={{ x: isOpen ? 0 : -280 }}
        transition={{ type: 'spring', damping: 20 }}
        className={`fixed left-0 top-0 h-full w-72 glass border-r border-white/10 z-50
          ${isOpen ? 'block' : 'hidden lg:block'}`}
      >
        <div className="flex flex-col h-full">
          { /* Logo */ }
          <div className="p-6 border-b border-white/10">
            <div className="flex items-center space-x-2">
              <div className="w-10 h-10 bg-gradient-to-r from-blue-500 to-purple-500 rounded-xl" />

```

```

    <div>
      <span className="text-xl font-bold gradient-text">SmartLearn</span>
      <p className="text-xs text-gray-400">Offline Learning</p>
    </div>
  </div>
</div>

{/* User Info */}
{user && (
  <div className="p-4 border-b border-white/10">
    <div className="flex items-center space-x-3">
      <div className="w-10 h-10 bg-gradient-to-r from-blue-500 to-purple-500 rounded-full flex
        items-center justify-center">
        <span className="text-lg font-bold">{user.name[0]}</span>
      </div>
      <div>
        <p className="font-semibold">{user.name}</p>
        <p className="text-xs text-gray-400">{user.email}</p>
      </div>
    </div>
  </div>
)}

{/* Navigation */}
<nav className="flex-1 p-4 space-y-1 overflow-y-auto">
  {navItems.map((item) => (
    <NavLink
      key={item.to}
      to={item.to}
      onClick={onClose}
      className={({ isActive }) => `
        flex items-center space-x-3 px-4 py-3 rounded-xl transition-all duration-200 group
        ${isActive
          ? 'bg-gradient-to-r from-blue-600/20 to-purple-600/20 text-white'
          : 'text-gray-400 hover:text-white hover:bg-white/5'}
      `}
    >
      <item.icon className="w-5 h-5 group-hover:scale-110 transition-transform" />
      <span className="flex-1">{item.label}</span>
      {item.to === '/offline' && (
        <span className="w-2 h-2 bg-green-500 rounded-full" />
      )}
    </NavLink>
  )
)}
</nav>

{/* Quick Stats */}
<div className="p-4 border-t border-white/10">
  <h4 className="text-xs font-semibold text-gray-400 mb-3 uppercase tracking-wider">Quick Stats</h4>
  <div className="space-y-3">
    {quickStats.map((stat, index) => (
      <div key={index} className="flex items-center justify-between">
        <div className="flex items-center space-x-2">
          <div className={`p-1.5 rounded-lg bg-${stat.color}-500/20`} >
            <stat.icon className={`w-3 h-3 text-${stat.color}-400`} />
          </div>
          <span className="text-sm text-gray-300">{stat.label}</span>
        </div>
        <span className="font-semibold text-sm">{stat.value}</span>
      </div>
    )
  )}
  </div>

  <div className="mt-4 space-y-2">
    <Button variant="outline" size="sm" className="w-full">
      <HelpCircle className="w-4 h-4 mr-2" />
      Help Center
    </Button>
    {user && (
      <Button variant="ghost" size="sm" className="w-full text-red-400 hover:text-red-300"
        onClick={logout}>
        <Logout className="w-4 h-4 mr-2" />
        Logout
      </Button>
    )}
  </div>
</div>
</div>
</motion.aside>
</>
);
};

export default Sidebar;

```

FILE: src/components/ui/Badge.jsx

```
import React from 'react';

const Badge = ({ children, variant = 'primary', className = '', size = 'md' }) => {
  const variants = {
    primary: 'bg-blue-500/20 text-blue-400 border-blue-500/30',
    success: 'bg-green-500/20 text-green-400 border-green-500/30',
    warning: 'bg-yellow-500/20 text-yellow-400 border-yellow-500/30',
    error: 'bg-red-500/20 text-red-400 border-red-500/30',
    purple: 'bg-purple-500/20 text-purple-400 border-purple-500/30'
  };

  const sizes = {
    sm: 'px-2 py-0.5 text-xs',
    md: 'px-2.5 py-1 text-sm',
    lg: 'px-3 py-1.5 text-base'
  };

  return (
    <span className={`inline-flex items-center rounded-full font-medium border ${variants[variant]} ${sizes[size]} ${className}`}>
      {children}
    </span>
  );
};

export default Badge;
```

FILE: src/components/ui/Button.jsx

```
import React from 'react';
import { motion } from 'framer-motion';

const Button = ({
  children,
  variant = 'primary',
  size = 'md',
  className = '',
  loading = false,
  disabled = false,
  ...props
}) => {
  const variants = {
    primary: 'bg-gradient-to-r from-blue-600 to-purple-600 text-white hover:shadow-lg',
    secondary: 'glass text-white hover:bg-white/10',
    outline: 'border border-white/20 text-white hover:bg-white/5',
    ghost: 'text-white hover:bg-white/5',
    danger: 'bg-red-600 text-white hover:bg-red-700'
  };

  const sizes = {
    sm: 'px-4 py-2 text-sm',
    md: 'px-6 py-3 text-base',
    lg: 'px-8 py-4 text-lg'
  };

  return (
    <motion.button
      whileHover={!disabled && !loading ? { scale: 1.05 } : {}}
      whileTap={!disabled && !loading ? { scale: 0.95 } : {}}
      className={`rounded-xl font-semibold transition-all duration-300 ${variants[variant]} ${sizes[size]} ${className} ${disabled || loading ? 'opacity-50 cursor-not-allowed' : ''}`}
      disabled={disabled || loading}
      {...props}
    >
      {loading ? (
        <div className="flex items-center justify-center">
          <div className="w-5 h-5 border-2 border-white border-t-transparent rounded-full animate-spin mr-2"/>
          Loading...
        </div>
      ) : children}
    </motion.button>
  );
};

export default Button;
```

FILE: src/components/ui/Card.jsx

```
import React from 'react';
```

```
import { motion } from 'framer-motion';

const Card = ({ children, className = '', hover = true, onClick }) => {
  return (
    <motion.div
      whileHover={hover ? { y: -5, scale: 1.02 } : {}}
      transition={{ duration: 0.2 }}
      className={`glass rounded-2xl overflow-hidden ${className}`}
      onClick={onClick}
    >
      {children}
    </motion.div>
  );
};

export default Card;
```

FILE: src/components/ui/Input.jsx

```
import React, { useState } from 'react';
import { motion } from 'framer-motion';
import { Eye, EyeOff } from 'lucide-react';

const Input = ({
  label,
  type = 'text',
  icon: Icon,
  error,
  className = '',
  required = false,
  ...props
}) => {
  const [showPassword, setShowPassword] = useState(false);
  const inputType = type === 'password' && showPassword ? 'text' : type;

  return (
    <motion.div
      className={`w-full ${className}`}
      initial={{ opacity: 0, y: 10 }}
      animate={{ opacity: 1, y: 0 }}
      transition={{ duration: 0.3 }}
    >
      {label && (
        <label className="block text-sm font-medium mb-2 text-gray-300">
          {label}
          {required && <span className="text-red-400 ml-1">*</span>}
        </label>
      )}
      <div className="relative">
        {Icon && (
          <Icon className="absolute left-3 top-1/2 transform -translate-y-1/2 w-5 h-5 text-gray-400" />
        )}
        <input
          type={inputType}
          className={`
            w-full
            ${Icon ? 'pl-10' : 'pl-4'}
            ${type === 'password' ? 'pr-12' : 'pr-4'}
            py-3
            glass
            rounded-xl
            focus:outline-none
            focus:ring-2
            focus:ring-blue-500
            transition-all
            duration-200
            ${error ? 'border-red-500 ring-1 ring-red-500' : ''}
          `}
          {...props}
        />
        {type === 'password' && (
          <button
            type="button"
            onClick={() => setShowPassword(!showPassword)}
            className="absolute right-3 top-1/2 transform -translate-y-1/2 text-gray-400 hover:text-white"
          >
            {showPassword ? <EyeOff className="w-5 h-5" /> : <Eye className="w-5 h-5" />}
          </button>
        )}
      </div>
      {error && (
        <motion.p
          initial={{ opacity: 0 }}
          animate={{ opacity: 1 }}
          className="text-red-400 text-sm mt-1"
        >
```

```

        {error}
      </motion.p>
    )}
  </motion.div>
);
};

export default Input;

```

FILE: src/components/ui/Modal.jsx

```

import React from 'react';
import { motion, AnimatePresence } from 'framer-motion';
import { X } from 'lucide-react';

const Modal = ({ isOpen, onClose, title, children, size = 'md', showClose = true }) => {
  const sizes = {
    sm: 'max-w-md',
    md: 'max-w-lg',
    lg: 'max-w-2xl',
    xl: 'max-w-4xl',
    full: 'max-w-6xl'
  };

  return (
    <AnimatePresence>
      {isOpen && (
        <>
          <motion.div
            initial={{ opacity: 0 }}
            animate={{ opacity: 1 }}
            exit={{ opacity: 0 }}
            className="fixed inset-0 bg-black/70 backdrop-blur-sm z-50"
            onClick={onClose}
          />
          <motion.div
            initial={{ opacity: 0, scale: 0.9, y: 20 }}
            animate={{ opacity: 1, scale: 1, y: 0 }}
            exit={{ opacity: 0, scale: 0.9, y: 20 }}
            className={`fixed left-1/2 top-1/2 transform -translate-x-1/2 -translate-y-1/2
              ${sizes[size]} w-full z-50 px-4`}
          >
            <div className="glass rounded-2xl overflow-hidden">
              <div className="flex justify-between items-center p-6 border-b border-white/10">
                <h2 className="text-xl font-semibold">{title}</h2>
                {showClose && (
                  <button
                    onClick={onClose}
                    className="p-1 hover:bg-white/10 rounded-lg transition-colors"
                  >
                    <X className="w-5 h-5" />
                  </button>
                )}
              </div>
              <div className="p-6 max-h-[70vh] overflow-y-auto">
                {children}
              </div>
            </div>
          </motion.div>
        </>
      )}
    </AnimatePresence>
  );
};

export default Modal;

```

FILE: src/components/ui/ProgressBar.jsx

```

import React from 'react';
import { motion } from 'framer-motion';

const ProgressBar = ({ progress, height = 'h-2', color = 'gradient', showLabel = false, label }) => {
  const colors = {
    gradient: 'bg-gradient-to-r from-blue-500 to-purple-500',
    blue: 'bg-blue-500',
    green: 'bg-green-500',
    orange: 'bg-orange-500',
    red: 'bg-red-500'
  };

  return (
    <div className="w-full">
      {showLabel && (
        <div className="flex justify-between text-sm mb-1">

```

```

    <span>{label || 'Progress'}</span>
    <span>{progress}%</span>
  </div>
)}
<div className={`w-full bg-white/10 rounded-full ${height} overflow-hidden`}>
  <motion.div
    initial={{ width: 0 }}
    animate={{ width: `${progress}%` }}
    transition={{ duration: 1, ease: "easeOut" }}
    className={`${colors[color]} ${height} rounded-full relative`}
  >
    {progress > 0 && (
      <div className="absolute inset-0 bg-white/20 animate-pulse" />
    )}
  </motion.div>
</div>
</div>
);
};

export default ProgressBar;

```

FILE: src/components/ui/Skeleton.jsx

```

import React from 'react';
import { motion } from 'framer-motion';

const Skeleton = ({ className = '', variant = 'rect' }) => {
  const variants = {
    rect: 'rounded-lg',
    circle: 'rounded-full',
    text: 'rounded'
  };

  return (
    <motion.div
      initial={{ opacity: 0.5 }}
      animate={{ opacity: 1 }}
      transition={{ duration: 0.5, repeat: Infinity, repeatType: 'reverse' }}
      className={`bg-gradient-to-r from-gray-800 via-gray-700 to-gray-800 shimmer ${variants[variant]} ${className}`}
    />
  );
};

export const SkeletonCard = () => {
  return (
    <div className="glass rounded-2xl p-4">
      <Skeleton className="w-full h-48 mb-4" />
      <Skeleton className="w-3/4 h-4 mb-2" />
      <Skeleton className="w-1/2 h-4 mb-4" />
      <Skeleton className="w-full h-10" />
    </div>
  );
};

export const SkeletonText = ({ lines = 3 }) => {
  return (
    <div className="space-y-2">
      {[...Array(lines)].map((_, i) => (
        <Skeleton key={i} className={`h-4 ${i === 0 ? 'w-3/4' : 'w-full'}`} />
      ))}
    </div>
  );
};

export default Skeleton;

```

FILE: src/components/ui/Tooltip.jsx

```

import React, { useState } from 'react';
import { motion, AnimatePresence } from 'framer-motion';

const Tooltip = ({ children, content, position = 'top', delay = 200 }) => {
  const [isVisible, setIsVisible] = useState(false);
  let timeoutId;

  const positions = {
    top: 'bottom-full left-1/2 transform -translate-x-1/2 mb-2',
    bottom: 'top-full left-1/2 transform -translate-x-1/2 mt-2',
    left: 'right-full top-1/2 transform -translate-y-1/2 mr-2',
    right: 'left-full top-1/2 transform -translate-y-1/2 ml-2'
  };

  const arrows = {

```

```

    top: 'bottom-[-4px] left-1/2 -translate-x-1/2 border-t-gray-900',
    bottom: 'top-[-4px] left-1/2 -translate-x-1/2 border-b-gray-900',
    left: 'right-[-4px] top-1/2 -translate-y-1/2 border-l-gray-900',
    right: 'left-[-4px] top-1/2 -translate-y-1/2 border-r-gray-900'
  };

  const handleMouseEnter = () => {
    timeoutId = setTimeout(() => setIsVisible(true), delay);
  };

  const handleMouseLeave = () => {
    clearTimeout(timeoutId);
    setIsVisible(false);
  };

  return (
    <div
      className="relative inline-block"
      onMouseEnter={handleMouseEnter}
      onMouseLeave={handleMouseLeave}
    >
      {children}
      <AnimatePresence>
        {isVisible && (
          <motion.div
            initial={{ opacity: 0, scale: 0.8, y: position === 'top' ? 10 : position === 'bottom' ? -10 : 0 }}
            animate={{ opacity: 1, scale: 1, y: 0 }}
            exit={{ opacity: 0, scale: 0.8 }}
            className={`absolute z-50 ${positions[position]} whitespace-nowrap`}
          >
            <div className="bg-gray-900 text-white text-sm px-3 py-1.5 rounded-lg shadow-lg border border-gray-700">
              {content}
              <div className={`absolute w-2 h-2 bg-gray-900 transform rotate-45 ${arrows[position]}`} />
            </div>
          </motion.div>
        )}
      </AnimatePresence>
    </div>
  );
};

export default Tooltip;

```

FILE: src/context/AuthContext.jsx

```

import React, { createContext, useContext, useState, useEffect } from 'react';

const AuthContext = createContext();

export const useAuth = () => {
  const context = useContext(AuthContext);
  if (!context) {
    throw new Error('useAuth must be used within AuthProvider');
  }
  return context;
};

export const AuthProvider = ({ children }) => {
  const [user, setUser] = useState(null);
  const [loading, setLoading] = useState(true);

  useEffect(() => {
    const savedUser = localStorage.getItem('user');
    if (savedUser) {
      setUser(JSON.parse(savedUser));
    }
    setLoading(false);
  }, []);

  const login = (email, password) => {
    return new Promise((resolve) => {
      setTimeout(() => {
        const user = {
          id: 1,
          email,
          name: 'John Doe',
          avatar: 'https://images.unsplash.com/photo-1472099645785-5658abf4ff4e',
          joinedDate: new Date().toISOString()
        };
        setUser(user);
        localStorage.setItem('user', JSON.stringify(user));
        resolve(true);
      }, 500);
    });
  };
};

```

```

const logout = () => {
  setUser(null);
  localStorage.removeItem('user');
};

const register = (name, email, password) => {
  return new Promise((resolve) => {
    setTimeout(() => {
      const user = {
        id: 1,
        email,
        name,
        avatar: 'https://images.unsplash.com/photo-1472099645785-5658abf4ff4e',
        joinedDate: new Date().toISOString()
      };
      setUser(user);
      localStorage.setItem('user', JSON.stringify(user));
      resolve(true);
    }, 500);
  });
};

return (
  <AuthContext.Provider value={{ user, loading, login, logout, register }}>
    {children}
  </AuthContext.Provider>
);
};

```

FILE: src/context/ThemeContext.jsx

```

import React, { createContext, useContext, useState, useEffect } from 'react';

const ThemeContext = createContext();

export const useTheme = () => {
  const context = useContext(ThemeContext);
  if (!context) {
    throw new Error('useTheme must be used within ThemeProvider');
  }
  return context;
};

export const ThemeProvider = ({ children }) => {
  const [darkMode, setDarkMode] = useState(() => {
    const saved = localStorage.getItem('darkMode');
    return saved !== null ? JSON.parse(saved) : true;
  });

  useEffect(() => {
    localStorage.setItem('darkMode', JSON.stringify(darkMode));
    if (darkMode) {
      document.documentElement.classList.add('dark');
    } else {
      document.documentElement.classList.remove('dark');
    }
  }, [darkMode]);

  const toggleDarkMode = () => setDarkMode(!darkMode);

  return (
    <ThemeContext.Provider value={{ darkMode, toggleDarkMode }}>
      {children}
    </ThemeContext.Provider>
  );
};

```

FILE: src/data/mockData.js

```

export const courses = [
  {
    id: 1,
    title: "Advanced React & Modern Web Development",
    instructor: "Sarah Johnson",
    instructorAvatar: "https://images.unsplash.com/photo-1494790108377-be9c29b29330",
    duration: "8 hours",
    progress: 45,
    thumbnail: "https://images.unsplash.com/photo-1633356122544-f134324a6cee",
    category: "Development",
    isDownloaded: true,
    lessons: 24,
    level: "Advanced",
    rating: 4.9,
    students: 12453,
    description: "Master React with hooks, context API, and modern best practices. Build real-world

```

```

    applications.",
    whatYouLearn: [
        "React Hooks in depth",
        "Context API for state management",
        "Performance optimization",
        "Testing React applications",
        "Deployment strategies"
    ],
    requirements: [
        "Basic JavaScript knowledge",
        "HTML/CSS fundamentals",
        "Computer with internet"
    ]
},
{
    id: 2,
    title: "Machine Learning Fundamentals",
    instructor: "Dr. Michael Chen",
    instructorAvatar: "https://images.unsplash.com/photo-1507003211169-0a1dd7228f2d",
    duration: "12 hours",
    progress: 20,
    thumbnail: "https://images.unsplash.com/photo-1555949963-ff9fe0c870eb",
    category: "AI & ML",
    isDownloaded: false,
    lessons: 36,
    level: "Intermediate",
    rating: 4.8,
    students: 8942,
    description: "Learn machine learning algorithms and real-world applications with Python.",
    whatYouLearn: [
        "Supervised learning",
        "Unsupervised learning",
        "Neural networks",
        "Model evaluation",
        "Real-world projects"
    ],
    requirements: [
        "Python basics",
        "Basic math knowledge",
        "Curiosity for AI"
    ]
},
{
    id: 3,
    title: "UI/UX Design Mastery",
    instructor: "Emma Rodriguez",
    instructorAvatar: "https://images.unsplash.com/photo-1534528741775-53994a69daeb",
    duration: "6 hours",
    progress: 80,
    thumbnail: "https://images.unsplash.com/photo-1561070791-2526d30994b5",
    category: "Design",
    isDownloaded: true,
    lessons: 18,
    level: "Beginner",
    rating: 4.7,
    students: 15234,
    description: "Design beautiful and functional user interfaces that users love.",
    whatYouLearn: [
        "Design principles",
        "Color theory",
        "Typography",
        "Wireframing",
        "Prototyping"
    ],
    requirements: [
        "No prior design experience",
        "Creativity",
        "Figma (free tool)"
    ]
},
{
    id: 4,
    title: "Data Science & Analytics",
    instructor: "Prof. James Wilson",
    instructorAvatar: "https://images.unsplash.com/photo-1472099645785-5658abf4ff4e",
    duration: "15 hours",
    progress: 10,
    thumbnail: "https://images.unsplash.com/photo-1551288049-bebda4e38f71",
    category: "Data Science",
    isDownloaded: false,
    lessons: 42,
    level: "Advanced",
    rating: 4.9,
    students: 6734,
    description: "Complete data science bootcamp with Python, pandas, and scikit-learn.",
    whatYouLearn: [
        "Data cleaning",

```

```

    "Data visualization",
    "Statistical analysis",
    "Machine learning",
    "Big data tools"
  ],
  requirements: [
    "Python programming",
    "Statistics basics",
    "Analytical mindset"
  ]
},
{
  id: 5,
  title: "Cloud Computing with AWS",
  instructor: "Alex Thompson",
  instructorAvatar: "https://images.unsplash.com/photo-1500648767791-00dcc994a43e",
  duration: "10 hours",
  progress: 0,
  thumbnail: "https://images.unsplash.com/photo-1451187580459-43490279c0fa",
  category: "Cloud",
  isDownloaded: false,
  lessons: 30,
  level: "Intermediate",
  rating: 4.8,
  students: 5231,
  description: "Master AWS services and cloud architecture for modern applications.",
  whatYouLearn: [
    "EC2 and S3",
    "Lambda functions",
    "Database services",
    "Security best practices",
    "Cost optimization"
  ],
  requirements: [
    "Basic IT knowledge",
    "Command line experience",
    "AWS free tier account"
  ]
},
{
  id: 6,
  title: "Cybersecurity Essentials",
  instructor: "Lisa Wang",
  instructorAvatar: "https://images.unsplash.com/photo-1544005313-94ddf0286df2",
  duration: "9 hours",
  progress: 0,
  thumbnail: "https://images.unsplash.com/photo-1550751827-4bd374c3f58b",
  category: "Security",
  isDownloaded: false,
  lessons: 28,
  level: "Beginner",
  rating: 4.9,
  students: 7823,
  description: "Learn cybersecurity fundamentals and protect digital assets.",
  whatYouLearn: [
    "Network security",
    "Cryptography",
    "Threat detection",
    "Security audits",
    "Incident response"
  ],
  requirements: [
    "Basic computer knowledge",
    "Interest in security",
    "Ethical mindset"
  ]
}
];

export const recentActivities = [
  { id: 1, activity: "Completed 'React Hooks' lesson", time: "2 hours ago", type: "lesson", details: "Advanced React Course" },
  { id: 2, activity: "Downloaded 'Machine Learning' course", time: "1 day ago", type: "download", details: "2.4 GB" },
  { id: 3, activity: "Earned '7 Day Streak' badge", time: "2 days ago", type: "achievement", details: "Keep it up!" },
  { id: 4, activity: "Started 'UI Design' course", time: "3 days ago", type: "course", details: "Lesson 1 completed" },
  { id: 5, activity: "Completed quiz with 95% score", time: "5 days ago", type: "achievement", details: "JavaScript Fundamentals" },
  { id: 6, activity: "Shared certificate on LinkedIn", time: "1 week ago", type: "achievement", details: "React Certification" }
];

export const statistics = {
  totalHours: 127,
  completedCourses: 8,

```

```

    streakDays: 15,
    downloadedLessons: 28,
    quizzesTaken: 24,
    averageScore: 85,
    certificatesEarned: 3,
    totalCourses: 12
  };

export const testimonials = [
  {
    id: 1,
    name: "Alex Thompson",
    role: "Computer Science Student",
    content: "This platform changed how I learn. Offline access is a game-changer! I can study anywhere without worrying about internet.",
    avatar: "https://images.unsplash.com/photo-1472099645785-5658abf4ff4e",
    rating: 5,
    course: "React Development"
  },
  {
    id: 2,
    name: "Maria Garcia",
    role: "Web Developer",
    content: "The AI study assistant is incredibly helpful. Best learning investment ever. The personalized recommendations are spot on!",
    avatar: "https://images.unsplash.com/photo-1494790108377-be9c29b29330",
    rating: 5,
    course: "UI/UX Design"
  },
  {
    id: 3,
    name: "David Kim",
    role: "Data Scientist",
    content: "Finally a platform that understands offline learning needs. The progress sync is flawless and the content is top-notch.",
    avatar: "https://images.unsplash.com/photo-1507003211169-0a1dd7228f2d",
    rating: 5,
    course: "Data Science"
  }
];

export const weeklyData = [
  { day: "Mon", hours: 2.5, lessons: 3 },
  { day: "Tue", hours: 3.5, lessons: 4 },
  { day: "Wed", hours: 2, lessons: 2 },
  { day: "Thu", hours: 4, lessons: 5 },
  { day: "Fri", hours: 3, lessons: 3 },
  { day: "Sat", hours: 1.5, lessons: 2 },
  { day: "Sun", hours: 2, lessons: 2 }
];

export const categories = [
  "All",
  "Development",
  "AI & ML",
  "Design",
  "Data Science",
  "Cloud",
  "Security",
  "Business",
  "Marketing"
];

export const achievements = [
  { id: 1, title: "Early Bird", description: "Complete 5 lessons before noon", points: 100, icon: "■", completed: true },
  { id: 2, title: "Night Owl", description: "Study after 10 PM", points: 100, icon: "■", completed: true },
  { id: 3, title: "Speed Demon", description: "Complete a course in 7 days", points: 200, icon: "■", completed: false },
  { id: 4, title: "Perfect Score", description: "Get 100% on a quiz", points: 150, icon: "■", completed: true },
  { id: 5, title: "Social Butterfly", description: "Share 5 certificates", points: 100, icon: "■", completed: false }
];

```