

project_bundle.txt - Part 2 of 3

Created: 2026-05-19 00:04:45

FILE: src/hooks/useClickOutside.js

```
import { useEffect, useRef } from 'react';

export const useClickOutside = (handler) => {
  const ref = useRef(null);

  useEffect(() => {
    const listener = (event) => {
      if (!ref.current || ref.current.contains(event.target)) {
        return;
      }
      handler(event);
    };

    document.addEventListener('mousedown', listener);
    document.addEventListener('touchstart', listener);

    return () => {
      document.removeEventListener('mousedown', listener);
      document.removeEventListener('touchstart', listener);
    };
  }, [handler]);

  return ref;
};
```

FILE: src/hooks/useDebounce.js

```
import { useState, useEffect } from 'react';

export const useDebounce = (value, delay = 500) => {
  const [debouncedValue, setDebouncedValue] = useState(value);

  useEffect(() => {
    const handler = setTimeout(() => {
      setDebouncedValue(value);
    }, delay);

    return () => {
      clearTimeout(handler);
    };
  }, [value, delay]);

  return debouncedValue;
};
```

FILE: src/hooks/useLocalStorage.js

```
import { useState, useEffect } from 'react';

export const useLocalStorage = (key, initialValue) => {
  const [storedValue, setStoredValue] = useState(() => {
    try {
      const item = window.localStorage.getItem(key);
      return item ? JSON.parse(item) : initialValue;
    } catch (error) {
      console.log(error);
      return initialValue;
    }
  });

  const setValue = (value) => {
    try {
      const valueToStore = value instanceof Function ? value(storedValue) : value;
      setStoredValue(valueToStore);
      window.localStorage.setItem(key, JSON.stringify(valueToStore));
    } catch (error) {
      console.log(error);
    }
  };

  return [storedValue, setValue];
};

export const useLocalStorageWithExpiry = (key, initialValue, expiryMs) => {
  const [storedValue, setStoredValue] = useState(() => {
    try {

```

```

const item = window.localStorage.getItem(key);
if (item) {
  const { value, expiry } = JSON.parse(item);
  if (expiry && Date.now() > expiry) {
    window.localStorage.removeItem(key);
    return initialValue;
  }
  return value;
}
return initialValue;
} catch (error) {
  return initialValue;
}
});

const setValue = (value) => {
  try {
    const valueToStore = value instanceof Function ? value(storedValue) : value;
    setStoredValue(valueToStore);
    const item = {
      value: valueToStore,
      expiry: Date.now() + expiryMs
    };
    window.localStorage.setItem(key, JSON.stringify(item));
  } catch (error) {
    console.log(error);
  }
};

return [storedValue, setValue];
};

```

FILE: src/hooks/useOnlineStatus.js

```

import { useState, useEffect } from 'react';

export const useOnlineStatus = () => {
  const [isOnline, setIsOnline] = useState(navigator.onLine);
  const [wasOffline, setWasOffline] = useState(false);

  useEffect(() => {
    const handleOnline = () => {
      setIsOnline(true);
      setWasOffline(true);
      setTimeout(() => setWasOffline(false), 3000);
    };

    const handleOffline = () => setIsOnline(false);

    window.addEventListener('online', handleOnline);
    window.addEventListener('offline', handleOffline);

    return () => {
      window.removeEventListener('online', handleOnline);
      window.removeEventListener('offline', handleOffline);
    };
  }, []);

  return { isOnline, wasOffline };
};

```

FILE: src/pages/About/About.jsx

```

import React from 'react';
import { Target, Heart, Users, Zap } from 'lucide-react';

const About = () => {
  const values = [
    { icon: Target, title: "Our Mission", description: "Make quality education accessible to everyone, everywhere" },
    { icon: Heart, title: "Our Values", description: "Student-first approach with focus on learning outcomes" },
    { icon: Users, title: "Community", description: "Join thousands of learners worldwide" },
    { icon: Zap, title: "Innovation", description: "Cutting-edge technology for better learning" }
  ];

  return (
    <div className="min-h-screen pb-20">
      <div className="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 py-8">
        <div className="text-center mb-12">
          <h1 className="text-4xl md:text-5xl font-bold mb-4">
            About <span className="gradient-text">SmartLearn</span>
          </h1>
          <p className="text-xl text-gray-400 max-w-2xl mx-auto">
            Revolutionizing education through offline-first technology
          </p>
        </div>
      </div>
    </div>
  );
};

```

```

    </p>
  </div>

  <div className="grid md:grid-cols-2 gap-8 mb-12">
    <div className="glass rounded-2xl p-8">
      <h2 className="text-2xl font-semibold mb-4">Our Story</h2>
      <p className="text-gray-300 mb-4">
        Founded in 2024, SmartLearn was born from a simple idea: education shouldn't be limited by
        internet connectivity.
      </p>
      <p className="text-gray-300">
        We've helped over 50,000 students worldwide continue their learning journey, even in areas with
        unreliable internet access.
      </p>
    </div>

    <div className="glass rounded-2xl p-8">
      <h2 className="text-2xl font-semibold mb-4">Our Impact</h2>
      <div className="grid grid-cols-2 gap-4">
        <div>
          <div className="text-3xl font-bold gradient-text">50K+</div>
          <div className="text-sm text-gray-400">Active Students</div>
        </div>
        <div>
          <div className="text-3xl font-bold gradient-text">200+</div>
          <div className="text-sm text-gray-400">Expert Instructors</div>
        </div>
        <div>
          <div className="text-3xl font-bold gradient-text">1M+</div>
          <div className="text-sm text-gray-400">Hours Learned</div>
        </div>
        <div>
          <div className="text-3xl font-bold gradient-text">98%</div>
          <div className="text-sm text-gray-400">Success Rate</div>
        </div>
      </div>
    </div>
  </div>

  <div className="grid md:grid-cols-2 lg:grid-cols-4 gap-6">
    {values.map((value, index) => (
      <div key={index} className="glass rounded-2xl p-6 text-center">
        <div className="w-16 h-16 bg-gradient-to-r from-blue-500 to-purple-500 rounded-2xl flex
          items-center justify-center mx-auto mb-4">
          <value.icon className="w-8 h-8" />
        </div>
        <h3 className="text-lg font-semibold mb-2">{value.title}</h3>
        <p className="text-gray-400 text-sm">{value.description}</p>
      </div>
    ))}
  </div>
</div>
);
};

export default About;

```

FILE: src/pages/AI/AIAssistant.jsx

```

import React, { useState } from 'react';
import { motion } from 'framer-motion';
import { Brain, Send, Mic, Sparkles, Target, Calendar, BookOpen, BarChart3, Lightbulb, Zap, MessageCircle }
from 'lucide-react';

const AIAssistant = () => {
  const [messages, setMessages] = useState([
    { id: 1, type: 'ai', content: "Hello! I'm your AI Study Assistant. How can I help you today? I can help
    with study plans, quiz recommendations, or explaining concepts!" }
  ]);
  const [input, setInput] = useState('');
  const [isTyping, setIsTyping] = useState(false);
  const [isListening, setIsListening] = useState(false);

  const suggestions = [
    { icon: Target, title: "Create Study Plan", description: "Personalized weekly schedule" },
    { icon: Lightbulb, title: "Summarize Topic", description: "Get quick concept summaries" },
    { icon: BarChart3, title: "Quiz Me", description: "Test your knowledge" },
    { icon: Calendar, title: "Set Goals", description: "Learning milestones" }
  ];

  const handleSend = () => {
    if (!input.trim()) return;

    setMessages([...messages, { id: Date.now(), type: 'user', content: input }]);
    setInput('');
  };

```

```

setIsTyping(true);

setTimeout(() => {
  const responses = [
    "That's a great question! Based on your learning progress, I recommend focusing on React hooks and state management this week.",
    "I've analyzed your study patterns. You're making excellent progress! Would you like me to generate a practice quiz?",
    "Here's a study tip: Break down complex topics into 25-minute focused sessions using the Pomodoro technique.",
    "Based on your goals, I've created a personalized study plan for you. Check your dashboard for details!"
  ];
  setMessages(prev => [...prev, {
    id: Date.now(),
    type: 'ai',
    content: responses[Math.floor(Math.random() * responses.length)]
  }]);
  setIsTyping(false);
}, 1500);
};

const startVoiceInput = () => {
  setIsListening(true);
  setTimeout(() => {
    setIsListening(false);
    setInput("Can you help me understand machine learning?");
  }, 2000);
};

return (
  <div className="min-h-screen pb-20">
    <div className="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 py-8">

      {/* Header */}
      <div className="mb-8">
        <div className="flex items-center space-x-3 mb-2">
          <div className="p-2 bg-gradient-to-r from-blue-500 to-purple-500 rounded-xl">
            <Brain className="w-6 h-6" />
          </div>
          <h1 className="text-3xl md:text-4xl font-bold">
            AI Study <span className="gradient-text">Assistant</span>
          </h1>
        </div>
        <p className="text-gray-400">Your personalized AI tutor for smarter learning</p>
      </div>

      <div className="grid lg:grid-cols-3 gap-8">

        {/* Left Column - Suggestions */}
        <div className="space-y-6">
          <div>
            <h2 className="text-lg font-semibold mb-4 flex items-center">
              <Sparkles className="w-5 h-5 mr-2 text-purple-400" />
              AI Suggestions
            </h2>
            <div className="space-y-3">
              {suggestions.map((suggestion, index) => (
                <div key={index} className="glass rounded-xl p-4 cursor-pointer hover:bg-white/5 transition-all">
                  <div className="flex items-center space-x-3">
                    <div className="p-2 bg-gradient-to-r from-blue-500 to-purple-500 rounded-lg">
                      <suggestion.icon className="w-4 h-4" />
                    </div>
                    <div>
                      <h3 className="font-semibold text-sm">{suggestion.title}</h3>
                      <p className="text-xs text-gray-400">{suggestion.description}</p>
                    </div>
                  </div>
                </div>
              ))}
            </div>
          </div>

          {/* Study Stats */}
          <div className="glass rounded-2xl p-6">
            <h3 className="font-semibold mb-3">Your Study Stats</h3>
            <div className="space-y-3">
              <div>
                <div className="flex justify-between text-sm mb-1">
                  <span>Weekly Goal</span>
                  <span>8/12 hours</span>
                </div>
                <div className="w-full bg-white/10 rounded-full h-2">
                  <div className="bg-blue-500 h-2 rounded-full" style={{ width: '66%' }} />
                </div>
              </div>
            </div>
          </div>
        </div>
      </div>
    </div>
  </div>
)

```

```

<div>
  <div className="flex justify-between text-sm mb-1">
    <span>Quizzes Completed</span>
    <span>12/20</span>
  </div>
  <div className="w-full bg-white/10 rounded-full h-2">
    <div className="bg-purple-500 h-2 rounded-full" style={{ width: '60%' }} />
  </div>
</div>
</div>
</div>
</div>

{/* Right Column - Chat Interface */}
<div className="lg:col-span-2">
  <div className="glass rounded-2xl overflow-hidden h-[500px] flex flex-col">
    {/* Chat Header */}
    <div className="p-4 border-b border-white/10 bg-white/5">
      <div className="flex items-center justify-between">
        <div className="flex items-center space-x-2">
          <div className="w-2 h-2 bg-green-500 rounded-full animate-pulse" />
          <span className="font-semibold">AI Assistant Active</span>
        </div>
      </div>
    </div>
    </div>
    </div>

    {/* Messages Area */}
    <div className="flex-1 overflow-y-auto p-4 space-y-4">
      {messages.map((message, index) => (
        <div key={message.id} className={`flex ${message.type === 'user' ? 'justify-end' : 'justify-start'} `}>
          <div className={`max-w-[80%] ${message.type === 'user' ? 'order-2' : 'order-1'} `}>
            <div className={`rounded-2xl p-3 ${message.type === 'user' ? 'bg-gradient-to-r from-blue-600 to-purple-600 text-white' : 'glass'}`}>
              {message.content}
            </div>
            <p className="text-sm">{message.content}</p>
          </div>
          <div className={`text-xs text-gray-400 mt-1 ${message.type === 'user' ? 'text-right' : 'text-left'} `}>
            {message.type === 'user' ? 'You' : 'AI Assistant'}
          </div>
        </div>
      ))}

      {isTyping && (
        <div className="flex justify-start">
          <div className="glass rounded-2xl p-3">
            <div className="flex space-x-1">
              <div className="w-2 h-2 bg-blue-400 rounded-full animate-bounce" />
              <div className="w-2 h-2 bg-purple-400 rounded-full animate-bounce" style={{ animationDelay: '0.2s' }} />
              <div className="w-2 h-2 bg-pink-400 rounded-full animate-bounce" style={{ animationDelay: '0.4s' }} />
            </div>
          </div>
        </div>
      )}
    </div>

    {/* Input Area */}
    <div className="p-4 border-t border-white/10">
      <div className="flex items-center space-x-2">
        <button
          onClick={startVoiceInput}
          className={`p-3 rounded-xl transition-all duration-200 ${isListening ? 'bg-red-500/20 text-red-400' : 'glass hover:bg-white/10'}`}
        >
          <Mic className="w-5 h-5" />
        </button>

        <input
          type="text"
          value={input}
          onChange={(e) => setInput(e.target.value)}
          onKeyDown={(e) => e.key === 'Enter' && handleSend()}
          placeholder="Ask me anything about your studies..."
          className="flex-1 glass rounded-xl px-4 py-3 focus:outline-none focus:ring-2"
        />
      </div>
    </div>
  </div>
</div>

```

```

        focus:ring-blue-500"
      />

      <button
        onClick={handleSend}
        className="p-3 bg-gradient-to-r from-blue-600 to-purple-600 rounded-xl hover:shadow-lg
        transition-all"
      >
        <Send className="w-5 h-5" />
      </button>
    </div>

    <div className="mt-3 text-center text-xs text-gray-400">
      ■ Try: "Create a study schedule" or "Explain React hooks"
    </div>
  </div>
</div>
</div>
</div>
</div>
</div>
</div>
);
};

export default AIAssistant;

```

FILE: src/pages/Auth/Login.jsx

```

import React, { useState } from 'react';
import { Link, useNavigate } from 'react-router-dom';
import { Mail, Lock, Eye, EyeOff, ArrowRight } from 'lucide-react';

const Login = () => {
  const [email, setEmail] = useState('');
  const [password, setPassword] = useState('');
  const [showPassword, setShowPassword] = useState(false);
  const navigate = useNavigate();

  const handleSubmit = (e) => {
    e.preventDefault();
    // Demo login - just navigate to dashboard
    localStorage.setItem('user', JSON.stringify({ name: 'John Doe', email }));
    navigate('/dashboard');
  };

  return (
    <div className="min-h-screen flex items-center justify-center py-20">
      <div className="absolute inset-0 bg-gradient-to-br from-blue-600/20 via-purple-600/20 to-pink-600/20
      blur-3xl" />

      <div className="w-full max-w-md px-4">
        <div className="glass rounded-2xl p-8">
          <div className="text-center mb-8">
            <div className="w-16 h-16 bg-gradient-to-r from-blue-500 to-purple-500 rounded-2xl flex
            items-center justify-center mx-auto mb-4">
              <span className="text-2xl font-bold">SL</span>
            </div>
            <h2 className="text-2xl font-bold mb-2">Welcome Back!</h2>
            <p className="text-gray-400">Sign in to continue learning</p>
          </div>

          <form onSubmit={handleSubmit} className="space-y-6">
            <div>
              <label className="block text-sm font-medium mb-2">Email Address</label>
              <div className="relative">
                <Mail className="absolute left-3 top-1/2 transform -translate-y-1/2 w-5 h-5 text-gray-400" />
                <input
                  type="email"
                  value={email}
                  onChange={(e) => setEmail(e.target.value)}
                  className="w-full pl-10 pr-4 py-3 glass rounded-xl focus:outline-none focus:ring-2
                  focus:ring-blue-500"
                  placeholder="you@example.com"
                  required
                />
              </div>
            </div>

            <div>
              <label className="block text-sm font-medium mb-2">Password</label>
              <div className="relative">
                <Lock className="absolute left-3 top-1/2 transform -translate-y-1/2 w-5 h-5 text-gray-400" />
                <input
                  type={showPassword ? 'text' : 'password'}
                  value={password}
                  onChange={(e) => setPassword(e.target.value)}
                />
              </div>
            </div>
          </form>
        </div>
      </div>
    </div>
  );
};

```

```

        className="w-full pl-10 pr-12 py-3 glass rounded-xl focus:outline-none focus:ring-2
        focus:ring-blue-500"
        placeholder="....."
        required
      />
      <button
        type="button"
        onClick={() => setShowPassword(!showPassword)}
        className="absolute right-3 top-1/2 transform -translate-y-1/2"
      >
        {showPassword ? <EyeOff className="w-5 h-5 text-gray-400" /> : <Eye className="w-5 h-5
        text-gray-400" />}
      </button>
    </div>
  </div>

  <button type="submit" className="w-full py-3 bg-gradient-to-r from-blue-600 to-purple-600
  rounded-xl font-semibold hover:shadow-lg transition-all">
    Sign In
    <ArrowRight className="w-4 h-4 inline ml-2" />
  </button>
</form>

<div className="mt-6 text-center">
  <p className="text-sm text-gray-400">
    Don't have an account?{' '}
    <Link to="/register" className="text-blue-400 hover:text-blue-300 font-semibold">
      Sign up
    </Link>
  </p>
</div>
</div>
</div>
</div>
);
};

export default Login;

```

FILE: src/pages/Auth/Register.jsx

```

import React, { useState } from 'react';
import { Link, useNavigate } from 'react-router-dom';
import { User, Mail, Lock, Eye, EyeOff, ArrowRight } from 'lucide-react';

const Register = () => {
  const [name, setName] = useState('');
  const [email, setEmail] = useState('');
  const [password, setPassword] = useState('');
  const [showPassword, setShowPassword] = useState(false);
  const navigate = useNavigate();

  const handleSubmit = (e) => {
    e.preventDefault();
    localStorage.setItem('user', JSON.stringify({ name, email }));
    navigate('/dashboard');
  };

  return (
    <div className="min-h-screen flex items-center justify-center py-20">
      <div className="absolute inset-0 bg-gradient-to-br from-blue-600/20 via-purple-600/20 to-pink-600/20
      blur-3xl" />

      <div className="w-full max-w-md px-4">
        <div className="glass rounded-2xl p-8">
          <div className="text-center mb-8">
            <div className="w-16 h-16 bg-gradient-to-r from-blue-500 to-purple-500 rounded-2xl flex
            items-center justify-center mx-auto mb-4">
              <span className="text-2xl font-bold">SL</span>
            </div>
            <h2 className="text-2xl font-bold mb-2">Create Account</h2>
            <p className="text-gray-400">Start your learning journey today</p>
          </div>

          <form onSubmit={handleSubmit} className="space-y-6">
            <div>
              <label className="block text-sm font-medium mb-2">Full Name</label>
              <div className="relative">
                <User className="absolute left-3 top-1/2 transform -translate-y-1/2 w-5 h-5 text-gray-400" />
                <input
                  type="text"
                  value={name}
                  onChange={(e) => setName(e.target.value)}
                  className="w-full pl-10 pr-4 py-3 glass rounded-xl focus:outline-none focus:ring-2
                  focus:ring-blue-500"
                  placeholder="John Doe"
                />
              </div>
            </div>

```

```

        required
      />
    </div>
  </div>

  <div>
    <label className="block text-sm font-medium mb-2">Email Address</label>
    <div className="relative">
      <Mail className="absolute left-3 top-1/2 transform -translate-y-1/2 w-5 h-5 text-gray-400" />
      <input
        type="email"
        value={email}
        onChange={(e) => setEmail(e.target.value)}
        className="w-full pl-10 pr-4 py-3 glass rounded-xl focus:outline-none focus:ring-2
        focus:ring-blue-500"
        placeholder="you@example.com"
        required
      />
    </div>
  </div>

  <div>
    <label className="block text-sm font-medium mb-2">Password</label>
    <div className="relative">
      <Lock className="absolute left-3 top-1/2 transform -translate-y-1/2 w-5 h-5 text-gray-400" />
      <input
        type={showPassword ? 'text' : 'password'}
        value={password}
        onChange={(e) => setPassword(e.target.value)}
        className="w-full pl-10 pr-12 py-3 glass rounded-xl focus:outline-none focus:ring-2
        focus:ring-blue-500"
        placeholder="....."
        required
      />
      <button
        type="button"
        onClick={() => setShowPassword(!showPassword)}
        className="absolute right-3 top-1/2 transform -translate-y-1/2"
      >
        {showPassword ? <EyeOff className="w-5 h-5 text-gray-400" /> : <Eye className="w-5 h-5
        text-gray-400" />}
      </button>
    </div>
  </div>

  <button type="submit" className="w-full py-3 bg-gradient-to-r from-blue-600 to-purple-600
  rounded-xl font-semibold hover:shadow-lg transition-all">
    Create Account
    <ArrowRight className="w-4 h-4 inline ml-2" />
  </button>
</form>

  <div className="mt-6 text-center">
    <p className="text-sm text-gray-400">
      Already have an account?{' '}
      <Link to="/login" className="text-blue-400 hover:text-blue-300 font-semibold">
        Sign in
      </Link>
    </p>
  </div>
</div>
</div>
</div>
);
};

export default Register;

```

FILE: src/pages/CourseDetails/CourseDetails.jsx

```

import React, { useState } from 'react';
import { useParams, Link } from 'react-router-dom';
import { motion } from 'framer-motion';
import {
  Play, Download, Bookmark, Share2, ChevronLeft, ChevronRight,
  FileText, Video, CheckCircle, Clock, User, Star, Heart,
  MessageCircle, ThumbsUp, BookOpen, Award, ExternalLink
} from 'lucide-react';
import Card from '../../components/ui/Card';
import Button from '../../components/ui/Button';
import { courses } from '../../data/mockData';

const CourseDetails = () => {
  const { id } = useParams();
  const course = courses.find(c => c.id === parseInt(id)) || courses[0];
  const [activeTab, setActiveTab] = useState('content');

```

```

const [isDownloading, setIsDownloading] = useState(false);

const lessons = [
  { id: 1, title: 'Introduction to the Course', duration: '10:00', type: 'video', completed: true },
  { id: 2, title: 'Setting Up Development Environment', duration: '15:30', type: 'video', completed: true },
  { id: 3, title: 'Core Concepts Explained', duration: '20:00', type: 'video', completed: false },
  { id: 4, title: 'Practical Examples', duration: '25:15', type: 'video', completed: false },
  { id: 5, title: 'Advanced Techniques', duration: '30:00', type: 'video', completed: false },
  { id: 6, title: 'Project: Build Your First App', duration: '45:00', type: 'project', completed: false },
  { id: 7, title: 'Quiz: Test Your Knowledge', duration: '15:00', type: 'quiz', completed: false }
];

const resources = [
  { id: 1, name: 'Course Slides PDF', size: '2.5 MB', type: 'pdf' },
  { id: 2, name: 'Source Code Bundle', size: '1.8 MB', type: 'zip' },
  { id: 3, name: 'Exercise Files', size: '3.2 MB', type: 'zip' },
  { id: 4, name: 'Cheat Sheet', size: '0.5 MB', type: 'pdf' }
];

return (
  <div className="min-h-screen pb-20">
    { /* Hero Section */ }
    <div className="relative h-[60vh] overflow-hidden">
      <img
        src={course.thumbnail}
        alt={course.title}
        className="w-full h-full object-cover"
      />
      <div className="absolute inset-0 bg-gradient-to-t from-black via-black/50 to-transparent" />

      <div className="absolute bottom-0 left-0 right-0 p-8">
        <div className="max-w-7xl mx-auto">
          <motion.div
            initial={{ opacity: 0, y: 20 }}
            animate={{ opacity: 1, y: 0 }}
          >
            <div className="flex items-center space-x-2 text-sm text-gray-300 mb-4">
              <Link to="/courses" className="hover:text-white">Courses</Link>
              <ChevronRight className="w-4 h-4" />
              <span>{course.category}</span>
              <ChevronRight className="w-4 h-4" />
              <span className="text-white">{course.title}</span>
            </div>

            <h1 className="text-3xl md:text-5xl font-bold mb-4">{course.title}</h1>

            <div className="flex flex-wrap items-center gap-4 text-sm text-gray-300 mb-6">
              <div className="flex items-center">
                <User className="w-4 h-4 mr-1" />
                {course.instructor}
              </div>
              <div className="flex items-center">
                <Clock className="w-4 h-4 mr-1" />
                {course.duration}
              </div>
              <div className="flex items-center">
                <BookOpen className="w-4 h-4 mr-1" />
                {course.lessons} lessons
              </div>
              <div className="flex items-center">
                <Star className="w-4 h-4 text-yellow-500 fill-current" />
                <span className="ml-1">4.8 (2.3k ratings)</span>
              </div>
            </div>

            <div className="flex flex-wrap gap-3">
              <Button>
                <Play className="w-4 h-4 mr-2" />
                Continue Learning
              </Button>
              <Button variant="secondary" onClick={() => setIsDownloading(true)}>
                <Download className="w-4 h-4 mr-2" />
                {isDownloading ? 'Downloading...' : 'Download Course'}
              </Button>
              <Button variant="outline">
                <Bookmark className="w-4 h-4" />
              </Button>
              <Button variant="outline">
                <Share2 className="w-4 h-4" />
              </Button>
            </div>
          </motion.div>
        </div>
      </div>
    </div>
  </div>
  { /* Content Section */ }

```

```

<div className="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 py-12">
  <div className="grid lg:grid-cols-3 gap-8">

    {/* Main Content */}
    <div className="lg:col-span-2">
      {/* Tabs */}
      <div className="flex border-b border-white/10 mb-6">
        {[ 'content', 'resources', 'discussion' ].map(tab => (
          <button
            key={tab}
            onClick={() => setActiveTab(tab)}
            className={ `px-4 py-2 font-semibold capitalize transition-all duration-200 ${
              activeTab === tab
                ? 'border-b-2 border-blue-500 text-blue-400'
                : 'text-gray-400 hover:text-white'
            }` }
          >
            {tab}
          </button>
        ))}
      </div>

      {/* Course Content */}
      {activeTab === 'content' && (
        <motion.div
          initial={{ opacity: 0 }}
          animate={{ opacity: 1 }}
          className="space-y-4"
        >
          <div className="glass rounded-xl p-6">
            <h3 className="text-xl font-semibold mb-4">Course Curriculum</h3>
            {lessons.map((lesson, index) => (
              <div key={lesson.id} className="flex items-center justify-between py-3 border-b border-white/10 last:border-0">
                <div className="flex items-center space-x-3">
                  {lesson.completed ? (
                    <CheckCircle className="w-5 h-5 text-green-500" />
                  ) : (
                    <div className="w-5 h-5 rounded-full border-2 border-gray-500" />
                  )}
                <div>
                  <div className="font-medium">{lesson.title}</div>
                  <div className="text-sm text-gray-400 flex items-center">
                    {lesson.type === 'video' && <Video className="w-3 h-3 mr-1" />}
                    {lesson.type === 'quiz' && <FileText className="w-3 h-3 mr-1" />}
                    {lesson.type === 'project' && <Award className="w-3 h-3 mr-1" />}
                    {lesson.duration}
                  </div>
                </div>
                <Button variant="ghost" size="sm">
                  {lesson.completed ? 'Review' : <Play className="w-4 h-4" />}
                </Button>
              </div>
            ))}
          </div>
        </motion.div>
      )}

      {/* Resources */}
      {activeTab === 'resources' && (
        <motion.div
          initial={{ opacity: 0 }}
          animate={{ opacity: 1 }}
          className="space-y-4"
        >
          <div className="glass rounded-xl p-6">
            <h3 className="text-xl font-semibold mb-4">Course Resources</h3>
            {resources.map(resource => (
              <div key={resource.id} className="flex items-center justify-between py-3 border-b border-white/10 last:border-0">
                <div className="flex items-center space-x-3">
                  <FileText className="w-5 h-5 text-blue-400" />
                <div>
                  <div className="font-medium">{resource.name}</div>
                  <div className="text-sm text-gray-400">{resource.size}</div>
                </div>
                <div>
                  <Button variant="ghost" size="sm">
                    <Download className="w-4 h-4" />
                  </Button>
                </div>
              </div>
            ))}
          </div>
        </motion.div>
      )}

      {/* Discussion */}

```

```

{activeTab === 'discussion' && (
  <motion.div
    initial={{ opacity: 0 }}
    animate={{ opacity: 1 }}
    className="space-y-4"
  >
    <div className="glass rounded-xl p-6">
      <div className="flex items-center justify-between mb-6">
        <h3 className="text-xl font-semibold">Discussion</h3>
        <Button variant="outline" size="sm">
          <MessageCircle className="w-4 h-4 mr-2" />
          New Post
        </Button>
      </div>

      <div className="space-y-4">
        {[1, 2, 3].map((_, index) => (
          <div key={index} className="pb-4 border-b border-white/10 last:border-0">
            <div className="flex items-start space-x-3">
              <div className="w-10 h-10 bg-gradient-to-r from-blue-500 to-purple-500 rounded-full"
                />
              <div className="flex-1">
                <div className="flex items-center justify-between mb-1">
                  <span className="font-semibold">Student_{index + 1}</span>
                  <span className="text-xs text-gray-400">2 hours ago</span>
                </div>
                <p className="text-gray-300 text-sm">Great course! The explanations are very
                  clear.</p>
                <div className="flex items-center space-x-3 mt-2">
                  <button className="flex items-center text-xs text-gray-400 hover:text-white">
                    <ThumbsUp className="w-3 h-3 mr-1" />
                    Like
                  </button>
                  <button className="flex items-center text-xs text-gray-400 hover:text-white">
                    <MessageCircle className="w-3 h-3 mr-1" />
                    Reply
                  </button>
                </div>
              </div>
            </div>
          </div>
        ))}
      </div>
    </div>
  </motion.div>
)}
</div>

{/* Sidebar */}
<div className="space-y-6">
  {/* Progress Card */}
  <Card className="p-6">
    <h3 className="font-semibold mb-3">Your Progress</h3>
    <div className="mb-2">
      <div className="flex justify-between text-sm mb-1">
        <span>Course Completion</span>
        <span>{course.progress}%</span>
      </div>
      <div className="w-full bg-white/10 rounded-full h-2">
        <div className="bg-gradient-to-r from-blue-500 to-purple-500 h-2 rounded-full" style={{
          width: `${course.progress}%` }} />
      </div>
    </div>
    <div className="text-sm text-gray-400 mb-4">
      {Math.floor(course.lessons * (course.progress / 100))} of {course.lessons} lessons completed
    </div>
    <Button variant="outline" className="w-full">
      <ExternalLink className="w-4 h-4 mr-2" />
      Continue Where You Left
    </Button>
  </Card>

  {/* Download Info */}
  <Card className="p-6">
    <h3 className="font-semibold mb-3">Offline Access</h3>
    <div className="text-sm text-gray-400 mb-3">
      Download this course to watch without internet
    </div>
    <div className="bg-green-500/10 rounded-lg p-3 mb-3">
      <div className="flex justify-between text-sm">
        <span>Course size</span>
        <span>2.4 GB</span>
      </div>
      <div className="flex justify-between text-sm mt-1">
        <span>Available space</span>
        <span>3.2 GB</span>
      </div>
    </div>
  </Card>

```

```

    </div>
    <Button className="w-full">
      <Download className="w-4 h-4 mr-2" />
      Download for Offline
    </Button>
  </Card>

  { /* Instructor Info */ }
  <Card className="p-6">
    <h3 className="font-semibold mb-3">About Instructor</h3>
    <div className="flex items-center space-x-3 mb-3">
      <div className="w-12 h-12 bg-gradient-to-r from-blue-500 to-purple-500 rounded-full" />
      <div>
        <div className="font-semibold">{course.instructor}</div>
        <div className="text-sm text-gray-400">Senior Developer</div>
      </div>
    </div>
    <p className="text-sm text-gray-300">
      Expert in web development with 10+ years of experience. Passionate about teaching and helping
      students succeed.
    </p>
  </Card>
</div>
</div>
</div>
</div>
);
};

export default CourseDetails;

```

FILE: src/pages/Courses/Courses.jsx

```

import React, { useState } from 'react';
import { motion, AnimatePresence } from 'framer-motion';
import { Search, Filter, Download, Clock, User, Star, ChevronDown, BookOpen, TrendingUp } from 'lucide-react';
import Card from '../../components/ui/Card';
import Button from '../../components/ui/Button';
import { courses } from '../../data/mockData';
import { Link } from 'react-router-dom';

const Courses = () => {
  const [searchTerm, setSearchTerm] = useState('');
  const [selectedCategory, setSelectedCategory] = useState('All');
  const [sortBy, setSortBy] = useState('popular');

  const categories = ['All', 'Development', 'AI & ML', 'Design', 'Data Science', 'Business', 'Marketing'];

  const filteredCourses = courses.filter(course => {
    const matchesSearch = course.title.toLowerCase().includes(searchTerm.toLowerCase());
    const matchesCategory = selectedCategory === 'All' || course.category === selectedCategory;
    return matchesSearch && matchesCategory;
  });

  return (
    <div className="min-h-screen pb-20">
      <div className="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8">
        { /* Header */ }
        <motion.div
          initial={{ opacity: 0, y: -20 }}
          animate={{ opacity: 1, y: 0 }}
          className="mb-8"
        >
          <h1 className="text-3xl md:text-4xl font-bold mb-2">
            Explore <span className="gradient-text">Courses</span>
          </h1>
          <p className="text-gray-400">Discover the best courses to advance your career</p>
        </motion.div>

        { /* Search and Filter Bar */ }
        <motion.div
          initial={{ opacity: 0, y: -10 }}
          animate={{ opacity: 1, y: 0 }}
          transition={{ delay: 0.1 }}
          className="flex flex-col md:flex-row gap-4 mb-8"
        >
          <div className="flex-1 relative">
            <Search className="absolute left-3 top-1/2 transform -translate-y-1/2 w-5 h-5 text-gray-400" />
            <input
              type="text"
              placeholder="Search courses..."
              value={searchTerm}
              onChange={(e) => setSearchTerm(e.target.value)}
              className="w-full pl-10 pr-4 py-3 glass rounded-xl focus:outline-none focus:ring-2
              focus:ring-blue-500"
            />

```

```

    />
  </div>

  <div className="flex gap-2 overflow-x-auto pb-2 md:pb-0">
    {categories.map(category => (
      <button
        key={category}
        onClick={() => setSelectedCategory(category)}
        className={`px-4 py-2 rounded-xl whitespace-nowrap transition-all duration-200 ${
          selectedCategory === category
            ? 'bg-gradient-to-r from-blue-600 to-purple-600 text-white'
            : 'glass text-gray-300 hover:bg-white/10'
        }`}
      >
        {category}
      </button>
    ))}
  </div>

  <div className="relative">
    <button className="flex items-center space-x-2 px-4 py-3 glass rounded-xl">
      <Filter className="w-4 h-4" />
      <span>Sort: {sortBy}</span>
      <ChevronDown className="w-4 h-4" />
    </button>
  </div>
</motion.div>

{/* Trending Section */}
<motion.div
  initial={{ opacity: 0 }}
  animate={{ opacity: 1 }}
  transition={{ delay: 0.2 }}
  className="mb-12"
>
  <div className="flex items-center space-x-2 mb-4">
    <TrendingUp className="w-5 h-5 text-orange-400" />
    <h2 className="text-xl font-semibold">Trending Now</h2>
  </div>
  <div className="grid md:grid-cols-2 lg:grid-cols-4 gap-6">
    {courses.slice(0, 4).map((course, index) => (
      <TrendingCard key={course.id} course={course} index={index} />
    ))}
  </div>
</motion.div>

{/* All Courses Grid */}
<motion.div
  initial={{ opacity: 0 }}
  animate={{ opacity: 1 }}
  transition={{ delay: 0.3 }}
>
  <div className="flex justify-between items-center mb-4">
    <h2 className="text-xl font-semibold">All Courses</h2>
    <span className="text-sm text-gray-400">{filteredCourses.length} courses found</span>
  </div>

  <AnimatePresence>
    <div className="grid md:grid-cols-2 lg:grid-cols-3 gap-6">
      {filteredCourses.map((course, index) => (
        <CourseCard key={course.id} course={course} index={index} />
      ))}
    </div>
  </AnimatePresence>
</motion.div>
</div>
</div>
);
};

const CourseCard = ({ course, index }) => {
  return (
    <motion.div
      initial={{ opacity: 0, y: 30 }}
      animate={{ opacity: 1, y: 0 }}
      transition={{ delay: index * 0.1 }}
      whileHover={{ y: -8 }}
    >
      <Link to={`/course/${course.id}`}>
        <Card className="overflow-hidden h-full">
          <div className="relative">
            <img
              src={course.thumbnail}
              alt={course.title}
              className="w-full h-48 object-cover"
            />
            {course.isDownloaded && (

```

```

        <div className="absolute top-2 right-2 bg-green-500/90 backdrop-blur-sm rounded-lg px-2 py-1
        text-xs flex items-center">
          <Download className="w-3 h-3 mr-1" />
          Offline
        </div>
      )}
    <div className="absolute bottom-2 left-2 bg-black/70 backdrop-blur-sm rounded-lg px-2 py-1
    text-xs">
      {course.level}
    </div>
  </div>

  <div className="p-4">
    <div className="flex items-center justify-between mb-2">
      <span className="text-xs text-blue-400">{course.category}</span>
      <div className="flex items-center">
        <Star className="w-3 h-3 text-yellow-500 fill-current" />
        <span className="text-xs ml-1">4.8</span>
      </div>
    </div>

    <h3 className="font-semibold text-lg mb-2 line-clamp-2">{course.title}</h3>
    <div className="flex items-center text-sm text-gray-400 mb-3">
      <User className="w-3 h-3 mr-1" />
      <span>{course.instructor}</span>
      <Clock className="w-3 h-3 ml-3 mr-1" />
      <span>{course.duration}</span>
    </div>

    <div className="mb-3">
      <div className="flex justify-between text-xs mb-1">
        <span>Progress</span>
        <span>{course.progress}%</span>
      </div>
      <div className="w-full bg-white/10 rounded-full h-2">
        <motion.div
          initial={{ width: 0 }}
          animate={{ width: `${course.progress}%` }}
          transition={{ duration: 1 }}
          className="bg-gradient-to-r from-blue-500 to-purple-500 h-2 rounded-full"
        />
      </div>
    </div>

    <Button variant="outline" size="sm" className="w-full">
      {course.progress > 0 ? 'Continue Learning' : 'Start Course'}
    </Button>
  </div>
</Card>
</Link>
</motion.div>
);
};

const TrendingCard = ({ course, index }) => {
  return (
    <motion.div
      initial={{ opacity: 0, scale: 0.9 }}
      animate={{ opacity: 1, scale: 1 }}
      transition={{ delay: index * 0.1 }}
      whileHover={{ scale: 1.05 }}
    >
      <Card className="p-4">
        <div className="flex items-center space-x-3">
          <div className="w-16 h-16 rounded-lg overflow-hidden">
            <img src={course.thumbnail} alt={course.title} className="w-full h-full object-cover" />
          </div>
          <div className="flex-1">
            <h4 className="font-semibold text-sm mb-1">{course.title}</h4>
            <p className="text-xs text-gray-400">{course.instructor}</p>
            <div className="flex items-center mt-1">
              <Star className="w-3 h-3 text-yellow-500 fill-current" />
              <span className="text-xs ml-1">4.8</span>
              <span className="text-xs text-gray-400 ml-2">{course.duration}</span>
            </div>
          </div>
        </div>
      </Card>
    </motion.div>
  );
};

export default Courses;

```

```

import React from 'react';
import { motion } from 'framer-motion';
import {
  TrendingUp, BookOpen, Download, Award, Calendar,
  Clock, Target, Brain, ChevronRight, Zap, Flame,
  BarChart3, CheckCircle2, PlayCircle, Video, Star
} from 'lucide-react';
import { Link } from 'react-router-dom';

const Dashboard = () => {
  const statsCards = [
    { icon: Clock, label: "Learning Hours", value: "127", change: "+12%", color: "blue" },
    { icon: Award, label: "Completed", value: "8", change: "+2", color: "purple" },
    { icon: Flame, label: "Day Streak", value: "15", change: "■", color: "orange" },
    { icon: Download, label: "Offline", value: "24", change: "Lessons", color: "green" }
  ];

  const continueCourses = [
    { id: 1, title: "Advanced React & Modern Web Development", instructor: "Sarah Johnson", progress: 45,
      thumbnail: "https://images.unsplash.com/photo-1633356122544-f134324a6cee", duration: "8 hours" },
    { id: 2, title: "Machine Learning Fundamentals", instructor: "Dr. Michael Chen", progress: 20, thumbnail:
      "https://images.unsplash.com/photo-1555949963-ff9fe0c870eb", duration: "12 hours" },
    { id: 3, title: "UI/UX Design Mastery", instructor: "Emma Rodriguez", progress: 80, thumbnail:
      "https://images.unsplash.com/photo-1561070791-2526d30994b5", duration: "6 hours" }
  ];

  const weeklyData = [
    { day: "Mon", hours: 2.5 },
    { day: "Tue", hours: 3.5 },
    { day: "Wed", hours: 2 },
    { day: "Thu", hours: 4 },
    { day: "Fri", hours: 3 },
    { day: "Sat", hours: 1.5 },
    { day: "Sun", hours: 2 }
  ];

  return (
    <div className="min-h-screen pb-20">
      <div className="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 py-4 sm:py-6 md:py-8">

        {/* Welcome Section - Responsive */}
        <motion.div
          initial={{ opacity: 0, y: -20 }}
          animate={{ opacity: 1, y: 0 }}
          className="mb-6 md:mb-8"
        >
          <h1 className="text-2xl sm:text-3xl md:text-4xl font-bold mb-2">
            Welcome back, <span className="gradient-text">Student! ■</span>
          </h1>
          <p className="text-sm sm:text-base text-gray-400">Ready to continue your learning journey?</p>
        </motion.div>

        {/* Stats Grid - Responsive: 2 columns on mobile, 4 on desktop */}
        <div className="grid grid-cols-2 lg:grid-cols-4 gap-3 sm:gap-4 mb-6 md:mb-8">
          {statsCards.map((stat, index) => (
            <motion.div
              key={index}
              initial={{ opacity: 0, y: 20 }}
              animate={{ opacity: 1, y: 0 }}
              transition={{ delay: index * 0.1 }}
              className="glass rounded-xl sm:rounded-2xl p-3 sm:p-4"
            >
              <div className="flex items-center justify-between mb-2">
                <div className={`p-2 rounded-lg bg-${stat.color}-500/20`} >
                  <stat.icon className={`w-4 h-4 sm:w-5 sm:h-5 text-${stat.color}-400`} />
                </div>
                <span className="text-xs sm:text-sm text-green-400">{stat.change}</span>
              </div>
              <div className="text-xl sm:text-2xl font-bold">{stat.value}</div>
              <div className="text-xs sm:text-sm text-gray-400">{stat.label}</div>
            </motion.div>
          ))}
        </div>

        {/* Main Content Grid - Responsive: 1 column on mobile, 3 on desktop */}
        <div className="grid lg:grid-cols-3 gap-6 md:gap-8">

          {/* Left Column - Takes 2 columns on desktop */}
          <div className="lg:col-span-2 space-y-6 md:space-y-8">

            {/* Continue Learning - Responsive cards */}
            <div>
              <div className="flex justify-between items-center mb-4">
                <h2 className="text-lg sm:text-xl font-semibold">Continue Learning</h2>
                <button className="text-sm text-gray-400 hover:text-white flex items-center">
                  View All <ChevronRight className="w-4 h-4 ml-1" />
                </button>
              </div>
            </div>
          </div>
        </div>
      </div>
    </div>
  );
};

```

```

</div>
<div className="space-y-3 sm:space-y-4">
  {continueCourses.map((course, index) => (
    <motion.div
      key={course.id}
      initial={{ opacity: 0, x: -20 }}
      animate={{ opacity: 1, x: 0 }}
      transition={{ delay: index * 0.1 }}
      className="glass rounded-xl sm:rounded-2xl p-3 sm:p-4"
    >
      <div className="flex flex-col sm:flex-row sm:items-center gap-3 sm:gap-4">
        <img
          src={course.thumbnail}
          alt={course.title}
          className="w-full sm:w-20 h-32 sm:h-20 rounded-lg object-cover"
        />
        <div className="flex-1">
          <h3 className="font-semibold text-sm sm:text-base mb-1">{course.title}</h3>
          <div className="flex flex-wrap items-center gap-2 sm:gap-4 text-xs sm:text-sm text-gray-400 mb-2">
            <span>{course.instructor}</span>
            <span>•</span>
            <span>{course.duration}</span>
          </div>
          <div className="flex items-center gap-2">
            <div className="flex-1 bg-white/10 rounded-full h-1.5 sm:h-2">
              <motion.div
                initial={{ width: 0 }}
                animate={{ width: `${course.progress}%` }}
                transition={{ duration: 1 }}
                className="bg-gradient-to-r from-blue-500 to-purple-500 h-1.5 sm:h-2 rounded-full"
              />
            </div>
            <span className="text-xs sm:text-sm">{course.progress}%</span>
          </div>
          <button className="p-2 glass rounded-lg hover:bg-white/10 sm:self-center">
            <PlayCircle className="w-5 h-5" />
          </button>
        </div>
      </div>
    </motion.div>
  )})
</div>
</div>

{/* Weekly Statistics - Responsive chart */}
<div>
  <h2 className="text-lg sm:text-xl font-semibold mb-4">Learning Activity</h2>
  <div className="glass rounded-xl sm:rounded-2xl p-4 sm:p-6">
    <div className="flex flex-col sm:flex-row justify-between items-start sm:items-center gap-3 mb-6">
      <div className="flex items-center space-x-2">
        <BarChart3 className="w-5 h-5 text-blue-400" />
        <span className="font-semibold text-sm sm:text-base">Weekly Learning Hours</span>
      </div>
      <select className="bg-white/5 rounded-lg px-3 py-1 text-sm w-full sm:w-auto">
        <option>This Week</option>
        <option>Last Week</option>
        <option>This Month</option>
      </select>
    </div>

    {/* Responsive Bar Chart */}
    <div className="flex justify-around items-end h-40 sm:h-48">
      {weeklyData.map((day, index) => (
        <div key={day.day} className="text-center flex-1">
          <motion.div
            initial={{ height: 0 }}
            animate={{ height: `${day.hours * 30}px` }}
            transition={{ duration: 0.5, delay: index * 0.1 }}
            className="w-full max-w-[40px] mx-auto bg-gradient-to-t from-blue-500 to-purple-500 rounded-lg"
            style={{ height: `${day.hours * 30}px` }}
          />
          <div className="text-[10px] sm:text-xs text-gray-400 mt-2">{day.day}</div>
          <div className="text-[10px] sm:text-xs font-semibold">{day.hours}h</div>
        </div>
      )})
    </div>
  </div>
</div>
</div>
</div>

{/* Right Column - Responsive */}
<div className="space-y-6 md:space-y-8">
  {/* Study Streak - Responsive */}

```

```

<div className="glass rounded-xl sm:rounded-2xl p-4 sm:p-6 text-center">
  <div className="relative inline-block">
    <div className="w-24 h-24 sm:w-32 sm:h-32 rounded-full border-4 border-purple-500/30 flex
      items-center justify-center mx-auto">
      <div className="text-center">
        <div className="text-2xl sm:text-3xl font-bold gradient-text">15</div>
        <div className="text-[10px] sm:text-xs text-gray-400">Days</div>
      </div>
    </div>
    <Flame className="absolute -top-2 -right-2 w-6 h-6 sm:w-8 sm:h-8 text-orange-500" />
  </div>
  <h3 className="text-base sm:text-lg font-semibold mt-4">15 Day Streak!</h3>
  <p className="text-xs sm:text-sm text-gray-400 mt-2">You're on fire! Keep going ■</p>
  <div className="mt-4 flex justify-center gap-1">
    [...Array(7)].map((_, i) => (
      <div key={i} className={`w-1.5 h-1.5 sm:w-2 sm:h-2 rounded-full ${i < 5 ? 'bg-green-500' :
        'bg-gray-600'}` } />
    ))
  </div>
</div>

{/* AI Recommendations - Responsive */}
<div>
  <div className="flex justify-between items-center mb-4">
    <h2 className="text-lg sm:text-xl font-semibold">AI Recommendations</h2>
    <Brain className="w-5 h-5 text-purple-400" />
  </div>
  <div className="space-y-3">
    {continueCourses.slice(0, 2).map((course, index) => (
      <div key={index} className="glass rounded-xl p-3 sm:p-4">
        <div className="flex items-center gap-3">
          <div className="w-10 h-10 sm:w-12 sm:h-12 rounded-lg bg-gradient-to-r from-purple-500
            to-pink-500 flex items-center justify-center flex-shrink-0">
            <Zap className="w-5 h-5 sm:w-6 sm:h-6" />
          </div>
          <div className="flex-1 min-w-0">
            <h4 className="font-semibold text-xs sm:text-sm truncate">{course.title}</h4>
            <p className="text-[10px] sm:text-xs text-gray-400">{course.duration}</p>
          </div>
          <button className="px-3 py-1.5 glass rounded-lg text-xs sm:text-sm whitespace-nowrap">
            Start
          </button>
        </div>
      </div>
    ))
  </div>
</div>

{/* Downloaded Lessons Card - Responsive */}
<div className="glass rounded-xl sm:rounded-2xl p-4 sm:p-6 bg-gradient-to-r from-blue-600/20
to-purple-600/20">
  <div className="flex items-center justify-between mb-4">
    <Download className="w-5 h-5 sm:w-6 sm:h-6 text-blue-400" />
    <span className="text-xs sm:text-sm text-green-400">Available Offline</span>
  </div>
  <h3 className="text-xl sm:text-2xl font-bold mb-2">24 Lessons</h3>
  <p className="text-xs sm:text-sm text-gray-300 mb-4">Ready to learn without internet</p>
  <div className="w-full bg-white/10 rounded-full h-1.5 sm:h-2 mb-2">
    <div className="bg-green-500 h-1.5 sm:h-2 rounded-full" style={{ width: '68%' }} />
  </div>
  <div className="flex justify-between text-[10px] sm:text-xs text-gray-400">
    <span>Used 1.2 GB</span>
    <span>of 4 GB</span>
  </div>
</div>
</div>
</div>
</div>
</div>
</div>
);
};

export default Dashboard;

```