



ALVIN B 2024-CSE ▾

A2

|              |                                 |
|--------------|---------------------------------|
| Started on   | Monday, 25 August 2025, 2:41 PM |
| State        | Finished                        |
| Completed on | Monday, 25 August 2025, 2:47 PM |
| Time taken   | 6 mins 21 secs                  |
| Marks        | 1.00/1.00                       |
| Grade        | 10.00 out of 10.00 (100%)       |

**Question 1** | Correct Mark 1.00 out of 1.00

Write a program to take value V and we want to make change for V Rs, and we have infinite supply of each of the denominations in Indian currency, i.e., we have infinite supply of { 1, 2, 5, 10, 20, 50, 100, 500, 1000} valued coins/notes, what is the minimum number of coins and/or notes needed to make the change.

Input Format:

Take an integer from stdin.

Output Format:

print the integer which is change of the number.

Example Input :

64

Output:

4

Explanaton:

We need a 50 Rs note and a 10 Rs note and two 2 rupee coins.

**Answer:** (penalty regime: 0 %)

```

1  #include <stdio.h>
2
3  void make_change(int V) {
4      int denominations[] = {1000, 500, 100, 50, 20, 10, 5, 2, 1};
5      int num_coins = 0;
6
7      for (int i = 0; i < 9; i++) {
8
9          num_coins += V / denominations[i];
10         V = V % denominations[i];
11
12         if (V == 0) break;
13     }
14
15     printf("%d\n", num_coins);
16 }
17
18 int main() {
19     int V;
20     scanf("%d", &V);
21     make_change(V);
22     return 0;
23 }
24

```

|   | Input | Expected | Got |   |
|---|-------|----------|-----|---|
| ✓ | 49    | 5        | 5   | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)



ALVIN B 2024-CSE ▾

A2

|              |                                   |
|--------------|-----------------------------------|
| Started on   | Monday, 25 August 2025, 2:47 PM   |
| State        | Finished                          |
| Completed on | Saturday, 30 August 2025, 8:31 PM |
| Time taken   | 5 days 5 hours                    |
| Marks        | 1.00/1.00                         |
| Grade        | 10.00 out of 10.00 (100%)         |

**Question 1** | Correct | Mark 1.00 out of 1.00

Assume you are an awesome parent and want to give your children some cookies. But, you should give each child at most one cookie.

Each child  $i$  has a greed factor  $g[i]$ , which is the minimum size of a cookie that the child will be content with; and each cookie  $j$  has a size  $s[j]$ . If  $s[j] \geq g[i]$ , we can assign the cookie  $j$  to the child  $i$ , and the child  $i$  will be content. Your goal is to maximize the number of your content children and output the maximum number.

**Example 1:****Input:**

```
3
1 2 3
2
1 1
```

**Output:**

```
1
```

Explanation: You have 3 children and 2 cookies. The greed factors of 3 children are 1, 2, 3.

And even though you have 2 cookies, since their size is both 1, you could only make the child whose greed factor is 1 content.

You need to output 1.

**Constraints:**

$1 \leq g.length \leq 3 \cdot 10^4$

$0 \leq s.length \leq 3 \cdot 10^4$

$1 \leq g[i], s[j] \leq 2^{31} - 1$

**Answer:** (penalty regime: 0 %)

```
1 #include <stdio.h>
2 #include <stdlib.h>
3 int compare(const void *a, const void *b) {
4     return (*(int*)a - *(int*)b);
5 }
6
7 int findContentChildren(int* g, int gSize, int* s, int sSize) {
8     qsort(g, gSize, sizeof(int), compare);
9     qsort(s, sSize, sizeof(int), compare);
10    int child_idx = 0;
11    int cookie_idx = 0;
12    int content_children = 0;
13    while (child_idx < gSize && cookie_idx < sSize) {
14        if (s[cookie_idx] >= g[child_idx]) {
15
16            content_children++;
17            child_idx++;
18            cookie_idx++;
19        } else {
20            cookie_idx++;
21        }
22    }
23
24    return content_children;
25 }
26
27 int main() {
28     int gSize;
29     scanf("%d", &gSize);
30     int g[gSize];
31     for (int i = 0; i < gSize; i++) {
32         scanf("%d", &g[i]);
33     }
34
35     int sSize;
36
37     scanf("%d", &sSize);
38 }
```

```
39     int s[sSize];
40     for (int i = 0; i < sSize; i++) {
41         scanf("%d", &s[i]);
42     }
43
44     int result = findContentChildren(g, gSize, s, sSize);
45     printf("%d",result);
46
47     return 0;
48 }
```

|   | Input | Expected | Got |   |
|---|-------|----------|-----|---|
| ✓ | 2     | 2        | 2   | ✓ |
|   | 1 2   |          |     |   |
|   | 3     |          |     |   |
|   | 1 2 3 |          |     |   |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)



ALVIN B 2024-CSE ▾

**A2****Started on** Saturday, 6 September 2025, 7:39 PM**State** Finished**Completed on** Saturday, 6 September 2025, 9:56 PM**Time taken** 2 hours 16 mins**Marks** 1.00/1.00**Grade** 10.00 out of 10.00 (100%)

**Question 1** | Correct Mark 1.00 out of 1.00

A person needs to eat burgers. Each burger contains a count of calorie. After eating the burger, the person needs to run a distance to burn out his calories.

If he has eaten  $i$  burgers with  $c$  calories each, then he has to run at least  $3^i * c$  kilometers to burn out the calories. For example, if he ate 3

burgers with the count of calorie in the order: [1, 3, 2], the kilometers he needs to run are  $(3^0 * 1) + (3^1 * 3) + (3^2 * 2) = 1 + 9 + 18 = 28$ .

But this is not the minimum, so need to try out other orders of consumption and choose the minimum value. Determine the minimum distance

he needs to run. Note: He can eat burger in any order and use an efficient sorting algorithm. Apply greedy approach to solve the problem.

**Input Format**

First Line contains the number of burgers

Second line contains calories of each burger which is  $n$  space-separate integers

**Output Format**

Print: Minimum number of kilometers needed to run to burn out the calories

**Sample Input**

```
3
5 10 7
```

**Sample Output**

```
76
```

**For example:**

| Test        | Input      | Result |
|-------------|------------|--------|
| Test Case 1 | 3<br>1 3 2 | 18     |

**Answer:** (penalty regime: 0 %)

```

1  #include <stdio.h>
2  #include <math.h>
3  int main() {
4      int n;
5      scanf("%d", &n);
6      int arr[n];
7      for(int i=0;i<n;i++){
8          scanf("%d",&arr[i]);
9      }
10     if(n==0){
11         printf("%d",0);
12     }
13     else{
14         int c=0;
15         for(int i=0;i<n;i++){
16             for(int j=0;j<n;j++){
17                 if(arr[i]>arr[j]){
18                     int t=arr[i];
19                     arr[i]=arr[j];
20                     arr[j]=t;
21                 }
22             }
23         }
24         for(int i=0;i<n;i++){
25             c=c+(pow(n,i)*arr[i]);
26         }
27         printf("%d",c);
28     }

```

29 | }

|   | Test        | Input        | Expected | Got |   |
|---|-------------|--------------|----------|-----|---|
| ✓ | Test Case 1 | 3<br>1 3 2   | 18       | 18  | ✓ |
| ✓ | Test Case 2 | 4<br>7 4 9 6 | 389      | 389 | ✓ |
| ✓ | Test Case 3 | 3<br>5 10 7  | 76       | 76  | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)





ALVIN B 2024-CSE ▾

A2

|              |                                     |
|--------------|-------------------------------------|
| Started on   | Saturday, 6 September 2025, 7:46 PM |
| State        | Finished                            |
| Completed on | Saturday, 6 September 2025, 7:50 PM |
| Time taken   | 4 mins 6 secs                       |
| Marks        | 1.00/1.00                           |
| Grade        | 10.00 out of 10.00 (100%)           |

**Question 1** | Correct | Mark 1.00 out of 1.00

Given an array of N integer, we have to maximize the sum of  $\text{arr}[i] * i$ , where  $i$  is the index of the element ( $i = 0, 1, 2, \dots, N$ ). Write an algorithm based on Greedy technique with a Complexity  $O(n \log n)$ .

Input Format:

First line specifies the number of elements- $n$

The next  $n$  lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

**Answer:** (penalty regime: 0 %)

```

1  #include <stdio.h>
2  #include <stdlib.h>
3  int compare(const void *a, const void *b) {
4      return (*(int *)a - *(int *)b);
5  }
6
7  int main() {
8      int n;
9      scanf("%d", &n);
10
11     int arr[n];
12     for(int i = 0; i < n; i++) {
13         scanf("%d", &arr[i]);
14     }
15
16     qsort(arr, n, sizeof(int), compare);
17
18     long long maxSum = 0;
19     for(int i = 0; i < n; i++) {
20         maxSum += (long long)arr[i] * i;
21     }
22
23     printf("%lld\n", maxSum);
24     return 0;
25 }
26

```

|   | Input | Expected | Got |   |
|---|-------|----------|-----|---|
| ✓ | 5     | 40       | 40  | ✓ |
|   | 2     |          |     |   |
|   | 5     |          |     |   |
|   | 3     |          |     |   |
|   | 4     |          |     |   |
|   | 0     |          |     |   |

|   | Input  | Expected | Got |   |
|---|--|----------|-----|---|
| ✓ | 10<br>2<br>2<br>2<br>4<br>4<br>3<br>3<br>5<br>5<br>5 | 191      | 191 | ✓ |
| ✓ | 2<br>45<br>3   | 45       | 45  | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)



ALVIN B 2024-CSE ▾

A2

|              |                                     |
|--------------|-------------------------------------|
| Started on   | Saturday, 6 September 2025, 7:50 PM |
| State        | Finished                            |
| Completed on | Saturday, 6 September 2025, 7:58 PM |
| Time taken   | 7 mins 53 secs                      |
| Marks        | 1.00/1.00                           |
| Grade        | 10.00 out of 10.00 (100%)           |

**Question 1** | Correct Mark 1.00 out of 1.00

Given two arrays `array_One[]` and `array_Two[]` of same size `N`. We need to first rearrange the arrays such that the sum of the product of pairs (1 element from each) is minimum. That is  $\text{SUM}(A[i] * B[i])$  for all `i` is minimum.

**For example:**

| Input | Result |
|-------|--------|
| 3     | 28     |
| 1     |        |
| 2     |        |
| 3     |        |
| 4     |        |
| 5     |        |
| 6     |        |

**Answer:** (penalty regime: 0 %)

```

1 #include <stdio.h>
2 #include <stdlib.h>
3 int compare_asc(const void *a, const void *b) {
4     return (*(int *)a - *(int *)b);
5 }
6 int compare_desc(const void *a, const void *b) {
7     return (*(int *)b - *(int *)a);
8 }
9
10 int main() {
11     int n;
12     scanf("%d", &n);
13
14     int array_One[n], array_Two[n];
15
16     for(int i = 0; i < n; i++) {
17         scanf("%d", &array_One[i]);
18     }
19
20     for(int i = 0; i < n; i++) {
21         scanf("%d", &array_Two[i]);
22     }
23     qsort(array_One, n, sizeof(int), compare_asc);
24     qsort(array_Two, n, sizeof(int), compare_desc);
25
26     long long min_sum = 0;
27     for(int i = 0; i < n; i++) {
28         min_sum += (long long)array_One[i] * array_Two[i];
29     }
30
31     printf("%lld\n", min_sum);
32     return 0;
33 }
34

```

|   | Input | Expected | Got |   |
|---|-------|----------|-----|---|
| ✓ | 3     | 28       | 28  | ✓ |
|   | 1     |          |     |   |
|   | 2     |          |     |   |
|   | 3     |          |     |   |
|   | 4     |          |     |   |
|   | 5     |          |     |   |
|   | 6     |          |     |   |

|   | Input   | Expected | Got |   |
|---|---|----------|-----|---|
| ✓ | 4<br>7<br>5<br>1<br>2<br>1<br>3<br>4<br>1                 | 22       | 22  | ✓ |
| ✓ | 5<br>20<br>10<br>30<br>10<br>40<br>8<br>9<br>4<br>3<br>10 | 590      | 590 | ✓ |

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

[Back to Course](#)