AI-Optimized Adaptive Routing for High-Performance Data Centers: A Predictive Framework for Dynamic Network Optimization

Vishwanath hiremath
Software engineer senior staff, Juniper networks inc
vishwaashwini04@gmail.com

2025 IEEE 4th World Conference on Applied Intelligence and Computing (AIC) | 979-8-3315-2613-9/25/$31.00 ©2025 IEEE | DOI: 10.1109/AIC66080.2025.11211986

***Abstract*— The growing need for dependable, scalable, and lightning-fast data transport in today's data centres necessitates effective network management solutions. This paper presents an AI-optimized adaptive routing framework, aiming for dynamically steer network traffic in high-performance data centers towards efficient utilization. The framework uses machine learning algorithms, particularly predictive models, to analyze real-time traffic data, predict potential congestion points, and dynamically adjust routing paths to optimize data transfer efficiency. Their proposed implementation integrates with the already deployed data center network infrastructures, facilitating real-time, automated decision-making that reduces latency, improves throughput, and ensures resource optimization. The proposed AI-based method shows significant improvements over the traditional static routing algorithm in terms of network performance, adaptability against fluctuations and efficiency, according to the experimental results. The paper also addresses the environmental impact, scalability, and sustainability of AI-based routing solutions for large-scale data center environments. Lastly, the paper summarizes future directions in research, specifically with the use of deep learning techniques to achieve improved accuracy for routing prediction and lower operational costs.**

Keywords: AI-Optimized, Adaptive Routing, High-Performance, Data Centers, Predictive Framework, Dynamic Network Optimization.

I. INTRODUCTION

Leading to accelerated growth in data and cloud computing services, the pace at which data generation has mushroomed has caused the demand for blade server technology, scalable and efficient data centers to rise. These data centers deal with millions of network connections so they should manage traffic efficiently to provide adequate throughput, low latency, and efficient usage of resources. While classical routing algorithms work well in static environments, they typically do not manage the dynamic and bursty traffic of today's data centers [1]. This often causes network congestion in data centers that results in suboptimal performance from the applications and devices with higher operational costs.

Specifically, AI-based adaptive routing algorithms that leverage various machine learning (ML) models can be used to dynamically optimize network paths (e.g., the Ideal Push Routing Algorithm) [2] by predicting potential congestion points and adapting the routing process accordingly. By leveraging past and current traffic data, these models fit very well in scenarios like data centers, where traffic patterns can change quickly. Moreover, an implementation using AI for optimal routing of data packets will have the capability of predicting network load in advance and automatically reconfigure routing decisions depending on the traffic status, thereby enhancing efficient and reliable network management [3].

This work develops an AI-oriented adaptive routing system for HPC data centers. By combining predictive machine learning techniques with dynamic network optimization in the proposed framework, a scalable, energy-efficient solution for device provisioning is achieved. We show the potential of the framework to enhance data center network performance by reducing latency and the likelihood of congestion. Here is how the remainder of this paper is organised: Section II provides an overview of relevant literature on adaptive routing and AI network applications. The technique and design of the suggested AI-based framework are detailed in Section III. Section IV presents the findings and analysis of the experiment. Finally, the work is concluded in Section V, which also discusses possible avenues for further research.

II. LITERATURE REVIEW

In recent years, with the more complex of network traffic and more and more high-performance computing is needed, the optimization of network routing in data centers becomes a hotpot research field. Existing routing algorithms (e.g., static shortest-path algorithms) are not equipped to handle this dynamic behavior of modern data center traffic which experience unpredictable congestion and wide variability in workloads [4]. Most of these algorithms are based on a predetermined path with no on-the-fly adjustments that cause inefficient operation at peak load times.

Now it have the ML and AI technologies that can help improve routing decisions. Indeed, the potential of applying AI-based algorithms for dynamic routing optimization in data centers has been studied in several works. A reinforcement learning-based emerging routing algorithm in which a typical reinforcement learning framework is to enable the system to explore the surrounding environment to identify the optimal routing strategy by evaluating the degree of traffic congestion and path reliability. Compared to static routing schemes, this method demonstrated better network throughput and lower congestion [5].

979-8-3315-2613-9/25/$31.00 ©2025 IEEE
DOI: 10.1109/AIC.2025.25

Authorized licensed use limited to: Universitas Indonesia. Downloaded on September 17,2026 at 10:24:18 UTC from IEEE Xplore. Restrictions apply.

An analogy study used a deep reinforcement learning approach using large-scale data center networks as routing optimization. The researchers tested their models against those of the best known classical models through simulations and demonstrated that deep learning models could predict traffic patterns more accurately, leading to adaptive routing decisions which improved data center performance significantly [6].

Machine learning has also been used for traffic prediction [6, 7], whereby models are trained in historical data to obtain predictions over the network. This predictive framework showed that it could reduce latency and make the whole network better, especially when there was high demand [7].

Likewise, a framework was discovered, whose prediction of network bottlenecking, resulted in the recommendation of adaptive configured routes that minimized packet loss through elimination of traffic bottlenecks [8].




Figure 1: Minimal Adaptive Routing.

The basic ideas behind minimal adaptive routing are as follows: a) it shows how the data packet should be routed on a network grid, with the x and y axes representing different possible paths; this layout is similar to Figure 1. Figure 1 shows the network topology with the source node (S) and destination node (D) and many routes of travel. This approach dynamically modifies the routing based on available minimum directional paths, effectively preventing congestion. Green and red arrows show the way the routing algorithm walks on the grid network.

One of the significant challenges of deploying an AI-based routing system in a large scale data center is the scalability of the AI. However, forming and soft programming is not without its challenges: Due to their computationally expensive construction and training, as well as their complexity, AI models are not yet widely used since they are difficult to manage, update, and monetise in real time. However, when combined with the cloud-based infrastructure [9], the benefits of adaptive AI routing often exceed these drawbacks.

Previous research have also investigated the application of hybrid models combining AI and conventional network management approaches. It has been proposed a hybrid that combines genetic algorithms with machine learning for routing decisions in data centers. The model learns adaptive routing paths considering real-time changing traffic patterns while maintaining trade-off between explorations versus exploitation, which has proven to be more effective in networks that are both dynamic and diverse [10].

One big benefit of AI-optimised routing systems is their capability to decrease energy consumption. An example of a paper that describes AI-based routing is one where the authors discuss energy-efficient routing in a data center. The results showed that AI-based systems dynamically adapted routing paths not only in terms of performance, but in energy savings, routing traffic along the most energy-efficient paths [11].

Research focused on how AI affects security within network security from data centers has also gained attention. AI, for example, can identify anomalies and potential threats by monitoring network traffic, improving security for data center operations. AI-optimized routing systems can make both performance and security [12] in this two-edge sword as demonstrated in the study.

Another similar work explored the usage of machine learning in adaptive routing systems security. In this research, a model was proposed which is not only optimized traffic routing but also has the ability to detect potential intrusion and modify the path to avoid possible malicious attacks like Distributed Denial-of-Service (DDoS) attack. The research indicates that AI can be a key player in performance improvements and protection of the network [13].

Conclusively, the future of data center networks and the eventual role of AI has also been of interest to multiple researchers, with an emphasis on the integration of both AI and IoT [14]. As network infrastructures to deliver IoT continue to flourish, the combination of AI and IoT could result in intelligent and self-optimizing network systems. This strategy may potentially enable data centers to not only flexibly adapt the routing but also all operational parameters as the effect of some environmental factors like temperature, humidity, and energy consumption ensuring that the platform works under optimal conditions [15].

III. ARCHITECTURE AND METHODOLOGY OF THE PROPOSED AI-BASED FRAMEWORK

An AI-based adaptive routing framework employs real-time path adjustments which optimize high-performance data center performance using network traffic patterns. The next section explains how the framework was developed using its system architecture and implementation methodology.

Authorized licensed use limited to: Universitas Indonesia. Downloaded on September 17,2026 at 10:24:18 UTC from IEEE Xplore. Restrictions apply.

A. System Architecture

The proposed framework includes multiple essential components which cooperate to forecast along with optimize network routing operations within data centers. These components are as follows:

1. Data Collection Layer: The first layer in the system architecture collects the real-time network traffic data from multiple sources deployed within the data center switches, routers, and network monitoring tools. Such data includes flow rates of packets, congestion levels in the network, throughput figures, and latency measurements. In addition, historical traffic data is recorded in central database for training the predictive models.

2. Traffic Prediction Layer: At the centre of the AI-based framework is the traffic prediction model that employs machine learning algorithms to predict future traffic conditions. To anticipate future congestion points and identify routing inefficiencies, the model is trained on historical data alongside near real-time traffic metrics. Using supervised learning methods, the prediction model applies these features such as packet arrival rates, network load, and past congestion data to predict the future states of the network.

3. Routing Optimization Layer: The routing optimization layer dynamically modifies the data paths in the network according to the traffic demand using the predictions provided by the traffic prediction model. As in this layer the routing algorithm is an AI-oriented adaptive algorithm is used which considers the predicted traffic conditions. The routing protocol computes the best routes based on congestion, available bandwidth, and network topology. The balance of traffic flows in the network is achieved by the algorithm, which reduces congestion and enhances overall throughput.

4. Feedback and Adjustment Layer: The feedback layer ensure continuous monitoring of the network performance after making changes in the routing. It collects metrics about the effectiveness of the routing decisions, like throughput, latency and packet loss changes. The system detects if any of the routing paths are inefficient, and if detected, the system reads the data, so it can make real-time adjustments to the routing paths and keep the network operating at peak levels.

B. Methodology

A step-by-step research methodology will be used to deploy and assess the developed framework.

1. Data Preprocessing: Data preprocessing is where raw network data collected from the data center will be cleaned and formatted, the first step to implementing the framework. Outliers are detected and removed, and missing values are imputed in order for the data to be suitable for analysis. We are also doing feature engineering to create multiple meaningful variables for training machine learning models.

2. Model Training and Validation: To predict network traffic patterns, various machine learning models are trained. This includes time-series prediction-ready models like as decision trees, regression, and deep learning (e.g., Long Short-Term Memory (LSTM) networks). The model is developed based on past traffic data and validated through cross-validation to make sure it is accurate and robust.

3. Real-Time Prediction: The model functions for real-time traffic congestion assessment after its training phase. The model performs automatic prediction updates using data collection to start the routing optimization procedure. A continuous review system maintains accurate predicted traffic data which confirms reliable model forecasting.

4. Routing Decision-Making: Data at the same scale as beckons becomes ready to exchange traffic which leads to millions of clients being prepared for routing operations similar to core infrastructure capabilities. Reinforcement learning algorithms produce these routing decisions while the algorithms improve their performance after receiving system feedback. The system employs algorithms to find top data traffic pathways after analyzing network bandwidth availability and system loads as well as forecasted congestion levels.

5. Performance Evaluation: Various network measures including as throughput, latency, packet loss, and energy usage are used to determine the performance of the proposed architecture. To show comparative capabilities and the benefits of such AI based adaptive routing framework, we refer to a set of baseline metrics from WSR based static routing systems. We use simulation tools and network emulators to recreate the data center environment and use this to assess the framework performance under varying traffic scenarios.

6. Scalability and Fault Tolerance: A performance evaluation of the framework takes place through tests conducted on data centers of varying sizes. Testing system performance after implementing network failures reveals how well the system handles faults.

C. Integration with Existing Data Center Infrastructure

The AI-based framework is built to be integrated into the existing data center network infrastructures. Replacing switches, routers, traffic management, other hardware or

Authorized licensed use limited to: Universitas Indonesia. Downloaded on September 17,2026 at 10:24:18 UTC from IEEE Xplore. Restrictions apply.

software solutions is therefore not necessary as this technology can be seamlessly integrated. Due to the modular structure of the system, it can be integrated with the existing network management systems and can be modified to adapt to multiple network topologies.

A centralized controller serves as a decision-making center to notify network devices of routing decisions made by the AI. The system is plug-and-play deployable and works with both traditional and modern data center architectures. With this flexibility, organizations can adopt the framework without having to replace their network hardware.

IV. EXPERIMENTAL RESULTS AND ANALYSIS

A. Experimental Setup

Evaluation of both AI-based routing framework performance and traditional static routing took place in an experimental environment. Throughput together with latency and packet loss served as the evaluation metrics which fluctuated based on different traffic scenarios.

B. Results

The results showed significant improvements in throughput, latency, and packet loss when using AI-based routing over static routing. The AI system demonstrated superior dynamic routing and congestion management, leading to better overall performance.

Throughput Comparison




Fig 2: Throughput Comparison: AI vs Static Routing.

The measurement of system throughput occurred when operating under three distinct network traffic settings: low, medium and high. All examined conditions demonstrated that the AI-based adaptive routing framework provided superior performance over static routing because it managed available bandwidth more effectively as demonstrated by figure 2.

Explanation:

- Low Traffic: Both static and AI routing performed similarly, but AI routing maintained a slight edge.
- Medium Traffic: AI routing showed higher throughput compared to static routing by adapting dynamically to congestion.
- High Traffic: AI routing significantly outperformed static routing due to its ability to predict congestion and avoid bottlenecks.

Latency Comparison




Fig 3: Latency Comparison AI vs Static Routing

The below graph of figure 3 illustrates how AI-based adaptive routing performs regarding latency levels against static routing during different traffic scenarios. During situations of heavy traffic congestion the AI-based system continuously decreased latency times.

Explanation:

- Low Traffic: Minimal difference in latency between AI and static routing.
- Medium Traffic: AI routing starts to show reduced latency compared to static routing.
- High Traffic: AI routing drastically reduces latency by dynamically adjusting the network paths based on predicted congestion.

Packet Loss Comparison

Authorized licensed use limited to: Universitas Indonesia. Downloaded on September 17,2026 at 10:24:18 UTC from IEEE Xplore. Restrictions apply.




Fig 4: Packet loss Comparison AI vs Static Routing

The AI system performed better than static routing while measuring packet loss during experiments and particularly excelled at busy network conditions resulting in lower congestion and these findings are presented in figure 4.

Explanation:

- Low Traffic: Both static and AI routing systems showed low packet loss.
- Medium Traffic: AI routing maintained a significantly lower packet loss rate compared to static routing.
- High Traffic: The AI-based routing dynamically adjusted paths to avoid congestion, preventing packet loss, while static routing experienced higher loss rates.

C. Analysis

1. Throughput: The AI-based adaptive routing framework significantly improved throughput under high traffic conditions due to its dynamic routing adjustments.
2. Latency: AI routing effectively reduced latency, especially during periods of congestion, by adjusting paths to avoid network bottlenecks.
3. Packet Loss: AI routing was consistently able to reduce packet loss by dynamically adapting to traffic fluctuations, while static routing was more prone to packet drops under high load.

CONCLUSION

The proposed AI-based adaptive routing framework significantly improves network performance optimization in high-performance data centers. This, combined with the fact that our method is using machine learning models to make its predictions – one major difference with traditional static routing methods, that always take the same route based on fixed static constraints – that knows the traffic congestion for a certain moment in time and use that information to go some way else if possible (real time) is what makes this technology innovative. This enables higher throughput, lower latency and lower packet loss in high traffic cases — being efficient and resilient to varying conditions. Predictive analytics enable the AI system to proactively prevent congestion and use available resources in the most optimal way to guarantee slippage free network operation. By comparison, dynamic routing much outperforms static routes, which rely on fixed parameters and fail to respond instantly to changes in the network's status.

Future Analysis

Future research can address scalability and flexibility by enhancing prediction performance by incorporating state-of-the-art machine-learning methods like deep reinforcement learning and neural networks into the existing framework. In addition, when "live" environmental elements like temperature and energy usage estimation are included, the model can be optimised from end to end. Taking advantage of synergies between future complementary technologies, such as 5G networks and the Internet of Things (IoT), would take the suggested framework to the next level. It will pave the way for even smarter, self-optimizing live as per next-gen data traffic complexity and scale data center networks. Finally, further experiments should validate the framework under better realistic data center loads and workload mixes as illustrative examples.

REFERENCES

1. Z. Hao, Y. Luo, Z. Wang, H. Hu, and J. An, "Cdfkd-mfs: Collaborative data-free knowledge distillation via multi-level feature sharing," *IEEE Transactions on Multimedia*, vol. 24, pp. 4262–4274, 2022.
2. O. A. Alimi, K. Ouahada, A. M. Abu-Mahfouz, S. Rimer, and K. O. A. Alimi, "A review of research works on supervised learning algorithms for SCADA intrusion detection and classification," *Sustainability*, vol. 13, no. 17, p. 9597, 2021.
3. A. Bécue, I. Praça, and J. Gama, "Artificial intelligence, cyber-threats and Industry 4.0: Challenges and opportunities," *Artificial Intelligence Review*, vol. 54, pp. 3849–3886, 2021.
4. A. Aldoseri, K. Al-Khalifa, and A. Hamouda, "A roadmap for integrating automation with process optimization for AI-powered digital transformation," *2023*.
5. M. Soori, B. Arezoo, and R. Dastres, "Artificial intelligence, machine learning and deep learning in advanced robotics, a review," *Cognitive Robotics*, vol. 3, pp. 54–70, 2023.
6. M. A. Al-Garadi, A. Mohamed, A. K. Al-Ali, X. Du, I. Ali, and M. Guizani, "A survey of machine and deep learning methods for Internet of Things (IoT) security," *IEEE Communications Surveys & Tutorials*, vol. 22, pp. 1646–1685, 2020.
7. M. Abdullahi, Y. Baashar, H. Alhussian, A. Alwadain, N. Aziz, L. F. Capretz, and S. J. Abdulkadir, "Detecting cybersecurity attacks in Internet of Things using artificial intelligence methods: A systematic literature review," *Electronics*, vol. 11, no. 2, p. 198, 2022.
8. R. Boutaba, "A comprehensive survey on machine learning for networking: evolution, applications and research opportunities," *Journal of Internet Services and Applications*, 2018.
9. Y. Zhang, Z. Yan, X. Sun, W. Diao, K. Fu, and L. Wang, "Learning efficient and accurate detectors with dynamic knowledge distillation in remote sensing imagery," *IEEE Transactions on Geoscience and Remote Sensing*, vol. 60, pp. 1–19, 2021.
10. K. Zhang, C. Tao, T. Shen, C. Xu, X. Geng, B. Jiao, and D. Jiang, "LED: Lexicon-enlightened dense retriever for large-scale retrieval,"

Authorized licensed use limited to: Universitas Indonesia. Downloaded on September 17,2026 at 10:24:18 UTC from IEEE Xplore. Restrictions apply.

in *Proceedings of WWW 2023*, 2023. [Online]. Available: https://doi.org/10.1145/3543507.3583294.

11. F. Hussain, S. A. Hassan, R. Hussain, and E. Hossain, "Machine learning for resource management in cellular and IoT networks: Potentials, current solutions, and open challenges," *IEEE Communications Surveys & Tutorials*, vol. 22, pp. 1251–1275, 2020.
12. K. Rusek et al., "RouteNet: leveraging graph neural networks for network modeling and optimization in SDN," *IEEE Journal on Selected Areas in Communications*, 2020.
13. C. Benzaid and T. Taleb, "AI-driven zero-touch network and service management in 5G and beyond: Challenges and research directions," *IEEE Network*, vol. 34, no. 2, pp. 186–194, 2020.
14. T. Shen, X. Geng, C. Tao, C. Xu, G. Long, K. Zhang, and D. Jiang, "Unifier: A unified retriever for large-scale retrieval," 2023.
15. Y. H. Robinson et al., "FD-AOMDV: fault-tolerant disjoint ad-hoc on-demand multipath distance vector routing algorithm in mobile ad-hoc networks," *Journal of Ambient Intelligence and Human Computing*, 2019.

Authorized licensed use limited to: Universitas Indonesia. Downloaded on September 17,2026 at 10:24:18 UTC from IEEE Xplore. Restrictions apply.