

# DTD - XML Building Blocks

< Previous</p>

Next >

The main building blocks of both XML and HTML documents are elements.

## The Building Blocks of XML Documents

Seen from a DTD point of view, all XML documents are made up by the following building blocks:

- Elements
- Attributes
- Entities
- PCDATA
- CDATA

### **Elements**

Elements are the **main building blocks** of both XML and HTML documents.

Examples of HTML elements are "body" and "table". Examples of XML elements could be "note" and "message". Elements can contain text, other elements, or be empty. Examples of empty HTML elements are "hr", "br" and "img".

Examples:



### **Attributes**

Attributes provide extra information about elements.

Attributes are always placed inside the opening tag of an element. Attributes always come in name/value pairs. The following "img" element has additional information about a source file:

```
<img src="computer.gif" />
```


The name of the element is "img". The name of the attribute is "src". The value of the attribute is "computer.gif". Since the element itself is empty it is closed by a " /".

**ADVERTISEMENT** 

### **Entities**

Some characters have a special meaning in XML, like the less than sign (<) that defines the start of an XML tag.

Most of you know the HTML entity: " ". This "no-breaking-space" entity is used in HTML to insert an extra space in a document. Entities are expanded when a document is parsed by an XML parser.



### **PCDATA**

PCDATA means parsed character data.

Think of character data as the text found between the start tag and the end tag of an XML element.

PCDATA is text that WILL be parsed by a parser. The text will be examined by the parser for entities and markup.

Tags inside the text will be treated as markup and entities will be expanded.

However, parsed character data should not contain any &, <, or > characters; these need to be represented by the &amp; &lt; and &gt; entities, respectively.

### **CDATA**

CDATA means character data.

**CDATA** is text that will **NOT** be parsed by a parser. Tags inside the text will **NOT** be treated as markup and entities will not be expanded.

Previous

Next >



 $\triangleright \times$ 



■ . CSS JAVASCRIPT SQL PYTHON JAVA PHP HOW TO W3.CSS C

ADVERTISEMENT



Tutorials **▼** Exercises **▼** Services **▼** Q Sign Up Log in

= .

W3.CSS

C

CSS JAVASCRIPT SQL PYTHON JAVA PHP HOW TO



SPACES

**UPGRADE** 

AD-FREE

NEWSLETTER GET CERTIFIED

**CONTACT US** 

#### **Top Tutorials**

**HTML Tutorial CSS Tutorial JavaScript Tutorial** How To Tutorial **SQL Tutorial Python Tutorial** W3.CSS Tutorial **Bootstrap Tutorial PHP Tutorial** Java Tutorial C++ Tutorial jQuery Tutorial

#### **Top References**

**HTML Reference CSS Reference JavaScript Reference SQL** Reference **Python Reference W3.CSS Reference Bootstrap Reference PHP Reference HTML Colors** Java Reference **Angular Reference** jQuery Reference

**Top Examples** 

**Get Certified** 



Tutorials **▼** Exercises **▼** Services **▼** Q Sign Up Log in

JAVASCRIPT

SQL

PYTHON

PHP

HOW TO

W3.CSS

C

CSS

> **W3.CSS Examples Bootstrap Examples PHP Examples**

Java Examples **XML Examples** jQuery Examples

**PHP Certificate** jQuery Certificate **Java Certificate** C++ Certificate **C# Certificate XML Certificate** 

JAVA











#### FORUM ABOUT CLASSROOM

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning.

Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness

of all content. While using W3Schools, you agree to have read and accepted our terms of use, cookie and privacy policy.

Copyright 1999-2024 by Refsnes Data. All Rights Reserved. W3Schools is Powered by W3.CSS.