

XSLT <xsl:choose> Element

[< Previous](#)[Next >](#)

The <xsl:choose> element is used in conjunction with <xsl:when> and <xsl:otherwise> to express multiple conditional tests.

The <xsl:choose> Element

Syntax

```
<xsl:choose>
  <xsl:when test="expression">
    ... some output ...
  </xsl:when>
  <xsl:otherwise>
    ... some output ....
  </xsl:otherwise>
</xsl:choose>
```

Where to put the Choose Condition

To insert a multiple conditional test against the XML file, add the <xsl:choose>, <xsl:when>, and <xsl:otherwise> elements to the XSL file:

```

<?xml version="1.0" encoding="UTF-8" ?>
<xsl:stylesheet version="1.0"
xmlns:xsl="http://www.w3.org/1999/XSL/Transform">

<xsl:template match="/">
  <html>
  <body>
  <h2>My CD Collection</h2>
  <table border="1">
    <tr bgcolor="#9acd32">
      <th>Title</th>
      <th>Artist</th>
    </tr>
    <xsl:for-each select="catalog/cd">
      <tr>
        <td><xsl:value-of select="title"/></td>
        <xsl:choose>
          <xsl:when test="price > 10">
            <td bgcolor="#ff00ff">
              <xsl:value-of select="artist"/></td>
          </xsl:when>
          <xsl:otherwise>
            <td><xsl:value-of select="artist"/></td>
          </xsl:otherwise>
        </xsl:choose>
      </tr>
    </xsl:for-each>
  </table>
  </body>
  </html>
</xsl:template>

</xsl:stylesheet>

```

[Try it Yourself »](#)

The code above will add a pink background-color to the "Artist" column WHEN the price of the CD is higher than 10.

Example

```
<?xml version="1.0" encoding="UTF-8"?>
<xsl:stylesheet version="1.0"
xmlns:xsl="http://www.w3.org/1999/XSL/Transform">

<xsl:template match="/">
  <html>
  <body>
  <h2>My CD Collection</h2>
  <table border="1">
    <tr bgcolor="#9acd32">
      <th>Title</th>
      <th>Artist</th>
    </tr>
    <xsl:for-each select="catalog/cd">
      <tr>
        <td><xsl:value-of select="title"/></td>
        <xsl:choose>
          <xsl:when test="price > 10">
            <td bgcolor="#ff00ff">
              <xsl:value-of select="artist"/></td>
          </xsl:when>
          <xsl:when test="price > 9">
            <td bgcolor="#cccccc">
              <xsl:value-of select="artist"/></td>
          </xsl:when>
          <xsl:otherwise>
            <td><xsl:value-of select="artist"/></td>
          </xsl:otherwise>
        </xsl:choose>
      </tr>
    </xsl:for-each>
  </table>
  </body>
</html>
</xsl:template>

</xsl:stylesheet>
```

The code above will add a pink background color to the "Artist" column WHEN the price of the CD is higher than 10, and a grey background-color WHEN the price of the CD is higher than 9 and lower or equal to 10.

[< Previous](#)[Next >](#)

W3schools Pathfinder

Track your progress - it's free!

[Sign Up](#)[Log in](#)

Get your
**knowledge
certified!**

Start Today!



COLOR PICKER



[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)

 [CSS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#)

[SPACES](#)[UPGRADE](#)[AD-FREE](#)[NEWSLETTER](#)[GET CERTIFIED](#)[CONTACT US](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)
[jQuery Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)
[Angular Reference](#)
[jQuery Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[Java Examples](#)
[XML Examples](#)
[jQuery Examples](#)

Get Certified

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[Front End Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[PHP Certificate](#)
[jQuery Certificate](#)
[Java Certificate](#)
[C++ Certificate](#)
[C# Certificate](#)
[XML Certificate](#)

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[☰](#) [CSS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#)[FORUM](#) [ABOUT](#) [CLASSROOM](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning.

Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie and privacy policy](#).

Copyright 1999-2024 by Refsnes Data. All Rights Reserved. W3Schools is Powered by W3.CSS.