

XML Elements vs. Attributes

[< Previous](#)[Next >](#)

In XML, there are no rules about when to use attributes, and when to use child elements.

Use of Elements vs. Attributes

Data can be stored in child elements or in attributes.

Take a look at these examples:

```
<person sex="female">
  <firstname>Anna</firstname>
  <lastname>Smith</lastname>
</person>
```

```
<person>
  <sex>female</sex>
  <firstname>Anna</firstname>
  <lastname>Smith</lastname>
</person>
```

experience is that attributes are handy in HTML, but in XML you should try to avoid them. Use child elements if the information feels like data.

My Favorite Way

I like to store data in child elements.

The following three XML documents contain exactly the same information:

A date attribute is used in the first example:

```
<note date="12/11/2002">
  <to>Tove</to>
  <from>Jani</from>
  <heading>Reminder</heading>
  <body>Don't forget me this weekend!</body>
</note>
```

A date element is used in the second example:

```
<note>
  <date>12/11/2002</date>
  <to>Tove</to>
  <from>Jani</from>
  <heading>Reminder</heading>
  <body>Don't forget me this weekend!</body>
</note>
```

An expanded date element is used in the third: (THIS IS MY FAVORITE):

```
<note>
  <date>
    <day>12</day>
```

```
<from>Jani</from>
<heading>Reminder</heading>
<body>Don't forget me this weekend!</body>
</note>
```

Avoid using attributes?

Should you avoid using attributes?

Some of the problems with attributes are:

- attributes cannot contain multiple values (child elements can)
- attributes are not easily expandable (for future changes)
- attributes cannot describe structures (child elements can)
- attributes are more difficult to manipulate by program code
- attribute values are not easy to test against a DTD

If you use attributes as containers for data, you end up with documents that are difficult to read and maintain. Try to use **elements** to describe data. Use attributes only to provide information that is not relevant to the data.

Don't end up like this (this is not how XML should be used):

```
body - Don't forget me this weekend! /  
</note>
```

An Exception to my Attribute Rule

Rules always have exceptions.

My rule about attributes has one exception:

Sometimes I assign ID references to elements. These ID references can be used to access XML elements in much the same way as the NAME or ID attributes in HTML. This example demonstrates this:

```
<messages>  
<note id="p501">  
  <to>Tove</to>  
  <from>Jani</from>  
  <heading>Reminder</heading>  
  <body>Don't forget me this weekend!</body>  
</note>  
  
<note id="p502">  
  <to>Jani</to>  
  <from>Tove</from>  
  <heading>Re: Reminder</heading>  
  <body>I will not!</body>  
</note>  
</messages>
```

The ID in these examples is just a counter, or a unique identifier, to identify the different notes in the XML file, and not a part of the note data.

What I am trying to say here is that metadata (data about data) should be stored as attributes, and that data itself should be stored as elements.

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[CSS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#)

W3schools Pathfinder

Track your progress - it's free!

[Sign Up](#)[Log in](#)

Get your
**knowledge
certified!**

Start Today!



COLOR PICKER



[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[CSS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#)[NEWSLETTER](#)[GET CERTIFIED](#)[CONTACT US](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)
[jQuery Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)
[Angular Reference](#)
[jQuery Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[Java Examples](#)
[XML Examples](#)
[jQuery Examples](#)

Get Certified

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[Front End Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[PHP Certificate](#)
[jQuery Certificate](#)
[Java Certificate](#)
[C++ Certificate](#)
[C# Certificate](#)
[XML Certificate](#)

[FORUM](#) [ABOUT](#) [CLASSROOM](#)



Tutorials ▼

Exercises ▼

Services ▼



Sign Up

Log in

☰ . CSS JAVASCRIPT SQL PYTHON JAVA PHP HOW TO W3.CSS C

Copyright 1999-2024 by Refsnes Data. All Rights Reserved. W3Schools is Powered by W3.CSS.