

XSI Restrictions/Facets

[< Pre](#)[Next >](#)

Restrict
Restrict

fine acceptable values for XML elements or attributes.
its are called facets.

Rest

The foll
age can

Values

is an element called "age" with a restriction. The value of
or greater than 120:

```
<xs:element name="age" type="xs:integer" base="xs:integer" value="0"/>
<xs:restriction base="xs:integer" value="0"/>
<xs:restriction base="xs:integer" value="120"/>
</xs:restriction>
</xs:simpleType>
</xs:element>
```

Restrictions on a Set of Values

To limit the content of an XML element to a set of acceptable values, we would use the enumeration constraint.

```
ADVERTISEMENT
<xs:element name="car">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:enumeration value="Audi"/>
      <xs:enumeration value="Golf"/>
      <xs:enumeration value="BMW"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
```

The example above could also have been written like this:

```
<xs:element name="car" type="carType"/>

<xs:simpleType name="carType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Audi"/>
    <xs:enumeration value="Golf"/>
    <xs:enumeration value="BMW"/>
  </xs:restriction>
</xs:simpleType>
```

Note: In this case the type "carType" can be used by other elements because it is not a part of the "car" element.

ADVERTISEMENT

Calcula tu ahorro y empieza a ahorrar en tu factura de energía con Formidable de Endesa*sponsored by: Endesa*

Restrictions on a Series of Values

To limit the content of an XML element to define a series of numbers or letters that can be used, we would use the pattern constraint.

The example below defines an element called "letter" with a restriction. The only acceptable value is ONE of the LOWERCASE letters from a to z:

```
<xs:element name="letter">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern value="[a-z]"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
```

The next example defines an element called "initials" with a restriction. The only acceptable value is THREE of the UPPERCASE letters from a to z:

```
<xs:element name="initials">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern value="[A-Z][A-Z][A-Z]"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
```

ADVERTISEMENT

```
<xs:element name="initials">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern value="[a-zA-Z][a-zA-Z][a-zA-Z]"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
```

The next example defines an element called "choice" with a restriction. The only acceptable value is ONE of the following letters: x, y, OR z:

```
<xs:element name="choice">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern value="[xyz]"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
```

The next example defines an element called "prodid" with a restriction. The only acceptable value is FIVE digits in a sequence, and each digit must be in a range from 0 to 9:

```
<xs:element name="prodid">
  <xs:simpleType>
    <xs:restriction base="xs:integer">
      <xs:pattern value="[0-9][0-9][0-9][0-9][0-9]"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
```

Other Restrictions on a Series of Values

```

<xs:element name="letter">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern value="([a-z])*"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>

```

The next example also defines an element called "letter" with a restriction. The acceptable value is one or more pairs of letters, each pair consisting of a lower case letter followed by an upper case letter. For example, "sToP" will be validated by this pattern, but not "Stop" or "STOP" or "stop":

```

<xs:element name="letter">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern value="([a-z][A-Z])+"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>

```

The next example defines an element called "gender" with a restriction. The only acceptable value is male OR female:

```

<xs:element name="gender">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern value="male|female"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>

```

The next example defines an element called "password" with a restriction. There must be exactly eight characters in a row and those characters must be lowercase or

```
<xs:element name="password">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:pattern value="[a-zA-Z0-9]{8}"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
```

Restrictions on Whitespace Characters

To specify how whitespace characters should be handled, we would use the `whiteSpace` constraint.

This example defines an element called "address" with a restriction. The `whiteSpace` constraint is set to "preserve", which means that the XML processor WILL NOT remove any white space characters:

```
<xs:element name="address">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:whiteSpace value="preserve"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
```

This example also defines an element called "address" with a restriction. The `whiteSpace` constraint is set to "replace", which means that the XML processor WILL REPLACE all white space characters (line feeds, tabs, spaces, and carriage returns) with spaces:

```
<xs:element name="address">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:whiteSpace value="replace"/>
    </xs:restriction>
```

ADVERTISEMENT

This example also defines an element called "address" with a restriction. The whiteSpace constraint is set to "collapse", which means that the XML processor WILL REMOVE all white space characters (line feeds, tabs, spaces, carriage returns are replaced with spaces, leading and trailing spaces are removed, and multiple spaces are reduced to a single space):

```
<xs:element name="address">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:whiteSpace value="collapse"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
```

Restrictions on Length

To limit the length of a value in an element, we would use the length, maxLength, and minLength constraints.

This example defines an element called "password" with a restriction. The value must be exactly eight characters:

```
<xs:element name="password">
  <xs:simpleType>
    <xs:restriction base="xs:string">
      <xs:length value="8"/>
    </xs:restriction>
  </xs:simpleType>
</xs:element>
```

This example defines another element called "password" with a restriction. The value must be minimum five characters and maximum eight characters:

```

<xs:restriction base="xs:string">
  <xs:minLength value="5"/>
  <xs:maxLength value="8"/>
</xs:restriction>
</xs:simpleType>
</xs:element>

```

Restrictions for Datatypes

Constraint	Description
enumeration	Defines a list of acceptable values
fractionDigits	Specifies the maximum number of decimal places allowed. Must be equal to or greater than zero
length	Specifies the exact number of characters or list items allowed. Must be equal to or greater than zero
maxExclusive	Specifies the upper bounds for numeric values (the value must be less than this value)
maxInclusive	Specifies the upper bounds for numeric values (the value must be less than or equal to this value)
maxLength	Specifies the maximum number of characters or list items allowed. Must be equal to or greater than zero
minExclusive	Specifies the lower bounds for numeric values (the value must be greater than this value)
minInclusive	Specifies the lower bounds for numeric values (the value must be greater than or equal to this value)
minLength	Specifies the minimum number of characters or list items allowed. Must be equal to or greater than zero
pattern	Defines the exact sequence of characters that are acceptable
totalDigits	Specifies the exact number of digits allowed. Must be greater than zero



Tutorials ▼

Exercises ▼

Services ▼



Sign Up

Log in

≡ . CSS JAVASCRIPT SQL PYTHON JAVA PHP HOW TO W3.CSS C

ADVERTISEMENT

◀ Previous

Next ▶

W3schools Pathfinder

Track your progress - it's free!

Sign Up

Log in

ADVERTISEMENT

ADVERTISEMENT


Level up with XML Course

Gain skills, and get certified

Start Today!



COLOR PICKER



ADVERTISEMENT

ADVERTISEMENT

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[CSS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#)

ADVERTISEMENT

[SPACES](#)[UPGRADE](#)[AD-FREE](#)[NEWSLETTER](#)[GET CERTIFIED](#)[CONTACT US](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)
[jQuery Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)
[Angular Reference](#)
[jQuery Reference](#)

Top Examples

Get Certified

[HTML Certificate](#)

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[CSS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#)

W3.CSS Examples
Bootstrap Examples
ADVERTISEMENT
PHP Examples
Java Examples
XML Examples
jQuery Examples

jQuery Certificate
Java Certificate
C++ Certificate
C# Certificate
XML Certificate

[FORUM](#) [ABOUT](#) [CLASSROOM](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning. Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie and privacy policy](#).

Copyright 1999-2024 by Refsnes Data. All Rights Reserved. [W3Schools is Powered by W3.CSS](#).