

XML Namespaces

[< Previous](#)[Next >](#)

XML Namespaces provide a method to avoid element name conflicts.

Name Conflicts

In XML, element names are defined by the developer. This often results in a conflict when trying to mix XML documents from different XML applications.

This XML carries HTML table information:

```
<table>
  <tr>
    <td>Apples</td>
    <td>Bananas</td>
  </tr>
</table>
```

This XML carries information about a table (a piece of furniture):

```
<table>
  <name>African Coffee Table</name>
  <width>80</width>
```

If these XML fragments were added together, there would be a name conflict. Both contain a `<table>` element, but the elements have different content and meaning.

A user or an XML application will not know how to handle these differences.

Solving the Name Conflict Using a Prefix

Name conflicts in XML can easily be avoided using a name prefix.

This XML carries information about an HTML table, and a piece of furniture:

```
<h:table>
  <h:tr>
    <h:td>Apples</h:td>
    <h:td>Bananas</h:td>
  </h:tr>
</h:table>

<f:table>
  <f:name>African Coffee Table</f:name>
  <f:width>80</f:width>
  <f:length>120</f:length>
</f:table>
```

In the example above, there will be no conflict because the two `<table>` elements have different names.

ADVERTISEMENT

ADVERTISEMENT

XML Namespaces - The xmlns Attribute

When using prefixes in XML, a **namespace** for the prefix must be defined.

The namespace can be defined by an **xmlns** attribute in the start tag of an element.

The namespace declaration has the following syntax. `xmlns:prefix="URI"`.

```
<root>

<h:table xmlns:h="http://www.w3.org/TR/html4/">
  <h:tr>
    <h:td>Apples</h:td>
    <h:td>Bananas</h:td>
  </h:tr>
</h:table>

<f:table xmlns:f="https://www.w3schools.com/furniture">
  <f:name>African Coffee Table</f:name>
  <f:width>80</f:width>
  <f:length>120</f:length>
</f:table>

</root>
```

In the example above:

The xmlns attribute in the first <table> element gives the h: prefix a qualified namespace.

are associated with the same namespace.

Namespaces can also be declared in the XML root element:

```
<root xmlns:h="http://www.w3.org/TR/html4/"
xmlns:f="https://www.w3schools.com/furniture">

  <h:table>
    <h:tr>
      <h:td>Apples</h:td>
      <h:td>Bananas</h:td>
    </h:tr>
  </h:table>

  <f:table>
    <f:name>African Coffee Table</f:name>
    <f:width>80</f:width>
    <f:length>120</f:length>
  </f:table>

</root>
```

Note: The namespace URI is not used by the parser to look up information.

The purpose of using an URI is to give the namespace a unique name.

However, companies often use the namespace as a pointer to a web page containing namespace information.

Uniform Resource Identifier (URI)

A **Uniform Resource Identifier** (URI) is a string of characters which identifies an Internet Resource.

The most common URI is the **Uniform Resource Locator** (URL) which identifies an Internet domain address. Another, not so common type of URI is the **Uniform Resource Name** (URN).

child elements. It has the following syntax:

```
xmlns="namespaceURI"
```

This XML carries HTML table information:

```
<table xmlns="http://www.w3.org/TR/html4/">
  <tr>
    <td>Apples</td>
    <td>Bananas</td>
  </tr>
</table>
```

This XML carries information about a piece of furniture:

```
<table xmlns="https://www.w3schools.com/furniture">
  <name>African Coffee Table</name>
  <width>80</width>
  <length>120</length>
</table>
```

Namespaces in Real Use

XSLT is a language that can be used to transform XML documents into other formats.

The XML document below, is a document used to transform XML into HTML.

The namespace "http://www.w3.org/1999/XSL/Transform" identifies XSLT elements inside an HTML document:

```
<xsl:stylesheet version="1.0"
xmlns:xsl="http://www.w3.org/1999/XSL/Transform">

<xsl:template match="/">
<html>
<body>
  <h2>My CD Collection</h2>
  <table border="1">
    <tr>
      <th style="text-align:left">Title</th>
      <th style="text-align:left">Artist</th>
    </tr>
    <xsl:for-each select="catalog/cd">
      <tr>
        <td><xsl:value-of select="title"/></td>
        <td><xsl:value-of select="artist"/></td>
      </tr>
    </xsl:for-each>
  </table>
</body>
</html>
</xsl:template>

</xsl:stylesheet>
```

If you want to learn more about XSLT, please read our [XSLT Tutorial](#).

[< Previous](#)[Next >](#)

W3schools Pathfinder

Track your progress - it's free!

[Sign Up](#)[Log in](#)



 XML

Level up with XML Course

Gain skills, and get certified

[Start Today!](#)



COLOR PICKER



Tutorials ▼

Exercises ▼

Services ▼



Sign Up

Log in

☰ . CSS JAVASCRIPT SQL PYTHON JAVA PHP HOW TO W3.CSS C



ADVERTISEMENT

ADVERTISEMENT

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)

 [HTML](#) [CSS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#)

ADVERTISEMENT

[SPACES](#)[UPGRADE](#)[AD-FREE](#)[NEWSLETTER](#)[GET CERTIFIED](#)[CONTACT US](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)
[jQuery Tutorial](#)

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)

CSS

JAVASCRIPT

SQL

PYTHON

JAVA

PHP

HOW TO

W3.CSS

C

[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)
[Angular Reference](#)
[jQuery Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[Java Examples](#)
[XML Examples](#)
[jQuery Examples](#)

Get Certified

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[Front End Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[PHP Certificate](#)
[jQuery Certificate](#)
[Java Certificate](#)
[C++ Certificate](#)
[C# Certificate](#)
[XML Certificate](#)



[FORUM](#) [ABOUT](#) [CLASSROOM](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning.
Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie and privacy policy](#).

Copyright 1999-2024 by Refsnes Data. All Rights Reserved. W3Schools is Powered by [W3.CSS](#).