# XML and XPath

What is XPath?

XPath is a major element in the XSLT standard.

XPath can be used to navigate through elements and attributes in an XML document.

- XPath is a syntax for defining parts of an XML document
- XPath uses path expressions to navigate in XML documents
- XPath contains a library of standard functions
- XPath is a major element in XSLT and in XQuery
- XPath is a W3C recommendation

XPath Path Expressions

XPath uses path expressions to select nodes or node-sets in an XML document. These path expressions look very much like the expressions you see when you work with a traditional computer file system.

XPath expressions can be used in JavaScript, Java, XML Schema, PHP, Python, C and C++, and lots of other languages.

XPath is a major element in the XSLT standard.

With XPath knowledge you will be able to take great advantage of XSL.

XPath Example

We will use the following XML document:

```xml
<?xml version="1.0" encoding="UTF-8"?>

<bookstore>

<book category="cooking">
  <title lang="en">Everyday Italian</title>
  <author>Giada De Laurentiis</author>
  <year>2005</year>
  <price>30.00</price>
</book>

<book category="children">
  <title lang="en">Harry Potter</title>
  <author>J K. Rowling</author>
  <year>2005</year>
  <price>29.99</price>
</book>

<book category="web">
  <title lang="en">XQuery Kick Start</title>
  <author>James McGovern</author>
  <author>Per Bothner</author>
  <author>Kurt Cagle</author>
  <author>James Linn</author>
  <author>Vaidyanathan Nagarajan</author>
  <year>2003</year>
  <price>49.99</price>
</book>
```

```
  <price>39.95</price>
</book>

</bookstore>
```

In the table below we have listed some XPath expressions and the result of the expressions:

XPath Expression	Result
/bookstore/book[1]	Selects the first book element that is the child of the bookstore element
/bookstore/book[last()]	Selects the last book element that is the child of the bookstore element
/bookstore/book[last()-1]	Selects the last but one book element that is the child of the bookstore element
/bookstore/book[position()<3]	Selects the first two book elements that are children of the bookstore element
//title[@lang]	Selects all the title elements that have an attribute named lang
//title[@lang='en']	Selects all the title elements that have a "lang" attribute with a value of "en"
/bookstore/book[price>35.00]	Selects all the book elements of the bookstore element that have a price element with a value greater than 35.00
/bookstore/book[price>35.00]/title	Selects all the title elements of the book elements of the bookstore element that have a price element with a value greater than 35.00

XPath Tutorial

‹ Previous   Next ›

COLOR PICKER

w³ schools

SPACES   UPGRADE   AD-FREE

NEWSLETTER   GET CERTIFIED   CONTACT US

Top Tutorials

HTML Tutorial
CSS Tutorial
JavaScript Tutorial
How To Tutorial
SQL Tutorial
Python Tutorial
W3.CSS Tutorial
Bootstrap Tutorial
PHP Tutorial
Java Tutorial
C++ Tutorial
jQuery Tutorial

Top References

HTML Reference
CSS Reference
JavaScript Reference
SQL Reference
Python Reference
W3.CSS Reference
Bootstrap Reference
PHP Reference
HTML Colors
Java Reference
Angular Reference
jQuery Reference

Top Examples

HTML Examples
CSS Examples
JavaScript Examples
How To Examples
SQL Examples
Python Examples
W3.CSS Examples
Bootstrap Examples
PHP Examples
Java Examples
XML Examples
jQuery Examples

Get Certified

HTML Certificate
CSS Certificate
JavaScript Certificate
Front End Certificate
SQL Certificate
Python Certificate
PHP Certificate
jQuery Certificate
Java Certificate
C++ Certificate
C# Certificate
XML Certificate

cannot warrant full correctness
of all content. While using W3Schools, you agree to have read and accepted our
terms of use, cookie and privacy policy.