

XML Syntax Rules

[< Previous](#)[Next >](#)

The syntax rules of XML are very simple and logical. The rules are easy to learn, and easy to use.

XML Documents Must Have a Root Element

XML documents must contain one **root** element that is the **parent** of all other elements:

```
<root>
  <child>
    <subchild>.....</subchild>
  </child>
</root>
```

In this example **<note>** is the root element:

```
<?xml version="1.0" encoding="UTF-8"?>
<note>
  <to>Tove</to>
  <from>Jani</from>
  <heading>Reminder</heading>
```

The XML Prolog

This line is called the XML **prolog**:

```
<?xml version="1.0" encoding="UTF-8"?>
```

The XML prolog is optional. If it exists, it must come first in the document.

XML documents can contain international characters, like Norwegian øæå or French êëé.

To avoid errors, you should specify the encoding used, or save your XML files as UTF-8.

UTF-8 is the default character encoding for XML documents.

Character encoding can be studied in our [Character Set Tutorial](#).

UTF-8 is also the default encoding for HTML5, CSS, JavaScript, PHP, and SQL.

ADVERTISEMENT

```
<p>This is a paragraph.</p>
```

```
<br />
```

Note: The XML prolog does not have a closing tag! This is not an error. The prolog is not a part of the XML document.

XML Tags are Case Sensitive

XML tags are case sensitive. The tag `<Letter>` is different from the tag `<letter>`.

Opening and closing tags must be written with the same case:

```
<message>This is correct</message>
```

"Opening and closing tags" are often referred to as "Start and end tags". Use whatever you prefer. It is exactly the same thing.

XML Elements Must be Properly Nested

In HTML, you might see improperly nested elements:

```
<b><i>This text is bold and italic</b></i>
```

In XML, all elements **must** be properly nested within each other:

In the example above, "Properly nested" simply means that since the `<i>` element is opened inside the `` element, it must be closed inside the `` element.

XML Attribute Values Must Always be Quoted

XML elements can have attributes in name/value pairs just like in HTML.

In XML, the attribute values must always be quoted:

```
<note date="12/11/2007">
  <to>Tove</to>
  <from>Jani</from>
</note>
```

Entity References

Some characters have a special meaning in XML.

If you place a character like "<" inside an XML element, it will generate an error because the parser interprets it as the start of a new element.

This will generate an XML error:

```
<message>salary < 1000</message>
```

To avoid this error, replace the "<" character with an **entity reference**:

```
<message>salary &lt; 1000</message>
```

>	>	greater than
&	&	ampersand
'	'	apostrophe
"	"	quotation mark

Only < and & are strictly illegal in XML, but it is a good habit to replace > with > as well.

Comments in XML

The syntax for writing comments in XML is similar to that of HTML:

```
<!-- This is a comment -->
```

Two dashes in the middle of a comment are not allowed:

```
<!-- This is an invalid -- comment -->
```

White-space is Preserved in XML

XML does not truncate multiple white-spaces (HTML truncates multiple white-spaces to one single white-space):

XML:	Hello Tove
HTML:	Hello Tove

Windows applications store a new line as: carriage return and line feed (CR+LF).

Unix and Mac OSX use LF.

Old Mac systems use CR.

XML stores a new line as LF.

Well Formed XML

XML documents that conform to the syntax rules above are said to be "Well Formed" XML documents.

[< Previous](#)[Next >](#)

W3schools Pathfinder

Track your progress - it's free!

[Sign Up](#)[Log in](#)

ADVERTISEMENT

Get Lifelong Access to
**All Current &
Future Courses**

Our certifications are
recognised worldwide.

Original price: \$1,465

Discount price: \$695

Start Today!

COLOR PICKER



Tutorials ▼

Exercises ▼

Services ▼



Sign Up

Log in

☰ . CSS JAVASCRIPT SQL PYTHON JAVA PHP HOW TO W3.CSS C



ADVERTISEMENT



ADVERTISEMENT

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)

 [HTML](#) [CSS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#)

ADVERTISEMENT

[SPACES](#)[UPGRADE](#)[AD-FREE](#)[NEWSLETTER](#)[GET CERTIFIED](#)[CONTACT US](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)
[jQuery Tutorial](#)

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)

CSS

JAVASCRIPT

SQL

PYTHON

JAVA

PHP

HOW TO

W3.CSS

C

[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)
[Angular Reference](#)
[jQuery Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[Java Examples](#)
[XML Examples](#)
[jQuery Examples](#)

Get Certified

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[Front End Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[PHP Certificate](#)
[jQuery Certificate](#)
[Java Certificate](#)
[C++ Certificate](#)
[C# Certificate](#)
[XML Certificate](#)



[FORUM](#) [ABOUT](#) [CLASSROOM](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning.
Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookie and privacy policy](#).

Copyright 1999-2024 by Refsnes Data. All Rights Reserved. W3Schools is Powered by [W3.CSS](#).