

XSD Indicators

[< Previous](#)[Next >](#)

We can control HOW elements are to be used in documents with indicators.

Indicators

There are seven indicators:

Order indicators:

- All
- Choice
- Sequence

Occurrence indicators:

- maxOccurs
- minOccurs

Group indicators:

- Group name
 - attributeGroup name
-

Order Indicators

Order indicators are used to define the order of the elements.

All Indicator

```
<xs:element name="person">
  <xs:complexType>
    <xs:all>
      <xs:element name="firstname" type="xs:string"/>
      <xs:element name="lastname" type="xs:string"/>
    </xs:all>
  </xs:complexType>
</xs:element>
```

Note: When using the <all> indicator you can set the <minOccurs> indicator to 0 or 1 and the <maxOccurs> indicator can only be set to 1 (the <minOccurs> and <maxOccurs> are described later).

Choice Indicator

The <choice> indicator specifies that either one child element or another can occur:

```
<xs:element name="person">
  <xs:complexType>
    <xs:choice>
      <xs:element name="employee" type="employee"/>
      <xs:element name="member" type="member"/>
    </xs:choice>
  </xs:complexType>
</xs:element>
```

Sequence Indicator

The <sequence> indicator specifies that the child elements must appear in a specific order:

```
<xs:element name="person">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="firstname" type="xs:string"/>
```

Occurrence Indicators

Occurrence indicators are used to define how often an element can occur.

Note: For all "Order" and "Group" indicators (any, all, choice, sequence, group name, and group reference) the default value for maxOccurs and minOccurs is 1.

maxOccurs Indicator

The <maxOccurs> indicator specifies the maximum number of times an element can occur:

```
<xs:element name="person">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="full_name" type="xs:string"/>
      <xs:element name="child_name" type="xs:string" maxOccurs="10"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

minOccurs Indicator

The <minOccurs> indicator specifies the minimum number of times an element can occur:

```
<xs:element name="person">
  <xs:complexType>
    <xs:sequence>
      <xs:element name="full_name" type="xs:string"/>
      <xs:element name="child_name" type="xs:string"
        maxOccurs="10" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
</xs:element>
```

The example above indicates that the "child_name" element can occur a minimum of zero times and a maximum of ten times in the "person" element.

Tip: To allow an element to appear an unlimited number of times, use the maxOccurs="unbounded" statement:

A working example:

An XML file called "Myfamily.xml":

```
<?xml version="1.0" encoding="UTF-8"?>

<persons xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:noNamespaceSchemaLocation="family.xsd">

  <person>
    <full_name>Hege Refsnes</full_name>
    <child_name>Cecilie</child_name>
  </person>

  <person>
    <full_name>Tove Refsnes</full_name>
    <child_name>Hege</child_name>
```

```
<person>
  <full_name>Stale Refsnes</full_name>
</person>

</persons>
```

The XML file above contains a root element named "persons". Inside this root element we have defined three "person" elements. Each "person" element must contain a "full_name" element and it can contain up to five "child_name" elements.

Here is the schema file "family.xsd":

```
<?xml version="1.0" encoding="UTF-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema"
  elementFormDefault="qualified">

  <xs:element name="persons">
    <xs:complexType>
      <xs:sequence>
        <xs:element name="person" maxOccurs="unbounded">
          <xs:complexType>
            <xs:sequence>
              <xs:element name="full_name" type="xs:string"/>
              <xs:element name="child_name" type="xs:string"
                minOccurs="0" maxOccurs="5"/>
            </xs:sequence>
          </xs:complexType>
        </xs:element>
      </xs:sequence>
    </xs:complexType>
  </xs:element>

</xs:schema>
```

Group Indicators

Element groups are defined with the group declaration, like this:

```
<xs:group name="groupname">
...
</xs:group>
```

You must define an all, choice, or sequence element inside the group declaration. The following example defines a group named "persongroup", that defines a group of elements that must occur in an exact sequence:

```
<xs:group name="persongroup">
  <xs:sequence>
    <xs:element name="firstname" type="xs:string"/>
    <xs:element name="lastname" type="xs:string"/>
    <xs:element name="birthday" type="xs:date"/>
  </xs:sequence>
</xs:group>
```

After you have defined a group, you can reference it in another definition, like this:

```
<xs:group name="persongroup">
  <xs:sequence>
    <xs:element name="firstname" type="xs:string"/>
    <xs:element name="lastname" type="xs:string"/>
    <xs:element name="birthday" type="xs:date"/>
  </xs:sequence>
</xs:group>

<xs:element name="person" type="personinfo"/>

<xs:complexType name="personinfo">
  <xs:sequence>
    <xs:group ref="persongroup"/>
    <xs:element name="country" type="xs:string"/>
  </xs:sequence>
</xs:complexType>
```

Attribute Groups

Attribute groups are defined with the `attributeGroup` declaration, like this:

```
<xs:attributeGroup name="groupname">
...
</xs:attributeGroup>
```

The following example defines an attribute group named "personattrgroup":

```
<xs:attributeGroup name="personattrgroup">
  <xs:attribute name="firstname" type="xs:string"/>
  <xs:attribute name="lastname" type="xs:string"/>
  <xs:attribute name="birthday" type="xs:date"/>
</xs:attributeGroup>
```

After you have defined an attribute group, you can reference it in another definition, like this:

```
<xs:attributeGroup name="personattrgroup">
  <xs:attribute name="firstname" type="xs:string"/>
  <xs:attribute name="lastname" type="xs:string"/>
  <xs:attribute name="birthday" type="xs:date"/>
</xs:attributeGroup>

<xs:element name="person">
  <xs:complexType>
    <xs:attributeGroup ref="personattrgroup"/>
  </xs:complexType>
</xs:element>
```

[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[CSS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#)

W3schools Pathfinder

Track your progress - it's free!

[Sign Up](#)[Log in](#)

Get your
**knowledge
certified!**

Start Today!



COLOR PICKER



[Tutorials ▼](#)[Exercises ▼](#)[Services ▼](#)[Sign Up](#)[Log in](#)[CSS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [HOW TO](#) [W3.CSS](#) [C](#)[NEWSLETTER](#)[GET CERTIFIED](#)[CONTACT US](#)

Top Tutorials

[HTML Tutorial](#)
[CSS Tutorial](#)
[JavaScript Tutorial](#)
[How To Tutorial](#)
[SQL Tutorial](#)
[Python Tutorial](#)
[W3.CSS Tutorial](#)
[Bootstrap Tutorial](#)
[PHP Tutorial](#)
[Java Tutorial](#)
[C++ Tutorial](#)
[jQuery Tutorial](#)

Top References

[HTML Reference](#)
[CSS Reference](#)
[JavaScript Reference](#)
[SQL Reference](#)
[Python Reference](#)
[W3.CSS Reference](#)
[Bootstrap Reference](#)
[PHP Reference](#)
[HTML Colors](#)
[Java Reference](#)
[Angular Reference](#)
[jQuery Reference](#)

Top Examples

[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[Java Examples](#)
[XML Examples](#)
[jQuery Examples](#)

Get Certified

[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[Front End Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[PHP Certificate](#)
[jQuery Certificate](#)
[Java Certificate](#)
[C++ Certificate](#)
[C# Certificate](#)
[XML Certificate](#)

[FORUM](#) [ABOUT](#) [CLASSROOM](#)



Tutorials ▼

Exercises ▼

Services ▼



Sign Up

Log in

☰ . CSS JAVASCRIPT SQL PYTHON JAVA PHP HOW TO W3.CSS C

Copyright 1999-2024 by Refsnes Data. All Rights Reserved. W3Schools is Powered by W3.CSS.