Tennis

Scoreboard







Points

| Number of Points | Corresponding call |
|------------------|--------------------|
| 0 | 0 - "Love" |
| | 15 - "Fifteen" |
| 2 | 30 - "Thirty" |
| 3 | 40 - "Forty" |



Rules

- A game is won by the first player to have won at least four points in total and at least two points more than the opponent.
- The running score from zero to three points are described as "Love", "Fifteen", "Thirty", and "Forty" respectively.



Rules

- If at least three points have been won by each player, and the scores are equal, the score is "Deuce".
- If at least three points have been scored by each side and a player has one more point than his opponent, the score of the game is "Advantage player!"



Two methods

- wonPoint("player1")
- getScore()



Example match (1)

```
wonPoint("player1")
getScore() -> "Fifteen - Love"
wonPoint("player2")
getScore() -> "Fifteen - Fifteen"
wonPoint("player1")
getScore() -> "Thirty - Fifteen"
wonPoint("player1")
getScore() -> "Forty - Fifteen"
```



Example match (2)

```
wonPoint("player2")
wonPoint("player2")
getScore() -> "Deuce"
```

```
wonPoint("player2")
getScore() -> "Advantage player2"
```

```
wonPoint("player2")
getScore() -> "Win for player2"
```



```
// String
var string = "hello world!";
console.log(string); // hello world!

// Integer
var number = 10;
number += 1;
console.log(number); // 11
console.log("Number: " + number); //Number: 11
```



```
if ("String1" !== "String2") {
    console.log("true");
}

if (0 === "0") {
    // false
} else {
    console.log("true");
}
```



```
var foobar = 4;
if (foobar >= 5) {
    // false
} else if (foobar > 2 && foobar < 4) {
    // false
} else if (foobar > 2 || foobar < 4) {
    console.log("true");
}</pre>
```



```
var array = ["zero", "one", "two", "three", "four"];
console.log(array[1]); // one

// For loop
for (var i = 0; i < array.length; i++) {
    console.log(array[i]);
}</pre>
```



```
function foo() {
    return "foo";
}

var bar = function() {
    return "bar";
};

console log(foo() + bar()); // foobar
```



```
function Foo() {
    this.value = 42;
}

Foo.prototype.getValue = function (){
    return this.value; //remember this keyword
};

var test = new Foo();
console.log(test.getValue()); // 42
```



Code

- /src Source code
- /spec Test folder
- SpecRunner.html Runs tests
- /slides Contains these slides
- /help JavaScript and Jasmine help



Download/Clone

git clone https://gitlab.knowit.no/oma/tenniskata.git

or

https://dl.dropboxusercontent.com/u/45621/ tenniskata.zip

