

Aqua City Filtration Systems

Standard Installation Guide & Technical Specification Sheet

GENERAL SPECIFICATIONS

Working Pressure 30 – 85 PSI

Operating Temperature 40°F – 100°F (4°C – 38°C)

Inlet/Outlet Port Size 1/2" or 3/8" Quick Connect

Filtration Stage Standard Multi-Stage Composite

Recommended Service Interval 6 - 12 Months

PRE-INSTALLATION CHECKLIST

Main Water Supply Cold Water Line Only

Pressure Regulator Required if > 80 PSI

Tools Required Wrench, Teflon Tape, Cutter

Clearance Needed 2 inches below housing

System Flushing 5 mins before first use

STANDARD STEP-BY-STEP INSTALLATION

1. Shut Off Water Supply & Relieve Pressure

Turn off the cold water supply valve under the sink or main supply line. Open the dedicated faucet to drain remaining water and release system pressure.

2. Install Feed Water Adapter & Tubing

Attach the included feed water adapter to the cold water supply line. Connect the PE tubing securely into the quick-connect fitting until it locks.

3. Mount Filter Unit & Connect Lines

Securely mount the filter bracket on the cabinet wall allowing at least 2 inches of clearance at the bottom. Connect INLET to supply line and OUTLET to faucet line.

4. Flush System & Inspect for Leaks

Slowly open the main cold water valve. Allow water to flow through the system for 5–10 minutes to flush carbon fines. Inspect all joints for leaks.

 Important Safety Notice

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Always verify water pressure before completing installation.