



ACL

An instance uses **access control list** (ACL) rules, also called access control rules, to control what data users can access and how they can access it. ACL rules require users to pass a set of requirements in order to gain access to particular data.

Users with the admin role can view Access Control records but cannot create, delete, or update Access Controls. All Access control operations except read require elevated security privileges. Elevated security privileges are also known as the **security_admin** role.



In the Elevate Roles dialog, select **security_admin** then click the OK button.



Access Controls can be created for

1. Records
2. Client callable Script Includes
3. Processors
4. REST Endpoints
5. UI Pages

There are four sections in Access Controls

1. Table/field
2. Requires Role
3. Condition
4. Script

In order for permission to be granted to access a table/field, the Requires Role, Condition, and Script sections must all return true. If there is no value, the section returns true.

Table/Field

Use the Name field in the Access Control configuration to specify which records and which field are secured.

Access Control
incident.u_email_received_date

* Type Application

* Operation Active ☒

Admin overrides ☒ Advanced ☒

* Name

Description

The example rule is a write rule:

Write: [incident] [Email Received Date]

Requires Role

Use the Requires role list to specify the role(s) required to access records. Click the Insert a new row... line to add a role to the list. If there are multiple rows in the list, the user only needs one of the roles for Requires role to return true

Requires role

Role

✖	✎	itil
✚ Insert a new row...		

Condition

Use the Condition field to create the condition(s) required to grant access. In the example, the Requested for value must be the currently logged in user.

Condition

3 records match condition

Add Filter Condition Add "OR" Clause

Requested for is (dynamic) Me

Script

Select the Advanced option to see the Script field

* Type record Application Global

* Operation write Active ☒

Admin overrides ☒ Advanced ☒

* Name Incident [incident] Email Received Date

Description Allow write for u_email_received_date in incident, if the ACL script returns true.

Access Control scripts execute server-side. For best performance, avoid Access Control scripts that use GlideRecord queries as they can adversely impact performance.

Restrict the script logic only to security-related logic. If other logic is included, such as managing date formats or validating record data, it can be difficult to debug problems in the future as you might not think to look in Access Control scripts for those actions

