Question 6 Implementation of the first case in similar to the code developed in question 5, with modified boundary condition as given in the question. case !: u(x,0)=(1-x)"(1+x) the code for his boundary condition implementation is given in the "quiana-qb-case I py" In this implementation  $p = 0t/0x^2 = 1$ , 0 = 0, and x(t) = 1. The result is stored in regular qb-case 1. jeg To reproduce me figure, simply (on the code as it is

To verify this, the code ", gulana - q 4 - advection py" is modified to have case I boundary conditions, all other terms constant. The output figure and code are found in respectively "gulara - 96 - verification. jpeg" "quana-96- verification. Py Comparison of mese graphs show that the same numerical values are obtained for 0=0 in the implicit theta coheme. case 2  $u(x,0) = (-x)^4(1+x)(\frac{2}{5}b_x + \alpha(x)+c)$ The code implementing this boundary condition can be found in: "gulana\_96-case2.py" display O-p parameter plots,

valu	et -	of		b		W	evi	<u>e</u>	P	xe	d	to	
	bχ	-										1959	
and as	To for	ulu llo	el W	o S N	by	(w)	har here	ngir Cod	veright	re ne o. of	Vo inp	uvied ut te nestep	o the s in
N=16.67 by varying N=6	ca	ase se se	2:2:2:2:3	-91	N =	mv = 16.6 mv	- 1 7 ( - 1 2 E	6.67 6.67	+_+ +_+ +_+ 	net o	7-C	avec Saver Distip	9" das peg"



