| Name | Designator | Quantity |
|----------------------------------|--|----------|
| | Resistors | |
| 0805 SMD Resistor 10Ω | R306, R309, R312, R315 | 4 |
| 0805 SMD Resistor 20Ω | R101, R102 | 2 |
| 0805 SMD Resistor 100Ω | R403, R406, R409, R412, R415 | 5 |
| 0805 SMD Resistor 1kΩ | R401, R404, R407, R410, R413, R501, R502, R602 | 8 |
| 0805 SMD Resistor 5.1kΩ | R305, R308, R402, R405, R408 | 8 |
| 0805 SMD Resistor 20kΩ | R001, R305, R308 | 3 |
| 0805 SMD Resistor 47kΩ | R603, R604, R606 | 8 |
| 0805 SMD Resistor 100kΩ | R301, R302, R303, R304, R307, R310, R313, R316 | 8 |
| 3296W-1-103 100kΩ | R605 | 1 |
| | Capacitors | |
| 0805 SMD Capacitor 0.1uF | C404, C405, C001, C003, C005, C007, C009, C101, C102, C201, C203, C204, C206, C207, C209, C210, C212, C301, C302, C401, C402, C403 | 22 |
| 1206 SMD Capacitor 0.47uF | C501, C502, C601, C602, C603 | 5 |
| Tantalum B case 68uF/10V | C004, C008 | 2 |
| Electrolytic capacitor 220uF/35V | C202, C205 ,C208, C211 | 4 |
| Electrolytic capacitor 470uF/25V | C002 | 1 |
| Electrolytic capacitor 330uF/35V | C010 | 1 |
| | Inductors | |
| 1206 SMD Inductor 1uH | L101 | 1 |
| | Diodes | |
| SS56 | D001 | 1 |
| SMBJ3.3CA | D501, D502 | 2 |
| 1206 LED Red | LED1, LED2, LED0 | 3 |
| | Mosfets | |
| IRLML0040TRPbF | Q3, Q4 | 2 |
| IRLR024NTRLPBF | Q2 | 1 |
| IRLS3034PBF | Q1 | 1 |
| | MC | |
| USBLC6-2SC6 | D101 | 1 |

| MC33152DR2G | U8, U9 | 2 |
|---------------------------|---|----|
| LM1117-3.3 | U6 | 1 |
| LM1117-5 | U7 | 1 |
| PC817S | U10, U11, U12, U13, U14, U15 | 6 |
| LM358M/TR | U16 | 1 |
| | Fuses | |
| 1808 fuse 12A | F0 | 1 |
| 1808 fuse 2A | F1 | 1 |
| 3216 resetable fuse 0.25A | F2, F3 | 2 |
| | Connectors | |
| XH-2.54 2pin | 3.3V, 5V, 12V_1, 12V_2, HOTFAN, PRIFAN, PROBE, RPM, TTL, T_HOTBED, T_HOTEND | 11 |
| XH-2.54 3pin | X_LIMIT, Y_LIMIT, Z_LIMIT, E_LIMIT | 4 |
| XH-2.54 4pin | E, X, Y, Z | 4 |
| HRD-2x3-2.54-MALE | J1, J2 ,J3, J4 | 4 |
| HRD-1x3-2.54-MALE | POWERSWITCH1, POWERSWITCH2 | 2 |
| KF301-5.0-2P | HOTEND | 1 |
| KF7.62 4-PIN | P1 | 1 |
| BH-10 | EXP1, EXP2 | 2 |
| USB-B | USB1 | 1 |
| HRD-1x8-2.54-FEMALE | U1, U2, U3, U4 connectors | 8 |
| | Modules | |
| STM32F401CC | U0 | 1 |
| LM2596 | U5 | 1 |
| Stepper Motor Drivers | U1, U2, U3, U4 | 4 |