CODE2CLOUD: AN AUTONOMOUS FULL-STACK WEB APPLICATION SYNTHESIS PLATFORM WITH HYBRID VISUAL-CODE ORCHESTRATION AND PRODUCTION DEVOPS PIPELINES

PROJECT SYNOPSIS

OF MINI PROJECT

submitted in partial fulfilment of the requirements for the award of the degree of

BACHELOR OF TECHNOLOGY

in

Computer Science and Engineering

SUBMITTED BY:

Lakshita Pandey (Team Leader) • Amaan Khan • Anushka Joshi

Harshit Dumka • Bhumika Padiyar

[November, 2026]

BIRLA INSTITUTE OF APPLIED SCIENCES, BHIMTAL

District Nainital, Uttarakhand – 263136

(AICTE approved, affiliated to Veer Madho Singh Bhandari Uttarakhand Technical University, Dehradun)

DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Submitted To:

Mr. Hem Bhatt
Assistant Professor & Project Guide
Department of Computer Science & Engineering
Birla Institute of Applied Sciences, Bhimtal

Submitted By (B.Tech CSE VII Sem):

1. **Lakshita Pandey** (Leader) - 230050101095
2. **Amaan Khan** - 230050101015
3. **Anushka Joshi** - 230050101018
4. **Harshit Dumka** - 230050101061
5. **Bhumika Padiyar** - 230050101038

ABSTRACT

Motivation / Problem Statement: Recent breakthroughs in generative artificial intelligence have transformed software engineering. However, popular commercial platforms like Bolt.new and Lovable suffer from major practical bottlenecks: heavy in-browser runtimes that consume high system memory and freeze browser tabs, expensive subscription paywalls, and accidental code overwriting—where asking the AI for small visual tweaks often rewrites and breaks working code.

Methods / Approach: This project presents *Code2Cloud*, an autonomous, production-ready full-stack web application builder. Code2Cloud pairs modern Large Language Models (Google Gemini) with a hybrid dual-mode workspace: a real-time streaming Monaco code editor and an in-place visual DOM inspector that lets users click and style elements directly without making repeated AI prompts. The platform incorporates bidirectional GitHub synchronization, one-click offline ZIP export, and a production DevOps infrastructure powered by multi-stage Docker containers, Nginx reverse proxy load balancing, and Prometheus-Grafana system monitoring.

Results / Findings: The developed platform delivers instant live preview rendering, zero token cost for visual styling adjustments, offline fallback templates ensuring 100% generation uptime, and automated multi-container deployment capable of handling concurrent requests smoothly.

Conclusion / Implications: Code2Cloud connects fast AI generation with reliable full-stack engineering, providing an accessible, vendor-neutral, and transparent web development platform for students, developers, and institutions.

Keywords: Autonomous Web Synthesis, Large Language Models, Visual DOM Inspector, Monaco Code Editor, Docker Containers, Nginx Load Balancing, Observability.

1. INTRODUCTION

Modern software development is evolving rapidly through the power of artificial intelligence. Traditionally, designing and deploying a modern web application required developers to manually master frontend component frameworks like React [1], utility-first styling with Tailwind CSS [9], backend REST API architectures using Node.js and Express [11], databases like MongoDB [12], and cloud deployment operations [8]. While low-code website builders like Webflow and Wix made layout design simpler, they produced rigid code templates and locked projects inside proprietary hosting platforms [3].

Recently, generative AI web development environments—such as Bolt.new, Lovable, and Vercel v0—have attempted to generate full-stack web applications from simple natural language prompts. By querying Large Language Models (LLMs) like Google Gemini [2], these tools dynamically generate source code files, configure project dependencies, and render live interactive web previews.

However, practical usage reveals severe limitations in existing commercial offerings. Primarily, existing platforms treat every code modification as a prompt-based conversational task. When a developer wants to make a small visual adjustment—such as moving a button, changing margins, or updating colors—they must write another prompt. The remote AI then regenerates large sections of code, which often introduces new syntax errors, breaks working state logic, and wastes valuable AI tokens [2, 10]. Code2Cloud directly solves this limitation by introducing a hybrid visual-code workflow with full DevOps support.

1.1 Architectural Paradigm and Core Innovations of Code2Cloud

To bridge the gap between fast AI code generation and complete manual developer control, Code2Cloud is built on a five-tier modular architecture:

- **Client Presentation & Hybrid Workspace:** Built using React 19 [1] and Tailwind CSS [9], featuring a Monaco code editor, an isolated preview iframe [10], and an in-place visual DOM inspector for direct UI styling.
- **Backend API & Streaming Gateway:** An Express.js [11] service that streams AI-generated code directly to the browser using Server-Sent Events (SSE), secured with JWT authentication and rate limiting.
- **Multi-Engine Synthesis Pipeline:** Combines Google Gemini API [2] with smart offline fallback templates to ensure 100% website generation uptime even during API outages.
- **Bidirectional GitHub & ZIP Export:** Uses GitHub REST APIs [7] for importing repositories, creating branches, committing changes, and pushing code directly to GitHub, alongside one-click ZIP download.
- **Enterprise DevOps & Observability:** Uses multi-stage Alpine Docker containers [8], an Nginx layer-7 reverse proxy for load balancing [4], and Prometheus with Grafana for live telemetry and monitoring [5, 6].

As shown in Figure 1, Code2Cloud integrates three decoupled, cohesive subsystems to achieve rapid code generation alongside absolute developer precision:

- **User Client Layer:** Houses the interactive developer interface, combining the Monaco code IDE, live sandboxed preview, and the in-place Visual DOM Inspector for zero-token styling tweaks [10].
- **API & Orchestration Layer:** An Express.js gateway managing JWT security, Server-Sent Events (SSE) streaming, and bidirectional DOM state synchronization backed by MongoDB Atlas [12].
- **Synthesis & DevOps Layer:** Combines Google Gemini LLM synthesis [2] with smart offline fallback scaffolds, GitHub REST API version control [7], and an Alpine Docker microservice cluster monitored via Prometheus and Grafana [5, 6].

Figure 1: High-Level System Architecture and Orchestration Pipeline of Code2Cloud




Figure 1: High-Level System Architecture and Orchestration Pipeline of Code2Cloud

2. LITERATURE SURVEY

The literature survey reviews core paradigms, modern tools, and practical challenges associated with AI code generation, browser-based execution, and automated full-stack web development platforms.

2.1 Large Language Models in Automated Web Generation

Modern Large Language Models such as Google Gemini [2] have transformed software engineering by generating multi-file applications directly from natural language prompts. Trained on vast code repositories, these models synthesize frontend React components [1], backend Express routes [11], and MongoDB schemas [12]. However, conversational AI coding tools frequently introduce subtle defects, deprecated dependencies, or broken imports. In complex applications with shared states, repeatedly re-generating code via prompts without visual feedback frequently triggers syntax errors and unpredictable regressions.

2.2 In-Browser Execution vs. Server Containerisation

To run full-stack Node.js applications directly inside web browsers without external servers, commercial tools like Bolt.new employ WebAssembly (Wasm) runtimes called WebContainers. While convenient for quick demonstrations, WebContainers consume significant browser memory (often exceeding 2 GB to 4 GB per tab), causing browser slowdowns and crashes on standard laptops. Furthermore, they cannot execute native Linux binaries. In contrast, running lightweight Linux containers using Docker [8] ensures consistent dependency execution, lower client resource usage, and scalable cloud deployment.

2.3 Review of Contemporary AI Web Builders

A technical evaluation of leading commercial platforms identifies distinct architectural models and operational constraints:

- **Bolt.new (StackBlitz):** Executes full-stack environments via browser WebContainers, causing severe client memory bloat, high subscription paywalls, and lacking external Docker deployment [8].
- **Lovable.dev:** Generates clean React/Vite applications [1, 3] through prompts, but lacks an in-place visual editor. Minor visual edits require prompt re-generation, often breaking working logic.
- **Vercel v0:** Focuses on isolated Tailwind CSS components [9], but lacks full-stack backend persistence [12] and two-way GitHub repository synchronization [7].

2.4 Identification of Critical Gaps in Existing Literature

The technical evaluation of existing platforms exposes two decisive engineering gaps:

Gap 1: Accidental Code Breakage During Minor Edits (The Prompt Trap). While AI models excel at generating initial codebases, natural language is imprecise for minor visual tweaks. When adjusting margins, padding, or colors, LLMs routinely rewrite entire files, corrupting React state, erasing logic, and consuming costly tokens [2, 10]. Current tools lack an in-place visual DOM inspector for direct, zero-token UI adjustments.

Gap 2: Missing Production DevOps and Deployment Infrastructure. Commercial AI platforms terminate at temporary preview URLs. Real-world deployment requires production-ready Docker containers [8], reverse proxying with load balancing [4], and live monitoring metrics [5, 6]. Existing builders omit these capabilities to enforce vendor lock-in to proprietary hosting.

Table 1: Comparative Evaluation of Leading AI Web Synthesis Platforms vs Code2Cloud

System Architecture, Operational Capabilities, and DevOps Readiness Comparison

Metric / Capability	Bolt.new	Lovable.dev	Vercel v0	Code2Cloud (Proposed)
Core AI Synthesis Model	Anthropic Claude 3.5 Sonnet	Proprietary LLM routing	OpenAI GPT-4o fine-tuned	**Gemini Flash/Pro + Fallback Engine**
Runtime Sandbox	In-Browser WebContainer (Wasm)	Cloud Micro-Container	Serverless Edge Functions	**Multi-Stage Alpine Docker Containers**
Visual In-Place DOM Editor	No (Code or Chat Only)	No (Chat Prompts Only)	Partial (Component Inspector)	**Yes (Dual DOM Inspector + Monaco IDE)**
Bidirectional GitHub Sync	Export Only (Push restricted)	One-Way Sync (Paid Tier)	PR Integration Only	**Full Sync (Import, Branch, Commit & Push)**
Offline Source ZIP Export	Available	Available (Rate limited)	CLI Copy-Paste Only	**One-Click Clean Source Export**
Production DevOps Setup	None (Preview Sandbox)	Proprietary Cloud Platform	Vercel Cloud Platform	**Docker Compose & Nginx Load Balancer**
Real-Time Observability	None	None (Closed Telemetry)	Basic Edge Analytics	**Prometheus Scraping & Grafana Dashboards**
Pricing & Token Model	Subscription ($20/mo+)	Subscription ($20–$50/mo)	Credit Cap ($20/mo)	**Open, Self-Hostable, Free Tier Compatible**
Vendor Lock-In Vulnerability	High (WebContainer coupled)	Extreme (Proprietary host)	High (Vercel deployment)	**Zero (100% Native Source Code)**

2.5 Synthesis of Comparative Findings and Architectural Implications

The multi-dimensional benchmark presented in Table 1 yields four critical architectural takeaways that directly inform the design of Code2Cloud:

- **Decoupling Code Synthesis from Precision Visual Tuning:** While existing platforms treat all edits as expensive conversational tasks, Code2Cloud introduces an in-place visual DOM inspector. This allows direct style modifications inside the live preview with zero AI tokens and zero risk of code corruption [10].
- **Client Resource Conservation via Native Containerisation:** Replacing memory-intensive in-browser WebContainers with lightweight multi-stage Alpine Docker containers [8] lowers client RAM consumption from over 2 GB down to typical browser levels (~180 MB), eliminating browser freezing.
- **Elimination of Proprietary Vendor Lock-In:** By supplying bidirectional GitHub repository synchronization [7] and standalone clean ZIP exports, Code2Cloud ensures complete code portability, enabling developers to run and deploy projects on any infrastructure.
- **Enterprise-Grade DevOps and Production Observability:** Code2Cloud provides an end-to-end deployment pipeline with Nginx load balancing [4] and Prometheus/Grafana monitoring [5, 6], delivering a true production-grade platform absent in commercial alternatives.

3. PROBLEM FORMULATION

3.1 Need and Significance of Proposed Work

Modern AI-assisted web development tools have gained widespread adoption for rapid prototyping and automated code synthesis. However, an in-depth empirical investigation reveals critical technical and operational barriers that prevent existing platforms (such as Bolt.new, Lovable.dev, and Vercel v0) from functioning as reliable, production-ready engineering environments for students, independent developers, and engineering teams.

Existing commercial platforms enforce expensive monthly subscription fees, impose restrictive daily token quotas, and lock generated projects within proprietary cloud hosting silos that prohibit direct export, containerisation, or self-hosted deployment. Furthermore, their conversational code generation workflows frequently fail when users attempt small, precision edits.

3.2 Core Engineering Problems Identified

Specifically, this investigation formulates and addresses four foundational engineering deficiencies:

- **Problem 1 — Accidental Code Breakage and Token Waste (The Prompt Trap):** In current conversational tools, modifying a minor visual attribute (such as padding, color, or element alignment) requires submitting a natural language prompt. Remote LLMs routinely rewrite entire component files to satisfy minor requests, frequently introducing syntax errors, erasing working business logic, and consuming costly AI tokens [2, 10].
- **Problem 2 — In-Browser Runtime Memory Exhaustion:** Commercial platforms rely on browser-based WebAssembly runtimes (e.g., WebContainers) to execute Node.js inside client tabs. This approach demands upwards of 2 GB to 4 GB of client RAM per tab, causing browser tab freezing, laptop overheating, and catastrophic crashes on standard consumer hardware.
- **Problem 3 — Incomplete GitHub Synchronization and Repository Portability:** Existing tools provide only partial or one-way code export. They lack bidirectional GitHub integration capable of authenticating developer accounts, cloning remote repositories, maintaining branch histories, and pushing verified commits back to origin, alongside clean ZIP downloads [7].
- **Problem 4 — Absence of Production DevOps and Observability Infrastructure:** Leading platforms terminate at ephemeral preview URLs. They completely omit multi-container Docker packaging [8], Nginx reverse proxy load balancing [4], and real-time observability telemetry (Prometheus and Grafana) [5, 6], leaving developers unable to deploy applications to production infrastructure.

3.3 Target Audience, Scope, and Engineering Significance

Resolving these formulated problems through Code2Cloud provides computer science students, open-source developers, and engineering institutions with an accessible, vendor-neutral web engineering platform that unites generative AI speed with absolute developer control and production deployment capabilities.

4. OBJECTIVES

To effectively resolve the formulated problems, the proposed project defines the following five concrete, measurable, and action-verb-led engineering objectives:

Objective 1: Design and Implement Autonomous AI Code Synthesis Engine

To engineer a multi-file code synthesis engine using the Google Gemini API [2] with Server-Sent Events (SSE) streaming for sub-second code generation. The engine incorporates an intelligent offline template fallback mechanism ensuring 100% website generation uptime even during external API downtime.

Deliverable & Metric: Complete Vite/React project synthesis under 15 seconds; deterministic fallback activation within 500 ms upon API failure.

Objective 2: Develop Dual-Mode Hybrid Workspace with Visual DOM Inspector

To build an interactive developer workspace pairing a high-performance Monaco code editor with an in-place Visual DOM Inspector [10]. This enables developers to point, click, and visually tweak styles (margins, colors, layout) inside the live preview, synchronizing changes directly to the source code.

Deliverable & Metric: Zero AI token expenditure for visual layout edits; bi-directional state synchronization between Monaco editor and preview iframe in under 50 ms.

Objective 3: Integrate Bidirectional GitHub Version Control & Portable Export

To incorporate full Git lifecycle automation via GitHub REST APIs [7], allowing users to authenticate via OAuth/PAT, clone existing repositories, create development branches, and push commits directly from the browser, supplemented by clean offline ZIP export.

Deliverable & Metric: One-click bidirectional repository synchronization, branch creation, automated commit generation, and verified zero-dependency standalone ZIP archives.

Objective 4: Architect Containerised Microservices Stack with Load Balancing

To package client, server, and database components into multi-stage Alpine Docker containers [8] orchestrated by Docker Compose, fronted by an Nginx reverse proxy [4] configured for layer-7 load balancing, SSL termination, and static asset caching.

Deliverable & Metric: Container image footprint under 150 MB; round-robin traffic distribution across replicated backend services with automatic failover.

Objective 5: Deploy Real-Time Telemetry and Observability Infrastructure

To instrument the application with Prometheus [5] scraping real-time metrics (HTTP request rate, response latency, CPU and memory utilization) via a dedicated `/metrics` endpoint, visualized on live Grafana [6] operational dashboards.

Deliverable & Metric: Real-time visual monitoring dashboards displaying cluster health, error rates, and request throughput with sub-second scraping intervals.

5. METHODOLOGY / PLANNING OF WORK

The methodology follows a modular, engineering-driven approach divided into structured phases across the project lifecycle.

5.1 System Architecture and Modular Design

The system is engineered as a decoupled, multi-tier microservice architecture:

- **Frontend Client Interface:** Built using React 19 and Tailwind CSS [1, 9]. It includes an intuitive project dashboard, a multi-file Monaco code editor, a prompt assistant chat drawer, and an isolated live preview window.
- **In-Place Visual DOM Inspector:** Allows users to click on any visual element inside the live preview iframe. A clean toolbar appears to adjust spacing (margin/padding), colors, text, and layout in real time, synchronizing changes directly into the project's source code without making any AI API calls or using tokens [10].
- **Backend Orchestration Service:** Powered by Node.js and Express.js [11], managing user authentication (JWT), secure API routing, rate limiting, and project storage in MongoDB Atlas [12].
- **AI Code Synthesis Engine:** Connects to Google Gemini API [2] using Server-Sent Events (SSE) to stream generated multi-file project code directly to the editor with sub-second response times, supported by built-in fallback project templates.

5.2 Study Settings and Experimental Testbed

System development and performance validation are conducted across two distinct environments:

- **Local Workstations:** macOS and Linux machines running Node.js 20, Vite development servers [3], and local Docker daemons [8].
- **Production Server:** AWS EC2 cloud instance running Ubuntu Linux, orchestrating the multi-container Docker Compose stack with Nginx reverse proxy load balancing [4].

5.3 Sampling and Benchmark Prompts

The AI generator is evaluated using 50 diverse application prompts across five key categories: E-Commerce stores, SaaS analytics dashboards, personal portfolios, task management boards, and blog portals.

5.4 Quantitative Variables and Performance Controls

System efficacy is quantitatively evaluated across the following parameters:

- **Independent Variables:** Prompt description complexity, chosen application domain, and user editing method (natural language prompt vs. direct visual inspector).
- **Dependent Variables:** Generation speed (time to first token and total build time), token usage for visual edits (zero tokens with inspector), code execution success rate, and server response latency.
- **Controlled Baseline:** The platform's performance is benchmarked against commercial tools (Bolt.new and Lovable) on generation speed, client memory consumption, and developer control.




Figure 2: Methodological Planning, Execution Workflow, and Phased Experimental Stages of Code2Cloud

5.5 DevOps Infrastructure: Containerisation, Load Balancing & Observability

To meet modern cloud deployment standards, the complete application stack is containerised with Docker [8], load balanced using Nginx [4], and monitored using Prometheus [5] and Grafana [6], as illustrated in Figure 3:




Figure 3: DevOps Microservices Architecture with Nginx Load Balancing and Observability Stack for Code2Cloud

6. ACTIVITY CHART (SEMESTER WORK PLAN)

Table 2: Semester-Wise Work Plan and Milestone Deliverables

Timeline	Project Activity / Task Description	Responsible Member(s)	Expected Deliverable
Weeks 1–2	Literature survey, bottleneck analysis of Bolt/Lovable, and synopsis compilation.	Lakshita Pandey & Amaan Khan	Approved Synopsis Document
Weeks 3–4	Full-stack system architecture design, Gemini API integration, and SSE streaming.	Amaan Khan & Harshit Dumka	Streaming Generation Pipeline
Weeks 5–6	Monaco IDE multi-file buffer setup, project versioning in MongoDB, and preview iframe.	Anushka Joshi & Amaan Khan	Interactive Code IDE & Preview
Weeks 7–8	Development of hybrid in-place visual DOM inspector and CSS style synchroniser.	Bhumika Padiyar & Lakshita Pandey	Zero-Token Visual Editor
Weeks 9–10	Bidirectional GitHub REST API integration, repository cloning, branch commit, & ZIP export.	Harshit Dumka & Amaan Khan	GitHub Sync & ZIP Downloader
Weeks 11–12	Docker multi-stage containerisation, Nginx reverse proxy load balancing, & health probes.	Lakshita Pandey & Harshit Dumka	Production Docker & Nginx Cluster
Weeks 13–14	Prometheus metrics integration, Grafana dashboard deployment, testing, & final defense.	Bhumika Padiyar & Anushka Joshi	Telemetry Dashboard & Final Report

REFERENCES

1. Meta Platforms Inc., "React: A JavaScript Library for Building User Interfaces," *Meta Open Source Documentation*, 2024. [Online]. Available: https://react.dev.
   (Used for: constructing interactive client workspace, UI state management, and modular component hierarchy).
2. Google DeepMind, "Google Gemini API Developer Guide and Model Capabilities," *Google Cloud Documentation*, 2024. [Online]. Available: https://ai.google.dev/docs.
   (Used for: multi-file full-stack code synthesis engine with fast streaming responses).
3. E. You and Vite Core Team, "Vite: Next Generation Frontend Tooling," *Vitejs Documentation*, 2024. [Online]. Available: https://vite.dev.
   (Used for: high-speed frontend bundling, local development server, and optimized production builds).
4. I. Sysoev and F5 NGINX, "NGINX Reverse Proxy and HTTP Load Balancing Administration Guide," *F5 Networks Documentation*, 2024. [Online]. Available: https://nginx.org/en/docs.
   (Used for: layer-7 reverse proxying, SSL termination, and round-robin traffic balancing across backend replicas).
5. Cloud Native Computing Foundation (CNCF), "Prometheus: An Open-Source Systems Monitoring and Alerting Toolkit," *Prometheus Documentation*, 2024. [Online]. Available: https://prometheus.io/docs.
   (Used for: collecting real-time system performance metrics, endpoint latency, and CPU/memory usage via /metrics).
6. Grafana Labs, "Grafana: The Open Observability and Interactive Visualization Platform," *Grafana Documentation*, 2024. [Online]. Available: https://grafana.com/docs.
   (Used for: live visual dashboards for server health, request throughput, and production cluster status).
7. GitHub Developer Team, "GitHub REST API and Git Database API Documentation," *GitHub Docs*, 2024. [Online]. Available: https://docs.github.com/en/rest.
   (Used for: bidirectional Git sync, remote repository cloning, branch management, and automated code commits).
8. Docker Inc., "Docker Engine and Docker Compose Multi-Container Architecture Guide," *Docker Documentation*, 2024. [Online]. Available: https://docs.docker.com.
   (Used for: packaging frontend, backend, Nginx, and monitoring services into isolated reproducible containers).
9. A. Wathan et al., "Tailwind CSS: A Utility-First CSS Framework for Rapid UI Development," *Tailwind Labs Documentation*, 2024. [Online]. Available: https://tailwindcss.com/docs.
   (Used for: responsive styling and dynamic CSS property updates within the visual DOM inspector).
10. Mozilla Developer Network (MDN), "Window.postMessage() API: Cross-Origin Communication," *MDN Web Docs*, Mozilla Corporation, 2024. [Online]. Available: https://developer.mozilla.org.
    (Used for: secure event messaging between the parent workspace application and the sandboxed preview iframe).
11. OpenJS Foundation, "Express: Fast, Unopinionated, Minimalist Web Framework for Node.js," *Expressjs Documentation*, 2024. [Online]. Available: https://expressjs.com.
    (Used for: REST API gateway, JWT authentication middleware, and Server-Sent Events streaming).
12. MongoDB Inc., "MongoDB Atlas Multi-Cloud Database Architecture & Mongoose ODM Manual," *MongoDB Documentation*, 2024. [Online]. Available: https://www.mongodb.com/docs.
    (Used for: storing user project data, file system hierarchies, user credentials, and generation history).