

HTML ~> hyper text Markup language

↳ describes the structure of a web page.

↳ Tell HTML tell the browser how to display the content.

<!DOCTYPE html> ~> declaration defines that this document is an HTML5 doc

<html> ~> element is the root element of an HTML page.

<head> ~> element contain meta information about the HTML page

<title> Page Title </title> ~> element specifies a title for the HTML page

</head>

<body> ~> element defines the document's body, and is a container for all the visible contents, such as heading, paragraph, images etc

<h1> My first heading </h1>

<p> My first paragraph. </p>

</body>

</html>

Some html elements don't have an ending tag hence called empty elements. Empty elements don't have an end tag.

HTML links

 This is a link

HTML Images.

↳ alternate if img isn't available.

↳ src can take two types of URL

↳ size

↳ Absolute URL (usually externally hosted)

↳ Relative URL (usually self hosted)

`<b style="color:red;"> This is a red paragraph </b>`

↳ used for inline CSS

The lang Attribute

`<!DOCTYPE html>`

`<html lang="en">`

`<body>`

....

`</body>`

`</html>`

HTML Headings.

↳ html heading are defined with the `<h1>` to `<h6>` tags.

↳ `<h1>` defines the most important heading. `<h6>` defined the least important heading.

↳ These are important as search engines use the heading to index the structure and content of your web pages.

HTML Paragraphs

Week → 1 (JavaScript)

compiled language

Interpreted language

usually go line by line.

1) first need to compile, then need to run.

2) Usually don't compile if there is an error in the code.

ex → java, c++

Can run partially if the error occurs later.

ex - js, python

Arrays

```
const personArray = ["harkirat", "raman", "priya"]
```

```
const genderArray = ["male", "male", "female"];
```

```
const numberOfUsers = personArray.length;
```

```
for (let i = 0; i < numberOfUsers; i++) {
```

```
  if (genderArray[i] === "male") {
```

```
    console.log(personArray[i]);
```

```
  }
```

```
}
```

JavaScript Objects →

```
const user1 = {
```

```
  firstName: "harkirat",
```

```
  gender: "male"
```


`user["firstName"]` ~ accessing Object Elements.

functions ↴ remember to use these quotation while accessing something.

```
function sum(a, b) {  
    const sumValue = a + b;  
    return sumValue;  
}
```

```
const value = sum(1, 2);  
console.log(value);
```

JavaScript Callbacks → Function as an Argument

```
function sum(num1, num2, fnToCall) {  
    let result = num1 + num2;  
    fnToCall(result);  
}
```

```
function displayResult(data) {  
    console.log("Result of the sum is: " + data);  
}
```

```
function displayResultPassive(data) {  
    console.log("Sum's result is: " + data);  
}
```


// you are only allowed to call one function after this
// how will you displayResult of a sum.

```
const ans = sum(1, 2, displayResult);
```

Another Type.

```
function calculateArithmetic(a, b, arithmeticFinalFunction) {
```

```
    const ans = arithmeticFinalFunction(a, b);
```

```
    console.log(ans);
```

```
}
```

```
function sum(a, b) {
```

```
    return a + b;
```

```
}
```

```
const value = calculateArithmetic(1, 2, sum);
```

```
console.log(value);
```

↳ will be discussed later in detail.

different / Various ways of creating function in javascript.

1) function greet(name) {

```
    return "Hello, " + name;
```

```
}
```

↳ hoisted

↳ is a JS default behavior of moving

declaration to the top of their scope (before code execution). Remember
declaration are hoisted not initialization.

2) Function Expression (Anonymous or Named)

```
const greet = function(name) {  
    return "Hi , " + name;  
};
```

↳ not hoisted & since const is there so ; is preferred.

3) Arrow Function (ES6+)

```
const greet = (name) => {  
    return "Hey , " + name;  
};
```

// or if single return

```
const greet = name => "Yo , " + name;
```

4. Immediately Involved Function Expression (IIFE)

```
(function(name) {  
    console.log("Welcome , " + name);  
})("Eve"); → // Welcome , Eve
```

Common JavaScript Web APIs

```
setTimeout(() => {  
    console.log("Runs after 2 seconds");  
}, 2000);
```

```
const intervalId = setInterval(() => {  
    console.log("Runs every 3 seconds");  
}, 3000);
```


// To stop the interval after 10 seconds.

```
setTimeout(() => clearInterval(intervalId), 10000);
```

// Networking API

```
fetch("https://jsonplaceholder.typicode.com/posts/1")
```

- then(response => response.json())

- then(data => console.log("fetched data:", data));

JavaScript Callback ~

(function as an argument) ~ usually in javascript
an argument can be a string, boolean, integer or a
function

```
function square(a) {  
  return a * a;  
}
```

```
function sumOfSomething(a, b, fn) {  
  const val1 = fn(a);  
  const val2 = fn(b);  
  return val1 + val2;  
}
```

```
sumOfSomething(a, b, square)
```


Async Nature of Javascript

↳ Task Delegation to other threads

setTimeout, fs.readFile, etc

Promises

↳ with we can create an async function, basically a wrapper on top of JS provided async function.

Example → Un Promised Code

```
const fs = require('fs');
```

```
function myAsyncFunc(callback) {
```

```
  fs.readFile("a.txt", "utf-8", function(err, data) {
```

```
    callback(data);
```

```
  });
```

```
}
```

```
// callback function to call
```

```
function onData(data) {
```

```
  console.log(data);
```

```
}
```

```
myAsyncFunc(onData);
```

Self made Async func

Same Promised Code

```
const fs = require('fs');  
  
// my own synchronous function  
function myAsyncFunc() {  
  return new Promise(function(resolve) {  
    fs.readFile("a.txt", "utf-8", function(err, data) {  
      resolve(data);  
    });  
  });  
}  
  
// callback function to call  
function onDone(data) {  
  console.log(data);  
}  
  
myAsyncFunc().then(onDone);
```

Async / Await Syntax

↳ just better syntax still uses promises
and callbacks under the hood and usually used at the
callers side


```
function myAsyncFunction( ) {  
  return new Promise( Function( callback) {  
    // do some async logic here  
    callback( "hi there" );  
  } );  
}
```

```
async function main( ) {  
  const value = await myAsyncFunction( );  
  console.log( value );  
}  
main( );
```

await only works with async function wrapper.