

Roadmap | Docs | HERY

Features that are planned but not yet implemented.

Server / Client Mode

When running the server the [SQLite](#) database would be loaded in memory for faster access to cached entities for querying. The server would be accessible via `/tmp/hery.sock` UNIX socket file.

```
hery server start --collection=amadla
hery server stop --collection=amadla
hery client --collection=amadla
```

Compose Lock File

Compose would put entities together and merge them into a `collection.lock` JSON file that is then added to the cache [SQLite](#) database for quick querying. Since the lock file is JSON, it would be possible to extract data from entities without using the caching system (but slower).

Rich Query Functions

The following query functions are planned:

Function	Description
<code>equal(<property>, <value>)</code>	Exact match filter
<code>like(<property>, <pattern>)</code>	Pattern matching with wildcards (<code>%</code> and <code>_</code>)
<code>in(<property>, <values>...)</code>	Filter where value matches any in a list
<code>not_equal(<property>, <value>)</code>	Inverse exact match
<code>not_like(<property>, <pattern>)</code>	Inverse pattern matching
<code>not_in(<property>, <values>...)</code>	Inverse list match
<code>and(<functions>...)</code>	Combine filters with AND logic
<code>or(<functions>...)</code>	Combine filters with OR logic
<code>limit(<number>)</code>	Maximum number of rows to return
<code>offset(<number>)</code>	Number of rows to skip

Function	Description
<code>order_by(<property> [, ASC DESC])</code>	Order output by a property
<code>group_by(<property> [, ...])</code>	Group by one or more properties

Additional Validation Subcommands

The following validation subcommands are planned:

- `hery entity validate-uri <URI>` - Verify that a URI is well formatted and the version exists
- `hery entity validate-version <version>` - Verify version format
- `hery entity validate-hash <URI>` - Verify repository/entity download integrity
- `hery entity have <URI>` - Verify if the entity exists on the local machine