

AfriShield Admin Command Center

Backend API Reference — for the web dashboard integration

Base URL (local dev): `http://localhost:8000` — interactive docs also live at `/docs`.

Authentication: every endpoint labeled "AUTH REQUIRED" below needs header `Authorization: Bearer <token>`, where the token comes from `/api/admin/signup` or `/api/admin/login`. Tokens expire after 24 hours — log in again to get a new one. A missing/invalid/expired token returns 401.

Content type: all request/response bodies are JSON unless noted otherwise.

Kept unchanged: the existing citizen-facing GET/POST `/api/hazard-reports` and photo endpoints are not modified — shown here for completeness only.

1. Admin Authentication

POST

`/api/admin/signup`

PUBLIC — no auth required

Creates a new admin account and logs them in immediately.

REQUEST BODY

```
{
  "name": "Habiba",
  "email": "habiba@afrishield-command.com",
  "password": "supersecret1"
}
```

RESPONSE

```
{
  "token": "eyJhbGciOi...",
  "admin": {
    "id": "a83f691ee8...",
    "name": "Habiba",
    "email": "habiba@afrishield-command.com",
    "created_at": "2026-09-07T07:08:36Z"
  }
}
```

- 201 Created.
- password must be ≥ 8 chars (422 otherwise).
- 409 if the email is already registered.

POST

`/api/admin/login`

PUBLIC — no auth required

Logs in an existing admin.

REQUEST BODY

```
{
  "email": "habiba@afrishield-command.com",
  "password": "supersecret1"
}
```

RESPONSE

Same shape as `signup`'s response.

- 200 OK.
- 401 on wrong email OR password (same error either way, on purpose).

GET /api/admin/me

AUTH REQUIRED (Bearer token)

Returns the profile of whoever the bearer token belongs to — use to verify a stored token is still valid.

RESPONSE

```
{
  "id": "a83f691ee8...",
  "name": "Habiba",
  "email": "habiba@afrishield-command.com",
  "created_at": "2026-09-07T07:08:36Z"
}
```

2. Reports / Incidents

GET /api/hazard-reports

PUBLIC — no auth required

All hazard reports, oldest first. (Existing endpoint, kept as-is; now also carries the incident-management fields below.)

RESPONSE

```
[
  {
    "id": "693c9204...", "category": "Trapped - Flooded Home",
    "location_name": "Lagos, Nigeria", "needs_assistance": true,
    "latitude": 6.5244, "longitude": 3.3792,
    "status": "assigned", "verified": true, "assigned_to": "Team 2",
    "responses": [ ... ], "status_history": [ ... ], ...
  }
]
```

GET /api/hazard-reports/{report_id}

PUBLIC — no auth required

One report, full detail (same fields as above). New endpoint, unauthenticated like its sibling.

- 404 if report_id doesn't exist.

3. Dashboard Statistics

GET /api/admin/dashboard/stats

AUTH REQUIRED (Bearer token)

Aggregate counts for the dashboard's summary tiles. Computed live on every call.

RESPONSE

```
{
  "total_reports": 2,
  "critical_or_high_priority": 1,
  "assistance_needed": 1,
  "resolved": 1,
  "by_status": { "resolved": 1, "new": 1 }
}
```

4. AI Priority / Triage

GET `/api/admin/incidents/prioritized`

AUTH REQUIRED (Bearer token)

Every report ranked by `priority_score` (highest first), each with an explainable factor breakdown. Query param `?include_resolved=true` to include resolved ones (excluded by default).

RESPONSE

```
[
  {
    "id": "693c9204...", "location_name": "Lagos, Nigeria",
    "priority_score": 0.85, "priority_level": "critical",
    "severity": "high",
    "factors": {
      "needs_assistance": "Reporter explicitly requested help (+0.40)",
      "region_risk_level": "Region flood risk: high (+0.30)",
      "category": "Category 'Trapped - Flooded Home' (+0.15)",
      "evidence": "No photo attached (+0.00)",
      "report_age": "0.0h since submission (+0.00)"
    },
    ...
  }
]
```

- Score 0.0–1.0, weighted sum of 5 factors (weights sum to 1.0): `needs_assistance` (0.40), `region_risk_level` (0.30), category keyword match (0.15), photo evidence (0.05), report age capped at 24h (0.10).
- `priority_level` buckets: critical ≥ 0.70 , high ≥ 0.45 , medium ≥ 0.20 , else low.
- severity = the report's region's current flood risk ("unknown" if location doesn't match a monitored region).

5. Incident Management

PATCH `/api/admin/incidents/{report_id}/status`

AUTH REQUIRED (Bearer token)

Moves a report through: New → Verifying → Prioritized → Assigned → Responding → Resolved.

REQUEST BODY

```
{ "status": "resolved" }
```

RESPONSE

Full updated report, with a new `status_history` entry (`status`, `changed_at`, `changed_by`).

- status must be one of the 6 values (422 otherwise). Backward moves are allowed. 404 if not found.

POST**/api/admin/incidents/{report_id}/verify****AUTH REQUIRED (Bearer token)**

Flags a report's evidence as verified or rejected — a human judgment call.

REQUEST BODY

```
{ "verified": true, "notes": "Photo matches location, credible" }
```

RESPONSE

```
Full updated report with verified / verified_by / verified_at / verification_notes set.
```

- If status was still "new", this also advances it to "verifying".

6. Assistance & Response

GET**/api/admin/assistance-requests****AUTH REQUIRED (Bearer token)**

Reports with needs_assistance: true, ranked by priority (same breakdown as section 4).

POST**/api/admin/assistance-requests/{report_id}/assign****AUTH REQUIRED (Bearer token)**

Assigns a responder/team to a report and sets status to "assigned".

REQUEST BODY

```
{  
  "assigned_to": "Lagos Rescue Team 2",  
  "team": "Water Rescue",  
  "notes": "closest unit"  
}
```

RESPONSE

```
Full updated report with assigned_to / assigned_by set.
```

- team and notes are optional.

POST**/api/admin/incidents/{report_id}/response****AUTH REQUIRED (Bearer token)**

Sends a response about this incident and logs it to the report's history.

REQUEST BODY

```
{
  "channel": "sms",
  "message": "Help is on the way, stay where you are",
  "recipients": ["+2348012345678"]
}
```

RESPONSE

```
{
  "id": "a2a6db2f...", "channel": "sms",
  "message": "Help is on the way, stay where you are",
  "recipients": ["+2348012345678"],
  "status": "simulated",
  "sent_at": "2026-09-07T07:09:01Z",
  "sent_by": "habiba@afrishield-command.com"
}
```

- channel: sms | voice | radio | community_leader.
- sms/voice: real send via Africa's Talking if configured + recipients given, else "simulated".
- radio/community_leader: NO real integration exists — always "simulated", logged honestly.
- Advances status to "responding" if the report was earlier in the workflow. 201 Created.

GET**/api/admin/incidents/{report_id}/responses****AUTH REQUIRED (Bearer token)**

Full response history for one report, oldest first.

7. Incident Map

GET**/api/admin/incidents/map****AUTH REQUIRED (Bearer token)**

Map-ready incident pins — only reports with a real GPS fix (lat AND lon set); others are skipped.

RESPONSE

```
[
  {
    "id": "693c9204...", "location_name": "Lagos, Nigeria",
    "latitude": 6.5244, "longitude": 3.3792,
    "severity": "high", "priority_score": 0.85, "priority_level": "critical",
    "status": "resolved", "needs_assistance": true,
    "category": "Trapped - Flooded Home"
  }
]
```

Full field-by-field detail: docs/api-contract.md — "Admin Command Center API" section. Verified end-to-end against a running server (signup→login→report→verify→assign→respond→resolve→map→stats).