Your Project Title

An industrial training project report submitted

to

MANIPAL UNIVERSITY

For Partial Fulfillment of the Requirement for the Award of the Degree

of

Bachelor of Technology

in

Information Technology

by

Your Name

Reg. No. 160953xyz

Under the guidance of

Name of Guide/Supervisor

Designation of Guide

Name of Company/Organization



Month Year

CERTIFICATE

This is to certify that Mr./Ms XYZ (Reg.No. 140953xyz), a student of x year B.Tech (Computer and Communications) from Manipal Institute of Technology has completed his/her internship with us from DD-MM-YY to DD-MM-YY.

During this tenure he/she has worked on project titled "Title of your project" and has successfully completed it to the best of his/her abilities. His/her conduct and attendance has been good during this tenure.

ACKNOWLEDGEMENTS

My sincere thanks to XYZ.

ABSTRACT

My abstract. My abstract. My abstract. My abstract. My abstract. My abstract. stract. My abstract. My abstract.My abstract.My abstract.My abstract.My abstract.My abstract. My abstract.My abstract.My abstract.My abstract.My abstract.My abstract. My abstract.My abstract.My abstract.My abstract.My abstract.My abstract. My abstract.My abstract.My abstract.My abstract.My abstract.My abstract. My abstract.My abstract.My abstract.My abstract.My abstract.My abstract. My abstract.

[Security and Privacy]: Cryptographykey management, symmetric cryptography; Security Services authentication, access control

Contents

\mathbf{A}	cknowledgements	ii
\mathbf{A}	bstract	iii
Li	ist of Tables	vi
Li	st of Figures	vii
\mathbf{A}	bbreviations	vii
N	otations	ix
1	Chapter Title	1
	1.1 Section 1	1
2	Chapter Title	3
	2.1 Section 1	3
3	Chapter Title	4
	3.1 ffffh	4
4	Chapter Title	5
	4.1 abvvv	5
5	Chapter Title	6
	5.1 ghf	6

6	Chapter Title	7		
	6.1 vvvvv	7		
7	Conclusion	8		
	7.1 fff	8		
Aj	ppendices	9		
\mathbf{A}	Code (if required)	10		
	A.1 Kerberos Protocol	10		
	A.2 Kerberos Protocol with Freshness Concept	14		
В	Trace Files	19		
	B.1 Replay Attack	19		
	B.2 Replay Attack overcome using Freshness Concept	22		
Re	References			

List of Tables

List of Figures

1.1 Learning how to learn		4
---------------------------	--	---

ABBREVIATIONS

LDA : Latent Drichlet Allocation

API : Application Programming Interface

NOTATIONS

 $\alpha~:~$ Smoothing factor for words

 $\beta~:~$ Smoothing factor for topics

Chapter Title

1.1 Section 1

Electronic reference is given in [1]. Journal article is given in [2]. Article from conference is given in [3]. Material from book [4]. Manual detail is given in [5]. Detail of technical report is given in [6]. A master thesis [7] has been referred. A PhD thesis [8] has been referred. Last reference is taken from [9].

Definition 1 vvhffff

Definition 2 fffffff




Figure 1.1: Learning how to learn

Chapter Title

2.1 Section 1

Definition 3 vvvvv

Definition 4 ttttttt

Chapter Title

3.1 ffffh

Chapter Title

4.1 abvvv

Chapter Title

5.1 ghf

Chapter Title

6.1 vvvvv

Conclusion

7.1 fff

Appendices

Appendix A

Code (if required)

A.1 Kerberos Protocol

```
MODULE main
VAR
--Creating agents which are to type agtype
agA : agtype;
agB : agtype;
agS : agtype;
agI : agtype;
Iactive: boolean;
--Assigning initial to values to all variables
ASSIGN
init(agA.state):=wait;
init(agB.state):=wait;
init(agS.state):=wait;
init(agI.state):=wait;
init(agA.count):=0;
init(agB.count):=0;
init(agS.count):=0;
init(agI.count):=0;
init(agA.authenticated):=FALSE;
init(agB.authenticated):=FALSE;
init(agI.authenticated):=FALSE;
init(agS.authenticated):=TRUE;
```

```
--Transitions for the variable indicating presence or absence of intruder
next(Iactive):=
!Iactive:{0,1};
Iactive & agI.state=receive4beta:{0,1};
1: Iactive;
esac;
--Transitions for agent A's state
next(agA.state):=
case
agA.state=wait: send1;
agS.state=send2 & agA.state=send1: receive2;
agA.state=receive2: send3alpha;
\verb|agB.state=send4alpha| & \verb|agA.state=send3alpha|: receive4alpha|;
agA.state=receive4alpha: wait;
1:agA.state;
esac;
--Transitions for agent B's state
next(agB.state):=
case
agA.state=send3alpha & agB.state=wait: receive3alpha;
agI.state=send3beta & agB.state=wait & Iactive: receive3beta;
agI.state=send3beta & agB.state=send4alpha & Iactive: receive3beta;
agB.state=receive3alpha:send4alpha;
agB.state=receive3beta:send4beta;
agB.state=send4alpha:wait;
1:agB.state;
esac;
--Transitions for Server S's state
next(agS.state):=
case
agA.state=send1 & agS.state=wait: receive1;
agS.state=receive1:send2;
agS.state=send2:wait;
1:agS.state;
esac;
```

```
--Transitions for the Intruder's state
next(agI.state):=
agI.state=wait & agA.state=send3alpha & agB.state=wait & Iactive: receive3beta;
agI.state=receive3beta & Iactive: send3beta;
agI.state=send3beta & agB.state=send4beta & Iactive : receive4beta;
agI.state=receive4beta & Iactive: wait;
1:agI.state;
esac;
--Transitions for Agent A's counter
next(agA.count):=
case
agA.state=send1|agA.state=receive2: agA.count;
agA.state=send3alpha & agA.count<1:agA.count+1;</pre>
agA.count=1 & agA.state=receive2: 0;
1:agA.count;
esac;
--Transitions for Agent B's counter
next(agB.count):=
case
agB.state=receive3beta & agB.count<2|agB.state=receive3alpha & agB.count<2: agB.count+1;
agB.state=send4alpha |agB.state=send4beta:agB.count;
agB.count=1 & agA.state=receive4alpha & !Iactive:0;
agB.count=2 & agA.state=send3alpha|agB.count=1 & agA.state=send3alpha: 0;
1:agB.count;
esac;
--Transitions for Agent I's counter
next(agI.count):=
case
agI.state=receive3beta & agI.count<2 & Iactive:agI.count+1;</pre>
agI.state=send3beta & Iactive:agI.count;
agI.state=receive4beta & agI.count<2 & Iactive: agI.count+1;</pre>
agI.count=2: 0;
1:agI.count;
esac;
--Transitions for variable indicating agent A's authentication
```

```
next(agA.authenticated):=
case
agA.state=receive4alpha :TRUE;
1:agA.authenticated;
esac;
--Transitions for variable indicating agent B's authentication
next(agB.authenticated):=
case
agB.state=send4alpha |agB.state=send4beta :TRUE;
1:agB.authenticated;
esac:
--Transitions for variable indicating agent B's authentication which
--indicates that it has received the fourth message
next(agI.authenticated):=
agI.state=receive4beta :TRUE;
1:agI.authenticated;
esac;
--Agent S always is authenticated so transitions to the false state do not occur
next(agS.authenticated):=
case
1:agS.authenticated;
esac;
--Specifications which detect the presence of replay attack
--Agent B should not receive more messages than what agent A has sent it
--SPEC AG!(agA.count < agB.count);
--Agent I should never receive the fourth message
SPEC AG!(agI.state=receive4beta);
--Module for each agent's type which includes the agent's state variable,
--its counter and its authentication variable
MODULE agtype
```

```
VAR
state: {wait, send1, receive1, send2,receive2,
send3alpha, send3beta, receive3alpha, receive3beta,
send4alpha,send4beta, receive4alpha, receive4beta };
count:{0,1,2};
authenticated:boolean;
```

A.2 Kerberos Protocol with Freshness Concept

```
MODULE main
VAR
--Creating agents which are to type agtype
agA : agtype;
agB : agtype;
agS : agtype;
agI : agtype;
Iactive: boolean;
Fresh:0..20;
Time:0..20;
--Assigning initial to values to all variables
ASSIGN
init(agA.state):=wait;
init(agB.state):=wait;
init(agS.state):=wait;
init(agI.state):=wait;
init(agA.count):=0;
init(agB.count):=0;
init(agS.count):=0;
init(agI.count):=0;
init(agA.authenticated):=FALSE;
init(agB.authenticated):=FALSE;
init(agI.authenticated):=FALSE;
init(agS.authenticated):=TRUE;
init(Fresh):=0;
init(Time):=0;
```

```
--Transitions for the variable indicating presence or absence of intruder
next(Iactive):=
!Iactive:{0,1};
Iactive & agI.state=receive4beta:{0,1};
1: Iactive;
esac;
--Transitions for agent A's state
next(agA.state):=
case
agA.state=wait: send1;
agS.state=send2 & agA.state=send1: receive2;
agA.state=receive2: send3alpha;
\verb|agB.state=send4alpha| & \verb|agA.state=send3alpha|: receive4alpha|;
agA.state=receive4alpha: wait;
1:agA.state;
esac;
--Transitions for agent B's state
next(agB.state):=
case
agA.state=send3alpha & agB.state=wait & Fresh=0: receive3alpha;
agI.state=send3beta & agB.state=wait & Iactive & Fresh=0: receive3beta;
agI.state=send3beta & agB.state=send4alpha & Iactive & Fresh=0: receive3beta;
agB.state=receive3alpha:send4alpha;
agB.state=receive3beta:send4beta;
agB.state=send4alpha:wait;
1:agB.state;
esac;
--Transitions for Server S's state
next(agS.state):=
case
agA.state=send1 & agS.state=wait: receive1;
agS.state=receive1:send2;
agS.state=send2:wait;
1:agS.state;
esac;
```

```
--Transitions for the Intruder's state
next(agI.state):=
agI.state=wait & agA.state=send3alpha & agB.state=wait & Iactive: receive3beta;
agI.state=receive3beta & Iactive: send3beta;
agI.state=send3beta & agB.state=send4beta & Iactive : receive4beta;
agI.state=receive4beta & Iactive: wait;
agI.state=send3beta & Time>2: wait;
1:agI.state;
esac:
--Transitions for Agent A's counter
next(agA.count):=
case
agA.state=send1|agA.state=receive2: agA.count;
agA.state=send3alpha & agA.count<1:agA.count+1;</pre>
agA.count=1 & agA.state=receive2: 0;
1:agA.count;
esac;
--Transitions for Agent B's counter
next(agB.count):=
case
agB.state=receive3beta & agB.count<2|agB.state=receive3alpha & agB.count<2: agB.count+1;
agB.state=send4alpha|agB.state=send4beta:agB.count;
agB.count=1 & agA.state=receive4alpha & !Iactive:0;
\verb|agB.count=2 \& agA.state=send3alpha|agB.count=1 \& agA.state=send3alpha: 0;\\
1:agB.count;
esac;
--Transitions for Agent I's counter
next(agI.count):=
agI.state=receive3beta & agI.count<2 & Iactive:agI.count+1;</pre>
agI.state=send3beta & Iactive:agI.count;
agI.state=receive4beta & agI.count<2 & Iactive: agI.count+1;</pre>
agI.count=2: 0;
1:agI.count;
esac;
```

```
--Transitions for variable indicating agent A's authentication
next(agA.authenticated):=
agA.state=receive4alpha :TRUE;
1:agA.authenticated;
esac;
--Transitions for variable indicating agent B's authentication
next(agB.authenticated):=
case
agB.state=send4alpha|agB.state=send4beta :TRUE;
1:agB.authenticated;
esac;
--Transitions for variable indicating agent B's authentication which
--indicates that it has received the fourth message
next(agI.authenticated):=
case
agI.state=receive4beta :TRUE;
1:agI.authenticated;
esac;
--Agent S always is authenticated so transitions to the false state do not occur
next(agS.authenticated):=
case
1:agS.authenticated;
esac;
--Transitions for the freshness variable
next(Fresh):=
case
agA.state=send3alpha & agB.state=wait:0;
Fresh<20:Fresh+1;
1:0;
esac;
--Transitions for the Intruder's timer variable
next(Time):=
```

```
case
agI.state=receive3beta:0;
Time<20:Time+1;</pre>
1:0;
esac;
\operatorname{\mathtt{--Specifications}} which detect the presence of replay attack
--Agent B should not receive more messages than what agent A has sent it
SPEC AG!(agA.count < agB.count);</pre>
--Agent I should never receive the fourth message
SPEC AG!(agI.state=receive4beta);
--Module for each agent's type which includes the agent's state variable,
--its counter and its authentication variable
MODULE agtype
VAR
state:{wait, send1, receive1, send2,receive2,
send3alpha, send3beta, receive3alpha, receive3beta,
send4alpha, send4beta, receive4alpha, receive4beta};
count:{0,1,2};
authenticated:boolean;
```

Appendix B

Trace Files

B.1 Replay Attack

```
-- specification AG !(agA.count < agB.count) is false
-- as demonstrated by the following execution sequence
Trace Description: CTL Counterexample
Trace Type: Counterexample
-> State: 1.1 <-
  agA.state = wait
  agA.count = 0
  agA.authenticated = 0
 agB.state = wait
  agB.count = 0
  agB.authenticated = 0
  agS.state = wait
  agS.count = 0
  agS.authenticated = 1
  agI.state = wait
  agI.count = 0
  agI.authenticated = 0
  Iactive = 0
-> Input: 1.2 <-
-> State: 1.2 <-
  agA.state = send1
  agS.count = 2
-> Input: 1.3 <-
-> State: 1.3 <-
  agS.state = receive1
-> Input: 1.4 <-
-> State: 1.4 <-
```

```
agS.state = send2
-> Input: 1.5 <-
-> State: 1.5 <-
 agA.state = receive2
 agS.state = wait
-> Input: 1.6 <-
-> State: 1.6 <-
 agA.state = send3alpha
 Iactive = 1
-> Input: 1.7 <-
-> State: 1.7 <-
 agA.count = 1
 agB.state = receive3alpha
 agI.state = receive3beta
-> Input: 1.8 <-
-> State: 1.8 <-
 agB.state = send4alpha
 agB.count = 1
 agI.state = send3beta
 agI.count = 1
-> Input: 1.9 <-
-> State: 1.9 <-
 agA.state = receive4alpha
 agB.state = receive3beta
 agB.authenticated = 1
-> Input: 1.10 <-
-> State: 1.10 <-
 agA.state = wait
 agA.authenticated = 1
 agB.state = send4beta
 agB.count = 2
-- specification AG !(agI.state = receive4beta) is false
-- as demonstrated by the following execution sequence
Trace Description: CTL Counterexample
Trace Type: Counterexample
-> State: 2.1 <-
 agA.state = wait
 agA.count = 0
 agA.authenticated = 0
 agB.state = wait
 agB.count = 0
 agB.authenticated = 0
  agS.state = wait
 agS.count = 0
```

```
agS.authenticated = 1
 agI.state = wait
 agI.count = 0
 agI.authenticated = 0
 Iactive = 0
-> Input: 2.2 <-
-> State: 2.2 <-
 agA.state = send1
 agS.count = 2
-> Input: 2.3 <-
-> State: 2.3 <-
 agS.state = receive1
-> Input: 2.4 <-
-> State: 2.4 <-
 agS.state = send2
-> Input: 2.5 <-
-> State: 2.5 <-
 agA.state = receive2
 agS.state = wait
-> Input: 2.6 <-
-> State: 2.6 <-
 agA.state = send3alpha
 Iactive = 1
-> Input: 2.7 <-
-> State: 2.7 <-
 agA.count = 1
 agB.state = receive3alpha
 agI.state = receive3beta
-> Input: 2.8 <-
-> State: 2.8 <-
 agB.state = send4alpha
 agB.count = 1
 agI.state = send3beta
 agI.count = 1
-> Input: 2.9 <-
-> State: 2.9 <-
 agA.state = receive4alpha
 agB.state = receive3beta
 agB.authenticated = 1
-> Input: 2.10 <-
-> State: 2.10 <-
 agA.state = wait
 agA.authenticated = 1
```

agB.state = send4beta

```
agB.count = 2
-> Input: 2.11 <-
-> State: 2.11 <-
agA.state = send1
agI.state = receive4beta</pre>
```

B.2 Replay Attack overcome using Freshness Concept

```
-- specification AG !(agA.count < agB.count) is true
-- specification AG !(agI.state = receive4beta) is true
```

References

- [1] M. Shell. (2007) IEEEtran webpage on CTAN. [Online]. Available: http://www.ctan.org/tex-archive/macros/latex/contrib/IEEEtran/
- [2] Y. Okada, K. Dejima, and T. Ohishi, "Analysis and comparison of PM synchronous motor and induction motor type magnetic bearings," *IEEE Trans. on EE*, vol. 31, pp. 1047–1053, Sep./Oct. 1995.
- [3] R. K. Gupta and S. D. Senturia, "Pull-in time dynamics as a measure of absolute pressure," in Proc. IEEE International Workshop on Microelectromechanical Systems (MEMS'97), Nagoya, Japan, Jan. 1997, pp. 290– 294.
- [4] B. D. Cullity, Introduction to Magnetic Materials. Reading, MA: Addison-Wesley, 1972.
- [5] FLEXChip Signal Processor (MC68175/D), Motorola, 1996.
- [6] R. Jain, K. K. Ramakrishnan, and D. M. Chiu, "Congestion avoidance in computer networks with a connectionless network layer," Digital Equipment Corporation, MA, Tech. Rep. DEC-TR-506, Aug 1987.
- [7] A. Karnik, "Performance of TCP congestion control with rate feedback: TCP/ABR and rate adaptive TCP/IP," M. Eng. thesis, Indian Institute of Science, Bangalore, India, jan 1999.

- [8] Q. Li, "Delay characterization and performance control of wide-area networks," Ph.D. dissertation, Univ. of Delaware, Newark, May 2000. [Online]. Available: http://www.ece.udel.edu/~qli
- [9] L. Roberts, "Enhanced proportional rate control algorithm PRCA," ATM Forum Contribution 94-0735R1, Aug. 1994.