

**Lab 7****1. Write code for A\* algorithm**

```

from collections import deque
class Graph:
    # example of adjacency list (or rather map)
    # adjacency_list = {
    # 'A': [('B', 1), ('C', 3), ('D', 7)],
    # 'B': [('D', 5)],
    # 'C': [('D', 12)]
    # }

    def __init__(self, adjacency_list):
        self.adjacency_list = adjacency_list

    def get_neighbors(self, v):
        return self.adjacency_list[v]

    # heuristic function with equal values for all nodes
    def h(self, n):
        H = {
            'A': 1,
            'B': 1,
            'C': 1,
            'D': 1
        }
        return H[n]

    def a_star_algorithm(self, start_node, stop_node):
        # open_list is a list of nodes which have been visited, but who's neighbors
        # haven't all been inspected, starts off with the start node
        # closed_list is a list of nodes which have been visited
        # and who's neighbors have been inspected
        open_list = set([start_node])
        closed_list = set([])

        # g contains current distances from start_node to all other nodes
        # the default value (if it's not found in the map) is +infinity
        g = {}
        g[start_node] = 0

        # parents contains an adjacency map of all nodes
        parents = {}
        parents[start_node] = start_node
        while len(open_list) > 0:
            n = None

            # find a node with the lowest value of f() - evaluation function
            for v in open_list:
                if n == None or g[v] + self.h(v) < g[n] + self.h(n):
                    n = v;

            if n == None:
                print('Path does not exist!')
                return None

            # if the current node is the stop_node
            # then we begin reconstructin the path from it to the start_node
            if n == stop_node:
                reconst_path = []
                while parents[n] != n:
                    reconst_path.append(n)
                    n = parents[n]
                reconst_path.append(start_node)
                reconst_path.reverse()

```

```
print('Path found: {}'.format(reconst_path))
return reconst_path

# for all neighbors of the current node do
for (m, weight) in self.get_neighbors(n):
    # if the current node isn't in both open_list and closed_list
    # add it to open_list and note n as it's parent
    if m not in open_list and m not in closed_list:
        open_list.add(m)
        parents[m] = n
        g[m] = g[n] + weight

    # otherwise, check if it's quicker to first visit n, then m
    # and if it is, update parent data and g data
    # and if the node was in the closed_list, move it to open_list
    else:
        if g[m] > g[n] + weight:
            g[m] = g[n] + weight
            parents[m] = n
            if m in closed_list:
                closed_list.remove(m)
                open_list.add(m)

# remove n from the open_list, and add it to closed_list
# because all of his neighbors were inspected
open_list.remove(n)
closed_list.add(n)
print('Path does not exist!')
return None

adjacency_list = {
    'A': [('B', 1), ('C', 3), ('D', 7)],
    'B': [('D', 5)],
    'C': [('D', 12)]
}
graph1 = Graph(adjacency_list)
graph1.a_star_algorithm('A', 'D')
```

## **Lab 7 Task**

- 1. Write code for A\* Algorithm**